

PROJECT: HANSON CONCRETE RECYCLING FACILITY

PLANSET: CONCEPT DRAINAGE PLAN

CLIENT: HANSON CONSTRUCTION MATERIALS

DRAWING LIST		
DWG NO.	REV	DWG TITLE
GENERAL		
PS02-A000	C	COVER SHEET
CONSTRUCTION MANAGEMENT WORKS		
PS02-B300	B	SEDIMENT & EROSION CONTROL PLAN
PS02-B310	A	SEDIMENT & EROSION CONTROL DETAILS
DRAINAGE		
PS02-E100	C	DRAINAGE PLAN - SHEET 1
PS02-E101	A	DRAINAGE PLAN - SHEET 2
PS02-E200	B	DRAINAGE DETAILS
PS02-E300	B	DRAINAGE LONGITUDINAL SECTIONS (SHEET 1)
PS02-E301	B	DRAINAGE LONGITUDINAL SECTIONS (SHEET 2)
PS02-E302	A	DRAINAGE LONGITUDINAL SECTIONS (SHEET 3)
PS02-E700	D	WATER BALANCE CATCHMENT PLAN & MODEL



LOCALITY PLAN
NOT TO SCALE

LGA: BLACKTOWN CITY COUNCIL

HANSON PLACE, EASTERN CREEK

REV	DESCRIPTION	DATE	DRAWN	DESIGNED	CHECKED	APPRVD	SCALE
C	MINOR AMENDMENT	23/07/2021	LL/JS	EZ	SL	JF	
B	MINOR AMENDMENT	19/02/2021	LL	SS/LL	SL	JF	
A	INITIAL RELEASE	04/02/2021	LL	SS/LL	SL	JF	

DISCLAIMER & COPYRIGHT
This plan must not be used for construction unless signed as approved by
principal certifying authority.
All measurements in millimetres unless otherwise specified.
This drawing must not be reproduced in whole or part without prior written
consent of Martens & Associates Pty Ltd
(C) Copyright Martens & Associates Pty Ltd

PROJECT NAME/PLANSET TITLE
HANSON CONCRETE RECYCLING FACILITY
CONCEPT DRAINAGE PLAN
HANSON PLACE, EASTERN CREEK
(C) Copyright Martens & Associates Pty Ltd



Suite 201, 20 George St, Hornsby, NSW 2077 Australia Phone: (02) 9476 9999 Fax: (02) 9476 8767
Email: mail@martens.com.au Internet: www.martens.com.au

Consulting Engineers
Environment
Water
Geotechnical
Civil

PROJECT NO.	PLANSET NO.	RELEASE NO.	DRAWING NO.	REVISION
P1806739	PS02	R06	PS02-A000	C



PRINTED: ----- - USER: JSUAREZ

A1 / A3 LANDSCAPE (A1LC_v02.0)

PPRVD	SCALE											
JF	0	7.5	15.0	22.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	
JF	A1 (A3)	1:750 (1:1,500)				METRES						

DISCLAIMER & COPYRIGHT

This plan must not be used for construction unless signed as appropriate by the principal certifying authority.

All measurements in millimetres unless otherwise specified.

This drawing must not be reproduced in whole or part without prior consent of Martens & Associates Pty Ltd

(C) Copyright Martens & Associates Pty Ltd

© Copyright Martens & Associates Pty Ltd

AGER	CLIENT
	HANSON CONSTRUCTION MATERIALS
oved by	PROJECT NAME/PLANSET TITLE
r written	HANSON CONCRETE RECYCLING FACILITY CONCEPT DRAINAGE PLAN HANSON PLACE, EASTERN CREEK



Suite 201, 20 George St, Hornsby, NSW 2077 Australia Phone: (02) 9476 9999 Fax: (02) 9476 8767
Email: mail@martens.com.au Internet: www.martens.com.au

Consulting Engineers
Environment
Water
Geotechnical
Civil

DRAWING TITLE


SEDIMENT & EROSION CONTROL PLAN

PROJECT NO.	PLANSET NO.	RELEASE NO.	DRAWING NO.	REVISION
P1806739	PS02	R06	PS02-B300	B

RAWING ID: P1806739-PS02-R06-B300

STABILISED ACCESS POINT**TYPE II SAP**

THE TYPE II SAP DESIGN IS MORE DEFINED IN THAT IT REQUIRES AN AREA OF BALLAST WITHIN THE SITE COMBINED WITH A SHAKER PAD; ADJACENT THE SHAKER PAD AND IN THE PUBLIC WAY IS A TEMPORARY (CONCRETE) VEHICULAR CROSSING. (SEE DIAGRAM)

STABILISED ACCESS POINT - TYPE 2

IN BOTH TYPE I AND TYPE II SAP'S, THE TEMPORARY VEHICULAR CROSSING MUST:

- CONNECT TO AN EXISTING GUTTER LAYBACK (WHERE THE KERB AND GUTTER EXIST). IF A GUTTER LAYBACK DOES NOT EXIST THEN THE CONNECTION MUST BE MADE TO THE GUTTER BY REMOVING THE ADJACENT KERB SECTION ONLY.
- CONNECT TO A DISH CROSSING (WHERE KERB AND GUTTER DOES NOT EXIST). IF A DISH CROSSING DOES NOT EXIST, THEN IT MUST BE CONSTRUCTED IN ACCORDANCE WITH DETAILS CONTAINED IN COUNCIL'S ISSUED FOOTPATH CROSSING LEVELS.

IT SHOULD BE NOTED THAT THESE TYPES OF SAPS ARE CONSIDERED TO BE APPLICABLE FOR THE MAJORITY OF ACTIVITIES HOWEVER SOME SITES MAY REQUIRE SPECIAL CONSIDERATION.

SHAKER PAD (CATTLE GRID)



A CORRECTLY DESIGNED AND INSTALLED SHAKER PAD WILL ASSIST IN PREVENTING SEDIMENT TRANSFER FROM A SITE. ANY STABILISED ACCESS POINT (SAP) CAN BE DESIGNED WITH A SHAKER PAD (COMPULSORY IN TYPE II SAP'S)

SHAKER PADS CAN BE DESIGNED AND CONSTRUCTED TO ENABLE RE-USE ON FUTURE PROJECTS.


THE SHAKER PAD:

- MUST BE DESIGNED AND CERTIFIED BY A PRACTICING STRUCTURAL ENGINEER. THE CERTIFIED DESIGN SHOULD BE SUBMITTED WITH THE RELEVANT APPLICATION.
- CAN BE CONSTRUCTED FROM ANY SUITABLE MATERIAL.
- MUST BE LOCATED ON A SUITABLY PREPARED AND COMPACTED SUB-GRADE/BASE MATERIAL.
- MUST BE SITUATED SO THAT THE RUNGS OF THE SHAKER PAD ARE LEVEL WITH THE ADJOINING NATURAL SURFACE.
- MUST BE A MINIMUM OF 3.5m IN LENGTH.
- MUST BE A MINIMUM OF 3.5m IN WIDTH.
- MUST HAVE CLEAR SPACING BETWEEN RUNGS OF 200 - 250mm.
- RUNGS MUST HAVE A MAXIMUM WIDTH (BEARING AREA) OF 75mm.
- MUST HAVE A MINIMUM CLEAR DEPTH OF 300mm IE FROM THE TOP OF THE RUNG TO THE FINISHED SUB-GRADE/BASE LEVEL.


THE SHAKER PAD MUST BE PROVIDED WITH SUITABLE BARRIERS AT THE SIDES TO ENSURE THAT ALL TIRES OF VEHICLES LEAVING THE SITE TRAVERSE THE DEVICE.

**Construction Notes**


1. Construct at the gradient specified on the ESCP or SWMP, normally between 1 and 5 percent.
2. Avoid removing trees and shrubs if possible - work around them.
3. Ensure the structures are free of projections or other irregularities that could impede water flow.
4. Build the drains with circular, parabolic or trapezoidal cross sections, not V-shaped, at the dimensions shown on the SWMP.
5. Ensure the banks are properly compacted to prevent failure.
6. Complete permanent or temporary stabilisation within 10 days of construction following Table 5.2 in Landcom (2004).
7. Where discharging to erodible lands, ensure they outlet through a properly constructed level spreader.
8. Construct the level spreader at the gradient specified on the ESCP or SWMP, normally less than 1 percent or level.
9. Where possible, ensure they discharge waters onto either stabilised or undisturbed disposal sites within the same subcatchment area from which the water originated. Approval might be required to discharge into other subcatchments.

EARTH BANK (HIGH FLOWS) SD 5-6**Construction Notes**


1. Construct sediment fences as close as possible to being parallel to the contours of the site, but with small returns as shown in the drawing to limit the catchment area of any one section. The catchment area should be small enough to limit water flow if concentrated at one point to 50 litres per second in the design storm event, usually the 10-year event.
2. Cut a 150-mm deep trench along the upslope line of the fence for the bottom of the fabric to be entrenched.
3. Drive 1.5 metre long star pickets into ground at 2.5 metre intervals (max) at the downslope edge of the trench. Ensure any star pickets are fitted with safety caps.
4. Fix self-supporting geotextile to the upslope side of the posts ensuring it goes to the base of the trench. Fix the geotextile with wire ties or as recommended by the manufacturer. Only use geotextile specifically produced for sediment fencing. The use of shade cloth for this purpose is not satisfactory.
5. Join sections of fabric at a support post with a 150-mm overlap.
6. Backfill the trench over the base of the fabric and compact it thoroughly over the geotextile.

SEDIMENT FENCE SD 6-8**Construction Notes**

1. Fabricate a sediment barrier made from geotextile or straw bales.
2. Follow Standard Drawing 6-7 and Standard Drawing 6-8 for installation procedures for the straw bales or geofabric. Reduce the picket spacing to 1 metre centres.
3. In waterways, artificial sag points can be created with sandbags or earth banks as shown in the drawing.
4. Do not cover the inlet with geotextile unless the design is adequate to allow for all waters to bypass it.

GEOTEXTILE INLET FILTER SD 6-12**Construction Notes**

1. Build with gradients between 1 percent and 5 percent.
2. Avoid removing trees and shrubs if possible - work around them.
3. Ensure the structures are free of projections or other irregularities that could impede water flow.
4. Build the drains with circular, parabolic or trapezoidal cross sections, not V shaped.
5. Ensure the banks are properly compacted to prevent failure.
6. Complete permanent or temporary stabilisation within 10 days of construction.

EARTH BANK (LOW FLOW) SD 5-5**Construction Notes**

1. Place stockpiles more than 2 (preferably 5) metres from existing vegetation, concentrated water flow, roads and hazard areas.
2. Construct on the contour as low, flat, elongated mounds.
3. Where there is sufficient area, topsoil stockpiles shall be less than 2 metres in height.
4. Where they are to be in place for more than 10 days, stabilise following the approved ESCP or SWMP to reduce the C-factor to less than 0.10.
5. Construct earth banks (Standard Drawing 5-5) on the upslope side to divert water around stockpiles and sediment fences (Standard Drawing 6-8) 1 to 2 metres downslope.

STOCKPILES SD 4-1

REV	DESCRIPTION	DATE	DRAWN	DESIGNED	CHECKED	APPRVD	SCALE
A	INITIAL RELEASE	04/02/2021	LL	SS/LL	SL	JF	


GRID	DATUM	PROJECT MANAGER	CLIENT	
---	---	JF	HANSON CONSTRUCTION MATERIALS	
DISCLAIMER & COPYRIGHT				
This plan must not be used for construction unless signed as approved by principal certifying authority.				
All measurements in millimetres unless otherwise specified.				
This drawing must not be reproduced in whole or part without prior written consent of Martens & Associates Pty Ltd.				
(C) Copyright Martens & Associates Pty Ltd				

HANSON CONCRETE RECYCLING FACILITY
CONCEPT DRAINAGE PLAN
HANSON PLACE, EASTERN CREEK


martens
& Associates Pty Ltd
Suite 201, 20 George St, Hornsby, NSW 2077 Australia Phone: (02) 9476 9999 Fax: (02) 9476 8767
Email: mail@martens.com.au Internet: www.martens.com.au

Consulting Engineers
Environment
Water
Geotechnical
Civil

DRAWING TITLE
SEDIMENT & EROSION CONTROL DETAILS
PROJECT NO. P1806739 PLANSET NO. PS02 RELEASE NO. R06 DRAWING NO. PS02-B310 REVISION A



REV	DESCRIPTION	DATE	DRAWN	DESIGNED	CHECKED	APPRVD	SCALE
C	MINOR AMENDMENT	23/07/2021	LL/JS	EZ	SL	JF	0 5 10 15 20 25 30 35 40 45 50 METRES
B	MINOR AMENDMENT	19/02/2021	LL	SS/LL	SL	JF	A1 (A3) 1:500 (1:1,000)
A	INITIAL RELEASE	04/02/2021	LL	SS/LL	SL	JF	



NOTE:

1. ALL PIT AND PIPE LOCATIONS & SIZES ARE PRELIMINARY ONLY AND ARE SUBJECTED TO CHANGE AT CC STAGE.
2. PIT SURFACE LEVELS ARE TO BE CONFIRMED AT CC STAGE.
3. EXISTING STORM WATER SYSTEM ON HANSON PLACE ARE BASED ON WAE PLAN (C431 TO C434) PROVIDED BY HANSON.
4. EXISTING CONTOURS & SURVEY HEIGHTS ARE BASED ON CIVIL PACKAGE PLAN (C010726.13) PROVIDED BY HANSON.
5. ROOF DRAINAGE AND INTERNAL DRAINAGE OF PROPOSED BUILDING ON LOT 5 TO BE PROVIDED BY OTHERS AT CC STAGE.

<p>DISCLAIMER & COPYRIGHT</p> <p>This plan must not be used for construction unless signed as approved by principal certifying authority.</p> <p>All measurements in millimetres unless otherwise specified.</p> <p>This drawing must not be reproduced in whole or part without prior written consent of Martens & Associates Pty Ltd.</p> <p>(C) Copyright Martens & Associates Pty Ltd</p>


PROJECT NAME/PLANSET TITLE
HANSON CONCRETE RECYCLING FACILITY
CONCEPT DRAINAGE PLAN
HANSON PLACE, EASTERN CREEK

The logo for Martens & Associates Pty Ltd. It features a stylized orange swoosh graphic above the company name. The name 'martens' is written in a bold, lowercase, sans-serif font, with the 'm' partially overlapping the swoosh. Below it, '& Associates Pty Ltd' is written in a smaller, bold, black, sans-serif font.

Consulting Engineers
Environment
Water
Geotechnical
Civil
ne: (02) 9476 9999 Fax: (02) 9476
www.martens.com.au


DRAINAGE PLAN SHEET 2

NO.	PLANSET NO.	RELEASE NO.	DRAWING NO.	REVISION
39	PS02	R06	PS02-E101	A




INSET A - PROPOSED INTERCONNECTED ABOVE GROUND RAINWATER TANK LAYOUT

SCALE - N.T.S.



SPLITTER PIT DETAILS

SCALE 1:25




PROPOSED UNDERGROUND STORMWATER TANK LAYOUT

SCALE - NTS

SWALE TYPE	H (m)	W (m)
1	0.17	1.00
2	0.25	1.50
3	0.50	3.00


TYPICAL SWALE SECTION

SCALE - M



ABOVE GROUND RAINWATER TANK SECTION (SHCEMATIC ONLY)

SCALE - N.T.



UNDERGROUND STORMWATER TANK DETAILS

NOT TO SCALE


A1 / A3 LANDSCAPE (A1LC_v02.0.01)

GRID MGA	DATUM mAHD	PROJECT MANAGER JF	CLIENT HANSON CONSTRUCTION MATERIALS
DISCLAIMER & COPYRIGHT This plan must not be used for construction unless signed as approved by principal certifying authority. All measurements in millimetres unless otherwise specified. This drawing must not be reproduced in whole or part without prior written consent of Martens & Associates Pty Ltd. (C) Copyright Martens & Associates Pty Ltd		PROJECT NAME/PLANSET TITLE HANSON CONCRETE RECYCLING FACILITY CONCEPT DRAINAGE PLAN HANSON PLACE, EASTERN CREEK	

martens
& Associates Pty Ltd

Suite 201, 20 George St, Hornsby, NSW 2077 Australia Phone: (02) 9476 9999 Fax: (02) 9476 8767
Email: mail@martens.com.au Internet: www.martens.com.au

DRAWING TITLE				
DRAINAGE DETAILS				
PROJECT NO.	PLANSET NO.	RELEASE NO.	DRAWING NO.	REVISION
1806739	PS02	R06	PS02-E200	B
ING ID: P1806739-PS02-R06-E200				



LINE 1A601

NOTE:
- ALL PIPE LEVELS AND CLASSES TO BE CONFIRMED AT DETAILED DESIGN STAGE.

LINE 1A602

RID GA	DATUM mAHD	PROJECT MANAGER JF	CLIENT HANSON CONSTRUCTION MATERIALS
DISCLAIMER & COPYRIGHT This plan must not be used for construction unless signed as approved by principal certifying authority. Measurements in millimetres unless otherwise specified. This drawing must not be reproduced in whole or part without prior written consent of Martens & Associates Pty Ltd. Copyright Martens & Associates Pty Ltd		PROJECT NAME/PLANSET TITLE HANSON CONCRETE RECYCLING FACILITY CONCEPT DRAINAGE PLAN HANSON PLACE, EASTERN CREEK	

LINE 1A603

LS
ILITY


 **martens**
& Associates Pty Ltd

Consulting Engineers

Environment
Water
Geotechnical
Civil

SEWER LONGITUDINAL SECTIONS
(SHEET 1)

SSDA



LINE 1A603

NOTE:
- ALL PIPE LEVELS AND CLASSES TO BE CONFIRMED AT DETAILED DESIGN STAGE.

LINE 1A604

D	SCALE	GRID MGA	DATUM mAHD	PROJECT MANAGER JF
DISCLAIMER & COPYRIGHT				


LINE 1A605

NT
HANSON CONSTRUCTION MATERIALS
JECT NAME/PLANSET TITLE
HANSON CONCRETE RECYCLING FACIL
CONCEPT DRAINAGE PLAN
HANSON PLACE, EASTERN CREEK



Suite 201, 20 George St, Hornsby, NSW 2077 Australia Phone: (02) 9476 9999 Fax: (02) 9476 8767
Email: mail@martens.com.au Internet: www.martens.com.au

N625/580.281
-04



SSDA


A

3

-

0

SSDA



LINE 1A606

NOTE:
- ALL PIPE LEVELS AND CLASSES TO BE CONFIRMED AT DETAILED DESIGN STAGE.

A1 / A3 LANDSCAPE (A1LC_v02.0)

LINE 1A607

	GRID MGA	DATUM mAHD	PROJECT MANAGER JF	CLIENT HAN
	<p>DISCLAIMER & COPYRIGHT</p> <p>This plan must not be used for construction unless signed as approved by principal certifying authority.</p> <p>All measurements in millimetres unless otherwise specified.</p> <p>This drawing must not be reproduced in whole or part without prior written consent of Martens & Associates Pty Ltd.</p> <p>(C) Copyright Martens & Associates Pty Ltd</p>			

NT

HANSON CONSTRUCTION MATERIALS

JECT NAME/PLANSET TITLE

HANSON CONCRETE RECYCLING FACILITY

CONCEPT DRAINAGE PLAN


HANSON PLACE, EASTERN CREEK

The logo for Martens & Associates Pty Ltd. It features a stylized orange swoosh that forms the top arc of the letter 'm'. Below this, the word 'martens' is written in a bold, blue, sans-serif font. Underneath 'martens', the words '& Associates Pty Ltd' are written in a smaller, blue, sans-serif font.


Consulting Engineers
Environment
Water
Geotechnical
Civil

DRAINAGE LONGITUDINAL SECTIONS (SHEET 3)

PLANSET NO.	RELEASE NO.	DRAWING NO.	REVISION
PS02	R06	PS02-E302	A




MUSIC MODELLING LAYOUT (P1806739MUS04V01)



MUSIC MODELLING CATCHMENTS FOR THE SITE

MUSIC CATCHMENTS (P1806739MUS04V01)					
THE SITE (LOT 3, 4 & 5)					
KEY	DESCRIPTION	MUSIC NODE TYPE	AREA (ha)	IMPERVIOUS %	MUSIC NODE REFERENCE
LOT 4&5 - INDUSTRIAL	REVEGETATED LAND	1.841	0%		BLACKTOWN CITY COUNCIL WSUD
LOT 4&5 - INTERNAL ROAD	SEALED ROAD	0.340	100%		BLACKTOWN CITY COUNCIL WSUD
LOT 4&5 - ROOF TO RWT	ROOF	0.949	100%		BLACKTOWN CITY COUNCIL WSUD
LOT 4&5 - LANDSCAPE	REVEGETATED LAND	0.655	0%		BLACKTOWN CITY COUNCIL WSUD
LOT 3 - INDUSTRIAL	REVEGETATED LAND	0.738	0%		BLACKTOWN CITY COUNCIL WSUD
LOT 3- INTERNAL ROAD	SEALED ROAD	0.264	100%		BLACKTOWN CITY COUNCIL WSUD
LOT 3- CAR PARK AREA	UNSEALED ROAD	0.189	100%		BLACKTOWN CITY COUNCIL WSUD
LOT 3 - ROOF	ROOF	0.025	100%		BLACKTOWN CITY COUNCIL WSUD
TOTAL AREA		5.00	= 100% OF TOTAL AREA		
TOTAL IMPERVIOUS AREA		1.77	= %35 OF TOTAL AREA		
TOTAL PERVERSUS AREA		3.23	= %65 OF TOTAL AREA		

REST OF THE ESTATE (P1806739MUS04V01)					
KEY	DESCRIPTION	MUSIC NODE TYPE	AREA (ha)	IMPERVIOUS %	MUSIC NODE REFERENCE
	INDUSTRIAL	UNSEALED ROAD	20.24	90%	BLACKTOWN CITY COUNCIL WSUD
TOTAL AREA			20.24	= 100% OF TOTAL AREA	
TOTAL IMPERVIOUS AREA			18.22	= %90 OF TOTAL AREA	
TOTAL PERVERSUS AREA			2.02	= %10 OF TOTAL AREA	



NOTE:

- MUSIC MODEL IS USED FOR WATER BALANCE ASSESSMENT ONLY. THE EXISTING ESTATE STORMWATER QUALITY TREATMENT SYSTEM (REGIONAL FACILITY) THAT SERVES THE SITE WHICH MEETS THE GROWTH CENTRES POLLUTANT REDUCTION TARGETS OF TSS, TP AND TN. NO FURTHER STORMWATER QUALITY MODELLING IS REQUIRED FOR TSS, TP AND TN. REFER TO MA REPORT P1806739JR03 FOR MORE DETAILS.

- ACCORDING TO AUSTRALIAN GUIDELINE FOR WATER RECYCLING- STORMWATER HARVESTING AND REUSE (2009), THE WATER QUALITY OBJECTIVES FOR REUSE OF STORMWATER FOR DUST SUPPRESSION INCLUDE:

- TURBIDITY: <25 NTU (EQUIVALENT TO 8.33 mg/L) (MEDIAN)

< 100 NTU (EQUIVALENT TO 33.33 mg/L) (95th PERCENTILE)

- E. COLI: <100 NTU

AS SHOWN IN FIGURE ABOVE, THE WATER QUALITY OBJECTIVES FOR TURBIDITY IS ACHIEVED.

- TURBIDITY: 0 - 8.33 mg/L (MEDIAN)

< 33.33 mg/L (95th PERCENTILE)

AS THE WASTEWATER RECYCLING IS NOT PROPOSED FOR THE SITE, THE OBJECTIVE FOR E.COLI IS CONSIDERED ACHIEVED. THEREFORE, THE STORMWATER COLLECTED IN STORMWATER RETENTION TANK IS FIT FOR REUSE FOR DUST SUPPRESSION.

REV	DESCRIPTION	DATE	DRAWN	DESIGNED	CHECKED	APPRVD	SCALE	GRID	DATUM	PROJECT MANAGER	CLIENT	
D	MINOR AMENDMENT	23/07/2021	LL/JS	EZ	SL	JF	0-15 15-30 30-45 45-60 60-75 75-90 90-105 105-120 120-135 135-150 METRES	A1 (A3) 1:1,500 (1:3,000)	mAHD	JF	HANSON CONSTRUCTION MATERIALS	
C	MINOR AMENDMENT	04/02/2021	LL	SS	SL	JF						
B	MINOR AMENDMENT	20/11/2020	JS	SS	SL	JF						
A	INITIAL RELEASE	03/09/2020	RK	SS	SL	JF						

PRINTED ---- - USER JSURE2

A1 / A3 LANDSCAPE (A1LC_v02.00)

DISCLAIMER & COPYRIGHT
This plan must not be used for construction unless signed as approved by principal certifying authority.
All measurements in millimetres unless otherwise specified.
This drawing must not be reproduced in whole or part without prior written consent of Martens & Associates Pty Ltd
(C) Copyright Martens & Associates Pty Ltd

HANSON CONCRETE RECYCLING FACILITY
CONCEPT DRAINAGE PLAN

HANSON PLACE, EASTERN CREEK


Consulting Engineers
Environment
Water
Geotechnical
Civil
Suite 201, 20 George St, Hornsby, NSW 2077 Australia Phone: (02) 9476 9999 Fax: (02) 9476 8767
Email: mail@martens.com.au Internet: www.martens.com.au

DRAWING TITLE
WATER BALANCE CATCHMENT PLAN & MODEL
PROJECT NO. P1806739
PLANSET NO. PS02
RELEASE NO. R06
DRAWING NO. PS02-E700
REVISION D

DRAWING ID: P1806739-PS02-R06-E700