

Parramatta Eels

JULY 2022

Kellyville Park PNRL Eels - Centre of Excellence and Community Sports Centre

Integrated Water Management Plan



Question today *Imagine tomorrow* Create for the future

Kellyville Park PNRL Eels - Centre of Excellence and Community Sports Centre Integrated Water Management Plan

Parramatta Eels

WSP




Level 15, 28 Freshwater Place
Southbank VIC 3006

Tel: +61 3 9861 1111

Fax: +61 3 9861 1144

wsp.com

REV	DATE	DETAILS
A	25/10/2021	Draft SSDA Issue
B	01/02/2022	Draft SSDA Issue
C	28/02/2022	Final Issue for SSDA Approval
D	23/03/2022	Final Issue for SSDA Approval
E	28/07/2022	Final Issue

	NAME	DATE	SIGNATURE
Prepared by:	Alex Khoshaba	28/07/2022	
Reviewed by:	Tyran Bell	28/07/2022	
Approved by:	Robert Day	28/07/2022	

This document may contain confidential and legally privileged information, neither of which are intended to be waived, and must be used only for its intended purpose. Any unauthorised copying, dissemination or use in any form or by any means other than by the addressee, is strictly prohibited. If you have received this document in error or by any means other than as authorised addressee, please notify us immediately and we will arrange for its return to us.

WSP acknowledges that every project we work on takes place on First Peoples lands.
We recognise Aboriginal and Torres Strait Islander Peoples as the first scientists and engineers and pay our respects to Elders past and present.



Table of contents

Glossary	i
Executive Summary	iii
1 Introduction	1
1.1 Design Response to SEARs	1
1.1.1 Design Response to External Referral Authorities	2
2 The Site	4
2.1 Existing Conditions	5
2.1.1 Existing Topography and Overland Flow Paths	5
2.1.2 Existing Stormwater Infrastructure	6
3 Proposed Development	8
4 Proposed Stormwater Strategy	10
4.1 Design Guidelines	10
4.2 Design Criteria	10
4.3 Stormwater Quantity Management	11
4.3.1 Hydrological Model	11
4.3.2 Points of Stormwater Discharge	11
4.3.3 Catchment Analysis	12
4.3.4 Onsite Stormwater Detention (OSD)	12
4.3.5 Overland Flow	13
4.4 Stormwater Quality Management	13
4.4.1 Rainwater Harvesting	13
5 Conclusion	14
6 Limitations	15
6.1 Permitted Purpose	15
6.2 Qualifications and Assumptions	15
6.3 Use and Reliance	15
6.4 Disclaimer	16

List of Tables

Table 1.1: Design Response to SEARs	1
Table 1.2: Design Response to Sydney Water Requirements	2
Table 4.1: Intensity-Frequency-Duration (IFD) Rainfall for the Hawkesbury Catchment	11
Table 4.2: Catchment Area Breakdowns	12
Table 4.3: Catchment Runoff Coefficients	12
Table 4.4: Catchment Peak Discharge Rate	12
Table 4.5: Rainwater Harvesting Strategy	13

List of Figures

Figure 2.1: Locality and Extent of Works Plan	4
Figure 2.2: New Site Works Plan	5
Figure 2.3: Topography Map	6
Figure 2.4: Existing Stormwater Infrastructure	7

List of Appendices

Appendix A Civil Drawings

Appendix B Civil Works Plans for Residential Subdivision

Appendix C Civil Works Plans for Kellyville Park Field Extension

Appendix D Council Correspondence

Appendix E Rainwater Harvesting Tank Calculations

Glossary

Annual Exceedance Probability (AEP)	<i>Refers to the probability or risk of a flood of a given size occurring or being exceeded in a given year.</i>
Australian Height Datum (AHD)	<i>A common national surface level datum approximately corresponding to mean sea level.</i>
Average Recurrence Interval (ARI)	<i>The average or expected value of the period between exceedances of a given rainfall total accumulated over a given duration e.g. 100-year ARI flood is expected to be exceeded once every 100 years on average (taken to be equivalent to 1% AEP). It is implicit in this definition that the periods between exceedances are generally random.</i>
Catchment	<i>Area draining to a site. It always relates to a particular location and may include the catchment tributaries as well as mainstream.</i>
Council	<i>The Hills Shire Council (THSC).</i>
Development Control Plan (DCP)	<i>Council document that sets out the criteria that all developments must adhere to.</i>
Design Storm	<i>Is the probabilistic or statistical estimate, being generally based on some form of probability analysis of flood or rainfall data.</i>
Discharge	<i>The rate of flow of water measured in terms of volume over time.</i>
Flood	<i>A relatively high stream flow which overtops the natural or constructed watercourse or drainage system such as a stream, river, estuary, lake, canal or pipe drainage network.</i>
Fraction Impervious	<i>Ratio of impervious to total site area.</i>
Hydrograph	<i>A graph that shows the discharge to time relationship of a hydraulic flow at a particular location.</i>
Hydrology	<i>The term given to the study of the rainfall and runoff process as it relates to the derivation of hydrographs for given floods.</i>
Intensity Frequency Duration (IFD) Table	<i>A table which outlines the rainfall intensities for a given storm event over various storm durations.</i>
Major Storm Event	<i>The design storm event conveyed at surface level via the designated overland flow path.</i>
Minor Storm Event	<i>The design storm event conveyed underground via the proposed stormwater pit and pipe network.</i>
Onsite Stormwater Detention (OSD)	<i>The practice of temporarily storing stormwater on site during a storm and releasing it slowly to reduce flow.</i>

Overland Flow Path	<i>The route taken by stormwater flowing over the ground surface.</i>
Peak Flow	<i>The maximum discharge during a flood event.</i>
Point of Stormwater Discharge	<i>The point at which the proposed stormwater network connects into the existing stormwater system.</i>
Rational Method	<i>Hydrological method used to assess the design peak flow rate (peak discharge) of stormwater generated onsite.</i>
Coefficient of Runoff	<i>The coefficient used in the Rational Method. Is the ratio of the peak rate of run-off to the average rainfall intensity during the critical rainfall period for the catchment area under consideration.</i>
Stormwater Harvesting	<i>The practice of capturing and storing stormwater runoff generated and reusing it on site.</i>
Time of Concentration	<i>The time required for the stormwater runoff to flow from the furthest part (relative to time) of the catchment to its outlet.</i>
Water Sensitive Urban Design (WSUD)	<i>The practice of treating and reusing stormwater runoff generated on site to improve the quality of stormwater discharge and reduce the impact on downstream waterways caused by urban developments.</i>

Executive Summary

This report constitutes the Integrated Water Management Plan for the ‘Eels Centre of Excellence and Community Sports Hub, Kellyville’ under SEARs application number SSD-24452965. The key issues in relation to stormwater drainage and water quality as outlined within the SEARs have been addressed and concurrently demonstrate compliance with all the relevant stormwater related requirements of The Hills Shire Council.

The stormwater strategy as currently proposed achieves a high standard in:

- Managing the stormwater runoff generated by the proposed development.
- Minimising the impact of the proposed development on the existing site stormwater infrastructure and downstream environments.
- Ensuring the safety of all development users.
- Protecting the new buildings from stormwater inundation.

The key items considered within the proposed stormwater strategy and how they have been addressed can be summarised as follows:

- Capturing of surface runoff – a combination of grated pits, kerbs, trench grates and swales are implemented to capture/convey surface runoff.
- Conveyance of flows from the design minor storm event – stormwater pipes have been designed to convey flows from the 10 year ARI event in the underground network.
- Conveyance of flows from the design major storm event – grading of the new carpark, footpath and landscaping has been completed to ensure adequate overland flow paths are available to convey flows at surface level safely away from the buildings. Where no adequate flow paths are available, the underground pipe network has been designed to cater for the 100 year ARI event.
- Points of stormwater discharge – two points of stormwater discharge have been nominated:
 - To the drainage being constructed as part of the field extension works project (by others).
 - To the existing 600 dia. Council drain running east to west through the site.

The two points of stormwater discharge effectively split the flows generated by the development evenly, reducing the reliance on any single section of drainage infrastructure.

- Stormwater Quantity Management – in accordance with Council advice, onsite stormwater detention is deemed not to be required as part of this development given there is an existing online basin along Strangers Creek, immediately downstream of the site. The drainage infrastructure at the nominated points of stormwater discharge have been proven to have adequate capacity to cater for the peak flows generated by the proposed development.
- Stormwater Quality Management – in accordance with Council advice, treatment of the stormwater runoff generated on site is not required to be provided as part of this development due to the planned water quality treatment works within the existing online basin along Strangers Creek, immediately downstream of the site.
- Stormwater Harvesting – 2x25 kL above ground tanks and 2x10 kL below ground tanks are to be provided to collect and store runoff from the entire roof areas of the new buildings. Captured runoff is to be reused onsite for toilet flushing and landscape irrigation with the tanks supplying a minimum of 50% of the anticipated demand.

1 Introduction

This Integrated Water Management Plan is intended to be submitted as part of the overall State Significant Development Application (SSDA) for the proposed development at Kellyville Memorial Park in Kellyville NSW. It has been specifically prepared in response to item 15 of the developments associated Secretary's Environmental Assessment Requirements (SEARs).

While addressing this SEARs item, the report provides commentary on existing site conditions including stormwater infrastructure, topography and overland flow paths. It will then outline the stormwater management strategy for the proposed development including the proposed points of stormwater discharge as well as commentary surrounding stormwater quantity and quality requirements that are applicable to this development as advised by Council.

1.1 Design Response to SEARs

The following design responses are provided to the key issues required to be addressed in relation to stormwater drainage and water quality (item 15) as outlined within the SEARs:

Table 1.1: Design Response to SEARs

(Source: SEARs Application No. SSD-24452965, dated 15/08/21)

15. STORMWATER DRAINAGE AND WATER QUALITY	
Key Issues to be Addressed	Design Response
The EIS must include an Integrated Water Management Plan that:	
Is prepared in consultation with Council and any relevant drainage authority.	This report constitutes the Integrated Water Management Plan and has been prepared in accordance with Council's requirements.
Details the proposed drainage design for the site including on-site detention facilities, water quality measures and the nominated discharge point(s).	Section 4 of this report discusses the proposed stormwater strategy for this development including points of discharge, stormwater quality and quantity. Detailed Civil drawings are also included in Appendix A.
Demonstrates compliance with relevant provisions of the Sydney Drinking Water Catchment SEPP with Council or other drainage authority requirements and avoids adverse impacts on any downstream properties.	The development is not located within the Sydney Drinking Water Catchment SEPP. The stormwater drainage strategy has been developed as per the requirements within The Hills Shire Council DCP and/or advice provided by Council officers.
Where drainage infrastructure works are required to be handed over to Council, provide full hydraulic details and detailed plans and specifications of proposed works that have been prepared in consultation with Council and comply with Council's relevant standards.	No new stormwater drains are required to be handed over to Council as part of this development. A new stormwater junction pit may be installed on the existing Council 600 dia. Council drain to provide a connection point for the harvesting tank overflow. This proposed new pit is shown on the Civil Works Plans included with the Civil drawings in Appendix A and noted to be constructed in accordance with the relevant Council standard drawing.

1.1.1 Design Response to External Referral Authorities

Sydney Water provided additional input on the SEARs in a letter dated 28th of July 2021. The following design responses are provided to the Civil/stormwater drainage related requirements as outlined by Sydney Water:

Table 1.2: Design Response to Sydney Water Requirements

(Source: Sydney Water Letter, dated 28/07/2021)

Key Issues to be Addressed	Design Response
The proponent of the development should determine service demands following servicing investigations and demonstrate that satisfactory arrangements for drinking water, wastewater, and recycled water (if required) services have been made.	Rainwater harvesting requirements for the development have been provided by The Hills Shire Council and have been incorporated within the overall design. Refer Section 4.4.1.
The proponent must obtain endorsement and/or approval from Sydney Water to ensure that the proposed development does not adversely impact on any existing water, wastewater or stormwater main, or other Sydney Water asset, including any easement or property. When determining landscaping options, the proponent should take into account that certain tree species can cause cracking or blockage of Sydney Water pipes and therefore should be avoided.	The development will not have an adverse impact on any Sydney Water stormwater assets as there are none located in close proximity to the proposed works.
Strict requirements for Sydney Water's stormwater assets (for certain types of development) may apply to this site. The proponent should ensure that satisfactory steps/measures been taken to protect existing stormwater assets, such as avoiding building over and/or adjacent to stormwater assets and building bridges over stormwater assets. The proponent should consider taking measures to minimise or eliminate potential flooding, degradation of water quality, and avoid adverse impacts on any heritage items, and create pipeline easements where required.	No works are proposed in close proximity to any Sydney Water stormwater asset. Stormwater generated by the proposed development shall discharge to existing stormwater pipes running through the site which are owned and maintained by The Hills Shire Council. Stormwater quality and quantity requirements have been provided by The Hills Shire Council and incorporated within the overall design. Refer Section 4.
The proponent should outline any sustainability initiatives that will minimise/reduce the demand for drinking water, including any alternative water supply and end uses of drinking and non-drinking water that may be proposed, and demonstrate water sensitive urban design (principles are used), and any water conservation measures that are likely to be proposed. This will allow Sydney Water to determine the impact of the proposed development on our existing services and required system capacity to service the development.	Water Sensitive Urban Design (WSUD) requirements for the development have been provided by The Hills Shire Council and have been incorporated within the overall design. Refer Section 4.4.
Proposed development has the common boundary with Sydney Water's Basin 35 on the western side. This common boundary has the dam wall which is part of the Basin 35. The proposal must ensure any earth work or building work, including piling work, excavation etc. should not cause any adverse impact on structural stability of the dam wall. It is recommended that the proponent provides details of their building works, earth works and construction methodology with the Specialised Engineering Report to ascertain that the proposed development work has no impact on dam wall of Basin 35.	No works are proposed in close proximity to Sydney Water's Strangers Creek Reserve or Basin 35 and therefore the development will not have an adverse impact on the existing dam wall of Basin 35. Refer to Figure 2.1 and Figure 2.2 showing the significant distance between the proposed development and Sydney Water's Reserve (approx 165m). Notes will be incorporated onto Construction Drawings communicating this condition to the Contractor.
If the development requires direct stormwater discharge into Sydney Water's Stranger Creek, it is recommended that the proponent liaises with Sydney Water as soon as possible to determine the suitable location of the point of	No direct stormwater connection is proposed to Sydney Water drainage assets. Runoff from the new development will discharge into existing stormwater

discharge in line with the meeting outcomes held between The Hills Council and Sydney Water on 26 March 2021 at the site.	pipes owned and maintained by The Hills Shire Council.
---	--

2 The Site

Kellyville Park is situated at 8 Memorial Avenue in Kellyville within The Hills Shire Council Local Government Area. The site borders Memorial Avenue to the north, Stone Mason Drive to the east, residential developments to the South and Strangers Creek to the West. Access to the site is via Memorial Avenue and Stone Mason Drive.

The current developed state of this site mostly consists of various sporting fields (some currently in construction) with surrounding access roads and carparks. A temporary construction compound currently occupies the north-eastern corner of the site.

The works to be completed as part of this proposed development are consigned to the north-eastern section of the site.



Figure 2.1: Locality and Extent of Works Plan

(Source: Nearmap, 06/10/2021)




Figure 2.2: New Site Works Plan

2.1 Existing Conditions

2.1.1 Existing Topography and Overland Flow Paths

The site generally falls in an east to westerly direction. The existing contours through the subject site fall from a high point of approximately RL70.00 AHD at the interface with Stone Mason Drive along the eastern boundary to a low point of approximately RL60.00 AHD at the interface with Strangers Creek along the western boundary.

The site is subject to overland flows from the residential subdivision to the east. Based on construction drawings provided by Council (refer Appendix B), the external catchment is estimated to be approximately 8.53 hectares in size.

Runoff from this catchment will generally be conveyed within an existing Council underground stormwater network discharging to Strangers Creek (refer Section 2.1.2). In major storm events, where the capacity of the existing Council stormwater network is exceeded, flows from the external catchment will run overland through the site from Stone Mason Drive to Strangers Creek.




Figure 2.3: Topography Map

(Source: The Hills Shire Council Interactive Map, 19/10/2021)

2.1.2 Existing Stormwater Infrastructure

A feature and level survey of the site was completed in March of 2021 which discovered the presence of both a 600 dia. and 900 dia. drainage lines which run east to west through the site. The survey data has been cross-referenced with historical construction drawings received from Council to develop an understanding as to what the existing drainage lines are servicing.

From these drawings it is understood that the 900 dia. drain services the residential catchment to the east of the site with the drain running from Stone Mason Drive and discharging to Strangers Creek. The 600 dia. drain services the existing carpark within the site and similarly discharges to Strangers Creek.

Neither of these drains are currently shown on the Council GIS mapping database. With regards to the 900 dia. drain this is due to the fact that the upstream catchment for which it relates has not yet been completed.

Additional surveying including CCTV is currently being organised to confirm the details and conditions of these drains.

STONE MASON DRIVE

EXISTING 900 DIA. DRAIN

EXISTING 600 DIA. DRAIN

EX.COMM

EX.E U/G

EX.W(R) U/G

EX.B U/G

EX.D

EX.S

(Source: Feature and Levels Survey by Cardno, Drawing No. 11930501001 Rev. 02, dated 29/03/21)

3 Proposed Development

The proposed development will provide state of the art facilities which enable physical recreation opportunities in conjunction with improved facilities for staff, players and existing users of the site. The proposed development will be integrated with the existing recreational landscape of the site and complement the upgrades to the existing playing fields being undertaken by Council. The proposed development is defined as a Recreation facility (major), and includes the following components:

- Construction of high-performance Centre of Excellence in the northeast of the site adjacent to Training Field 2:
 - Elite level gymnasium.
 - Medical and rehabilitation facilities.
 - Aquatic recovery and rehabilitation pools.
 - Lecture theatre and meeting rooms.
 - Player education and study areas.
 - Administrative offices for the Paramatta Eels.
 - New female facilities including a dedicated female change room, cubicle toilets and shower.
 - Balcony and terrace area.
 - End of Trip Facilities and bicycle parking.
 - Refuse Area.
- Construction of a Community Facility, including a grandstand with approximately 1,500 seats in the centre of the site adjacent to the Main Playing Field 3:
 - Unisex changerooms and amenities.
 - Referee changeroom and amenities.
 - First Aid/Medical room.
 - Community gymnasium.
 - Café/kiosk.
 - Concourse terrace.
 - Multipurpose community function room with kitchen and amenities.
 - Refuse Area.
 - Bicycle parking.
- Solar arrays will be included on the roof of both the Centre of Excellence and Community Facility.
- Additional 40 car parking spaces for the proposed facility to operate in conjunction with existing at grade car parking already constructed by Council.
- Additional landscaping throughout the development footprints.
- Removal of a small number of trees internal to the site, however noting perimeter trees will be retained where not affected by the proposed building footprints.

- Hours of operation for the Centre of Excellence and Community Facility are 5:00am to 12:00am, however the following key times are likely:
 - Centre of Excellence: 7.00am – 7.00pm.
 - Community Facility: 7.00am – 10.00pm.

4 Proposed Stormwater Strategy

4.1 Design Guidelines

The following list of documents/sources have been utilised to inform the stormwater quantity management strategy of the development:

- The Hills Development Control Plan (DCP) 2012
 - Part D, Section 7 – Balmoral Road Release Area
 - Appendix B – Water Sensitive Urban Design
 - The Hills Shire Council Design Guidelines Subdivision/Developments (September 2011)
 - Australian Rainfall and Runoff (AR&R) 1998
 - AS3500.3:2018 Plumbing and Drainage Part 3: Stormwater Drainage
 - The Hills Shire Council Site Specific Advice
-

4.2 Design Criteria

Referencing the document/sources listed in Section 4.1, the following key criteria have informed the stormwater management strategy:

- The stormwater drainage system shall be designed in accordance with Chapter 14 of the AR&R (1998).
- Overland flow paths shall be provided, capable of conveying the maximum discharge up to the 100 year ARI event, in excess of the capacity of the underground stormwater network, safely away from the proposed buildings towards the closest existing external overland flow path (Strangers Creek).
- The underground stormwater pit and pipe network shall be designed to cater for the minor storm event identified as the 10 year ARI event. Where no suitable overland flow paths are present, the underground system will be designed to convey the 100 year ARI event.
- The proposed stormwater pit and pipe network shall connect to existing stormwater infrastructure deemed to be a 'Lawful Point of Discharge' by Council by adhering to the following:
 - The point of stormwater discharge(s) is under the lawful control of Council or other statutory authority whose permission to discharge has been received.
 - The point of stormwater discharge(s) will not cause an actionable nuisance to the neighbouring sites.
- Should Onsite Stormwater Detention (OSD) be required, it shall be provided using the same principles as that of the Upper Parramatta River Catchment Trust (UPRCT) 'On-site Stormwater Detention Handbook' adjusted as per the design parameters of the Hawkesbury River Catchment which the development is situated in.
- Should Water Sensitive Urban Design (WSUD) be required, it shall be designed and constructed to comply with the requirements of Council, Water Sensitive Urban Design Technical Guidelines for Western Sydney (NSW Government Stormwater Trust and UPRCT, May 2004) and Australian Runoff Quality (Engineers Australia 2005).

4.3 Stormwater Quantity Management

As per correspondence received from The Hills Shire Council, onsite stormwater detention is not required to be provided as part of this development. This is provided the existing drainage proposed to act as the points of stormwater discharge can be demonstrated to have sufficient capacity to cater for the design flows from the minor storm event. The reason for this being that there is an existing online basin along Strangers Creek immediately downstream of the site. Refer to Appendix D for correspondence from The Hills Shire Council.

4.3.1 Hydrological Model

The Rational Method has been utilised to assess the peak design flow rate for the catchments within the development for the minor storm event as well as the major storm event where an overland flow path is not available. Within this method the following design parameters have been adopted in accordance with the Council design guidelines:

- The coefficient of runoffs are computed using the principles set out in AR&R.
- A time of concentration of 5 minutes.
- The rainfall intensities utilized are for that of the Hawkesbury catchment area as shown below.

Table 4.1: Intensity-Frequency-Duration (IFD) Rainfall for the Hawkesbury Catchment

(Source: The Hills Shire Council Design Guidelines Subdivision/Developments, September 2011)

DURATION (MIN.)	AVERAGE STORM RECURRENCE INTERVAL						
	1 Year (mm/hr)	2 Year (mm/hr)	5 Year (mm/hr)	10 Year (mm/hr)	20 Year (mm/hr)	50 Year (mm/hr)	100 Year (mm/hr)
5	79.76	102.36	130.81	147.22	169.01	197.45	219.06
6	74.73	95.90	122.52	137.88	158.27	184.88	205.10
10	61.12	78.40	100.10	112.59	129.21	150.88	167.33
12	56.49	72.46	92.49	104.02	119.35	139.35	154.53
15	51.06	65.49	83.55	93.95	107.78	125.81	139.50
18	46.83	60.05	76.59	86.11	98.11	115.29	127.82
20	44.48	57.03	72.73	81.76	93.77	109.44	121.33
24	40.58	52.03	66.33	74.55	85.50	99.76	110.59
30	36.13	46.32	59.02	66.32	76.04	88.71	98.32
45	28.96	31.11	47.25	53.07	60.82	70.93	78.59
60	24.59	31.50	40.08	45.00	51.57	60.12	66.60
90	19.33	24.80	31.66	35.61	40.86	47.71	52.91

4.3.2 Points of Stormwater Discharge

Based on the size of the development and the topography of the land, the area of works has been separated into two catchments. The North catchment includes the Centre of Excellence (COE) building, the new carpark and surrounding landscaping. The South catchment includes the new Community Facilities (CF) building, Tenancy Building, Grandstand, the surrounding pavement and landscaping as well as a section of the existing carpark.

Suitable points of connection have been nominated at the downstream ends of each catchment which allow for the flows generated by the proposed development to be discharged to Council requirements. The North catchment (Point of Discharge #1) will discharge to a new drainage line at the north-west corner of the COE building currently in construction as part of the 'Field Extension Works' project by others. The South catchment (Point of Discharge #2) will discharge to the existing 600 dia. Council drain running east to west through the site.

The existing 900 dia. Council drain would also be a suitable point of discharge for the South catchment based on available capacity. Refer to the Stormwater Layout and Catchment Plan contained within the Civil drawings in Appendix A.

4.3.3 Catchment Analysis

To determine the runoff coefficient for each catchment, the total areas have been further broken down into landscaping (pervious) and pavement and roof (impervious) sub-areas. The North catchment is observed to be the significantly larger catchment by total area, however it consists of more than 60% of pervious landscaping and it therefore converts only 57% of rainfall into runoff for the design minor storm event. Conversely, the South catchment predominantly consists of impervious roof and pavement areas and as such converts 83% of its rainfall into runoff for the design minor storm event.

Table 4.2: Catchment Area Breakdowns

CATCHMENT	TOTAL AREA (SQ.M)	LANDSCAPE AREA (SQ.M)	TOTAL PERVIOUS AREA (SQ.M)	PAVEMENT AREA (SQ.M)	ROOF AREA (SQ.M)	TOTAL IMPERVIOUS AREA (SQ.M)
North	12,988	7,950	7,950	1,545	3,493	5,038
South	8,661	1,108	1,108	5,339	2,214	7,553

Table 4.3: Catchment Runoff Coefficients

CATCHMENT	IMPERVIOUS FRACTION, F	PERVIOUS 10 YR ARI RUNOFF COEFFICIENT, C'10	10 YR ARI RUNOFF COEFFICIENT, C10
North	0.39	0.37	0.57
South	0.87	0.37	0.83

The Rational Method was then utilised to assess the peak flow rate of each catchment for the minor design storm event. The table below shows that the peak discharge rate generated by the proposed development is approximately even for the two catchments.

Table 4.4: Catchment Peak Discharge Rate

CATCHMENT	10 YR ARI RUNOFF COEFFICIENT, C10	TIME OF CONCENTRATION, T _c (MINS.)	10 YR ARI RAINFALL INTENSITY, I ¹⁰ (MM/HR)	10 YR ARI PEAK DISCHARGE RATE, Q _P (L/S)
North	0.57	5	147.22	304.41
South	0.83	5	147.22	294.57

4.3.4 Onsite Stormwater Detention (OSD)

Drawings received from Council for the 'Kellyville Memorial Park Field Extension Civil Engineering Works' (refer Appendix C) reveal that the soon to be constructed drainage nominated as the point of connection for the North catchment (Point of Discharge #1), has been designed based on an incoming flow rate of 307.17 L/s for the 10 year ARI storm event and therefore has capacity for the North catchment.

Construction drawings of the 600 dia. drain nominated as the point of connection for the South catchment (Point of Discharge #2) have not been made available. In lieu of this, the slope of the drain has been assumed to match that of the existing ground surface at approximately 1:60 grade. Utilising this grade, the pipe capacity of the existing 600 dia. reinforced concrete pipe has been estimated using Manning's Equation to be 828.41 L/s and therefore has ample capacity to service the South catchment.

Construction drawings of the 900 dia. drain running east to west through the site (refer Appendix B) indicate that the Council drain has 191.40 L/s of 'spare' capacity in excess of the design flows from the catchment it services for the 10 year ARI event. This supports the proposal to act as an optional point of stormwater discharge should it be required.

Based on the above and in line with Council advice (refer Appendix D), no onsite detention is required to be provided for this development for either catchment and thus none is proposed.

4.3.5 Overland Flow

The 900 dia. Council drain passing between the two new buildings has been designed to convey the 10 year ARI storm event without surcharge. An overland flow path has been provided between the two new buildings to safely convey overland flow associated with larger events or blockage scenarios. Overland flow is expected to surcharge into the existing carpark before overtopping between the two buildings and running down towards the creek.

The proposed strategy will be assessed within the Flood Impact Assessment Report being prepared in response to item 14 of the SEARs.

4.4 Stormwater Quality Management

As per correspondence received from The Hills Shire Council, treatment of the stormwater runoff generated on site is not required to be provided as part of this development. This is due to planned water quality treatment works within the existing online basin along Strangers Creek immediately downstream of the site. Refer to Appendix D for correspondence from The Hills Shire Council.

4.4.1 Rainwater Harvesting

In accordance with guidelines surrounding developments within the Balmoral Road Release Area contained within Part D, Section 7 of the Council DCP, rainwater harvesting tanks are being provided. The development will incorporate separate rainwater harvesting tanks for each new building collecting and storing runoff from the entire roof areas and reusing onsite for toilet flushing and landscape irrigation.

Sydney Water's online rainwater tank calculator can be used to assess the performance of various tank sizes in meeting the demand needs of a development. The Hydraulic consultant has utilised this tool to model the roof catchment areas and estimated reuse demand rates. The volumes they have proposed have been based on ensuring a minimum 50% of the demand can be met through the harvesting tanks. The table below summarises the proposed harvesting strategy for each of the buildings. Refer to Appendix E for the rainwater harvesting tank calculations.

Table 4.5: Rainwater Harvesting Strategy

BUILDING	PROPOSED TANK VOLUME (KL)	ROOF AREA CAPTURED (SQ.M)	REUSE PURPOSES	LOCATION	DEMAND MET (%)
Centre of Excellence (COE)	2x25	3300	Toilet Flushing & Landscape Irrigation	Above ground, external to the building within the landscaping.	56
Community Facilities (CF) and Tenancy	2x10	2200	Toilet Flushing & Landscape Irrigation	Below ground, external to the building within the existing carpark.	81

5 Conclusion

This report constituting the Integrated Water Management Plan (IWMP) outlined the proposed stormwater management strategy of the proposed development. It has addressed each point within item 15 'Stormwater Drainage and Water Quality' of the SEARs, as well as demonstrating compliance with all the relevant stormwater related requirements of The Hills Shire Council. A summary of the key proposals are as follows:

- New stormwater pits and pipes on site will be sized to convey the 10 year ARI storm event. Where no overland flow path is available, the pits and pipes will be sized to cater for the 100 year ARI storm event.
- Overland flow paths will be provided to convey flows in excess of the capacity of the underground stormwater network at surface level safely away from the buildings.
- Runoff generated from the proposed development will discharge to the existing and soon to be constructed (as part of separate works) drainage infrastructure.
- Onsite stormwater detention will not be provided given the drainage at the proposed points of connection have been proven to have adequate capacity to cater for the peak discharge generated by the development.
- No stormwater quality treatment measures will be implemented as part of this development. This is due to the planned water quality treatment works within the existing online basin along Strangers Creek immediately downstream of the site
- Stormwater harvesting tanks will be provided to each of the new buildings to capture runoff from the roof areas and reuse onsite for toilet flushing and landscape irrigation.

6 Limitations

This Report is provided by WSP Australia Pty Limited (*WSP*) for HB Arch (*Client*) in response to specific instructions from the Client and in accordance with WSP's proposal dated June 2020 (*Agreement*).

6.1 Permitted Purpose

This Report is provided by WSP for the purpose described in the Agreement and no responsibility is accepted by WSP for the use of the Report in whole or in part, for any other purpose (*Permitted Purpose*).

6.2 Qualifications and Assumptions

The services undertaken by WSP in preparing this Report were limited to those specifically detailed in the Report and are subject to the scope, qualifications, assumptions and limitations set out in the Report or otherwise communicated to the Client.

Except as otherwise stated in the Report and to the extent that statements, opinions, facts, conclusion and/or recommendations in the Report (*Conclusions*) are based in whole or in part on information provided by the Client and other parties identified in the report (*Information*), those Conclusions are based on assumptions by WSP of the reliability, adequacy, accuracy and completeness of the Information and have not been verified. WSP accepts no responsibility for the Information.

WSP has prepared the Report without regard to any special interest of any person other than the Client when undertaking the services described in the Agreement or in preparing the Report.

6.3 Use and Reliance

This Report should be read in its entirety and must not be copied, distributed or referred to in part only. The Report must not be reproduced without the written approval of WSP. WSP will not be responsible for interpretations or conclusions drawn by the reader. This Report (or sections of the Report) should not be used as part of a specification for a project or for incorporation into any other document without the prior agreement of WSP.

WSP is not (and will not be) obliged to provide an update of this Report to include any event, circumstance, revised Information or any matter coming to WSP's attention after the date of this Report. Data reported and Conclusions drawn are based solely on information made available to WSP at the time of preparing the Report. The passage of time; unexpected variations in ground conditions; manifestations of latent conditions; or the impact of future events (including (without limitation) changes in policy, legislation, guidelines, scientific knowledge; and changes in interpretation of policy by statutory authorities); may require further investigation or subsequent re-evaluation of the Conclusions.

This Report can only be relied upon for the Permitted Purpose and may not be relied upon for any other purpose. The Report does not purport to recommend or induce a decision to make (or not make) any purchase, disposal, investment, divestment, financial commitment or otherwise. It is the responsibility of the Client to accept (if the Client so chooses) any Conclusions contained within the Report and implement them in an appropriate, suitable and timely manner.

In the absence of express written consent of WSP, no responsibility is accepted by WSP for the use of the Report in whole or in part by any party other than the Client for any purpose whatsoever. Without the express written consent of WSP, any use which a third party makes of this Report or any reliance on (or decisions to be made) based on this Report is at the sole risk of those third parties without recourse to WSP. Third parties should make their own enquiries and obtain independent advice in relation to any matter dealt with or Conclusions expressed in the Report.

6.4 Disclaimer

No warranty, undertaking or guarantee whether expressed or implied, is made with respect to the data reported or the Conclusions drawn. To the fullest extent permitted at law, WSP, its related bodies corporate and its officers, employees and agents assumes no responsibility and will not be liable to any third party for, or in relation to any losses, damages or expenses (including any indirect, consequential or punitive losses or damages or any amounts for loss of profit, loss of revenue, loss of opportunity to earn profit, loss of production, loss of contract, increased operational costs, loss of business opportunity, site depredation costs, business interruption or economic loss) of any kind whatsoever, suffered on incurred by a third party.

Appendix A

Civil Drawings

Contained within this appendix are drawings documenting the proposed Civil works relating to the 'Kellyville Park PNRL Eels – Centre of Excellence and Community Sports Centre' development under SEARs Application No. SSD-24452965 that this report has been prepared in response to.



KELLYVILLE PARK

CENTRE OF EXCELLENCE & SPORTS HUB

CIVIL DRAWINGS

DRAWING INDEX	
DRAWING NUMBER	DRAWING TITLE
CV-000	FACE SHEET, DRAWING INDEX AND LOCALITY PLAN
CV-005	EXISTING CONDITIONS PLAN
CV-015	STORMWATER LAYOUT AND CATCHMENT PLAN
CV-030	CIVIL WORKS PLAN SHEET 1 OF 3
CV-031	CIVIL WORKS PLAN SHEET 2 OF 3
CV-032	CIVIL WORKS PLAN SHEET 3 OF 3




LOCALITY PLAN
N.T.S.

P3	23/03/2022	A.K	FOR SSDA APPROVAL	T.B	
P2	10/12/2021	A.K	50% DD ISSUE	T.B	
P1	25/10/2021	A.K	DRAFT SSDA ISSUE	T.B	
REV	DATE	BY	DESCRIPTION	CHK	APP
DRAWING STATUS: PRELIMINARY ISSUE NOT TO BE USED FOR CONSTRUCTION					




<http://www.wsp.com>

CLIENT:



ARCHITECT:



HB ARCHITECTS PTY LTD


PROJECT:

KELLYVILLE PARK
CENTRE OF EXCELLENCE & SPORTS HUB

TITLE:

FACE SHEET, DRAWING INDEX
AND LOCALITY PLAN

SCALE @ A1:	CHECKED:	APPROVED:
N.T.S	T.B	
PROJECT NUMBER:	DRAWN:	DATE:
PS123790	R.B	15/09/2021
DRAWING No:		REV:
CV-000		P3
© WSP Australia Pty Ltd		




NOTES:

- THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL DRAWINGS AS REFERENCED ON C000. FOR GENERAL NOTES REFER TO DRAWING C001.
- THE SITE FEATURE AND LEVEL SURVEY WAS PROVIDED BY CARDNO AND REFLECTS THE EXISTING CONDITIONS CURRENT TO 29/03/2021. CAD DRAWING NO. 11930501001 REV. 02. LEVELS SHOWN ARE TO A.H.D VIDE SSM165380 WITH A STATED VALUE OF RL 70.086. FOR FURTHER INFORMATION RELATING TO SURVEY CONTACT CARDNO ON (02) 9597 9700.
- WARNING: THE LOCATION OF UNDERGROUND SERVICES ARE APPROXIMATE ONLY AND THE EXACT POSITION SHOULD BE PROVEN ON SITE. NO GUARANTEE IS GIVEN THAT ALL EXISTING SERVICES ARE SHOWN.
- ALL EXISTING DRAINAGE CHANNELS ARE LIVE. THE CONTRACTOR MUST MAKE ADEQUATE PROVISIONS TO MAINTAIN THESE DURING THE WORKS INCLUDING TEMPORARY RE ROUTING ETC.

LEGEND

- EX.D — EXISTING DRAINAGE
- EX.W — EXISTING WATER
- EX.W(R) — EXISTING RECYCLED WATER
- EX.E U/G — EXISTING ELECTRICAL UNDERGROUND
- EX.G — EXISTING GAS
- EX.COMM — EXISTING COMMUNICATIONS
- EX.S — EXISTING SEWER
- — TITLE BOUNDARY



WARNING
BEWARE OF UNDERGROUND SERVICES.
THE LOCATION OF UNDERGROUND SERVICES ARE APPROXIMATE ONLY AND THEIR EXACT POSITION SHOULD BE PROVEN ON SITE BY CIVIL CONTRACTOR PRIOR TO CONSTRUCTION OF ANY CIVIL WORKS. NO GUARANTEE IS GIVEN THAT ALL EXISTING SERVICES ARE SHOWN.

P3	23/03/2022	A.K	FOR SSDA APPROVAL	T.B	
P2	18/12/2021	A.K	50% DD ISSUE	T.B	
P1	25/10/2021	A.K	DRAFT SSDA ISSUE	T.B	
REV	DATE	BY	DESCRIPTION	CHK	APP
<div>DRAWING STATUS: PRELIMINARY ISSUE NOT TO BE USED FOR CONSTRUCTION</div>					

wsp

<http://www.wsp.com>

CLIENT:



ARCHITECT:



HB ARCHITECTS PTY LTD

PROJECT:

KELLYVILLE PARK
CENTRE OF EXCELLENCE & SPORTS HUB

TITLE:

EXISTING CONDITIONS PLAN

SCALE @ A1:

1:500

PROJECT NUMBER:

PS123790

DRAWING No:

CV-005

CHECKED:

T.B

DRAWN:

R.B

APPROVED:

DATE:

15/09/2021

REV:


P3

© WSP Australia Pty Ltd

CAD FILE: PS123790-CV-015.DWG

DATE PLOTTED: 23/03/2022 1:39:36 PM BY: DESSMANN, PETER

MEMORIAL AVENUE



NOTES:

- THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL DRAWINGS AS REFERENCED ON DRAWING CV-000.
- DRAWING SHOWS TRUNK STORMWATER ONLY. REFER TO CIVIL WORKS PLANS OF DRAWINGS CV-030 TO CV-032 FOR MINOR DRAINAGE ELEMENTS.

LEGEND

- TITLE BOUNDARY
- EXISTING STORMWATER DRAINAGE
- 'FIELD EXTENSION' STORMWATER DRAINAGE PIPE BY OTHERS
- 'FIELD EXTENSION' STORMWATER DRAINAGE PITS BY OTHERS
- 'FIELD EXTENSION' SWALE BY OTHERS
- PROPOSED STORMWATER DRAINAGE PIPE
- PROPOSED GRATED PIT
- PROPOSED JUNCTION PIT
- PROPOSED SWALE
- PROPOSED CONTOURS
- PROPOSED BATTER
- NORTHERN CATCHMENT TO POINT OF STORMWATER DISCHARGE #1
- SOUTHERN CATCHMENT TO POINT OF STORMWATER DISCHARGE #2
- OVERLAND FLOW PATH

AREA BREAKDOWN				
	LANDSCAPE AREA (m ²)	PAVEMENT AREA (m ²)	ROOF AREA (m ²)	TOTAL AREA (m ²)
NORTH CATCHMENT	7944	1550	3493	12987
SOUTH CATCHMENT	1015	5434	2214	8663



SERVICE CLASHES
CONTRACTOR TO REFER TO SERVICES DOCUMENTATION AND LIAISE WITH THE RELEVANT AUTHORITY TO MITIGATE ANY SERVICE CLASHES WITH THE PROPOSED WORKS.

WARNING
BEWARE OF UNDERGROUND SERVICES. THE LOCATION OF UNDERGROUND SERVICES ARE APPROXIMATE ONLY AND THEIR EXACT POSITION SHOULD BE PROVEN ON SITE BY CIVIL CONTRACTOR PRIOR TO CONSTRUCTION OF ANY CIVIL WORKS. NO GUARANTEE IS GIVEN THAT ALL EXISTING SERVICES ARE SHOWN.

P3	23/03/2022	A.K	FOR SSDA APPROVAL	T.B	
P2	19/12/2021	A.K	50% DD ISSUE	T.B	
P1	25/10/2021	A.K	DRAFT SSDA ISSUE	T.B	
REV	DATE	BY	DESCRIPTION	CHK	AP
<div>DRAWING STATUS: PRELIMINARY ISSUE NOT TO BE USED FOR CONSTRUCTION</div>					

wsp

<http://www.wsp.com>

CLIENT:



ARCHITECT:



HB ARCHITECTS PTY LTD

PROJECT:

KELLYVILLE PARK
CENTRE OF EXCELLENCE & SPORTS HUB

TITLE:

STORMWATER LAYOUT AND CATCHMENT PLAN

SCALE @ A1:

1:500

PROJECT NUMBER:

PS123790

DRAWING No:

CV-015

© WSP Australia Pty Ltd

CHECKED:

T.B.

DRAWN:


R.B.

DATE:


15/09/2021

REV:

P3



SCALE @ A1:	1:200	CHECKED:	T.B	APPROVED:	
PROJECT NUMBER:	PS123790	DRAWN:	R.B	DATE:	15/09/2021
DRAWING No: CV-030				REV:	P3
© WSP Australia Pty Ltd					



NOTES:

- THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL DRAWINGS AS REFERENCED ON CV-000.
- ADDITIONAL SURVEYING AND CCTV TO BE COMPLETED ON EXISTING 600 & 900 DIA. COUNCIL DRAINS TO CONFIRM DETAILS AND CONDITION.
- LOCATIONS OF DOWNPIPE CONNECTIONS FROM BALCONY AND TERRACES (NOT DISCHARGING TO THE RAINWATER HARVESTING TANKS) TO BE CONFIRMED BY THE HYDRAULIC CONSULTANT.
- PIPE CONNECTIONS FROM AGI DRAINS, TRENCH GRATES, DOWNPIPES, ETC. TO BE 100 DIA. UPVC AT MIN. 1:100 GRADE UNO.

LEGEND

- EX D — EXISTING STORMWATER DRAINAGE
- FIELD EXTENSION' STORMWATER DRAINAGE PIPE BY OTHERS
- FIELD EXTENSION' STORMWATER DRAINAGE PITS BY OTHERS
- FIELD EXTENSION' SWALE BY OTHERS
- FIELD EXTENSION' RETAINING WALL BY OTHERS
- EXISTING WATER
- EXISTING RECYCLED WATER
- EXISTING SEWER
- EXISTING COMMUNICATIONS
- EXISTING ELECTRICAL UNDERGROUND
- EXISTING GAS
- TITLE BOUNDARY
- 2250 — DRAINAGE PIPE
- GP — GRATED PIT
- JP — JUNCTION PIT
- AG — AG DRAIN
- < — GRASSED SWALE
- FO — TRENCH GRATE
- FW — FLUSH OUT
- FW — SPOON DRAIN WITH FLOOR WASTE AND CONNECTION
- FW — SQUARE FLOOR WASTE
- 1:100 — SLOPE ARROW
- x P66.00 — PROPOSED LEVEL
- 66.50 — PROPOSED CONTOURS
- RW — RETAINING WALL
- ES — EDGE STRIP - TYPE ES
- B1 — BARRIER KERB - TYPE B1
- B2 — BARRIER KERB AND CHANNEL - TYPE B2
- PROPOSED BATTER
- PEDESTRIAN CONCRETE PAVEMENT
- VEHICULAR CONCRETE PAVEMENT
- ASPHALT PAVEMENT
- SAWCUT LINE

CAD FILE: PS123790-CV-030-CV-032.DWG

DATE PLOTTED: 23/03/2022 1:42:38 PM BY: DESSMANN, PETER

P3	23/03/2022	A.K	FOR SSDA APPROVAL	T.B	
P2	10/12/2021	A.K	50% DD ISSUE	T.B	
P1	25/10/2021	A.K	DRAFT SSDA ISSUE	T.B	
REV	DATE	BY	DESCRIPTION	CHK	APP
<div>DRAWING STATUS: PRELIMINARY ISSUE NOT TO BE USED FOR CONSTRUCTION</div>					

wsp

http://www.wsp.com

CLIENT:

ARCHITECT:

HB ARCHITECTS PTY LTD

PROJECT:

**KELLYVILLE PARK
CENTRE OF EXCELLENCE & SPORTS HUB**

TITLE:

**CIVIL WORKS PLAN
SHEET 2 OF 3**



SCALE @ A1:	1:200	CHECKED:	T.B.	APPROVED:	
PROJECT NUMBER:	PS123790	DRAWN:	R.B.	DATE:	15/09/2021
DRAWING No:	CV-031				REV: P3

© WSP Australia Pty Ltd



SERVICE CLASHES
CONTRACTOR TO REFER TO SERVICES DOCUMENTATION AND LIAISE WITH THE RELEVANT AUTHORITY TO MITIGATE ANY SERVICE CLASHES WITH THE PROPOSED WORKS.

WARNING
BEWARE OF UNDERGROUND SERVICES. THE LOCATION OF UNDERGROUND SERVICES ARE APPROXIMATE ONLY AND THEIR EXACT POSITION SHOULD BE PROVEN ON SITE BY CIVIL CONTRACTOR PRIOR TO CONSTRUCTION OF ANY CIVIL WORKS. NO GUARANTEE IS GIVEN THAT ALL EXISTING SERVICES ARE SHOWN.



- NOTES:**
- THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL DRAWINGS AS REFERENCED ON CV-000.
 - ADDITIONAL SURVEYING AND CCTV TO BE COMPLETED ON EXISTING 600 & 900 DIA. COUNCIL DRAINS TO CONFIRM DETAILS AND CONDITION.
 - LOCATIONS OF DOWNPIPE CONNECTIONS FROM BALCONY AND TERRACES (NOT DISCHARGING TO THE RAINWATER HARVESTING TANKS) TO BE CONFIRMED BY THE HYDRAULIC CONSULTANT.
 - PIPE CONNECTIONS FROM AGI DRAINS, TRENCH GRATES, DOWNPIPES, ETC. TO BE 100 DIA. UPVC AT MIN. 1:100 GRADE UNO.

- LEGEND**
- EX.D EXISTING STORMWATER DRAINAGE
 - FIELD EXTENSION STORMWATER DRAINAGE PIPE BY OTHERS
 - FIELD EXTENSION STORMWATER DRAINAGE PITS BY OTHERS
 - FIELD EXTENSION SWALE BY OTHERS
 - FIELD EXTENSION RETAINING WALL BY OTHERS
 - EXISTING WATER
 - EXISTING RECYCLED WATER
 - EXISTING SEWER
 - EXISTING COMMUNICATIONS
 - EXISTING ELECTRICAL UNDERGROUND
 - EXISTING GAS
 - TITLE BOUNDARY
 - 2250 DRAINAGE PIPE
 - GP GRATED PIT
 - JP JUNCTION PIT
 - AG AG DRAIN
 - GRASSSED SWALE
 - TRENCH GRATE
 - FO FLUSH OUT
 - FW SPOON DRAIN WITH FLOOR WASTE AND CONNECTION
 - FW SQUARE FLOOR WASTE
 - 1:100 SLOPE ARROW
 - x P66.00 PROPOSED LEVEL
 - 66.50 PROPOSED CONTOURS
 - RW RETAINING WALL
 - ES EDGE STRIP - TYPE ES
 - B1 BARRIER KERB - TYPE B1
 - B2 BARRIER KERB AND CHANNEL - TYPE B2
 - PROPOSED BATTER
 - PEDESTRIAN CONCRETE PAVEMENT
 - VEHICULAR CONCRETE PAVEMENT
 - ASPHALT PAVEMENT
 - SAWCUT LINE



SERVICE CLASHES
CONTRACTOR TO REFER TO SERVICES DOCUMENTATION AND LIAISE WITH THE RELEVANT AUTHORITY TO MITIGATE ANY SERVICE CLASHES WITH THE PROPOSED WORKS.

WARNING
BEWARE OF UNDERGROUND SERVICES. THE LOCATION OF UNDERGROUND SERVICES ARE APPROXIMATE ONLY AND THEIR EXACT POSITION SHOULD BE PROVEN ON SITE BY CIVIL CONTRACTOR PRIOR TO CONSTRUCTION OF ANY CIVIL WORKS. NO GUARANTEE IS GIVEN THAT ALL EXISTING SERVICES ARE SHOWN.

CAD FILE: PS123790-CV-030-C4-02.DWG

DATE PLOTTED: 23/03/2022 1:44:07 PM BY: DESSMANN, PETER

P3	23/03/2022	A.K	FOR SSDA APPROVAL	T.B	
P2	16/12/2021	A.K	50% DD ISSUE	T.B	
P1	25/10/2021	A.K	DRAFT SSDA ISSUE	T.B	
REV	DATE	BY	DESCRIPTION	CHK	APP
DRAWING STATUS: PRELIMINARY ISSUE NOT TO BE USED FOR CONSTRUCTION					

wsp

http://www.wsp.com

CLIENT:

ARCHITECT:

HB ARCHITECTS PTY LTD

PROJECT:

**KELLYVILLE PARK
CENTRE OF EXCELLENCE & SPORTS HUB**

TITLE:

**CIVIL WORKS PLAN
SHEET 3 OF 3**

SCALE @ A1:	1:200	CHECKED:	T.B	APPROVED:	
PROJECT NUMBER:	PS123790	DRAWN:	R.B	DATE:	15/09/2021
DRAWING No:	CV-032	REV:	P3		

© WSP Australia Pty Ltd

Appendix B

Civil Works Plans for Residential Subdivision

Contained within this appendix are an excerpt of drawings provided by The Hills Shire Council for the 'Plan of Civil Works for the Subdivision of Lot 2 D.P. 135989 at Windsor Road, Kellyville L.G.A. Baulkham Hills' by North Western Surveys.

Project Reference: 13180

Revision: FF

Dated: 16/12/2016





THE HILLS SHIRE COUNCIL
CONSTRUCTION CERTIFICATE

DA ...980/2016/ZD...
CC ...52/2017/EC...
CC APPROVED ON
28/02/2017

LEGEND OF LINES AND SYMBOLS


PROPOSED	DESCRIPTION	EXISTING
	KERB & GUTTER WITH VEHICULAR CROSSING	
	EDGE OF SEAL	
	TABLEDRAIN	
	ROAD CENTRELINE, CHAINAGE	
	CONCRETE FOOTPATH/DRIVEWAY	
	ROAD PAVEMENT	
	DRAINAGE LINE, PIT, HEADWALL	
	COMMON DRAINAGE LINE, SLOPE JUNCTION, PIT	
	SURFACE CONTOURS	
	SURFACE LEVEL	
	AREAS OF CUT	
	AREAS OF FILL	
	LIMIT OF WORKS	
	STREET SIGNS	
	POWER POLE	
	HYDRANT / STOP VALVE	
	TELECOMMUNICATION CABLE, PIT	
	SEWER LINE, PIT	
	MASONRY RETAINING WALL	
	TOP OF BANK	
	TOE OF BANK	

WRITTEN APPROVAL REQUIRED FOR WORKS AND
ACCESS FROM ADJACENT PROPERTY



- NOTES:
- > PROVIDE COUNCILS STANDARD INDUSTRIAL/COMMERCIAL CONCRETE LAYBACK & FOOTWAY CROSSINGS.
 - > # ALL STUBS TO BE 375mm RCP 1% TO BOUNDARY UNLESS OTHERWISE SPECIFIED.
 - > REPLACE EXISTING PITS AT LOCATIONS 2/101, 3/101, 4/101 WITH NEW PITS. SEE SHEETS 15 FOR PIT SCHEDULE AND SHEET 17 FOR LONGSECTIONS.
 - > REPLACE EXISTING HEADWALL AT 5/101 WITH NEW.

REV.	DESCRIPTION	DATE	APPR.
EE	PIPE UPSIZED	15/12/2016	-
DD	DRAINAGE LINE 1 MOVED	3/11/2016	-
CC	DRAINAGE LINE 1 PIPES UPSIZED	27/10/2016	-
BB	AMENDED TO COUNCILS REQUIREMENTS	7/09/2016	-
AA	ENGINEERING CC DRAWINGS	2/08/2016	-



CLIENT/ PROJECT
J&M MCNAMEE HOLDINGS PTY LTD
THIS PLAN MUST NOT BE USED FOR CONSTRUCTION UNLESS SIGNED AS APPROVED BY PRINCIPAL CERTIFYING AUTHORITY

North Western Surveys
Surveyors, Engineers & Water Servicing Coordinators
1/11 Romford Road, P.O. Box 1045, Blacktown N.S.W. 2148
Phone: 9831-2040 Fax: 9622-5716 Email: nws@nwsurveys.com.au
THIS DRAWING IS SUBJECT TO COPYRIGHT. IT MUST NOT BE REPRODUCED IN WHOLE OR PART WITHOUT PRIOR WRITTEN CONSENT OF NORTH WESTERN SURVEYS Pty. Ltd.

SURVEYED: ---	GRID: M.G.A.	DATUM: AHD
DRAWN: F.H	DRAFTING CHECK: B.M	HORIZONTAL RATIO: 1:500
DESIGNED: B.M	DESIGN CHECK: -	VERTICAL RATIO: -

PROPOSED CIVIL WORKS FOR LOT 102 IN A SUBDIVISION OF LOT 2 IN DP 135989 AT WINDSOR RD, KELLYVILLE L.G.A THE HILLS SHIRE				SHEET 2 OF 21 SHEETS
PROJECT MANAGER: A.L.	DATE: 15/12/2016	REVISION: EE	PROJECT REFERENCE: 13180	

21
EETS

																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									</
--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	----

Appendix C

Civil Works Plans for Kellyville Park Field Extension


Contained within this appendix are an excerpt of drawings provided by The Hills Shire Council for the 'Kellyville Memorial Park Field Extension Civil Engineering Works' by C & M Consulting Engineers.

Project Reference: 02081

Revision: A

Dated: 20/09/2020







FOR CONTINUATION REFER DRG. 202

FOR CONTINUATION REFER DRG. 202

A	W.M.	20/09/2020	A.M.	TENDER ISSUE	
REV.	DES.	DATE	VER.	DESCRIPTION	



CLIENT



CIVIL AND HYDRAULIC
ENGINEERING DESIGN AND
PROJECT MANAGEMENT

SUITE 26
11 - 13 BROOKHOLLOW AVE
NORWEST NSW 2153



PHONE: (02) 9680 3100
FAX: (02) 9634 6989
ABN 21 118 134 240

DESIGNER	W.M.	DATE	JUNE 2020
ENGINEER	A.M.	LGA	THE HILLS
VERIFIER	A.M.	SCALE @ A1	1:250
© THIS DRAWING AND DESIGN IS THE COPYRIGHT OF C&M CONSULTING ENGINEERS PTY. LTD. NO PART OF THIS DRAWING OR DESIGN SHALL BE REPRODUCED OR USED WITHOUT PRIOR WRITTEN CONSENT FROM C&M CONSULTING ENGINEERS PTY. LTD.			







KELLYVILLE MEMORIAL PARK- FIELD EXTENSION

GENERAL ARRANGEMENT PLAN - SHEET 1

STATUS	TENDER	DRAWING No.	02081_FE_201	REVISION	A
--------	--------	-------------	--------------	----------	---




Stormwater Pit Schedule			
Pit Identifier	Pit Type	Pit Chamber Size	Pit Grate/Lid Type
A/1	GSIP	900 x 900	Nominal 900 x 900 Class C Galv. Steel Grate
A/2	GSIP	900 x 650	Nominal 900 x 900 Class C Galv. Steel Grate
A/3	GSIP	900 x 900	Nominal 900 x 900 Class C Galv. Steel Grate
A/4	GSIP	900 x 900	Nominal 900 x 900 Class C Galv. Steel Grate
A/5	JP	900 x 900	Nominal 900 x 900 Class C Solid Cover
A/6	GSIP	900 x 900	Nominal 900 x 900 Class C Galv. Steel Raised Grate & Frame




- STORMWATER PIT NOTES:**
1. PROVIDE STEP IRONS FOR PITS DEEPER THAN 120mm.
 2. COMPRESSIVE STRENGTH IF (I) FOR CAST INSITU CONCRETE SHALL BE A MINIMUM 25MPa @ 28 DAYS.
 3. 100mm SLOTTED SUBSOIL DRAINAGE PIPE 3.0m LONG WRAPPED IN GEOTEXTILE FILTER SOCK TO BE PROVIDED ADJACENT ALL INLET PIPES.
 4. ALL PITS TO BE ADEQUATELY STREAMLINED AND BENCHED.
 5. GRATES TO BE PROVIDED WITH ADEQUATE LOCKING CLIPS OR 'J' BOLTS.
 6. ALL GRATES TO BE HINGED TO FRAME.
 7. PITS DEEPER THAN 180mm TO HAVE 200mm THICK WALLS AND BASE WITH SL81 MESH CENTRALLY PLACED. N12 CORNER BARS @ 400 C/C 450 LEGS IN BASE & SIDE.
 8. ALL REINFORCEMENT TO HAVE MINIMUM 40mm COVER.
 9. PITS MUST BE FINISHED AS PER THE DETAILS SHOWN ON THE DRAWINGS. i.e. PITS MUST BE BENCHED, PIPES MUST BE CUT FLUSH WITH PIT WALLS, STEP IRONS MUST BE INSTALLED etc.
 10. PIPE PENETRATIONS ARE TO BE PROPERLY FINISHED WITH CONCRETE GROUT, RENDER etc.

REV.	DES.	DATE	VER.	DESCRIPTION
A	W.M.	20/09/2020	A.M.	TENDER ISSUE



CLIENT



CIVIL AND HYDRAULIC
ENGINEERING DESIGN AND
PROJECT MANAGEMENT

SUITE 26
11 - 13 BROOKHOLLOW AVE
NORWEST NSW 2153

PHONE: (02) 9680 3100
FAX: (02) 9634 6989
ABN 21 118 134 240

DESIGNER	W.M.	DATE	JUNE 2020
ENGINEER	A.M.	LGA	THE HILLS
VERIFIER	A.M.	SCALE @ A1	AS NOTED

© THIS DRAWING AND DESIGN IS THE COPYRIGHT OF C&M CONSULTING ENGINEERS PTY. LTD. NO PART OF THIS DRAWING OR DESIGN SHALL BE REPRODUCED OR USED WITHOUT PRIOR WRITTEN CONSENT FROM C&M CONSULTING ENGINEERS PTY. LTD.

KELLYVILLE MEMORIAL PARK - FIELD EXTENSION			
STORMWATER DRAINAGE CATCHMENT PLAN & DETAILS			
STATUS	TENDER	DRAWING No.	02081_601
REVISION	A		

CALCULATION TABLE - HYDRAULICS - 1 IN 10 YEAR ARI																						
PIPE ID	PIPE U/S TOTAL CATCHMENT	PIPE U/S DRAINAGE TIME	PIPE U/S ToC	PIPE U/S INTENSITY	PIPE FLOW	PIPE TYPE & CLASS	PIPE DIAMETER	PIPE LENGTH	PIPE GRADE	COLEBROOK - WHITE 'k'	PIPE D/S INVERT	PIPE U/S INVERT	U/S PIT LOSS COEFFICIENT	PIPE VELOCITY	PIPE FRICTION LOSS	PIPE FRICTION SLOPE	PIPE D/S HGL	PIPE U/S HGL	PIT LOSS	WATER SURFACE ELEVATION	PIPE SURFACE FLOW	PIPE ID
	(Ha)	(min)	(min)	(mm/hr)	(L/s)		(mm)	(m)	(%)	(mm)	(mRL)	(m/RL)	(ku)	(m/s)	(m)	(%)	(m/RL)	(m/RL)	(m)	(m/RL)	(L/s)	
A/1-A/2	1.303	0.343	6.343	135.857	337.0	RCP2-RRJ	450	43.62	1.5	0.60	57.15	57.80	1.0	2.12	0.47	0.01	57.60	58.25	0.23	58.48	0.00	A/1-A/2
A/2-A/3	1.052	0.542	5.801	139.791	305.8	RCP2-RRJ	450	62.52	2.1	0.60	57.83	59.15	1.0	1.92	0.56	0.01	58.48	59.60	0.19	59.79	0.00	A/2-A/3
A/3-A/4	0.968	0.411	5.390	143.494	299.8	RCP2-RRJ	450	46.53	1.3	0.60	59.18	59.80	2.0	1.89	0.40	0.01	59.79	60.25	0.36	60.61	0.00	A/3-A/4
A/4-A/5	0.968	0.313	5.076	146.314	305.7	RCP2	450	36.15	1.0	0.60	59.83	60.20	1.0	1.92	0.32	0.01	60.61	60.94	0.19	61.12	0.00	A/4-A/5
A/5-A/6	0.926	0.076	5.000	147.000	300.0	RCP2-RRJ	450	8.62	11.8	0.60	60.23	61.25	1.0	1.89	0.07	0.01	61.12	61.70	0.18	61.88	0.00	A/5-A/6

PIT ID	LOCAL CATCHMENT AREA	FRACTION IMPERVIOUS	FLOW LENGTH	FLOW SLOPE	CATCHMENT ROUGHNESS	CRITICAL TC	RAINFALL INTENSITY	ROUGHNESS COEFFICIENT	LOCAL SURFACE INFLOW	LOCAL PIPE INFLOW	LOCAL SPECIFIED INFLOW	BYPASS FROM PIT	BYPASS FLOW RECIEVED	TOTAL PIT INFLOW	PIT TYPE	PIT INLET CAPACITY	BYPASS OUTFLOW	BYPASS TO PIT	GUTTER FLOW WIDTH	PIT ID
	(ha)		(m)	%	n	(min)	(mm/hr)	C	(L/s)	(L/s)	(L/s)		(L/s)	(L/s)		(L/s)	(L/s)		(m)	
A/1												A/2			GSIP					A/1
A/2	0.251	0.10				5.00	147.00	0.42	43.04			A/3		43.04	GSIP	43.04		A/1		A/2
A/3	0.084	0.10				5.00	147.00	0.42	14.40			A/4		14.40	GSIP	14.40		A/2		A/3
A/4							147.00					A/5			GSIP	0.00		A/3		A/4
A/5	0.042	0.10				5.00	147.00	0.42	7.20			A/6		7.20	GSIP	7.20		A/4		A/5
A/6	0.926	0.80				5.00	147.00	0.79	299.97					299.97	GSIP	299.97		A/5		A/6

[illegible]

Appendix D

Council Correspondence

Contained within this appendix is correspondence received from The Hills Shire Council on the 28/05/2021. This correspondence specifies site specific requirements in relation to stormwater quality and quantity for the 'Kellyville Park PNRL Eels – Centre of Excellence and Community Sports Centre' development under SEARs Application No. SSD-24452965 that this report has been prepared in response to.



Khoshaba, Alex

From: Benjamin Hawkins <bhawkins@thehills.nsw.gov.au>
Sent: Friday, 28 May 2021 4:14 PM
To: Khoshaba, Alex
Cc: Bell, Tyran; Gray Barton; Eric Ruiz; Robert DiNatale; Coskun Nadiroglu; Anisul Huq
Subject: RE: Attention Subdivision Team - Kellyville Park Centre of Excellence and Community Facilities [Filed 29 May 2021 17:51]
Attachments: PS123790-20210527-AK5-Existing SW Markup.pdf

Hi Alex

See responses in red below.

This should negate the need for a meeting but let me know if you still need to discuss anything.

Thanks

Ben H

From: Khoshaba, Alex [mailto:Alex.Khoshaba@wsp.com]
Sent: Friday, 28 May 2021 3:27 PM
To: Coskun Nadiroglu; Anisul Huq
Cc: Bell, Tyran; Gray Barton; Eric Ruiz; Robert DiNatale; Benjamin Hawkins
Subject: RE: Attention Subdivision Team - Kellyville Park Centre of Excellence and Community Facilities

Hi Coskun & Anisul,

Further to my last sentence in my email from yesterday, we believe it is a good idea to setup a teams meeting to discuss the below. This will enable us to clearly communicate and discuss the items we are requesting preliminary Council advice on which should save us some time rather than going back and forth via email.

Can you please advise a day and time that suits you for a brief meeting next week? I will forward through an invite once received.

Kind Regards,

Alex Khoshaba
Project Engineer - Civil



T: +61 3 9622 9795

Alex.Khoshaba@wsp.com

WSP Australia Pty Limited
Level 15, 28 Freshwater Place
Southbank, VIC
3006 Australia

wsp.com

From: Khoshaba, Alex
Sent: Thursday, 27 May 2021 2:20 PM
To: Coskun Nadiroglu <cnadiroglu@thehills.nsw.gov.au>; Anisul Huq <ahuq@thehills.nsw.gov.au>

Cc: Bell, Tyran <Tyran.Bell@wsp.com>; Gray Barton <barton@hbarch.com.au>; Eric Ruiz <jruiz@thehills.nsw.gov.au>; Robert DiNatale <rdinatale@thehills.nsw.gov.au>; Benjamin Hawkins <bhawkins@thehills.nsw.gov.au>
Subject: RE: Attention Subdivision Team - Kellyville Park Centre of Excellence and Community Facilities

Hi Coskun and Anisul,

As we have now confirmed the presence of an existing council drain conveying flows through our site (Kellyville Park) from Stone Masons Drive (refer previous correspondence below), we request your preliminary advice on each of the below items to assist with our civil/stormwater design ahead of our formal SEARs request.

- What are Council's build-over requirements for this drain?
- Would council object to permanent building structure spanning laterally over the drain assuming that the pipe below the building was upgraded to convey the major design storm with blockage allowance and could be readily maintained from upstream and downstream pits?
 - Does Council have a preference as to which option we move forward with as shown on the stormwater markup available at the link below?
- Horizontal and vertical clearance requirements?
- Restrictions of pavement types, concrete staircases, planting etc.

Option two (relocation) is preferred. Our specifications do not allow for structures over pipes and so option one would need to be considered as a variation on merit at the development application stage and is unlikely to be supported when there is an obvious alternative.

If you are seeking to upgrade the existing twin pipes to convey the major/ 100 year design storm anyway it makes even more sense to just relocate them clear of the proposed building. The current twin pipes are designed to convey flows associated with the minor/ 10 year design storm. If you increase the size of the pipes you need to extend it all the way to the outlet/ you cannot connect a big pipe into a smaller pipe at the downstream extent of your works for example.

Alternatively you could amend the building to locate the gap where the pipes are located.

Whatever major flows are not contained to the pipes need to be conveyed overland. If the pipes are upsized to convey major flows you still need to shape the land around the buildings to protect them from flooding/ in the event of a blockage.

- If the drain requires diversion around the new building footprint, what degree of modelling, documentation and reporting is required to be reviewed by Council for approval of the stormwater diversion?

Basic stormwater calculations as part of the civil design will do. You will need to quantify the volume of overland flow in the major storm to ensure overland flow around the building is catered for.

- Will Council permit the stormwater generated from the new development to discharge to the existing 900 dia. stormwater drain running below the training fields?

Yes, so long as you can demonstrate capacity with your calculations (above).

- Will Council impose their standard onsite detention requirements as outlined in the DCP on this development?
 - In our opinion a dispensation should be provided with regards to the general OSD requirement as there are no properties immediately downstream of the site and the existing stormwater network discharges directly to Strangers Creek. In addition to this the recent council projects on-site including the carpark and upstream residential development were not required to restrict stormwater discharge.

No OSD or stormwater quality treatment is required. There is an existing basin and planned water quality treatment works within the online basin along Strangers Creek immediately downstream. You do need to include stormwater or rainwater reuse in your development (similar to all other development in the precinct as per the Balmoral Road section from our Development Control Plan).

- Will Council impose their standard water sensitive urban design requirements as outlined in the DCP on this development?

See above.

The following documents are available for download at the link below for your reference:

- Feature and services survey.
- Approved construction drawings for the lot 2 subdivision civil works which include the design of the existing 900 dia. drain running through the development site.
- Work-in-Progress architectural concept plan for the proposed development to give context on what is being proposed.
- Stormwater markup of the existing drainage illustrating two options as to how these can be integrated within the proposed development.

<https://spaces.hightail.com/space/0pvFOkO8Dm>

We kindly request your preliminary advice with respect to the above items by Friday June 4th. We are happy to discuss this over a short teams meeting with you next week to provide further detail/clarity if you feel this would assist.

Kind Regards,

Alex Khoshaba
Project Engineer - Civil



T: +61 3 9622 9795

Alex.Khoshaba@wsp.com

WSP Australia Pty Limited
Level 15, 28 Freshwater Place
Southbank, VIC
3006 Australia

wsp.com

Appendix E

Rainwater Harvesting Tank Calculations

Contained within this appendix are rainwater harvesting tank calculations completed by Erbas, dated 15/10/2021, for the 'Kellyville Park PNRL Eels – Centre of Excellence and Community Sports Centre' development under SEARs Application No. SSD-24452965 that this report has been prepared in response to.



**COMMUNITY FACILITIES (CF)
& TENANCY BUILDINGS**

Rainwater tank calculator

Calculate how much water a rainwater tank could save your business and what size tank is the most suitable for your needs.

Postcode**Roof area that will be connected to the rainwater tank**m²**Planned rainwater tank size**

litres

Where will you use rainwater?

Describe where you will use rainwater in your business. Leave a section blank if you do not intend to supply rainwater to that area.

1. Toilet

Number of employees**Number of operating days a year**

2. Irrigation

Flow rate

L/min

Hours/week

Enter information about other water using processes in your business. Use section 3 for processes with fixed water use and section 4 when the water use varies over the year, eg cooling towers

3. Other water use (fixed)

Item demand

	kL/day
--	--------

4. Other water use (variable)

January

	kL/day
--	--------

Febuary

	kL/day
--	--------

March

	kL/day
--	--------

April

	kL/day
--	--------

May

	kL/day
--	--------

June

	kL/day
--	--------

July

	kL/day
--	--------

August

	kL/day
--	--------

September

	kL/day
--	--------

October

	kL/day
--	--------

November

	kL/day
--	--------

December

	kL/day
--	--------

Rainwater tank calculator results


Summary

You selected a tank size of **20000 litres**

This sized tank could provide up to **56%** of the rainwater you need each day.

Some additional tank sizes are displayed in the chart below to help you select the most suitable rainwater tank for your business

Percentage of your business water needs provided by various tank sizes.



Tank size (kL)	% rainwater provided	Drinking water saved each day (litres)
20	56	1,924
30	63	2,214
50	74	2,611
80	83	2,943
110	89	3,166
130	92	3,276
160	95	3,386


Interpreting the results

The range of tank sizes shown is based on the water needs of your business. The benefits may reduce when you reach a certain tank size.

The best tank size will be the one that balances increased water savings with cost effectiveness. Use the information in the table above with quotations from your rainwater tank supplier to determine the best tank for your business.

Water savings depend on rainfall, roof area and tank size. If your water needs are not being met by any of the tank sizes shown, your roof area may be too small or the rainfall in your area too low.

Daily rainwater provided by a 20,000 litre tank each month



Toilets

3,375.00 L/day

Irrigation

2,520.00 L/week

Other (fixed)

0.00 kl/day

Other (variable)

0.00 kl/day

Rainfall information

Five years of rainfall data (2005 to 2009) from the **PARAMATTA NORTH (MASONS DRIVE)** was used in the calculations.

Printed on: 15/10/21 13:01

URL: <http://www.sydneywater.com.au/SW/your-business/managing-your-water-use/water-efficiency-tips/rainwater-tank-calculator/index.htm>

Copyright: © Sydney Water 2021

**CENTRE OF EXCELLENCE
(COE) BUILDING**

Rainwater tank calculator

Calculate how much water a rainwater tank could save your business and what size tank is the most suitable for your needs.

Postcode



Roof area that will be connected to the rainwater tank



Planned rainwater tank size



Where will you use rainwater?

Describe where you will use rainwater in your business. Leave a section blank if you do not intend to supply rainwater to that area.

1. Toilet

Number of employees

Number of operating days a year

2. Irrigation

Flow rate

Hours/week

Enter information about other water using processes in your business. Use section 3 for processes with fixed water use and section 4 when the water use varies over the year, eg cooling towers

3. Other water use (fixed)

Item demand

	kL/day
--	--------

4. Other water use (variable)

January

	kL/day
--	--------

Febuary

	kL/day
--	--------

March

	kL/day
--	--------

April

	kL/day
--	--------

May

	kL/day
--	--------

June

	kL/day
--	--------

July

	kL/day
--	--------

August

	kL/day
--	--------

September

	kL/day
--	--------

October

	kL/day
--	--------

November

	kL/day
--	--------

December

	kL/day
--	--------

Rainwater tank calculator results


Summary

You selected a tank size of **50000 litres**

This sized tank could provide up to **81%** of the rainwater you need each day.

Some additional tank sizes are displayed in the chart below to help you select the most suitable rainwater tank for your business

Percentage of your business water needs provided by various tank sizes.



Tank size (kL)	% rainwater provided	Drinking water saved each day (litres)
30	70	2,471
50	81	2,871
80	90	3,205
110	95	3,391
130	97	3,462
160	98	3,532


Interpreting the results

The range of tank sizes shown is based on the water needs of your business. The benefits may reduce when you reach a certain tank size.

The best tank size will be the one that balances increased water savings with cost effectiveness. Use the information in the table above with quotations from your rainwater tank supplier to determine the best tank for your business.

Water savings depend on rainfall, roof area and tank size. If your water needs are not being met by any of the tank sizes shown, your roof area may be too small or the rainfall in your area too low.

Daily rainwater provided by a 50,000 litre tank each month



Toilets

3,375.00 L/day

Irrigation

2,520.00 L/week

Other (fixed)

0.00 kl/day

Other (variable)

0.00 kl/day

Rainfall information

Five years of rainfall data (2005 to 2009) from the **PARAMATTA NORTH (MASONS DRIVE)** was used in the calculations.

Printed on: 15/10/21 13:01

URL: <http://www.sydneywater.com.au/SW/your-business/managing-your-water-use/water-efficiency-tips/rainwater-tank-calculator/index.htm>

Copyright: © Sydney Water 2021