



## EXPLANATION SHEET BOREHOLE LOG

### GENERAL

#### Method

Non-Cored Borehole
Auger
Hand Auger
Diamond Rotary
Percussion
Other

#### Coring Size

Cored Borehole	Nominal Core Diameter (mm)
NMLC	51.9
BQ	36.5
BQ3	33.5
NQ	47.6
NQ3	45.1
HQ	63.5
HQ3	61.1
PQ	85
PQ3	83.1
Diatube	Variable
Other	-





#### Testing

Symbol	Description
UCS	Uniaxial Compressive Strength
TXL	Triaxial Test
BT	Brazilian Test
DT	Direct Tensile
SD	Slake Durability
Packer	Rock Mass Permeability

#### Samples

Symbol	Description
U50	50 mm undisturbed tube sample
D	Disturbed sample
Bs	Bulk sample

#### Water

Symbol	Description
	Water level
	Water inflow
	Complete water loss
	Partial water loss

## SOIL DESCRIPTIONS

### Unified Soil Classification System (USCS)

Major Divisions			Symbol	Typical Names
Coarse-Grained Soils More than 50% coarser than 0.075mm	Gravels (more than 50% coarser than 2mm)	Clean Gravels	GW	Well-graded gravels and gravel-sand mixtures, little or no fines.
			GP	Poorly graded gravels and gravel-sand mixtures, little or no fines.
		Gravels With Fines	GM	Silty gravels, gravel-sand-silt mixtures.
			GC	Clayey gravels. gravel-sand-clay mixtures.
	Sands (more than 50% of coarse fraction finer than 2mm)	Clean Sands	SW	Well-graded sands and gravelly sands, little or no fines.
			SP	Poorly graded sands and gravelly sands, little or no fines.
		Sand With Fines	SM	Silty sands, sand-silt mixture.
			SC	Clayey sands, sand-clay mixtures.
Fine-Grained Soils 50% or more finer than 0.075mm	Silts and Clays Liquid limit 50% or less		ML	Inorganic silts, very fine sands, rock flour silty or clayey fine sands.
			CL	Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays.
			OL	Organic silts and silty clays of low plasticity.
	Silts and Clays Liquid limit greater than 50%		MH	Inorganic silts, micaceous or diatomaceous fine sands or silts, elastic silts.
			CH	Inorganic clays of high plasticity, fat clays.
			OH	Organic clays of medium to high plasticity.
	Highly Organic Soils		PT	Peat etc.

### Moisture Condition

Term	Symbol
Dry	D
Moist	M
Wet	W
Wet at Plastic Limit	WP
Wet at Liquid Limit	WL

## Strength

**COHESIVE SOILS** are described in terms of undrained shear strength, colour and structure with comments on minor constituents or apparent special features. Undrained shear strength is measured by hand penetrometer or determined by laboratory testing or estimated from experience. Classification in terms of undrained shear strength is as follows:

Term	Symbol	Description for Field Estimation	Shear Strength (kPa)	UCS (kPa)
Very Soft	VS	Easily penetrated several centimetres by fist.	<12	<25
Soft	S	Easily penetrated several centimetres by thumb. Can be moulded by light finger pressure.	12-25	25-50
Firm	F	Can be penetrated by thumb with moderate effort. Can be moulded by strong finger pressure.	25-50	50-100
Stiff	ST	Readily indented by thumb.	50-100	100-200
Very Stiff	VST	Readily indented by thumbnail.	100-200	200-400
Hard	H	Indented with difficulty by thumbnail	>200	>400

**NON-COHESIVE SOILS** are described in terms of density, colour, with comments on minor constituents or special features. Density (density index) is generally based on standard penetration testing (AS1289 Method 6.3.1), or other forms of penetration testing. Terms used in describing density are set out below:

Term	Symbol	Density Index	SPT N Values
Very Loose	VL	<15%	<5
Loose	L	15-35 %	5-10
Medium Dense	MD	35-65 %	10-30
Dense	D	65-85 %	30-50
Very Dense	VD	>85 %	>50



## ROCK DESCRIPTIONS

### Weathering

Term	Symbol	Description
Fresh	FR	Rock substance unaffected by weathering.
Slightly Weathered	SW	Rock substance affected by weathering to the extent that partial staining or partial discolouration of the rock substance usually by limonite has taken place. The colour and texture of the fresh rock is recognisable; strength properties are essentially those of the fresh rock substance.
Moderately Weathered	MW	Rock substance affected by weathering to the extent staining extends throughout whole of the rock substance and the original colour of the fresh rock is no longer recognisable.
Highly Weathered	HW	Rock substance affected by weathering to the extent that limonite staining or bleaching affects the whole of the rock substance and signs of chemical or physical decomposition of individual minerals are usually evident. Porosity and strength may be increased or decreased when compared to the fresh rock substance, usually as a result of the leaching or deposition of iron. The colour and strength of the original fresh rock substance is no longer recognisable.
Extremely Weathered	EW	Rock substance affected by weathering to the extent that the rock exhibits soil properties, i.e. it can be remoulded and can be classified according to the Unified Soil Classification System, but the texture of the original rock is still evident.

### Strength

Term	Symbol	Description for Field Estimation	UCS (MPa)
Extremely Low	R0	Thumbnail easily scratches; gentle blow with geological pick leaves deep impression.	0.7-1.5
Very Low	R1	Can be peeled by a pocket knife. Crumbles under firm blows with geological pick.	1.5-3.0
Low	R2	Can be peeled by a pocket knife with difficulty; shallow indentation made by firm blow of geological pick.	3.0-10
Medium	R3	Cannot be scraped or peeled with a pocket knife; specimen can be fractured with single firm blow of hammer end of geological pick.	10-25
High	R4	Specimen requires more than one blow with hammer end of geological pick to fracture.	25-80
Very High	R5	Specimen requires many blows of hammer end of geological pick to fracture.	>80

## Defect Description

**Order of description:** type, inclination, shape, roughness, infill type, infill thickness, number

### Defect Type

Symbol	Description
CL	Clay Seam
FL	Fault - fracture along which displacement is recognisable.
SR	Shear - a fracture along which movement has taken place but no displacement is recognisable. Evidence for movement may be slickensides, polishing and/or clay gouge.
SH	Sheared Zone - zone of multiple closely spaced fracture planes with roughly parallel planar boundaries usually forming blocks of lenticular or wedge shaped intact material. Fractures are typically smooth, polished or slickensided; and curved.
BG	Bedding parting - arrangement in layers of mineral grains or crystals parallel to surface of deposition along which a continuous observable parting occurs.
BSH	Bedding plane shear - a shear formed along a bedding plane
JN	Joint - a single fracture across which rock has little or no tensile strength and is not obviously related to rock fabric.
CN	Contact - surface between two lithologies.
SC	Schistosity - plane formed by the preferred orientation of the constituent minerals in a parallel arrangement in a coarse grained rock which has undergone regional metamorphism (schist).
CV	Cleavage - plane of mechanical fracture in a rock normally sufficiently closely spaced to form parallel-sided slices.
FO	Foliation
CZ	Crushed Zone - zone with roughly parallel, planar boundaries (commonly slickensided) containing disoriented usually angular rock fragments of variable size often in a soil matrix.
VN	Vein - fracture in which a tabular or sheet-like body of minerals have been intruded.
DK	Dyke - Igneous intrusion - often weathered and altered to a clay like substance.
DZ	Decomposed Zone - zone of any shape but commonly with parallel planar boundaries containing moderately to gradational boundaries into fresher rock.
FZ	Fractured Zone - a zone of closely spaced defects (mainly joints, bedding, cleavage and/or schistosity) comprised of core lengths in the order of 50 mm or less.

### Standard Defect Symbols

	Fault
	Shear
	Shear Zone
	Joint
	Bedding
	Bedding Shear
	Contact
	Crush Zone
	Cleavage
	Schistosity
	Dyke

### Roughness Colour Code (for summary log)

	Ro1
	Ro2
	Ro3
	Ro4
	Ro4