Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
2. Precinct Planning Outcomes			
2.1 Mamre Road Precinct Structure Plan			
 All development applications are to be generally in accordance with the Precinc Structure Plan (Figure 2), the water cycle management and local road network strategy for the Precinct. When assessing development applications, the consent authority will consider the extent to which the proposed development is consistent with the Structure Plan including cumulative and precedent implications for the planned infrastructure, and services and amenities provision. Any proposed variations to the general arrangement of the Structure Plan, must be demonstrated by the applicant, to the consent authority's satisfaction, to be consisten with the Precinct Vision. 		The proposal will be generally in accordance with the Precinct Structure Plan, water cycle management and local road network strategy. Any variation to the general arrangement of the Structure Plan will be consistent with the Precinct Vision.	
2.2 Biodiversity			
2.2.2 Biodiversity Certification			
1) Development is to be sited, designed and managed to avoid or mitigate potential adverse impacts on natural areas and habitat.	YES	The proposal will be sited, designed and managed to avoid or mitigate potential adverse impacts on natural areas and habitat.	
Development located on land that has the potential to impact biodiversity prior to the approval of the CPCP is to be accompanied by a Biodiversity Development Assessmen Report.		The Site is not identified to contain areas of high value biodiversity or riparian corridor under the Draft DCP, there are pockets of land zoned RE1 Public Recreation adjoining the Site; however, the Proposed Development will not impact upon these areas, for which the proposed landscaped design will compliment. The Site is also not identified to comprise biodiversity values under the <i>Biodiversity Conservation Act 2016</i> (BC Act).	
		Therefore, the proposal is not considered to adversely impact on biodiversity and thus a	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
De	velopment Control	Compliance	Planning Assessment
			BDAR is not required, by which a BDAR waiver has been requested as a result of the Proposed Development.
3)	Where development is proposed to impact on an area of native vegetation, it will be demonstrated that no reasonable alternative is available. Suitable ameliorative measures will also be proposed (e.g. weed management, rehabilitation, nest boxes).	YES	Suitable management and mitigation measures will be implemented as part of the Proposed Development to minimise any potential impacts on the native vegetation, which were previously assessed and approved under SSD 9522.
4)	A Weed Eradication and Management Plan outlining weed control measures during and after construction is to be submitted with the development application.	YES	A Weed Eradication and Management Plan was implemented under SSD 9522.
2.2	2.3 Biodiversity Conservation and Management		
1)	Minimise clearing of native vegetation within land zoned E2 Environmental Conservation and RE1 Public Recreation and riparian corridors. These areas are identified in Figure 3. Note: Clause 33K of WSEA SEPP also applies.	N/A	The proposal does not comprise land zoned E2 Environmental Conservation.
2)	No clearing of native vegetation shall occur within the Precinct without consent.	NOTED	Noted.
3)	A Vegetation Management Plan (VMP) for the rehabilitation and conservation of native vegetation and habitat is to be prepared for land located within E2 Environmental Conservation, RE1 Public Recreation or a riparian corridor.	N/A	The Site does not comprise land located within the E2 zone, RE1 zone or a riparian corridor. Hence a VMP is not required.
4)	Asset Protection Zones (APZs) for bushfire protection purposes are to be located wholly within land zoned for IN1 General Industrial.	YES	The proposed APZs will be located within the IN1 General Industrial zoned land as identified within the Bushfire Assessment Report.
5)	Stormwater and road infrastructure, including pipelines and detention basins, are not to be located within land zoned E2 Environmental Conservation.	YES	No stormwater and road infrastructure will be located within the E2 zoned land.
6)	Provide a green vegetated landscape setback or public road to all land zoned E2 Environmental Conservation, RE1 Public Recreation, RE2 Private Recreation in accordance with Section 4.2.3. The landscape buffer should generally be vegetated with endemic tree species and shrubs.	N/A	The Site does not adjoin E2, RE1 or RE2 zoned land.
7)	The following infrastructure will be considered within the landscape buffer, providing impacts on the Environmental Conservation and Recreation zoned lands can be minimised: Pedestrian and shared pathways. Street furniture.	N/A	The Proposal does not affect Environmental Conservation and Recreation zoned land.



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 Stormwater and drainage infrastructure (refer to section 2.6.1). 			
8) In general, development should address lands zoned Environmental Conservation and Recreation zoned lands, and the associated buffer area to ensure the lands are managed appropriately, to provide amenity for workers and visitors, and passive surveillance. Ideally, a subdivisional road would be located between the buffer and development.	N/A	The Proposal does not affect Environmental Conservation and Recreation zoned land.	
9) Where a vegetated landscape setback is provided to Environmental Conservation and Recreational lands and retained in private ownership, the consent authority may consider increased site coverage to offset the cost of delivering and managing the setback. This is to be considered on a case by case basis.	N/A	The Proposal does not affect Environmental Conservation and Recreation zoned land.	
10) A Threatened Species Assessment is to be undertaken for sites within 500m of an E2 Environmental Conservation zone to determine the presence of threatened species or their habitat. Building setbacks for particular threatened species, if present, are required in accordance with Table 3.	YES	The Site is located within 500m of E2 Environmental Conservation zoned land. Notwithstanding, a BDAR was undertaken for SSD 9522 which ameliorated any further consideration with respect to native vegetation across the Site.	
11) Development applications are to contain a Landscape Plan showing the location, extent and area of any existing native vegetation on the development site in accordance with Section 4.2.3.	YES	A set of Landscape Plans have been procured by Habit8 which outline the proposed landscaping strategy for the Site (refer to Appendix 7).	
12) A Flora and Fauna Assessment is to be submitted with all subdivision development applications.	YES	A BDAR was undertaken for SSD 9522 which ameliorated any further consideration with respect to native vegetation across the Site.	
13) Avoid impacts to habitat features which provide essential habitat for threatened species and other fauna including large trees including dead trees at (>50cm diameter at breast height) and avoid impacts to soil within the dripline of the retained trees.	YES	Appropriate mitigation and management measures will be implemented to minimise impacts to habitat features.	
 14) Mitigation to be undertaken in accordance with the following best practice guidelines for threatened ecological communities: Best Practice Guidelines: Cooks River/Castlereagh Ironbark Forest (NSW DECC, 2008) within and adjacent to the TEC. Recovering Bushland on the Cumberland Plain: Best Practice Guidelines for the Management and Restoration of Bushland (NSW DECC, 2005). 	YES	Mitigation will be undertaken in accordance with the relevant guidelines for threatened ecological communities.	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 15) Where practical, prior to development commencing, applicants are to: Provide for the appropriate re-use of native plants (including but not limited to seed collection) and re-use of topsoil that contains known or potential native seed bank. Relocate native animals from development sites. Applicants should refer to the former Office of Environment and Heritage's Policy on the Translocation of Threatened Fauna in NSW. 	YES	The re-use of native plants and topsoil and relocation of native animals will be considered where deemed appropriate/required.	
16) Weeds of National Significance (WONS) and on the National Environmental Alert List under the National Weeds Strategy are to be managed and eradicated. Proponent to reference NSW Weed Wise for current weed identification and management approaches.	YES	The proposed weed management will be undertaken in accordance with the DCP.	
17) All subdivision design and bulk earthworks are to consider the need to minimise weed dispersion and promote weed eradication. A Weed Eradication and Management Plan, outlining weed control measures during and after construction, is to be submitted with any subdivision development application.	YES	A Weed Eradication and Management Plan will be implemented as per the approved Plan under SSD 9522.	
18) Pest control techniques implemented during and post construction are to be in accordance with regulatory requirements for chemical use and address the relevant pest control strategy and are to reduce the risk of secondary poisoning (e.g. from Pindone or second-generation rodenticides).	YES	Pest control will be undertaken in accordance with the relevant regulatory requirements.	
19) Vegetation to which Part 3 of <i>State Environmental Planning Policy (Vegetation in Non-Rural Areas) 2017</i> applies is the same vegetation that must not be ringbarked, cut down, lopped, topped, removed, injured, wilfully destroyed or cleared without a development consent or permit granted by Council.	NOTED	Noted.	
20) High intensity lighting is to be designed to avoid light spill into adjoining natural areas. Australian Standard AS 4282 or updates to that standard are to be considered as a minimum.	YES	The proposed lighting will be designed to avoid light spill.	
21) Where a development footprint contains or is within 100 m of known microbat colonies or habitat likely to support microbat colonies, street lighting must not attract insects such as warm coloured LED light.	YES	Appropriate lighting will be used for the Proposal in accordance with the relevant Australian Standards and DCP requirements.	
22) Where noise or lighting adjacent to land zoned E2 Environmental Conservation is likely to impact wildlife, the proponent must manage light spill, and timing of noise producing activities, including installing appropriate noise treatment barriers along major roads and other attenuation measures.	N/A	The Site is not located adjacent to E2 zoned land.	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
23) Ensure that appropriate mitigation strategies (including fauna-sensitive road design elements) are employed to minimise vehicle strike during and after road construction and upgrading.	YES	Appropriate mitigation strategies will be implemented for the proposed internal site road / access works.	
 24) Traffic calming measures are required in all development areas not subject to wildlife (including koala) exclusion fencing, for example: Local roads with speed limit restrictions for areas adjacent to Environmental Conservation and Recreation zoned lands. Roads adjacent to wildlife habitat areas will be signposted in accordance with Austroads, RMS technical guidelines, Council Guidelines and relevant Australian Standards. Traffic calming devices such as speed humps and audible surfacing to be installed along perimeter roads adjacent to Environmental Conservation and Recreation zoned lands. Fauna-friendly road design structures such as underpasses, fauna bridges and overpasses should be installed and maintained by the proponent for a time period consistent with any approval conditions. Reference to the RMS Biodiversity Guidelines is to be made. 	YES	Appropriate traffic calming measures will be provided.	
 25) Ensure movement of fauna is facilitated within and through wildlife corridors by: Ensuring that activities do not create barriers to the movement of fauna along and within wildlife corridors. Separating fauna from potential construction hazards through the pre-construction and construction process. 	YES	The Proposal will not interfere with the movement of fauna.	
26) Adopt and implement open structure design for roads adjacent to known populations of Cumberland Plain Land Snail in accordance with actions under the Save our Species Program (EES, 2020).	YES	Where (and if) the Cumberland Plain Land Snails are identified within the Site, an appropriate design for roads will be implemented.	
2.3 Non-indigenous Heritage			
 1) A Heritage Impact Statement shall be lodged with a development application for subdivision, buildings or works in the vicinity of heritage items identified in Figure 4, including development that: May have an impact on the setting of a heritage item, for example, by affecting a significant view to or from the item or by overshadowing; or May undermine or otherwise cause physical damage to a heritage item; or Will otherwise have any adverse impact on the heritage significance of a heritage item within which it is situated. 	N/A	There are no Heritage items in close proximity to the Subject Site. Notwithstanding, a Statement of Heritage Impact has been prepared by Artefact and is located within Appendix 15 .	



Dr	Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
De	Development Control		Planning Assessment	
	Proposals for subdivision should define an appropriate setting or curtilage for the heritage building as part of the Heritage Impact Statement or Conservation Management Plan. In determining the curtilage of a heritage building, consideration is to be given to the following: The original form and function of the heritage building: The type of structure that constitutes the heritage building should be reflected in the curtilage. For example, it may be appropriate that a larger curtilage be maintained around a former rural homestead than that of a suburban building; Outbuildings: A heritage building and its associated outbuildings should be retained on the same allotment; and Gardens, trees, fencing, gates and archaeological sites: Features that are considered valuable in interpreting the history and in maintaining the setting of a building should be identified and, where possible, retained within the curtilage.	N/A	There are no Heritage items in close proximity to the Subject Site. Notwithstanding, a Statement of Heritage Impact has been prepared by Artefact and is located within Appendix 15 .	
4)	 New development shall be of a scale and form that does not detract from the historical significance, appearance and setting of the heritage item. In this way, the following elements require specific consideration: The height of new development near heritage items shall be less than the subject item. Increases in height shall be proportional to increased distance from the items and will be considered on merit; Views and vistas to the heritage item from roads and other prominent areas are key elements in the landscape and shall be retained; If the development site can be viewed from a heritage item(s), any new development will need to be designed and sited so that it is not obtrusive when it is viewed from the heritage item(s); and Curtilages shall be retained around all listed items sufficient to ensure that views to them and their relationship with adjacent settings are maintained. 	N/A	As above.	
5)	In order to preserve and maintain an appropriate scale and the visual prominence of a heritage item, the building height of new development shall generally not exceed that of the original heritage item. New development or large additions or alterations must provide a transition in height from the heritage item.	N/A	As above.	
6)	Development proposals, which involve largescale redevelopment and alteration to the original character of the heritage item and will negatively impact on the heritage significance of the curtilage, will not be permitted.	N/A	As above.	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Compliance	Planning Assessment		
N/A	As above.		
YES	The Site is not identified to be located within or in proximity to areas of high and moderate Aboriginal archaeological potential. Where areas of Aboriginal heritage value are located within or adjoining the Site, a detailed Aboriginal Cultural Heritage Assessment Report was undertaken for SSD 9522, for which an addendum was prepared for the Proposed Development.		
	N/A N/A N/A YES		



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
De	velopment Control	Compliance	Planning Assessment	
4) 5)	findings of the due diligence should guide future assessment and approval requirements for the activity (if any). Developments or other activities that will impact on Aboriginal heritage may require consent from the Heritage NSW, DCP under the National Parks and Wildlife Act 1974 (NPW Act) and consultation with the relevant Aboriginal communities. Any development application that is within or adjacent to land that contains a known Aboriginal cultural heritage site, as indicated on Figure 5, must consider and comply with the requirements of the NPW Act. An Aboriginal Heritage Impact Permit (AHIP) issued under Part 6 of the NPW Act is required for any works which directly affect these sites. Where the necessary consents have already been obtained from Heritage NSW, the development application must demonstrate that the development will be undertaken			
	in accordance with any requirements of that consent.			
2.!	5 Riparian Land			
1)	 Within a riparian corridor, as indicatively identified in Figure 2 and Figure 3: All existing native vegetation is to be retained and rehabilitated, except where clearing is required for essential infrastructure such as roads. Native vegetation is to be conserved and managed in accordance with the controls below. 	N/A	The Site is not located within a riparian corridor.	
	There should be no modifications to a natural (or historic) waterbody in its dimensions, depth or bank height unless the approval of Natural Resources and Assessment Regulator is obtained, including the enhancement of the ecological outcomes of the watercourse, hydrological benefits and ensure the long-term geomorphic stability of the watercourse. Watercourses should not be modified to maximise flood conveyance unless there are no other means to avoid damage to existing dwellings or infrastructure that cannot be	N/A	No modifications to a waterbody are proposed.	
	relocated.			
2.0	2.6 Integrated Water Cycle Management			
2.0	5.1 Stormwater Management			
1)	Development must demonstrate how the proposed site design and water sensitive urban design measures contribute to the interim NSW Government stormwater catchment flow objectives for Wianamatta-South Creek Catchment. The combined effect of site design and site water sensitive urban design measures (including on-lot,	YES	An Estate-wide stormwater management cycle was prepared under SSD 9522, for which the Proposed Development would seek to maintain and adhere to the water quality and quantity targets established across the Site. A Civil	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control		Compliance	Planning Assessment
2)	on street and end of pipe measures) shall contribute no more than 1.9 ML/ha/year in mean annual runoff at any discharge point. Any stormwater harvesting approaches will need to be consistent with a regional wastewater approach and the precinct water balance. All stormwater treatment measures need to be designed with consideration for ongoing operation and maintenance.		Engineering Report has been prepared for the Proposal which confirms and validates this further, for which pre-and post-development flows will not be impacted as a result of the Proposed Development (refer to Appendix 9).
4)	A Maintenance Plan for stormwater treatment measures is to be submitted with all development applications for approval.	YES	As above.
5)	All proposed industrial buildings are required to install a rainwater tank on the site for re-use of water in irrigation, industrial processes, toilet flushing, evaporative cooling or for other non-drinking purposes through a separate reticulated water supply system. The size of the tank should be determined in the calculation of required stormwater runoff volume reductions to meet NSW Government interim flow objectives for the Wianamatta-South Creek Catchment.	YES	Rainwater tanks would be installed as a result of the Proposed Development.
6)	Industrial developments must supply at least 80% of their non-potable demand using nonpotable sources including rainwater and recycled water.	YES	Rainwater tanks would be installed as a result of the Proposed Development.
7)	Applicants should target 35% pervious surfaces within lots and streets to ensure adequate management of stormwater runoff and contribute to mean annual runoff volume and water quality targets. Perviousness is to be calculated in accordance with the following index: Deep soil (one metre or more in depth, connected subsoil) – 100% Shallow soil (less than one metre in depth, not connected to subsoil) – 75% Permeable pavement – 50% Hardstand – 0%	YES	The Proposed Development would achieve the adjoining controls.
8)	Water sensitive urban design measures to retain stormwater within the development footprint are outlined in the Integrated Water Cycle Management controls outlined in this DCP. An example of stormwater retention measures applied to an industrial development is shown in the Table 5.	YES	An Estate-wide stormwater management cycle was prepared under SSD 9522, for which the Proposed Development would seek to maintain and adhere to the water quality and quantity targets established across the Site. A Civil Engineering Report has been prepared for the Proposal which confirms and validates this further, for which pre-and post-development flows will not be impacted as a result of the Proposed Development (refer to Appendix 9).



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
9) The consent authority may consider stormwater management targets being satisfied on a developer estate level.	YES	As above.	
10) Major trunk drainage elements proposed are shown in Figure 6. Additional drainage infrastructure will be required to be provided upstream of these identified elements in conjunction with development of sites to achieve the desired stormwater management objectives. Whole of life costs and ease of maintenance will be critical considerations in determining the form of the final drainage option.	YES	As above.	
11) Development consent must not be granted on land which is to be serviced by this infrastructure until such time as it has been delivered to the satisfaction of the trunk drainage manager (Council or other).	YES	As above.	
12) Existing flows entering the catchment are to be accommodated within the stormwater drainage infrastructure elements provided within development in the precinct.	YES	As above.	
13) The additional drainage infrastructure is to be constructed by the developer of the land concerned.	YES	As above.	
14) All land identified by Council as performing a significant drainage function and where not specifically identified in the Contributions Plan, is to be covered by an appropriate "restriction to user" as deemed application by Council, and created free of cost to Council.	YES	As above.	
15) Trunk drainage infrastructure is to be retained in private ownership, unless otherwise agreed by Council.	YES	As above.	
2.6.2 Stormwater Quality			
1) All development proposals must include a Water Management Strategy. The Water Management Strategy must include a Water Sensitive Urban Design strategy detailing the proposed stormwater flow and quality control measures and how these measures will be implemented as part of the development including ongoing management and maintenance responsibilities. The Strategy should include details of modelling (eg. eWater MUSIC) to reflect how the mean annual runoff targets are met.	YES	An Estate-wide stormwater management cycle was prepared under SSD 9522, for which the Proposed Development would seek to maintain and adhere to the water quality and quantity targets established across the Site. A Civil Engineering Report has been prepared for the Proposal which confirms and validates this further, for which pre-and post-development flows will not be impacted as a result of the Proposed Development (refer to Appendix 9).	



Compliance YES	Planning Assessment
YES	
	As above.
	As above.
YES	As above.
	YES



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
Development Control	Compliance	Planning Assessment		
 Where relevant, a comprehensive Flood Impact Risk Assessment (FIRA) is to be submitted with any development application on land identified as fully or partially flood affected. The FIRA should utilise Council's existing data and is to provide an understanding of existing flooding condition and developed conditions consistent with the requirements of the NSW Flood Prone Land Policy and Floodplain Development Manual. The FIRA shall determine: A detailed flood behaviour for existing and developed scenarios for the full range of flooding including the 5% AEP, 1% AEP, 0.5% AEP, 0.2% AEP and the PMF. Flood Function (floodways and flood storage areas); Flood Hazard; and Flood constraints including evacuation constraints (if applicable). The levels on the survey are required to be verified during construction by a survey certificate. The study shall incorporate: A survey of the main watercourse; A survey of the site; and A detailed flood and drainage investigation which establishes the estimated 20% AEP, 1% AEP (100 year ARI) 0.2% AEP and Probable Maximum Flood levels including overland flow paths. The applicant shall demonstrate to the satisfaction of the consent authority (on the basis of a qualified consultant report) that: The development will not increase the flood hazard, flood levels or risk to other properties; The development is to be located within the PMF, a flood evacuation plan will be required; The structure of the proposed building works shall be adequate to deal with the flood behaviour for a full range of floods identified in control 1; The proposed building materials are flood compatible with a full range of floods identified in control 2.7(1); The buildings and the	YES	A Civil Engineering Report has been prepared for the Proposal which confirms and validates this further, for which pre-and post-development flows will not be impacted as a result of the Proposed Development (refer to Appendix 9).		
 identified in control 2.7(1); The buildings and their access are sited in the optimum position to avoid flood waters and allow optimal vehicular flood access from the site for evacuation; 				



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
Development Control	Compliance	Planning Assessment		
 Compliance of any existing buildings with the Standard - Construction of Buildings in Flood Hazard Area and the accompanying handbook developed by the Australian Building Codes Board (2012); The proposed development will limit impact on riparian corridors and be designed and maintained to allow for natural stream processes; and Fencing does not impede the flow of flood waters/overland flow paths. Council will consider development on land subject to the full range of flooding based on understanding of flooding in accordance with the NSW Flood Prone Land Policy and the principles of the Floodplain Development Manual. New development in floodways and flood storages or in high hazard areas in the 1% AEP flood event considering climate change should be avoided. Consideration will be given to such matters as depth and nature of flood waters, whether the area forms flood storage, the nature and risk posed to the development by flood waters, the velocity of floodwaters and the speed of inundation, and whether the development lies in an area classed as a 'floodway', 'flood fringe area' or 'flood storage area'. Floor levels shall be at least 0.5m above the 1% AEP (100 year ARI) flood. Flood safe access and emergency egress shall be provided to all new and modified developments. Where the application is for an extension to an existing building on land at or below the flood planning level or for new development that can be classed as infill development, Council may approve of the development with floor levels below the 1% AEP (100 yearARI) flood if it can be demonstrated by the applicant that all practical measures will be taken to prevent or minimise the impact of flooding. In considering such applications and determining the required floor level, Council shall take into account such matters as: 	Compliance	Planning Assessment		
 The nature of the business to be carried out; The frequency and depth of flooding; The potential for personal and property loss; 				
 The utility of the building for its proposed use; 				
 Whether the filling of the site or raising of the floor levels would render the development of the property unworkable or uneconomical; 				
 Whether the raising of the floor levels would be out of character with adjacent buildings; and Any risk of pollution of water from storage or use of chemicals within the building. 				



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
Development Control	Compliance	Planning Assessment		
9) Any portion of the proposed building extension subject to inundation shall be built from				
flood compatible materials.				
10) Generally, subdivision of land below the flood planning level will not be supported.				
Further provisions relating to the proposed subdivision of such land can be found in the Subdivision Section of this Plan.				
11) Subdivisions must comply with 'Designing safer subdivisions guidance on subdivision				
design in flood prone areas, 2007' Hawkesbury-Nepean Floodplain Management				
Steering Committee'.				
12) All potential pollutants that are stored or detained on-site (such as on-site effluent				
treatment plants, pollutant stores or on-site water treatment facilities) should be stored				
above the 1% AEP (100 year ARI) flood. Details must be provided as part of any				
development application.				
13) Consideration must be given to the impact on any overland flow path. Generally,				
Council will not support development obstructing overland flow paths. Development is				
required to demonstrate that any overland flow is maintained for the 1% AEP (100				
year ARI) overland flow with consideration for failsafe of flows up to the Probable Maximum Flood (PMF). A merit based approach will be taken when assessing				
development applications that affect the overland flow.				
14) Council's Stormwater Drainage Specification for Building Developments provides				
information on the details required in the preparation of an overland flow study.				
15) Where existing natural streams do not exist, naturalised drainage channels are				
encouraged to ensure overland flows are safely conveyed via vegetated trunk drainage				
channels systems with 1% Annual Exceedance Probability capacity plus 0.5m				
freeboard. Constructed trunk drainage systems potentially increase peak flows by				
removing flood storage and increase conveyance. Any increase in peak flow must be				
offset using on-site stormwater detention (OSD) basins.				
16) All required flood detention is to be accommodated, on-lot, within the development site.				
17) OSD must be sized to ensure no increase in 50% and 1% Annual Exceedance				
Probability peak storm flows at the Precinct boundary or at Mamre Road culverts. An				
allowance shall be made for any local roads that bypass OSD or any vegetated trunk				
drainage systems that increase peak flows through the precinct.				
18) Earthworks up to the PMF must meet the requirements of Clauses 33H and 33J of the				
WSEA SEPP as well as Sections 2.7 and 4.4 of this DCP.				



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
Development Control	Compliance	Planning Assessment		
 19) Development consent will not grant consent to filling of floodways and /or critical flood storage areas in the 1% AEP flood. The filling of other land at or below the 1% AEP but outside the floodways and critical flood storage will generally not be supported. In particular, an application to fill land shall also describe the purpose for which the filling is to be undertaken. Council may consider such an application when the following criteria are met: Flood levels are not increased by more than 10mm by the proposed filling on surrounding properties; Downstream velocities are not increased by more than 10% by the proposed filling; Proposed filling does not redistribute flows by more than 15%; The potential for cumulative effects of possible filling proposals in that area is minimal; There are alternative opportunities for flood storage; The development potential of surrounding properties is not adversely affected by the filling proposal; The flood liability of buildings on surrounding properties is not increased; No local drainage flow/runoff problems are created by the filling; and The filling does not occur within the drip line of existing trees. 20) The above criteria can only be addressed and satisfied by the submission of a detailed flood study report by a qualified engineer. The flood study report would involve both hydrologic and hydraulic analysis of the watercourse and the effects of the proposed filling on flood levels, flow velocities and distribution of flows as listed above. The report needs to address items listed above. Any filling of land also needs to be in accordance with the other provisions in this DCP. 				
2.8 Bush Fire Prone Land				
 Land identified as 'bushfire prone land' on the Penrith City Council Bushfire Prone Land Map is to address the bush fire protection measures in the Rural Fire Service publication Planning for Bushfire Protection 2019 (PBP) (as amended). A Bushfire Assessment Report, prepared in accordance with PBP, must accompany all development applications on land identified as bush fire prone land on the Bushfire Prone Land Map. 		The Site is identified as Bushfire Prone Land – Vegetation Category 2. A Bushfire Assessment Report has been prepared in accordance with PBP (refer to Appendix 20).		
3) Development on land within 250m of land zoned RU2, E2, and E4 that is not identified as 'bushfire prone land' on the Bushfire Prone Land Map must consider ways to		The entire Site is identified as bushfire prone land. Mitigation and protection measures would		



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment					
Development Control	Compliance	Planning Assessment			
minimise the risk of ember attack, particularly with regard to roof design, building materials and landscape design. These matters must be addressed in the Statement of Environmental Effects.		be implemented accordingly that are consistent with the PBP.			
4) Bushfire hazard reduction work must be authorised by the Rural Fires Act 1997.	NOTED	Noted.			
2.9 Salinity					
1) A detailed salinity analysis and Salinity Management Plan will be necessary if an initial investigation shows the site is saline or affected by salinity.		The geotechnical profile of the Subject Site provides an unconstrained platform for development.			
2.10 Contaminated Land					
 Prior to granting development consent, the consent authority must be satisfied that the site is suitable, or can be made suitable, for the proposed use having regard to land contamination. All DAs shall be accompanied by a Stage 1 Preliminary Site Investigation prepared in accordance with State Environmental Planning Policy No 55 – Remediation of Land and the Contaminated Land Management Act 1995. Where the site has known contamination, or a Stage 1 Preliminary Site Investigation identifies potential or actual site contamination a Stage 2 Detailed Site Investigation must be prepared in accordance with State Environmental Planning Policy No 55 – Remediation of Land and the Contaminated Land Management Act 1995. A Remediation Action Plan (RAP) will be required for areas identified as contaminated land in the Stage 2 Detailed Site Investigation. A Site Audit Statement (SAS) (issued by an Accredited Site Auditor) will be required where remediation works have been undertaken to confirm that a site is suitable for the proposed use. 	YES	A Stage 2 Detailed Site Investigation was undertaken as part of SSD 9522. Notwithstanding, further environmental investigations were undertaken as part of the subject Proposal and are located within Appendix 10 .			
2.11 Aviation Safeguarding					
 An Aviation Safeguarding Assessment is to be submitted detailing compliance with aviation safeguarding measures and the controls outlined below. The height of buildings, structures, landscaping and cranes do not impact on the operations of the Airport or create a hazard to the safe navigation of aircraft. Buildings and any ancillary structures must not encroach into protected airspace. Development is constructed in accordance with Australian Standards AS2021 – Acoustics Noise Intrusion – Building Siting and Construction. 	YES	An Aviation Safeguarding Assessment has been prepared for the Proposed Development and is located within Appendix 24 .			



Dra	Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
De	velopment Control	Compliance	Planning Assessment		
4) 5) 6) 7) 8) 9) 10) 11) 12) 13) 14)	Renovations to existing houses or minor extensions within ANEC/ANEF 20 and above must be constructed in accordance with Australian Standard AS2021 – Acoustics – Aircraft Noise Intrusion – Building Siting and Construction. Development does not create a permanent or temporary physical or transient obstruction in the operational airspace of the Airport and complies with the Airports Act 1996 and Airports (Protection of Airspace) Regulations 1996. Development does not impact on the operational aspects of the Airport with regard to light emission and reflective surfaces. External lighting must be downlights or shrouded lights. Development must not generate emissions into the protected airspace. Any plumes do not: Have peak vertical velocities of more than 4.3m/sec. Incorporate flares. Development must not attract wildlife which would create a safety hazard in the operations of the Airport. All waste bins are to be designed and installed with fixed lids. Any bulk waste receptacle or communal waste storage area must be contained within enclosures that cannot be accessed by birds or flying foxes. Any stormwater detention within the 8km wildlife buffer is to be designed to fully drain within 48 hours after a rainfall event. Development must not impact upon communication, navigation and surveillance systems. Development within the building restricted area does not create electromagnetic field radiations that will interfere with signals transmitted by the communication, navigation or surveillance facility.				
	Development must not generate windshear and/or turbulence. L4 Utilities Services				
1)	The developer shall liaise with relevant service providers to ensure adequate arrangements have been made to service the development. This includes water and sewer, electricity, gas (where required) and telecommunications. The developer shall submit sufficient evidence at subdivision state to demonstrate the satisfactory arrangements have been made to ensure the delivery and construction utilities and services connections. All utilities are to be accommodated in the road reserve. The design of roads will need to take this into consideration.	YES	Adequate utilities services will be provided as part of the Proposal.		



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
Development Control	Compliance	Planning Assessment		
 4) Utilities services are to be provided in accordance with the relevant service providers requirements. 5) Development consents will include a condition requiring the applicant to provide evidence that satisfactory arrangements to Sydney Water have been made for water supply and sewer services to the development. Indicative trunk infrastructure is identified in Figure 9. 6) Applicants will be required to deliver water and sewer services upgrades (in accordance with current Sydney Water procurement guidelines) required to meet the anticipated demands for future industrial users. 				
2.15 Transport Investigation Areas				
 This section applies to the Mamre Road corridor and land identified as Transport Investigation Area marked "B" under Clause 33B of State Environmental Planning Policy (Western Sydney Employment Area) 2009. 12) Proposed development on land subject to Mamre Road and the proposed Southern Link Road (refer Figure 9) must make provision for the upgrade and construction of these roads and future access to the corridors. 13) Applicants must consult with TfNSW in preparing development applications for this land to ensure an appropriate area of land is available and future access is not adversely impacted by development. 	YES	SSD 9522 considered traffic impacts for the entire Estate. Furthermore, the Traffic Impact Assessment prepared by ARUP considers traffic and parking impacts in relation to the subject Proposal (refer to Appendix 11).		
3. Precinct and Subdivision Design				
3.1 Subdivision				
 Lots fronting biodiversity areas and corridors are required to have on-site drainage controls that prevent nutrient and erosion impacts on bushland. Lot design should maximise the conservation of natural features, including important fauna habitats, rare or threatened plant habitats, and designated biodiversity areas. Lots adjoining or containing watercourses are required to maintain or establish native vegetation riparian corridors. Perimeter roads should be provided for bushfire control and to improve outlook and amenity, but this should be balanced with the need to minimise impacts on vegetation. Variations to subdivision controls will be considered for lots created for "utility installations" or "utility undertakings" (e.g. electricity substation). Land zoned E2 Environmental Conservation must not be subdivided unless the consent authority is satisfied appropriate arrangements have been made for revegetation and 	N/A	SSD 9522 considered subdivision across the Site.		



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment						
Dev	elopment Contr	ol			Compliance	Planning Assessment
7)	arrangements for	ne land in accordance wi ongoing monitoring and ontrols are outlined in Ta		lan, including		
	Subdivision element	Area	Control			
	Minimum Allotment Size	IN1 General Industrial	1,000m²			
		E2 Environmental Conservation	Single contiguous lot			
	Minimum Frontage	IN1 General Industrial	40m (excluding cul-de-sacs) and 35m minimum lot width at building line (for lots >5,000m²) 60m (for lot >10,000m²)			
8)		e development of the int	d integrated freight network she rermodal terminal and co-locate			
3.2	Views and Visua	al Impacts				
2)	view corridors ide how the natural fe Subdivision and bu buildings and cons	ntified in Figure 10. De eatures of the site have uilding design should rel sider the use of height to	ate to the scale of adjoining ruransitions and building setback	demonstrate ral residential s.	YES	The Site is identified to comprise precinct ridgelines/high points and is within a view corridor as identified in the Landscape features and visually sensitive locations map under the DCP.
,	impact of the indu Uses and building	strial use, particularly o elements that are likel	I vegetation screening to soft n adjoining rural residential use y to adversely impact the visu be sited as far as possible av	es. al amenity of		The proposed layout has been designed to respond to the landscape elements and view corridor relevant to the Site.
	sensitive interface and integrate suitable landscaped screening.					corridor relevant to the site.
5)	5) Site design should promote visual connections with waterways, conservation areas,				The proposed Data Centre is sufficiently	
7)			petween the development and we surveillance of the open spa			separated adequately from the surrounding rural-residential properties.
8)	Avoid barriers, suc space areas and ir	ndustrial uses.	, between environmental conso	•		The Proposal has been designed to respond to the landscape character and ridgelines of the Site.
)	landscape design.	iva,5 Siloulu be lillegi	atea as key reatures of the	ballaring and		



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
Development Control	Compliance	Planning Assessment		
10) Landscape design and plant selection should provide continuity with the existing natural vegetation.11) Lots adjoining Mamre Road should be designed in a manner that promote high quality landscape character, including vistas.12) In general, buildings should not be sited on ridgelines, with lower building heights around ridgelines.				
3.4.1 Road Network, Hierarchy and Design				
 The Mamre Road Precinct should be developed generally in accordance with the road network map identified in Figure 14. The external road network will generally comprise the arterial roads of Mamre Road and the future Southern Link Road (Movement Corridors), Aldington Road/ Abbots Road as a distributor road and indicative internal road network. The external road network Is carefully designed and planned to ensure that development of the precinct to projected capacity is supported. Internal local roads are to be designed to: create a permeable network that is based on a modified grid system; provide access to adjoining properties and not limit development on adjoining properties, including demonstration of impact on the development of adjoining lots; provide for pedestrian and cycle network and minimise travel distances and conflict with industrial traffic; maximise connectivity between industrial areas and community facilities, open space and employment hubs; take account of topography, view corridors and site drainage, and accommodate significant vegetation; provide frontage to and maximise surveillance of open space and riparian corridors; provide views and vistas to landscape features and visual connections to nodal points and centres; and maximise the effectiveness of water sensitive urban design measures. A public road adjoining open space should be developed generally in accordance with Figure 14. Access points shall be located so as to optimise safety, traffic flow and landscape opportunity. All parking shall be provided either on site or in centralised off-road locations. Upgrading of Mamre Road shall be undertaken to accommodate the increases in traffic 	YES	The Proposal is generally in accordance with the road network map. The Proposed Development would not impact the Estate access road layout as approved under SSD 9522.		
generated by this development.				



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment					
Development Control	Compliance	Planning Assessment			
6) No direct vehicle access to Mamre Road or Southern Link or distributer roads are permitted.					
7) All intersections within the internal road network shall incorporate traffic facilities, which promote safe and efficient pedestrian, cyclist and traffic movement.					
8) The internal road pattern is to facilitate 'through-roads' with cul-de-sac to be avoided unless dictated by topography or other constraints.					
9) Any additional connection(s) on Bakers Lane need to protect the amenity of existing developments (e.g. schools).					
10) The internal road network intersections to be provided at the following minimum intervals:					
 Local to local industrial street 40m-60m; Local to collector / distributor street 100-200m; and 					
Collector / distributor to sub-arterial 400m-500m.					
11) The proponent shall have regard to "Guide for Traffic Generating Development", Roads and Traffic Authority of NSW, October 2002.					
12) Development shall, where appropriate, be designed to:					
 Allow all vehicles to either leave or enter the site in a forward direction; Accommodate heavy vehicle parking and manoeuvring areas; 					
 Avoid conflict with staff, customer and visitor vehicular movements; and Ensure satisfactory and safe operation with the adjacent road system. 					
13) Full details of the volume, frequency and type of vehicle movements shall be submitted					
with the development application. 14) In general:					
 Turning circles will be required to be provided to accommodate the largest type of 					
truck which could reasonably be expected to service the site. • All developments must be designed and operated so that a standard truck may					
complete a 3-point or semi-circular turn on the site without interfering with parked					
vehicles, buildings, landscaping or outdoor storage and work areas; and					
 Large-scale developments shall be designed to accommodate 26m B-double (PBS Level 2 Type B). In the case of the conversion of an existing development, should 					
it appear that a truck turning circle may prove difficult; a practical demonstration					
may be required. 15) Council will assess the suitability of manoeuvring areas provided for large vehicles by					
reference to Australian Standard 2890 series and Performance Based Standards 'An					
Introduction for Road Managers (National Heavy Vehicle Regulator – May 2019).					



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
Development Control	Compliance	Planning Assessment		
 16) Adequate space is to be provided within the site for the loading, unloading and fuelling (if applicable) of vehicles. These areas shall be screened from the road. 17) Proposed industrial roads must comply with the road configurations in Table 9. 18) Main industrial roads to each have a width capable of providing either four travel lanes or two travel lanes and two parking lanes. 19) The internal road network needs to be designed for 26m long B-double (PBS Level 2 Type B) and tested for a 36m long B triple (PBS Level 3 Type A). 20) To accommodate the design vehicle (i.e. B-double and B-triple) the standard kerb return radius will need to increase from 12.5m to 15.0m. 21) To improve safety for cyclists, separate cycle paths within the verge to avoid locating a bike lane adjacent to lanes carrying large trucks. 22) The internal road network is to incorporate a footpath of 1.5m on one side (minimum) and shared path of 2.5m (minimum) on the opposing side of the road. 23) The consent authority may consider a reduced road configuration for local roads adjoining open space, subject to road function, public utilities, bollards and fencing. Consideration of reduced widths will solely be at the discretion of Council and only where the finished road design levels match with existing levels of open space and negate the need for any retaining wall or battering. Applications that proposed reduced widths will be assessed by Council with consideration given to: Public access to open space; Function of the road; Impact on existing vegetation; Public safety; and Impact on ability to provide street tree planting. 24) In special circumstances where it can be clearly demonstrated that the road configuration in Table 9 is not appropriate, then the following key principles must be 	Compliance	Planning Assessment		
 applied to any alternative proposal: Road and lane widths must allow for two-way movement and turning movements of design vehicles, including consideration for buses, heavy vehicles, garbage trucks and emergency vehicles; Verge widths must consider requirements for utilities, street tree planting, footpaths, shared paths and urban design outcomes; Adequate on-street parking must be provided; 				



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment					
Development Control	Compliance	Planning Assessment			
 Adequate turning paths must be provided for all design vehicles at intersections and for property access to meet the required design vehicle; Road widths must be set to minimise kerbside restrictions and regulatory signage; Sufficient width must be provided for specialist drainage functions; and Life cycle costs for construction and maintenance must be minimised. Industrial roads are to achieve the following performance objectives: Provide direct access to industrial properties and interconnectivity with the adjoining road network; Provide for all classes of heavy vehicles and appropriate circulation; Provide a shared path or on road cycle ways; and Provide lighting in accordance with relevant Australian Standards. Further controls may be applied as part of a development consent based on the individual circumstances of any proposed layout with reference to the adjoining road network. 					
3.4.2 Traffic and Transport Assessments, Studies and Plans					
 A Transport Management and Accessibility Plan (TMAP) is to be prepared for all significant developments. The TMAP is to address the objectives and controls in this section. Development applications for major development proposals should be accompanied by an appropriate Traffic and Transport Report. The Traffic and Transport Report should detail the assessed impact of projected pedestrian and vehicular traffic associated with the proposal, with recommendations on the extent and nature of the traffic facilities necessary to preserve or improve the safety and efficiency of the adjacent road system. A Traffic and Transport Report must be provided for applications required to be referred to the Roads and Maritime Services (RMS) under Column 2 and a Traffic Impact Statement for Column 3 of SEPP (Infrastructure) 2007. Depending on the scale, type and nature of the use proposed, Council may determine that a Traffic and Transport Report or Traffic Impact Statement is required for certain development which is not listed under Column 2 or 3 of SEPP (Infrastructure) 2007. Any Traffic Report or Traffic Impact Statement is required to address the following issues: The objectives of this section relating to transport and land use; 	YES	A Green Travel Plan accompanies the Traffic Impact Assessment prepared by ARUP which satisfactorily addresses traffic and parking related impacts as a result of the Proposal (refer to Appendix 11).			
 The objectives of this section relating to transport and land use; The objectives of this section relating to traffic management and safety; 					



Dr	Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
De	velopment Control	Compliance	Planning Assessment		
	 The objectives and controls of this section relating to traffic generating developments; and The objectives and controls in Section 4.7.1 				
3.4	 The objectives and controls in Section 4.7.1. 3 Western Sydney Intermodal Terminal and Freight Network 				
1)	Development within the Precinct shall not preclude the delivery of the Intermodal	YES	SSD 9522 appropriately considered the future		
1)	Terminal and integrated freight network.	125	Western Sydney Freight Line Corridor to the		
2)	Land identified for the intermodal facility is to be integrated with a dedicated road		north of the Subject Site. Further consideration		
'	freight network to the south, via a dedicated crossing of future Southern Link Road, as		is not considered to be required in this respect.		
	identified in Figure 16.				
3)	Development is to enable the future delivery of an integrated freight network by				
4.	preserving a dedicated freight corridor as shown in Figure 16.				
4)	The dedicated freight corridor is to have a minimum width of 10m and not prohibit the				
	construction of the freight road meeting the design standards as identified in Table 10				
5)	and Figure 15. Development applications for lots fronting Mamre Road shall make provision for the				
3)	dedicated freight corridor as identified in Figure 16.				
6)	All fire compliant access roads are to be a minimum of 8.0m wide to safeguard for a				
'	precinct-wide integrated freight network.				
7)	Development applications for lots with an identified access point (refer to Figure 16)				
	shall demonstrate how access to and from the dedicated freight corridor will be				
	achieved within the development site.				
8)	All fire compliant access roads are to be a minimum of 8.0m wide to safeguard for a				
	precinct-wide integrated freight network unless development applications can				
	demonstrate how an integrated freight network can be safeguarded within their				
9)	development. The dedicated freight network should be designed to accommodate current higher				
"	performance freight vehicles, in accordance with AS 2890.2:2018 Parking Facilities,				
	Part 2: 'Off-street commercial vehicle facilities'. The dedicated freight corridor is to be				
	designed to accommodate Performance Based Standards (PBS) Level 2B vehicles. The				
	design vehicle must also consider future implementation of autonomous vehicles with				
	the integrated freight network able to be easily adapted to accommodate these				
	vehicles.				
10	Minimum road widths, maximum grades and maximum rate of change of grade should				
	be designed to accommodate a 26m long B-double (PBS level 2 type B) and tested for				
	a 36m long B-triple (PBS Level 3 Type A) design vehicles with provision for future				



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
implementation of autonomous vehicles at a minimum 40 km/h operating speed (50 km/h design speed).			
3.4.4 Public Transport, Pedestrian and Cycle Network			
 3.4.4 Public Transport, Pedestrian and Cycle Network Bus stops should be provided. The final location of bus stops will be determined by bus operators and TfNSW in consultation with Council. Provision for a future bus link to the M4 Motorway. Pathways for cyclists and pedestrians are to be provided at a strategic level to include regional active transport connections, and links to key catchments and employment hubs across WSEA. The road network is to ensure public transport (i.e. buses) is made available along key roads to support early adoption of good travel practices by future workers. The design of the internal road network to identify the future public bus network and coverage. Any required infrastructure and bus services to be provided at the early stages of development (refer to TfNSW – Guidelines for Public transport Capable Infrastructure in Greenfield sites). Public transport use is to be enhanced by providing good pedestrian connections from places of employment to transport networks or nodes. Footpaths should have ramps at all kerb corners for wheelchairs and pram access and cater for all people with diverse abilities in line with current Australian Standards. Street lighting in accordance with the provisions of AS1158 should be present in all urban streets, while on rural traffic routes in general only intersections will be lit. Pedestrian crossing distances in local streets should be shortened through kerb extensions and tight turning radii, which can cause vehicular traffic to slow to negotiate the tighter corners. To enable comfortable passage for all people with diverse abilities, footpaths must be: Provided on both sides of the road; A minimum of 1.5m wide on one side; A minimum of 3.0m on approach routes to predictable destinations such as 	YES	The Proposal will be capable of accommodating the public transport infrastructure.	
 employment hubs and parks; and A minimum width of 3.5m for shared paths for recreational use within open space and environmental corridors. 			
11) A durable, non-slip surface and even paving is to be designed and constructed for minimum maintenance. Continuous pathways, uninterrupted by variations in surface material must be provided.			



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 Gradients from pathways to streets are to be minimal, safe and comfortable for people with limited mobility and those using wheelchairs, prams and trolleys in line with current Australian Standards. Gradients and ramps must be aligned with desired paths of travel for pedestrians and cyclists. A smooth transition from ramps to roads is to be provided for people using wheelchairs or prams. Ramps should be designed in accordance with appropriate design guidelines and be as wide as the pathway or marked crossing point to eliminate squeeze points at transition areas. Reconstructed driveways/pathways are to achieve a useable cross slope for a width of 915mm. Cars must slow to negotiate the two steeper ramps on either side of the pathway crossing, but will not 'bottom out' at these angles. (Source: Preiser. W and Ostroff E (2001) Universal Design Handbook McGraw-Hill). All cycle routes and facilities are to be consistent with the relevant requirements of "Austroads Cycling Aspects of Austroads Guides" and Roads and Maritime Services' "Bicycle Guidelines" including line-marking, signage and logos and Council policies regarding bicycle access. The minimum width of off-street shared cycle and pedestrian pathways is to be 2.5m. The minimum width of 3.5m for shared paths for recreational use within open space and environmental corridors. Pedestrian and cycle routes and facilities in public spaces are to encourage way finding and be convenient, safe, well lit, clearly defined, functional and accessible to all. Shared paths and pedestrian refuge islands are to be designed to be fully accessible by all in terms of access points and gradients, in accordance with Australian Standard 1428:1-4. 			
4. General Requirements for Industrial Development			
4.2.1 Building Height			
 Building height should respond to the natural landscape and scale of existing adjoining development, incorporating lower elements towards the street, pedestrian paths, adjoining rural-residential areas and areas of environmental value, such as riparian corridors and ridgelines. Buildings should not exceed a maximum height of 16m from the existing ground level within 250m of a rural-residential zone. For all other sites, a maximum building height of 20m from existing ground level is permitted. 	YES	The Site is subject to a maximum height limit of 20m under the DCP. Taller built forms are to demonstrate that solar and visual impacts can be mitigated. A Visual Impact Assessment has been prepared as part of the Proposed Development by	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 Should the nature of the business require a taller built form (above 20m), the proponent must demonstrate that the taller element will mitigate solar and visual impacts to the surrounding uses and public amenity. The development application must be accompanied by a visual impact assessment by a suitably qualified consultant. Taller building elements over 15m should be recessed from the street frontage. Building height must ensure direct solar access to public footpaths, open space an environmental areas, between the hours of 11:00am and 2:00pm at the winter solstice 21 June. Shadow diagrams must be submitted demonstrating this outcome. Building services located on the roof (such as HVAC, lift motor room, exhaust fans, etc must be accommodated within the maximum permissible height of the building. A Visual Impact Assessment to be submitted with development application demonstrating that development will not adversely affect the scenic quality of: The precinct, particularly when viewed from elevated locations. Wianamatta-South Creek. Adjoining rural-residential areas. Buildings should be sited on mid-slope to avoid visual impact on ridges and to be i harmony with the existing landscape. On sloping sites, the building or buildings should be designed, where possible, so as t "step" physically up or down the site to avoid visual impact on ridges. Buildings located within visually sensitive locations (e.g. around ridgelines) should us materials that minimise visual impacts and reflectivity, such as green roofs. Visuall sensitive areas are identified in Figure 8. 		Geoscapes which considers any potential impacts as a result of the Proposal (refer to Appendix 8). Appropriate materials will be used to minimise visual impacts and reflectivity around the ridgelines.	
4.2.2 Building Setbacks			
 Building setbacks are to be in accordance with the standards outlined in Table 11. Building setback requirements: Lots fronting designated roads (Mamre Road and Potential Southern Link Road) 20m Lots fronting key access roads (distributor and collector roads): 12m Lots fronting all other roads (local estate roads): 7.5m Secondary road frontages (corner lots): 5m Rear and side boundaries: 5m Lots adjoining the proposed WSFL corridor: 5m 	YES	The proposed Data Centre will comply with the relevant setback controls. The Proposal will provide a 20m building setback from Mamre Road.	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 2) Notwithstanding Control (1) above, no development other than the following development is permitted within the defined setback for any road, other than Mamre Road and potential Southern Link Road: Landscaping; Maintenance/rehabilitation of biodiversity corridors or areas; Utility services installation; Accessways and driveways (not permitted in setbacks to designated roads); Fire access roads; Approved signage; Street furniture; or Drainage works. 	YES	No other development other than the development prescribed in subclause (2) will be provided within the defined setback.	
 3) Setbacks may incorporate an off-street parking area if it can be demonstrated that the location of the car parking area: Is within a setback which is at least 13m wide and set behind a landscaped area which is at 50% of the required setback; Promotes the function and operation of the development; Enhances the overall design of the development by implementing design elements, including landscaping, that will screen the parking area and is complementary to the development; and Does not detract from the streetscape values of the locality. 	NOTED	Noted.	
 The design of setbacks and hardstand areas should seek to minimise the visual impacts of the development (see also Landscaping). Additional setbacks may be applicable to avoid construction over easements. For corner sites, setbacks must also ensure clear vehicular sight lines for perpendicular traffic (Figure 17). 	NOTED	Noted.	
4.2.3 Landscaping			
 1) Landscaped area is to be provided generally in accordance with the requirements set out in Table 12. Minimum landscape requirements: Lots fronting designated roads (Mamre Road and Potential Southern Link Road): 10m landscape setback to the road frontage Lots fronting key access roads (distributor and collector roads): 6m or average 50% of the setback along the road frontage 	YES	The Proposal will provide a 10m landscaped setback from Mamre Road.	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control		Planning Assessment	
 Lots fronting all other roads (local estate roads): Average of 50% of setback along the road frontage Rear boundary: 2.5m from the rear boundary Side boundary: No minimum requirement 			
2) A Landscape Plan prepared by a Landscape Architect is to be submitted with all development applications.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
3) Landscape design should contribute to the Greater Sydney Regional Plan canopy cover target of 40%, including by retaining existing paddock trees, windrows and large canopy trees where possible, and adding to the existing canopy.	YES	The proposed landscaping design will contribute to the overall canopy cover across the Mamre Road Precinct.	
4) Outdoor recreation areas for staff should be integrated into landscaped areas, where possible, to provide shade and an appropriate level of amenity and comfort.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
5) Minimum of 15% of the site area is to be pervious. Achieved via either landscaping or the use of permeable paving materials.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
6) Landscaped front setbacks should include canopy trees whose mature height is in scale with the proposed development.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
7) Tree planting in the form of island planter beds should be provided at a rate of one planter bed per 10 car spaces within car parks to reduce the heat effect and soften the hard surfaces.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
8) Existing remnant vegetation within front, rear and side setback areas shall be retained and enhanced as an integral part of the landscaping proposals for each development.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
9) Where sites back onto designated roads or the main access roads, setback areas shall be provided with mounded landscape screens.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
10) Screen planting with evergreen shrubs and trees is required to screen car parks, vehicular manoeuvring areas, garbage areas, storage areas from the street frontage.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
11) Paving, structures and wall materials should complement the architectural style of buildings on the site.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
 12) The selection of proposed trees and other landscaping plants is to consider: The preferred trees identified in the Penrith Council Street and Park Tree Management Plan. The use of relevant local native vegetation communities that occur, or once occurred in the area rather than exotic plant or non-local native species. The re-use of native plants or topsoil removed during subdivisions works or earthworks. 	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 The contribution to the management of soil salinity, water levels and soil erosion. Tree species being low maintenance and drought tolerant. The capacity of the species to contribute to tree canopy cover. That invasive turf (including Kikuyu) must not be used in areas adjoining, remnant vegetation within open space areas and riparian corridors. A diverse range of flora species for both street and suburban plantings to increase species disease resilience. o Service authority requirements in easement locations. 			
13) Street planting is to have a minimum container pot of 100L.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
14) Sufficient area/space is to be made available to allow trees to grow to maturity.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
15) Consolidate landscape areas to maximise space for deep soil, tree growth and aesthetic opportunities.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
16) No plant species that are considered a weed shall be used.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
17) Groundcovers should be considered as a grass alternative in areas not specifically designed for pedestrian use.	YES	A set of Landscape Plans has been prepared by Habit8 (refer to Appendix 7).	
4.2.4 Building Design			
 Developments with a construction cost of \$1 million or more are to demonstrate a commitment to achieving no less than 4 stars under Green Star or 4.5 stars under the Australian Building Greenhouse Rating system (now part of the National Australian Built Environment Rating System (NABERS)), where appropriate. An access report is required where disabled access is a requirement of the Disabilities Discrimination Act 1992. 	YES	The Proposed Development will target a 4-Star-Green-Star NABERS Rating.	
Siting/Building Orientation:	YES	The proposed architectural design has	
 The design and layout of buildings must consider local climatic factors. Buildings should take advantage of a north or north-easterly aspect to maximise passive solar illumination, heating and natural cross-ventilation for cooling. Western orientations should be avoided to prevent excessive heating and the reliance on mechanical services to provide cooling. Trees should be planted around the building to create shade, screening and wind breaks. 		considered the adjoining building orientation controls, whilst being considerate towards the built form outcomes achieved under SSD 9522 as well as the wider Mamre Road Precinct.	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 Building design should minimise impacts of overshadowing within the site and on adjoining development. Buildings should be oriented so that the building frontage is parallel with the primary street frontage. Setbacks on corner sites should enable clear sight lines for the expected vehicular traffic. Building siting must allow for adequate setbacks landscaping, water sensitive urban design, tree planting and to strengthen envisaged character of the area. Building siting and orientation should avoid construction over existing and required easements. Buildings should be oriented so that loading, servicing and areas of car parking greater that 20 spaces are accommodated to the rear or the side of the site. Only visitor carparking (under 20 spaces) is permitted at the front of the site. Building elevations oriented towards rural-residential areas shall be minimised. Where site constraints create difficulties in complying in this regard, elevations shall be appropriately detailed using windows, broken building planes and other architectural 			
 devices. Architectural Design 14) The design of buildings must reflect an industrial and commercial character of the precinct while responding to the adjacent scale and rural character of the area. 15) Facades along the main street frontage(s) must provide a minimum of 30% glazing to strengthen passive surveillance and streetscape character. 16) Utilise a mix of materials and colours on the visible facades, to provide articulation and visual interest to the street. 17) Where the rear or side of a building is visible from a publicly accessible area, provide articulation or utilise a textured surface treatment in order to provide visual interest. 18) External finishes should be of low reflectivity to minimise glare and reflection to surrounding areas. 19) The colour and material palette should utilise muted tones of the natural landscape and avoid incompatible bright bold colours and textures. The consent authority will have regard to the use materials in assessing development. 20) Elevations fronting the street or public reserves or those that are visible from public areas and adjoining rural-residential areas, must present a building form of significant architectural and design merit. The construction of large, blank wall surfaces is not permitted in visually sensitive locations. 	YES	The Proposal includes an aesthetically pleasing architectural design treatment that has been strategically prepared by Greenbox (refer to Appendix 6), and is justified and further explained within the Architectural Design Report located within Appendix 28 .	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment					
Development Control	Compliance	Planning Assessment			
21) Large unrelieved expanses of wall or building mass will not be supported, and as such should be broken up by the use of suitable building articulation, fenestration or alternative architectural enhancements.					
22) The use of large, uninterrupted areas of metal cladding or untreated concrete surfaces for wall construction is not supported. Applicants shall vary materials or finishes for external walls to provide attractive streetscapes and quality building designs. The use of a single construction material shall be limited to 50% of a wall surface area (refer Figure 18 and Figure 19)					
17) All loading areas should be located towards the rear of allotments. Loading areas are to be screened from the view of primary road frontages through physical and/or vegetation screening.					
18) Details of samples of external materials and finishes shall be submitted with the Development Application.					
19) External materials should not have an index of reflectivity above 20%. A reflectivity statement is to be submitted with all building development applications.20) Energy efficient design principles should be employed in all building designs (refer					
Figure 20Figure 20).					
21) Walls shall be articulated to provide more varied streetscapes, particularly where visible from public roads or adjacent residential areas.					
22) Part of the cross-section of buildings shall be projected to reduce apparent height and scale of external walls, including:					
 awnings and/or upper storeys that project above footpaths; roofs with eaves that project beyond external walls; or 					
colonnades.23) Entrances to buildings must be highlighted by architectural features consistent with the					
overall design of the building. 24) Courtyard and screen walls should be in the same material as the building facades.					
25) Particular care should also be taken in: o designing roof elements; and o locating plant and mechanical equipment including exhausts, so as to reduce their visual impact from elevated locations.					
26) Any office and administration component is to be located to the main frontage of the building and be designed as an integral part of the overall building, rather than a 'tack on' addition.					
27) The main office administration component is to have a designated entry point that is highly visible and directly accessible from visitor parking and the main street frontage.					



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment					
Development Control	Compliance	Planning Assessment			
 28) The entry, design and layout of the main office or administration component is to consider the principles of Universal Design and incorporate, if possible: A level or graded path from the car park area to the entrance. A level entry (no steps). An accessible toilet. Easy access doors and corridors. Accessible placement of switches, power points and window controls. 					
 Roof Design 29) Roof design must provide visual interest and variation from the streetscape. 30) Roofs forms should generally be of low pitch to reduce the bulk of buildings. 31) Roof forms should help to visually articulate the use within the building. This may include transitions between foyer, office and larger warehouse uses. 32) Building services located in / on the roof, such as solar panels, HVAC systems, lift motor rooms, exhaust fans, must be screened from the façade with an integrated built element such as parapets. 33) Roof design must provide natural illumination to the interior of the building. 	YES	As above.			
4.2.5 Design of Storage Areas					
 External storage of goods must be avoided, wherever possible. Where the nature of the activity or the materials means that internal storage is impractical, all external storage areas must be located behind the front building setback. In addition, when assessing development applications involving external storage of goods, the following will be taken into consideration: The proposed height and on-site arrangement of stored goods; The visual impact of the storage area and how this is proposed to be minimised (orientation, screening with landscaping and/or solid fencing, etc.); Access arrangements; and Safety issues. For sites with multiple frontages, either to roads or other public spaces, the location and orientation of external storage areas shall minimise visual impact from all potential viewpoints. Rainwater tanks are not to be visually intrusive from the main street frontage or other public areas. 	YES	As above.			
4.2.6 Storage, Transportation and Processing of Chemical Substances					



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 1) A Chemical Use and Storage Report is to be submitted with any Development Application which involves the storage, transportation and/or processing of chemical substances, except in the following circumstances: The use of chemicals is for routine cleaning and the chemicals to be used are of household or hospital grade. The total quantity of chemicals to be routinely used or stored on the site does not exceed 100 litres. The chemicals to be used or stored are not of sufficient acidity, alkalinity or strength to cause significant harm on skin contact, or to the environment if a spill were to occur. The application outlines the methods proposed to be used to minimise the potential for spills. 	YES	The Proposal includes provisions for diesel fuel storage across the Site to cater for emergency backup power to run the proposed generators in the case of an emergency situation across the Site. A SEPP 33 Report has been prepared by ARUP which addresses the storage and handling of Dangerous Goods (refer to Appendix 21).	
4.2.7 Signage and Estate Entrance Walls			
 All advertising is required to be: Constructed of high quality, durable materials; Considered in conjunction with the design and construction of buildings; Restricted generally to one sign identifying the name of the occupants and/or products manufactured or produced on the site; and Contained wholly within the site. The dimensions of free standing pylon signage must not exceed 10m in height from finished ground level and 2m width. No signage is permitted in the bottom 2m of the structure. Building identification signage should have a maximum advertising area of up to 0.5 square metres for every metre of lineal street frontage. Sky signs and other roof signs that project vertically above the roof of a building are not permitted. Flat mounted wall signs for business identification signage are to be no higher than 15 metres above existing ground level. Signs should generally be confined to the ground level of the building, awning or fascia, unless it can be demonstrated that the building is of a scale, architectural style and in a location that would be enhanced by signage at different elevations. The sign is to be contained fully within the confines of the wall or awning to which it is mounted. 	N/A	There is no signage proposed under the Proposed Development.	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 8) In the case of multiple occupancy of a building or site: o Each development should have a single directory board listing each occupant of the building or site. Freestanding signs will not be supported. Only one sign is to be placed on the face of each premises either located on or over the door of the shop, unit, office, suite, etc. One under awning sign shall be permitted for each shop, unit, office, suite, etc. In the case where the shop, office, suite etc. has more than one street frontage, one under awning sign may be permitted to each street frontage. The minimum distance between under awning signs shall be 3m. Multiple tenancies in the same building should use consistent sign size, location and design to avoid visual clutter and promote business identification. 9) Projecting wall signs, generally, will not be supported unless it can be demonstrated to be of an architectural style which is particularly suited to that building in relation to its design. 10) Illuminated signs are not to detract from the architecture of the supporting building during daylight. 11) Illumination (including cabling) of signs is to be either: Concealed. Integral with the sign. Provided by means of carefully designed and located remote or spot lighting. 12) The ability to adjust the light intensity of illuminated signs is to be installed where the consent authority considers it necessary. 13) A curfew may be imposed on the operation of illuminated signs where continuous 	Compliance	Planning Assessment	
 illumination may impact adversely on the amenity of residential buildings or have other adverse environmental effects. 14) Up-lighting of signs is prohibited. Any external lighting of signs is to be downward pointing and focused directly on the sign and is to prevent or minimise the escape of light beyond the sign. 15) A maximum of one illuminated sign is permitted on each elevation of each of each 			
warehouse building. 16) All illuminated signage shall be oriented away from residential receivers.			
4.2.8 Lighting			
 Lighting details shall be provided as part of any relevant development application. Lighting design should address the principles of CPTED, where there is significant pedestrian activity, late night work-shifts or safety and security issues. 	YES	Lighting would be designed to be in compliance with the latest version of AS1158 and AS4282 (INT) – Control of Obtrusive Effects of Outdoor	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control		Compliance	Planning Assessment
3) 4) 5)	Adequate lighting should be provided to meet security requirements without excessive energy consumption. Lighting powered by solar batteries or other renewable energy sources is encouraged. The use of sensor lighting, both internally and externally, should be considered. Where premises are used outside daylight hours, car parks and entrances shall be adequately illuminated. Lighting is to be designed or directed so as to not cause light spill onto adjoining sites where there could be an impact on the adjoining site's operations, safety or amenity.		Lighting. Lighting has also been provided in accordance with the requirements of Australian Standard 1158.3.1-1999 and the recommendations contained therein. Glare and spill lights would be limited by the selection of fittings and are in accordance with the Australian Standard 4282-1987. Additionally, light fittings are LED wall mounted, pole mounted and mounted on the face of the awning and directed in such a manner, that they do not cause nuisance to surrounding properties or the public road network.
4.2	2.9 Fencing		
2)	Fencing along street frontages should provide open style fencing, which does not obstruct views of landscaping from the street or reduce visibility. Palisade fencing is encouraged. Solid fences above 1 metre in height are not permitted along street frontages. No fencing other than a low ornamental type may be erected at the front or secondary street site boundary. Should the applicant elect to use high security fencing, such fencing must be located either behind the landscape setback or alternatively within the landscaped area midway between the site front or secondary boundary and the building line (refer to Figure 21).	YES	Fencing proposed will be in accordance with the Draft DCP, as well as meet the future tenant demands
4.2	2.10 Ecologically Sustainable Design		
1)	Development applications should demonstrate Ecological Sustainable Design (ESD) measures have been incorporated into the design. An architect or appropriate building design consultant with demonstrated ESD skills should be engaged to consider the following issues: Scale and massing of the built form. Building and window orientation. Window size and glass type. o Roof materials and colour. Thermal mass and floor material. Façade material, colour and surface treatments. Insulation.	YES	Sustainability measure that will be implemented (where deemed practicable), include: Heat Island Effect: Consider high solar reflectivity materials. Water Use: Planting of water efficient native plants; Rainwater recycling;



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
Development Control	Compliance	Planning Assessment		
 Landscape to provide amenity, shade and moderation of the building microclimate. External shading to reduce summer heat particularly on windows and roofs. Natural ventilation with generous, all weather openings which take advantage of the height of the spaces. Natural light preferred over artificial. Utilise extensive roof areas for energy and water collection. 		 Installation of water efficient appliances; Building-level metering; and Sub-metering. Energy Use: Power Utilization Effectiveness (PUE) reduction; Whole building energy simulation; Building-level metering; and Sub-metering. Refrigerants: Refrigerant use reduction; and Avoid CFC-based refrigerants. Waste: Storage and collection of recyclables; and Construction and demolition waste management planning. Sustainable Site / Neighbourhood: Construction activity pollution prevention; Bicycle facilities; and Electric vehicle charging. 		
 Building services, excluding manufacturing plant and operations, should promote the following ESD measures: Separate metering of water and electricity is required for buildings with multiple uses or multiple tenants. Zoning of lighting to match use, and movement sensitive lighting controls. Shut-off valve at stormwater outlets is required to trap any toxic spills into piped stormwater systems. Waterless urinals are required at a minimum. Energy efficient lighting to be used throughout. Gas boosted solar hot water for staff amenities (kitchen, toilets, showers) unless approved otherwise. 	YES	As above.		



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 A suitably sized rainwater and recycled water storage tank is required for toilet flushing, irrigation or other permissible non-potable water uses. Strategic use of translucent/transparent wall and roof cladding to increase natural light. Waste heat recovery systems which use waste heat from refrigeration systems or other sources for uses such as preheating hot water. Alternatives to cooling towers such as air-cooled systems, ground source heat rejection or pond heat rejection. State of the art energy storage systems combined with the use of photo voltaic cells for roof areas. 			
 Measures to improve air quality and visual and thermal comfort include: Ventilation systems are to be designed to supply a generous amount of fresh air through the use of natural cross flow ventilation. Low VOC paints and low-formaldehyde floor covering, adhesives and furniture are to be used. Provision of natural light over artificial light. Control of direct sun in working areas. Two component artificial lighting is required which includes reflected light to ceiling and task lighting for desks. Radiant heat is to be controlled though glazed facades by shading and/or performance glass. Occupant control of comfort parameters (e.g. operable windows, control of temperature and air flow). Protection from excessive noise, particularly when windows are open or between production and office areas. Provision of quality landscaped outdoor amenity areas for staff for lunch and recreation. Hydronic heating and ceiling fans. Materials with low reflectance values, Solar Reflective Index (SRI) < 4.0 are to be used. 	YES	As above.	
 In areas where a recycled water scheme is planned: stormwater harvesting measures respond to the balance of demand for water from recycled and stormwater sources; street trees are to be indirectly connected to the recycled water network for irrigation during periods of drought; 	YES	As above.	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 where a recycled water system is to be delivered as part of individual developme proposals, reticulation should be designed in consultation with Sydney Water. Where dual reticulation is being provided for future recycled water delivery, recycled water supply be designed to supplement stormwater harvesting in a way does not compromise waterway health objectives. Rainwater tanks shall not be topped up with recycled water unless approved by Syd Water. Water use within the landscape (for uses such as irrigation, ponds, water feature must be supplied from non-potable sources such as recycled water, roof was harvested stormwater or other non-licensed water sources and treated to Australian Guidelines for Recycled Water. All buildings not covered by the State Environmental Planning Policy (Build Sustainability Index: BASIX) 2004: That are installing any water use fittings must demonstrate minimum standardefined by the Water Efficiency Labelling and Standards (WELS) Scheme. Minim WELS ratings are 4 star dual-flush toilets, 3 star showerheads, 4 star taps (for taps other than bath outlets and garden taps) and 3 star urinals. Water efficiency washing machines and dishwashers are to be used wherever possible. To install rainwater tanks to meet 80% of non-potable demand including outcuse, toilets and laundry. To incorporate passive cooling methods that rely on improved natural ventilate to supplement or preclude mechanical cooling. 	the that ney res) oter, the ding ards num r all ient		
4.3 Amenity			
4.3.1 Noise and Vibration	h-II VEC	A surfitching and sure that the state of	
1) Any machinery or activity considered to produce noise emissions from a premise s be adequately sound-proofed so that noise emissions are in accordance with provisions of the Protection of the Environment Operations Act 1997.	the	A qualitative and quantitative Noise Impact Assessment has been prepared by ARUP which assesses the construction and operational	
 2) The use of mechanical plant and equipment may be restricted in areas close to sensi receivers, such as adjoining rural residential development. Developers in all as should ensure through design of their development that no offensive noise is emit 3) Where it is considered likely that a development may cause an adverse impact 	reas ted.	phases of the Proposed Development against the relevant noise emission criteria applicable to the Site, ensuring compliance can be achieved (refer to Appendix 14).	
nearby rural or residential areas, an acoustic report from a qualified acoustical engir will be required to be submitted for consideration with the development applicat	neer	о пренил 17.	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
The acoustic report will need to demonstrate that the proposed development will not create any adverse impact. 4) All development shall comply with the requirements of relevant Australian Standards and State Government policies and guidelines relating to noise. 5) An acoustic report shall be required for developments that are likely to generate high noise levels and for development within 500m of residential areas and other sensitive noise receivers, including seniors housing, places of public worship and educational establishments. The acoustic design report should refer to the relevant Australian Standards and State Government policies and guidelines relating to noise. 6) If an acoustic report is not required at the development application stage, conditions will be imposed as part of the development consent which requires compliance with the relevant Australian Standards and State Government policies and guidelines relating to noise. Applicants must have regard to the criteria and demonstrate a standard of acoustic treatment for the building to comply with such criteria. 7) It is essential that potential developers investigate noise amelioration features to be included in building design, which will assist in achieving compliance with Council's acoustic criteria. Having regard to the surrounding topography, it is critical that the roof element of all buildings be acoustically capable of controlling potential breakout noise.			
4.3.2 Trading and Operating Hours of Premises			
 The hours of operation for premises involved in any type of employment generating activity shall be dealt with on a merit basis. In considering applications Council shall have regard to the likely impact of the trading hours of a particular activity on the amenity of adjoining rural-residential areas. 	YES	The Proposal would operate 24-hours 7-days per week. There are no adverse impacts anticipated as a result of the proposed operations.	
4.3.3 Air Quality			
 The emission of air impurities is to be controlled and limited to the standards allowed by the Protection of the Environment Operations Act 1997, to the satisfaction of Council and the Environmental Protection Authority at all times. An Air Quality and Odour Assessment is required for industrial development that in the opinion of the consent authority, may have an impact on the air quality of in the region. An assessment of the merits of the proposal will be made at the development application stage. However, applicants should be able to demonstrate that the most efficient means of minimising emissions are being utilised. 	YES	A qualitative and quantitative Air Quality Impact Assessment (AQIA) has been prepared by ARUP which assesses the construction and operational phases of the Proposed Development against the relevant air quality emission criteria applicable to the Site, ensuring compliance can be achieved (refer to Appendix 13).	
4.4 Earthworks and Retaining Walls			



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control		Planning Assessment	
4.4.1 Development on Sloping Sites			
 4.4.1 Development on Sloping Sites A Geotechnical Report is to be submitted with development applications proposing earthworks that change the levels of a site. Level transitions must be managed between lots and not at the interface to the public domain. Excavation and fill in excess of 1.0 metre may be permitted to allow for the establishment of a level construction pad providing the excavations are adequately retained and drained in accordance with engineering requirements. Finished ground levels adjacent to the public domain or public road dedication be no greater than 1.0m above the finished road level (or public domain level). Where a level difference must exceed 1.0m and adjoins the public domain or public road dedication, the resulting landscape setback must be increased to accommodate tiered retaining walls. Cut or fill retaining walls up to 3.0m in height are to be setback 2.0m into the property boundary and the setback is to be suitably landscaped. Fill retaining walls exceeding 3.0m in height, are to be provided with a 1.5m deep soil zone setback and landscaping from the property boundary, with the retaining wall stepped and a deep soil zone is to be provided between each tier. A maximum height of 3.0m for each retaining wall element is permitted. The highest retaining wall element is to be suitably fenced for safety. Development applications should ensure vegetation is protected on the site, particularly 	YES	The geotechnical profile of the Subject Site provides an unconstrained platform for development.	
 where it is important to site stability, and that site planning responds to the natural topography of the site. 10) Where fill material is required to be imported to the site, all material is required to be Virgin Excavated Natural Material (VENM) or Excavated Natural Material (ENM). Where possible, fill material should be sourced from within the Mamre Road Precinct. 11) Any fill that is being transported from a development can only be transported to sites that are lawfully able to receive such material The EPA legislation and guidelines should be consulted and consent should be sought for any such activity where required. 12) Any VENM, ENM or material received under an EPA Resource Recovery Order and Exemption must be validated by a suitably qualified person to demonstrate that it is fit for its intended use. 13) On sloping sites, site disturbance is to be minimised by using split level or pier foundation building designs. 			



velopment Control		
	Compliance	Planning Assessment
encouraged. During any earthworks, any topsoil should be preserved on site for re-use and should be stockpiled and covered to avoid dust or loss of topsoil. Refer to the Landscape Design Section of this Plan for controls on stockpiling topsoil on site. Earthworks in the floodplain must consider Section 2.7 of this DCP and Clause 33H		
	YES	An Erosion and Sediment Control Plan (ESCP)
		has been prepared and approved under SSD
commencement of any earthworks or development activity, in accordance with the approved ESCP. These must be maintained throughout the course of construction until disturbed areas have been revegetated and the soil stabilised. The applicant will be required to provide certification to this effect, which is to be lodged with Council prior to construction.		9522 for the wider Estate. Notwithstanding, a site-specific ESCP will be implemented for the Subject Site as a result of the Proposed Development.
Council or the proposed Certifier, in accordance with best management practices recommended by recognised authorities (including Managing Urban Stormwater – Soils		
The work supervisor is responsible for ensuring that all erosion and sediment control measures are implemented in accordance with conditions of approval and are maintained until a final inspection has indicated that the site is sufficiently rehabilitated		
Council may require erosion and sediment control works to be carried out in addition to, or in variation from, the approved ESCP, should circumstances necessitate it. Any variations are to be approved by Council and implemented in accordance with this section and current best practice guidelines, where relevant.		
	application for the proposed development. Retaining walls are to be kept to a minimum to reduce earthworks. Use of materials that complement the natural environment is encouraged. During any earthworks, any topsoil should be preserved on site for re-use and should be stockpiled and covered to avoid dust or loss of topsoil. Refer to the Landscape Design Section of this Plan for controls on stockpiling topsoil on site. Earthworks in the floodplain must consider Section 2.7 of this DCP and Clause 33H within the WSEA SEPP. 2 Erosion and Sediment Control All applications for subdivision and development which involve site disturbance must be accompanied by an Erosion and Sediment Control Plan (ESCP). Soil erosion and sediment control measures are to be provided on-site before the commencement of any earthworks or development activity, in accordance with the approved ESCP. These must be maintained throughout the course of construction until disturbed areas have been revegetated and the soil stabilised. The applicant will be required to provide certification to this effect, which is to be lodged with Council prior to construction. All erosion and sediment control measures n are to be installed to the satisfaction of Council or the proposed Certifier, in accordance with best management practices recommended by recognised authorities (including Managing Urban Stormwater – Soils and Construction). The work supervisor is responsible for ensuring that all erosion and sediment control measures are implemented in accordance with conditions of approval and are maintained until a final inspection has indicated that the site is sufficiently rehabilitated and stabilised. The decision to install a particular mechanism to prevent erosion and/or sedimentation depends on the location and type of activity proposed and may vary from site to site. Council may require erosion and sediment control works to be carried out in addition to, or in variation from, the approved ESCP, should circumstances necessitate it. Any variations ar	to reduce earthworks. Use of materials that complement the natural environment is encouraged. During any earthworks, any topsoil should be preserved on site for re-use and should be stockpilled and covered to avoid dust or loss of topsoil. Refer to the Landscape Design Section of this Plan for controls on stockpilling topsoil on site. Earthworks in the floodplain must consider Section 2.7 of this DCP and Clause 33H within the WSEA SEPP. 2 Erosion and Sediment Control All applications for subdivision and development which involve site disturbance must be accompanied by an Erosion and Sediment Control Plan (ESCP). Soil erosion and sediment control measures are to be provided on-site before the commencement of any earthworks or development activity, in accordance with the approved ESCP. These must be maintained throughout the course of construction until disturbed areas have been revegetated and the soil stabilised. The applicant will be required to provide certification to this effect, which is to be lodged with Council prior to construction. All erosion and sediment control measures n are to be installed to the satisfaction of Council or the proposed Certifier, in accordance with best management practices recommended by recognised authorities (including Managing Urban Stormwater – Soils and Construction). The work supervisor is responsible for ensuring that all erosion and sediment control measures are implemented in accordance with conditions of approval and are maintained until a final inspection has indicated that the site is sufficiently rehabilitated and stabilised. The decision to install a particular mechanism to prevent erosion and/or sedimentation depends on the location and type of activity proposed and may vary from site to site. Council may require erosion and sediment control works to be carried out in addition to, or in variation from, the approved ESCP, should circumstances necessitate it. Any variations are to be approved by Council and implemented in accordance with this section and curr



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
place and approval should be obtained from the Certifying Authority before removing erosion and sediment control measures. 8) Where an application is for a site over 2,500m2 and there will be substantial earthworks, the applicant is required to address a number of additional measures in the ESCP, including: • Identify all areas likely to cause pollution of waterways from the transport of stormwater run-off containing sediment and silt and implement appropriate devices to stop the risk of pollution; • Divert clean water around the construction site to prevent contamination; • Retain as much natural vegetation as possible and limit site disturbance; • Control stormwater that enters the construction site from upstream; • Divert stormwater from undisturbed upper slopes onto stable areas; • Retain and stockpile all excavated topsoil on site for future landscaping and to minimise risk of erosion; • Prevent sediment/silt from entering adjoining public or private property (especially drains) by installing sediment control devices at the low side of sites and wash down areas; • Provide a single, stabilised entry/exit point to the site; • Prevent sediment, including building materials, from reaching the road or Council's stormwater system. Sediment is to be removed by sweeping, shovelling or sponging. Under no circumstances shall sediment be hosed; • Where a work zone permit over public property is applicable, ensure that appropriate debris control devices are implemented to prevent spillage of building materials into stormwater drains; • Compact all drainage lines when backfilling; • Connect downpipes to the stormwater system as early as possible; • Revegetate all disturbed areas, after on-site works are completed, in order to stabilise the surface; and • Maintain all sediment control devices during earthworks and construction to standards acceptable to Council.			
4.5.1 General Principles for the Provision of Services	W=2	All the state of the state of	
1) Council shall require as conditions of any development consent that arrangements satisfactory to:	YES	All services will be augmented accordingly to the Site. Further provisions for a 132 kV line are	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 Sydney Water will be made for the provision of water and sewerage services; Endeavour Energy have been made for the supply of electricity; Arrangements satisfactory to the relevant telecommunications authority will be made for the provision of telecommunications services; and Council have been made for the drainage of the land. A Utilities Plan is to be submitted with all subdivision and new building development applications. Council will require, as a condition of consent, that electricity and telecommunication mains be placed underground. Where technically feasible, compatible public utility services shall be coordinated in common trenching to maximise cost-effectiveness. Council will require that all new premises be provided with state of the art telecommunications infrastructure utilising optic fibre or DSL technology to enable companies to access broad band services using high speed, high reliability telecommunications. 		proposed through concurrence with Endeavour Energy to provide power to the Site to facilitate the future operations.	
4.5.2 Council Engineering Works and Construction Standards			
 All engineering works shall be undertaken in accordance with the provisions of Council's standards, as amended: Stormwater Drainage Specifications for Building Developments; Council's Water Sensitive Urban Design (WSUD) Technical Guidelines; Engineering Design Specifications for Civil Works; and Engineering Construction Specifications for Civil Works. 	YES	All civil works will be undertaken in accordance with the adjoining Council Standards and Guidelines.	
4.6 Waste Minimisation and Management			
 Applicants are to submit a Waste Management Plan when lodging a development application for: Demolition or construction of buildings. Change of use of buildings. Subdivision of land and/or buildings. o Alterations to 50% or more of the existing gross floor area of buildings, or additions to buildings resulting in a 50% increase (or more) to the existing gross floor area. The Waste Management Plan must be supported by scaled waste management drawings that are to assist in demonstrating compliance with the provisions of this Plan. 	YES	A Waste Management Plan has been prepared for the Proposed Development (refer to Appendix 19).	



Dra	Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
De	velopment Control	Compliance	Planning Assessment		
	A Waste Management Plan will also be required for applications for a Complying Development Certificate.				
4)	The Waste Management Plan enables Council (or the Certifying Authority) to assess the waste likely to be generated by the development and ensure that appropriate actions are taken so as to properly manage the generation, storage and disposal of wastes.				
5)	 Waste storage and collection areas should be: Flexible in their design so as to allow for future changes in the operation, tenancies and uses; 				
	 Located away from primary street frontages, where applicable; Suitably screened from public areas so as to reduce the impacts of noise, odour and visual amenity; and 				
6)	 Designed and located to consider possible traffic hazards (pedestrian/vehicular) likely to be caused by the storage and collection of waste. The following features will need to be considered in the design of waste storage and 				
	 collection areas: Dry recyclables including containers, paper, cardboard and toners for printers and photocopiers should be separated from other waste, for recycling; Food scraps should be placed in specialised containment bins and collected on a regular basis (particularly where large volumes of perishable wastes are generated); 				
	 Refrigerated garbage rooms should be provided where there are large quantities of perishable wastes and infrequent collections; and Clinical or hazardous and liquid waste should be placed in specialised containment bins and collected by specialised services. 				
7)	Grease traps must be provided where there is a likelihood of liquid waste entering the drainage systems (contact Sydney Water to obtain trade waste requirements).				
8)	Communal storage/collection facilities are recommended where: The design makes it difficult for all tenants to have ready access to a collection point; or				
9)	• The site characteristics restrict vehicle entry. Where a communal facility exists, each tenant should have a designated area which is clearly signposted.				



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment				
Development Control		Compliance	Planning Assessment	
manoeuvring area must and design. 11) The system for waste n to be used whether Cou	hicle be required to enter the property, the driveway and be suitable for a collection vehicle in terms of both its strength nanagement must be compatible with the collection service(s) uncil or private contractor. Iting adequate manoeuvring area are to be provided with the			
4.7 Access and Parking				
	e is to meet AS 2890 and where appropriate, AS 1428. On-site yided to a standard appropriate to the intensity of the proposed in Table 13.	YES	A qualitative and quantitative Traffic Impact Assessment has been prepared by ARUP, which includes an assessment against the relevant	
Activity	Parking Requirement		traffic and parking impacts as a result of the Proposal (refer to Appendix 11).	
Freight Transport Facilities	1 per transport vehicle present at peak vehicle accumulation plus 1 per 2 employees, or to be determined by a car parking survey of a comparable facility			
Industries	1 space per 200m² of gross floor area or 1 space per 2 employees, whichever is the greater			
Vehicle Body Repair Workshops/ Vehicle Repair Stations	3 spaces per 100m² of gross floor area or 6 per work bay, whichever is the greater			
Warehouses or distribution centres	1 space per 300m² of gross floor area or 1 space per 4 employees, whichever is the greater.			
Ancillary office space	1 space per 40m² of gross floor area			
Neighbourhood shops	1 space per 40m ² of gross leasable area			
Other Uses	In accordance with RMS Guidelines or if there are no parking guidelines for a specific use, then a site specific car parking analysis will be required. This may require the applicant to submit a car parking report from a suitably qualified traffic consultant.			



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control		Compliance	Planning Assessment
Activity	Parking Requirement		
Accessible Parking	Accessible car spaces should be in accordance with the Access to Premises Standards, Building Code of Australia and AS2890.		
Bicycle Parking	Bicycle parking in accordance with the suggested bicycle parking provision rates for different land use types in the document 'Planning Guidelines for Walking and Cycling' (NSW Government 2004). Bicycle parking spaces should comply with AS2890.3:1993 Bicycle Parking Facilities.		
increased until the recorresponding to the accorresponding to the accorresponding to the according to the ac	ents, a new use must not commence or the floor area be equired car park spaces have been provided on the site, ctivities outlined in Table 13. ed in Table 13 are to be based on the initial use identified at the ne development application. ecific requirements relevant to particular developments, the in the RTA's "Guide to Traffic Generating Developments" (as in Standard AS 2890.1 and 2 - 2004 should be referred to as a seriof all data, the applicant should revert to the use of first		
the anticipated heavy v 6) Stacked parking will no 7) Car parking above grou	and level is to have a minimum floor to ceiling height of 2.8m so		
8) Underground/basemen 9) Car parking and associ- requirements of this D	nother use in the future. t car parking is not permitted. ated internal manoeuvring areas provided over and beyond the CP shall be calculated as part of the development's gross floor		
11) The movement of pede	must comply with the relevant Australian Standards. strians throughout the car park should be clearly delineated and f the car park to minimise conflict with vehicles. The car parking		



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
and manoeuvring layout should be in accordance with the provisions of AS 2890.1 - 2004.			
12) Provision of parking spaces for disabled persons should be in accordance with the			
Access to Premises Standards, the Building Code of Australia and AS2890.			
13) All car parking areas to be constructed of hard standing, all weather material, with parking bays and circulation aisles clearly delineated.			
14) Vehicle access is to be integrated into the building design as to be visually recessive.			
15) The design of parking and access areas is to address Water Sensitive Urban Design (WSUD) principles (refer Section 2.6).			
16) All vehicles must be able to enter and leave the site in a forward direction without the need to make more than a three point turn.			
17) Internal directional signs are to be provided to assist site visitors in locating parking areas.			
18) The design of the car park should ensure that passive surveillance is possible and,			
where appropriate, incorporate active measures such as cameras and security patrols.			
Car parks should be designed to minimise dark areas through the provision of			
appropriate lighting.			
19) Access to security parking shall be designed to ensure the access mechanism is			
accessible to the vehicle driver on the entry side of the driveway.			
20) Provision should be made for all vehicles to enter and exit a secure (i.e. boom-gated) area in a forward direction.			
21) Visitor parking should be provided outside the secured parking areas.			
22) The design of car parks should ensure adequate separation of staff/visitor parking and loading dock circulation areas for heavy vehicles.			
23) Vehicular ramps less than 20m long within developments and parking stations must			
have a maximum grade of 1 in 5 (20%). Ramp widths must be in accordance with AS2890.			
24) Loading docks associated with the development shall be provided on-site, with all			
loading and unloading activities occurring on-site.			
25) All loading and unloading areas are to be:			
 Integrated into the design of developments; 			
 Separated from car parking and waste storage and collection areas; 			
 Located away from the circulation path of other vehicles; and 			
 Designed for commercial vehicle circulation and access complying with AS 2890.2. 			



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 26) Vehicular access to the loading / unloading area(s) is preferred off rear lanes, side streets and right of ways. Where appropriate, consider a single vehicular access point for the loading/unloading area(s) and waste collection area(s). 27) Secure multi-deck car parks should incorporate communication devices such as: o Intercoms at boom gates; o Public address systems; o Telephones; or o Emergency alarms. 28) To ensure users of secure multi-deck car parks are easily able to determine the location of exit and access points, security intercoms or similar and appropriate signage are to be included. 29) All surfaces in the car park should be painted in light coloured paint or finished in light grey concrete to reflect as much light as possible. 30) All potential entrapment points should be avoided, e.g. under stairs, blind corners and wide columns. Adequate lighting and mirrors should be used when certain design features are unavoidable. 31) Access, parking, manoeuvring and loading facilities for industrial development shall be in accordance with AS 2890.2 - 2004 and Performance Based Standards 'An introduction for road managers' (National Heavy Vehicle Register - May 2019) to accommodate vehicle types as outlined in Table 14. 32) A development is required to cater for vehicles larger than the minimum specified above where the development is for uses such as a transport depot, warehouse, etc. All service vehicles must enter and exit the development site in a forward direction. \ 33) Reversing of heavy vehicles must only occur in designated loading bays and loading docks. No reversing of heavy vehicles is permitted in carparks or areas where pedestrians may be permitted. 			
4.7.2 Bicycle Parking, Facilities and Storage	1		
 Applicants should comply with the suggested bicycle parking provision rates for different land use types in the document 'Planning Guidelines for Walking and Cycling' (NSW Government 2004). Bicycle parking spaces must be provided in accordance with AS2890.3:2015 Bicycle Parking Facilities. The following associated bicycle facilities are to be provided: Change and shower facilities for cyclists are to be conveniently located close to the 	YES	A qualitative and quantitative Traffic Impact Assessment has been prepared by ARUP, which includes an assessment against the relevant traffic and parking impacts as a result of the Proposal (refer to Appendix 11).	
 bicycle storage areas; and Where the building is to be strata-titled, the bicycle storage facilities and shower/change facilities are to be made available to all occupants of the building. 			



Draf	Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Dev	elopment Control	Compliance	Planning Assessment	
5) /	Bicycle parking spaces must: Be located to provide convenient access from surrounding bicycle routes and main building entrances; o Not interfere with reasonable access to doorways, loading areas, access covers, furniture, services and infrastructure; Not cause a hazard; and o Be adequately lit during periods of use. A bicycle rail must: Be securely fixed to a wall or to the floor or ground; Be in a highly visible location for bicycle security (when not in a compound); Be of a shape that allows a cyclist to easily lock the bicycle frame and wheels; and Be located to allow easy access to park, lock and remove the bicycle. A bicycle compound or a bicycle locker must: Be located to provide convenient access to other bicycle facilities including showers and change rooms; Be fully enclosed; Be able to be locked; and If outside, provide weather protection for the bicycle.			
4.7.	3 Access and Driveways			
2) - 1	The road access to the site should provide for safe entry and exit. All vehicles must enter/exit the site in a forward direction. The entry and exit from the site should provide for appropriate traffic sight distance in both directions, in accordance with the provisions of AS2890.1 and 2 - 2004 for car parking and commercial vehicles respectively. The design of the development driveway should take into consideration the traffic volumes of the surrounding road network. Driveways should be: Provided from lanes and secondary streets rather than the primary street, wherever practical; Located taking into account any services located within the road reserve, such as power poles, drainage inlet pits and existing street trees; Setback a minimum of 6m from the perpendicular of any intersection of any two roads; and Located to minimise noise and amenity impacts on adjacent residential development.	YES	A qualitative and quantitative Traffic Impact Assessment has been prepared by ARUP, which includes an assessment against the relevant traffic and parking impacts as a result of the Proposal (refer to Appendix 11).	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
5) The driveway crossing and access roads shall be designed in accordance with the provisions of AS2890.1 and 2 - 2004 for car parking and commercial vehicles respectively.			
6) Driveway widths must comply with the relevant Australian Standards and swept turning paths tested for larger vehicle types such as B-double (PBS Level 2 Type B).			
7) Site specific driveway designs should be designed for sites which require access arrangements for 36m B-triple (PBS Level 3 Type A).			
8) Driveway grades, vehicular ramp width/grades and passing bays must be in accordance with the relevant Australian Standard (AS2890.1).			
9) The required threshold should be set within the property to prevent cross fall greater than 4% within the footway area.			
10) All driveways are to be sealed from the point of the public road up to and including the hard-stand parking areas.			
11) Roads shall be constructed to Council's standards in consultation with Council's Engineering Services Unit and Council's 'Guidelines for Engineering Works - Development and Subdivision'.			
12) New road reservations and rights-of-way shall be dedicated or created at no cost to Council.			
 13) New allotments must have direct access to dedicated public roads. 14) Bushfire requirements must be considered when designing access roads for subdivisions of land which is classified as 'bushfire prone land'. Access arrangements must include adequate provision for turning areas and emergency access. 			
15) Natural contours should be followed when designing and constructing driveways. Driveways should be located to retain as much of the property's vegetation as practicable.			
16) Any new private access roads or driveways that connect to a public road should be sealed with asphalt or another suitable surface from the public road to prevent erosion and minimise dust and dirt transfer.			
4.7.4 Site Access and Servicing			
 Development that fronts Mamre Road, the Potential Southern Link Road, or a classified road, shall ensure that: The allotment of land was created in accordance with a subdivision approved pursuant to this DCP; and Access to the allotment is in accordance with the access arrangements approved with the subdivision. 		A qualitative and quantitative Traffic Impact Assessment has been prepared by ARUP, which includes an assessment against the relevant traffic and parking impacts as a result of the Proposal (refer to Appendix 11).	



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 Development shall, where appropriate, be designed to: Allow all vehicles to enter and leave the site in a forward direction; Accommodate heavy vehicle parking and manoeuvring areas; Avoid conflict with staff, customer and visitor vehicular and cycle movements; and Ensure satisfactory and safe operation with the adjacent road system. 			
3) In determining access and servicing requirements, Council will take the following into consideration:			
 The location, type and scale of the proposed development; The compatibility of the location and design of the car park with adjoining properties; 			
 Traffic Authority Guidelines and comments of the Local or Regional Traffic Committee(s); and 			
 The potential for the development to generate heavy vehicle movements. Full details of the volume, frequency and type of vehicle movements shall be submitted with the development application. 			
5) In general, turning circles will be required to be provided to accommodate the largest type of truck which could reasonably be expected to service the site. All developments must be designed and operated so that a standard truck may complete a 3-point or semi- circular turn on the site without interfering with parked vehicles, buildings, landscaping or outdoor storage and work areas. Large scale developments shall be designed to accommodate 26m B-double (PBS Level 2 Type B).			
6) The suitability of manoeuvring areas provided for large vehicles will be assessed by reference to the Standard Vehicle Turning Templates which appear in Figures A.5a (small rigid truck), A.7a (large rigid truck) and A.9a (large articulated truck) of the Roads and Maritime Services publication Policies Guidelines and Procedures for Traffic Generating Developments and turning templates for either 26m B-doubles (PBS :Level 2 Type B) or 36m long B-triple (PBS Level 3 Type A).			
7) Adequate space is to be provided within the site for the loading, unloading and fuelling (if applicable) of vehicles. These areas shall be screened from the road.			
8) Car parks, aisles and manoeuvring areas shall be designed with function and safety in mind, and have minimum dimensions conforming with the Australian Standards 2890 Parking Facilities. The relevant parts of this standard are AS2890. 1 Off-street parking, AS2890.2 Commercial vehicle facilities and AS2890.3 Bicycle parking facilities.			
 9) Where the nature of the industrial development will attract clients/visitors to the site, the following elements shall be included in the car park design: 			



Draft Mamre Road Precinct Development Control Plan (Mamre Road DCP) Assessment			
Development Control	Compliance	Planning Assessment	
 The internal (vehicular) circulation network is to be free of disruption to circulating traffic and ensure pedestrian safety; The car park should, where possible, be designed with wheel stop kerbs only, rather than a barrier kerb between parking areas and pedestrian pathways; The movement of pedestrians throughout the car park is clearly delineated by all users of the car park and minimises conflict with vehicles; and Where parking spaces are to be provided for people with disabilities, these spaces are to be: Suitably located near entrances to the building, lifts and access ramps (if required); Provided in accordance with AS1428.1 Design for Access and Mobility; and Supplemented by the installation of appropriate tactile pavement treatments where required. Major developments shall make adequate provision for bicycle parking. 			
4.8 Employment Service Hubs			
 Indicative locations for employment service hubs are identified in the Mamre Road Precinct Structure Plan (Figure 2). Alternate location for an employment service hub may be considered, if: It is located at least 1km from other existing and/or planned employment service hubs; It does not preclude the provision of an employment service hub in a more accessible location. Development applications must demonstrate that the size, function and proposed use serves the daily convenience needs of the workforce in the zone or is for the benefit of the local workforce and businesses. Employment service hubs must not have an unreasonable impact on the viability of any other nearby established centre within an industrial or business zone. Uses are to be located within the primary street frontage to generate activity and interest on the street. Active transport paths and bicycle parking should be prioritised and incorporated into the design of the development. The built form should address co-located open space areas. 	YES	The proposed Data Centre will create employment-generating opportunities within the Mamre Road Precinct and facilitate employment-generating development in the industrial sector. The Proposal will not result in any unreasonable impact on the viability of any nearby established centre within an industrial or business zone. Rather, the Proposal will support the viability of the Western Sydney Aerotropolis and foster its economic growth in the Western City District. Active transport paths and bicycle parking will be incorporated into the design of the development, as a result of SSD 9522.	
7) Outdoor furniture and shading shall be provided.		The proposed built form will address co-located open space areas that adjoin the Site.	

