

Fire hazard properties & non-combustibility compliance  
of  
EQUITONE fibre cement façade materials

- ü EQUITONE facade materials are fibre cement sheeting, manufactured in compliance with AS/NZS 2908.2:2000 (Cellulose-cement products Part 2: Flat sheets) and ISO 8336:2009 (Fibre-cement flat sheets), and as such are deemed non-combustible in accordance with the following clauses of the NCC, and may be used wherever a non-combustible material is required.
  - C1.9<sub>e(iv)</sub> of the NCC 2019 Volume 1
  - 3.7.1.1<sub>(d)</sub> of the NCC 2019 Volume 2
  - C1.9<sub>e(iv)</sub> of the NCC 2016 Volume 1 (Amendment 1)
  - 3.7.1.2<sub>(d)</sub> of the NCC 2016 Volume 2
- ü EQUITONE fibre cement façade materials are classified as a 'Group 1' material in compliance with AS5637.1 and Specification C1.10 - Fire hazard properties, of the NCC 2019 Volume 1.

For further information, please consult with EQUITONE Australia technical department.

---

EQUITONE Australia

[www.equitone.com](http://www.equitone.com)

[info.australia@equitone.com](mailto:info.australia@equitone.com)

**Disclaimer**

The information in this Material Information Sheet is correct at time issuing. However, due to our committed program of continuous material and system development we reserve the right to amend or alter the information contained therein without prior notice. Please contact your local EQUITONE Sales Organization to ensure you have the most current version.

All information contained in this document is copyrighted ©.

This information is supplied in good faith and no liability can be accepted for any loss or damage resulting from its use