

Nationwide House Energy Rating Scheme — Class 2 summary

NatHERS Certificate No. 0006203140

Generated on 06 Jul 2021 using BERS Pro v4.4.0.2 (3.21)

Property

Address 26-42 Eden Street , Arncliffe ,
NSW , 2205

Lot/DP 1/447649

NatHERS climate zone 56

Accredited assessor 

Martin Pinson

INTEGRECO

consulting@integreco.com

0422144603

Accreditation No. DMN/19/1921

Assessor Accrediting Organisation Design Matters
National



Verification

To verify this certificate, scan the QR code or visit hstar.com.au/QR/Generate?p=vTUQJKpk.
When using either link, ensure you are visiting hstar.com.au

Summary of all dwellings

Certificate number and link	Unit Number	Heating load (MJ/m ² /p.a.)	Cooling load (MJ/m ² /p.a.)	Total load (MJ/m ² /p.a.)	Star rating
0006207195	A-001	31.9	19.9	51.9	5.9
0006207229	A-002	39	16.4	55.4	5.7
0006207237	A-003	33.9	22.3	56.1	5.7
0006207245	A-004	17.5	12	29.5	7.8
0006207252	A-005	9.4	21.7	31.1	7.6

Continued Over

National Construction Code (NCC) requirements

The NCC's requirements for NatHERS-rated buildings are detailed in 3.12.0(a)(i) and 3.12.5 of the NCC Volume Two. For apartments the requirements are detailed in J0.2 and J5 to J8 of the NCC Volume One.

In NCC 2019, these requirements include minimum star ratings and separate heating and cooling load limits that need to be met by buildings and apartments through the NatHERS assessment. Requirements additional to the NatHERS assessment that must also be satisfied include, but are not limited to: insulation installation methods, thermal breaks, building sealing, water heating and pumping, and artificial lighting requirements. The NCC and NatHERS Heating and Cooling Load Limits (Australian Building Codes Board Standard) are available at www.abcb.gov.au.

State and territory variations and additions to the NCC may also apply.

Summary of all dwellings (continued)

Certificate number and link	Unit Number	Heating load (MJ/m ² /p.a.)	Cooling load (MJ/m ² /p.a.)	Total load (MJ/m ² /p.a.)	Star rating
0006207260	A-006	45.4	12	57.4	5.6
0006207278	A-101	25.6	12.9	38.5	7.1
0006207286	A-102	17.1	11.2	28.3	7.9
0006207294	A-103	6.3	12.6	18.8	8.6
0006207302	A-104	12.9	10.9	23.8	8.2
0006207310	A-105	14.7	18.1	32.8	7.4
0006207328	A-106	8.2	15.7	23.8	8.2
0006207336	A-107	42.9	18	60.9	5.4
0006207344	A-108	42.2	9	51.2	5.9
0006207351-01	A-109	34.2	9.4	43.6	6.7
0006207369	A-201	14.8	12.5	27.2	7.9
0006207377	A-202	6.7	11.6	18.3	8.7
0006207385	A-203	6.9	13.4	20.3	8.4
0006207393	A-204	15.8	9.7	25.4	8.1
0006207401	A-205	7.6	16	23.6	8.2
0006207419	A-206	10	14.4	24.4	8.2
0006207427	A-207	27.2	19.8	47	6.4
0006207435	A-208	30.6	7.5	38	7.1
0006209548	A-209	19.1	9.1	28.3	7.9
0006207443	A-301	15.2	12.2	27.4	7.9
0006207450	A-302	7	11.4	18.4	8.7
0006207468	A-303	7.2	12.8	20	8.5
0006207476	A-304	16.3	9.6	25.9	8
0006207484	A-305	7.9	16.2	24.1	8.2
0006207492	A-306	9.9	13	22.9	8.3
0006207500	A-307	27.2	19.5	46.7	6.4
0006207518	A-308	31.1	7.6	38.7	7
0006207526	A-309	19.4	8.3	27.7	7.9
0006207534	A-401	15.5	12.3	27.8	7.9
0006207542	A-402	7.2	11.3	18.5	8.7
0006207559	A-403	7.3	12.6	19.9	8.5
0006207567	A-404	16.7	9.5	26.2	7.9
0006207575	A-405	8.2	16	24.2	8.2
0006207583	A-406	9.8	12.3	22	8.4
0006207591	A-407	27.1	18.4	45.4	6.4
0006207609	A-408	31.4	7.7	39.1	6.9
0006207617	A-409	19.5	9	28.5	7.8
0006207625	A-501	18.6	12.7	31.3	7.6
0006207633	A-502	8.8	11.4	20.2	8.4
0006207641	A-503	9.5	12.6	22.1	8.4

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006207658	A-504	25.5	9.8	35.3	7.3
0006207666	A-505	14.6	17.3	31.9	7.5
0006207674	A-506	9.6	11.1	20.7	8.4
0006207682	A-507	25.9	16.9	42.8	6.7
0006207690	A-508	33.5	7.9	41.4	6.9
0006207708	A-509	19.2	9.1	28.3	7.9
0006207716	A-601	20.3	10.3	30.6	7.7
0006207724-01	A-602	27.9	19.4	47.3	6.4
0006207732	A-603	14.4	19.5	33.8	7.4
0006207740	A-604	10	13	23.1	8.3
0006207757	A-605	20.7	17.1	37.8	7.1
0006209514	A-606	23.3	22.7	46	6.4
0006207765	A-607	15	15.8	30.9	7.6
0006207773	A-608	33.8	19.8	53.6	5.9
0006207781	A-609	31.5	8.6	40.1	6.9
0006207799	A-610	22.5	15.7	38.2	7.1
0006207807	A-701	20.4	10.8	31.2	7.6
0006207815-01	A-702	24.7	20.9	45.5	6.4
0006207823	A-703	14.4	19.5	33.8	7.4
0006207831	A-704	8.6	17.6	26.3	7.9
0006207849	A-705	15.4	20.3	35.7	7.3
0006207856-01	A-706	25.4	14.7	40	6.9
0006207864	A-707	16.6	14.8	31.4	7.6
0006207872	A-708	34.1	19.3	53.3	5.9
0006207880	A-709	27.3	8.9	36.2	7.3
0006207898	A-801	20.4	10.8	31.2	7.6
0006209522	A-802	25	21.7	46.7	6.4
0006207906	A-803	14.6	18.8	33.3	7.4
0006207914	A-804	8.8	17.5	26.3	7.9
0006207922	A-805	16.4	17.7	34.1	7.4
0006209530	A-806	20.7	15.1	35.9	7.3
0006207930	A-807	15.5	15.6	31.1	7.6
0006207948	A-808	34.3	19.1	53.4	5.9
0006207955	A-809	27.6	8.6	36.2	7.3
0006207963	A-901	21.9	8.2	30.1	7.7
0006207971	A-902	26.9	19.2	46.1	6.4
0006207989	A-903	15.9	17.5	33.4	7.4
0006207997	A-904	9	17.3	26.3	7.9
0006208003	A-905	18.4	16.6	35	7.3
0006208011	A-906	22.8	14.1	36.9	7.2
0006208029	A-907	17.1	14.1	31.2	7.6
0006208037	A-908	36.2	15.8	52	5.9

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006208045	A-909	30.2	9.8	40	6.9
0006208052	A-1001	22	8	29.9	7.7
0006208060-01	A-1002	26.9	19.5	46.4	6.4
0006208078	A-1003	16	17.2	33.2	7.4
0006208086	A-1004	9.9	15.4	25.3	8.1
0006208094	A-1005	18.5	16.6	35.1	7.3
0006208102	A-1006	22.9	14.2	37.1	7.2
0006208110	A-1007	17.3	14.2	31.5	7.6
0006208128	A-1008	36.3	15.8	52.1	5.9
0006208136	A-1009	29.4	8.4	37.8	7.1
0006208144	A-1101	22	8	29.9	7.7
0006208235-01	A-1102	27.1	19.1	46.2	6.4
0006208151	A-1103	16.2	17.4	33.7	7.4
0006208169	A-1104	10	15.2	25.2	8.1
0006208177	A-1105	18.8	16.7	35.5	7.3
0006208185	A-1106	23.2	14.1	37.3	7.2
0006208193	A-1107	17.3	14.1	31.4	7.6
0006208201	A-1108	36.6	15.5	52.1	5.9
0006208219	A-1109	29.7	8.4	38	7.1
0006208227	A-1201	22.1	8	30.1	7.7
0006209753	A-1202	27.4	18.8	46.2	6.4
0006208243	A-1203	16.3	17.4	33.7	7.4
0006208250	A-1204	10.1	15.3	25.5	8.1
0006208268	A-1205	18.9	16.5	35.4	7.3
0006208276	A-1206	23.3	14.1	37.4	7.2
0006208284	A-1207	17.4	13.8	31.2	7.6
0006208292	A-1208	36.7	15.2	51.9	5.9
0006208300	A-1209	32.2	9.3	41.5	6.8
0006208318	A-1301	22.3	8	30.3	7.7
0006208326	A-1302	27.4	18.8	46.2	6.4
0006208334	A-1303	16.5	17.3	33.8	7.4
0006208342	A-1304	10.1	15.2	25.3	8.1
0006208359	A-1305	19	16.6	35.6	7.3
0006208367	A-1306	23.4	14	37.4	7.2
0006208375	A-1307	17.8	13.9	31.7	7.5
0006208391	A-1308	36.8	15.6	52.4	5.9
0006208409	A-1309	29.9	8.6	38.5	7.1
0006208417	A-1401	22.4	8	30.4	7.7
0006208425	A-1402	27.6	18.5	46	6.4
0006208433	A-1403	16.7	17.1	33.7	7.4
0006208441	A-1404	10.3	15.2	25.5	8.1
0006208458	A-1405	19.3	16.5	35.8	7.3

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006208466	A-1406	23.6	13.8	37.4	7.2
0006208474	A-1407	17.8	13.6	31.3	7.6
0006208482	A-1408	37.1	15.3	52.4	5.9
0006208490	A-1409	30.1	8.8	38.9	7
0006208508	A-1501	22.6	7.9	30.5	7.7
0006208516	A-1502	27.7	18.3	46	6.4
0006208524	A-1503	16.8	17.1	33.9	7.4
0006208532	A-1504	10.4	15	25.4	8.1
0006208540	A-1505	19.4	16.3	35.7	7.3
0006208557	A-1506	23.7	13.9	37.6	7.2
0006208565	A-1507	17.9	13.5	31.4	7.6
0006208573	A-1508	37.2	14.8	52.1	5.9
0006208581	A-1509	32.8	9.2	42	6.8
0006208599	A-1601	22.7	7.8	30.5	7.7
0006208607	A-1602	27.8	18.2	46	6.4
0006208615	A-1603	16.9	16.8	33.7	7.4
0006208623	A-1604	10.5	14.9	25.4	8.1
0006208631	A-1605	19.5	16.3	35.8	7.3
0006208649	A-1606	23.7	13.7	37.4	7.2
0006208656	A-1607	18.3	13.7	32	7.5
0006208664	A-1608	37.4	14.9	52.3	5.9
0006208672	A-1609	30.4	8.8	39.2	6.9
0006208680	A-1701	22.8	7.7	30.5	7.7
0006208698	A-1702	27.9	18.2	46.1	6.4
0006208706	A-1703	17	16.7	33.8	7.4
0006208714	A-1704	10.6	14.9	25.5	8.1
0006208722	A-1705	19.7	15.9	35.6	7.3
0006208730	A-1706	23.9	13.6	37.5	7.2
0006208748	A-1707	18.1	13.1	31.2	7.6
0006208755	A-1708	37.5	14.8	52.3	5.9
0006208763	A-1709	30.5	8.5	39.1	6.9
0006208771	A-1801	22.9	7.7	30.6	7.7
0006208789	A-1802	28	17.9	45.9	6.4
0006208797	A-1803	17.1	16.6	33.7	7.4
0006208805	A-1804	10.7	15	25.6	8.1
0006208813	A-1805	19.8	16	35.8	7.3
0006208821	A-1806	24	13.6	37.6	7.1
0006208839	A-1807	18.2	13	31.2	7.6
0006208847	A-1808	37.6	14.6	52.3	5.9
0006208854	A-1809	33.1	9.1	42.2	6.8
0006208862	A-1901	23	7.6	30.6	7.7
0006208870	A-1902	28.2	17.8	45.9	6.4

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006208888	A-1903	17.3	16.7	34	7.4
0006208896	A-1904	10.8	15	25.8	8
0006208904-01	A-1905	20	15.9	35.8	7.3
0006208912	A-1906	25.6	15.4	41	6.9
0006208920	A-1907	18.7	13.6	32.3	7.4
0006208938	A-1908	37.9	14.4	52.2	5.9
0006208946	A-1909	30.9	8.4	39.3	6.9
0006208953	A-2001	34.3	10.2	44.5	6.6
0006208961	A-2002	38.7	19.8	58.5	5.4
0006208979	A-2003	26.3	19	45.3	6.4
0006208987	A-2004	20.1	15.8	35.9	7.3
0006209746	A-2005	28.2	15.9	44.1	6.6
0006208995	A-2006	42.5	26.4	68.9	4.9
0006209001	A-2007	43.1	26.4	69.4	4.9
0006209019	A-2008	40.2	9.4	49.7	6.2
0006211593	B-001	42	18.1	60.1	5.4
0006211577	B-002	34.6	27.2	61.8	5.3
0006211536	B-003	43.3	17.9	61.2	5.4
0006211601	B-101	22.4	15.8	38.2	7.1
0006211544	B-102	29.1	15.1	44.2	6.6
0006211486	B-103	26.2	13	39.2	6.9
0006211346	B-104	37.7	11.1	48.8	6.2
0006211361	B-105	18.3	10.5	28.8	7.8
0006211429	B-106	45.4	10.3	55.7	5.7
0006211932	B-107	42	13.3	55.3	5.7
0006210090	B-108	39.1	12.4	51.4	5.9
0006211882	B-109	37.2	23.2	60.4	5.4
0006210702-01	B-110	21.9	23.5	45.4	6.4
0006211619	B-201	26.6	15	41.6	6.8
0006211551-01	B-202	26.9	14.9	41.8	6.8
0006211494	B-203	17.7	12.2	29.9	7.7
0006211338-01	B-204	30.6	11.2	41.8	6.8
0006211379	B-205	20	9.6	29.5	7.8
0006211437	B-206	38.1	9.8	47.9	6.3
0006211940	B-207	32.5	12.5	45	6.5
0006210108	B-208	26.6	13.4	40.1	6.9
0006210496	B-209	42.6	28.5	71	4.8
0006210686	B-210	26	15.9	41.8	6.8
0006210314	B-211	23.9	19.2	43.1	6.7
0006211627	B-301	26.2	12.7	38.9	7
0006212138	B-302	32.7	10.7	43.4	6.7
0006211502-01	B-303	18.5	12.2	30.7	7.7

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006211874	B-304	29.4	11	40.4	6.9
0006211387	B-305	20.3	9.4	29.6	7.7
0006211445	B-306	39.2	9.6	48.8	6.2
0006211957	B-307	33	12.3	45.4	6.4
0006210116	B-308	30	10.6	40.6	6.9
0006210512	B-309	32	27.8	59.8	5.4
0006210710	B-310	24.2	19.4	43.6	6.7
0006210322	B-311	24.4	18.5	42.9	6.7
0006211635	B-401	30.8	12	42.8	6.7
0006211569-01	B-402	30.5	9.5	40	6.9
0006212112	B-403	30.6	13.8	44.4	6.6
0006212120-01	B-404	31.7	10.4	42.1	6.8
0006211395	B-405	20.4	9.4	29.8	7.7
0006211452	B-406	39.2	9.8	49	6.2
0006211965	B-407	33.6	12.3	45.8	6.4
0006210124	B-408	30.6	10.7	41.2	6.9
0006210504	B-409	31.8	29.3	61.1	5.4
0006210694	B-410	27.3	15.4	42.7	6.7
0006211841	B-411	25	17.9	42.8	6.7
0006211643	B-501	29.1	12.7	41.9	6.8
0006212104	B-502	32.6	10.1	42.7	6.7
0006211510	B-503	31.6	13.8	45.4	6.4
0006211353	B-504	30.1	10.8	41	6.9
0006211403	B-505	19.9	9.2	29.1	7.8
0006211460	B-506	40.2	9.3	49.5	6.2
0006211916	B-507	35.3	12.4	47.7	6.3
0006210132	B-508	30.9	10.4	41.3	6.9
0006210520	B-509	29.1	28.2	57.3	5.6
0006210728	B-510	25.3	19	44.3	6.6
0006210330-01	B-511	25.5	17.3	42.9	6.7
0006211650	B-601	30.5	17.8	48.3	6.3
0006211585	B-602	27.4	10.4	37.8	7.1
0006211528	B-603	29.9	18.5	48.3	6.3
0006211411	B-604	31.6	13.3	44.8	6.5
0006211478	B-605	39	9.6	48.5	6.3
0006211924	B-606	34.9	12.9	47.8	6.3
0006210140	B-607	31.2	10.5	41.7	6.8
0006211866	B-608	31.7	29.5	61.2	5.3
0006210736	B-609	24.9	19.9	44.9	6.5
0006212146	B-610	25.4	17.5	43	6.7
0006211668	B-701	22.1	15.1	37.1	7.2
0006210892	B-702	19.1	8	27	7.9

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006211031	B-703	30.4	16.9	47.3	6.4
0006211189	B-704	28	11.2	39.2	6.9
0006211908	B-705	35.1	13.2	48.3	6.3
0006210157	B-706	30.2	11.2	41.3	6.9
0006210538	B-707	29	28.2	57.2	5.6
0006210744	B-708	23.4	16.7	40.2	6.9
0006210348	B-709	25.9	20.4	46.2	6.4
0006211676	B-801	24	15.4	39.5	6.9
0006210900	B-802	19.5	8.6	28.1	7.9
0006211049	B-803	36	16.1	52.1	5.9
0006211197	B-804	27.8	16.7	44.5	6.6
0006211973	B-805	35.2	13.1	48.3	6.3
0006210165	B-806	30.4	11.1	41.5	6.8
0006210546	B-807	29.3	27.8	57.1	5.6
0006210751	B-808	25	13.4	38.4	7.1
0006210355	B-809	26.1	20.1	46.3	6.4
0006211684	B-901	24.3	15.5	39.8	6.9
0006210918	B-902	21.2	8.2	29.4	7.8
0006211056	B-903	36	16.1	52	5.9
0006211205	B-904	29.7	14.4	44.1	6.6
0006211981	B-905	36.8	11.7	48.5	6.3
0006210173	B-906	32.2	9.7	41.9	6.8
0006210553	B-907	31.4	22.9	54.3	5.8
0006210769	B-908	25.4	13.5	38.9	7
0006210363	B-909	28	16.3	44.4	6.6
0006211692	B-1001	26.2	14.5	40.7	6.9
0006210926	B-1002	21.2	8.1	29.4	7.8
0006211064	B-1003	35.6	16.5	52.1	5.9
0006211213	B-1004	29.6	14.5	44.1	6.6
0006211999	B-1005	36.6	11.7	48.3	6.3
0006210181	B-1006	32.3	9.9	42.1	6.8
0006210561	B-1007	31.4	22.8	54.2	5.8
0006210777	B-1008	25.5	13.3	38.8	7
0006210371	B-1009	28.2	16.3	44.4	6.6
0006211700	B-1101	26.5	14.9	41.4	6.9
0006210934	B-1102	21.3	8	29.3	7.8
0006211072	B-1103	35.1	16.7	51.8	5.9
0006211221	B-1104	28.8	14.7	43.5	6.7
0006212005	B-1105	36.1	11.8	48	6.3
0006210199	B-1106	32.5	10	42.4	6.8
0006210579	B-1107	31.7	22.1	53.9	5.8
0006210785	B-1108	25.7	13.4	39.1	6.9

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006210389	B-1109	28.4	15.9	44.3	6.6
0006211718	B-1201	26.6	14.6	41.1	6.9
0006210942	B-1202	21.2	8.5	29.8	7.7
0006211080	B-1203	34.2	17.7	51.9	5.9
0006211239	B-1204	28.3	15.3	43.7	6.7
0006212013	B-1205	35.8	12.1	47.9	6.3
0006210207	B-1206	32.4	9.7	42.1	6.8
0006210587	B-1207	31.9	22.1	54	5.8
0006210793	B-1208	25.9	13.4	39.2	6.9
0006210397	B-1209	28.6	15.9	44.4	6.6
0006211726	B-1301	26.9	14.4	41.3	6.9
0006211858	B-1302	21.1	8.1	29.1	7.8
0006211098	B-1303	32.4	18	50.4	6.1
0006211247	B-1304	27.3	15.6	42.8	6.7
0006212021	B-1305	35.6	12	47.6	6.3
0006210215	B-1306	32.2	9.7	41.9	6.8
0006210595	B-1307	32	21.8	53.7	5.9
0006210801	B-1308	25.9	12.8	38.8	7
0006210405	B-1309	28.7	15.7	44.4	6.6
0006211734	B-1401	27	14.6	41.6	6.8
0006210959	B-1402	20.8	8.3	29	7.8
0006211106	B-1403	30.6	18.2	48.9	6.2
0006211254	B-1404	25.2	15.6	40.8	6.9
0006212039	B-1405	35.2	12.5	47.7	6.3
0006210223	B-1406	32.3	9.5	41.9	6.8
0006210603	B-1407	32.3	21.6	53.9	5.8
0006210819	B-1408	26.2	12.9	39.1	6.9
0006210413	B-1409	28.7	15.7	44.4	6.6
0006211742	B-1501	27.1	14.8	41.8	6.8
0006210967	B-1502	20.3	8.7	29	7.8
0006211114	B-1503	28.1	19.3	47.5	6.3
0006211262	B-1504	23.9	15.6	39.5	6.9
0006212047	B-1505	33.7	12.6	46.4	6.4
0006210231	B-1506	32.3	9.5	41.8	6.8
0006210611	B-1507	32.4	21.4	53.9	5.8
0006210827	B-1508	26.3	13	39.3	6.9
0006210421	B-1509	29.1	15.8	44.9	6.5
0006211759	B-1601	27.2	15.2	42.4	6.8
0006210975	B-1602	19.7	8.3	28.1	7.9
0006211122	B-1603	26.6	20	46.7	6.4
0006211270	B-1604	22.2	15.9	38.1	7.1
0006212054	B-1605	32.5	12.5	45	6.5

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006210249	B-1606	31.9	9.4	41.4	6.9
0006210629	B-1607	32.6	21.2	53.8	5.9
0006210835	B-1608	26.4	12.6	39.1	6.9
0006210439	B-1609	29.2	15.5	44.8	6.5
0006211767	B-1701	27.4	15.2	42.5	6.8
0006210983	B-1702	19.2	8.5	27.7	7.9
0006211130	B-1703	24.7	20.9	45.7	6.4
0006211288	B-1704	20.6	15.8	36.4	7.2
0006212062	B-1705	31	12.4	43.5	6.7
0006210256	B-1706	31.7	9.4	41.1	6.9
0006210637	B-1707	32.7	20.9	53.6	5.9
0006210843	B-1708	26.5	12.5	39	6.9
0006210447	B-1709	29.4	15.3	44.7	6.6
0006211775	B-1801	27.5	14.6	42	6.8
0006210991	B-1802	18.8	8.4	27.2	7.9
0006211148	B-1803	21.5	21	42.5	6.8
0006211296	B-1804	18.4	15.7	34.1	7.4
0006212070	B-1805	28.6	12.4	41	6.9
0006210264	B-1806	31.7	9.4	41.1	6.9
0006210645	B-1807	36	21.3	57.2	5.6
0006210850	B-1808	26.8	12.7	39.5	6.9
0006210454	B-1809	29.5	15	44.5	6.6
0006211783	B-1901	27.6	14.5	42.1	6.8
0006211007	B-1902	18.5	8.4	27	7.9
0006211155	B-1903	19.6	21.1	40.6	6.9
0006211304	B-1904	16.7	15.8	32.5	7.4
0006211890	B-1905	27.1	12.1	39.2	6.9
0006210272	B-1906	31.3	9.4	40.7	6.9
0006210652	B-1907	36.1	20.8	56.9	5.6
0006210868	B-1908	26.8	12.7	39.5	6.9
0006210462	B-1909	29.6	14.9	44.5	6.6
0006211791	B-2001	27.8	14.8	42.5	6.8
0006211015	B-2002	18.4	8.5	26.9	7.9
0006211163	B-2003	17.3	20.9	38.2	7.1
0006211312	B-2004	15	16.2	31.3	7.6
0006212088	B-2005	25.5	12.1	37.6	7.2
0006210280	B-2006	31.3	9.6	40.9	6.9
0006210660	B-2007	36.3	20.2	56.5	5.7
0006210876	B-2008	26.9	12.6	39.5	6.9
0006210470	B-2009	29.8	14.9	44.6	6.6
0006211809	B-2101	38.3	13.6	51.9	5.9
0006211023	B-2102	28.2	8.1	36.3	7.2

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006211171	B-2103	31.9	24.8	56.7	5.6
0006211320	B-2104	22.9	17.3	40.2	6.9
0006212096	B-2105	31.7	13.7	45.4	6.4
0006210298	B-2106	41.2	10.5	51.7	5.9
0006210678	B-2107	45.3	21.9	67.2	4.9
0006210884	B-2108	37.1	14.5	51.6	5.9
0006210488	B-2109	38.2	18	56.2	5.7
0006201388	C-101	16.8	6	22.8	8.3
0006201370	C-102	15.6	5.5	21.1	8.4
0006201396	C-103	17.2	2.4	19.7	8.6
0006201404	C-104	16	6	22	8.4
0006201412	C-105	39.1	4.9	44	6.6
0006201420	C-106	45.4	3.9	49.3	6.2
0006201438	C-107	26.2	5.2	31.4	7.6
0006201446	C-108	16.4	5.6	22	8.4
0006201453	C-109	35.1	4.5	39.5	6.9
0006201461	C-110	26.9	10.8	37.6	7.1
0006201479	C-111	26.7	13.6	40.3	6.9
0006201487	C-112	24.9	22.4	47.2	6.4
0006201495	C-201	9.2	11.6	20.8	8.4
0006201503	C-202	8.3	9.9	18.2	8.7
0006201511	C-203	8.2	3.4	11.6	9.3
0006201529	C-204	6.6	10.2	16.8	8.8
0006201537	C-205	29.3	5.4	34.7	7.4
0006201545	C-206	35	5.1	40.1	6.9
0006201552	C-207	23.7	2.9	26.6	7.9
0006201560	C-208	2.4	8.4	10.9	9.4
0006201578	C-209	28.5	7.2	35.7	7.3
0006201586	C-210	10.6	13.6	24.2	8.2
0006201594	C-211	13.8	17.5	31.3	7.6
0006201602	C-212	18.2	24.3	42.5	6.8
0006201610-01	C-301	10.1	8.2	18.3	8.7
0006201628	C-302	9.5	6.1	15.6	8.9
0006201636	C-303	9.9	2.9	12.8	9.2
0006201644	C-304	8.5	8.2	16.7	8.8
0006201651	C-305	32.6	4.7	37.3	7.2
0006201669	C-306	36.9	3.8	40.6	6.9
0006201677	C-307	34.4	3.2	37.6	7.2
0006201685	C-308	3.8	7.1	10.9	9.4
0006201693	C-309	31.8	6.4	38.2	7.1
0006201701	C-310	14	7.1	21.2	8.4
0006201719	C-311	16.4	13.6	30	7.7

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006201727	C-312	18.8	23.4	42.2	6.8
0006201842-01	C-401	11.6	8.8	20.4	8.4
0006201735	C-402	11	6.5	17.6	8.8
0006201743	C-403	10.6	2.9	13.5	9.1
0006201750	C-404	9.5	8.9	18.4	8.7
0006201768	C-405	33.1	4.9	38	7.1
0006201776-01	C-406	39.4	3.9	43.3	6.7
0006201784	C-407	34.5	3.9	38.5	7.1
0006201792	C-408	4.4	6.9	11.4	9.3
0006201800	C-409	32.3	6.1	38.4	7.1
0006201818	C-410	16	7.8	23.8	8.2
0006201826	C-411	18.2	15.7	33.9	7.4
0006201834	C-412	20.7	25.2	45.9	6.4
0006203186	C-501	12.9	9.3	22.2	8.4
0006201859	C-502	12.5	7.1	19.6	8.6
0006201867	C-503	12.9	3.2	16	8.9
0006201875	C-504	13.3	10	23.4	8.3
0006201883	C-505	42.9	6.8	49.7	6.2
0006203160	C-506	39.3	4.8	44.1	6.6
0006201891	C-507	36	3.8	39.8	6.9
0006201909	C-508	4.6	6.9	11.4	9.3
0006201917	C-509	44.2	8.1	52.3	5.9
0006201925	C-510	24.3	10.1	34.5	7.4
0006201933	C-511	26.9	15.4	42.2	6.8
0006201941	C-512	21.4	25.7	47.1	6.4
0006201958	C-601	15.7	6	21.7	8.4
0006201966	C-602	16.1	7.4	23.5	8.3
0006201974	C-603	28.2	6.5	34.7	7.4
0006201982	C-604	15.1	6.6	21.7	8.4
0006201990	C-605	24.1	6.6	30.7	7.7
0006202006	C-606	41.1	4.8	45.8	6.4
0006202014	C-607	35.2	3.6	38.8	7
0006202022	C-608	21.4	22.2	43.6	6.7
0006202030-01	C-609	37.5	6.3	43.8	6.7
0006202048	C-610	20.9	21.2	42.1	6.8
0006202055-01	C-701	13.9	6.4	20.3	8.4
0006202063	C-702	13.1	7.9	21	8.4
0006202071	C-703	14	8	22	8.4
0006202089	C-704	15.3	6.8	22.1	8.4
0006202097	C-705	19.6	7.2	26.7	7.9
0006202105	C-706	41.3	6	47.3	6.4
0006202113	C-707	34.1	3.8	37.8	7.1

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006202121	C-708	21.6	23.7	45.3	6.4
0006203152	C-709	23.4	8.9	32.3	7.4
0006202139	C-710	18.9	23.4	42.3	6.8
0006203178	C-801	14.2	6.3	20.5	8.4
0006202147	C-802	13.4	7.7	21.1	8.4
0006202154	C-803	14.2	7.8	22	8.4
0006202162	C-804	15.2	6.7	21.9	8.4
0006202170	C-805	19.4	7.6	27	7.9
0006202188	C-806	41.5	5.8	47.3	6.4
0006202196	C-807	34.1	3.7	37.8	7.1
0006202204	C-808	21.8	23.5	45.3	6.4
0006202212	C-809	23.5	9	32.5	7.4
0006202220	C-810	19.1	23.1	42.3	6.8
0006202238	C-901	14.2	6.3	20.5	8.4
0006202246	C-902	13.8	7.7	21.5	8.4
0006202253	C-903	14.6	8	22.6	8.3
0006202261	C-904	15.9	6.8	22.7	8.3
0006202279	C-905	19	7.7	26.7	7.9
0006202287-01	C-906	41.7	5.9	47.6	6.3
0006202295	C-907	34.3	3.7	38	7.1
0006202303	C-908	22.1	23.3	45.4	6.4
0006202311	C-909	23.8	9	32.8	7.4
0006202329	C-910	19.4	22.9	42.3	6.8
0006202337	C-1001	15.9	5.9	21.9	8.4
0006202345	C-1002	15	7.2	22.2	8.4
0006202352	C-1003	14.7	8	22.7	8.3
0006202360	C-1004	15.6	6.8	22.4	8.4
0006202378	C-1005	19.7	7	26.6	7.9
0006203194	C-1006	43.4	5.2	48.7	6.2
0006202386	C-1007	35.9	3.5	39.4	6.9
0006202394	C-1008	22.2	23	45.2	6.4
0006202402	C-1009	25.6	7.9	33.5	7.4
0006202410	C-1010	21.3	21.1	42.4	6.8
0006202428	C-1101	16	5.8	21.9	8.4
0006202436	C-1102	15.2	7.2	22.5	8.3
0006202444	C-1103	18.7	7.6	26.3	7.9
0006202451	C-1104	15.7	6.9	22.7	8.3
0006202469	C-1105	18.8	6.8	25.6	8.1
0006202477	C-1106	43.4	5.2	48.6	6.2
0006202485	C-1107	35.8	3.6	39.4	6.9
0006202493	C-1108	23.6	20.4	44	6.6
0006202501	C-1109	25.7	7.9	33.5	7.4

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006202519	C-1110	21.5	21	42.4	6.8
0006202527	C-1201	16.3	5.8	22.1	8.4
0006202535	C-1202	15.3	7	22.3	8.4
0006202543	C-1203	19.2	7.5	26.6	7.9
0006202550	C-1204	15.7	6.8	22.5	8.3
0006202568	C-1205	20.5	7.7	28.2	7.9
0006202576	C-1206	42.9	5.5	48.4	6.3
0006202584	C-1207	35.8	3.4	39.2	6.9
0006202592	C-1208	23.8	20.2	44	6.6
0006202600	C-1209	25.9	7.7	33.5	7.4
0006202618	C-1210	21.8	20.9	42.7	6.7
0006202626	C-1301	16.4	5.8	22.2	8.4
0006202634	C-1302	15.4	6.9	22.3	8.4
0006202642	C-1303	19.3	7.3	26.6	7.9
0006202659	C-1304	15.4	7	22.4	8.3
0006202667	C-1305	18.4	7.6	26.1	7.9
0006202675	C-1306	42.5	5.7	48.2	6.3
0006202683	C-1307	35.6	3.5	39.1	6.9
0006202691	C-1308	23.9	20.1	43.9	6.6
0006202709	C-1309	26	7.7	33.7	7.4
0006202717	C-1310	21.9	21.1	42.9	6.7
0006202725	C-1401	16.5	5.6	22.1	8.4
0006202733	C-1402	15.6	6.8	22.4	8.4
0006202741	C-1403	19.3	7.2	26.5	7.9
0006202758	C-1404	15	6.9	21.9	8.4
0006202766	C-1405	18.4	8.1	26.4	7.9
0006202774	C-1406	42.3	6.5	48.8	6.2
0006202782	C-1407	35.4	3.6	39	7
0006202790	C-1408	22.2	18.9	41.1	6.9
0006202808	C-1409	26.1	7.6	33.7	7.4
0006202816	C-1410	29.4	24.1	53.5	5.9
0006202824	C-1501	10.5	5.4	15.9	8.9
0006202832	C-1502	15.7	6.7	22.4	8.3
0006202840	C-1503	19.4	7.3	26.7	7.9
0006202857	C-1504	14.6	7	21.6	8.4
0006202865	C-1505	18	8.6	26.5	7.9
0006202873	C-1506	41.9	6.7	48.6	6.3
0006202881	C-1507	35	3.9	39	7
0006202899	C-1508	29.2	6.2	35.4	7.3
0006202907	C-1509	25.8	5.3	31.1	7.6
0006202915	C-1510	11.5	7.2	18.7	8.7
0006202923	C-1601	10.6	5.3	15.9	8.9

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006202931	C-1602	15.9	6.6	22.4	8.3
0006202949	C-1603	19.5	7.2	26.7	7.9
0006202956	C-1604	13.8	6.9	20.7	8.4
0006202964	C-1605	16.8	9	25.8	8
0006202972	C-1606	41.5	6.6	48.1	6.3
0006202980	C-1607	34.4	3.9	38.3	7.1
0006202998	C-1608	29	6.2	35.2	7.3
0006203004	C-1609	24.2	6.2	30.4	7.7
0006203012	C-1610	11.6	6.9	18.5	8.7
0006203020	C-1701	21.3	7.2	28.5	7.8
0006203038	C-1702	26	8.8	34.9	7.3
0006203046	C-1703	29.9	8.6	38.5	7.1
0006203053	C-1704	21.6	9.6	31.2	7.6
0006203061	C-1705	25.5	10.5	36	7.3
0006203079	C-1706	45	9.4	54.4	5.8
0006203087	C-1707	42.7	4.9	47.7	6.3
0006203095	C-1708	37.6	8.4	45.9	6.4
0006203103	C-1709	37.2	8.5	45.7	6.4
0006203111	C-1710	21.3	9.6	30.9	7.6
0006203541	D001	42.6	9.4	52	5.9
0006203558-01	D002	26.5	10.5	36.9	7.2
0006203566-01	D003	31.9	17.6	49.5	6.2
0006203574-01	D-101	29.9	7.7	37.6	7.2
0006203582-01	D-102	28.1	11.6	39.7	6.9
0006203590-01	D-103	34.6	13.4	48	6.3
0006203608-01	D-104	39.3	10.1	49.5	6.2
0006203616-01	D-105	29.9	12.4	42.3	6.8
0006203624-02	D-106	20.1	14	34.1	7.4
0006203632-01	D-107	34.5	10.4	44.9	6.5
0006203640-01	D-108	32.8	10.3	43.1	6.7
0006203657-01	D-201	37.4	8.6	46	6.4
0006203665-01	D-202	37.8	9.9	47.8	6.3
0006203673-01	D-203	28.3	8.4	36.7	7.2
0006203681-01	D-204	25.6	14	39.6	6.9
0006203699-01	D-205	23.7	15.8	39.5	6.9
0006203707-01	D-206	28.2	12.2	40.4	6.9
0006203715-01	D-207	21.4	13.6	35	7.3
0006205322	D-208	16.5	14.9	31.3	7.6
0006203723-01	D-209	23.8	12.7	36.5	7.2
0006203731-01	D-210	34	10	44	6.6
0006203749-01	D-301	23.5	9.2	32.6	7.4
0006203756-01	D-302	26.4	12.1	38.5	7.1

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006203764-01	D-303	23.2	10	33.2	7.4
0006203772-01	D-304	15.8	17	32.9	7.4
0006203780-01	D-305	27.6	12.6	40.2	6.9
0006203798-02	D-306	26.2	9.5	35.7	7.3
0006203806-01	D-307	24.9	10.8	35.7	7.3
0006203814-01	D-308	19.3	11.3	30.7	7.7
0006203822-01	D-309	24.2	13.1	37.2	7.2
0006203830-01	D-310	34.5	9.7	44.2	6.6
0006203848-01	D-401	26.1	7.3	33.4	7.4
0006203855-01	D-402	28.2	9.1	37.4	7.2
0006203863-01	D-403	25.7	8	33.7	7.4
0006203871-01	D-404	17.7	15.2	32.9	7.4
0006203889-01	D-405	28.1	12.4	40.5	6.9
0006203988-02	D-406	30.3	9.8	40.1	6.9
0006203897-01	D-407	25.3	10.8	36.1	7.3
0006203905-01	D-408	19.7	11.1	30.8	7.7
0006203913-01	D-409	27	11.5	38.5	7.1
0006203921-01	D-410	38.1	8.1	46.2	6.4
0006203939-01	D-501	39.7	9	48.8	6.2
0006203947-01	D-502	41.3	11.4	52.7	5.9
0006203954-01	D-503	36	9.4	45.4	6.4
0006203962-01	D-504	16.4	14	30.3	7.7
0006203970-01	D-505	28.5	12.3	40.8	6.9
0006205330	D-506	27.3	9.1	36.4	7.2
0006203996-01	D-507	25.4	10.8	36.2	7.3
0006204002-01	D-508	20.1	10.8	30.9	7.6
0006204010-01	D-509	30.1	12.9	43	6.7
0006204028-01	D-510	41.4	8.6	50	6.1
0006204036-01	D-601	22.2	11.1	33.3	7.4
0006204044-01	D-602	34.7	13.5	48.2	6.3
0006204051-01	D-603	29	11.4	40.3	6.9
0006204069-01	D-604	29	14.7	43.7	6.7
0006204077-01	D-605	29.1	14.7	43.8	6.6
0006204085-01	D-606	22.7	11	33.7	7.4
0006204093-01	D-607	20.3	10.7	31	7.6
0006204101-01	D-608	24.6	9.6	34.2	7.4
0006204119-01	D-609	31.5	13.9	45.4	6.4
0006204127-01	D-701	25.8	9	34.8	7.4
0006204135-01	D-702	39.8	12.7	52.4	5.9
0006204143-01	D-703	31	11.6	42.7	6.7
0006204150-01	D-704	29.2	14.5	43.7	6.7
0006204168-01	D-705	31.3	14.3	45.6	6.4

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006204176-01	D-706	21.9	10.9	32.8	7.4
0006204184-01	D-707	22.9	11.9	34.7	7.4
0006204192-01	D-708	25.6	14	39.5	6.9
0006204200-01	D-709	27.1	12.8	40	6.9
0006204218-01	D-801	26.2	9	35.2	7.3
0006204226-01	D-802	40.1	12.8	52.8	5.9
0006204234-01	D-803	31.2	11.7	42.9	6.7
0006204242-01	D-804	29	14.4	43.4	6.7
0006204259-01	D-805	28.3	14.6	42.9	6.7
0006204267-01	D-806	21.8	11	32.8	7.4
0006204275-01	D-807	22.8	11.7	34.5	7.4
0006204283-01	D-808	25.9	14	39.9	6.9
0006204291-01	D-809	27.4	12.5	40	6.9
0006204309	D-901	26.5	8.9	35.4	7.3
0006204317	D-902	40.1	13.2	53.3	5.9
0006204325	D-903	31	11.8	42.8	6.7
0006204333	D-904	28.6	14.4	43	6.7
0006204341	D-905	28.4	14.4	42.8	6.7
0006204358	D-906	21.9	11	32.9	7.4
0006204366	D-907	22.6	11.5	34.1	7.4
0006204374	D-908	26.1	14.1	40.1	6.9
0006204382	D-909	27.7	12.2	39.9	6.9
0006204390	D-1001	25.4	8.8	34.2	7.4
0006204408	D-1002	41.3	12	53.3	5.9
0006204416	D-1003	28.8	10	38.9	7
0006204424	D-1004	29.8	12.8	42.7	6.7
0006204432	D-1005	30.1	13.5	43.5	6.7
0006204440	D-1006	26.2	9.9	36.1	7.3
0006204457	D-1007	23.8	10.7	34.4	7.4
0006204465	D-1008	27.7	12.8	40.5	6.9
0006204473	D-1009	29.6	11.1	40.7	6.9
0006204481	D-1101	25.5	8.8	34.3	7.4
0006204499	D-1102	41	12	53	5.9
0006204507	D-1103	28.3	10.2	38.5	7.1
0006204515	D-1104	27.6	12.9	40.6	6.9
0006204523	D-1105	28.7	13.4	42.2	6.8
0006204531	D-1106	23.5	9.8	33.2	7.4
0006204549	D-1107	23.1	10.7	33.8	7.4
0006204556	D-1108	28	12.8	40.8	6.9
0006204564	D-1109	29.9	11.1	41	6.9
0006204572	D-1201	25.7	8.7	34.4	7.4
0006204580	D-1202	40	11.9	51.9	5.9

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006204598	D-1203	28	10.4	38.4	7.1
0006204606	D-1204	27.5	12.8	40.3	6.9
0006204614	D-1205	27.6	13.6	41.2	6.9
0006204622	D-1206	23.1	10.2	33.3	7.4
0006204630	D-1207	22.8	10.7	33.5	7.4
0006204648	D-1208	28.1	12.8	40.9	6.9
0006204655	D-1209	30	11	41	6.9
0006204663	D-1301	26.1	8.4	34.5	7.4
0006204671	D-1302	40	13	53	5.9
0006204689	D-1303	34.8	12.6	47.4	6.3
0006204697	D-1304	27.4	12.8	40.3	6.9
0006204705	D-1305	26.3	13.7	40	6.9
0006204713	D-1306	22.2	9.7	31.9	7.5
0006204721	D-1307	16.5	9.4	25.9	8
0006204739	D-1308	28.3	12.8	41.1	6.9
0006204747	D-1309	30.3	11.1	41.4	6.9
0006204754	D-1401	26.4	8.4	34.8	7.3
0006204762	D-1402	38	12.9	50.9	6
0006204770	D-1403	33.5	12.8	46.2	6.4
0006204788	D-1404	25.9	12.6	38.5	7.1
0006204796	D-1405	25	13.7	38.7	7
0006204804	D-1406	20.4	9.7	30.1	7.7
0006204812	D-1407	15.3	9.4	24.7	8.2
0006204820	D-1408	28.4	12.8	41.2	6.9
0006204838	D-1409	30.4	10.6	41	6.9
0006204846	D-1501	26.5	8.2	34.7	7.4
0006204853	D-1502	35.4	13.6	49	6.2
0006204861	D-1503	31.3	12.9	44.2	6.6
0006204879	D-1504	26.4	13.1	39.4	6.9
0006204887	D-1505	24.2	13.5	37.7	7.1
0006204895	D-1506	19.9	9.4	29.3	7.8
0006204903	D-1507	15	9.3	24.3	8.2
0006204911	D-1508	28.5	12.7	41.3	6.9
0006204929	D-1509	30.5	10.6	41.1	6.9
0006204937	D-1601	26.6	8.4	35	7.3
0006204945	D-1602	33.6	14.7	48.2	6.3
0006204952	D-1603	29.2	13.3	42.6	6.8
0006204960	D-1604	24.2	12.8	37	7.2
0006204978	D-1605	22	13.6	35.6	7.3
0006204986	D-1606	18.7	9.4	28.1	7.9
0006204994	D-1607	15	9.3	24.3	8.2
0006205009	D-1608	28.7	12.7	41.3	6.9

Certificate number and link	Unit Number	Heating load (MJ/m /p.a.)	Cooling load (MJ/m /p.a.)	Total load (MJ/m /p.a.)	Star rating
0006205017	D-1609	30.7	11.1	41.7	6.8
0006205025	D-1701	24.9	7.9	32.8	7.4
0006205033	D-1702	28.6	14	42.6	6.7
0006205041	D-1703	23.7	12.8	36.6	7.2
0006205058	D-1704	22.7	12.7	35.3	7.3
0006205066	D-1705	20.3	13.7	33.9	7.4
0006205074	D-1706	16.9	9.4	26.2	7.9
0006205082	D-1707	14.8	9.4	24.2	8.2
0006205090	D-1708	28.9	12.6	41.5	6.8
0006205108	D-1709	30.9	10.7	41.6	6.8
0006205116	D-1801	24.9	8	32.9	7.4
0006205124	D-1802	28	13.5	41.6	6.8
0006205132	D-1803	24.1	13.2	37.3	7.2
0006205140	D-1804	30.2	12.8	43	6.7
0006205157	D-1805	20	13.9	33.9	7.4
0006205165	D-1806	29	10.5	39.6	6.9
0006205173	D-1807	28	9.7	37.7	7.1
0006205181	D-1808	42.2	15.6	57.8	5.5
0006205199	D-1809	45.4	13.1	58.5	5.4
0006205207	D-1901	34.9	9.3	44.3	6.6
0006205215	D-1902	36.4	10.7	47.1	6.4
0006205223	D-1903	24.2	15.9	40.2	6.9
0006205231	D-1904	23.6	18.5	42.1	6.8
0006205249	D-1905	20.1	14.3	34.4	7.4
0006205256	TW001	19.8	17.9	37.8	7.1
0006205264	TW002	9.9	21.4	31.3	7.6
0006205272	TW003	24.7	14	38.7	7
Average		25.41	12.50	37.90	7.09

Explanatory Notes

About this report

This summary rating is the average rating of all NCC Class 2 dwellings in a development. The individual dwellings' ratings are a comprehensive, dynamic computer modelling evaluation of a home, using the floorplans, elevations and specifications to estimate the energy load. It addresses the building layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings), but does not cover the water or energy use of appliances, or energy production of solar panels. For more details about an individual dwelling's assessment, refer to the individual dwelling's NatHERS Certificate (accessible via link).

Accredited Assessors

To ensure the NatHERS Certificate is of a high quality, always use an accredited or licenced assessor. NatHERS accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO). AAOs have specific quality assurance processes in place, and continuing professional development requirements, to maintain a high and consistent standard of assessments across the country.

Any questions or concerns about this report should be directed to the assessor in the first instance. If the assessor is unable to address these questions or concerns, the AAO specified on the front of this certificate should be contacted.

Disclaimer

The format of the NatHERS Certificate was developed by the NatHERS Administrator. However the content, input and creation of the NatHERS Certificate is by the assessor. It is the responsibility of the assessor who prepared this certificate to use NatHERS accredited software correctly.

and follow the NatHERS Technical Notes to produce a NatHERS Certificate.