



Prepared for:

The Trust Company (Australia) Limited

ATF WH Redfern Trust

Site Location:

104-116 Regent Street

Prepared by:

RPS Australia East

Level 13
255 Pitt Street
Sydney
NSW 2000 Australia

Telephone: +61 2 8099 3200

ABN: 44 140 292 762

rpsgroup.com

© RPS 2021

The information contained in this document produced by RPS is solely for the use of WEEHUR

Pty Ltd for the purpose for which it has been prepared and RPS undertakes no duty to or accepts
any responsibility to any third party who may rely upon this document.

All rights reserved. No section or element of this document may be removed from this document, reproduced, electronically stored or transmitted in any form without the written permission of RPS.

1.0 DESIGN INTENT

1.1 Design Intent	0
1.2 Connection to Country	0
1.3 Designing with Country Principles	0
1.1 Site Design Drivers	0
2.0 DESIGN RESPONSE	
2.0 15-23 Approved scheme	0
2.1 Ground plan	1
2.2 Through site link detail	1
2.3. Level 2 - Recreational Deck	1
2.4 Level 4 - Sky lounge	1
2.6 Level 6 - Sky Park	1
2.7 Section	1
2.8 Indicative Image	1
2.9 Facade planting	1
2.10 Planting Strategy	1
2.11 Tree Plan	1
2.12 Material Strategy	2
2.13 Typical Details	2
2.14 Mainteanance Strategy	2





1.2 COUNTRY CONNECTIONS


A number of swamps and small waterlines were located within the low-lying areas of the undulating dune landform in the region surrounding the development site.

Historical sources suggest there was a large swamp to the east, where Redfern Park is today, known as Boxley's Lagoon. Blackwattle Creek and Blackwattle Swamp were also located to the northwest of the site.


Many of the swamps in the area would have fed into Shea's Creek (Alexandra Canal) approximately 1.8 kilometres (km) to the southwest of the site, which is a tributary to Cooks River.

Gadi land extends from Burrawara (South Head) through to Warrane (Sydney Cove), Gomora (Cockle Bay-Darling Harbour) and possibly to Blackwattle Creek, taking in the wetland sand and dunes now known as Redfern, Erskineville, Surry Hills and Paddington, down to the Cook's River.

The Gadigal (Cadigal) are a harbour-dwelling saltwater people. The suffix 'gal' denotes 'people of', and Cadi (gadi) may be the name of the grass trees (Xanthorrhoea species), the flower stalks being used as spear shafts. Another theory is that Cadi is the name of the freshwater creek at Camp Cove, others suggest that it may be Kutti the traditional name of what is now called Watson's Bay.



https://eveleighstories.com.au/stories/indigenous-place/indigenous-connections



Coopers Distillery on Black Wattle Swamp Creek, 1868



Sydney Parkland



Balga / Xanthorrhoea



Lost Waterways



Fishing Tools


1.3 DESIGNING WITH COUNTRY







LEARNING FROM COUNTRY





BUILDING RELATIONSHIPS WITH WATER





PLACES FOR SHARING & MEETING

1.4 SITE DESIGN DRIVERS

















ACCESSIBILITY


SUSTAINABLE SYSTEMS

GREENER PLACES


INTEGRATED ART





2.0 15-23 GIBBONS ST - APPROVED PLANS



2.1 PROPOSED GROUND PLAN










1 Decorative weaving brick pattern







2.2 PROPOSED GROUND PLAN - PUBLIC DOMAIN



2.3 LEVEL 2 - RECREATIONAL DECK

General + EX 0.000 Existing surface level Property boundary + TW 0.000 Top of wall + TS 0.000 Top of seat


Grading

+ 0.000 Relative surface level


1:14 Indicates direction of Inclining gradient on


Indicates direction of declining gratient


Softscape Planting area PLTR 1 On Grade PLTR 2 Planting area 2 On Slab




Pavement type 4
City of Sydney Footpath













2.5 LEVEL 4

General + TS 0.000 Top of seat

Grading + EX 0.000 Existing surface level

+ 0.000 Relative surface level + TW 0.000 Top of wall

1:14 Indicates direction of Inclining gradient on ramp 1:50 Indicates direction of declining gratient Softscape

Existing tree To be removed

Planting area PLTR 1 On Grade

Planting area 2
PLTR 2 On Slab Gravel to Planting area

Walls Wall type 1 W1 Insity Concrete Wall

Pavement

Pavement type 1
P1 Brick Decorative Pavement

Pavement type 2
P2 City Of Sydney Bridge Detail

Pavement type 3 Brick Pavers on Slab

Pavement type 4
City of Sydney Footpath

Pavement type 1A P1A Sandstone Inlay

Furniture Sandstone Seat type 1
Sandstone Seat type 1

_Integrated Concrete Seat S2

TG-1 City of Sydney Tree Grate


Table type 1

— = ⊤₁ **= —** Trellis type 1

2 PLTR-2 Podium planter - 1000mm depth

1 S2 - Seating edges and sun lounges










2.6 LEVEL 16 SKY PARK

General Property boundary

Grading





+ TW 0.000 Top of wall


+ TS 0.000 Top of seat

1:14 Indicates direction of Inclining gradient on

< 1:50 Indicates direction of declining gratient








Softscape



Pavement





Pavement type 2
City Of Sydney Bridge Detail Pavement type 3 Brick Pavers on Slab

P4 Pavement type 4
City of Sydney Footpath

Furniture

S2

Sandstone Seat type 1
Seating

Bollard Type 1

TG-1 City of Sydney Tree Grate

Table type 1

— ■T1 ■ **—** Trellis type 1

_ Integrated Concrete Seat

1 TBL - Outdoor tables fixed

2 Arbour above with climbers

3 s2 - Seating edges and sun lounges

4 Garden Lounge

5 PLTR-2 Podium planter


6 Small Shade Trees

7 BBQ bench


8 Outdoor cinema

Property Boundary

Awning Over









2.7 THOUGH SITE SECTION



1 Decorative weaving brick pattern

2 Native WSUD planting

3 Bio-Swale as per City Sydney Details

4 Livistona Palm




2.8 INDICATIVE ILLUSTRATION - P1



2.9 FACADE GREENING

- - Drip irrigation to be installed and integrated drainage
 - Maintenance can be achieved within building or outside in public realm with a cherry picker



SPECIES



Dianella revoluta Blueberry Lily

W:\PROJECTS\CONICS_SYDNEY\PR149106 - 104-116 REGENT STREET, REDFERN\C_TECHNICAL\C4_INDESIGN\C4_1_A3 REPORT\149106 LANDSCAPE REPORT.INDD



Viola hederacea Native Violet



Hardenbergia Violacea Happy Wanderer"



Cissus antarctica Kangaroo Vine



Carpobrotus glaucescens Pig face



GRC Fyto Green Planter


2.10 PLANTING PALETTE

The planting palette celebrates the native landscapes of Sydney. Species proposed are either used as tools such as weaving, provide a food source or provide environmental benefits with waterways and attracting native birds and insects




Pg 18 of 25


2.11 TREE PLAN




2.12 MATERIALITY STRATEGY




2.13 TYPICAL DETAILS





TYPICAL PLANTING DETAIL ON GROUND SCALE 1:10






TYPICAL PLANTING DETAIL SCALE 1:10






SCALE 1:20

Notes: - Mortar mix must be compatible with waterproofing system - Crossfall grades - Min 1:100 Max 1:40





01 UNIT PAVING - ON PODIUM

SCALE 1:10

02 INSITU CONCRETE - ON PODIUM

SCALE 1:10

_

GV1 - GRAVEL MULCH ON PODIUM

Notes:
Gravel mulch to cover all beams and

extrusions in the surface of the roof /

Undulations in the finished surface will not

Gravel mulch

Geotextile fabric

 Waterproofing - To Arch's Specification.

Roof slab - refer Arch.


Drainage cell


dwgs.

planter with a flat and even finish.

be accepted.

SCALE 1:10





04

SANDSTONE CUBE SEAT


SCALE 1:20

07 TYPICAL WALL
SCALE 1:20

150 x 40mm DRESSED HARDWOOD DECKING FIXED TO JOISTS WITH GALVANISED COUNTERSUNK SCREWS (FINISH FLUSH WITH SURFACE)

> BEARERS AND JOISTS To Engineers Specification

TYPICALLY 200 x 100mm HARDWOOD BEARERS AND 200 x 75mm HARDWOOD JOISTS



08


TIMBER BOARDWALK

SCALE 1:20


2.14 WIND DETAILS

LANDSCAPE STRATEGY - WIND PROTECTION


Canopy cover is extremely important in helping reduce temperatures and helping increase biodiversity. New developments often create wind tunnels that effect landscapes on podium spaces which can damage tree species in storm conditions. A series of details including guying, rootball anchoring and deep soil podium planters can help provide trees the infrastructure and stability during early establishment periods and ensuing mature vegetation will not be damaged in high wind conditions.



TREE GUYING DETAIL -SCALE 1: 20@A1



ROOT BALL ANCHOR TYPICAL -SCALE 1:10 @A1



TYPICAL PODIUM PLANTER DETAIL -SCALE 1:10

Pg 23 of 25

2.15 MAINTENANCE GUILDELINES



MINIMISING MAINTENANCE NEEDS

The maintenance of the landscape will be important to its success both in the critical establishment phase (the first 12 months) and ongoing for its life span. The reduction and practicality of ongoing maintenance requirements has been intrinsic in the design with key considerations as follows:

- Use of endemic and native species and those known to do well in the local area.
- Selection of species by their size and habit, which do not require frequent pruning to maintain their form as a hedge or to contain then within the desired planting zone.
- Species selected for each area determined based on the micro-climatic conditions, particularly in respect to sun and shade conditions.
- Selection of low water plants to reduce the need for additional watering.
- Roof water to be collected for use in irrigation to reduce the need for the use of potable water for this purpose. Automatic irrigation provided throughout the landscape areas.



MAINTENANCE SCHEDULE

The maintenance of the landscape will be undertaken by the contractor for the first 12 months to ensure successful establishment. Following this the maintenance will be taken over by a maintenance contractor.

The maintenance to be undertaken will be detailed in the landscape specification in the form of a Landscape Maintenance Plan. The Landscape Maintenance Plan will ensure the necessary scope and level of maintenance is achieved to ensure the plants remain healthy and other landscape elements are maintained in a safe, functional and attractive condition and will include the following:



SHRUB PRUNING & TRIMMING

- Tip prune shrubs and ground covers to encourage density in spring and winter. Length removed depending on vigor of previous plant growth.
- Pruning should reflect the natural growth, flowering and regrowth habit of the individual species. Generally prune after flowering. Inspect for failed or dying plants requiring replacement monthly and record probable cause.
- All plants that have died or failed (lost more than 50% of their normal foliage cover) shall be replaced with the same species and commercially available size as the plant to be replaced.
- Generally plant material shall be uniformly high quality stock equal to best available for 'retail sale'. The root systems shall be balanced in relation to the size of the plant.
- Plants shall be healthy well grown, hardened off specimens of good shape and free from pests and diseases and in accordance with 'Specifying Trees: a guide to assessment of tree quality' (Clark 2006). Should the contractor believe that alternative species should be utilised a proposal is to be put to SHMH for approval. Inspect climbers, trailing plants monthly, train leaders onto supports as required. Prune long leaders which cannot be reattached to climbing frame or mesh supports in summer.



TREE MAINTENANCE

- Inspect trees monthly during the first 12 months and annually thereafter. Ensure trees are not showing any signs of stress, adjust watering as required to ensure good health and top up mulch to specified depths as required.
- Avoid unnecessary pruning during the first three years. Prune only critical branches and remove damaged or dead wood. Remove branches that limit public access or present a safety risk.
- Lift the crown of the trees to maintain clear site lines where required to a level of 2.5m.
- Structural tree work including the removal of large branches should be undertaken by a qualified arborist with appropriate applications for the works made to Council.



TURF MAINTENANCE

- Mow turf every 2 weeks in summer, 3 weeks in Spring / Autumn and 4 weeks in winter. Mow at heights of between 40 to-60mm & remove no more than 1/3 of the leaf blade at any one time. Do not mow under wet conditions.
- Apply fertiliser at rates as recommended by manufacturer in Spring and Autumn.
 Apply fertiliser at rates as recommended by manufacturer
- Inspect for compaction and thatching in Spring. Carry out aeration treatment if required using dethatching or verticutting equipment
- Inspect for failed turf requiring replacement and record probable cause in Winter. Remove failed turf, prepare surface & lay new turf in accordance with original turf specified.



FERTILISING, SOIL IMPROVEMENT & PEST CONTROL

- Soil testing is to be undertaken at the commencement of the maintenance contract and shall include taking samples from a cross section of planting areas. Slow release fertiliser selected to take into account the soil testing results and the insitu plants should be applied annually in spring and in accordance with the manufacturer's recommended rate. Prior approval required for fertiliser use.
- Check for incidence of fungal and insect attack monthly.
- Apply appropriate treatment for fungal and insect attack if necessary subject to approval.
- Avoid use of chemical sprays. If chemical control is considered necessary, these should be mixed and applied in strict accordance with manufacturer's directions.
 Do not spray in windy or extreme weather. Prior approval required of chemical to be applied.
- Do not remove leaf litter from planted areas unless depth of litter is impacting on plant growth.



MULCHING & WEEDING

- Prevent reproduction of weeds by removal of seedlings and established weeds before seed set. This work should be carried out regularly so that the planted and mulched areas are weed free when observed at monthly intervals.
- Weed garden areas manually or with approved herbicide monthly. Prior approval required for Herbicide use. Approved Herbicide use to be in accordance with regulation rates and manufacturer's recommendation. Protect plants from overspray and avoid if rain is likely within 12 hour period
- Surface mulch is to be replenished as required, at least annually in spring, to maintain a consistent depth as specified at installation. Mulching materials to be consistent with those specified at installation.
- Plant and other litter to be removed from paths and garden areas where required.



ADJUSTMENT OF TREE STAKES & TIES

- Inspect stakes and ties monthly, replace as required. Check the straps during spring and autumn, ensuring they are loose around the tree to prevent damage to the trunk
- Remove all stakes and ties at the completion of the 12 month establishment period.

DEC 2021 STUDENT ACCOMMODATION REDFERN

Pg 24 of 25

