

21 Oct 2021

Ref: 170095 -CV-LE01-1

Matthew Giddy  
GIDDIS Project Management  
via Email mattgiddy@giddis.com.au

Suite 2.01, Level 2, 3 Horwood Place  
Parramatta NSW 2150  
02 9241 4188  
sydney@northrop.com.au

ABN 81 094 433 100

Dear Matthew ,

**Re: – 17-23 Talavera Road Macquarie Park - Realignment of Drainage Easement**

Further to our meeting with City of Ryde, held on-line on 21 October 2021 at 2pm we have summarised the options presented to Council regarding realignment of the 3.5m wide easement for drainage currently traversing the site. Three (3) alternate alignments were presented, all of which were located outside of the proposed building's footprint. The attached diagram SK100 Rev 4 details possible alternate alignments.

Option 1 which follows the alignment of an easement for drainage, benefiting Council, created in response to a development consent condition for LDA/2018/0322, will fall within the undercroft area of the proposed building. Council have stated they are not supportive of this outcome, leaving Options 2, 3, 4A and 4B as alternative alignments.

Council requested a modification to the Option 2 alignment which accommodates future works within upstream sites. Option 2 as described on the attached drawing presents the alignment meeting Council's request. Feasibility, of this alignment is still subject to review of impacts caused by existing in ground services.

Northrop has undertaken a preliminary hydraulic analysis of each option to assess viability. A summary of analysis is presented below.

Design Storm - 1%AEP 2 Hour Duration Storm (peak flow)

Design Flow -  $6.1 \text{ m}^3 / \text{s}$  (within pipe) - taken from flood report.

Tail Water - Downstream controlled, Tail water assumed to be 1% AEP flood level in Talavera Road.

Velocity in Pipe -  $1.76 \text{ m} / \text{s}$

Flow in Ø1800 -  $5.7 \text{ m}^3 / \text{s}$  - noted for comparison

Our analysis showed a similar flow capacity (or hydraulic performance) was achieved in all realignment options to that of the existing Ø1800 and caused no changed to flood behavior.

The following benefits and constraints of each option were reviewed during the meeting.

| Alignment Option | Benefit   | Constraint  |
|------------------|---|---|
| 1                | <ul style="list-style-type: none"> <li>• Shortest alignment path.</li> <li>• Avoids realignment of Sydney Water Sewer.</li> <li>• No disturbance to existing trees in northwest corner.</li> <li>• Provides equivalent hydraulic performance when compared to Ø1800 pipeline.</li> </ul>  | <ul style="list-style-type: none"> <li>• Alignment reliant on easements in private land.</li> <li>• Part of alignment located in building undercroft.</li> <li>• Trench depths of up to 6m.</li> </ul>  |
| 2                | <ul style="list-style-type: none"> <li>• Provides equivalent hydraulic performance when compared to Ø1800 pipeline.</li> <li>• Pipeline located outside of building footprint.</li> </ul>   | <ul style="list-style-type: none"> <li>• Requires removal of approx. 14 mature high value trees in northwest corner of site.</li> <li>• Adjustment of Sydney Water Sewer likely to be required.</li> <li>• Trench depths of up to 6m.</li> <li>• Alignment reliant on easements / access in private land.</li> <li>•</li> </ul> |
| 3                | <ul style="list-style-type: none"> <li>• Allows a portion of the pipeline to be located within public roadways.</li> <li>• Provides equivalent hydraulic performance when compared to Ø1800 pipeline.</li> <li>• Pipeline located outside of building footprint.</li> </ul>   | <ul style="list-style-type: none"> <li>• Requires removal of approx. 14 mature high value trees in northwest corner of site.</li> <li>• Trench depths of up to 6m.</li> <li>• Reliant on Road 1 being activated.</li> <li>• Adjustment of Sydney Water Sewer required.</li> </ul>   |
| 4A               | <ul style="list-style-type: none"> <li>• Allows a portion of the pipeline to be located within public roadways.</li> <li>• Provides equivalent hydraulic performance when compared to Ø1800 pipeline.</li> <li>• Pipeline located outside of building footprint.</li> <li>• No disturbance to 14 existing trees in northwest corner.</li> </ul>                   | <ul style="list-style-type: none"> <li>• Trench depths of up to 6m.</li> <li>• Reliant on Road 22 being activated.</li> <li>• Adjustment of Sydney Water Sewer required.</li> </ul>   |
| 4B               | <ul style="list-style-type: none"> <li>• Entire pipeline located within public roadways. (i.e., avoids easements in private land)</li> <li>• Provides equivalent hydraulic performance when compared to Ø1800 pipeline.</li> <li>• Pipeline located outside of building footprint.</li> <li>• No disturbance to 14 existing trees in northwest corner.</li> </ul> | <ul style="list-style-type: none"> <li>• Trench depths of up to 6m.</li> <li>• Reliant on Road 1 &amp; 22 being activated.</li> <li>• Adjustment of Sydney Water Sewer required.</li> </ul>   |

Council were generally in agreeance that each of the options were feasible form a hydraulic and flooding viewpoint. However, Option 3, 4A and 4B options are reliant on the future road network being dedicated to Council subject to coordination with existing services, in particular the Sydney Water sewer.

The future roadways offer a desirable outcome for Council as it allows Council infrastructure to be located wholly outside of private land.

Further consultation with Council is required as both planning and commercial matters in addition to engineering matters need to be considered before final agreement can be reached.


I trust you find this satisfactory at this stage. Feel free to discuss any aspect with me.

Yours faithfully,

A handwritten signature in blue ink that reads "S. Fryer". The signature is fluid and cursive, with a long horizontal stroke extending to the right.

**Stephen Fryer**  
Parramatta Office Leader / Principal / Civil Engineer  
BE(Civil) MIEAust CPEng NER

Attachment: Drawing SK100 Rev 4 Ø1800 Stormwater Trunk Main Realignment Options



| NOT FOR CONSTRUCTION |             |        |      |       |      |                      |           |                          |   |
|----------------------|-------------|--------|------|-------|------|----------------------|-----------|--------------------------|---|
| REV                  | DESCRIPTION | ISSUED | VERD | APP'D | DATE | CLIENT               | ARCHITECT | PROJECT                  | DRAWING TITLE                                   |
| 1                    | xx          | xx     | xx   | xx    | xx   | MAQUARIE DATA        | HDR       | IC3 SUPER WEST           | Ø1800 STORMWATER TRUNK MAIN REALIGNMENT OPTIONS |
|                      |             |        |      |       |      | JOB NUMBER<br>170095 |           | DRAWING NUMBER<br>SK-100 |   |
|                      |             |        |      |       |      | REVISION<br>4        |           | DRAWING SHEET SIZE = A1  |   |

ALL SETOUT TO ARCHITECT'S DRAWINGS. DIMENSIONS TO BE VERIFIED WITH ARCHITECT AND BUILDER BEFORE COMMENCING SHOP DRAWINGS OR SITE WORK. NORTHROP ACCEPTS NO RESPONSIBILITY FOR THE USABILITY, COMPLETENESS OR SCALE OF DRAWINGS TRANSFERRED ELECTRONICALLY.

NORTHROP

Sydney

Level 11, 345 George St. Sydney NSW 2000

T (02) 9241 4188

P.O. Box H171 Australia Square, NSW 1215

Email sydney@northrop.com.au ABN 81 094 433 100

PROJECT

IC3 SUPER WEST

DRAWING NOT TO BE USED FOR CONSTRUCTION UNLESS VERIFICATION SIGNATURE HAS BEEN ADDED

THE COPYRIGHT OF THIS DRAWING REMAINS WITH NORTHROP CONSULTING ENGINEERS PTY LTD