

ENGINEERING REPORT ON

PROPOSED EXCAVATION AND CONSTRUCTION

175-177 CLEVELAND STREET AND

6-8 WOODBURN STREET, REDFERN



Prepared by
Richard Yates BE(Hons) MIEAust CPEng NER 620330 APEC Engineer IntPE(Aus)

September 2022

Version 1

CONTENTS

	Page No.
1. INTRODUCTION	3
2. GEOTECHNICAL INVESTIGATION	4
3. RAIL TUNNEL	5
4. LOADING OVER TUNNEL	5
5. RAIL CORRIDOR	6
6. EXCAVATION	6
7. SUMMARY	7

REFERENCE DOCUMENTS

- Civil and Structural Drawings
- Survey
- Geotechnical Report
- Rail Tunnel Drawings

1. INTRODUCTION

This report has been prepared to detail the impact of the proposed development at the above address on the nearby rail corridor and tunnel works.

This report shall be read in conjunction with the structural plans prepared by James Taylor & Associates numbered 6394 S01, S09, S10, S20, S21, S25, S26.

This report has been prepared for submission with Development Application documentation.

The site at 175-177 Cleveland Street and 6-8 Woodburn Street Redfern is bounded by Cleveland Street to the North, Woodburn Street to the east and Eveleigh Street to the west. The southern boundary consists of a neighbouring property. The site slopes down from Cleveland Street in the north.

The sites are currently occupied by several masonry buildings with full site coverage.

The sites are being combined as part of the development proposal.

The proposed development works consist of the construction of a new co-living development consisting of 6 levels above a single storey basement.

2. GEOTECHNICAL INVESTIGATION

A geotechnical investigation of the site has been carried out by Environmental investigations ref R22434 GA. The site consists of shallow fill overlying clay overlying differing grades of weathered rock.

The allowable bearing pressures at the basement foundation levels is nominated as 1000KPa for distinctly weathered shale and 2000KPa for slightly weathered shale.

3. RAIL TUNNELS

The south eastern corner of site is underlain by proposed rail tunnels.

The alignment and levels of the tunnels is described on drawings 482749-280 VER 1 ASSUMED TRACK ALIGNMENT AND TUNNEL prepared by Halcrow.

Loading and easement requirements have been described on drawing 482749-281 VER1 LOADING REQUIREMENTS prepared by Halcrow.

The easement zones identified are indicated on cross sectional drawings 6394 S25, S26.

4. LOADING OVER TUNNEL

The proposed structure of the building consists of a reinforced concrete frame with concrete walls supporting concrete floor slabs.

Proposed foundations are detailed as strip footings bearing on approved natural material with an allowable bearing pressure of 1000Kpa.

The foundations extend into the easement zone 5 above the proposed tunnels. This zone allows excavation and allows bearing pressures of up to 3000KPa.

In all instances the quantum of load and applied bearing pressures are within the nominated maximum allowable amounts.

No excavation is proposed in the other easement zones. No temporary anchors are proposed within the easement zones.

5. RAIL CORRIDOR

The site is bounded to the East by Woodburn Street. Woodburn Street is bounded to the east by the rail corridor.

The rail corridor boundary is not parallel to the site boundary. Cross sectional drawings have been prepared at the two closest proximity points to the rail corridor. Refer JTA drawings 6394 S25, S26.

The distance to the tracks varies and is indicated on the cross sections.

6. EXCAVATION

A basement level is proposed to be excavated to RL16.1 on a portion of the site. The footprint of the basement excavation is limited by the extent of the rail easement that prevents excavation to the east. No basement is proposed in the south eastern quadrant of the site.

The excavation depth along the eastern side adjacent to Woodburn Street varies. At the closest proximity, the basement excavation is approximately 10m from the corridor boundary and over 25m from the nearest track.

A 45 degree zone of influence for the basement excavation has been plotted on the appropriate cross section. The zone of influence of the proposed basement excavation does not impact the rail corridor. Refer 6394 S25.

Footing excavations to bear on the weathered shale band in the south eastern quadrant of the site where no basement is planned are plotted on the attached drawings.

A 45 degree zone of influence for the proposed footing excavations has been plotted on the appropriate cross section. The zone of influence of the proposed footing excavation does not impact on the rail corridor. Refer 6394 S26.

Temporary shoring will be required around the perimeter of the basement to provide lateral restraint to Woodburn, Cleveland and Eveleigh Streets. Temporary shoring is not required to support Rail corridor land.

7. SUMMARY

In summary the proposed development at 175-177 Cleveland Street and 6-8 Woodburn Street Redfern has been detailed to avoid encroachment into easements around the rail tunnels that lie beneath the south eastern quadrant of the site. This has restricted the basement excavation extent. The zone of influence of the proposed basement does not impact on the rail corridor. The proposed basement excavation is located no closer than 25m from the nearest rail tracks.

The subject property does not abut the rail corridor.

Given the proximity of the proposed works, the potential impact on the rail corridor as a result of construction of the proposed works is assessed to be negligible.

The proposed loads imparted over the tunnel easement are within the allowable parameters. Localised excavation into Zone 5 of the easement is detailed to comply within the requirements of the easement as detailed on the rail tunnel drawings.


DOCUMENTATION OF CIVIL WORKS

PROPOSED CO-LIVING DEVELOPMENT

175-177 CLEVELAND STREET & 6-8 WOODBURN STREET, REDFERN

JAMES TAYLOR AND ASSOCIATES

SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089 A.C.N. 002 376 454
Tel: (02) 9969 1999 Email: mail@jamestaylorassociates.com.au



LOCALITY PLAN

GENERAL

- G1.

THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT DOCUMENTS INCLUDING ALL WORKING DRAWINGS, MAIN CONTRACT, SPECIFICATIONS AND WRITTEN INSTRUCTIONS AS MAY BE ISSUED PRIOR TO OR DURING THE COURSE OF CONSTRUCTION. ALL DISCREPANCIES AND VARIATIONS SHALL BE REFERRED TO THE ENGINEER BEFORE PROCEEDING WITH THE WORK.
- G2.

ALL CIVIL WORK SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF ALL RELEVANT AND CURRENT S.A.A. CODES.
- G3.

CIVIL DRAWINGS SHALL NOT BE SCALED IN ORDER TO OBTAIN DIMENSIONS. DIMENSIONS WHERE SHOWN ON CIVIL DRAWINGS SHALL BE CO-ORDINATED WITH ALL OTHER RELEVANT DRAWINGS.
- G4.

DURING CONSTRUCTION, THE STRUCTURE SHALL BE MAINTAINED IN A STABLE CONDITION AND NO PART SHALL BE OVERSTRESSED.


STORMWATER NOTES

1.
- ALL STORMWATER WORKS ARE TO BE UNDERTAKEN GENERALLY IN ACCORDANCE WITH AS 3500 (LATEST EDITION) STORMWATER DRAINAGE.
2.
- UNLESS OTHERWISE APPROVED ALL DRAINAGE PIPES SHALL BE APPROVED SPIGOT AND SOCKET RCP PIPES WITH RUBBER RING JOINTS, CLASS '2'.
3.
- ALL PIPE JUNCTIONS UP TO AND INCLUDING 450DIA AND ALL TAPERS SHALL BE VIA PURPOSE MADE FITTINGS.
4.
- THE CONTRACTOR IS TO SUPPLY AND INSTALL ALL FITTINGS AND SPECIALS INCLUDING VARIOUS PIPE ADAPTORS TO ENSURE PROPER CONNECTION TO DISSIMILAR PIPEWORK.
5.
- ALL CONNECTIONS TO EXISTING DRAINAGE PITS SHALL BE MADE IN A TRADESMAN-LIKE MANNER AND THE INTERNAL WALL OF THE PIT AT THE POINT OF ENTRY SHALL BE CEMENT RENDERED WITH A NON SHRINK EPDXY GROUT TO ENSURE A SMOOTH FINISH.
6.
- STEP IRONS AT SPACINGS OF 0.3M ARE TO BE PROVIDED IN DRAINAGE PITS MORE THAN 1.0M DEEP.
7.
- PROVIDE 3.0M LENGTH OF 100DIA SUBSOIL DRAINAGE PIPE WRAPPED IN FABRIC SOCK AT UPSTREAM END OF EACH PIT.
8.
- ALL CONCRETE USED IN DRAINAGE PITS SHALL HAVE A MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 32MPA.
9.
- THE EXCAVATED TRENCH WIDTH FOR PIPE LAYING MUST BE AT LEAST 300mm WIDER THAN THE OUTER DIAMETER OF THE PIPE. PIPES ARE TO BE LAID CENTRALLY WITHIN THE EXCAVATED TRENCH.
10.
- ALL PIPES ARE TO BE LAID ON A MINIMUM BEDDING OF 75mm OF SAND GRADED IN ACCORDANCE WITH AS 3500.3 (LATEST EDITION). BEDDING SHALL BE COMPACTED TO AT LEAST 90% OF THE MAXIMUM DRY DENSITY.
11.
- BACKFILL FOR STORMWATER PITS AND PIPES SHALL BE COMPACTED TO AT LEAST 95% (98% UNDER ROADS) OF THE MAXIMUM DRY DENSITY AND GRADED IN ACCORDANCE WITH AS 3500.3 (LATEST EDITION).
12.
- BACKFILL MATERIAL SHALL BE INSPECTED AND APPROVED BY THE SUPERINTENDENT PRIOR TO PLACING AND COMPACTION.
13.
- UNLESS OTHERWISE SPECIFIED PIPE TRENCH TO BE TYPE H2.
14.
- THE CONTRACTOR SHALL ENSURE THAT ANY EXISTING STRUCTURES LOCATED ADJACENT TO EXCAVATED TRENCHES ARE SUPPORTED OR PROTECTED TO PREVENT DAMAGE TO OR MOVEMENT OF THESE STRUCTURES
15.
- UNLESS SPECIFIED ALL DRAINAGE GRATES TO BE CLASS C HEAVY DUTY GALVANISED MILD STEEL TO AS 3996 (LATEST EDITION).
16.
- CHASES SHALL BE FORMED WHERE NECESSARY TO PREVENT SOCKETS, FLANGES OR THE LIKE FROM BEARING ON THE TRENCH BOTTOM OR THE UNDERLAY.
17.
- MATERIAL SHALL BE PLACED IN THE PIPE SURROUND IN LAYERS NOT MORE THAN 200mm LOOSE THICKNESS AND COMPACT WITHOUT DAMAGING OR DISPLACING THE PIPEWORK. CARE TO BE TAKEN IN VICINITY OF EXISTING SERVICES.
18.
- UPVC PIPES SHALL CONFORM IN ALL RESPECTS WITH THE REQUIREMENTS OF AS1254 (LATEST EDITION). THE CLASS OF PIPES SHALL BE UPVC "STORMWATER HD" DESIGNED FOR SOLVENT WELD SPIGOT AND SOCKET CONNECTION UNLESS NOTED OTHERWISE.
19.
- UPVC PIPES SHALL BE SUPPLIED WITH SUFFICIENT QUANTITIES OF SOLVENT FOR MAKING OF THE PIPE JOINTS.
20.
- UPVC PIPES SHALL BE TRANSPORTED, HANDLED AND STACKED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
21.
- UPVC PIPE LAYING SHALL BEGIN AT THE DOWNSTREAM END OF THE LINE WITH THE SOCKET END OF THE PIPE FACING UPSTREAM. WHEN THE PIPES ARE LAID, THE BARREL OF EACH PIPE SHALL BE IN CONTACT WITH THE BEDDING MATERIAL THROUGHOUT ITS FULL LENGTH.
22.
- THE UPVC PIPE ENDS SHALL BE THOROUGHLY CLEANED BEFORE THE JOINT IS MADE. JOINTING SHALL BE IN ACCORDANCE WITH THE MANUFACTURERS DIRECTIONS USING JOINTING SOLVENT AND PRIMER.

DRAWING LIST

Sheet Number	Sheet Name
C01	COVER SHEET
C05	SITE PLAN
C06	EXISTING SERVICES PLAN
C10	STORMWATER CATCHMENT PLAN - SITE
C11	STORMWATER DRAINAGE PLAN - BASEMENT
C12	PUMP OUT PIT DETAILS
C13	STORMWATER DRAINAGE PLAN - GF
C14	STORMWATER DRAINAGE PLAN - LEVEL 1
C15	STORMWATER DRAINAGE PLAN - LEVEL 2
C16	STORMWATER DRAINAGE PLAN - LEVEL 3
C17	STORMWATER DRAINAGE PLAN - LEVEL 4
C18	STORMWATER DRAINAGE PLAN - LEVEL 5
C19	STORMWATER DRAINAGE PLAN - LEVEL 6
C20	STORMWATER DRAINAGE PLAN - ROOF
C21	STORMWATER SECTIONS SHEET 1
C30	SILT & SEDIMENT CONTROL PLAN

						ARCHITECT		CLIENT		PROJECT		James Taylor & Associates		DESIGN		RY		DRAWN		HL		PROJECT NO.	
						MARK SHAPIRO ARCHITECTS		EG FUNDS MANAGEMENT		PROPOSED CO-LIVING DEVELOPMENT		Civil & Structural Consulting Engineers										6394	
						markshapiro.com.au		ADDRESS		175-177 CLEVELAND ST & 6-8 WOODBURN ST, REDFERN		SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089											
						markshapiro.com.au		LEVEL 21, GOVERNOR PHILLIP TOWER,				A.B.N. 33 102 603 558											
						PHONE 0421 996 467		1 FARRER PLACE, SYDNEY, 2000				TEL: 02 9969 1999		EMAIL: mail@jamestaylorassociates.com.au									
HL BY		R.Y. CHKD		FOR DA DESCRIPTION		14.09.2022 DATE		A REV														DRAWING NO.	
																						REV	
																						C01	
																						A	



STORMWATER CATCHMENT PLAN - SITE

SCALE 1 : 100 @A1

Diagram illustrating the layout of the roof and ground areas, showing five distinct regions:

- ROOF 1 AREA
- ROOF 2 AREA
- ROOF 3 AREA
- PLANTER AREA
- GROUND AREA
- EXTERNAL GROUND PAVED AREA

SITE A

SITE A AREA: 1062.4m²

ROOF 1 AREA: 93.1m²
ROOF 2 AREA: 403.5m²
ROOF 3 AREA: 334.0m²
TOTAL ROOF AREA: 830.6m²

PLANTER AREA ROOF 2: 153.4m²
 PLANTER AREA ROOF 3: 94.8m²
 PLANTER AREA GROUND: 65.0m²

GROUND AREA: 190.2m²

EXTERNAL GROUND PLANTER
AREA: 23.1m²

EXTERNAL GROUND PAVED
AREA: 18.5m²

SITE B

SITE B AREA: 968.0m²


ROOF 1 AREA: 301.5m²
ROOF 2 AREA: 354.4m²
ROOF 3 AREA: 111.5m²
TOTAL ROOF AREA: 767.4m²

PLANTER AREA ROOF 2: 96.5m²
PLANTER AREA ROOF 3: 19.7m²
PLANTER AREA GROUND: 89.0m²


GROUND AREA: 195.8m²

EXTERNAL GROUND PAVED
AREA: 4.8m²


[illegible]




PUMP FLOW CHART
NOT TO SCALE
USE LOWARA XYLEM DN120 PUMP



PUMP OUT PIT 7
VOLUME REQUIRED 4m³ TO SATISFY 90 MIN ARI 100 STORM.
PUMP REQUIRED LIMITED TO ARI 100 5 MIN PSD=4L/S



SECTION T-B



SECTION T-A

HL	R.Y.	FOR DA	14.09.2022	A	
BY	CHKD	DESCRIPTION	DATE	REV	

ARCHITECT
MARK SHAPIRO ARCHITECTS
markshapiro.com.au
EMAIL mark@markshapiro.com.au
PHONE 0421 996 467



CLIENT
EG FUNDS MANAGEMENT
ADDRESS
LEVEL 21, GOVERNOR PHILLIP TOWER,
1 FARRER PLACE, SYDNEY, 2000

PROJECT
PROPOSED CO-LIVING DEVELOPMENT
175-177 CLEVELAND ST & 6-8 WOODBURN ST, REDFERN
PUMP OUT PIT DETAILS

James Taylor & Associates
Civil & Structural Consulting Engineers
SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089
A.B.N. 33 102 603 558
TEL: 02 99691999 EMAIL: mail@jamestaylorassociates.com.au

DESIGN	RY	DRAWN	HL
CHKD.			
APPRD.			
SCALE	As indicated	DATE	

PROJECT NO.
6394
DRAWING NO.
C12
REV
A



LEGEND

- EXISTING SEWER PIPE
- EXISTING STORMWATER PIPE
- PROPOSED SEWER PIPE
- PROPOSED STORMWATER PIPE
- PROPOSED AGRICULTURAL DRAIN
- EXISTING PIT
- PROPOSED SEWER MANHOLE
- PROPOSED GRATED DRAIN
- PROPOSED STORMWATER PIT
- DOWNPIPE
- RAIN WATER OUTLET
- RAINWATER TANK
- ON SITE DETENTION TANK
- EXISTING LEVEL FROM SURVEY
- PROPOSED LEVEL BY ARCHITECT
- OVERLAND FLOW

NOTES:

- DP, RWO & PIT SIZES, LOCATIONS & NUMBERS INDICATIVE ONLY & SUBJECT TO FINAL ARCHITECTURAL SETOUT
- ALL WORKS TO BE IN ACCORDANCE WITH AS3500.3.2

STORMWATER DRAINAGE PLAN - LEVEL 2

SCALE 1 : 100 @A1

NOTE: PLAN IS SCHEMATIC AND SUBJECT TO DETAILED DESIGN

HL	R.Y.	FOR DA	14.09.2022	A
BY	CHKD	DESCRIPTION	DATE	REV


ARCHITECT
MARK SHAPIRO ARCHITECTS
markshapiro.com.au
EMAIL mark@markshapiro.com.au
PHONE 0421 996 467

CLIENT
EG FUNDS MANAGEMENT
ADDRESS
LEVEL 21, GOVERNOR PHILLIP TOWER,
1 FARRER PLACE, SYDNEY, 2000

PROJECT
PROPOSED CO-LIVING DEVELOPMENT
175-177 CLEVELAND ST & 6-8 WOODBURN ST, REDFERN
STORMWATER DRAINAGE PLAN - LEVEL 2

James Taylor & Associates
Civil & Structural Consulting Engineers
SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089
A.B.N. 33 102 603 558
TEL: 02 99691999 EMAIL: mail@jamestaylorassociates.com.au

DESIGN	RY	DRAWN	HL	PROJECT NO.
CHKD.				6394
APPRD.				DRAWING NO.
SCALE 1 : 100	DATE			C15
				REV A



LEGEND

EXISTING SEWER PIPE

EXISTING STORMWATER PIPE

PROPOSED SEWER PIPE

PROPOSED STORMWATER PIPE

PROPOSED AGRICULTURAL DRAIN

EXISTING PIT

PROPOSED SEWER MANHOLE

PROPOSED GRATED DRAIN

PROPOSED STORMWATER PIT

DOWNPIPE

RAIN WATER OUTLET

RAINWATER TANK

ON SITE DETENTION TANK

EXISTING LEVEL FROM SURVEY

PROPOSED LEVEL BY ARCHITECT

OVERLAND FLOW

NOTES:

- DP, RWO & PIT SIZES, LOCATIONS & NUMBERS INDICATIVE ONLY & SUBJECT TO FINAL ARCHITECTURAL SETOUT
- ALL WORKS TO BE IN ACCORDANCE WITH AS3500.3.2



STORMWATER DRAINAGE PLAN - LEVEL 3

SCALE 1 : 100 @A1

NOTE: PLAN IS SCHEMATIC AND SUBJECT TO DETAILED DESIGN

				ARCHITECT		CLIENT		PROJECT		James Taylor & Associates Civil & Structural Consulting Engineers SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089 A.B.N. 33 102 603 558 TEL: 02 99691999 EMAIL: mail@jamestaylorassociates.com.au	DESIGN	RY	DRAWN	HL	PROJECT NO.		
				MARK SHAPIRO ARCHITECTS		EG FUNDS MANAGEMENT		PROPOSED CO-LIVING DEVELOPMENT			CHKD.			6394			
				markshapiro.com.au		ADDRESS		STORMWATER DRAINAGE PLAN - LEVEL 3			APPRD.			DRAWING NO.	REV		
HL	R.Y.	FOR DA	14.09.2022	A	REV	EMAIL	mark@markshapiro.com.au	LEVEL 21, GOVERNOR PHILLIP TOWER, 1 FARRER PLACE, SYDNEY, 2000			SCALE 1 : 100	DATE			C16	A	
BY	CHKD	DESCRIPTION	DATE			PHONE	0421 996 467				COPYRIGHT: THIS DESIGN AND PLANS ARE NOT TO BE USED OR REPRODUCED WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION FROM JAMES TAYLOR AND ASSOCIATES						

A1



LEGEND

- EXISTING SEWER PIPE
- EXISTING STORMWATER PIPE
- PROPOSED SEWER PIPE
- PROPOSED STORMWATER PIPE
- PROPOSED AGRICULTURAL DRAIN
- EXISTING PIT
- PROPOSED SEWER MANHOLE
- PROPOSED GRATED DRAIN
- PROPOSED STORMWATER PIT
- DOWNPIPE
- RAIN WATER OUTLET
- RAINWATER TANK
- ON SITE DETENTION TANK
- EXISTING LEVEL FROM SURVEY
- PROPOSED LEVEL BY ARCHITECT
- OVERLAND FLOW

NOTES:

- DP, RWO & PIT SIZES, LOCATIONS & NUMBERS INDICATIVE ONLY & SUBJECT TO FINAL ARCHITECTURAL SETOUT
- ALL WORKS TO BE IN ACCORDANCE WITH AS3500.3.2

STORMWATER DRAINAGE PLAN - LEVEL 4

SCALE 1 : 100 @A1

NOTE: PLAN IS SCHEMATIC AND SUBJECT TO DETAILED DESIGN

HL	R.Y.	FOR DA	14.09.2022	A
BY	CHKD	DESCRIPTION	DATE	REV



ARCHITECT
MARK SHAPIRO ARCHITECTS
markshapiro.com.au
EMAIL mark@markshapiro.com.au
PHONE 0421 996 467

CLIENT
EG FUNDS MANAGEMENT
ADDRESS
LEVEL 21, GOVERNOR PHILLIP TOWER,
1 FARRER PLACE, SYDNEY, 2000

PROJECT
PROPOSED CO-LIVING DEVELOPMENT
175-177 CLEVELAND ST & 6-8 WOODBURN ST, REDFERN
STORMWATER DRAINAGE PLAN - LEVEL 4

James Taylor & Associates
Civil & Structural Consulting Engineers
SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089
A.B.N. 33 102 603 558
TEL: 02 99691999 EMAIL: mail@jamestaylorassociates.com.au

DESIGN	RY	DRAWN	HL	PROJECT NO.
CHKD.				6394
APPRD.				DRAWING NO.
SCALE 1 : 100		DATE		C17
				REV A



LEGEND

- EXISTING SEWER PIPE
- EXISTING STORMWATER PIPE
- PROPOSED SEWER PIPE
- PROPOSED STORMWATER PIPE
- PROPOSED AGRICULTURAL DRAIN
- EXISTING PIT
- SMH PROPOSED SEWER MANHOLE
- GD PROPOSED GRATED DRAIN
- P PROPOSED STORMWATER PIT
- DP DOWNPIPE
- RWO RAIN WATER OUTLET
- RWT RAINWATER TANK
- OSD ON SITE DETENTION TANK
- EXISTING LEVEL FROM SURVEY
- PROPOSED LEVEL BY ARCHITECT
- OVERLAND FLOW

NOTES:

- DP, RWO & PIT SIZES, LOCATIONS & NUMBERS INDICATIVE ONLY & SUBJECT TO FINAL ARCHITECTURAL SETOUT
- ALL WORKS TO BE IN ACCORDANCE WITH AS3500.3.2

STORMWATER DRAINAGE PLAN - LEVEL 6

SCALE 1 : 100 @A1

NOTE: PLAN IS SCHEMATIC AND SUBJECT TO DETAILED DESIGN

HL	R.Y.	FOR DA	14.09.2022	A	REV
BY	CHKD	DESCRIPTION	DATE		



ARCHITECT
MARK SHAPIRO ARCHITECTS
markshapiro.com.au
EMAIL mark@markshapiro.com.au
PHONE 0421 996 467

CLIENT
EG FUNDS MANAGEMENT
ADDRESS
LEVEL 21, GOVERNOR PHILLIP TOWER,
1 FARRER PLACE, SYDNEY, 2000

PROJECT
PROPOSED CO-LIVING DEVELOPMENT
175-177 CLEVELAND ST & 6-8 WOODBURN ST, REDFERN
**STORMWATER DRAINAGE PLAN -
LEVEL 6**

James Taylor & Associates
Civil & Structural Consulting Engineers
SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089
A.B.N. 33 102 603 558
TEL: 02 99691999 EMAIL: mail@jamestaylorassociates.com.au

DESIGN	RY	DRAWN	HL	PROJECT NO.
CHKD.				6394
APPRD.				DRAWING NO.
SCALE 1 : 100	DATE			C19
				REV
				A



LEGEND

- EXISTING SEWER PIPE
- EXISTING STORMWATER PIPE
- PROPOSED SEWER PIPE
- PROPOSED STORMWATER PIPE
- PROPOSED AGRICULTURAL DRAIN
- EP EXISTING PIT
- SMH PROPOSED SEWER MANHOLE
- GD PROPOSED GRATED DRAIN
- P PROPOSED STORMWATER PIT
- DP DOWNPIPE
- RWO RAIN WATER OUTLET
- RWT RAINWATER TANK
- OSD ON SITE DETENTION TANK
- + XXX.XXX EXISTING LEVEL FROM SURVEY
- + RL XX.XXX PROPOSED LEVEL BY ARCHITECT
- OVERLAND FLOW

NOTES:

- DP, RWO & PIT SIZES, LOCATIONS & NUMBERS INDICATIVE ONLY & SUBJECT TO FINAL ARCHITECTURAL SETOUT
- ALL WORKS TO BE IN ACCORDANCE WITH AS3500.3.2

STORMWATER DRAINAGE PLAN - ROOF

SCALE 1 : 100 @A1

NOTE: PLAN IS SCHEMATIC AND SUBJECT TO DETAILED DESIGN

HL	R.Y.	FOR DA	14.09.2022	A	
BY	CHKD	DESCRIPTION	DATE	REV	


ARCHITECT
MARK SHAPIRO ARCHITECTS
markshapiro.com.au
EMAIL mark@markshapiro.com.au
PHONE 0421 996 467

CLIENT
EG FUNDS MANAGEMENT
ADDRESS
LEVEL 21, GOVERNOR PHILLIP TOWER,
1 FARRER PLACE, SYDNEY, 2000


PROJECT
PROPOSED CO-LIVING DEVELOPMENT
175-177 CLEVELAND ST & 6-8 WOODBURN ST, REDFERN
STORMWATER DRAINAGE PLAN - ROOF

James Taylor & Associates
Civil & Structural Consulting Engineers
SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089
A.B.N. 33 102 603 558
TEL: 02 99691999 EMAIL: mail@jamestaylorassociates.com.au

DESIGN	RY	DRAWN	HL	PROJECT NO.	
CHKD.				6394	
APPRD.				DRAWING NO.	REV
SCALE 1 : 100		DATE		C20	A



1 Section
C13 SCALE 1 : 50 @A1




OSD PLAN
SCALE 1 : 50 @A1

OSD INFORMATION


SYDNEY WATER REQUIREMENTS
OSD VOLUME: 31m³ MIN
PSD: 74L/S

SYDNEY COUNCIL REQUIREMENTS
FOR KERB DISCHARGE
PSD: 25L/S




OSD ROOF PLAN
SCALE 1 : 50 @A1


LID 1-4: ACCESS LIDS. SEALED



GROSS POLLUTANT TRAP
NOT TO SCALE




ORIFICE PLATE
1:10



2 Section
C13 SCALE 1 : 50 @A1

OSD NOTE
OSD VOLUMES HAVE BEEN CALCULATED BASED ON CITY OF SYDNEY DCP. NO IN GROUND STORMWATER DRAINAGE IS LOCATED ADJACENT TO THE SITE IN EVELEIGH STREET. SITE LEVELS PRECLUDE FULL DRAINAGE TO CLEVELAND STREET. KERB DISCHARGE REQUIRED. COUNCIL LIMITS PSD TO 25L/S FOR AED 5% (1 IN 20 STORM). PSD CONSISTS OF OSD DISCHARGE PLUS GROUND FLOOR DRAINAGE EXCLUDING DEEP SOIL. GROUND FLOOR DRAINAGE 10L/S. OSD PSD 15L/S. OSD CONTAINS TWO CHAMBERS AND 2 ORIFICE PLATES. THE MAIN CHAMBER DISCHARGES THROUGH ORIFICE 1 LIMITING FLOW TO 15L/S UNDER THE 5% AEP STORM EVENT. THE OVERFLOW DISCHARGES INTO THE HIGH OUTPUT CHAMBER WITH ORIFICE 2 LIMITING FLOW TO 74L/S UNDER THE 1%AEP STORM EVENT AS NOMINATED BY SYDNEY WATER. OSD VOLUME OF 45 CUBIC METRES HAS BEEN CALCULATED BASED ON DRAINS MODELLING. LOWER BASEMENT DRAINAGE IS PUMPED TO THE OSD FOR DISCHARGE BASED ON A TIMED FLOAT SWITCH FOR STORM EVENTS LIMITING DISCHARGE TO HOURS AGREED BY CITY OF SYDNEY COUNCIL. THE MAIN OSD CONTAINS A FILTER CHAMBER TO REMOVE POLUTANTS. THIS CHAMBER FORMS PART OF THE OSD VOLUME.

A1																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																						</
----	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	----



LEGEND

PROPOSED STORMWATER PIPE ————

SEDIMENT FENCE ————

EXISTING PIT OR EP

PIT PROTECTION - REFER NOTE BESIDE

TEMPORARY DRIVEWAY/VEHICLE WASHDOWN







VEGETATED AREA

OVERLAND FLOW

SP SETTLEMENT POND

ST SETTLING TANK

NOTE:
PROVIDE DOWNSTREAM PROTECTION OF EXISTING STORMWATER PITS. COVER WITH GEOFABRIC & PROTECT WITH AGGREGATE. PITS TO BE INSPECTED TWICE A WEEK AND AFTER RAIN. REFER GRAVEL KERB INLET SEDIMENT TRAP DETAILS.



SILT & SEDIMENT CONTROL PLAN
SCALE 1 : 100 @A1

DOWNSTREAM PITS SHALL BE PROTECTED AS ABOVE. INSPECT WEEKLY AND AFTER HEAVY RAIN.

A1																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
----	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

DOCUMENTATION OF STRUCTURAL WORKS

PROPOSED CO-LIVING DEVELOPMENT

175-177 CLEVELAND STREET & 6-8 WOODBURN STREET, REDFERN

JAMES TAYLOR AND ASSOCIATES


SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089 A.C.N. 002 376 454

Tel: (02) 9969 1999 Email: mail@jamestaylorassociates.com.au

STRUCTURAL DRAWING LIST	
Sheet Number	Sheet Name
S01	COVER SHEET
S09	TUNNEL ALIGNMENT PLAN
S10	BULK EXCAVATION PLAN
S20	FOOTING PLAN
S21	BASEMENT PLAN
S25	SECTION 1
S26	SECTION 2

CONCRETE

- C1. ALL WORKMANSHIP AND MATERIALS SHALL BE IN ACCORDANCE WITH AS3600-2009 EXCEPT WHERE VARIED BY THE CONTRACT DOCUMENTS.
- C2. CONCRETE COMPOSITION AND CLEAR COVER TO REINFORCEMENT SHALL BE AS FOLLOWS:
- | | | |
|---------------------------------|-------------------------------|-----------|
| ELEMENT | AS 3600
f _c MPa | COVER mm. |
| FOOTINGS | 40 | 45 |
| ALL - UNO. INTERNAL
EXTERNAL | 40
40 | 25
45 |
- C3. ADMIXTURES, WHERE USED, SHALL COMPLY WITH THE REQUIREMENTS OF AS1478 AND AS1479. THESE COVER REQUIREMENTS MAY VARY DUE TO REQUIRED FIRE RESISTANCE RATING - REFER AS3600
- C3. ALL CONCRETE SUPPLY & TESTING SHALL CONFORM WITH AS1379 AND SHALL HAVE MAXIMUM SLUMP OF 80mm AND AGGREGATES IN ACCORDANCE WITH AS2758.1 TO A MAXIMUM SIZE OF 20mm
- C4. CONSTRUCTION JOINTS SHALL BE PROPERLY FORMED AND USED ONLY WHERE SHOWN ON DRAWINGS OR SPECIFICALLY APPROVED BY THE ENGINEER.
- C5. NO HOLES, CHASES OR EMBEDMENTS OF PIPES, OTHER THAN THOSE SHOWN ON THE STRUCTURAL DRAWINGS, SHALL BE MADE IN CONCRETE MEMBERS WITHOUT THE PRIOR APPROVAL OF THE ENGINEER.
- C6. ALL CONCRETE SHALL BE PLACED AND CURED IN ACCORDANCE WITH AS3600. WHERE A SURFACE CURING COMPOUND IS USED, IT MUST BE APPLIED ONTO SLABS WITHIN 2 HOURS OF FINISHING OPERATION AND ONTO WALLS AND COLUMNS IMMEDIATELY AFTER REMOVAL OF THE FORMWORK. HORIZONTAL FORMWORK SHALL BE STRIPPED WHEN APPROVED BY THE ENGINEER.
- C8. SLABS AND BEAMS SHALL BEAR ONLY ON THE BEAMS, WALLS ETC. SHOWN ON THE STRUCTURAL DRAWINGS. ALL OTHER BUILDING ELEMENTS SHALL BE KEPT 15mm CLEAR OF SOFFITS OF STRUCTURAL ELEMENTS.
- C9. COMPLETED STRUCTURAL ELEMENTS SHALL CONFORM WITH THE SHAPES, LINES, LEVELS, GRADES AND DIMENSIONS REQUIRED BY THE CONTRACT DRAWINGS.
- C10. ALL CONCRETE REINFORCEMENT SHALL CONFORM WITH AS/NZS 4671. DUCTILITY GRADE: CLASS N. NO REINFORCEMENT SHALL BE WELDED WITHOUT PRIOR APPROVAL.
- C11. R = STRUCTURAL GRADE ROUND BAR
N = "TEMPCORE" DEFORMED BAR
F = HARD DRAWN STEEL WIRE REINFORCING FABRIC
DESIGNATION CODE OF REINFORCEMENT BARS:-



- UNO - UNLESS NOTED OTHERWISE.
NSOP - NOT SHOWN ON PLAN.
LV - LENGTH VARIES.
- C12. TRANSVERSE TIE BARS N12-300, WHERE NOT OTHERWISE SHOWN, SPLICE WHERE NECESSARY AND LAP WITH MAIN BARS 400mm.
- C13. SPLICES IN REINFORCEMENT SHALL BE MADE ONLY IN POSITIONS SHOWN ON THE STRUCTURAL DRAWINGS OR IN POSITIONS OTHERWISE APPROVED IN WRITING BY THE PRINCIPAL. LAPS SHALL BE IN ACCORDANCE WITH AS3600 AND NOT LESS THAN THE DEVELOPMENT FOR EACH BAR. SITE BENDING OF REINFORCING BARS SHALL BE DONE WITHOUT HEATING USING MECHANICAL BENDING TOOLS. WELDING OF REINFORCEMENT SHALL NOT BE PERMITTED UNLESS SHOWN ON THE STRUCTURAL DRAWINGS OR APPROVED BY THE STRUCTURAL ENGINEER. FABRICS SHALL BE LAPPED 2 TRANSVERSE WIRES PLUS 50mm. BUNDLED BARS SHALL BE TIED TOGETHER AT 30 BAR DIAMETER CENTRES WITH THREE WRAPS OF TIE WIRE.
- C14. REINFORCEMENT IS SHOWN DIAGRAMMATICALLY. IT IS NOT NECESSARILY SHOWN IN TRUE ROJECTION.
- C15. ALL REINFORCEMENT SHALL BE MAINTAINED IN POSITION DURING CONCRETING.


GENERAL

- G1. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT DOCUMENTS INCLUDING ALL WORKING DRAWINGS AND SPECIFICATIONS, AND WRITTEN INSTRUCTIONS AS MAY BE ISSUED PRIOR TO OR DURING THE COURSE OF CONSTRUCTION. ALL DISCREPANCIES AND VARIATIONS SHALL BE REFERRED TO THE ENGINEER BEFORE PROCEEDING WITH THE WORK.
- G2. ALL STRUCTURAL WORK SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF ALL RELEVANT AND CURRENT S.A.A. CODES.
- G3. STRUCTURAL DRAWINGS SHALL NOT BE SCALED IN ORDER TO OBTAIN DIMENSIONS. DIMENSIONS WHERE SHOWN ON STRUCTURAL DRAWINGS SHALL BE CO-ORDINATED WITH ALL OTHER RELEVANT DRAWINGS.
- G4. DURING CONSTRUCTION, THE STRUCTURE SHALL BE MAINTAINED IN A STABLE CONDITION AND NO PART SHALL BE OVERSTRESSED.

FOUNDATION

- F1. DESIGN BEARING PRESSURE = 1000kPa (APPROVED ROCK)
- F2. FOUNDATION MATERIAL SHALL BE APPROVED FOR THE ABOVE DESIGN BEARING PRESSURE PRIOR TO CONSTRUCTION OF FOOTINGS.

					ARCHITECT MARK SHAPIRO ARCHITECTS markshapiro.com.au EMAIL mark@markshapiro.com.au PHONE 0421 996 467	CLIENT EG FUNDS MANAGEMENT ADDRESS LEVEL 21, GOVERNOR PHILLIP TOWER, 1 FARRER PLACE, SYDNEY, 2000	PROJECT PROPOSED CO-LIVING DEVELOPMENT 175-177 CLEVELAND ST & 6-8 WOODBURN ST, REDFERN	James Taylor & Associates Civil & Structural Consulting Engineers SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089 A.B.N. 33 102 603 558 TEL: 02 99691999 EMAIL: mail@jamestaylorassociates.com.au <small>COPYRIGHT: THIS DESIGN AND PLANS ARE NOT TO BE USED OR REPRODUCED WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION FROM JAMES TAYLOR AND ASSOCIATES</small>	DESIGN RY CHKD. APPRD. SCALE As indicated	DRAWN HL DATE	PROJECT NO. 6394 DRAWING NO. REV S01 A
HL	R.Y.	FOR DA	14.09.2022	A							
BY	CHKD	DESCRIPTION	DATE	REV							



TUNNEL ALIGNMENT PLAN

SCALE1 : 150 @A1

HL	R.Y.	FOR DA	14.09.2022	A
RY	CHKD	DESCRIPTION	DATE	REV

ARCHITECT
MARK SHAPIRO ARCHITECTS

markshapiro.com.au
EMAIL mark@markshapiro.com.au
PHONE 0421 996 467

CLIENT
EG FUNDS MANAGEMENT


ADDRESS
LEVEL 21, GOVERNOR PHILLIP TOWER,
1 FARRER PLACE, SYDNEY, 2000

PROJECT
PROPOSED CO-LIVING DEVELOPMENT

TUNNEL ALIGNMENT PLAN


James Taylor & Associates
Civil & Structural Consulting Engineers
SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089
A.B.N. 33 102 603 558
TEL: 02 99691999 EMAIL: mail@jamestaylorassociates.com.au

DESIGN	RY	DRAWN	HL	PROJECT NO.	
CHKD.				6394	
APPRD.				DRAWING NO.	REV
SCALE 1 : 150		DATE		S09	A



TUNNEL LEVELS AND ALIGNMENT SOURCED FROM DRAWING 482749-280 VER 1
TITLED: 175-177 CLEVELAND ST & 1-5 WOODBURN ST. CBD RAIL LINK (CBDRL).
ASSUMED TRACK & TUNNEL ALIGNMENT.
BY HALCROW PACIFIC PTY LTD
DATED 27.05.16

LOADING ZONES AND TUNNEL PROFILES SOURCED FROM DRAWING 482749-281 VER 1
TITLED: 175-177 CLEVELAND ST & 1-5 WOODBURN ST. CBD RAIL LINK (CBDRL).
LOADING REQUIREMENTS.
BY HALCROW PACIFIC PTY LTD
DATED 27.05.16



FOOTING LOADS OVER RAILWAY EASEMENT

LOAD	DEAD LOAD (KN/m)	LIVE LOAD (KN/m)	TOTAL LOAD (KN/m)	MAXIMUM ALLOWABLE BEARING PRESSURE (KPa)	FOOTING AREA (mm x mm)
1	1200	200	1400	1000	2000x2000
2	1200	200	1400	1000	1000x1000
3	500	80	580	1000	1000x1000
4	500	80	580	1000	1000x1000
5	850	150	150	1000	1000x1000
6	620	140	760	1000	1000x1000
7	650	150	800	1000	1000x1000
8	760	200	960	1000	1000x1000
9	850	150	150	1000	1000x1000
10	500	80	580	1000	1000x1000
11	600	120	720	1000	1500x600

BEAM SUPPORT CONCENTRATED LOADS FROM LEVEL 1 ABOVE

TUNNEL LEVELS AND ALIGNMENT SOURCED FROM DRAWING 482749-280 VER 1
TITLED: 175-177 CLEVELAND ST & 1-5 WOODBURN ST. CBD RAIL LINK (CBDRL).
ASSUMED TRACK & TUNNEL ALIGNMENT.
BY HALCROW PACIFIC PTY LTD
DATED 27.05.16

LOADING ZONES AND TUNNEL PROFILES SOURCED FROM DRAWING 482749-281 VER 1
TITLED: 175-177 CLEVELAND ST & 1-5 WOODBURN ST. CBD RAIL LINK (CBDRL).
LOADING REQUIREMENTS.
BY HALCROW PACIFIC PTY LTD
DATED 27.05.16

1000 WIDE FOOTING

FOOTING PLAN
SCALE 1 : 100 @A1

HL	R.Y.	FOR DA	14.09.2022	A	
BY	CHKD	DESCRIPTION	DATE	REV	

ARCHITECT
MARK SHAPIRO ARCHITECTS
markshapiro.com.au
EMAIL mark@markshapiro.com.au
PHONE 0421 996 467


CLIENT
EG FUNDS MANAGEMENT
ADDRESS
LEVEL 21, GOVERNOR PHILLIP TOWER,
1 FARRER PLACE, SYDNEY, 2000

PROJECT
PROPOSED CO-LIVING DEVELOPMENT
175-177 CLEVELAND ST & 6-8 WOODBURN ST, REDFERN
FOOTING PLAN

James Taylor & Associates
Civil & Structural Consulting Engineers
SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089
A.B.N. 33 102 603 558
TEL: 02 99691999 EMAIL: mail@jamestaylorassociates.com.au

DESIGN	RY	DRAWN	HL
CHKD.			
APPRD.			
SCALE 1 : 100		DATE	

PROJECT NO.
6394
DRAWING NO.
S20
REV
A



BASEMENT PLAN

SCALE 1 : 100 @A1

HL	R.Y.	FOR DA	14.09.2022	A	
BY	CHKD	DESCRIPTION	DATE	REV	

ARCHITECT
MARK SHAPIRO ARCHITECTS
markshapiro.com.au
EMAIL mark@markshapiro.com.au
PHONE 0421 996 467


CLIENT
EG FUNDS MANAGEMENT
ADDRESS
LEVEL 21, GOVERNOR PHILLIP TOWER,
1 FARRER PLACE, SYDNEY, 2000

PROJECT
PROPOSED CO-LIVING DEVELOPMENT
175-177 CLEVELAND ST & 6-8 WOODBURN ST, REDFERN
BASEMENT PLAN

James Taylor & Associates
Civil & Structural Consulting Engineers
SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089
A.B.N. 33 102 603 558
TEL: 02 99691999 EMAIL: mail@jamestaylorassociates.com.au

DESIGN	RY	DRAWN	HL
CHKD.			
APPRD.			
SCALE 1 : 100		DATE	

PROJECT NO.	
6394	
DRAWING NO.	REV
S21	A



- ZONE 1 EXCAVATIONS, STRUCTURES NOT PERMITTED
- ZONE 2 VERTICAL LOADING NOT ALLOWED
- ZONE 5 3000kN/m² OVER 3x3m MAX (3000KPa) AND 1000kN/m² OVER 10x10m MAX (1000KPa)

TUNNEL CROWN @ CH670 RL +8.87 m


RAIL @ CH670 RL +3.37 m

DATUM
0


1 Section
S09 SCALE 1 : 100 @A1

TUNNEL LEVELS AND ALIGNMENT SOURCED FROM DRAWING 482749-280 VER 1
TITLED: 175-177 CLEVELAND ST & 1-5 WOODBURN ST. CBD RAIL LINK (CBDRL).
ASSUMED TRACK & TUNNEL ALIGNMENT.
BY HALCROW PACIFIC PTY LTD
DATED 27.05.16

LOADING ZONES AND TUNNEL PROFILES SOURCED FROM DRAWING 482749-281
VER 1
TITLED: 175-177 CLEVELAND ST & 1-5 WOODBURN ST. CBD RAIL LINK (CBDRL).
LOADING REQUIREMENTS.
BY HALCROW PACIFIC PTY LTD
DATED 27.05.16



A Detail
S25 1 : 20 @A1



B Detail
S25 1 : 20 @A1

HL	R.Y.	FOR DA	14.09.2022	A	REV
BY	CHKD	DESCRIPTION	DATE		

ARCHITECT
MARK SHAPIRO ARCHITECTS
markshapiro.com.au
EMAIL mark@markshapiro.com.au
PHONE 0421 996 467


CLIENT
EG FUNDS MANAGEMENT
ADDRESS
LEVEL 21, GOVERNOR PHILLIP TOWER,
1 FARRER PLACE, SYDNEY, 2000

PROJECT
PROPOSED CO-LIVING DEVELOPMENT
175-177 CLEVELAND ST & 6-8 WOODBURN ST, REDFERN
SECTION 1

James Taylor & Associates
Civil & Structural Consulting Engineers
SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089
A.B.N. 33 102 603 558
TEL: 02 99691999 EMAIL: mail@jamestaylorassociates.com.au
COPYRIGHT: THIS DESIGN AND PLANS ARE NOT TO BE USED OR REPRODUCED WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION FROM JAMES TAYLOR AND ASSOCIATES

DESIGN	RY	DRAWN	HL
CHKD.			
APPRD.			
SCALE As indicated	DATE		

PROJECT NO.
6394
DRAWING NO.
S25
REV
A




2 Section
S09 SCALE 1 : 100 @A1

- ZONE 1 EXCAVATIONS, STRUCTURES NOT PERMITTED
- ZONE 2 VERTICAL LOADING NOT ALLOWED
- ZONE 5 3000kN/m² OVER 3x3m MAX (3000KPa) AND 1000kN/m² OVER 10x10m MAX (1000KPa)


TUNNEL LEVELS AND ALIGNMENT SOURCED FROM DRAWING 482749-280 VER 1
TITLED: 175-177 CLEVELAND ST & 1-5 WOODBURN ST. CBD RAIL LINK (CBDRL).
ASSUMED TRACK & TUNNEL ALIGNMENT.
BY HALCROW PACIFIC PTY LTD
DATED 27.05.16

LOADING ZONES AND TUNNEL PROFILES SOURCED FROM DRAWING 482749-281
VER 1
TITLED: 175-177 CLEVELAND ST & 1-5 WOODBURN ST. CBD RAIL LINK (CBDRL).
LOADING REQUIREMENTS.
BY HALCROW PACIFIC PTY LTD
DATED 27.05.16



C Detail
S26 1 : 20 @A1

				ARCHITECT		CLIENT		PROJECT		James Taylor & Associates		DESIGN		RY		DRAWN		HL		PROJECT NO.	
				MARK SHAPIRO ARCHITECTS		EG FUNDS MANAGEMENT		PROPOSED CO-LIVING DEVELOPMENT		Civil & Structural Consulting Engineers										6394	
				markshapiro.com.au		ADDRESS		175-177 CLEVELAND ST & 6-8 WOODBURN ST, REDFERN		SUITE 301, 115 MILITARY ROAD NEUTRAL BAY NSW 2089											
				mark@markshapiro.com.au						A.B.N. 33 102 603 558											
				0421 996 467		LEVEL 21, GOVERNOR PHILLIP TOWER,				TEL: 02 99691999		EMAIL: mail@jamestaylorassociates.com.au								DRAWING NO.	
						1 FARRER PLACE, SYDNEY, 2000														RE	
																				A	



GENERAL / SPECIFIC NOTES

THESE NOTES ARE AN INTEGRAL PART OF THIS PLAN. THE INFORMATION SHOWN ON THIS PLAN OR IN THE ASSOCIATED CAD FILE IS SUPPLIED ON THE CONDITION THAT THESE GENERAL NOTES ARE ALWAYS SHOWN/KEPT ON ANY COPY OR EXTRACT OF THE HARD COPY/DATA FILE.

LEVELS ARE BASED ON AUSTRALIAN HEIGHT DATUM (AHD) THE ORIGIN OF WHICH IS PM 46916 RL 28.577 AHD (SOURCE: SCIMS 06-07-2021).

THE LOCATION OF PROPERTY BOUNDARIES HAVE BEEN COMPILED FROM SURVEY MEASUREMENTS & REGISTERED PLANS OBTAINED FROM NSW LAND REGISTRY SERVICES & REPRESENT TITLE DIMENSIONS.

ANY CONSTRUCTION OR WORKS RELYING ON CRITICAL SETBACKS FROM BOUNDARIES WILL REQUIRE ADDITIONAL BOUNDARY SURVEY & PLACEMENT OF BOUNDARY/SETOUT MARKS PRIOR TO COMMENCEMENT OF ANY WORKS. REALSERVE WILL NOT BE HELD RESPONSIBLE FOR ANY ISSUES RESULTING FROM NON COMPLIANCE WITH THIS ADVICE.

NO EASEMENTS HAVE BEEN INVESTIGATED OR SHOWN AS PART OF TIS SURVEY.

REFER TO THE SUBJECT CERTIFICATES OF TITLE AND DEPOSITED PLANS FOR THE LOCATION & NATURE OF ANY EASEMENTS, RESTRICTIONS OR COVENANTS

THE LOCATION OF ADJOINING BUILDING/LAND FEATURES HAVE BEEN OBTAINED WHERE VISIBLE FROM THE SUBJECT PROPERTY & PUBLIC DOMAIN. ANY ADDITIONAL INFORMATION REQUIRED IS SUBJECT TO ADDITIONAL SURVEY & ACCESS BEING GRANTED TO ADJOINING PROPERTIES.

THE LOCATION & LEVELS OF BUILDING RIDGES AND ROOF FEATURES HAVE BEEN DETERMINED BY INDIRECT METHODS (WHERE VISIBLE) & ACCURATE TO APPROXIMATELY +/- 0.02m.

THE RECORDS OF THE SERVICE AUTHORITIES HAVE NOT BEEN INVESTIGATED. ONLY THOSE SERVICES VISIBLE / APPARENT AT THE TIME OF SURVEY HAVE BEEN SHOWN.

SCHEDULE OF ABBREVIATIONS

- APPROX. - APPROXIMATE
AWN - AWNING
BAL - BALCONY
BASE - BASEMENT
BIT - BITUMEN
BRW - BRICK RETAINING WALL
CO - CONCRETE
CRW - CONCRETE RETAINING WALL
DT - DOOR TOP
DW - DRIVEWAY
ELP - POWER POLE/LIGHT
FHR - FIRE HOSE REEL
FL - FLOOR LEVEL
GAS - GAS LID
GB - GUTTER BOX
HYD - HYDRANT
IK - INVERT KERB
INV - INVERT PIT
LK - LIP KERB
LM - LINE MARKING (APPROX SPACING)
MFC - METAL FENCE
MH - MANHOLE (SERVICE)
PAR - PARAPET
PP - POWER POLE
RI - ROOF RIDGE (APPROX)
ROLL - ROLLER SHUTTER
RT - ROOF TOP (APPROX.)
SLH - SEWER LAMP HOLE
SS - SIGNAGE
STR - STAIR
SV - STOP VALVE
TA - TOP AWNING
TEL - TELSTRA/COMMS LID-PIT
TG - TOP GUTTER (APPROX HEIGHT)
TK - TOP KERB (GENERALLY 0.15 HIGH)
TPG - TPG PIT
TW - TOP WALL
UA - UNDERSIDE AWNING
UC - UNCLASSIFIED SERVICES
US - UNDERSIDE STRUCTURE
WS - WINDOW SILL
WT - WINDOW TOP
1 - FIRST FLOOR
2 - SECOND FLOOR

DIRECT MEASUREMENT TO RAIL TRACKS IS INACCESSIBLE FROM THE SURROUNDING LANDS/ROADS/PUBLIC DOMAIN. RAIL TRACK LOCATION HAS BEEN INTERPOLATED FROM AERIAL IMAGERY.

David McCulloch
Registered Surveyor
Surveyor ID: 125


0 2 4 6 8
SCALE 1 : 150

<div>Australia New Zealand</div> <div>REALSERVE</div> <div>Start confident.</div>	<div>Building Measurement Specialist</div> <div>Consulting Land Surveyors</div> <div>3D Laser Scanning</div> <div>ph. 02 9629 9377</div> <div>www.realserve.com.au</div>	DATE	REV	COMMENTS	PLAN PREPARED FOR: EG FUNDS MANAGEMENT	DATUM : A.H.D	SCALE : 1:150 @ A1	DATE : 07-07-2021	DESCRIPTION: PLAN SHOWING SELECT FEATURE & LEVELS OVER LOT 1 IN DP 780307, LOT 1 DP 121029 & ADJACENT LANDS No. 6-8 WOODBURN STREET, REDFERN NSW
						ORIGIN OF LEVELS : PM 46916	LOCALITY : REDFERN	SURVEY : JP	
						CONTOUR INTERVAL : N/A	L.G.A. : SYDNEY	DRAWN : JP	
						SHEET No. 1 OF 1	REF: 79177JP	CHECKED : DM	

PLATINUM RESTAURANT GROUP

Preliminary Geotechnical Investigation Report

175 Cleveland Street, Redfern, NSW



Report No. E22434 GA

18 March 2015

Report Distribution



Preliminary Geotechnical Investigation Report

175 Cleveland Street, Redfern, NSW

El Report No. E22434 GA

Date: 18 March 2015

Copies	Recipient
1 Soft Copy (PDF – Secured, issued by email)	Coco Simonian Platinum Restaurant Group c/- JPR Architects Pty Ltd Level 4, 50 Stanley Street <u>EAST SYDNEY NSW 2010</u>
1 Original (Saved to Digital Archives)	Environmental Investigations Australia Suite 6.01, 55 Miller Street <u>PYRMONT NSW 2009</u>

Author:		Technical Reviewer:	
			
Rachael Prosser Engineering Geologist		Alan Morrow Senior Geotechnical Engineer	
Revision	Details	Date	Amended By
GA	Original	18 March 2015	-

© Environmental Investigations Australia Pty Ltd 2015 T/A Environmental Investigations (EI)

This report is protected by copyright law and may only be reproduced, in electronic or hard copy format, if it is copied and distributed in full and with prior written permission by EI.



Environmental Investigations Australia
Contamination | Remediation | Geotechnical

CONTENTS

1	INTRODUCTION.....	1
1.1	BACKGROUND.....	1
1.2	PROPOSED DEVELOPMENT.....	1
1.3	INVESTIGATION OBJECTIVES.....	1
1.4	SCOPE OF WORKS.....	2
1.5	INVESTIGATION CONSTRAINTS.....	2
2	SITE DESCRIPTION.....	3
2.1	SITE DESCRIPTION AND IDENTIFICATION.....	3
2.2	LOCAL LAND USE.....	3
2.3	REGIONAL SETTING.....	4
3	INVESTIGATION RESULTS.....	5
3.1	STRATIGRAPHY.....	5
3.2	GROUNDWATER OBSERVATIONS.....	6
3.3	LABORATORY TEST RESULTS.....	6
4	PRELIMINARY GEOTECHNICAL DISCUSSIONS AND DESIGN ADVICE.....	8
4.1	EXCAVATION RETENTION.....	11
4.2	BASEMENT EXCAVATION MONITORING.....	12
4.3	FOUNDATIONS.....	14
4.4	CONSTRUCTION CONSIDERATIONS FOR THE ASHFIELD SHALE FORMATION.....	14
5	CONCLUSIONS.....	15
6	RECOMMENDATIONS FOR FURTHER GEOTECHNICAL SERVICES.....	16
7	STATEMENT OF LIMITATIONS.....	17
8	REFERENCES.....	18
9	ABBREVIATIONS.....	18

TABLES

Table 2-1	Summary of Site Information.....	3
Table 2-2	Summary of Local Land Use.....	3
Table 2-3	Topographic, Geological and Hydrogeological Information.....	4
Table 3-1	Summary of Inferred Subsurface Conditions.....	5
Table 3-2	Summary of Groundwater Seepage and Measurements.....	6
Table 3-3	Summary of Laboratory Test Results.....	7
Table 4-1	Preliminary Geotechnical Discussions and Design Advice.....	9
Table 4-2	Recommended Safe Working Distances for Vibration Intensive Plant.....	13

FIGURES

- 1 Site Locality Plan
- 2 Borehole Location Plan

APPENDICES

- A Borehole Logs and Explanatory Notes
- B Geotechnical Laboratory Testing Certificates
- C Important Information



1 INTRODUCTION

1.1 BACKGROUND

At the request of Platinum Restaurant Group (PRG), Environmental Investigations Australia Pty Ltd (EI) has carried out a Preliminary Geotechnical Investigation (PGI) for the proposed development at 175 Cleveland Street in Redfern, NSW (the Site).

This PGI report has been prepared to provide preliminary geotechnical advice and recommendations in support of a Development Application (DA) and the preparation of initial concept designs for the proposed mixed-use development. Work has been carried out in accordance with the scope of works outlined in our proposal referenced P12787.1, dated 28 October 2014, and the authorisation to proceed dated 6 February 2014.

1.2 PROPOSED DEVELOPMENT

JPR Architects Pty Ltd (JPR) supplied EI with pre-DA concept drawings:

- *Basement Level 02 to Level 07 Loft*, Project No. 2014067, Drawing No. SK02 to SK09, Revision A, dated 8 October 2014; and
- *Section A and Section B*, Project No. 2014067, Drawing No. SK11 and SK12, Revision A, dated 29 September 2014.

Based on the drawings provided, EI understands that the proposed development will involve the construction of an eight-storey building over a two-storey basement car park. We expect that the basement will extend to a maximum depth of approximately 9.0 m below existing ground level (mBGL) adjacent to Cleveland Street.

1.3 INVESTIGATION OBJECTIVES

The objective of the PGI is to assess site surface and subsurface conditions and to provide preliminary geotechnical advice and recommendations addressing the following:

- Building and retaining wall foundation options, including;
 - ▶ Preliminary design parameters;
 - ▶ Earthquake loading factor in accordance with AS1170.4:2007;
 - ▶ Subgrade preparation and earthworks requirements;
- Excavation methodologies, limitations and monitoring requirements, including monitoring of excavation induced vibrations;
- Excavation support requirements, including preliminary geotechnical design parameters for retaining walls and shoring systems;
- Approaches to limit potential impacts on adjacent structures, services and roads;
- Construction constraints including groundwater management requirements, if necessary; and
- The requirement for additional geotechnical investigations.



1.4 SCOPE OF WORKS

The scope of works for the PGI included:

- Review of available information from in-house sources;
- Preparation of appropriate health and safety plans;
- Review of relevant soil landscape and geological maps for the project area;
- Site walkover inspection by a Geotechnical Engineer to assess topographical features, condition of surrounding structures and site conditions;
- Dial Before You Dig (DBYD) services search and scan of proposed borehole locations for buried conductive services using a licensed service locator;
- Concrete coring through existing concrete hardstand at two borehole locations (BH1 & BH2);
- Drilling of one borehole (BH1) by a track-mounted drill rig and one borehole (BH2) by a ute-mounted drill rig using solid flight augers equipped with a 'tungsten-carbide' bit (T-C bit). BH1 was terminated at approximately 7.5 metres below ground level (mBGL), and BH2 reached T-C bit refusal at approximately 6.5 mBGL. Approximate borehole locations are shown in Figure 2;
- Standard Penetration Testing (SPT) during drilling of the boreholes at between 0.5 m and 1.5 m depth intervals to assess soil strength and collect soil samples for laboratory testing. Soil samples were sent to Macquarie Geotechnical Pty Ltd (Macquarie), a National Australian Testing Authority (NATA) accredited laboratory;
- Continuation of BH2 from T-C bit refusal, using NMLC coring techniques, to a termination depth of approximately 11.0 mBGL. Rock core recovered from the boreholes was logged, placed into core trays, photographed and delivered to Macquarie for testing and storage;
- Measurements of groundwater seepage/levels from boreholes during and immediately post drilling. No monitoring wells were installed as part of this investigation. Three monitoring wells installed from a previous investigation by others were measured during the field work;
- Backfilling of the boreholes with drilling spoil in the reverse order of excavation; and
- Preparation of this PGI report.

The fieldwork was supervised by a Geotechnical Engineer and included logging of subsurface conditions during drilling and locating of boreholes from existing structures.

1.5 INVESTIGATION CONSTRAINTS

The PGI was limited by the preliminary intent of the investigation and the presence of structures at the site at the time of the investigation. The physical extent of the investigation was limited to an asphalt car park on the boundary with Cleveland Street, with no access available to the interior of the buildings for geotechnical purposes. The discussions and advice presented in this report are intended for the development of initial designs for the development. Further geotechnical investigations should be carried out before final design to confirm both the geotechnical and groundwater model, and the preliminary design parameters provided in this report.



2 SITE DESCRIPTION

2.1 SITE DESCRIPTION AND IDENTIFICATION

The site identification details and associated information are presented in Table 2-1 while the site locality is shown in Figure 1.

Table 2-1 Summary of Site Information

Information	Detail
Street Address	175 Cleveland Street, Redfern, NSW 2016
Lot and Deposited Plan (DP) Identification	Lot 15 in DP 57107, Lot 5 in DP 68798, Lot 1 in DP 724328, Lot 10 in DP 809537, Lots 3 and 4 in Section 2, DP 977379, and lot 1 in DP 1093304
Local Government Authority	Council of the City of Sydney
Parish	Alexandria
County	Cumberland
Current Zoning	MD – SEPP Major Development 2005 (Sydney Local Environment Plan, 2012)
Site Description	The site is irregular in shape. The site is currently occupied by a brick single-storey commercial warehouse, used as a furniture store and art workshop, and a second brick warehouse, used as a commercial printers. An irregular sloping asphalt car park is present at the corner of Cleveland Street and Woodburn Street. The car park is approximately 0.5 m higher than Woodburn Street. Paved surfaces at the site were in good condition. Cleveland Street is a Transport for NSW Roads and Maritime Services (RMS) asset.
Site Area	The site is approximately 1,060 m ² (JPR, 2014)

2.2 LOCAL LAND USE

The site is situated within an area of high density residential and commercial use. Current uses on surrounding land are described in Table 2-3.

Table 2-2 Summary of Local Land Use

Direction Relative to Site	Land Use Description
North	Cleveland Street (an RMS asset), followed by a two-storey concrete commercial building and a five-storey brick apartment hotel.
East	Woodburn Street, followed by a four-storey brick youth hostel with a single-storey partially in-ground basement car park. Sydney Trains rail corridor lies beyond, 25 m from the site, orientated north-northwest between Redfern and Central Station.
South	A three-storey concrete residential building with a single-level partially in-ground basement car park, followed by two to three-storey brick residential buildings.



Direction Relative to Site	Land Use Description
West	Eveleigh Street, followed by a three to four-storey brick residential building. To the south-west is a construction site for a four-storey concrete residential building. No information was available regarding basements.

2.3 REGIONAL SETTING

The site topography, geological and hydrogeological information for the locality is summarised in Table 2-3.

Table 2-3 Topographic, Geological and Hydrogeological Information

Attribute	Description
Topography	The site is on the side slopes of a spur line which runs approximately southwest-northeast, following the alignment of the Sydney Trains railway corridor. Local topography slopes downwards to the northwest, at approximately 10°.
Regional Geology	Information on regional sub-surface conditions, referenced from the Department of Mineral Resources Geological Map Sydney 1:100,000 Geological Series Sheet 9130 (DMR 1991) indicates the site to be underlain by Ashfield Shale of the Wianamatta Group, which typically comprises of black to dark-grey shale and laminite. Ashfield Shale generally weathers into silty clay of medium to high plasticity. The site is close to the boundary of the Ashfield Shale, it is expected that Hawkesbury Sandstone may be present beneath the site at shallow depths. Outcrops of Quaternary aged Aeolian Sands (Botany Sands) are mapped approximately 90 m to the south-east of the site. Recent investigations in the area have indicated Aeolian Sands are present 50m to the south on Eveleigh Street. An infilled paleo channel (man made fill over alluvial soils) is present approximately 75 m to the north.
Soil Landscapes	The Soil Conservation Service of NSW Sydney 1:100,000 Soil Landscapes Series Sheet 9130 (2nd Edition) indicates that the residual landscape of the region of the site comprises the Blacktown Landscape. Soils are generally shallow to moderately deep (<100 cm) red and brown podzolic soils on crests, upper slopes and well-drained areas, and deep (150-300 cm) yellow podzolic soils and soloths on lower slopes and in areas of poor drainage. Land use is dominantly intensive residential and light and heavy industry. Soil Limitations include moderately reactive highly plastic subsoil, low soil fertility, and poor soil drainage.
Acid Sulfate Soils (ASS)	In accordance with the Sydney Local Environmental Plan 2012 Acid Sulfate Soils Map – Sheet ASS_009, the site does not fall within any category of Acid Sulfate Soils (ASS). For an unclassified site, works do not require development consent from council regarding ASS.

An online search was conducted using the NSW Office of Water (NOW) real-time database, which records relevant information pertaining to all licensed water bores for the state of New South Wales, revealed forty three (43) registered monitoring bore located within 500 km of the site. No standing water level data for the monitoring bores was recorded within the NOW database.

3 INVESTIGATION RESULTS

3.1 STRATIGRAPHY

For the development of a site-specific geotechnical model, the observed stratigraphy of shallow fill overlying a residual soil and weathered bedrock profile has been grouped into four geotechnical units. A summary of the subsurface conditions across the site, interpreted from the investigation results, is presented in Table 3-1.

More detailed descriptions of subsurface conditions at the test locations are available in the borehole logs presented in Appendix A. The details of the method of soil and rock classification, explanatory notes and abbreviations adopted in the borehole logs are also presented in Appendix A.

Table 3-1 Summary of Inferred Subsurface Conditions

Unit	Material	Depth (mBGL) to Top of Unit ¹	Observed Thickness (m)	Material Description ¹	Comments
1	Fill	0	1.5 to 1.8	CONCRETE over mixed FILL	Asphalt up to 70 mm thick overlying Sand and Clayey and Gravelly Sand, with some ceramic and brick fill. Fill is inferred to be uncontrolled and poorly compacted. This area was formerly a brick building, with evidence of former brick footings on the boundary with Woodburn Street.
2	Residual Soil	1.5 to 1.8	0.7 to 3.0	Sandy CLAY	Generally medium plasticity firm to very stiff sandy clay. SPT N values range from 5 to 33 blows with hammer bouncing at the end of the second increment.
3	Extremely Weathered Shale	2.5 to 4.5	1.5 to 3.0	SHALE	Generally extremely weathered, extremely low to very low strength shale. SPT N values of refusal with hammer bouncing.
4	Distinctly Weathered Shale	5.5 to 6.0	11.3 ²	SHALE	Generally distinctly weathered, very low to low strength shale. Where cored the bedding dips 0-5°, <1 mm thick. Defects within Unit 3 are generally closely spaced (~ 30-100 mm spacing) sub horizontal bedding partings, with one joint set (J1) dipping at 20-40° at 100-300mm spacing. Unit 3 is classified as Class IV Shale in accordance with Pells (2004).
5	Slightly Weathered Shale	6.8	N/A ³	SHALE	Generally fresh, medium to high strength shale. Bedding dips 0-5°, <1 mm thick. Defects within Unit 4 are generally closely to moderately spaced (~ 100-300 mm spacing) sub horizontal bedding partings. There are two joint sets within Unit 4, one set (J1) dipping at 20-40° at 100-300mm spacing, increasing to >1m from 8.3mBGL. Joint set 2 (J2) is sub-vertical, typically irregular to curved, closed at depth, spacing typically >1m. Unit 4 is classified as Class III Shale in accordance with Pells (2004).

Notes:

- 1 Approximate depth below ground level at the time of our investigation. More detailed descriptions of subsurface conditions are available in the borehole logs in Appendix A. Depths may vary across the site.
- 2 Unit 4 was observed up to borehole termination depth in BH1.
- 3 Unit 5 was observed up to borehole termination depth in BH2.

3.2 GROUNDWATER OBSERVATIONS

Groundwater seepage was observed during the drilling of BH1 on 25 February 2015. No groundwater seepage was observed during the drilling of BH2. Groundwater measurements taken during drilling and from existing groundwater wells are presented in Table 3-2.

Table 3-2 Summary of Groundwater Seepage and Measurements

Borehole ID	Date of Observation	Depth to Groundwater (mBGL)	Tip Depth of well (mBGL)
BH1	25/02/2015	6.10 (inflow during drilling)	-
MW1	25/02/2015	2.40	7.00
MW2	25/02/2015	3.90	7.45
MW3	25/02/2015	4.23	7.15

Observed groundwater seepage levels may be affected by the low permeability of the encountered strata. Further groundwater monitoring should be undertaken prior to final design.

3.3 LABORATORY TEST RESULTS

Two soil samples were selected for laboratory testing to assess the following:

- Soil Moisture Content, Linear Shrinkage and Atterberg Limits (Liquid Limit and Plastic Limit); and
- Soil aggressivity (pH, Chloride and Sulfate content and electrical conductivity).

A summary of soil test results is provided in Table 3-2.

Four rock core samples were tested by Macquarie to determine Point Load Strength Index (Is_{50}) values to assist with rock strength classification. The results of the testing are shown on the borehole logs at the appropriate depths in Appendix A.

Laboratory test certificates are presented in Appendix B

Table 3-3 Summary of Laboratory Test Results

Test/ Sample ID		BH1 (1.5-1.95 mBGL)	BH2 (4.5-4.95 mBGL)
Unit		Unit 2	Unit 2
Material Description ¹		Sandy CLAY	Sandy CLAY
Atterberg Limits	Liquid Limit (%)	31	38
	Plastic Limit (%)	16	22
	Plasticity Index (%)	15	16
Linear Shrinkage (%)		10.0	8.5
Moisture Content (%)		17.6	14.9
Soil Aggressivity	pH	6.4	5.3
	Electrical Conductivity (Ω.cm)	15,000	3,400
	Sulfate SO ₄ (mg/kg)	240	82
	Chloride Cl (mg/kg)	20	<10

Notes:

- 1 More detailed descriptions of the subsurface conditions at borehole locations are available in the borehole logs presented in Appendix A.



4 PRELIMINARY GEOTECHNICAL DISCUSSIONS AND DESIGN ADVICE

The main geotechnical factors for the design of the development include:

- Excavation adjacent to Cleveland Street, an RMS asset.
- Basement excavatability.
- Basement excavation retention to prevent potential lateral deflections and ground loss as a result of excavations.
- Foundation design for building loads.

Geotechnical discussions and design advice are presented in Table 4-1. The advice and parameters presented in Table 4-1 are intended for the development of initial concept designs. Further geotechnical investigations should be carried out prior to final design to confirm the preliminary design parameters provided here.



Table 4-1 Preliminary Geotechnical Discussions and Design Advice

	Preliminary Design ¹	Geotechnical Constraints ²	Preliminary Discussions and Design Advice ²	Preliminary Design Parameters ²							
				Material ³	Unit 1 Fill	Unit 2 Residual Soil	Unit 3 Extremely Weathered Shale	Unit 4 Distinctly Weathered Shale	Unit 5 Slightly Weathered Shale		
				Typical Depth to Top of Unit (mBGL) ⁴	0	1.5 to 1.8	2.5 to 4.5	5.5 to 6.0	6.8		
				Bulk Unit Weight (kN/m³) ⁵	16	19	21	24	24		
Elastic Modulus (MPa)	5	30	50	100	200						
Basement Excavations and Earthworks	<ul style="list-style-type: none">Two levels of basement car parking. Excavation for the basement is expected to extend to a maximum depth of approximately 9 mBGL along Cleveland Street.	<ul style="list-style-type: none">Proposed excavation will likely encounter Unit 1, 2, 3, 4 and 5 material.	<ul style="list-style-type: none">Temporary batters may be considered for retention of material encountered during basement excavation where site constraints allow.Batters given for rock units may only be used with consideration of rock support systems such as pattern bolting, spot bolting or shotcreting based upon the rock mass characteristics encountered during excavation. Inspection during construction by an experienced geotechnical engineer or engineering geologist will be required to determine temporary and permanent rock support requirements. Permanent batters may require surface protection to prevent erosion and slakingWhere excavations extend beneath the zone of influence of nearby structures/ services/ pavements basement retention will be required.Units 1, 2 and 3 should be diggable with a 20t Hydraulic Excavator. Unit 4 should be easy ripping with a D6 or similar. Unit 5 will be hard ripping with a D8 dozer or equivalent.All earthworks should be carried out in accordance with AS3798: 2007. This standard applies to any site filling undertaken and to the preparation of basement slab subgrades.	Batter Angle ⁶	Temporary ⁶	N/A	1.5H:1V	1.5H:1V	Vertical with Rock Support	Vertical with Rock Support	
					Permanent ⁶	N/A	2H:1V	2H:1V	Vertical with Rock Support	Vertical with Rock Support	
Excavation Retention and Rock Face Support				<ul style="list-style-type: none">Cantilevered retaining walls are typically the most economically viable retention method up to 5 m height. Anchored walls may be more economically viable above 5 m height and may be required to limit lateral deflections where retention systems are within the zone of influence of nearby structures/ services/ pavements.Rock face protection of Unit 4 and 5 material using shotcrete and drainage systems will be required.Consideration will need to be given to excavation retention in competent rock and should be given to the potential for stress relief movement of excavation faces in the design of the basement retention system. Further discussion of this is given in Section 4.1.Consideration will need to be given to monitoring lateral and vertical deflections of retained soil and to monitoring construction induced vibrations. Further discussion of this is given in Section 4.2.Parameters given in this table for design of deep foundations may be used for design of basement retention systems.	Earth Pressure Coefficients	At rest, K _o ⁷	0.66	0.58	0.58	-	-
						Passive, K _p ⁷	2.04	2.46	2.46	1000 kPa Ultimate stress block	2000 kPa Ultimate stress block
						Active, K _a ⁷	0.49	0.41	0.41	-	-
Foundations	<ul style="list-style-type: none">Eight-storey building over two levels of basement parking.Proposed basement plan extents to all site boundaries	<ul style="list-style-type: none">Final excavation levels likely to be in Unit 5 material.	Footing Foundations <ul style="list-style-type: none">All footings should found below Unit 1 materials to avoid the potential of potentially large settlements caused by founding in these low density materials.Footings and slabs on Unit 5 – Slightly Weathered Shale should be designed in accordance with AS2870:2011 based on a Site Classification of ‘A.’.Consideration must be given to the possibility of differential settlement caused by foundations for a structure spanning the interface of differing materials. Further discussion of this is given in Section 4.3.	Preliminary Allowable Bearing Pressure (kPa) ⁸	NA	250	500	1000	2000		
				Undrained shear strength, c _u (kPa)	-	100	-	-	-		
				Drained friction angle, ϕ' (°)	20	25	-	-	-		
				Drained cohesion, c' (kPa)	0	5	-	-	-		

	Preliminary Design ¹	Geotechnical Constraints ²	Preliminary Discussions and Design Advice ²	Preliminary Design Parameters ²						
				Material ³		Unit 1 Fill	Unit 2 Residual Soil	Unit 3 Extremely Weathered Shale	Unit 4 Distinctly Weathered Shale	Unit 5 Slightly Weathered Shale
				Typical Depth to Top of Unit (mBGL) ⁴		0	1.5 to 1.8	2.5 to 4.5	5.5 to 6.0	6.8
				Bulk Unit Weight (kN/m ³) ⁵		16	19	21	24	24
				Elastic Modulus (MPa)		5	30	50	100	200
			<p>Pile Foundations</p> <ul style="list-style-type: none">Pile foundations may be considered where high lateral or axial loads are to be supported.The parameters given may also be used for design of retention support.We recommend that a Preliminary Geotechnical Strength Reduction Factor (GSRF) of 0.40 is used for the preliminary design of piled support in accordance with AS 2159:2009 based upon the preliminary nature of the soil parameters given. The GSRF may be increased upon finalising the development details and subject to further assessments having been carried out e.g. pile testing during construction.	Ultimate Vertical End Bearing Pressure (kPa) ^{9, 11}		N/A	750	1500	3000	6000
				Ultimate Shaft Adhesion (kPa) ^{10, 11}	in Compression	15	45	75	150	350
					in Uplift	5	15	37.5	75	175
				Susceptibility to Liquefaction during an Earthquake ¹²		Medium	Low	Low	Low	Low
Groundwater Management	<ul style="list-style-type: none">Two levels of basement car parking. Excavation for the basement is expected to extend to a maximum depth of approximately 9.0 mBGL.	<ul style="list-style-type: none">Groundwater levels were observed during the investigation at approximately 2.4 to 4.2 mBGL.	<ul style="list-style-type: none">Groundwater is expected to be encountered within the basement excavations. Although the intact rock mass permeability of the Ashfield formation is generally low, groundwater flows may be moderate to high from fractured zones within the rock mass. Groundwater management options may include the grouting of water bearing fractures during excavation or the installation of drainage systems behind the excavation retention facing.Surface water seepage into these excavations may occur during and following periods of rainfall. Surface water should be controlled by diverting overland flows away from excavations and may be managed by conventional sump and pump methods.							
Earthquake Site Risk Classification			<ul style="list-style-type: none">AS 1170.4:2007 indicates an earthquake subsoil class of Class C_e (Shallow Soil).AS 1170.4:2007 indicates that the hazard factor (z) for Sydney is 0.08.							
Soil and Groundwater Aggressivity	<ul style="list-style-type: none">Proposed structure will incorporate buried concrete and steel elements.	<ul style="list-style-type: none">Low permeability soils above and below the groundwater table.AS2159:2009 gives guidelines for foundation susceptibility to soil and groundwater aggressivity.	<ul style="list-style-type: none">Analysis of the pH, chloride and sulfate content and electrical conductivity of the soil was compared with criteria in AS 2159:2009, providing the following exposure classifications:<ul style="list-style-type: none">'Mild' for buried concrete structural elements; and'Non-aggressive' for buried steel structural elements.							

Notes:

- 1
- Design details are based on proposed development details provided by JPR at the time of the preparation of this report.
- 2
- Advice and parameters presented in this PGI report are intended for DA purposes and for the development of initial designs for the development. Further geotechnical investigations should be carried out prior to final design to confirm both the geotechnical model and the preliminary design parameters provided in this report.
- 3
- More detailed descriptions of subsurface conditions are available in the borehole logs in **Appendix A**. Depths may vary across the site.
- 4
- Approximate depth below ground level at the time of our investigation. More detailed descriptions of subsurface conditions are available in the borehole logs in **Appendix A**. Depths may vary across the site.
- 5
- Unit Weight is based on visual estimate only, order of accuracy is about 10%.
- 6
- Batter angles recommended are based upon ground conditions encountered in the borehole locations only. Ground conditions may vary and preliminary batter angles should be confirmed by additional geotechnical investigations and inspections during construction by an experienced geotechnical engineer. Batter angles provided assume an overall batter height of less than 5 m. Should batters extend beyond 5 m, batter designs should be carried out by an experienced geotechnical engineer and may need to incorporate benches.
- 7
- Earth pressures are provided on the assumption that the ground behind the retaining wall is flat and drained.
- 8
- Bearing pressures given are indicative only and will vary according to footing type, shape and embedment and should be confirmed by additional geotechnical investigations, design checks and foundation inspections during construction by an experienced geotechnical engineer.
To adopt these bearing pressures we have assumed that:
 - Shallow footings have an embedment depth of at least 750mm into the founding material.
 - The bases of all footings are cleaned of loose debris and water and inspected by a suitably qualified Geotechnical Engineer prior to footing construction to verify that ground conditions meet design assumptions.
- 9
- Ultimate geotechnical strengths are provided for use in limit state design. Allowable or serviceability bearing pressures and side adhesions may be estimated using factors of safety of 3 and 2, respectively. These are the factors of safety generally adopted in geotechnical practice to limit settlements to an acceptable level for conventional building structures, typically less than 1% of the minimum footing width. Assumes the base of pile holes are clean and penetrate at least 1.0m or 2 pile diameters, whichever is greater, into the respective Unit.

- Bearing pressures may vary and must be confirmed by additional geotechnical investigations and foundation inspections during construction by an experienced geotechnical engineer.
Higher bearing pressures may be applied upon confirmation by additional geotechnical investigations and subject to an experienced geotechnical engineer carrying out foundation inspections during construction.
- 10
- Side adhesion values given assume there is intimate contact between the pile and foundation material. Design engineer to check both 'piston' pull-out and 'cone' pull-out mechanics in accordance with AS4678-2002 Earth Retaining Structures.
- 11
- To adopt these parameters we have assumed that:
 - Piles have an embedment depth of at least two pile diameters or 1 m, whichever is greater, into the relevant founding material;
 - There is intimate contact between the pile and foundation material;
 - Potential soil and groundwater aggressivity will be considered in the design of bored piles;
 - The bases of all pile excavations are cleaned of loose debris and water and inspected by a suitably qualified Geotechnical Engineer prior to pile construction to verify that ground conditions meet design assumptions. Where groundwater ingress is encountered during pile excavation, concrete is to be placed as soon as possible upon completion of pile excavation. Pile excavations should be pumped dry of water prior to pouring concrete, or alternatively a tremmie system could be used; and
 - An experienced Geotechnical Engineer has reviewed the pile designs to assess whether all recommendations presented in this report have been incorporated in the design.
- 12
- Susceptibility to liquefaction during an earthquake is based on the following definition:

Low	-	Medium to very dense sands, stiff to hard clays, and rock
Medium	-	Loose to medium dense sands, soft to firm clays, or uncontrolled fill below the water table
High	-	Very loose sands or very soft clays below the water table

4.1 EXCAVATION RETENTION

Rigid retaining structures, such as propped or anchored walls, should be adopted to limit lateral and vertical movements when in close proximity to existing buildings, buried services and pavement. We recommend the use of closely spaced soldier pile walls or contiguous reinforced concrete bored pile walls that are socketed into Class III Shale or better.

If cantilevered piles are employed for the design, relatively flexible shoring systems may be used, adopting a triangular earth pressure distribution using active pressures presented in Table 4-1. For design of rigid walls, a trapezoidal earth pressure distribution should be used with a maximum pressure of $0.65 \cdot K_a \cdot \gamma \cdot H$ (kPa) where 'H' is the effective vertical height of the wall in metres. For excavations spanning the interface of soil and rock, 'H' may be taken as the depth to a zero active earth pressure coefficient.

In addition, design of retaining walls should consider the following:

- If piled retaining walls are to provide permanent support to proposed structures, pile sockets in rock may need to be longer to accommodate additional lateral and axial loads. Anchoring may be required for additional lateral support.
- Care must be taken to ensure that the bored piles found in rock below neighbouring foundation and basement levels, where present.
- The effect of stress relief in the rock on neighbouring foundation systems and pavements, resulting from proposed excavations, should be considered in the retaining wall design.
- Static water pressures should be taken into consideration, unless subsoil drainage is provided behind retaining walls. A hydrostatic pressure distribution could be used for this analysis.

Appropriate surcharge loading from construction equipment and vehicular traffic at finished surface level should be adopted. Any applicable surcharge loads should be taken into account in the retention design.

4.1.1 Rock Support

An allowance should be made for support of vertical excavation faces in Unit 3 and better material, including rock bolts, rock anchors and/ or shotcrete (mesh reinforced) to support weak seams, fracture zones and isolated individual blocks of rock. Specific support requirements can only be assessed during excavation. An experienced Engineering Geologist or Geotechnical Engineer should carry out regular inspections as excavation progresses (at least every 1.5 m depth of excavation).

Rock bolts, and anchors should they be required, should generally be specified in terms of performance requirements and constructed by contractors experienced in ground anchor technology.

We recommend that a geotechnical engineer inspect battered and unsupported excavations and excavation support installations to confirm inferred geotechnical conditions. This will allow for the assessment of design assumptions and to provide further advice with regards to excavation retention / support and proposed construction methodologies, if required.

4.1.2 Construction Considerations for Deep Excavations

As the basement excavation will likely extend through both materials which require full retention (Units 1, and 2) and material which will require rock face support (Unit 3 and better), particular consideration must be given to the integration of retention and support designs at the site. The following methodologies could be considered for design of retention/ support systems:



- **Full Height Retention** – Soldier pile walls to continue the full depth of basement excavation with a socket in Unit 4 below bulk excavation level. This option would allow excavation to continue through the full depth of excavation without concern of disturbing the rock on which the piles are founded. Boring of piles within the medium to high strength rock will likely be slow and cause machine wear; or
- **Part Retention** – Construction of a part-retention system may proceed as follows:
 - Units 1, 2 are to be retained as described above, socketed into Unit 3 – Distinctly Weathered Shale.
 - Excavation to the top of Unit 3 material.
 - Anchors to be installed near the base of the retaining wall, socketed into Unit 3.
 - Excavation could then proceed into Unit 3. Spot bolting beneath the toe of the retaining wall may be required to limit block failure from the wall foundation.
 - Further bolting and mesh reinforced shotcrete support of Unit 4 as required, as discussed in Section 4.1.1.

Should the proposed structure found on the retaining wall, consideration should be given in the wall design to the suitability of the rock beneath the pile toe as foundation and ability to support additional building loads. We recommend that further investigations, modelling of the rock conditions, and site inspections are carried out to assess rock support requirements below the pile toe.

4.1.3 Excavation Interaction with Neighbouring Structures and Basements

Medium rise structures and potential basements of unknown extent were noted on adjoining properties as part of the development. Surrounding footings and excavation faces of these developments will lie within the zone of influence of the proposed excavation. There is the potential for neighbouring structures to be adversely affected.

The design of excavation support should consider loading from neighbouring structures and the requirement for underpinning where excavations in rock extend below adjacent building foundation levels.

Detailed survey of the relative positions, levels and working loading of neighbouring basements and footings should be acquired prior to final design. The detailed survey should be used to accurately model the interaction of the proposed development with existing structures in the vicinity of the site using finite element software.

4.2 BASEMENT EXCAVATION MONITORING

Consideration should be made to the impact of the proposed development upon neighbouring structures. Basement excavation retention systems should be designed so as to limit lateral deflections to allowable levels, particularly adjacent to Cleveland Street.

Contractors should also consider the following limits associated with carrying out excavation and construction activities:

- Limit lateral deflection of temporary or permanent retaining structures;
- Limit vertical settlements of ground surface at common property boundaries and services easement; and
- Limit peak particle velocities (ppv) from vibrations, caused by construction equipment or excavation, experienced by any structure within bounding properties and the services easement.

Monitoring of deflections of retaining structures and surface settlements should be carried out by a registered surveyor at agreed points along the excavation boundaries and along existing building foundations/ services/ pavements and other structures located within or near the zone of influence of the excavation. Owners of existing services at the site should be consulted to assess appropriate deflection limits for their infrastructure. Along Cleveland Street it would be



expected that RMS will require a minimum of two inclinometer installations and level monitoring points should excavations exceed 6 m depth. Measurements should be taken:

- Prior to commencement of excavations;
- Immediately after installation of any temporary or permanent retaining structures;
- Immediately after the excavation has reached a depth of 1.5 m, and each 1.5 m depth increment thereafter;
- Immediately after the excavation has reached bulk excavation level; and
- Immediately after backfilling behind retaining structures.

Vibration monitoring should be carried out periodically during excavation works, particularly at the base of external walls of existing buildings in closest proximity to the excavation and easement. EI recommends an upper limit for ppv of 3 mm/sec is adopted for sensitive structures such as the Telstra, Ausgrid and Sydney Water mains (or as recommended by utility owner), 10 mm/sec is adopted for residential buildings and 20 mm/sec is adopted for commercial and industrial buildings or reinforced concrete structures.

An ongoing monitoring programme will not be required if the contractor can verify, based on trials carried out at the commencement of the works and with the agreement of a Geotechnical Engineer, that the ppv will not exceed set limits. However, should equipment used during excavation and construction works vary from that used during the trial or as agreed, further vibrations assessments by a Geotechnical Engineer, and/ or an ongoing monitoring programme, may be required.

Should vibrations, settlements or deflections exceed set limits, we recommend the following:

- Cease excavation works and notify the Geotechnical Engineer immediately;
- Backfill excavations or support exposed excavations with buttresses or props, where settlement/ lateral movement limits have been exceeded; and
- Develop an alternative excavation/ support plan in conjunction with the Structural and Geotechnical Engineers.

4.2.1 Construction Vibration Mitigation

As a guide, safe working distances for typical items of vibration intensive plant are listed in Table 4-2. The safe working distances are quoted for both “cosmetic” damage (refer British Standard BS 7385:1993) and human comfort (refer NSW Environmental Protection Agency Vibration Guideline). The safe working distances should be complied with at all times, unless otherwise mitigated to the satisfaction of the relevant stakeholders.

Table 4-2 Recommended Safe Working Distances for Vibration Intensive Plant

Plant Item	Rating/Description	Safe Working Distance	
		Cosmetic Damage (BS 7385:1993) ¹	Human Response (EPA Vibration Guideline)
Vibratory Roller	< 50 kN (typically 1-2 tonnes)	5 m	15 m to 20 m
	< 100 kN (typically 2-4 tonnes)	6 m	20 m
	< 200 kN (typically 4-6 tonnes)	12 m	40 m
	< 300 kN (typically 7-13 tonnes)	15 m	100 m
	< 300 kN (typically 13-18 tonnes)	20 m	100 m

Plant Item	Rating/Description	Safe Working Distance	
		Cosmetic Damage (BS 7385:1993) ¹	Human Response (EPA Vibration Guideline)
	< 300 kN (typically >18 tonnes)	25 m	100 m
Small Hydraulic Hammer	300 kg – 5 to 12 t excavator	2 m	7 m
Medium Hydraulic Hammer	900 kg – 12 to 18 t excavator	7 m	23 m
Large Hydraulic Hammer	1600 kg – 18 to 34 t excavator	22 m	73 m
Vibratory Pile Driver	Sheet Piles	2 m to 20 m	20 m
Pile Boring	≤ 800 mm	2m (nominal)	N/A
Jackhammer	Hand held	1 m (nominal)	Avoid contact with structure

Notes:

- 1 More stringent conditions may apply to heritage buildings or other sensitive structures.

In relation to human comfort (response), the safe working distances in Table 4-2 relate to continuous vibration and apply to residential receivers. For most construction activities, vibration emissions are intermittent in nature and for this reason, higher vibration levels, occurring over shorter periods are permitted, as discussed in British Standard BS 6472-1:2008.

The safe working distances provided in Table 4-2 are given for guidance only. The values obtained from these codes are general in nature and site specific values by detailed acoustic assessment of the rock mass should be obtained.

4.3 FOUNDATIONS

Should footings for the proposed development span the interface of several materials identified in this investigation, variable ground conditions may cause difficulties for subgrade preparation. Selection of footing types and founding depth will need to consider the risk of adverse differential ground movements within the foundation footprint and between high level and deeper footings. Unless an allowance for such movement is included in the design of the proposed development, we recommend that all new structures found on natural materials with comparable end bearing capacities. Possible features designed to accommodate potential differential movement of the structures may include movement joints, dowelled connections or shear keys.

4.4 CONSTRUCTION CONSIDERATIONS FOR THE ASHFIELD SHALE FORMATION

Long and intermediate term durability of exposed residual soil and rock is a major concern within the Ashfield Shale formation. Exposure of residual soil and weathered rock due to excavation can lead to rapid degradation of the material. Slaking of rock faces, erosion of soil cuts and softening of foundation subgrade material may occur quickly after excavation. Formations will need to be protected with blinding concrete without undue delay to limit any degradation of these materials.



5 CONCLUSIONS

Based on the findings of this report and within the limitations of geotechnical investigations, EI considers the following geotechnical factors will influence the possible development of the site, including:

- Excavation adjacent to Cleveland Street, an RMS asset.
- Basement excavatability.
- Basement excavation retention to prevent potential lateral deflections and ground loss as a result of excavations.

In summary, and considering the limitations of geotechnical investigations, EI considers there is a low risk of geotechnical conditions preventing the proposed development if the recommendations of this report are considered for the preliminary design and construction of the development.



6 RECOMMENDATIONS FOR FURTHER GEOTECHNICAL SERVICES

The adopted investigation scope was limited by the investigation intent and by the presence of structures at the site during the investigation. This PGI report will need to be supplemented with additional cored boreholes given the scale of the proposed development.

Further geotechnical investigations should be carried out to confirm the results and address any limitations prior to adoption of the recommendations of this report for detailed design. These investigations should be carried out once preliminary design and construction details are available and should include:

For Design Phase

- For the design of the excavation adjacent to Cleveland Road consider the guidance and additional investigation requirement given in RMS technical directive GTD2012/001 – Excavations adjacent to RMS Infrastructure.
- The rock classifications for material encountered at foundation level may be improved on the basis of consistent rock quality encountered in additional boreholes. Should higher bearing pressures be required for foundation design, at least three additional deep cored boreholes to 5 m below foundation level should be drilled to confirm the quality of Shale in Table 4-1.
- Ongoing monitoring of existing groundwater monitoring wells should be undertaken to determine hydrogeological conditions.
- Stress-strain dependent analysis of basement retention systems should be undertaken for final design to determine expected deflections and interaction with adjacent structures.
- All excavated material transported off site should be classified in accordance with NSW EPA 2014 - Waste Classification Guideline Part 1; Classifying Waste.

For Construction Phase

- Dilapidation surveys should be carried out on existing structures that may be impacted by any proposed excavations, particularly where located within the zone of influence of excavations. These surveys should be carried out by a qualified structural engineer and/or geotechnical engineer prior to and following completion of construction works.
- Working platforms for construction plant, placed on in-situ materials or on engineered fill, should be designed by an experienced and qualified geotechnical engineer.
- A suitably qualified geotechnical engineer is to assess the condition of exposed material at foundation or subgrade level to assess the ability of the prepared surface to act as a foundation or as a subgrade.
- Ongoing monitoring of ground vibrations, settlements and lateral movements in conjunction with survey results should be carried out during basement excavation.
- Regular inspections of battered and unsupported excavations where localised excavations are proposed, to confirm inferred geotechnical conditions, to assess the suitability of design assumptions and to provide further advice with regards to excavation retention/ support and proposed construction methodologies, if required.



7 STATEMENT OF LIMITATIONS

The adopted investigation scope was limited by site access restrictions due to site conditions at the time of our investigation and by the investigation intent. The advice and parameters presented in this PGI report are intended for the development of initial concept designs for the development. Further geotechnical investigation should be carried out before final design to confirm both the geotechnical model and the preliminary design parameters provided in this report.

We draw your attention to the document “Important Information”, which is included in **Appendix C** of this report. The statements presented in this document are intended to advise you of what your realistic expectations of this report should be. The document is not intended to reduce the level of responsibility accepted by EI, but rather to ensure that all parties who may rely on this report are aware of the responsibilities each assumes in so doing.

Should you have any queries regarding this report, please do not hesitate to contact EI.



8 REFERENCES

- AS1170.4:2007, *Structural Design Actions, Part 4: Earthquake Actions in Australia*, Standards Australia.
- AS1726:1993, *Geotechnical Site Investigations*, Standards Australia.
- AS2159:2009, *Piling – Design and Installation*, Standards Australia.
- AS2870:2011, *Residential Slabs and Footings*, Standards Australia.
- AS3798:2007, *Guidelines on Earthworks for Commercial and Residential Developments*, Standards Australia.
- Chapman, G.A. and Murphy, C.L. (1989), Soil Landscapes of the Sydney 1:100000 sheet. Soil Conservation Services of NSW, Sydney.
- NSW Department of Finance and Service, Spatial Information Viewer, maps.six.nsw.gov.au.
- NSW Department of Mineral Resources (1983) Sydney 1:100,000 Geological Series Sheet 9130 (Edition 1). Geological Survey of New South Wales, Department of Mineral Resources.
- NSW Office of Water, Continuous Water Monitoring Network, <http://realtimedata3.water.nsw.gov.au/water.stm>.
- Pells (2004) Substance and Mass Properties for the Design of Engineering Structures in the Hawkesbury Sandstone, Australian Geomechanics Journal, Vol 39 No 3.
- Pettifer and Fookes 1994, A Revision of the Graphical Method for Assessing the Excavatability of Rock, Quarterly Journal of Engineering Geology and Hydrogeology.


9 ABBREVIATIONS


AHD	Australian Height Datum
BGL	Below Ground Level
BH	Borehole
DP	Deposited Plan
EI	Environmental Investigations
EPA	NSW Environmental Protection Agency
NATA	National Association of Testing Authorities, Australia
NOW	NSW Department of Primary Industries, Office of Water
PGI	Preliminary Geotechnical Investigation
RMS	NSW Roads and Maritime Services






FIGURES







LEGEND

-  Approximate Borehole Location (EI, 2015)
-  Approximate Existing Borehole/Monitoring Well Location
-  Approximate Site Boundary

Environmental Investigations Australia
 Contamination | Remediation | Geotechnical
 Suite 6.01, 55 Miller Street, PYRMONT 2009
 Ph (02) 9516 0722 Fax (02) 9518 5088

Drawn:	SK
Approved:	RP
Date:	16/3/15
Approx Scale:	1:300 @ A4

Platinum Restaurant Group
 Preliminary Geotechnical Investigation
 175 Cleveland Street, Redfern, NSW
 Borehole Location Plan

Figure:

2

Project: E22434 GA

APPENDIX A

BOREHOLE LOG REPORTS AND EXPLANATORY NOTES



















Project New Mixed-use Development
Location 175 Cleveland Street, Redfern, NSW
Position Refer to Figure 2
Job No. E22434
Client Platinum Restaurant Group

East 333588.1 m
North 6248688.1 m MGA94 Zone 56
Contractor Traccess Drilling Pty Ltd
Drill Rig MultiDrill 4000
Inclination -90°

BOREHOLE: BH1

Sheet 1 OF 1
Date Started 25/2/15
Date Completed 25/2/15
Logged SK Date: 25/2/15
Checked RP Date: 16/3/15

Drilling				Sampling		Field Material Description						
METHOD	PENETRATION RESISTANCE	WATER	DEPTH (metres)	DEPTH RL	SAMPLE OR FIELD TEST	RECOVERED	GRAPHIC LOG	USCS SYMBOL	SOIL/ROCK MATERIAL DESCRIPTION	MOISTURE CONDITION	CONSISTENCY DENSITY	STRUCTURE AND ADDITIONAL OBSERVATIONS
AD/T	F		0					-	FILL: ASPHALT; 70 mm.	-		ROAD SURFACE FILL
	E-F				SPT 0.50-0.95 m 2,2,2 N=4 BH1_0.5-0.95			-	FILL: Gravelly SAND; fine to medium grained, black, gravel is fine to coarse, subangular bluestone and brick gravel, trace ceramics.			
			1.50					CI	Sandy CLAY; medium plasticity, pale brown to brown, sand is fine grained.			RESIDUAL SOIL
			2		SPT 1.50-1.95 m 1,2,3 N=5 BH1_1.5-1.95						F	
	E		2.50						From 2.5 m, grey mottled red, no sand.			
					SPT 3.00-3.45 m 5,8,10 N=18 BH1_3.0-3.45					D		
			4								VSt	
			4.50					-	SHALE; red brown, inferred extremely low strength, inferred extremely weathered.			WEATHERED ROCK
			5.50		SPT 4.50-4.95 m 5,20,20 N=40 BH1_4.5-4.95				From 5.5 m, dark brown.			
	F			6		SPT 6.00-6.10 m 10 HB BH1_6.0-6.10				From 6.0 m, extremely low to very low strength.		
		7.00						From 7.0 m, dark grey.	W			
		7.50										
		8							Hole Terminated at 7.50 m Terminated due to rig failure. Backfilled with drilling spoil and concrete capped.			

This borehole log should be read in conjunction with Environmental Investigations Australia's accompanying standard notes.

Project New Mixed-use Development
Location 175 Cleveland Street, Redfern, NSW
Position Refer to Figure 2
Job No. E22434
Client Platinum Restaurant Group

East 333601.2 m
North 6248686.7 m MGA94 Zone 56
Contractor Terratest Pty Ltd
Drill Rig MCT-200
Inclination -90°

BOREHOLE: BH2

Sheet 1 OF 2
Date Started 6/3/15
Date Completed 6/3/15
Logged SK Date: 6/3/15
Checked RP Date: 16/3/15

Drilling				Sampling		Field Material Description						
METHOD	PENETRATION RESISTANCE	WATER	DEPTH (metres)	DEPTH RL	SAMPLE OR FIELD TEST	RECOVERED	GRAPHIC LOG	USCS SYMBOL	SOIL/ROCK MATERIAL DESCRIPTION	MOISTURE CONDITION	CONSISTENCY DENSITY	STRUCTURE AND ADDITIONAL OBSERVATIONS
AD/T	F	GWNE	0					-	FILL: ASPHALT; 50 mm.	-		ROAD SURFACE FILL
	E		0.50	SPT 0.50-0.95 m 5,3,2 N=5 BH2_0.5-0.95			-	FILL: SAND; medium to coarse grained, brown, with some fine to coarse, subrounded gravel.	D			
			1.60	SPT 1.50-1.95 m 0,0,1 N=1 BH2_1.5-1.80 BH2_1.8-1.95 PP =225-255 kPa			-	FILL: Clayey SAND; fine to medium grained, grey to brown, clay is of high plasticity, trace ceramics.	D - M			
			1.80					From 1.60 to 1.65 m, with some ash.				
	2		2.50			CI	Sandy CLAY; medium plasticity, grey mottled red, sand is fine to medium grained.	D	VSt	RESIDUAL SOIL		
	F						-	SHALE; grey, inferred extremely low to very low strength, inferred extremely weathered.			WEATHERED ROCK	
			4									
	H		5.50					-	From 5.5 m, inferred very low to low strength, inferred distinctly weathered.			ROCK
			6									
			6.50		SPT 6.00-6.13 m 10 HB BH2_6.0-6.13							
									Continued as Cored Borehole			

This borehole log should be read in conjunction with Environmental Investigations Australia's accompanying standard notes.


Project	New Mixed-use Development	East	333601.2 m	Sheet	2 OF 2
Location	175 Cleveland Street, Redfern, NSW	North	6248686.7 m MGA94 Zone 56	Date Started	6/3/15
Position	Refer to Figure 2	Contractor	Terratest Pty Ltd	Date Completed	6/3/15
Job No.	E22434	Drill Rig	MCT-200	Logged	SK
Client	Platinum Restaurant Group	Inclination	-90°	Checked	RP
				Date:	6/3/15
				Date:	16/3/15

Drilling						Field Material Description		Defect Information			
METHOD	WATER	TCR	RQD (SCR)	DEPTH (metres)	DEPTH RL	GRAPHIC LOG	ROCK / SOIL MATERIAL DESCRIPTION	WEATHERING	INFERRED STRENGTH $I_{s(50)}$ MPa	DEFECT DESCRIPTION & Additional Observations	AVERAGE DEFECT SPACING (mm)
								EL 0.03 VL 0.01 L 0.1 M 0.3 H 1 VH 3 EH 10			10 100 1000 10000 30000
				0							
				2							
				4							
				6							
				6.50			Continuation from non-cored borehole				
				6.80			SHALE; dark grey, returned as stiff to very stiff, high plasticity sandy clay.	XW		6.63-6.68: BPx2 0° PR S CN	
							SHALE; bedding dipping 0-5 degrees, <1 mm thick, dark grey.	DW		6.84: JT 20° ST RF Fe SN	
								SW		6.90-7.02: BPx6 0 - 5° PR RF Fe SN avg sp = 5-30 mm	
										7.03-7.06: JT 45° PR RF Fe SN	
										7.06-7.09: JT 50° PR RF Fe SN	
										7.19: BP 0° PR S CN	
										7.23: JT 5 - 20° UN RF Fe SN	
										7.24-7.32: JT 60° IR RF Fe SN	
										7.27-7.30: JT 60° PR RF Fe SN	
										7.34: BP 0° PR RF Fe SN	
										7.34-7.35: JT 20° PR RF Fe SN	
										7.36-7.40: JT 0 - 80° IR RF CN	
										7.42-7.44: JT 30° PR RF CN	
										7.50-7.57: BPx3 0 - 10° PR RF Fe SN avg sp = 20-30 mm	
										7.50-7.67: JT 60° PR RF Fe SN	
										7.61-7.64: DB	
										7.64-7.70: JT 60° PR RF CN	
										7.75-7.77: JT 30° PR RF CN	
										7.89: BP 0° PR RF CN	
										7.98-8.00: CS 20 mm, f-m, wedged	
										8.13: BP 5° PR RF CN	
										8.21: BP 5° PR RF CN	
										8.30-8.34: JTx2 30 - 40° PR RF CN	
										8.76: BP 0° PR RF CN	
										8.97: HB	
										9.00: HB	
										9.08: HB	
										9.39: BPx2 0° PR RF CN	
										9.43: JT 10° PR RF CN	
										9.43-9.63: JT 80° closed	
										9.53: BP 0° PR RF CN	
										9.69-9.77: JT 60° closed	
										9.78-9.81: JT 40° PR RF CN	
										9.97-10.05: CS 70 mm, f-c, a	
										10.33: BP 0° PR RF CN	
										10.54-10.57: JT 35° PR RF CN	
										10.78: BP 0° PR RF CN	
										10.90: BP 0° PR RF CN	
				11.00			Hole Terminated at 11.00 m Target Depth Reached. Backfilled with drilling spoil and concrete capped.				
				12							

This borehole log should be read in conjunction with Environmental Investigations Australia's accompanying standard notes.

REPORT OF BOREHOLE: BH2

Project: New Mixed-use Development	East: 333601.2 m	Depth Range: 6.50 m to 11.00 m
Location: 175 Cleveland Street, Redfern, NSW	North: 6248686.7 m MGA94 Zone 56	Contractor: Terratest Pty Ltd
Position: Refer to Figure 2	Inclination: -90°	Drill Rig: MCT-200
Job No. : E22434	Box: 1 of 1	LOGGED: SK
Client: Platinum Restaurant Group	Hole Depth: 11.00 m	CHECKED:RP
		DATE: 6/3/2015
		DATE: 16/3/2015



EXPLANATION OF NOTES, ABBREVIATIONS & TERMS USED ON BOREHOLE AND TEST PIT LOGS

DRILLING/EXCAVATION METHOD

HA	Hand Auger	RD	Rotary blade or drag bit	NQ	Diamond Core - 47 mm
DTC	Diatube Coring	RT	Rotary Tricone bit	NMLC	Diamond Core - 52 mm
NDD	Non-destructive digging	RAB	Rotary Air Blast	HQ	Diamond Core - 63 mm
AS*	Auger Screwing	RC	Reverse Circulation	HMLC	Diamond Core - 63mm
AD*	Auger Drilling	PT	Push Tube	BH	Tractor Mounted Backhoe
*V	V-Bit	CT	Cable Tool Rig	EX	Tracked Hydraulic Excavator
*T	TC-Bit, e.g. ADT	JET	Jetting	EE	Existing Excavation
ADH	Hollow Auger	WB	Washbore or Bailer	HAND	Excavated by Hand Methods

PENETRATION/EXCAVATION RESISTANCE

- L Low resistance.** Rapid penetration/ excavation possible with little effort from equipment used.
- M Medium resistance.** Penetration/ excavation possible at an acceptable rate with moderate effort from equipment used.
- H High resistance.** Penetration/ excavation is possible but at a slow rate and requires significant effort from equipment used.
- R Refusal/ Practical Refusal.** No further progress possible without risk of damage or unacceptable wear to equipment used.

These assessments are subjective and are dependent on many factors, including equipment power and weight, condition of excavation or drilling tools and experience of the operator.

WATER



Water level at date shown



Partial water loss



Water inflow



Complete water loss

GROUNDWATER NOT OBSERVED

Observation of groundwater, whether present or not, was not possible due to drilling water, surface seepage or cave-in of the borehole/ test pit.

GROUNDWATER NOT ENCOUNTERED

Borehole/ test pit was dry soon after excavation. However, groundwater could be present in less permeable strata. Inflow may have been observed had the borehole/ test pit been left open for a longer period.

SAMPLING AND TESTING

SPT	Standard Penetration Test to AS1289.6.3.1-2004
4,7,11 N=18	4,7,11 = Blows per 150mm. N = Blows per 300mm penetration following 150mm
seating 30/80mm	Where practical refusal occurs, the blows and penetration for that interval are reported
RW	Penetration occurred under the rod weight only
HW	Penetration occurred under the hammer and rod weight only
HB	Hammer double bouncing on anvil

Sampling

DS	Disturbed Sample
BDS	Bulk disturbed Sample
GS	Gas Sample
WS	Water Sample
U63	Thin walled tube sample - number indicates nominal sample diameter in millimetres

Testing

FP	Field Permeability test over section noted
FVS	Field Vane Shear test expressed as uncorrected shear strength (sv = peak value, sr = residual value)
PID	Photoionisation Detector reading in ppm
PM	Pressuremeter test over section noted
PP	Pocket Penetrometer test expressed as instrument reading in kPa
WPT	Water Pressure tests
DCP	Dynamic Cone Penetrometer test
CPT	Static Cone Penetration test
CPTu	Static Cone Penetration test with pore pressure (u) measurement

RANKING OF VISUALLY OBSERVABLE CONTAMINATION AND ODOUR (for specific soil contamination assessment)

R = 0	No visible evidence of contamination	R = A	No non-natural odours identified
R = 1	Slight evidence of visible contamination	R = B	Slight non-natural odours identified
R = 2	Visible contamination	R = C	Moderate non-natural odours identified
R = 3	Significant visible contamination	R = D	Strong non-natural odours identified

ROCK CORE RECOVERY

TCR = Total Core Recovery (%)	SCR = Solid Core Recovery (%)	RQD = Rock Quality Designation (%)
$= \frac{\text{Length of core recovered}}{\text{Length of core run}} \times 100$	$= \frac{\Sigma \text{Length of cylindrical core recovered}}{\text{Length of core run}} \times 100$	$= \frac{\Sigma \text{Axial Lengths of core} > 100\text{mm}}{\text{Length of core run}} \times 100$

MATERIAL BOUNDARIES

———— = inferred boundary - - - - - = probable boundary — ? — ? — ? — ? = possible boundary

METHOD OF SOIL DESCRIPTION USED ON BOREHOLE AND TEST PIT LOGS



FILL



**COUBLES or
BOULDERS**



**GRAVEL (GP or
GW)**



**ORGANIC SOILS
(OL, OH or Pt)**



SILT (ML or MH)



CLAY (CL, CI or CH)




SAND (SP or SW)

Combinations of these basic symbols may be used to indicate mixed materials such as sandy clay

CLASSIFICATION AND INFERRED STRATIGRAPHY

Soil is broadly classified and described in Borehole and Test Pit Logs using the preferred method given in AS1726 – 1993, (Amdt1 – 1994 and Amdt2 – 1994), Appendix A. Material properties are assessed in the field by visual/tactile methods.

PARTICLE SIZE CHARACTERISTICS			USCS SYMBOLS		
Major Division	Sub Division	Particle Size	Major Divisions	Symbol	Description
BOULDERS		>200 mm	COARSE GRAINED SOILS More than 50% by dry mass less than 63mm is greater than 0.075mm	GW	Well graded gravel and gravel-sand mixtures, little or no fines.
COBBLES		63 to 200 mm		GP	Poorly graded gravel and gravel-sand mixtures, little or no fines.
GRAVEL	Coarse	20 to 63 mm		GM	Silty gravel, gravel-sand-silt mixtures.
	Medium	6 to 20 mm		GC	Clayey gravel, gravel-sand-clay mixtures.
	Fine	2 to 6 mm		SW	Well graded sand and gravelly sand, little or no fines.
SAND	Coarse	0.6 to 2 mm		SP	Poorly graded sand and gravelly sand, little or no fines.
	Medium	0.2 to 0.6 mm		SM	Silty sand, sand-silt mixtures.
	Fine	0.075 to 0.2mm		SC	Clayey sand, sandy-clay mixtures.
SILT		0.002 to 0.075 mm		ML	Inorganic silts of low plasticity, very fine sands, rock flour, silty or clayey fine sands.
CLAY		<0.002 mm		CL	Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays.
PLASTICITY PROPERTIES			FINE GRAINED SOILS More than 50% by dry mass less than 63mm is less than 0.075mm	OL	Organic silts and organic silty clays of low plasticity.
				MH	Inorganic silts of high plasticity.
				CH	Inorganic clays of high plasticity.
				OH	Organic clays of medium to high plasticity.
				PT	Peat muck and other highly organic soils.



MOISTURE CONDITION

Symbol	Term	Description
D	Dry	Sands and gravels are free flowing. Clays & Silts may be brittle or friable and powdery.
M	Moist	Soils are darker than in the dry condition & may feel cool. Sands and gravels tend to cohere.
W	Wet	Soils exude free water. Sands and gravels tend to cohere.

Moisture content of cohesive soils may also be described in relation to plastic limit (WP) or liquid limit (WL) [» much greater than, > greater than, < less than, « much less than].

CONSISTENCY			DENSITY			
Symbol	Term	Undrained Shear Strength	Symbol	Term	Density Index %	SPT "N" #
VS	Very Soft	0. to 12 kPa	VL	Very Loose	< 15	0 to 4
S	Soft	12 to 25 kPa	L	Loose	15 to 35	4 to 10
F	Firm	25 to 50 kPa	MD	Medium Density	35 to 65	10 to 30
St	Stiff	50 to 100 kPa	D	Dense	65 to 85	30 to 50
VSt	Very Stiff	100 to 200 kPa	VD	Very Dense	Above 85	Above 50
H	Hard	Above 200 kPa				

In the absence of test results, consistency and density may be assessed from correlations with the observed behaviour of the material. # SPT correlations are not stated in AS1726 – 1993, and may be subject to corrections for overburden pressure and equipment type.

MINOR COMPONENTS

Term	Assessment Guide	Proportion by Mass
Trace	Presence just detectable by feel or eye but soil properties little or no different to general properties of primary component	Coarse grained soils: ≤ 5% Fine grained soil: ≤15%
Some	Presence easily detectable by feel or eye but soil properties little or no different to general properties of primary component	Coarse grained soils: 5 - 12% Fine grained soil: 15 - 30%

TERMS FOR ROCK MATERIAL STRENGTH AND WEATHERING

CLASSIFICATION AND INFERRED STRATIGRAPHY

Soil is broadly classified and described in Borehole and Test Pit Logs using the preferred method given in AS1726 – 1993, (Amdt1 – 1994 and Amdt2 – 1994), Appendix A. Material properties are assessed in the field by visual/ tactile methods.

STRENGTH

Symbol	Term	Point Load Index, $Is_{(50)}$ (MPa) #	Field Guide
EL	Extremely Low	< 0.03	Easily remoulded by hand to a material with soil properties.
VL	Very Low	0.03 to 0.1	Material crumbles under firm blows with sharp end of pick; can be peeled with knife; too hard to cut a triaxial sample by hand. Pieces up to 30 mm can be broken by finger pressure.
L	Low	0.1 to 0.3	Easily scored with a knife; indentations 1 mm to 3 mm show in the specimen with firm blows of pick point; has dull sound under hammer. A piece of core 150 mm long by 50 mm diameter may be broken by hand. Sharp edges of core may be friable and break during handling.
M	Medium	0.3 to 1	Readily scored with a knife; a piece of core 150 mm long by 50 mm diameter can be broken by hand with difficulty.
H	High	1 to 3	A piece of core 150 mm long by 50 mm diameter cannot be broken by hand but can be broken with pick with a single firm blow; rock rings under hammer.
VH	Very High	3 to 10	Hand specimen breaks with pick after more than one blow; rock rings under hammer.
EH	Extremely High	>10	Specimen requires many blows with geological pick to break through intact material; rock rings under hammer.

Rock Strength Test Results

▼ Point Load Strength Index, $Is_{(50)}$, Axial test (MPa)

◀ Point Load Strength Index, $Is_{(50)}$, Diametral test (MPa)

Relationship between rock strength test result ($Is_{(50)}$) and unconfined compressive strength (UCS) will vary with rock type and strength, and should be determined on a site-specific basis. UCS is typically 10 to 30 x $Is_{(50)}$, but can be as low as 5 MPa.

ROCK MATERIAL WEATHERING

Symbol	Term	Field Guide
RS	Residual Soil	Soil developed on extremely weathered rock; the mass structure and substance fabric are no longer evident; there is a large change in volume but the soil has not been significantly transported.
EW	Extremely Weathered	Rock is weathered to such an extent that it has soil properties - i.e. it either disintegrates or can be remoulded, in water.
DW	Distinctly Weathered	Rock strength usually changed by weathering. The rock may be highly discoloured, usually by iron staining. Porosity may be increased by leaching, or may be decreased due to deposition of weathering products in pores. In some environments it is convenient to subdivide into Highly Weathered and Moderately Weathered, with the degree of alteration typically less for MW.
SW	Slightly Weathered	Rock slightly discoloured but shows little or no change of strength relative to fresh rock.
FR	Fresh	Rock shows no sign of decomposition or staining.

ABBREVIATIONS AND DESCRIPTIONS FOR ROCK MATERIAL AND DEFECTS

CLASSIFICATION AND INFERRED STRATIGRAPHY

Rock is broadly classified and described in Borehole Logs using the preferred method given in AS1726 – 1993, (Amdt1 – 1994 and Amdt2 – 1994), Appendix A. Material properties are assessed in the field by visual/ tactile methods.

ROCK MATERIAL DESCRIPTION

Layering		Structure	
Term	Description	Term	Spacing (mm)
Massive	No layering apparent	Thinly laminated	<6
		Laminated	6 – 20
Poorly Developed	Layering just visible; little effect on properties	Very thinly bedded	20 – 60
		Thinly bedded	60 – 200
Well Developed	Layering (bedding, foliation, cleavage) distinct; rock breaks more easily parallel to layering	Medium bedded	200 – 600
		Thickly bedded	600 – 2,000
		Very thickly bedded	> 2,000

ABBREVIATIONS AND DESCRIPTIONS FOR DEFECT TYPES

Defect Type	Abbr.	Description
Joint	JT	Surface of a fracture or parting, formed without displacement, across which the rock has little or no tensile strength. May be closed or filled by air, water or soil or rock substance, which acts as cement.
Bedding Parting	BP	Surface of fracture or parting, across which the rock has little or no tensile strength, parallel or sub-parallel to layering/ bedding. Bedding refers to the layering or stratification of a rock, indicating orientation during deposition, resulting in planar anisotropy in the rock material.
Foliation	FL	Repetitive planar structure parallel to the shear direction or perpendicular to the direction of higher pressure, especially in metamorphic rock, e.g. Schistosity (SH) and Gneissosity.
Contact	CO	The surface between two types or ages of rock.
Cleavage	CL	Cleavage planes appear as parallel, closely spaced and planar surfaces resulting from mechanical fracturing of rock through deformation or metamorphism, independent of bedding.
Sheared Seam/ Zone (Fault)	SS/SZ	Seam or zone with roughly parallel almost planar boundaries of rock substance cut by closely spaced (often <50 mm) parallel and usually smooth or slickensided joints or cleavage planes.
Crushed Seam/ Zone (Fault)	CS/CZ	Seam or zone composed of disoriented usually angular fragments of the host rock substance, with roughly parallel near-planar boundaries. The brecciated fragments may be of clay, silt, sand or gravel sizes or mixtures of these.
Decomposed Seam/ Zone	DS/DZ	Seam of soil substance, often with gradational boundaries, formed by weathering of the rock material in places.
Infilled Seam	IS	Seam of soil substance, usually clay or clayey, with very distinct roughly parallel boundaries, formed by soil migrating into joint or open cavity.
Schistosity	SH	The foliation in schist or other coarse grained crystalline rock due to the parallel arrangement of platy or prismatic mineral grains, such as mica.
Vein	VN	Distinct sheet-like body of minerals crystallised within rock through typically open-space filling or crack-seal growth.

ABBREVIATIONS AND DESCRIPTIONS FOR DEFECT SHAPE AND ROUGHNESS

Shape	Abbr.	Description	Roughness	Abbr.	Description
Planar	PI	Consistent orientation	Polished	Pol	Shiny smooth surface
Curved	Cu	Gradual change in orientation	Slickensided	SL	Grooved or striated surface, usually polished
Undulating	Un	Wavy surface	Smooth	S	Smooth to touch. Few or no surface irregularities
Stepped	St	One or more well defined steps	Rough	RF	Many small surface irregularities (amplitude generally <1mm). Feels like fine to coarse sandpaper
Irregular	Ir	Many sharp changes in orientation	Very Rough	VR	Many large surface irregularities, amplitude generally >1mm. Feels like very coarse sandpaper

Orientation:

Vertical Boreholes – The dip (inclination from horizontal) of the defect.

Inclined Boreholes – The inclination is measured as the acute angle to the core axis.

ABBREVIATIONS AND DESCRIPTIONS FOR DEFECT COATING

DEFECT APERTURE

Coating	Abbr.	Description	Aperture	Abbr.	Description
Clean	CN	No visible coating or infilling	Closed	CL	Closed.
Stain	SN	No visible coating but surfaces are discoloured by staining, often limonite (orange-brown)	Open	O	Without any infill material.
Veneer	VNR	A visible coating of soil or mineral substance, usually too thin to measure (< 1 mm); may be patchy	Infilled	-	Soil or rock i.e. clay, talc, pyrite, quartz, etc.

APPENDIX B

LABORATORY TEST CERTIFICATES



POINT LOAD STRENGTH INDEX REPORT

AS4133 4.1

Client:	Environmental Investigations	Moisture Content Condition:	As received
Address:	Suite 6.01, 55 Miller Street Pyrmont NSW 2009	Storage History:	Core Boxes
Project:	175 Cleveland Street, Redfern (E22434)	Report No:	S2439-PLT
Job No:	S15056	Date Tested:	13/03/2015

Test Procedure: ☒ AS4133 4.1 Rock strength tests - Determination of point load strength index

Sampling: Sampled by Client **Date Sampled:** Unknown

Preparation: Prepared in accordance with the test method

Sample Number	Borehole ID	Depth (m)	Sample Description	Test Type	Average Width (mm)	Platen Separation (mm)	Failure Load (kN)	Point Load Index Is (MPa)	Point Load Index Is ₍₅₀₎ (MPa)	Notes
S2439	BH2	6.50-6.60	Sandstone	Diametral	-	50.0	0.11	0.04	0.04	
				Axial	50.0	43.0	0.10	0.04	0.04	
S2440	BH2	7.10-7.20	Siltstone	Diametral	-	52.0	0.25	0.09	0.09	
				Axial	52.0	47.0	1.48	0.47	0.50	
S2441	BH2	8.20-8.30	Siltstone	Diametral	-	52.0	0.25	0.09	0.09	
				Axial	52.0	38.0	0.85	0.34	0.34	
S2442	BH2	9.30-9.40	Siltstone	Diametral	-	52.0	0.05	0.02	0.02	
				Axial	52.0	42.0	0.64	0.23	0.24	

Comments:



The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025. This document shall not be reproduced, except in full.

NATA Accredited Laboratory Number: 14874

Authorised Signatory:

Chris Lloyd

Chris Lloyd

16/03/2015

Date:



Facility Name: Sydney Branch Site
Facility Location: 8/10 Bradford Street, Alexandria NSW 2015
Site No.: 22365

Macquarie Geotechnical
3 Watt Drive
BATHURST NSW 2795

SOIL CLASSIFICATION REPORT

Client:	Environmental Investigations	Source:	BH1 1.50-1.95m
Address:	Suite 6.01, 55 Miller Street Pyrmont NSW 2009	Sample Description:	sandy CLAY
Project:	175 Cleveland Street, Redfern (E22434)	Report No:	S2437-PI
Job No:	S15056	Lab No:	S2437

Test Procedure:	<input checked="" type="checkbox"/> AS1289 2.1.1 Soil moisture content tests (Oven drying method)
	<input type="checkbox"/> AS1289 3.1.1 Soil classification tests - Determination of the liquid limit of a soil - Four point casagrande method
	<input checked="" type="checkbox"/> AS1289 3.1.2 Soil classification tests - Determination of the liquid limit if a soil - One point Casagrande method (subsidiary method)
	<input checked="" type="checkbox"/> AS1289 3.2.1 Soil classification tests - Determination of the plastic limit of a soil - Standard method
	<input checked="" type="checkbox"/> AS1289 3.3.1 Soil classification tests - Calculation of the plasticity Index of a soil
	<input checked="" type="checkbox"/> AS1289 3.4.1 Soil classification tests - Determination of the linear shrinkage of a soil - Standard method

Sampling:	Sampled by Client	Date Sampled:	Unknown
Preparation:	Prepared in accordance with the test method		


Liquid Limit (%): 31

Linear Shrinkage (%): 10.0

Plastic Limit (%): 16

Field Moisture Content (%): 17.6

Plastic Index: 15



Soil Preparation Method: Dry Sieved

Soil History: Oven Dried

Soil Condition: Linear



The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025. This document shall not be reproduced, except in full.

NATA Accredited Laboratory Number: 14874

Authorised Signatory:

Chris Lloyd

16/03/2015

Date:



Facility Name: Sydney Branch Site
Location: 8/10 Bradford St, Alexandria NSW 2015
Site No.: 22365

Facility

Macquarie Geotechnical
3 Watt Drive
Bathurst NSW 2795

SOIL CLASSIFICATION REPORT

Client:	Environmental Investigations	Source:	BH2 4.50-4.95m
Address:	Suite 6.01, 55 Miller Street Pyrmont NSW 2009	Sample Description:	sandy CLAY
Project:	175 Cleveland Street, Redfern (E22434)	Report No:	S2438-PI
Job No:	S15056	Lab No:	S2438

Test Procedure:	<input checked="" type="checkbox"/> AS1289 2.1.1 Soil moisture content tests (Oven drying method)
	<input type="checkbox"/> AS1289 3.1.1 Soil classification tests - Determination of the liquid limit of a soil - Four point casagrande method
	<input checked="" type="checkbox"/> AS1289 3.1.2 Soil classification tests - Determination of the liquid limit if a soil - One point Casagrande method (subsidiary method)
	<input checked="" type="checkbox"/> AS1289 3.2.1 Soil classification tests - Determination of the plastic limit of a soil - Standard method
	<input checked="" type="checkbox"/> AS1289 3.3.1 Soil classification tests - Calculation of the plasticity Index of a soil
	<input checked="" type="checkbox"/> AS1289 3.4.1 Soil classification tests - Determination of the linear shrinkage of a soil - Standard method

Sampling:	Sampled by Client	Date Sampled:	Unknown
Preparation:	Prepared in accordance with the test method		


Liquid Limit (%): 38

Linear Shrinkage (%): 8.5

Plastic Limit (%): 22

Field Moisture Content (%): 14.9

Plastic Index: 16



Soil Preparation Method: Dry Sieved

Soil History: Oven Dried

Soil Condition: Linear



The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025. This document shall not be reproduced, except in full.

NATA Accredited Laboratory Number: 14874

Authorised Signatory:

Chris Lloyd

16/03/2015

Date:



Facility Name: Sydney Branch Site
Location: 8/10 Bradford St, Alexandria NSW 2015
Site No.: 22365

Facility

Macquarie Geotechnical
3 Watt Drive
Bathurst NSW 2795

CERTIFICATE OF ANALYSIS

124935

Client:

Macquarie Geotech

3 Watt Dr

Bathurst

NSW 2795

Attention: Chris Lloyd

Sample log in details:

Your Reference:

S15056, Refern

No. of samples:

2 soils

Date samples received / completed instructions received

11/03/15

/ 11/03/15

Analysis Details:

Please refer to the following pages for results, methodology summary and quality control data.

Samples were analysed as received from the client. Results relate specifically to the samples as received.

Results are reported on a dry weight basis for solids and on an as received basis for other matrices.

Please refer to the last page of this report for any comments relating to the results.

Report Details:

Date results requested by: / Issue Date:

18/03/15

/ 13/03/15

Date of Preliminary Report:

Not Issued

NATA accreditation number 2901. This document shall not be reproduced except in full.

Accredited for compliance with ISO/IEC 17025.

Tests not covered by NATA are denoted with *.

Results Approved By:



Jacinta Hurst
Laboratory Manager

Misc Inorg - Soil			
Our Reference:	UNITS	124935-1	124935-2
Your Reference	-----	S2437	S2438
Depth	-----	1.5-1.95	4.5-4.95
Type of sample		Soil	Soil
Sample ID		BH3	BH2
Date prepared	-	12/03/2015	12/03/2015
Date analysed	-	12/03/2015	12/03/2015
pH 1:5 soil:water	pH Units	6.4	5.3
Chloride, Cl 1:5 soil:water	mg/kg	20	<10
Sulphate, SO ₄ 1:5 soil:water	mg/kg	240	82
Resistivity in soil*	ohmm	150	34

MethodID	Methodology Summary
Inorg-001	pH - Measured using pH meter and electrode in accordance with APHA latest edition, 4500-H+. Please note that the results for water analyses are indicative only, as analysis outside of the APHA storage times.
Inorg-081	Anions - a range of Anions are determined by Ion Chromatography, in accordance with APHA latest edition, 4110-B.
Inorg-002	Conductivity and Salinity - measured using a conductivity cell at 25oC in accordance with APHA 22nd ED 2510 and Rayment & Lyons. Resistivity is calculated from Conductivity.

Client Reference: S15056, Refern

QUALITY CONTROL	UNITS	PQL	METHOD	Blank	Duplicate Sm#	Duplicate results	Spike Sm#	Spike % Recovery
Misc Inorg - Soil						Base Duplicate %RPD		
Date prepared	-			12/03/2015	124935-1	12/03/2015 12/03/2015	LCS-1	12/03/2015
Date analysed	-			12/03/2015	124935-1	12/03/2015 12/03/2015	LCS-1	12/03/2015
pH 1:5 soil:water	pH Units		Inorg-001	[NT]	124935-1	6.4 6.4 RPD: 0	LCS-1	102%
Chloride, Cl 1:5 soil:water	mg/kg	10	Inorg-081	<10	124935-1	20 20 RPD: 0	LCS-1	103%
Sulphate, SO4 1:5 soil:water	mg/kg	10	Inorg-081	<10	124935-1	240 260 RPD: 8	LCS-1	115%
Resistivity in soil*	ohmm	1	Inorg-002	<1.0	124935-1	150 160 RPD: 6	[NR]	[NR]

Report Comments:

Asbestos ID was analysed by Approved Identifier:	Not applicable for this job
Asbestos ID was authorised by Approved Signatory:	Not applicable for this job

INS: Insufficient sample for this test	PQL: Practical Quantitation Limit	NT: Not tested
NA: Test not required	RPD: Relative Percent Difference	NA: Test not required
<: Less than	>: Greater than	LCS: Laboratory Control Sample

Quality Control Definitions

Blank: This is the component of the analytical signal which is not derived from the sample but from reagents, glassware etc, can be determined by processing solvents and reagents in exactly the same manner as for samples.

Duplicate: This is the complete duplicate analysis of a sample from the process batch. If possible, the sample selected should be one where the analyte concentration is easily measurable.

Matrix Spike: A portion of the sample is spiked with a known concentration of target analyte. The purpose of the matrix spike is to monitor the performance of the analytical method used and to determine whether matrix interferences exist.

LCS (Laboratory Control Sample): This comprises either a standard reference material or a control matrix (such as a blank sand or water) fortified with analytes representative of the analyte class. It is simply a check sample.

Surrogate Spike: Surrogates are known additions to each sample, blank, matrix spike and LCS in a batch, of compounds which are similar to the analyte of interest, however are not expected to be found in real samples.

Laboratory Acceptance Criteria

Duplicate sample and matrix spike recoveries may not be reported on smaller jobs, however, were analysed at a frequency to meet or exceed NEPM requirements. All samples are tested in batches of 20. The duplicate sample RPD and matrix spike recoveries for the batch were within the laboratory acceptance criteria.

Filters, swabs, wipes, tubes and badges will not have duplicate data as the whole sample is generally extracted during sample extraction.

Spikes for Physical and Aggregate Tests are not applicable.

For VOCs in water samples, three vials are required for duplicate or spike analysis.

Duplicates: <5xPQL - any RPD is acceptable; >5xPQL - 0-50% RPD is acceptable.

Matrix Spikes, LCS and Surrogate recoveries: Generally 70-130% for inorganics/metals; 60-140% for organics and 10-140% for SVOC and speciated phenols is acceptable.

In circumstances where no duplicate and/or sample spike has been reported at 1 in 10 and/or 1 in 20 samples respectively, the sample volume submitted was insufficient in order to satisfy laboratory QA/QC protocols.

When samples are received where certain analytes are outside of recommended technical holding times (THTs), the analysis has proceeded. Where analytes are on the verge of breaching THTs, every effort will be made to analyse within the THT or as soon as practicable.

APPENDIX C

IMPORTANT INFORMATION



Important Information

SCOPE OF SERVICES

The geotechnical report (“the report”) has been prepared in accordance with the scope of services as set out in the contract, or as otherwise agreed, between the Client and Environmental Investigations (“EI”). The scope of work may have been limited by a range of factors such as time, budget, access and/or site disturbance constraints.

RELIANCE ON DATA

EI has relied on data provided by the Client and other individuals and organizations, to prepare the report. Such data may include surveys, analyses, designs, maps and plans. EI has not verified the accuracy or completeness of the data except as stated in the report. To the extent that the statements, opinions, facts, information, conclusions and/or recommendations (“conclusions”) are based in whole or part on the data, EI will not be liable in relation to incorrect conclusions should any data, information or condition be incorrect or have been concealed, withheld, misrepresented or otherwise not fully disclosed to EI.

GEOTECHNICAL ENGINEERING

Geotechnical engineering is based extensively on judgment and opinion. It is far less exact than other engineering disciplines. Geotechnical engineering reports are prepared for a specific client, for a specific project and to meet specific needs, and may not be adequate for other clients or other purposes (e.g. a report prepared for a consulting civil engineer may not be adequate for a construction contractor). The report should not be used for other than its intended purpose without seeking additional geotechnical advice. Also, unless further geotechnical advice is obtained, the report cannot be used where the nature and/or details of the proposed development are changed.

LIMITATIONS OF SITE INVESTIGATION

The investigation programme undertaken is a professional estimate of the scope of investigation required to provide a general profile of subsurface conditions. The data derived from the site investigation programme and subsequent laboratory testing are extrapolated across the site to form an inferred geological model, and an engineering opinion is rendered about overall subsurface conditions and their likely behaviour with regard to the proposed development. Despite investigation, the actual conditions at the site might differ from those inferred to exist, since no subsurface exploration program, no matter how comprehensive, can reveal all subsurface details and anomalies.

The engineering logs are the subjective interpretation of subsurface conditions at a particular location and time, made by trained personnel. The actual interface between materials may be more gradual or abrupt than a report indicates.

SUBSURFACE CONDITIONS ARE TIME DEPENDENT

Subsurface conditions can be modified by changing natural forces or man-made influences. The report is based on conditions that existed at the time of subsurface exploration. Construction operations adjacent to the site, and natural events such as floods, or ground water fluctuations, may also affect subsurface conditions, and thus the continuing adequacy of a geotechnical report. EI should be kept apprised of any such events, and should be consulted to determine if any additional tests are necessary.

VERIFICATION OF SITE CONDITIONS

Where ground conditions encountered at the site differ significantly from those anticipated in the report, either due to natural variability of subsurface conditions or construction activities, it is a condition of the report that EI be notified of any variations and be provided with an opportunity to review the recommendations of this report. Recognition of change of soil and rock conditions requires experience and it is recommended that a suitably experienced geotechnical engineer be engaged to visit the site with sufficient frequency to detect if conditions have changed significantly.

REPRODUCTION OF REPORTS

This report is the subject of copyright and shall not be reproduced either totally or in part without the express permission of this Company. Where information from the accompanying report is to be included in contract documents or engineering specification for the project, the entire report should be included in order to minimize the likelihood of misinterpretation from logs.

REPORT FOR BENEFIT OF CLIENT

The report has been prepared for the benefit of the Client and no other party. EI assumes no responsibility and will not be liable to any other person or organisation for or in relation to any matter dealt with or conclusions expressed in the report, or for any loss or damage suffered by any other person or organisation arising from matters dealt with or conclusions expressed in the report (including without limitation matters arising from any negligent act or omission of EI or for any loss or damage suffered by any other party relying upon the matters dealt with or conclusions expressed in the report). Other parties should not rely upon the report or the accuracy or completeness of any conclusions and should make their own inquiries and obtain independent advice in relation to such matters.

OTHER LIMITATIONS

EI will not be liable to update or revise the report to take into account any events or emergent circumstances or fact occurring or becoming apparent after the date of the report.

