

THE WORKS CORRIMAL - STAGE 2A

BASIX Summary Table - Building 2.1

Aspire Sustainability Consulting BASIX Specifications		Certificate No:	
P067004 Building 2.1 Corrimal Coke Works, Railway Street Corrimal NSW 2518		P067004 Building 2.1 Corrimal Coke Works, Railway Street Corrimal NSW 2518	
Target	Project Score	Compliance	
Water	40	40	Pass
Energy	61	61	Pass
Thermal Comfort		Pass	Pass
Material		N/A	N/A
Minimum Glazing Performance Requirements: Typical Glazing for All Levels			
Performance (Total System)	Description	Comment	Location
≤U4.10 SHGC0.47±5%	Double Glazed, Light Tint / Clear	Awning Glazing & Hinged Doors Glazing	All Units unless specified otherwise
≤U3.60 SHGC0.49±5%	Double Glazed, Light Tint / Clear	Fixed, Sliding Door & Double Hung Glazing	All Units unless specified otherwise
Minimum Insulation Performance Requirements:			
Construction Element	Additional Insulation		
Concrete Roof Medium Colour Roof	Waterproof membrane ≥R2.50 with reflective backing facing cavity/ceiling void ≥20mm Units: All other units on Level 3 apartment ceilings to roof above & 2.1G01, 2.1G03, 2.1G05, 2.1G06, 2.1207 where exposed above		
External Walls Brick Veneer/FC Cladding/Metal Cladding/Hebel - Light/Medium/Dark Colour (as shown on elevations)	≥R2.50		
Floor Slab Suspended Slab over Unconditioned spaces and Exposed Air	≥R1.00 in direct contact with Slab Soffit Units: 2.1G01, 2.1G02, 2.1G04, 2.1G03, 2.1G05, 2.1G06, 2.1108, 2.1201		
Internal Walls	No Insulation		
Intertenancy Walls & Walls to Corridor, Lifts & Fire Stairs	RVaries Per Acoustic Specification		
Floor Coverings	Tile to Wet Rooms Carpet and Underlay to Bedrooms Timber to All Other Areas		
Ceilings	Plasterboard Ceilings		
Ceiling Penetrations	No RCPs provided with current assessment. Following assumptions have been made: - 1 x LED Downlight allocated per 5m ² - 1 x Exhaust Fan per wet area and kitchen		
Ceiling Fans	1 x 1200mm ceiling fan required to Kitchen & Living: 2.1104, 2.1105 No Ceiling Fan required for remaining units.		
Other Modelling Assumptions			
All modelled downlights are assumed to be Sealed LEDs, with insulation clearance of 150mm to either side of fixture All glazing where there is fall risk to have window restrictors installed.			
Summary of Requirements: Common Areas			
Category	Item	Comment	
Water	Fixtures	No common shower No common toilets No common taps	
	Appliances	No common laundry facility	
	Landscape - Common	224.1m ² Common area lawn (TBC) 224.1m ² Common area garden including 112.05m ² Area of indigenous or low water use species (TBC)	
	RW Tank	10kL RW tank Served by 488m ² roof area (50% of available roof area), 0m ² impervious area and 0m ² planter box area Serving 448.2m ² common landscape (TBC) and 0 car wash bay	
	Fire Sprinkler System	Re-use of fire system test water is not required	
	Pool	No Pool	
Energy	Lighting Type	LED required throughout	
	Lighting Control	Please refer to BASIX Report for detailed requirements	
	Ventilation		
	Lifts	Gearless traction with VVVF motors required	
	Hot Water	Central Hot Water: Electric instantaneous R0.6 Piping insulation internal and external to building	
	Spa	No Spa	
	Pool	No Pool	
	Solar PV	10kW PV required	
Other	No BMS No indoor or outdoor drying line No common laundry No common clothes dryer		
Summary of Requirements: Residential Dwellings			
Category	Item	Comment	
Water	Fixtures	4 star showers (>4.5 but ≤6 L/min) 4 star toilets 5 star taps kitchen taps 5 star taps bathroom taps No HW recirculation on demand	
	Appliances	5 star dishwasher 4 star clothes washer (required to be installed to at least 5 x 3-Bed Units) Remaining units: No clothes washer specified	
Energy	Exhaust Fans	Kitchen, Laundry & bathroom fans individually ducted to façade or roof manual on/off	
	HVAC	Central cooling system: Variable refrigerant volum units Electric driven compressor Air cooled condenser COP 3.5-5.5 Central heating system: Variable refrigerant volum units Electric driven compressor + Air sourced evaporator COP 3.5-5.5	
	Lighting	Sealed LED lighting throughout	
	Hot Water	Central Hot Water: Electric instantaneous	
	Appliances	Induction cooktop & electric oven 3.5 star dishwasher specified 2 star dryer specified	
	Other	No Indoor clothes drying line provided No Outdoor Private clothes drying line provided	

BASIX Summary Table - Building 2.2

Aspire Sustainability Consulting BASIX Specifications		Certificate No:	
P067004 Building 2.2 Corrimal Coke Works, Railway Street Corrimal NSW 2518		P067004 Building 2.2 Corrimal Coke Works, Railway Street Corrimal NSW 2518	
Target	Project Score	Compliance	
Water	40	41	Pass
Energy	60	60	Pass
Thermal Comfort		Pass	Pass
Material		N/A	N/A
Minimum Glazing Performance Requirements: Typical Glazing for All Levels			
Performance (Total System)	Description	Comment	Location
≤U4.10 SHGC0.47±5%	Double Glazed, Light Tint / Clear	Awning Glazing & Hinged Doors Glazing	All Units unless specified otherwise
≤U3.60 SHGC0.49±5%	Double Glazed, Light Tint / Clear	Fixed, Sliding Door & Double Hung Glazing	All Units unless specified otherwise
Minimum Insulation Performance Requirements:			
Construction Element	Additional Insulation		
Concrete Roof Medium Colour Roof	Waterproof membrane ≥R4.00 with reflective backing facing cavity/ceiling void ≥20mm Units: 2.2502 ≥R2.50 with reflective backing facing cavity/ceiling void ≥20mm Units: All other units on Level 5 apartment ceilings to roof above & 2.2G01, 2.2G03, 2.2G04, 2.2G06, 2.2G07, 2.2301, 2.2302, 2.2303, 2.2306, 2.2307, 2.2308, 2.2309, 2.2310, 2.2211, 2.2401, 2.2402, 2.2405, 2.2406, 2.2407 where exposed above		
External Walls Brick Veneer/FC Cladding/Metal Cladding/Hebel - Light/Medium/Dark Colour (as shown on elevations)	≥R2.50		
Floor Slab Suspended Slab over Unconditioned spaces and Exposed Air	≥R2.00 in direct contact with Slab Soffit Units: 2.2G03, 2.2G04 ≥R1.00 in direct contact with Slab Soffit Units: All other units on Ground Floor, 2.2104, 2.2204, 2.2407		
Internal Walls	No Insulation		
Intertenancy Walls & Walls to Corridor, Lifts & Fire Stairs	RVaries Per Acoustic Specification		
Floor Coverings	Tile to Wet Rooms Carpet and Underlay to Bedrooms Timber to All Other Areas		
Ceilings	Plasterboard Ceilings		
Ceiling Penetrations	No RCPs provided with current assessment. Following assumptions have been made: - 1 x LED Downlight allocated per 5m ² - 1 x Exhaust Fan per wet area and kitchen		
Ceiling Fans	1 x 1200mm ceiling fan required to Kitchen & Living: 2.2G03, 2.2G04, 2.2502 No Ceiling Fan required for remaining units.		
Other Modelling Assumptions			
All modelled downlights are assumed to be Sealed LEDs, with insulation clearance of 150mm to either side of fixture All glazing where there is fall risk to have window restrictors installed.			
Summary of Requirements: Common Areas			
Category	Item	Comment	
Water	Fixtures	No common shower No common toilets No common taps	
	Appliances	No common laundry facility	
	Landscape - Common	407.6m ² Common area lawn (TBC) 407.6m ² Common area garden including 203.8m ² Area of indigenous or low water use species (TBC)	
	RW Tank	10kL RW tank Served by 427m ² roof area (50% of available roof area), 0m ² impervious area and 0m ² planter box area Serving 815.2m ² common landscape (TBC) and 1 car wash bay	
	Fire Sprinkler System	Re-use of fire system test water is not required	
	Pool	No Pool	
Energy	Lighting Type	LED required throughout	
	Lighting Control	Please refer to BASIX Report for detailed requirements	
	Ventilation		
	Lifts	Gearless traction with VVVF motors required	
	Hot Water	Central Hot Water: Electric instantaneous R0.6 Piping insulation internal and external to building	
	Spa	No Spa	
	Pool	No Pool	
	Solar PV	20kW PV required	
Other	No BMS No indoor or outdoor drying line No common laundry No common clothes dryer		
Summary of Requirements: Residential Dwellings			
Category	Item	Comment	
Water	Fixtures	4 star showers (>4.5 but ≤6 L/min) 4 star toilets 5 star taps kitchen taps 5 star taps bathroom taps No HW recirculation on demand	
	Appliances	5 star dishwasher No clothes washer specified	
Energy	Exhaust Fans	Kitchen, Laundry & bathroom fans individually ducted to façade or roof manual on/off	
	HVAC	Central cooling system: Variable refrigerant volum units Electric driven compressor Air cooled condenser COP 3.5-5.5 Central heating system: Variable refrigerant volum units Electric driven compressor + Air sourced evaporator COP 3.5-5.5	
	Lighting	Sealed LED lighting throughout	
	Hot Water	Central Hot Water: Electric instantaneous	
	Appliances	Induction cooktop & electric oven 3.5 star dishwasher specified 2 star dryer specified	
	Other	No Indoor clothes drying line provided No Outdoor Private clothes drying line provided	

BASIX Summary Table - Building 2.3 & 2.4

Aspire Sustainability Consulting BASIX Specifications		Certificate No:	
P067004 Building 2.3&2.4 Corrimal Coke Works, Railway Street Corrimal NSW 2518		P067004 Building 2.3&2.4 Corrimal Coke Works, Railway Street Corrimal NSW 2518	
Target	Project Score	Compliance	
Water	40	41	Pass
Energy	60	60	Pass
Thermal Comfort		Pass	Pass
Material		N/A	N/A
Minimum Glazing Performance Requirements: Typical Glazing for All Levels			
Performance (Total System)	Description	Comment	Location
≤U4.10 SHGC0.47±5%	Double Glazed, Light Tint / Clear	Awning Glazing & Hinged Doors Glazing	All Units unless specified otherwise
≤U3.60 SHGC0.49±5%	Double Glazed, Light Tint / Clear	Fixed, Sliding Door & Double Hung Glazing	All Units unless specified otherwise
Minimum Insulation Performance Requirements:			
Construction Element	Additional Insulation		
Concrete Roof Medium Colour Roof	Waterproof membrane ≥R4.00 with reflective backing facing cavity/ceiling void ≥20mm Units: 2.3501 ≥R2.50 with reflective backing facing cavity/ceiling void ≥20mm Units: All other units on Level 5 apartment ceilings to roof above & 2.3G01, 2.3G07, 2.3G08, 2.3308, 2.3309, 2.3404, 2.3405, 2.4301, 2.4305, 2.4306, 2.4310 where exposed above		
External Walls Brick Veneer/FC Cladding/Metal Cladding/Hebel - Light/Medium/Dark Colour (as shown on elevations)	≥R2.50		
Floor Slab Suspended Slab over Unconditioned spaces and Exposed Air	≥R1.50 in direct contact with Slab Soffit Units: 2.3G01, 2.4G03 ≥R1.00 in direct contact with Slab Soffit Units: All other units on Ground Floor, 2.3104, 2.3109, 2.3205, 2.4102, 2.4106, 2.4111, 2.4112		
Internal Walls	No Insulation		
Intertenancy Walls & Walls to Corridor, Lifts & Fire Stairs	RVaries Per Acoustic Specification		
Floor Coverings	Tile to Wet Rooms Carpet and Underlay to Bedrooms Timber to All Other Areas		
Ceilings	Plasterboard Ceilings		
Ceiling Penetrations	No RCPs provided with current assessment. Following assumptions have been made: - 1 x LED Downlight allocated per 5m ² - 1 x Exhaust Fan per wet area and kitchen		
Ceiling Fans	1 x 1200mm ceiling fan required to Kitchen & Living: 2.3202, 2.3104, 2.3304, 2.3204, 2.3205, 2.3305, 2.3405, 2.4203, 2.4105, 2.4106, 2.4205, 2.4206, 2.4305, 2.4306 No Ceiling Fan required for remaining units.		
Other Modelling Assumptions			
All modelled downlights are assumed to be Sealed LEDs, with insulation clearance of 150mm to either side of fixture All glazing where there is fall risk to have window restrictors installed.			
Summary of Requirements: Common Areas			
Category	Item	Comment	
Water	Fixtures	No common shower No common toilets No common taps	
	Appliances	No common laundry facility	
	Landscape - Common	1,972m ² Common area lawn (TBC) 1,972m ² Common area garden including 986m ² Area of indigenous or low water use species (TBC)	
	RW Tank	10kL RW tank Served by 1,200m ² roof area (50% of available roof area), 0m ² impervious area and 0m ² planter box area Serving 3,944m ² common landscape (TBC) and 1 car wash bay	
	Fire Sprinkler System	Re-use of fire system test water is not required	
	Pool	No Pool	
Energy	Lighting Type	LED required throughout	
	Lighting Control	Please refer to BASIX Report for detailed requirements	
	Ventilation		
	Lifts	Gearless traction with VVVF motors required	
	Hot Water	Central Hot Water: Electric instantaneous R0.6 Piping insulation internal and external to building	
	Spa	No Spa	
	Pool	No Pool	
	Solar PV	25kW PV required	
Other	No BMS No indoor or outdoor drying line No common laundry No common clothes dryer		
Summary of Requirements: Residential Dwellings			
Category	Item	Comment	
Water	Fixtures	4 star showers (>4.5 but ≤6 L/min) 4 star toilets 5 star taps kitchen taps 5 star taps bathroom taps No HW recirculation on demand	
	Appliances	5 star dishwasher No clothes washer specified	
Energy	Exhaust Fans	Kitchen, Laundry & bathroom fans individually ducted to façade or roof manual on/off	
	HVAC	Central cooling system: Variable refrigerant volum units Electric driven compressor Air cooled condenser COP 3.5-5.5 Central heating system: Variable refrigerant volum units Electric driven compressor + Air sourced evaporator COP 3.5-5.5	
	Lighting	Sealed LED lighting throughout	
	Hot Water	Central Hot Water: Electric instantaneous	
	Appliances	Induction cooktop & electric oven 3.5 star dishwasher specified 2 star dryer specified	
	Other	No Indoor clothes drying line provided No Outdoor Private clothes drying line provided	

BASIX™ Certificate

Building Sustainability Index

www.planningportal.nsw.gov.au/development-and-assessment/basix

Multi Dwelling

Certificate number: 1826444M_02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.planningportal.nsw.gov.au/definitions

Secretary

Date of issue: Tuesday, 16 December 2025

To be valid, this certificate must be submitted with a development application or lodged with a complying development certificate application within 3 months of the date of issue.



When submitting this BASIX certificate with a development application or complying development certificate application, it must be accompanied by NatHERS certificate 0012158830.

Project summary

Project name	Corrimal Stage 2A - Building 2.1 (Lot 9)_02
Street address	27 RAILWAY STREET CORRIMAL 2518
Local Government Area	WOLLONGONG
Plan type and plan number	Deposited Plan DP1313981
Lot no.	9
Section no.	-
No. of residential flat buildings	1
Residential flat buildings: no. of dwellings	31
Multi-dwelling housing: no. of dwellings	0
No. of single dwelling houses	0

Project score

Water	✓ 40	Target 40
Thermal Performance	✓ Pass	Target Pass
Energy	✓ 61	Target 61
Materials	✓ -100	Target n/a

Certificate Prepared by

Name / Company Name: Aspire Sustainability Consulting Pty Ltd

ABN (if applicable): 62636142017

Description of project

Project address	
Project name	Corrimal Stage 2A - Building 2.1 (Lot 9)_02
Street address	27 RAILWAY STREET CORRIMAL 2518
Local Government Area	WOLLONGONG
Plan type and plan number	Deposited Plan DP1313981
Lot no.	9
Section no.	-
Project type	
No. of residential flat buildings	1
Residential flat buildings: no. of dwellings	31
Multi-dwelling housing: no. of dwellings	0
No. of single dwelling houses	0
Site details	
Site area (m ²)	2312
Roof area (m ²)	977.62
Non-residential floor area (m ²)	0
Residential car spaces	40
Non-residential car spaces	-

Common area landscape		
Common area lawn (m ²)	224.1	
Common area garden (m ²)	224.1	
Area of indigenous or low water use species (m ²)	112.05	
Assessor details and thermal loads		
Assessor number	10070	
Certificate number	0012158830	
Climate zone	56	
Project score		
Water	✔ 40	Target 40
Thermal Performance	✔ Pass	Target Pass
Energy	✔ 61	Target 61
Materials	✔ -100	Target n/a

Description of project

The tables below describe the dwellings and common areas within the project

Residential flat buildings - Building 2.1, 31 dwellings, 4 storeys above ground

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
101	1	81	0	0	0
105	2	81	0	0	0
201	1	52	0	0	0
205	3	113	0	0	0
209	2	93	0	0	0
304	2	81	0	0	0
G01	1	60	0	22.76	0
G05	2	81	0	21.75	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
102	2	81	0	0	0
106	2	102	0	0	0
202	1	52	0	0	0
206	2	81	0	0	0
301	1	52	0	0	0
305	3	112	0	0	0
G02	2	82	0	65.72	0
G06	2	90	0	63.49	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
103	3	112	0	0	0
107	2	105	0	0	0
203	1	81	0	0	0
207	2	81	0	0	0
302	1	52	0	0	0
306	3	117	0	0	0
G03	2	105	0	70.16	0
G07	2	86	0	74.93	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
104	2	81	0	0	0
108	1	52	0	0	0
204	2	81	0	0	0
208	3	115	0	0	0
303	1	81	0	0	0
307	2	93	0	0	0
G04	2	81	0	21.69	0

Description of project

The tables below describe the dwellings and common areas within the project

Schedule of BASIX commitments

1. Commitments for Residential flat buildings - Building 2.1

(a) Buildings

(i) Materials

(b) Dwellings

(i) Water

(ii) Energy

(iii) Thermal Performance

(c) Common areas and central systems/facilities

(i) Water

(ii) Energy

2. Commitments for common areas and central systems/facilities for the development (non-building specific)

(b) Common areas and central systems/facilities

(i) Water

(ii) Energy

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

1. Commitments for Residential flat buildings - Building 2.1

(a) Buildings

(i) Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Floor types", "External wall types", "Internal wall types", "Ceiling and roof types", "Frames" and "Glazing" tables below.			✓
(b) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all specifications included in the tables below.		✓	
(c) The applicant must construct the floors, walls, roof, ceiling and roof, windows, glazed doors and skylights of the development in accordance with the specifications listed in the tables below. In the case of glazing, a 5% variance from the area values listed in the "Frames" and "Glazing" tables is permitted.	✓	✓	✓
(d) The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the below tables.			✓

Floor types

Floor type	Area (m2)	Insulation	Low emissions option
floors above habitable rooms, frame: suspended concrete slab	182.22	-	-
floors above habitable rooms, frame: suspended concrete slab	184	-	-
concrete slab on ground, frame:	1598.29	-	none
floors above habitable rooms, frame: suspended concrete slab	1980	-	-
floors above habitable rooms, frame: suspended concrete slab	86	-	-
floors above habitable rooms, frame: suspended concrete slab	602	fibreglass batts or roll	-

External wall types

External wall type	Construction type	Area (m2)	Low emissions option	Insulation
External wall type 1	framed (fibre cement sheet or boards),frame:light steel frame	324.1	-	fibreglass batts or roll
External wall type 2	AAC veneer,frame:light steel frame	104.3	-	fibreglass batts or roll
External wall type 3	AAC veneer,frame:light steel frame	12	-	-
External wall type 4	brick veneer,frame:light steel frame	117.5	-	fibreglass batts or roll
External wall type 5	brick veneer,frame:light steel frame	47.4	-	-
External wall type 6	off form concrete,frame:no frame	4587	none	-

Internal wall types

Internal wall type	Construction type	Area (m2)	Insulation
Internal wall type 1	75 mm AAC panel, frame:light steel frame	835.78	fibreglass batts or roll
Internal wall type 2	75 mm AAC panel, frame:light steel frame	493	fibreglass batts or roll
Internal wall type 3	block with low cement content and reconstituted sawdust, frame:no frame	669.4	-
Internal wall type 4	block with low cement content and reconstituted sawdust, frame:no frame	440.8	fibreglass batts or roll
Internal wall type 5	plasterboard, frame:light steel frame	598.5	-

Reinforcement concrete frames/columns

Building has reinforced concrete frame/columns?	Volume (m³)	Low emissions option
yes	76.52	-

Ceiling and roof types

Ceiling and roof type	Area (m²)	Roof Insulation	Ceiling Insulation
concrete - bare internal, frame: no frame	1893.92	-	-
concrete - plasterboard internal, frame: light steel frame	774.08	foil backed blanket	fibreglass batts or roll
concrete - bare internal, frame: no frame	78.53	-	-
concrete - plasterboard internal, frame: light steel frame	287.69	foil backed blanket	fibreglass batts or roll

Glazing types			Frame types				
Single glazing (m ²)	Double glazing (m ²)	Triple glazing (m ²)	Aluminium frames (m ²)	Timber frames (m ²)	uPVC frames (m ²)	Steel frames (m ²)	Composite frames (m ²)
35	570.9	-	605.9	-	-	-	-

(b) Dwellings








(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	✔	✔	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		✔	✔
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		✔	✔
(e) The applicant must install: (aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and (bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling.		✔ ✔	✔ ✔
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	✔	✔	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		✔	
(g) The pool or spa must be located as specified in the table.	✔	✔	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	✔	✔	✔

Dwelling no.	Fixtures					Appliances		Individual pool				Individual spa		
	All shower-heads	All toilet flushing systems	All kitchen taps	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish-washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
103, 205, 208, 305, 306	4 star (> 4.5 but <= 6 L/min)	4 star	5 star	5 star	-	4 star	5 star	-	-	-	-	-	-	-

Dwelling no.	Fixtures					Appliances		Individual pool				Individual spa		
	All shower-heads	All toilet flushing systems	All kitchen taps	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish-washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
All other dwellings	4 star (> 4.5 but <= 6 L/min)	4 star	5 star	5 star	-	not specified	5 star	-	-	-	-	-	-	-

Dwelling no.	Alternative water source							
	Alternative water supply systems	Size	Configuration	Landscape connection	Toilet connection (s)	Laundry connection	Pool top-up	Spa top-up
All dwellings	No alternative water supply	-	-	-	-	-	-	-

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must install each hot water system specified for the dwelling in the table below, so that the dwelling's hot water is supplied by that system. If the table specifies a central hot water system for the dwelling, then the applicant must connect that central system to the dwelling, so that the dwelling's hot water is supplied by that central system.	✔	✔	✔
(c) The applicant must install, in each bathroom, kitchen and laundry of the dwelling, the ventilation system specified for that room in the table below. Each such ventilation system must have the operation control specified for it in the table.		✔	✔
(d) The applicant must install the cooling and heating system/s specified for the dwelling under the "Living areas" and "Bedroom areas" headings of the "Cooling" and "Heating" columns in the table below, in/for at least 1 living/bedroom area of the dwelling. If no cooling or heating system is specified in the table for "Living areas" or "Bedroom areas", then no systems may be installed in any such areas. If the term "zoned" is specified beside an air conditioning system, then the system must provide for day/night zoning between living areas and bedrooms.		✔	✔
(e) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Artificial lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that the "primary type of artificial lighting" for each such room in the dwelling is fluorescent lighting or light emitting diode (LED) lighting. If the term "dedicated" is specified for a particular room or area, then the light fittings in that room or area must only be capable of being used for fluorescent lighting or light emitting diode (LED) lighting.		✔	✔
(f) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Natural lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that each such room or area is fitted with a window and/or skylight.	✔	✔	✔

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(g) This commitment applies if the applicant installs a water heating system for the dwelling's pool or spa. The applicant must: (aa) install the system specified for the pool in the "Individual Pool" column of the table below (or alternatively must not install any system for the pool). If specified, the applicant must install a timer, to control the pool's pump; and (bb) install the system specified for the spa in the "Individual Spa" column of the table below (or alternatively must not install any system for the spa). If specified, the applicant must install a timer to control the spa's pump.		 	
(h) The applicant must install in the dwelling: (aa) the kitchen cook-top and oven specified for that dwelling in the "Appliances & other efficiency measures" column of the table below; (bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and (cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		  	
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".			

	Hot water		Bathroom ventilation system		Kitchen ventilation system		Laundry ventilation system	
Dwelling no.	Hot water system	Each bathroom	Operation control	Each kitchen	Operation control	Each laundry	Operation control	
All dwellings	Central hot water system (No. 1)	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off	

	Cooling		Heating		Natural lighting	
Dwelling no.	living areas	bedroom areas	living areas	bedroom areas	No. of bathrooms or toilets	Main kitchen
All dwellings	Central cooling system (No. 1)	Central cooling system (No. 1)	Central heating system (No. 1)	Central heating system (No. 1)	0	no

Dwelling no.	Individual pool			Individual spa		Appliances other efficiency measures				
	Pool heating system	Pool Pump	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Dishwasher	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	-	induction cooktop & electric oven	3.5 star	2 star	no	no

(iii) Thermal Performance	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	✓		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		✓	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		✓	✓
(g) Where there is an in-slab heating or cooling system, the applicant must: (aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or (bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.	✓	✓	✓
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	✓	✓	✓
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	✓		

(iii) Thermal Performance	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		✔	

Thermal loads			
Dwelling no.	Area adjusted heating load (in MJ/m ² /yr)	Area adjusted cooling load (in MJ/m ² /yr)	Area adjusted total load (in MJ/m ² /yr)
All dwellings	16	12.7	28.700

(c) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		✓	✓
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	✓	✓	✓
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	✓	✓	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		✓	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		✓	✓
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		✓	✓

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common areas	no common facility	no common facility	no common facility	no common laundry facility

Central systems	Size	Configuration	Connection (to allow for...)
Central water tank - rainwater or stormwater (No. 1)	10000	To collect run-off from at least: - 488 square metres of roof area of buildings in the development - 0 square metres of impervious area in the development - 0 square metres of garden/lawn area in the development - 0 square metres of planter box area in the development (excluding, in each case, any area which drains to, or supplies, any other alternative water supply system).	- irrigation of 448.2 square metres of common landscaped area on the site - car washing in 0 car washing bays on the site
Fire sprinkler system (No. 1)	-	-	-

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		✓	✓

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		✓	✓
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	✓	✓	✓

Common area	Common area ventilation system		Common area lighting		
	Ventilation system type	Ventilation efficiency measure	Primary type of artificial lighting	Lighting efficiency measure	Lighting control system/ BMS
Car Park + Loading Dock (B1-GF)	ventilation (supply + exhaust)	carbon monoxide monitor + VSD fan	light-emitting diode	zoned switching with motion sensor	yes
Combined Switch/Main comms (B1)	air conditioning system	thermostatically controlled	light-emitting diode	manual on / manual off	yes
Chute Room + FOGO Bin room (B1)	ventilation exhaust only	-	light-emitting diode	motion sensors	yes
Community Bin Room (B1)	ventilation supply only	-	light-emitting diode	motion sensors	yes
Bulky Waste Room (B1)	ventilation exhaust only	-	light-emitting diode	motion sensors	yes
Fire Pump Room (B1)	ventilation supply only	thermostatically controlled	light-emitting diode	manual on / manual off	yes
Pressure Pump Room (B1)	ventilation supply only	thermostatically controlled	light-emitting diode	manual on / manual off	yes
Services Shafts (GF-L3)	no mechanical ventilation	-	light-emitting diode	manual on / manual off	yes
Ground floor lobby (GF)	ventilation supply only	time clock or BMS controlled	light-emitting diode	motion sensors	yes
Hallway/lobby type (L1-L3)	ventilation supply only	time clock or BMS controlled	light-emitting diode	motion sensors	yes
Lift bank (No. 1)	-	-	light-emitting diode	connected to lift call button	yes

Central energy systems	Type	Specification
Lift bank (No. 1)	gearless traction with V V V F motor	Number of levels with apartments served by a lift: 4 number of levels from the bottom of the lift shaft to the top of the lift shaft: 5 number of lifts: 1 lift load capacity: >= 1001 kg but <= 1500kg
Central hot water system (No. 1)	electric instantaneous	Piping insulation (ringmain & supply risers): (a) Piping external to building: R0.6 (~25 mm); (b) Piping internal to building: R0.6 (~25 mm)

Central energy systems	Type	Specification
Central cooling system (No. 1)	variable refrigerant volume units	Energy source: electric driven compressor Heat rejection method: air cooled condenser Unit efficiency (min): medium – COP 3.5 – 5.5
Central heating system (No. 1)	variable refrigerant volume units	Energy source: electric driven compressor + air sourced evaporator Unit efficiency medium – COP 3.5 – 5.5

2. Commitments for common areas and central systems/facilities for the development (non-building specific)

(b) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		✓	✓
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	✓	✓	✓
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	✓	✓	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		✓	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		✓	✓
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		✓	✓

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common areas	no common facility	no common facility	no common facility	no common laundry facility

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		✓	✓
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		✓	✓
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	✓	✓	✓

Central energy systems	Type	Specification
Alternative energy supply	Photovoltaic system	Rated electrical output (min): 10 peak kW
Other	-	-

Notes

1. In these commitments, "applicant" means the person carrying out the development.
2. The applicant must identify each dwelling, building and common area listed in this certificate, on the plans accompanying any development application, and on the plans and specifications accompanying the application for a construction certificate / complying development certificate, for the proposed development, using the same identifying letter or reference as is given to that dwelling, building or common area in this certificate.
3. This note applies if the proposed development involves the erection of a building for both residential and non-residential purposes (or the change of use of a building for both residential and non-residential purposes). Commitments in this certificate which are specified to apply to a "common area" of a building or the development, apply only to that part of the building or development to be used for residential purposes.
4. If this certificate lists a central system as a commitment for a dwelling or building, and that system will also service any other dwelling or building within the development, then that system need only be installed once (even if it is separately listed as a commitment for that other dwelling or building).
5. If a star or other rating is specified in a commitment, this is a minimum rating.
6. All alternative water systems to be installed under these commitments (if any), must be installed in accordance with the requirements of all applicable regulatory authorities. NOTE: NSW Health does not recommend that stormwater, recycled water or private dam water be used to irrigate edible plants which are consumed raw, or that rainwater be used for human consumption in areas with potable water supply.

Legend

1. Commitments identified with a "✔" in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).
2. Commitments identified with a "✔" in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.
3. Commitments identified with a "✔" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled. (Note: a certifying authority must not issue an occupation certificate (either interim or final) for a building listed in this certificate, or for any part of such a building, unless it is satisfied that each of the commitments whose fulfilment it is required to monitor in relation to the building or part, has been fulfilled).

BASIX™ Certificate

Building Sustainability Index

www.planningportal.nsw.gov.au/development-and-assessment/basix

Multi Dwelling

Certificate number: 1826446M_02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.planningportal.nsw.gov.au/definitions

Secretary

Date of issue: Tuesday, 16 December 2025

To be valid, this certificate must be submitted with a development application or lodged with a complying development certificate application within 3 months of the date of issue.



When submitting this BASIX certificate with a development application or complying development certificate application, it must be accompanied by NatHERS certificate 0012158470.

Project summary

Project name	Corrimal Stage 2A - Building 2.2 (Lot 10)_02
Street address	27 RAILWAY STREET CORRIMAL 2518
Local Government Area	WOLLONGONG
Plan type and plan number	Deposited Plan DP1313981
Lot no.	10
Section no.	-
No. of residential flat buildings	1
Residential flat buildings: no. of dwellings	57
Multi-dwelling housing: no. of dwellings	0
No. of single dwelling houses	0

Project score

Water	✓ 41	Target 40
Thermal Performance	✓ Pass	Target Pass
Energy	✓ 60	Target 60
Materials	✓ -14	Target n/a

Certificate Prepared by

Name / Company Name: Aspire Sustainability Consulting Pty Ltd

ABN (if applicable): 62636142017

Description of project

Project address	
Project name	Corrimal Stage 2A - Building 2.2 (Lot 10)_02
Street address	27 RAILWAY STREET CORRIMAL 2518
Local Government Area	WOLLONGONG
Plan type and plan number	Deposited Plan DP1313981
Lot no.	10
Section no.	-
Project type	
No. of residential flat buildings	1
Residential flat buildings: no. of dwellings	57
Multi-dwelling housing: no. of dwellings	0
No. of single dwelling houses	0
Site details	
Site area (m ²)	2591
Roof area (m ²)	855
Non-residential floor area (m ²)	0
Residential car spaces	35
Non-residential car spaces	0

Common area landscape		
Common area lawn (m ²)	407.6	
Common area garden (m ²)	407.6	
Area of indigenous or low water use species (m ²)	203.8	
Assessor details and thermal loads		
Assessor number	10070	
Certificate number	0012158470	
Climate zone	56	
Project score		
Water	✔ 41	Target 40
Thermal Performance	✔ Pass	Target Pass
Energy	✔ 60	Target 60
Materials	✔ -14	Target n/a

Description of project

The tables below describe the dwellings and common areas within the project

Residential flat buildings - Building 2.2, 57 dwellings, 6 storeys above ground

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
101	2	76	0	0	0
105	1	52	0	0	0
109	1	60	0	0	0
203	1	52	0	0	0
207	2	71	0	0	0
211	2	80	0	0	0
304	2	74	0	0	0
308	1	52	0	0	0
401	2	76	0	0	0
405	2	73	0	0	0
501	1	67	0	0	0
505	1	58	0	0	0
G01	1	63	0	13.55	0
G05	2	71	0	39.84	0
G09	2	80	0	11.36	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
102	2	71	0	0	0
106	2	71	0	0	0
110	2	80	0	0	0
204	2	74	0	0	0
208	1	52	0	0	0
301	2	76	0	0	0
305	2	74	0	0	0
309	1	52	0	0	0
402	2	73	0	0	0
406	2	71	0	0	0
502	1	58	0	0	0
506	1	51	0	0	0
G02	2	71	0	64.07	0
G06	1	51	0	5.97	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
103	1	52	0	0	0
107	1	52	0	0	0
201	2	76	0	0	0
205	2	74	0	0	0
209	1	52	0	0	0
302	2	71	0	0	0
306	1	52	0	0	0
310	1	60	0	0	0
403	2	74	0	0	0
407	1	67	0	0	0
503	2	74	0	0	0
507	1	53	0	0	0
G03	1	37	0	3.26	0
G07	1	37	0	9.49	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
104	2	74	0	0	0
108	1	52	0	0	0
202	2	71	0	0	0
206	1	52	0	0	0
210	1	60	0	0	0
303	1	52	0	0	0
307	2	71	0	0	0
311	2	80	0	0	0
404	2	74	0	0	0
408	1	56	0	0	0
504	2	74	0	0	0
508	1	56	0	0	0
G04	1	37	0	3.9	0
G08	1	60	0	11.38	0

Description of project

The tables below describe the dwellings and common areas within the project

Schedule of BASIX commitments

1. Commitments for Residential flat buildings - Building 2.2

(a) Buildings

(i) Materials

(b) Dwellings

(i) Water

(ii) Energy

(iii) Thermal Performance

(c) Common areas and central systems/facilities

(i) Water

(ii) Energy

2. Commitments for common areas and central systems/facilities for the development (non-building specific)

(b) Common areas and central systems/facilities

(i) Water

(ii) Energy

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

1. Commitments for Residential flat buildings - Building 2.2

(a) Buildings

(i) Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Floor types", "External wall types", "Internal wall types", "Ceiling and roof types", "Frames" and "Glazing" tables below.			✓
(b) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all specifications included in the tables below.		✓	
(c) The applicant must construct the floors, walls, roof, ceiling and roof, windows, glazed doors and skylights of the development in accordance with the specifications listed in the tables below. In the case of glazing, a 5% variance from the area values listed in the "Frames" and "Glazing" tables is permitted.	✓	✓	✓
(d) The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the below tables.			✓

Floor types

Floor type	Area (m2)	Insulation	Low emissions option
floors above habitable rooms, frame: suspended concrete slab	223.3	-	-
floors above habitable rooms, frame: suspended concrete slab	108.86	-	-
concrete slab on ground, frame:	1831.86	-	none
floors above habitable rooms, frame: suspended concrete slab	96.5	-	-
floors above habitable rooms, frame: suspended concrete slab	630.9	fibreglass batts or roll	-
floors above habitable rooms, frame: suspended concrete slab	3095.6	-	-

External wall types

External wall type	Construction type	Area (m2)	Low emissions option	Insulation
External wall type 1	AAC veneer,frame:light steel frame	1098.70	-	-
External wall type 2	AAC veneer,frame:light steel frame	181.05	-	-
External wall type 3	brick veneer,frame:light steel frame	435.9	-	-
External wall type 4	brick veneer,frame:light steel frame	185.83	-	fibreglass batts or roll

Internal wall types

Internal wall type	Construction type	Area (m2)	Insulation
Internal wall type 1	75 mm AAC panel, frame:light steel frame	1422.28	fibreglass batts or roll
Internal wall type 2	block with low cement content and reconstituted sawdust, frame:no frame	311.03	-
Internal wall type 3	plasterboard, frame:light steel frame	1974	-

Reinforcement concrete frames/columns

Building has reinforced concrete frame/columns?	Volume (m³)	Low emissions option
yes	732.8	-

Ceiling and roof types

Ceiling and roof type	Area (m²)	Roof Insulation	Ceiling Insulation
concrete - bare internal, frame: no frame	3095.6	-	-
concrete - plasterboard internal, frame: light steel frame	761.38	foil backed blanket	fibreglass batts or roll
concrete - bare internal, frame: no frame	67.34	-	-
concrete - plasterboard internal, frame: light steel frame	264.82	foil backed blanket	fibreglass batts or roll

Glazing types

Frame types

Single glazing (m²)	Double glazing (m²)	Triple glazing (m²)	Aluminium frames (m²)	Timber frames (m²)	uPVC frames (m²)	Steel frames (m²)	Composite frames (m²)
27.29	1064.6	-	1091.89	-	-	-	-

(b) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	✔	✔	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		✔	✔
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		✔	✔
(e) The applicant must install: <ul style="list-style-type: none"> (aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and (bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling. 		✔ ✔	✔ ✔
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	✔	✔	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		✔	
(g) The pool or spa must be located as specified in the table.	✔	✔	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	✔	✔	✔

	Fixtures					Appliances		Individual pool				Individual spa		
Dwelling no.	All shower-heads	All toilet flushing systems	All kitchen taps	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish-washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
All dwellings	4 star (> 4.5 but <= 6 L/min)	4 star	5 star	5 star	-	not specified	5 star	-	-	-	-	-	-	-

Alternative water source								
Dwelling no.	Alternative water supply systems	Size	Configuration	Landscape connection	Toilet connection (s)	Laundry connection	Pool top-up	Spa top-up
All dwellings	No alternative water supply	-	-	-	-	-	-	-

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must install each hot water system specified for the dwelling in the table below, so that the dwelling's hot water is supplied by that system. If the table specifies a central hot water system for the dwelling, then the applicant must connect that central system to the dwelling, so that the dwelling's hot water is supplied by that central system.	✓	✓	✓
(c) The applicant must install, in each bathroom, kitchen and laundry of the dwelling, the ventilation system specified for that room in the table below. Each such ventilation system must have the operation control specified for it in the table.		✓	✓
(d) The applicant must install the cooling and heating system/s specified for the dwelling under the "Living areas" and "Bedroom areas" headings of the "Cooling" and "Heating" columns in the table below, in/for at least 1 living/bedroom area of the dwelling. If no cooling or heating system is specified in the table for "Living areas" or "Bedroom areas", then no systems may be installed in any such areas. If the term "zoned" is specified beside an air conditioning system, then the system must provide for day/night zoning between living areas and bedrooms.		✓	✓
(e) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Artificial lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that the "primary type of artificial lighting" for each such room in the dwelling is fluorescent lighting or light emitting diode (LED) lighting. If the term "dedicated" is specified for a particular room or area, then the light fittings in that room or area must only be capable of being used for fluorescent lighting or light emitting diode (LED) lighting.		✓	✓
(f) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Natural lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that each such room or area is fitted with a window and/or skylight.	✓	✓	✓
(g) This commitment applies if the applicant installs a water heating system for the dwelling's pool or spa. The applicant must: (aa) install the system specified for the pool in the "Individual Pool" column of the table below (or alternatively must not install any system for the pool). If specified, the applicant must install a timer, to control the pool's pump; and (bb) install the system specified for the spa in the "Individual Spa" column of the table below (or alternatively must not install any system for the spa). If specified, the applicant must install a timer to control the spa's pump.		✓ ✓	
(h) The applicant must install in the dwelling: (aa) the kitchen cook-top and oven specified for that dwelling in the "Appliances & other efficiency measures" column of the table below;		✓	

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and (cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		✓ ✓	✓
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".		✓	

	Hot water	Bathroom ventilation system		Kitchen ventilation system		Laundry ventilation system	
Dwelling no.	Hot water system	Each bathroom	Operation control	Each kitchen	Operation control	Each laundry	Operation control
All dwellings	Central hot water system (No. 1)	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off

	Cooling		Heating		Natural lighting	
Dwelling no.	living areas	bedroom areas	living areas	bedroom areas	No. of bathrooms or toilets	Main kitchen
All dwellings	Central cooling system (No. 1)	Central cooling system (No. 1)	Central heating system (No. 1)	Central heating system (No. 1)	0	no

	Individual pool			Individual spa		Appliances other efficiency measures				
Dwelling no.	Pool heating system	Pool Pump	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Dishwasher	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	-	induction cooktop & electric oven	3.5 star	2 star	no	no

(iii) Thermal Performance	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	✔		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		✔	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		✔	✔
(g) Where there is an in-slab heating or cooling system, the applicant must: (aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or (bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.	✔	✔	✔
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	✔	✔	✔
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	✔		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		✔	

Thermal loads			
Dwelling no.	Area adjusted heating load (in MJ/m ² /yr)	Area adjusted cooling load (in MJ/m ² /yr)	Area adjusted total load (in MJ/m ² /yr)
All dwellings	12.7	11.2	23.900

(c) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		✓	✓
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	✓	✓	✓
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	✓	✓	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		✓	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		✓	✓
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		✓	✓

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common areas	no common facility	no common facility	no common facility	no common laundry facility

Central systems	Size	Configuration	Connection (to allow for...)
Central water tank - rainwater or stormwater (No. 1)	10000	To collect run-off from at least: - 427 square metres of roof area of buildings in the development - 0 square metres of impervious area in the development - 0 square metres of garden/lawn area in the development - 0 square metres of planter box area in the development (excluding, in each case, any area which drains to, or supplies, any other alternative water supply system).	- irrigation of 815.2 square metres of common landscaped area on the site - car washing in 1 car washing bays on the site
Fire sprinkler system (No. 1)	-	-	-

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		✓	✓

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		✔	✔
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	✔	✔	✔

Common area	Common area ventilation system		Common area lighting		
	Ventilation system type	Ventilation efficiency measure	Primary type of artificial lighting	Lighting efficiency measure	Lighting control system/ BMS
Lift bank (No. 1)	-	-	light-emitting diode	connected to lift call button	yes
Car Park (B1)	ventilation (supply + exhaust)	carbon monoxide monitor + VSD fan	light-emitting diode	zoned switching with motion sensor	yes
Loading Dock (GF)	no mechanical ventilation	-	light-emitting diode	motion sensors	yes
Combined Switch/Main comms (B1)	air conditioning system	thermostatically controlled	light-emitting diode	manual on / manual off	yes
Chute Room + FOGO Bin room (B1)	ventilation exhaust only	-	light-emitting diode	motion sensors	yes
Community Bin Room (B1)	ventilation supply only	-	light-emitting diode	motion sensors	yes
Bulky Waste Room +Waste (B1)	ventilation exhaust only	-	light-emitting diode	motion sensors	yes
Fire Pump Room (B1)	ventilation supply only	thermostatically controlled	light-emitting diode	manual on / manual off	yes
Pressure Pump Room (B1)	ventilation supply only	thermostatically controlled	light-emitting diode	manual on / manual off	yes
Services Shafts (GF-L5)	no mechanical ventilation	-	light-emitting diode	manual on / manual off	yes
Ground floor lobby (GF)	ventilation supply only	time clock or BMS controlled	light-emitting diode	motion sensors	yes
Hallway/lobby type (L1-L5)	ventilation supply only	time clock or BMS controlled	light-emitting diode	motion sensors	yes
Lift bank (No. 2)	-	-	light-emitting diode	connected to lift call button	yes

Central energy systems	Type	Specification
Lift bank (No. 1)	gearless traction with V V V F motor	Number of levels with apartments served by a lift: 6 number of levels from the bottom of the lift shaft to the top of the lift shaft: 7 number of lifts: 1 lift load capacity: >= 1001 kg but <= 1500kg

Central energy systems	Type	Specification
Lift bank (No. 2)	gearless traction with V V V F motor	Number of levels with apartments served by a lift: 6 number of levels from the bottom of the lift shaft to the top of the lift shaft: 7 number of lifts: 1 lift load capacity: ≥ 1001 kg but ≤ 1500 kg
Central hot water system (No. 1)	electric instantaneous	Piping insulation (ringmain & supply risers): (a) Piping external to building: R0.6 (~25 mm); (b) Piping internal to building: R0.6 (~25 mm)
Central cooling system (No. 1)	variable refrigerant volume units	Energy source: electric driven compressor Heat rejection method: air cooled condenser Unit efficiency (min): medium – COP 3.5 – 5.5
Central heating system (No. 1)	variable refrigerant volume units	Energy source: electric driven compressor + air sourced evaporator Unit efficiency medium – COP 3.5 – 5.5

2. Commitments for common areas and central systems/facilities for the development (non-building specific)

(b) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		✓	✓
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	✓	✓	✓
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	✓	✓	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		✓	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		✓	✓
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		✓	✓

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common areas	no common facility	no common facility	no common facility	no common laundry facility

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		✓	✓
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		✓	✓
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	✓	✓	✓

Central energy systems	Type	Specification
Alternative energy supply	Photovoltaic system	Rated electrical output (min): 20 peak kW
Other	-	-

Notes

1. In these commitments, "applicant" means the person carrying out the development.
2. The applicant must identify each dwelling, building and common area listed in this certificate, on the plans accompanying any development application, and on the plans and specifications accompanying the application for a construction certificate / complying development certificate, for the proposed development, using the same identifying letter or reference as is given to that dwelling, building or common area in this certificate.
3. This note applies if the proposed development involves the erection of a building for both residential and non-residential purposes (or the change of use of a building for both residential and non-residential purposes). Commitments in this certificate which are specified to apply to a "common area" of a building or the development, apply only to that part of the building or development to be used for residential purposes.
4. If this certificate lists a central system as a commitment for a dwelling or building, and that system will also service any other dwelling or building within the development, then that system need only be installed once (even if it is separately listed as a commitment for that other dwelling or building).
5. If a star or other rating is specified in a commitment, this is a minimum rating.
6. All alternative water systems to be installed under these commitments (if any), must be installed in accordance with the requirements of all applicable regulatory authorities. NOTE: NSW Health does not recommend that stormwater, recycled water or private dam water be used to irrigate edible plants which are consumed raw, or that rainwater be used for human consumption in areas with potable water supply.

Legend

1. Commitments identified with a "✔" in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).
2. Commitments identified with a "✔" in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.
3. Commitments identified with a "✔" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled. (Note: a certifying authority must not issue an occupation certificate (either interim or final) for a building listed in this certificate, or for any part of such a building, unless it is satisfied that each of the commitments whose fulfilment it is required to monitor in relation to the building or part, has been fulfilled).

BASIX™ Certificate

Building Sustainability Index

www.planningportal.nsw.gov.au/development-and-assessment/basix

Multi Dwelling

Certificate number: 1826443M_02

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.planningportal.nsw.gov.au/definitions

Secretary

Date of issue: Tuesday, 16 December 2025

To be valid, this certificate must be submitted with a development application or lodged with a complying development certificate application within 3 months of the date of issue.



When submitting this BASIX certificate with a development application or complying development certificate application, it must be accompanied by NatHERS certificate 0012157170.

Project summary		
Project name	Corrimal Stage 2A - Building 2.3&2.4. (Lot 13)_02	
Street address	27 RAILWAY STREET CORRIMAL 2518	
Local Government Area	WOLLONGONG	
Plan type and plan number	Deposited Plan DP1313981	
Lot no.	13	
Section no.	-	
No. of residential flat buildings	2	
Residential flat buildings: no. of dwellings	119	
Multi-dwelling housing: no. of dwellings	0	
No. of single dwelling houses	0	
Project score		
Water	✓ 41	Target 40
Thermal Performance	✓ Pass	Target Pass
Energy	✓ 60	Target 60
Materials	✓ -100	Target n/a

Certificate Prepared by

Name / Company Name: Aspire Sustainability Consulting Pty Ltd

ABN (if applicable): 62636142017

Description of project

Project address

Project name	Corrimal Stage 2A - Building 2.3&2.4. (Lot 13)_02
Street address	27 RAILWAY STREET CORRIMAL 2518
Local Government Area	WOLLONGONG
Plan type and plan number	Deposited Plan DP1313981
Lot no.	13
Section no.	-

Project type

No. of residential flat buildings	2
Residential flat buildings: no. of dwellings	119
Multi-dwelling housing: no. of dwellings	0
No. of single dwelling houses	0

Site details

Site area (m ²)	8003
Roof area (m ²)	2434
Non-residential floor area (m ²)	0
Residential car spaces	175
Non-residential car spaces	-

Common area landscape

Common area lawn (m ²)	1972
Common area garden (m ²)	1972
Area of indigenous or low water use species (m ²)	986

Assessor details and thermal loads

Assessor number	10070
Certificate number	0012157170
Climate zone	56

Project score

Water	✔ 41	Target 40
Thermal Performance	✔ Pass	Target Pass
Energy	✔ 60	Target 60
Materials	✔ -100	Target n/a

Description of project

The tables below describe the dwellings and common areas within the project

Residential flat buildings - Building 2.3, 59 dwellings, 6 storeys above ground

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
101	3	137	0	0	0
105	2	85	0	0	0
109	3	126	0	0	0
203	2	84	0	0	0
207	1	53	0	0	0
211	2	97	0	0	0
304	2	98	0	0	0
308	2	88	0	0	0
401	3	137	0	0	0
405	2	98	0	0	0
409	1	59	0	0	0
503	2	84	0	0	0
507	3	130	0	0	0
G02	3	112	0	0	0
G06	2	91	0	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
102	1	53	0	0	0
106	1	53	0	0	0
110	2	97	0	0	0
204	2	98	0	0	0
208	2	88	0	0	0
301	3	137	0	0	0
305	2	98	0	0	0
309	2	91	0	0	0
402	1	53	0	0	0
406	2	85	0	0	0
410	2	97	0	0	0
504	3	142	0	0	0
508	1	66	0	0	0
G03	2	84	0	0	0
G07	1	62	0	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
103	2	84	0	0	0
107	2	88	0	0	0
201	3	137	0	0	0
205	2	98	0	0	0
209	2	92	0	0	0
302	1	53	0	0	0
306	2	85	0	0	0
310	1	59	0	0	0
403	2	84	0	0	0
407	1	53	0	0	0
501	3	133	0	0	0
505	2	85	0	0	0
509	2	96	0	0	0
G04	2	87	0	0	0
G08	3	120	0	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
104	2	98	0	0	0
108	2	91	0	0	0
202	1	53	0	0	0
206	2	85	0	0	0
210	1	59	0	0	0
303	2	84	0	0	0
307	1	53	0	0	0
311	2	97	0	0	0
404	2	98	0	0	0
408	3	130	0	0	0
502	1	53	0	0	0
506	1	53	0	0	0
G01	1	70	0	0	0
G05	3	116	0	0	0

Residential flat buildings - Building 2.4, 60 dwellings, 6 storeys above ground

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
101	3	112	0	0	0
105	2	98	0	0	0
109	2	97	0	0	0
201	3	111	0	0	0
205	2	98	0	0	0
209	2	97	0	0	0
301	3	112	0	0	0
305	2	98	0	0	0
309	2	97	0	0	0
401	3	123	0	0	0
405	3	137	0	0	0
501	3	123	0	0	0
505	3	138	0	0	0
G01	3	112	0	0	0
G05	3	132	0	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
102	2	83	0	0	0
106	2	98	0	0	0
110	2	94	0	0	0
202	2	83	0	0	0
206	2	98	0	0	0
210	2	93	0	0	0
302	2	83	0	0	0
306	2	98	0	0	0
310	2	93	0	0	0
402	2	84	0	0	0
406	2	84	0	0	0
502	2	85	0	0	0
506	2	84	0	0	0
G02	3	111	0	0	0
G06	2	82	0	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
103	1	53	0	0	0
107	2	84	0	0	0
111	1	60	0	0	0
203	1	53	0	0	0
207	2	84	0	0	0
211	1	60	0	0	0
303	1	53	0	0	0
307	2	84	0	0	0
311	1	60	0	0	0
403	2	85	0	0	0
407	2	84	0	0	0
503	2	85	0	0	0
507	2	85	0	0	0
G03	2	83	0	0	0
G07	3	119	0	0	0

Dwelling no.	No. of bedrooms	Conditioned floor area (m ²)	Unconditioned floor area (m ²)	Area of garden & lawn (m ²)	Indigenous species (min area m ²)
104	2	84	0	0	0
108	1	53	0	0	0
112	1	60	0	0	0
204	2	84	0	0	0
208	1	53	0	0	0
212	1	60	0	0	0
304	2	84	0	0	0
308	1	53	0	0	0
312	1	60	0	0	0
404	3	137	0	0	0
408	3	131	0	0	0
504	3	137	0	0	0
508	3	128	0	0	0
G04	3	133	0	0	0
G08	2	94	0	0	0

Description of project

The tables below describe the dwellings and common areas within the project

Common areas of unit building - Building 2.4

Common area	Floor area (m ²)	Common area	Floor area (m ²)	Common area	Floor area (m ²)
Lift bank (No. 1)	-	Lift bank (No. 2)	-	Hallway/lobby type 2.4 (L1-L5)	383
Lift bank (No. 3)	-	Lift bank (No. 4)	-		

Common areas of the development (non-building specific)

Common area	Floor area (m ²)	Common area	Floor area (m ²)	Common area	Floor area (m ²)
Car Park (B1)	5453	Loading Dock (GF)	111	Switch Room (B1)	13.25
Chute Room + FOGO Bin room (B1)	71.91	Bin Holding Room (B1)	79.18	Bulky Storage (B1)	30.18
Fire Pump Room (B1)	34.98	CW Press (B1)	7.88	Services Shafts (GF-L5)	108
Main Comms Room (B1)	17.58	Ground floor lobby (GF)	227		

Schedule of BASIX commitments

1. Commitments for Residential flat buildings - Building 2.3

(a) Buildings

(i) Materials

(b) Dwellings

(i) Water

(ii) Energy

(iii) Thermal Performance

(c) Common areas and central systems/facilities

(i) Water

(ii) Energy

2. Commitments for Residential flat buildings - Building 2.4

(a) Buildings

(i) Materials

(b) Dwellings

(i) Water

(ii) Energy

(iii) Thermal Performance

(c) Common areas and central systems/facilities

(i) Water

(ii) Energy

3. Commitments for common areas and central systems/facilities for the development (non-building specific)

(a) Buildings 'Other'

(i) Materials

(b) Common areas and central systems/facilities

(i) Water

(ii) Energy

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

1. Commitments for Residential flat buildings - Building 2.3

(a) Buildings

(i) Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Floor types", "External wall types", "Internal wall types", "Ceiling and roof types", "Frames" and "Glazing" tables below.			✓
(b) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all specifications included in the tables below.		✓	
(c) The applicant must construct the floors, walls, roof, ceiling and roof, windows, glazed doors and skylights of the development in accordance with the specifications listed in the tables below. In the case of glazing, a 5% variance from the area values listed in the "Frames" and "Glazing" tables is permitted.	✓	✓	✓
(d) The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the below tables.			✓

Floor types

Floor type	Area (m2)	Insulation	Low emissions option
suspended floor above enclosed subfloor, frame: suspended concrete slab	5812.08	-	-
suspended floor above enclosed subfloor, frame: suspended concrete slab	1328.53	fibreglass batts or roll	-

External wall types

External wall type	Construction type	Area (m2)	Low emissions option	Insulation
External wall type 1	framed (fibre cement sheet or boards), frame: light steel frame	106.1	-	-
External wall type 2	framed (metal clad), frame: light steel frame	565.3	-	fibreglass batts or roll
External wall type 3	framed (fibre cement sheet or boards), frame: light steel frame	154	-	fibreglass batts or roll

External wall types

External wall type	Construction type	Area (m2)	Low emissions option	Insulation
External wall type 4	off form concrete,frame:light steel frame	95	none	fibreglass batts or roll
External wall type 5	AAC veneer,frame:light steel frame	602	-	fibreglass batts or roll

Internal wall types

Internal wall type	Construction type	Area (m2)	Insulation
Internal wall type 1	75 mm AAC panel, frame:light steel frame	2436.58	fibreglass batts or roll
Internal wall type 2	75 mm AAC panel, frame:light steel frame	39	-
Internal wall type 3	plasterboard, frame:light steel frame	1138	-

Reinforcement concrete frames/columns

Building has reinforced concrete frame/columns?	Volume (m ³)	Low emissions option
yes	643.86	-

Ceiling and roof types

Ceiling and roof type	Area (m ²)	Roof Insulation	Ceiling Insulation
concrete - bare internal, frame: light steel frame	45.99	-	-
concrete - plasterboard internal, frame: light steel frame	1293.24	foil backed blanket	fibreglass batts or roll

Glazing types

Frame types

Single glazing (m ²)	Double glazing (m ²)	Triple glazing (m ²)	Aluminium frames (m ²)	Timber frames (m ²)	uPVC frames (m ²)	Steel frames (m ²)	Composite frames (m ²)
23.29	487.80	-	511.09	-	-	-	-

(b) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	✔	✔	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		✔	✔
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		✔	✔
(e) The applicant must install: <ul style="list-style-type: none"> (aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and (bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling. 		✔ ✔	✔ ✔
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	✔	✔	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		✔	
(g) The pool or spa must be located as specified in the table.	✔	✔	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	✔	✔	✔

	Fixtures					Appliances		Individual pool				Individual spa		
Dwelling no.	All shower-heads	All toilet flushing systems	All kitchen taps	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish-washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
All dwellings	4 star (> 4.5 but <= 6 L/min)	4 star	5 star	5 star	-	not specified	5 star	-	-	-	-	-	-	-

Alternative water source								
Dwelling no.	Alternative water supply systems	Size	Configuration	Landscape connection	Toilet connection (s)	Laundry connection	Pool top-up	Spa top-up
All dwellings	No alternative water supply	-	-	-	-	-	-	-

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must install each hot water system specified for the dwelling in the table below, so that the dwelling's hot water is supplied by that system. If the table specifies a central hot water system for the dwelling, then the applicant must connect that central system to the dwelling, so that the dwelling's hot water is supplied by that central system.	✓	✓	✓
(c) The applicant must install, in each bathroom, kitchen and laundry of the dwelling, the ventilation system specified for that room in the table below. Each such ventilation system must have the operation control specified for it in the table.		✓	✓
(d) The applicant must install the cooling and heating system/s specified for the dwelling under the "Living areas" and "Bedroom areas" headings of the "Cooling" and "Heating" columns in the table below, in/for at least 1 living/bedroom area of the dwelling. If no cooling or heating system is specified in the table for "Living areas" or "Bedroom areas", then no systems may be installed in any such areas. If the term "zoned" is specified beside an air conditioning system, then the system must provide for day/night zoning between living areas and bedrooms.		✓	✓
(e) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Artificial lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that the "primary type of artificial lighting" for each such room in the dwelling is fluorescent lighting or light emitting diode (LED) lighting. If the term "dedicated" is specified for a particular room or area, then the light fittings in that room or area must only be capable of being used for fluorescent lighting or light emitting diode (LED) lighting.		✓	✓
(f) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Natural lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that each such room or area is fitted with a window and/or skylight.	✓	✓	✓
(g) This commitment applies if the applicant installs a water heating system for the dwelling's pool or spa. The applicant must: (aa) install the system specified for the pool in the "Individual Pool" column of the table below (or alternatively must not install any system for the pool). If specified, the applicant must install a timer, to control the pool's pump; and (bb) install the system specified for the spa in the "Individual Spa" column of the table below (or alternatively must not install any system for the spa). If specified, the applicant must install a timer to control the spa's pump.		✓ ✓	
(h) The applicant must install in the dwelling: (aa) the kitchen cook-top and oven specified for that dwelling in the "Appliances & other efficiency measures" column of the table below;		✓	

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and (cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		✓ ✓	✓
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".		✓	

	Hot water	Bathroom ventilation system		Kitchen ventilation system		Laundry ventilation system	
Dwelling no.	Hot water system	Each bathroom	Operation control	Each kitchen	Operation control	Each laundry	Operation control
All dwellings	Central hot water system (No. 1)	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off

	Cooling		Heating		Natural lighting	
Dwelling no.	living areas	bedroom areas	living areas	bedroom areas	No. of bathrooms or toilets	Main kitchen
All dwellings	Central cooling system (No. 1)	Central cooling system (No. 1)	Central heating system (No. 1)	Central heating system (No. 1)	0	no

	Individual pool			Individual spa		Appliances other efficiency measures				
Dwelling no.	Pool heating system	Pool Pump	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Dishwasher	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	-	induction cooktop & electric oven	3.5 star	2 star	no	no

(iii) Thermal Performance	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	✔		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		✔	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		✔	✔
(g) Where there is an in-slab heating or cooling system, the applicant must: (aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or (bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.	✔	✔	✔
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	✔	✔	✔
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	✔		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		✔	

Thermal loads			
Dwelling no.	Area adjusted heating load (in MJ/m ² /yr)	Area adjusted cooling load (in MJ/m ² /yr)	Area adjusted total load (in MJ/m ² /yr)
All dwellings	11.3	13.3	24.600

(c) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		✓	✓
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	✓	✓	✓
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	✓	✓	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		✓	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		✓	✓
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		✓	✓

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common areas	no common facility	no common facility	no common facility	no common laundry facility

Central systems	Size	Configuration	Connection (to allow for...)
Central water tank - rainwater or stormwater (No. 1)	10000	To collect run-off from at least: - 1200 square metres of roof area of buildings in the development - 0 square metres of impervious area in the development - 0 square metres of garden/lawn area in the development - 0 square metres of planter box area in the development (excluding, in each case, any area which drains to, or supplies, any other alternative water supply system).	- irrigation of 3944 square metres of common landscaped area on the site - car washing in 1 car washing bays on the site
Fire sprinkler system (No. 1)	-	-	-

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		✓	✓

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		✓	✓
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	✓	✓	✓

Common area	Common area ventilation system		Common area lighting		
	Ventilation system type	Ventilation efficiency measure	Primary type of artificial lighting	Lighting efficiency measure	Lighting control system/ BMS
Hallway/lobby type 2.3 (L1-L5)	ventilation supply only	time clock or BMS controlled	light-emitting diode	motion sensors	yes

Central energy systems	Type	Specification
Lift bank (No. 1)	gearless traction with V V V F motor	Number of levels with apartments served by a lift: 6 number of levels from the bottom of the lift shaft to the top of the lift shaft: 7 number of lifts: 1 lift load capacity: >= 1001 kg but <= 1500kg
Lift bank (No. 2)	gearless traction with V V V F motor	Number of levels with apartments served by a lift: 6 number of levels from the bottom of the lift shaft to the top of the lift shaft: 7 number of lifts: 1 lift load capacity: >= 1001 kg but <= 1500kg
Central hot water system (No. 1)	electric instantaneous	Piping insulation (ringmain & supply risers): (a) Piping external to building: R0.6 (~25 mm); (b) Piping internal to building: R0.6 (~25 mm)
Central cooling system (No. 1)	variable refrigerant volume units	Energy source: electric driven compressor Heat rejection method: air cooled condenser Unit efficiency (min): medium – COP 3.5 – 5.5
Central heating system (No. 1)	variable refrigerant volume units	Energy source: electric driven compressor + air sourced evaporator Unit efficiency medium – COP 3.5 – 5.5

2. Commitments for Residential flat buildings - Building 2.4

(a) Buildings

(i) Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Floor types", "External wall types", "Internal wall types", "Ceiling and roof types", "Frames" and "Glazing" tables below.			✓
(b) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all specifications included in the tables below.		✓	
(c) The applicant must construct the floors, walls, roof, ceiling and roof, windows, glazed doors and skylights of the development in accordance with the specifications listed in the tables below. In the case of glazing, a 5% variance from the area values listed in the "Frames" and "Glazing" tables is permitted.	✓	✓	✓
(d) The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the below tables.			✓

Floor types

Floor type	Area (m2)	Insulation	Low emissions option
suspended floor above enclosed subfloor, frame: suspended concrete slab	6131.63	-	-
suspended floor above enclosed subfloor, frame: suspended concrete slab	1144.26	fibreglass batts or roll	-

External wall types

External wall type	Construction type	Area (m2)	Low emissions option	Insulation
External wall type 1	framed (fibre cement sheet or boards),frame:light steel frame	220.1	-	-
External wall type 2	framed (metal clad),frame:light steel frame	671.3	-	fibreglass batts or roll
External wall type 3	framed (fibre cement sheet or boards),frame:light steel frame	510.3	-	fibreglass batts or roll
External wall type 4	AAC veneer,frame:light steel frame	695.5	-	fibreglass batts or roll

Internal wall types

Internal wall type	Construction type	Area (m2)	Insulation
Internal wall type 1	75 mm AAC panel, frame:light steel frame	2521.43	fibreglass batts or roll
Internal wall type 2	75 mm AAC panel, frame:light steel frame	5.8	-
Internal wall type 3	plasterboard, frame:light steel frame	3227.4	-

Reinforcement concrete frames/columns

Building has reinforced concrete frame/columns?	Volume (m³)	Low emissions option
yes	763.89	-

Ceiling and roof types

Ceiling and roof type	Area (m²)	Roof Insulation	Ceiling Insulation
concrete - bare internal, frame: light steel frame	99.04	-	-
concrete - plasterboard internal, frame: light steel frame	1257.39	foil backed blanket	fibreglass batts or roll

Glazing types

Frame types

Single glazing (m²)	Double glazing (m²)	Triple glazing (m²)	Aluminium frames (m²)	Timber frames (m²)	uPVC frames (m²)	Steel frames (m²)	Composite frames (m²)
33.45	1316.60	-	1350.05	-	-	-	-

(b) Dwellings

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must plant indigenous or low water use species of vegetation throughout the area of land specified for the dwelling in the "Indigenous species" column of the table below, as private landscaping for that dwelling. (This area of indigenous vegetation is to be contained within the "Area of garden and lawn" for the dwelling specified in the "Description of Project" table).	✓	✓	
(c) If a rating is specified in the table below for a fixture or appliance to be installed in the dwelling, the applicant must ensure that each such fixture and appliance meets the rating specified for it.		✓	✓
(d) The applicant must install an on demand hot water recirculation system which regulates all hot water use throughout the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below.		✓	✓
(e) The applicant must install: <ul style="list-style-type: none"> (aa) a hot water diversion system to all showers, kitchen sinks and all basins in the dwelling, where indicated for a dwelling in the "HW recirculation or diversion" column of the table below; and (bb) a separate diversion tank (or tanks) connected to the hot water diversion systems of at least 100 litres. The applicant must connect the hot water diversion tank to all toilets in the dwelling. 		✓ ✓	✓ ✓
(e) The applicant must not install a private swimming pool or spa for the dwelling, with a volume exceeding that specified for it in the table below.	✓	✓	
(f) If specified in the table, that pool or spa (or both) must have a pool cover or shading (or both).		✓	
(g) The pool or spa must be located as specified in the table.	✓	✓	
(h) The applicant must install, for the dwelling, each alternative water supply system, with the specified size, listed for that dwelling in the table below. Each system must be configured to collect run-off from the areas specified (excluding any area which supplies any other alternative water supply system), and to divert overflow as specified. Each system must be connected as specified.	✓	✓	✓

	Fixtures					Appliances		Individual pool				Individual spa		
Dwelling no.	All shower-heads	All toilet flushing systems	All kitchen taps	All bathroom taps	HW recirculation or diversion	All clothes washers	All dish-washers	Volume (max volume)	Pool cover	Pool location	Pool shaded	Volume (max volume)	Spa cover	Spa shaded
All dwellings	4 star (> 4.5 but <= 6 L/min)	4 star	5 star	5 star	-	not specified	5 star	-	-	-	-	-	-	-

Alternative water source								
Dwelling no.	Alternative water supply systems	Size	Configuration	Landscape connection	Toilet connection (s)	Laundry connection	Pool top-up	Spa top-up
All dwellings	No alternative water supply	-	-	-	-	-	-	-

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must comply with the commitments listed below in carrying out the development of a dwelling listed in a table below.			
(b) The applicant must install each hot water system specified for the dwelling in the table below, so that the dwelling's hot water is supplied by that system. If the table specifies a central hot water system for the dwelling, then the applicant must connect that central system to the dwelling, so that the dwelling's hot water is supplied by that central system.	✓	✓	✓
(c) The applicant must install, in each bathroom, kitchen and laundry of the dwelling, the ventilation system specified for that room in the table below. Each such ventilation system must have the operation control specified for it in the table.		✓	✓
(d) The applicant must install the cooling and heating system/s specified for the dwelling under the "Living areas" and "Bedroom areas" headings of the "Cooling" and "Heating" columns in the table below, in/for at least 1 living/bedroom area of the dwelling. If no cooling or heating system is specified in the table for "Living areas" or "Bedroom areas", then no systems may be installed in any such areas. If the term "zoned" is specified beside an air conditioning system, then the system must provide for day/night zoning between living areas and bedrooms.		✓	✓
(e) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Artificial lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that the "primary type of artificial lighting" for each such room in the dwelling is fluorescent lighting or light emitting diode (LED) lighting. If the term "dedicated" is specified for a particular room or area, then the light fittings in that room or area must only be capable of being used for fluorescent lighting or light emitting diode (LED) lighting.		✓	✓
(f) This commitment applies to each room or area of the dwelling which is referred to in a heading to the "Natural lighting" column of the table below (but only to the extent specified for that room or area). The applicant must ensure that each such room or area is fitted with a window and/or skylight.	✓	✓	✓
(g) This commitment applies if the applicant installs a water heating system for the dwelling's pool or spa. The applicant must: (aa) install the system specified for the pool in the "Individual Pool" column of the table below (or alternatively must not install any system for the pool). If specified, the applicant must install a timer, to control the pool's pump; and (bb) install the system specified for the spa in the "Individual Spa" column of the table below (or alternatively must not install any system for the spa). If specified, the applicant must install a timer to control the spa's pump.		✓ ✓	
(h) The applicant must install in the dwelling: (aa) the kitchen cook-top and oven specified for that dwelling in the "Appliances & other efficiency measures" column of the table below;		✓	

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(bb) each appliance for which a rating is specified for that dwelling in the "Appliances & other efficiency measures" column of the table, and ensure that the appliance has that minimum rating; and (cc) any clothes drying line specified for the dwelling in the "Appliances & other efficiency measures" column of the table.		✓ ✓	✓
(i) If specified in the table, the applicant must carry out the development so that each refrigerator space in the dwelling is "well ventilated".		✓	

	Hot water	Bathroom ventilation system		Kitchen ventilation system		Laundry ventilation system	
Dwelling no.	Hot water system	Each bathroom	Operation control	Each kitchen	Operation control	Each laundry	Operation control
All dwellings	Central hot water system (No. 1)	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off	individual fan, ducted to façade or roof	manual switch on/off

	Cooling		Heating		Natural lighting	
Dwelling no.	living areas	bedroom areas	living areas	bedroom areas	No. of bathrooms or toilets	Main kitchen
All dwellings	Central cooling system (No. 1)	Central cooling system (No. 1)	Central heating system (No. 1)	Central heating system (No. 1)	0	no

	Individual pool			Individual spa		Appliances other efficiency measures				
Dwelling no.	Pool heating system	Pool Pump	Timer	Spa heating system	Timer	Kitchen cooktop/oven	Dishwasher	Clothes dryer	Indoor or sheltered clothes drying line	Private outdoor or unsheltered clothes drying line
All dwellings	-	-	-	-	-	induction cooktop & electric oven	3.5 star	2 star	no	no

(iii) Thermal Performance	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The applicant must attach the certificate referred to under "Assessor details" on the front page of this BASIX certificate (the "Assessor Certificate") to the development application and construction certificate application for the proposed development (or, if the applicant is applying for a complying development certificate for the proposed development, to that application). The applicant must also attach the Assessor Certificate to the application for a final occupation certificate for the proposed development.			
(b) The Assessor Certificate must have been issued by an Accredited Assessor in accordance with the Thermal Comfort Protocol.			
(c) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Thermal Loads" table below.			
(d) The applicant must show on the plans accompanying the development application for the proposed development, all matters which the Thermal Comfort Protocol requires to be shown on those plans. Those plans must bear a stamp of endorsement from the Accredited Assessor, to certify that this is the case.	✔		
(e) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all thermal performance specifications set out in the Assessor Certificate, and all aspects of the proposed development which were used to calculate those specifications.		✔	
(f) The applicant must construct the development in accordance with all thermal performance specifications set out in the Assessor Certificate, and in accordance with those aspects of the development application or application for a complying development certificate which were used to calculate those specifications.		✔	✔
(g) Where there is an in-slab heating or cooling system, the applicant must: (aa) Install insulation with an R-value of not less than 1.0 around the vertical edges of the perimeter of the slab; or (bb) On a suspended floor, install insulation with an R-value of not less than 1.0 underneath the slab and around the vertical edges of the perimeter of the slab.	✔	✔	✔
(h) The applicant must construct the floors and walls of the development in accordance with the specifications listed in the table below.	✔	✔	✔
(i) The applicant must show on The plans accompanying The development application for The proposed development, The locations of ceiling fans set out in The Assessor Certificate.	✔		
(j) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), the locations of ceiling fans set out in the Assessor Certificate.		✔	

Thermal loads			
Dwelling no.	Area adjusted heating load (in MJ/m ² /yr)	Area adjusted cooling load (in MJ/m ² /yr)	Area adjusted total load (in MJ/m ² /yr)
All dwellings	11.3	13.3	24.600

(c) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		✓	✓
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	✓	✓	✓
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	✓	✓	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		✓	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		✓	✓
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		✓	✓

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common areas	no common facility	no common facility	no common facility	no common laundry facility

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		✓	✓
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		✓	✓
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	✓	✓	✓

	Common area ventilation system		Common area lighting		
Common area	Ventilation system type	Ventilation efficiency measure	Primary type of artificial lighting	Lighting efficiency measure	Lighting control system/ BMS
Lift bank (No. 1)	-	-	light-emitting diode	connected to lift call button	yes
Lift bank (No. 2)	-	-	light-emitting diode	connected to lift call button	yes
Hallway/lobby type 2.4 (L1-L5)	ventilation supply only	time clock or BMS controlled	light-emitting diode	motion sensors	yes
Lift bank (No. 3)	-	-	light-emitting diode	connected to lift call button	yes
Lift bank (No. 4)	-	-	light-emitting diode	connected to lift call button	yes

Central energy systems	Type	Specification
Lift bank (No. 3)	gearless traction with V V V F motor	Number of levels with apartments served by a lift: 6 number of levels from the bottom of the lift shaft to the top of the lift shaft: 7 number of lifts: 1 lift load capacity: >= 1001 kg but <= 1500kg
Lift bank (No. 4)	gearless traction with V V V F motor	Number of levels with apartments served by a lift: 6 number of levels from the bottom of the lift shaft to the top of the lift shaft: 7 number of lifts: 1 lift load capacity: >= 1001 kg but <= 1500kg

3. Commitments for common areas and central systems/facilities for the development (non-building specific)

(a) Buildings 'Other'

(i) Materials	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) The details of the proposed development on the Assessor Certificate must be consistent with the details shown in this BASIX Certificate, including the details shown in the "Floor types", "External wall types", "Internal wall types", "Ceiling and roof types", "Frames" and "Glazing" tables below.			✓
(b) The applicant must show on the plans accompanying the application for a construction certificate (or complying development certificate, if applicable), all specifications included in the tables below.		✓	
(c) The applicant must construct the floors, walls, roof, ceiling and roof, windows, glazed doors and skylights of the development in accordance with the specifications listed in the tables below. In the case of glazing, a 5% variance from the area values listed in the "Frames" and "Glazing" tables is permitted.	✓	✓	✓
(d) The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the below tables.			✓

Floor types

Floor type	Area (m2)	Insulation	Low emissions option
concrete slab on ground, frame:	6091.11	-	none

External wall types

External wall type	Construction type	Area (m2)	Low emissions option	Insulation
External wall type 1	off form concrete,frame:no frame	1353.6	none	-
External wall type 2	framed (fibre cement sheet or boards),frame:light steel frame	116.99	-	-

Internal wall types

Internal wall type	Construction type	Area (m2)	Insulation
Internal wall type 1	single skin masonry, frame:no frame	797.54	-

Reinforcement concrete frames/columns

Building has reinforced concrete frame/columns?	Volume (m³)	Low emissions option
yes	223.14	-

Ceiling and roof types

Ceiling and roof type	Area (m ²)	Roof Insulation	Ceiling Insulation
concrete - bare internal, frame: no frame	3547.91	-	-

Glazing types**Frame types**

Single glazing (m ²)	Double glazing (m ²)	Triple glazing (m ²)	Aluminium frames (m ²)	Timber frames (m ²)	uPVC frames (m ²)	Steel frames (m ²)	Composite frames (m ²)
-	-	-	-	-	-	-	-

(b) Common areas and central systems/facilities

(i) Water	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a showerhead, toilet, tap or clothes washer into a common area, then that item must meet the specifications listed for it in the table.		✓	✓
(b) The applicant must install (or ensure that the development is serviced by) the alternative water supply system(s) specified in the "Central systems" column of the table below. In each case, the system must be sized, be configured, and be connected, as specified in the table.	✓	✓	✓
(c) A swimming pool or spa listed in the table must not have a volume (in kLs) greater than that specified for the pool or spa in the table.	✓	✓	
(d) A pool or spa listed in the table must have a cover or shading if specified for the pool or spa in the table.		✓	
(e) The applicant must install each fire sprinkler system listed in the table so that the system is configured as specified in the table.		✓	✓
(f) The applicant must ensure that the central cooling system for a cooling tower is configured as specified in the table.		✓	✓

Common area	Showerheads rating	Toilets rating	Taps rating	Clothes washers rating
All common areas	no common facility	no common facility	no common facility	no common laundry facility

(ii) Energy	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
(a) If, in carrying out the development, the applicant installs a ventilation system to service a common area specified in the table below, then that ventilation system must be of the type specified for that common area, and must meet the efficiency measure specified.		✓	✓
(b) In carrying out the development, the applicant must install, as the "primary type of artificial lighting" for each common area specified in the table below, the lighting specified for that common area. This lighting must meet the efficiency measure specified. The applicant must also install a centralised lighting control system or Building Management System (BMS) for the common area, where specified.		✓	✓
(c) The applicant must install the systems and fixtures specified in the "Central energy systems" column of the table below. In each case, the system or fixture must be of the type, and meet the specifications, listed for it in the table.	✓	✓	✓

	Common area ventilation system		Common area lighting		
Common area	Ventilation system type	Ventilation efficiency measure	Primary type of artificial lighting	Lighting efficiency measure	Lighting control system/ BMS
Car Park (B1)	ventilation (supply + exhaust)	carbon monoxide monitor + VSD fan	light-emitting diode	zoned switching with motion sensor	yes
Loading Dock (GF)	no mechanical ventilation	-	light-emitting diode	motion sensors	yes
Switch Room (B1)	ventilation supply only	thermostatically controlled	light-emitting diode	manual on / manual off	yes
Chute Room + FOGO Bin room (B1)	ventilation exhaust only	-	light-emitting diode	motion sensors	yes
Bin Holding Room (B1)	ventilation supply only	-	light-emitting diode	motion sensors	yes
Bulky Storage (B1)	ventilation exhaust only	-	light-emitting diode	motion sensors	yes
Fire Pump Room (B1)	ventilation supply only	thermostatically controlled	light-emitting diode	manual on / manual off	yes
CW Press (B1)	ventilation supply only	thermostatically controlled	light-emitting diode	manual on / manual off	yes
Services Shafts (GF-L5)	no mechanical ventilation	-	light-emitting diode	manual on / manual off	yes
Main Comms Room (B1)	air conditioning system	thermostatically controlled	light-emitting diode	manual on / manual off	yes
Ground floor lobby (GF)	ventilation supply only	time clock or BMS controlled	light-emitting diode	motion sensors	yes

Central energy systems	Type	Specification
Alternative energy supply	Photovoltaic system	Rated electrical output (min): 25 peak kW
Other	-	-

Notes

1. In these commitments, "applicant" means the person carrying out the development.
2. The applicant must identify each dwelling, building and common area listed in this certificate, on the plans accompanying any development application, and on the plans and specifications accompanying the application for a construction certificate / complying development certificate, for the proposed development, using the same identifying letter or reference as is given to that dwelling, building or common area in this certificate.
3. This note applies if the proposed development involves the erection of a building for both residential and non-residential purposes (or the change of use of a building for both residential and non-residential purposes). Commitments in this certificate which are specified to apply to a "common area" of a building or the development, apply only to that part of the building or development to be used for residential purposes.
4. If this certificate lists a central system as a commitment for a dwelling or building, and that system will also service any other dwelling or building within the development, then that system need only be installed once (even if it is separately listed as a commitment for that other dwelling or building).
5. If a star or other rating is specified in a commitment, this is a minimum rating.
6. All alternative water systems to be installed under these commitments (if any), must be installed in accordance with the requirements of all applicable regulatory authorities. NOTE: NSW Health does not recommend that stormwater, recycled water or private dam water be used to irrigate edible plants which are consumed raw, or that rainwater be used for human consumption in areas with potable water supply.

Legend

1. Commitments identified with a "✔" in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).
2. Commitments identified with a "✔" in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.
3. Commitments identified with a "✔" in the "Certifier check" column must be certified by a certifying authority as having been fulfilled. (Note: a certifying authority must not issue an occupation certificate (either interim or final) for a building listed in this certificate, or for any part of such a building, unless it is satisfied that each of the commitments whose fulfilment it is required to monitor in relation to the building or part, has been fulfilled).