

Non-combustibility compliance of EQUITONE façade materials

- ✓ EQUITONE façade materials are manufactured in compliance with AS/NZS 2908.2:2000, Cellulose-cement products Part 2: Flat sheets, (ISO 8336:2009 Fibre-cement flat sheets).
- ✓ EQUITONE façade materials are classified as fibre-reinforced cement sheeting in accordance with AS/NZS 2908.2 (ISO 8336:2009 Fibre-cement flat sheets).
- ✓ According to Clause C1.12 of the Building Code of Australia, EQUITONE façade materials may be used wherever a non-combustible material is required.
- ✓ In accordance with AS/NZS 3837, EQUITONE façade materials are classified as Group 1, with average specific extinction area of only 7.6 m<sup>2</sup>/Kg, significantly lower than 250 m<sup>2</sup>/Kg referenced in the specification C1.10 of the Building Code of Australia.
- ✓ EQUITONE facade materials do not contribute to the spread of fire as per AS/NZS 1530.3.
- ✓ The following table provides a summary of the fire hazard properties of EQUITONE façade materials;

Reaction to fire	Value	Standard
Ignitability index	0	AS/NZS 1530.3
Spread of flame index	0	
Heat evolved index	0	
Smoke developed index	2	
Average specific extinction area Classification	7.6 m <sup>2</sup> /Kg Group 1	AS/NZS 3837

For further information, please consult with EQUITONE Australia Technical Department.

EQUITONE Australia

[www.equitone.com](http://www.equitone.com)

[info.australia@equitone.com](mailto:info.australia@equitone.com)