



NABERS Embodied emissions material

New non-residential developments must complete this for

From 1 October 2023, all new non-residential developments must report on embodied emissions as part of the NSW government's State Environmental Planning Policy (Sustainable Buildings SEPP) requirements for key materials at the development application and construction certificate stages.

[More on the Sustainable Buildings SEPP](#)

Embodied carbon emissions are generated across the full life cycle of a building from "cradle to gate" of the whole-of-life carbon footprint of Australia's buildings in 2019 [1]. The purpose of this reporting form is to support project team discussions about potential reduction in emissions from key material and construction emissions factors. This reporting form will be updated to reflect the NABERS Embodied Carbon Reporting Form.

Step 1: About the building

In the 'About the building' tab, you will add the location, function, and type of building you are reporting on. You will also add information that describes the building, including gross floor area, number of floors, and other relevant details. This information will allow the NSW Government to compare similar buildings.

Step 2: Quantity of materials

In the 'Quantity of materials' tab, you will add the amounts of materials that you will use in your building. Complete those fields relevant to your building. Leave fields that aren't relevant to your building blank. Due to uncertainty, particularly at DA stage, so please use your best estimates where information is not available.

How much do I need to include?

You must include all parts of the building delivered by the main contractor, covering at least the building envelope. If you spent \$100,000 on materials, you need to include the material amounts of at least \$100,000.

Wherever possible, consider materials costs only, not labour, plant or equipment. However, if you include labour or equipment costs, please simply be consistent in the way the costs are reported throughout the spreadsheet.

Enter the **quantity of materials** (excluding labour, plant, equipment, margins and taxes) for each material type.

- (1) Structure (substructure and superstructure) within the envelope of the building. Also include the main building to function (for example, plant that is in a separate building).
- (2) Envelope (cladding, curtain walls, roofing, windows, doors etc.)
- (3) Permanent internal walls and doors. At minimum, this should include all structural walls and doors.
- (4) External works (hard landscaping, carparks, etc.) outside of the building envelope.

Enter the **cost of materials** (excluding labour, plant, equipment, margins and taxes) for (5) Building services (mechanical, electrical, plumbing, vertical transport, etc.) required and equipment required by a particular tenant.

You must enter the amounts of materials in SI units (commonly known as the metric system) for various products on the market. However, you might need to convert the units of some materials.

Step 3: Certifier details

In the 'Certifier' tab you will add the details of the person who has entered data, and the data. The certifier must be a quantity surveyor, designer, engineer or NABERS assessor.

Step 4: Attach to approval

Attach this Excel spreadsheet to your development application or construction certificate. The data collected in this form will be used by the NSW Government to inform future policy.

Help!

If you have general questions about reporting on the embodied emissions of your building, contact your consent authority.

If you have technical questions about this spreadsheet, please contact NABERS: nabers@environment.nsw.gov.au

[1] Green Building Council of Australia, 2021, <https://new.gbca.org.au/news/gbca-news/gbca-and-thinkstep-n>

Materials form

Form

emissions using this form in NSW, where the 2022 applies. You must disclose the amounts of

cradle to grave". Embodied carbon made up 16% of the total carbon footprint. This form is to report on material quantities only, to support the NABERS Green Star rating. The form does not include embodied carbon tool when it's available in 2024.

you are planning to construct. You will also need to provide details of the area of carpark, and more. Collecting this

to construct your building. You only need to provide a rough estimate of the building blank. We recognise that there will be some uncertainty in the data (e.g., based on past projects).

at least 80% of the total materials bill. For example, if you have a total bill of \$80,000 of those materials in this form.

However, where you cannot split out the materials into a separate sheet.

is) for:

include any ancillary buildings that are necessary

alls.

..

to run the core of the building. Exclude special

stem). These are generally consistent across the materials (for example, convert volume to kg).

person who has certified the accuracy of the r.

e application.

olicy development.

ng, you should contact your local council or

elease-embodied-carbon-report/

Step 1: About the building

Building location and site data	Value	Unit	Note	Comment
Building address	33 & 37 Herbert St, St Leonards			
Postcode	2065		Required	Postcode of building
Town/city	St Leonards		Town/city/suburb/region automated from postcode (may not give exact town name)	Town/city/suburb/region of the building site.
Distance to nearest major city/town		km	Enter for rural/regional locations only	Declare the shortest route by road to your site from the centre of your nearest major city (>100,000 people). The route must be traversable by a semitrailer truck.
Project stage	Development Application		Required	Stage of development
New build or major renovation?	New build		Required	Portion of existing basement retained.
Brownfield or greenfield site?	Brownfield			

Floor area by NCC building classification	Gross (GFA)	Net (NLA/NSA/UFA)	Unit	Note	
Please enter all floor areas relevant to your building. Leave areas blank if not applicable. Please enter Gross Floor Area (GFA) for all building classifications. Please also enter the corresponding net area (Net Lettable Area, Net Sellable Area or Usable Floor Area) where it is commonly used for that building classification.					
Class 1a: Detached residential buildings			m²	Required for Class 1a: Detached residential houses, townhouses	Gross Floor Area (GFA), as defined by the AIQS Australian Cost Management Manual
Class 1b: Boarding houses and hostels			m²	Required for Class 1b: Boarding house, guest house, hostel	Net area (Net Lettable Area, Net Sellable Area, Usable Floor Area), as defined by the PCA's Method of Measurement
Class 2: Multi-unit residential buildings	52,735	36,835	m²	Required for Class 2: Multi-unit residential, including apartment buildings	
Class 3: Other residential buildings			m²		
Class 4: Residential inside non-residential			m²	Required for Class 4: Residential building inside a non-residential building, e.g., caretaker residence	
Class 5: Office buildings	6,247	5,652	m²	Required for Class 5: Office building	
Class 6: Retail buildings			m²	Required for Class 6: Retail building, e.g., shop, restaurant, café	
Class 7a: Carparks	17,708		m²	Required for Class 7a: Carparks	
Class 7b: Warehouse-type buildings			m²		
Class 8: Industrial buildings			m²	Required for Class 8: Industrial buildings, e.g., factories and workshops	
Class 9a: Healthcare buildings			m²	Required for Class 9a: Healthcare, e.g., hospitals, clinics, day surgeries	
Class 9b: Civic buildings			m²		
Class 9c: Aged care and personal care buildings			m²	Required for Class 9c: Aged care and personal care	
Class 10a: Non-habitable buildings			m²	Required for Class 10a: Non-habitable buildings including sheds, carports and private garages	
Class 10b: Miscellaneous structures			m²	Required for Class 10b: Miscellaneous structures, including fences, masts, antennas, retaining walls and swimming pools	
Class 10c: Bushfire shelters			m²	Required for Class 10c: Bushfire shelters not attached to a Class 1a building	
Total	76,690	42,487	m²	Required: Sum of m² inputs must be more than 0.	

Project information	Value	Unit	Note	
Total cost of project	313,006,156	AUD excl. GST	Required	Include labour, materials, transport, plant, equipment and professional fees. Exclude GST, land, finance, escalation and other costs.
Building design life	50	years	Required	If uncertain, enter 50 years
Estimated envelope life		years	Optional	
Estimated replacement cycle for mechanical services		years	Optional	
Estimated replacement cycle for vertical transportation		years	Optional	

Dimensions of the building and the site	Value	Unit	Note	
Site area	5,930	m²	Required	Total area of site to external boundary.
Shared services or infrastructure	Yes		Required	Indicate if there are shared services that the building utilises, or shared foundations, basement or podium
Building footprint area	4,077	m²	Required	Total floor area of the ground floor measured to the outside edge of the floorplate.
Typical floor area (if different to building footprint area)	2,263	m²	Only needed if different to row above	
Typical floor perimeter	340	m	Required	
Area of external carpark (not included in GFA)	0	m²	Required. Enter 0 if not applicable.	
Area of external hardstand (not included in GFA)	0	m²	Required. Enter 0 if not applicable.	
Area of other hard landscaping (not included in GFA)	1,438	m²	Required. Enter 0 if not applicable.	
Number of floors/storeys above ground, including ground floor	39	no.	Required	
Number of floors/storeys below ground	2	no.	Required. Enter 0 if not applicable.	
Number of floors/storeys of car parking	4	no.	Required. Enter 0 if not applicable.	
Total height above ground	129	m	Required	Measured from the average finished grade to the highest point of the building, excluding protrusions (lighting rods, masts, chimneys, etc.)

Structural material choices	Value	Unit	Note	
Foundation type	Spot/pad footing		Required	
Frame type (dominant)	Reinforced concrete			
Suspended floor type (typical)	Post-tensioned concrete		Only needed for multi-storey buildings	
Describe low carbon materials specified in your building (e.g. green concrete, low carbon bricks)	Low carbon materials specified at this time are but not limited to - Toilet Cubicle Partitions to be sustainably sourced and Greenstar certified materials supplied by Laminex - Laminate for Joinery to be sustainably sourced and Greenstar certified materials supplied by Laminex		Required	

Describe recycled content specified in your building (e.g. recycled steel)	Recycled Content specified at this time are but not limited to - Existing basement shoring & site fill. - Rainwater Reuse with the rainwater tanks with combined volume of 100kL - Mix water for all concrete used in the project contains at least 50% captured or reclaimed water - Recycled Aluminium to be used for movement joint, stair nosing, tactical indicator, carpet trim, threshold ramp plate - Recycled Fibre cement to be used for the ceiling soffit lining, perforated ceiling wall lining.		Required	
---	--	--	----------	--

Step 2: Quantity of materials

Complete all blue cells that are applicable to the building. Leave items that aren't applicable blank.

Material category	Sub-category 1	Sub-category 2	Sub-category 3	Value	Unit of measure	Comment	AIQS ACMM Code	ICMS3 (Level 3 Codes Construction)
Structure								
The structural parts of the building that are below ground (substructure) and above ground (superstructure). This includes fill below the substructure, foundations, basement levels, suspended floors, wall structure, roof structure, stairs, lift shafts and balconies. It excludes external areas such as hardstands, carparks, patios, etc.								
Coverage of structural material spend	-	-	-	80	%	Required. Coverage of spend for structural elements entered below. Minimum requirement = 80%. Exclude head contractor preliminaries and margins.		
Concrete in-situ	≤10 MPa	-	-		m³	Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
Concrete in-situ	>10 MPa to ≤20 MPa	-	-		m³	Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
Concrete in-situ	>20 MPa to ≤32 MPa	-	-		m³	Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
Concrete in-situ	>32 MPa to ≤40 MPa	-	-		m³	Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
Concrete in-situ	>40 MPa to ≤50 MPa	-	-	20,941.2	m³	Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
Concrete in-situ	>50 MPa to ≤60 MPa	-	-		m³	Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
Concrete in-situ	>60 MPa to ≤80 MPa	-	-	13,317.5	m³	Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
Concrete in-situ	>80 MPa to ≤100 MPa	-	-		m³	Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
Concrete in-situ	>100 MPa	-	-		m³	Please enter reinforcing steel as part of "Reinforcing steel" below	01_SB or 02-11	02 or 03
Concrete pre-cast panel	-	-	-		m³	Please enter reinforcing steel in relevant line items below. If not known at DA stage, please make your best estimate. If not known at CC stage, please ask your supplier.	01_SB or 02-11	02 or 03
Concrete block	Hollow core	-	-		m³	Enter as <u>cubic metres</u> , calculated as (area in m²) * (thickness in mm / 1000). Please include all block fill concrete and all reinforcing steel in relevant line items above/below.	01_SB	02 or 03
Concrete block/brick	Solid	-	-	5,964.0	m³	Enter as <u>cubic metres</u> , calculated as (area in m²) * (thickness in mm / 1000)	01_SB	02 or 03
Concrete block/brick	Solid AAC	-	-		m³	Solid Aerated Autoclaved Concrete (AAC) block. Enter as <u>cubic metres</u> , calculated as (area in m²) * (thickness in mm / 1000).	01_SB	02 or 03
Mortar	-	-	-		kg		01_SB	02 or 03
Reinforcing steel	Bar & mesh	-	-	4,430,138	kg	Include all reinforcing steel bar/mesh in the building's structure in this row. Usually this is calculated as kg/m³ per concrete element and then summed. Example: 10 m³ of 40 MPa concrete @ 100 kg/m³ + 5 m³ of 50 MPa concrete @ 150 kg/m³ = 1,750 kg reinforcing steel.	01_SB or 02-11	02 or 03
Reinforcing steel	Fibre & strand	-	-		kg	Include all steel fibre reinforcing and steel strand in the building's structure in this row.	01_SB or 02-11	02 or 03
Structural steel	Hot rolled structural	-	-	0.0	t	Examples include universal beams, universal columns and welded beams	01_SB	02 or 03
Structural steel	Cold formed structural	-	-	0.00	t	Examples include C purlins, Z purlins and all light gauge steel framing	01_SB	02 or 03
Structural steel	Other welded structural	-	-		t		01_SB	02 or 03
Structural steel	Plate	-	-		t	Include any allowance for connections here	01_SB	02 or 03
Structural steel	Sheet	-	-		t		01_SB	02 or 03
Stainless steel	-	-	-		t	Primarily for engineered timber structure connections	02_11	02 or 03
Reinforced concrete piles	Concrete	-	-	769	m³	Please enter reinforcing steel in the line below. If not known at DA stage, please make your best estimate. If not known at CC stage, please ask your supplier.	01_SB	02 or 03
Reinforced concrete piles	Steel reinforcing	-	-	92,287	kg	If not known at DA stage, please make your best estimate. If not known at CC stage, please ask your supplier.	01_SB	02 or 03
Steel piles	-	-	-	0.0	t	Where concrete and reinforcing steel are also used, enter these in the rows above.	01_SB	02 or 03
Timber poles/piles	-	-	-	0.0	m³	Where concrete and reinforcing steel are also used, enter these in the rows above.	01_SB	02 or 03
Timber (solid)	Sawn softwood	-	-	0.0	m³		02_11	02 or 03
Timber (solid)	Sawn hardwood	-	-	0.0	m³		02_11	02 or 03
Timber (engineered)	CLT	-	-	0.0	m³		02_11	02 or 03
Timber (engineered)	Glulam	-	-	0.0	m³		02_11	02 or 03
Timber (engineered)	LVL	-	-	0.0	m³		02_11	02 or 03
Timber (engineered)	OSB	-	-	0.0	m³	Enter as <u>cubic metres</u> , calculated as (area of wall in m²) * (thickness in mm / 1000)	02_11	02 or 03
Brick	Heat cured	-	-	0.0	m³	Enter as <u>cubic metres</u> , calculated as (area of wall in m²) * (thickness in mm / 1000)	02_11	02 or 03
Structural Insulated Panel (SIP)	Steel outer	-	-	0.0	m²		01_SB	02 or 03
Structural Insulated Panel (SIP)	Aluminium outer	-	-	0.0	m²		01_SB	02 or 03
Structural Insulated Panel (SIP)	Engineered timber outer	-	-	0.0	m²		01_SB	02 or 03
Fill	-	-	-	0.0	t	Include purchased material only. Exclude site-won material.	01_SB	01
Sand & gravel	-	-	-	0.0	t	Include purchased material only. Exclude site-won material and sand/gravel in concrete.	01_SB	01
Waterproofing membrane	Bituminous	-	-	0	m²		01_SB	01 or 02 or 03
Waterproofing membrane	Polyethylene	-	-	10,509	m²		01_SB	01 or 02 or 03
Other structural (Describe and add unit >>)	Post Tensioning	-	-	115,685.4	kg	Please enter a description for any structural material that does not fit a predefined classification		
Other structural (Describe and add unit >>)		-	-			Please enter a description for any structural material that does not fit a predefined classification		
Other structural (Describe and add unit >>)		-	-			Please enter a description for any structural material that does not fit a predefined classification		

Envelope

The skin of the building that separates the internal building from the external environment.

This includes the roof cladding, wall cladding, windows, doors and internal/external shading. It also includes insulation and the internal wall lining of envelope walls.

Coverage of envelope material spend	-	-	-	80	%	Required. Coverage of spend for the envelope items you have entered below. Minimum requirement = 80%. Exclude head contractor preliminaries and margins.		
Roof cladding	Profiled steel	-	-		m²	Enter as m² of roof area. Exclude allowances for overlap in the roofing sheets. This row includes all metal-coated and pre-painted steel sheets where steel is the base metal. Examples include: galvanised steel, zinc-aluminium (zincalume) coated steel and zinc-aluminium-magnesium (ZAM) coated steel, whether painted or unpainted.	05_RF	03 or 04
Roof cladding	Profiled aluminium	-	-		m²	Enter as m² of roof area. Exclude allowances for overlap in the roofing sheets. This row also includes pre-painted aluminium sheets.	05_RF	03 or 04
Roof cladding	Profiled zinc	-	-	0	m²	Enter as m² of roof area. Exclude allowances for overlap in the roofing sheets. This row also includes pre-painted zinc sheets.	05_RF	03 or 04
Roof cladding	Membrane	-	-	0	m²	Enter as m² of roof area. Exclude allowances for overlap in the membrane sheets.	05_RF	03 or 04
Roof cladding	Tiles (traditional clay)	-	-	0	m²	Enter as m² of roof area. Exclude allowances for overlap between the tiles.	05_RF	03 or 04
Roof cladding	Tiles (concrete)	-	-	0	m²	Enter as m² of roof area. Exclude allowances for overlap between the tiles.	05_RF	03 or 04
Roof cladding	Other (Please describe >>)	Soffit Cladding	-	1,140	m²	Please enter a description for any roofing that does not fit a predefined classification	05_RF	03 or 04
Wall cladding	Bricks (heat cured)	-	-		m²	Enter as m² of wall area. Heat-cured bricks use a kiln or furnace to raise the brick temperature above ambient temperature during curing process.	06_EW	03 or 04
Wall cladding	Bricks (air dried)	-	-	0	m²	Enter as m² of wall area. Air-dried bricks are cured using ambient temperature.	06_EW	03 or 04
Wall cladding	Bricks (under fired)	-	-	0	m²	Enter as m² of wall area.	06_EW	03 or 04
Wall cladding	Bricks (concrete)	-	-	0	m²	Enter as m² of wall area	06_EW	03 or 04
Wall cladding	Mortar and render	-	-	1,980	kg		06_EW	03 or 04
Wall cladding	Profiled steel	-	-	0	m²	Enter as m² of wall area. Exclude allowances for overlap in the cladding sheets, offcuts, etc. This row includes all metal-coated and pre-painted steel sheets where steel is the base metal. Examples include: galvanised steel, zinc-aluminium (zincalume) coated steel and zinc-aluminium-magnesium (ZAM) coated steel, whether painted or unpainted.	06_EW	03 or 04
Wall cladding	Profiled aluminium	-	-	3,384	m²	Enter as m² of wall area. Exclude allowances for overlap in the cladding sheets, offcuts, etc. This row also includes pre-painted aluminium sheets.	06_EW	03 or 04
Wall cladding	Profiled zinc	-	-	0	m²	Enter as m² of wall area. Exclude allowances for overlap in the cladding sheets, offcuts, etc. This row also includes pre-painted zinc sheets.	06_EW	03 or 04
Wall cladding	GRC cladding	-	-	0	m²	Enter as m² of wall area. GRC = Glass Reinforced Concrete.	06_EW	03 or 04
Wall cladding	Timber weatherboards	-	-	0	m²	Enter as m² of wall area. Exclude allowances for overlap between weatherboards, offcuts, etc.	06_EW	03 or 04
Wall cladding	Fibre cement board	-	-	7,895	m²	Enter as m² of wall area. Exclude allowances for offcuts, etc.	06_EW	03 or 04
Wall cladding	Terracotta	-	-	0	m²	Enter as m² of wall area. Exclude allowances for offcuts, etc.	06_EW	03 or 04
Wall cladding	Brick tiles / veneers	-	-	0	m²	Enter as m² of wall area. Exclude allowances for offcuts, etc.	06_EW	03 or 04
Wall cladding	Plasterboard	-	-	12,543	m²	Enter as m² of wall area. Exclude allowances for offcuts, etc. Include both external wall linings and internal wall linings for envelope walls.	12_WF or 06_EW	03 or 04
Wall cladding	Plywood	-	-		m²	Enter as m² of wall area. Exclude allowances for offcuts, etc. Include both external wall linings and internal wall linings for envelope walls.	12_WF or 06_EW	03 or 04
Wall cladding	Other (Please describe >>)		-		m²	Please enter a description for any wall cladding that does not fit a predefined classification	06_EW or 12_WF	03 or 04
Windows & doors	Aluminium frame	Single glazed	-	6,414	m²	Include all single glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Aluminium frame	Double glazed	-	4,821	m²	Include all double glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Aluminium frame	Triple glazed	-		m²	Include all triple glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Timber frame	Single glazed	-		m²	Include all single glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Timber frame	Double glazed	-		m²	Include all double glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Timber frame	Triple glazed	-		m²	Include all triple glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	uPVC frame	Single glazed	-		m²	Include all single glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	uPVC frame	Double glazed	-		m²	Include all double glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	uPVC frame	Triple glazed	-		m²	Include all triple glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Frameless	Single glazed	-		m²	Include all single glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Frameless	Double glazed	-		m²	Include all double glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Frameless	Triple glazed	-		m²	Include all triple glazing, including standard, toughened, laminated and low-E	07_WW or 08_ED	03 or 04
Windows & doors	Other (Please describe >>)		-		m²	Please enter a description for any windows or doors that do not fit a predefined classification	07_WW or 08_ED	03 or 04
Curtain wall	Single skin façade	Glazed panel	Single glazed		m²	Please declare all single-skin façade area in this section. All double-skin façade area should be entered in the next section. Include all single glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Curtain wall	Single skin façade	Glazed panel	Double glazed		m²	Include all double glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Curtain wall	Single skin façade	Glazed panel	Triple glazed		m²	Include all triple glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Curtain wall	Single skin façade	Opaque panel	Aluminium cladding		m²		06_EW	03 or 04
Curtain wall	Single skin façade	Opaque panel	GRC cladding		m²	GRC = Glass-fibre Reinforced Concrete	06_EW	03 or 04
Curtain wall	Single skin façade	Opaque panel	Insulated shadow box		m²		06_EW	03 or 04
Curtain wall	Single skin façade	Opaque panel	Brick cladding		m²		06_EW	03 or 04
Curtain wall	Single skin façade	Opaque panel	Stone cladding		m²		06_EW	03 or 04
Curtain wall	Double skin façade	Glazed panel	Single glazed		m²	Please declare all double-skin façade area in this section. Please declare as the area of the curtain wall and do not enter the inner and outer skins twice.	06_EW	03 or 04
Curtain wall	Double skin façade	Glazed panel	Double glazed		m²	Include all single glazing, including standard, toughened, laminated and low-E.	06_EW	03 or 04
Curtain wall	Double skin façade	Glazed panel	Triple glazed		m²	The type of glazing refers to the building's envelope wall, not including the outer skin	06_EW	03 or 04
Curtain wall	Double skin façade	Opaque panel	Aluminium cladding		m²	The type of glazing refers to the building's envelope wall, not including the outer skin	06_EW	03 or 04
Curtain wall	Double skin façade	Opaque panel	GRC cladding		m²	GRC = Glass-fibre Reinforced Concrete	06_EW	03 or 04
Curtain wall	Double skin façade	Opaque panel	Insulated shadow box		m²		06_EW	03 or 04

Curtain wall	Double skin façade	Opaque panel	Brick cladding		m²		06_EW	03 or 04
Curtain wall	Double skin façade	Opaque panel	Stone cladding		m²		06_EW	03 or 04
Curtain wall	Other (Please describe >>)		-		m²	Please enter a description for any curtain wall that does not fit a predefined classification	06_EW	03 or 04
Stick-framed wall system	Aluminium frame	Glazed section	Single glazed		m²	Include all single glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Stick-framed wall system	Aluminium frame	Glazed section	Double glazed		m²	Include all double glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Stick-framed wall system	Aluminium frame	Glazed section	Triple glazed		m²	Include all triple glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Stick-framed wall system	Aluminium frame	Opaque section	Aluminium cladding		m²		06_EW	03 or 04
Stick-framed wall system	Aluminium frame	Opaque section	GRC cladding		m²	GRC = Glass-fibre Reinforced Concrete	06_EW	03 or 04
Stick-framed wall system	Aluminium frame	Opaque section	Insulated shadow box		m²		06_EW	03 or 04
Stick-framed wall system	Aluminium frame	Opaque section	Brick cladding		m²		06_EW	03 or 04
Stick-framed wall system	Aluminium frame	Opaque section	Stone cladding		m²		06_EW	03 or 04
Stick-framed wall system	Steel frame	Glazed section	Single glazed		m²	Include all single glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Stick-framed wall system	Steel frame	Glazed section	Double glazed		m²	Include all double glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Stick-framed wall system	Steel frame	Glazed section	Triple glazed		m²	Include all triple glazing, including standard, toughened, laminated and low-E	06_EW	03 or 04
Stick-framed wall system	Steel frame	Opaque section	Aluminium cladding		m²		06_EW	03 or 04
Stick-framed wall system	Steel frame	Opaque section	GRC cladding		m²	GRC = Glass-fibre Reinforced Concrete	06_EW	03 or 04
Stick-framed wall system	Steel frame	Opaque section	Insulated shadow box		m²		06_EW	03 or 04
Stick-framed wall system	Steel frame	Opaque section	Brick cladding		m²		06_EW	03 or 04
Stick-framed wall system	Steel frame	Opaque section	Stone cladding		m²		06_EW	03 or 04
Stick-framed wall system	Other (Please describe >>)		-		m²	Please enter a description for any wall system that does not fit a predefined classification	06_EW	03 or 04
Wall louvre system	Aluminium	-	-	3,589	m²		06_EW	03 or 04
External shading system	Aluminium frame	Aluminium cladding	-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Aluminium frame	GRC cladding	-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000). GRC = Glass-fibre Reinforced Concrete.	06_EW	03 or 04
External shading system	Aluminium frame	Terracotta cladding	-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Aluminium frame	Stone cladding	-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Aluminium frame	Pre-cast concrete	-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Aluminium frame	Timber	-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Aluminium frame	Glass (opaque)	-	269	m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Aluminium frame	Steel	-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
External shading system	Other (Please describe >>)		-		m²	Please enter as m² of shaded area = linear metres * (width in mm / 1000)	06_EW	03 or 04
Roller doors	Steel profile	-	-	24	m²	Please note unit is <u>square metres</u> , not quantity	08_ED	03 or 04
Roller doors	Hardwood over steel	-	-	0	m²	Please note unit is <u>square metres</u> , not quantity	08_ED	03 or 04
Roller doors	Softwood over steel	-	-		m²	Please note unit is <u>square metres</u> , not quantity	08_ED	03 or 04
Revolving doors	Glass/aluminium/steel	-	-	5	no.		08_ED	03 or 04
Fire-rated doors	Engineered timber	-	-	6	no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	08_ED	03 or 04
Fire-rated doors	Steel	-	-		no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	08_ED	03 or 04
Fire-rated doors	Aluminium/glass	-	-		no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	08_ED	03 or 04
Insulation	Glass wool / fibreglass	-	-	23,929	m²	Please include both wall and ceiling insulation	05_RF or 06_EW	03 or 04
Insulation	Stone wool	-	-		m²	Please include both wall and ceiling insulation	05_RF or 06_EW	03 or 04
Insulation	Polyester	-	-		m²	Please include both wall and ceiling insulation	05_RF or 06_EW	03 or 04
Insulation	Expanded polystyrene	-	-		m²	Please include both wall and ceiling insulation	05_RF or 06_EW	03 or 04
Insulation	Other (Please describe >>)		-		m²	Please include both wall and ceiling insulation	05_RF or 06_EW	03 or 04
Other (Please describe and add unit >>)	Concrete Precast Panel	-	-	6,842.3	m²	Please enter a description for any envelope material that does not fit a predefined classification		
Other (Please describe and add unit >>)	Vertical Shrouds	-	-	1,214.6	m	Please enter a description for any envelope material that does not fit a predefined classification		
Other (Please describe and add unit >>)	Structural steel wall framing	-	-	103.4	t	Please enter a description for any envelope material that does not fit a predefined classification		

Permanent internal walls and doors

Walls and doors within the building that are either structural or designed to be permanent.

Coverage of material spend on permanent internal walls and doors				50	%	Enter the % coverage of <u>spend</u> for the items you have entered below. There is no minimum requirement, enter what you know. This should include all structural walls. Exclude head contractor preliminaries and margins.		
Interior wall (permanent)	Steel (light framing)	-	-	266	t		09_NW	03 or 04
Interior wall (permanent)	Timber framing	-	-		m³		09_NW	03 or 04
Interior wall (permanent)	AAC panel (reinforced)	-	-		m²	Panels of autoclaved aerated concrete (AAC) with reinforcing steel. E.g., Hebel.	09_NW or 12_WF	03 or 04
Interior wall (permanent)	Concrete-filled steel panel	-	-		m²	Panels made from a steel sheet outer with an aerated concrete core. E.g., Speedpanel.	09_NW or 12_WF	03 or 04
Interior wall (permanent)	Plasterboard	-	-	112,232	m²	Enter as single-layer equivalent. If using 2 layers, multiply the area by 2.	09_NW or 12_WF	03 or 04
Interior wall (permanent)	Plywood	-	-		m²	Enter as single-layer equivalent. If using 2 layers, multiply the area by 2.	09_NW or 12_WF	03 or 04
Interior wall (permanent)	Fibre cement sheet	-	-		m²	Enter as single-layer equivalent. If using 2 layers, multiply the area by 2.	09_NW or 12_WF	03 or 04
Interior wall (permanent)	Insulation	-	-	31,217	m²		09_NW or 12_WF	03 or 04
Interior wall (permanent)	Glass	-	-	67.0	m²		09_NW or 12_WF	03 or 04
Interior wall (permanent)	Other (Please describe >>)		-		m²	Please enter a description for any internal wall that does not fit a predefined classification	09_NW or 12_WF	03 or 04
Internal door (permanent)	Aluminium/glass	-	-	3	no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	11_ND	03 or 04
Internal door (permanent)	Timber/glass	-	-		no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	11_ND	03 or 04
Internal door (permanent)	Timber solid lightweight	-	-	1,783	no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	11_ND	03 or 04

Internal door (permanent)	Fire resistant	-	-	989	no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	11_ND	03 or 04
Internal door (permanent)	Steel	-	-		no.	Please enter as single-leaf equivalent. For double-leaf doors, multiply the quantity by 2.	11_ND	03 or 04
Internal door (permanent)	Other (Please describe >>)		-		no.	Please enter a description for any internal door that does not fit a predefined classification	11_ND	03 or 04
Other (Please describe and add unit >>)		-	-			Please enter a description for any material that does not fit a predefined classification		
Other (Please describe and add unit >>)		-	-			Please enter a description for any material that does not fit a predefined classification		
Other (Please describe and add unit >>)		-	-			Please enter a description for any material that does not fit a predefined classification		

Services				Unit of measure				
Building services included <u>within the main building contract</u> . If the building components that are the subject of the development application or the construction certificate are base building only, then only enter these items. If you cannot split services by type, please enter them all in the "Other services" category at the bottom. Enter all values as material costs in dollars.								
Mechanical services	-	-	-	7,597,755	AUD excl. GST	Where possible, enter material costs excluding labour, plant, equipment, margins and taxes	28_SS	05
Vertical transportation	-	-	-	2,818,080	AUD excl. GST	Where possible, enter material costs excluding labour, plant, equipment, margins and taxes	28_SS	05
Electrical services	-	-	-	11,697,009	AUD excl. GST	Electrical services including the main power supply, backup generators, security and communications. Excluding solar installations.	26_LP	05
Solar photovoltaic installations	-	-	-	0	AUD excl. GST	Where possible, enter material costs excluding labour, plant, equipment, margins and taxes.	26_LP_LPGP	05
Plumbing/hydraulic services	-	-	-	4,697,469	AUD excl. GST	Where possible, enter material costs excluding labour, plant, equipment, margins and taxes	18_PD and 19_WS	05 or 06
Fire services				3,443,324	AUD excl. GST	Where possible, enter material costs excluding labour, plant, equipment, margins and taxes	25_FPSS04 or 39_XWAW_03 or 41_XF	05
Other services (Please describe)	Waste Services & Pool	-	-	432,825	AUD excl. GST	Please group all other services here, meaning that coverage will always be 100% for services. Enter only the material costs (excluding labour, plant, equipment, margins and taxes).	29_SS or multiple	

External works									
The materials associated with hard landscaping and outbuildings on the site but outside the building envelope. This includes hardstands, carparks, driveways, covered walkways, decks, patios, awnings, fences, gates, etc. Soft landscaping should be excluded.									
Coverage of spend on external works	-	-	-	80	%	Required. Coverage of spend for external works (excluding soft landscaping) entered below. Minimum requirement = 80%. Exclude head contractor preliminaries and margins.			
Asphalt	-	-	-	0	t		33_XR		07
Concrete in-situ	≤10 MPa	-	-		m³	Please enter reinforcing steel as part of "Reinforcing steel" below	33_XR or 34_XN or 35_XB or 36_XL		07
Concrete in-situ	>10 MPa to ≤20 MPa	-	-		m³	Please enter reinforcing steel as part of "Reinforcing steel" below	33_XR or 34_XN or 35_XB or 36_XL		07
Concrete in-situ	>20 MPa to ≤32 MPa	-	-	122.8	m³	Please enter reinforcing steel as part of "Reinforcing steel" below	33_XR or 34_XN or 35_XB or 36_XL		07
Concrete in-situ	>32 MPa to ≤40 MPa	-	-		m³	Please enter reinforcing steel as part of "Reinforcing steel" below	33_XR or 34_XN or 35_XB or 36_XL		07
Concrete in-situ	>40 MPa to ≤50 MPa	-	-		m³	Please enter reinforcing steel as part of "Reinforcing steel" below	33_XR or 34_XN or 35_XB or 36_XL		07
Concrete in-situ	>50 MPa	-	-		m³	Please enter reinforcing steel as part of "Reinforcing steel" below	33_XR or 34_XN or 35_XB or 36_XL		07
Pavers, bricks and blocks	Concrete	-	-		m²		33_XR		07
Pavers, bricks and blocks	Clay	-	-	2,780	m²		33_XR		07
Reinforcing steel	Bar & mesh	-	-	12,094	kg	Include all reinforcing steel bar/mesh in the external works in this row. Usually this is calculated as kg/m³ per concrete element and then summed. Example: 10 m³ of 40 MPa concrete @ 100 kg/m³ + 5 m³ of 50 MPa concrete @ 150 kg/m³ = 1,750 kg reinforcing steel.	33_XR or 34_XN or 35_XB or 36_XL		07
Reinforcing steel	Fibre & strand	-	-		kg	Include all steel fibre reinforcing and steel strand in the external works in this row.	33_XR or 34_XN or 35_XB or 36_XL		07
Structural steel	-	-	-	40	t		02_11		07
Structural aluminium	-	-	-		t	Includes structures, louvre systems, etc.	35_XB		07
External roof/wall cladding	Polycarbonate	-	-	403	m²	Enter as profiled polycarbonate sheet that would ordered, including allowance for overlap	35_XB		07
External roof/wall cladding	PVC	-	-		m²	Enter as profiled PVC sheet that would ordered, including allowance for overlap	35_XB		07
External roof/wall cladding	Bitumen sheet	-	-		m²	Enter as bituminous sheet that would ordered, including allowance for overlap	35_XB		07
External roof/wall cladding	Steel profile	-	-	384	m²	Enter as profiled steel sheet that would ordered, including allowance for overlap	35_XB		07
Fill	-	-	-	315	t	Include purchased material only. Exclude site-won material.	33_XR or 34_XN or 35_XB or 36_XL		07
Sand & gravel	-	-	-	79	t	Include purchased material only. Exclude site-won material and sand/gravel in concrete.	33_XR or 34_XN or 35_XB or 36_XL		07
Timber (solid)	Sawn softwood	-	-		m³		33_XR or 34_XN or 35_XB or 36_XL		07
Timber (solid)	Sawn hardwood	-	-		m³		33_XR or 34_XN or 35_XB or 36_XL		07
Timber (engineered)	CLT	-	-		m³		33_XR or 34_XN or 35_XB or 36_XL		07
Timber (engineered)	Glulam	-	-		m³		33_XR or 34_XN or 35_XB or 36_XL		07
Timber (engineered)	LVL	-	-	106.0	m³		33_XR or 34_XN or 35_XB or 36_XL		07
Timber (engineered)	OSB	-	-		m³		33_XR or 34_XN or 35_XB or 36_XL		07
Fabric (awning/sunshade)		-	-		m²		35_XB or 36_XL		07
Other (Please describe and add unit >>)					no.	Please enter a description for any external works that does not fit a predefined classification			
Other (Please describe and add unit >>)					no.	Please enter a description for any external works that does not fit a predefined classification			
Other (Please describe and add unit >>)					m²	Please enter a description for any external works that does not fit a predefined classification			
Other (Please describe and add unit >>)					m²	Please enter a description for any external works that does not fit a predefined classification			
Other (Please describe and add unit >>)		-	-			Please enter a description for any external works that does not fit a predefined classification			

Step 3: Certifier details

The material quantities must be determined through an itemised list of building materials (such as a bill of quantities) and certified by a quantity surveyor, designer, engineer or NABERS Assessor.

Person that completed this form	Value	Note
Name	Brendon Draybi	Required
Company	MBMpl Pty Ltd	Required
ABN	74099962231	
Profession	Senior Quantity Surveyor	Required
Qualification or registration	BConMgt (QS)	Required

Person that certified the details in this form	Value	Note
Name	Autumn Lu	Required
Company	MBMpl Pty Ltd	Required
ABN	74099962231	
Profession	Quantity Surveyor - Director	Required
Qualification or registration	BConMgt (QS), CQS, MAIQS, MRICS	Required

Confirmation of certification	Value	Note
Are 80% of material costs captured for the building's structure, envelope and external works?	Yes	Required
If no - why not?		

Additional comments from data provider

The DA Documents are reasonably detailed however there are some areas that are subject to change such as reinforcement currently being a ratio set by the engineer which once detailed could fluctuate therefore all care has been taken to provide a reasonable estimate of the materials in this project

Additional comments of certifier

The Extent of known information has been informed by the DA Documents and reasonable assumptions based on best industry Practice and are a reasonable estimate of the Embodied Carbon at this stage

This version:

1.20

Version history:

1.00	01-October-2023
1.10	12-October-2023
1.20	24-October-2023

Initial version.

Error on 'Instructions' tab - changed 'cost of materials' for (1)-(4) to 'quantity of materials'.

Manual check for updates using button (instead of each time the sheet is opened).