



BASIX REPORT

19A EVANS AVENUE, EASTLAKES

WF277-03F03(REV0)- BASIX REPORT

MAY 18, 2026

Prepared for:

Builtcom Developments Eastlakes Pty Ltd

Level 1, 15 George Street, Burwood, NSW, 2134



WINDTECH CONSULTANTS

www.windtechconsult.com

reception@windtechglobal.com

Sydney | Singapore | London | Melbourne | Mumbai | New York | Hong Kong | Dubai | Miami | Toronto

DOCUMENT CONTROL

Date	Revision History	Issued Revision	Prepared By (initials)	Instructed By (initials)	Reviewed & Authorised by (initials)
May 18, 2026	Initial.	0	CT/RF	MM	TH

The work presented in this document was carried out in accordance with the Windtech Consultants Quality Assurance System, which is based on International Standard ISO 9001.

This document is issued subject to review and authorisation by the Team Leader noted by the initials printed in the last column above. If no initials appear, this document shall be considered as preliminary or draft only and no reliance shall be placed upon it other than for information to be verified later.

This document is prepared for our Client's particular requirements which are based on a specific brief with limitations as agreed to with the Client. It is not intended for and should not be relied upon by a third party and no responsibility is undertaken to any third party without prior consent provided by Windtech Consultants. The information herein should not be reproduced, presented or reviewed except in full. Prior to passing on to a third party, the Client is to fully inform the third party of the specific brief and limitations associated with the commission.

CONTENTS

1	Introduction	2
2	BASIX Assessment Methodology	3
2.1	Water Usage	3
2.2	Thermal Comfort	3
2.3	Energy Usage	3
3	Results of the BASIX Assessment	4
3.1	Water	4
3.2	Thermal Comfort	6
3.3	Energy	81
4	Conclusion	85

INTRODUCTION

This report presents the results of a detailed BASIX assessment of the various residential dwellings within the proposed development located at 19A Evans Avenue, Eastlakes. The assessment is carried out using online BASIX and BERS Pro Thermal Performance assessment tool. This assessment is based on the architectural drawings prepared by DKO, received May 2026.

BASIX ASSESSMENT METHODOLOGY

A BASIX assessment is split into three sections; Water, Thermal Comfort and Energy. Each section measures the efficiency of the development in these areas. For the Water and Energy sections, the development is given a score based on the efficiency. BASIX sets a minimum score in these areas that the development must satisfy. The Thermal Performance section of the BASIX assessment requires a BERS Pro simulation to be undertaken. BASIX sets requirements on the maximum heating and cooling loads for each residential apartment of the development. The results of this are rated in BASIX as either a pass or fail.

2.1 Water Usage

The water usage of the development is measured based on the area of gardens/lawn and the number and efficiency of permanent fixtures within the development (such as showerheads, taps and toilets). The development is given a rating, with BASIX requiring a minimum rating of 40% to pass this section.

2.2 Thermal Comfort

The thermal comfort of the development is measured using the BERS Pro Thermal Performance assessment tool. This gives an expected level of energy consumption (expressed in Mega Joules used per square metre per annum) for the heating and cooling loads.

The thermal comfort of the development can be improved by using higher performance building materials (such as performance glazing) and/or insulation materials. BASIX sets a maximum heating and cooling load that the development is to achieve. This is given as a weighted average heating and cooling load for the entire development, and for each individual dwelling to achieve.

2.3 Energy Usage

The energy section of the BASIX assessment measures the energy efficiency of the development based on the efficiency of the fixed appliances to be used. This includes the hot water system, air-conditioning system, exhaust fans, lighting and the cook top/oven. If a pool is to be included in the proposal then the efficiency measure of the pool heater and the pool pump is also required. The development is given a rating, with BASIX requiring a minimum rating of 60% to pass this section.

RESULTS OF THE BASIX ASSESSMENT

3.1 Water

The minimum target score in BASIX to achieve water usage compliance is 40%. The minimum score is achieved through the inclusion of the following;

3.1.1 Central Systems & Common Areas

- A rainwater tank with a volume capacity of least 5,000L capacity is to be included. Water is to be provided from at least 1,000m² of the roof area. Water from the tank is to be used for all public landscaping (total area of 3,210m²) within the development site.
- An outdoor swimming pool with a volume capacity of 112kL is included within the proposed development.
- The fire sprinkler test water for the car park and building fire sprinkler systems are to be contained in a closed system.
- Note that BASIX defines fire sprinkler test water as water used to periodically test a building's automatic fire sprinkler system. Instead of pumping the water used to periodically test a building's fire sprinkler system into the sewerage system, a closed system is a system where this water can be stored in a storage tank (or similar) to reuse in the next periodic fire sprinkler test. If the water is partially or completely diverted to a tank for purposes other than fire sprinkler tests (such as garden watering), the system cannot be considered as a closed system.
- The common area showerheads are to have a water efficiency rating of at least 4.0 Stars (>6.0 but ≤7.5L/min).
- The common area toilets are to have a water efficiency rating of at least 4.0 Stars.
- The common area taps are to have a water efficiency rating of at least 4.0 Stars.

3.1.2 Dwellings

- All showerheads within each residential dwelling is to have a water efficiency rating of at least 4.0 Stars (>6.0 but ≤7.5L/min).
- All toilets within each residential dwelling is to have a water efficiency rating of at least 4.0 Stars.
- All kitchen taps within each residential dwelling is to have a water efficiency rating of at least 6.0 Stars.
- All bathroom taps within each residential dwelling is to have a water efficiency rating of at least 6.0 Stars.
- Dishwasher units are to be installed within each residential dwelling. The dishwasher units are to have a water efficiency rating of at least 4.0 stars.

3.2 Thermal Comfort

The BERS Pro assessments take into account the following fundamental aspects of energy efficient design:

- The orientation and size of the walls.
- The location, proportion and type of windows and doors, and any internal or external coverings to them.
- The materials and colours of the exterior of the building.
- Internal floor, wall and ceiling materials.
- Cross ventilation.
- Provision of any insulation in walls, roof or ceiling.
- Overshadowing to walls and windows from eaves, other parts of the development and neighbours.
- The topography and climate of the area around the proposed development.

The climate zone selected for analysis was Climate Zone 56. In BASIX, the required weighted averaged maximum heating and cooling loads of the entire proposed development are 28.0 MJ/m²/year for heating and 19.9 MJ/m²/year for cooling and for each individual dwelling a maximum heating and cooling load of 34.4 MJ/m²/year for heating and 21.4 MJ/m²/year for cooling. The required heating and cooling loads for the individual residential dwelling are indicated in Table 3. Note that the overall weighted average heating and cooling loads are significantly harder to achieve than the individual unit requirements.

3.2.1 Dwelling Construction Materials and Initial Results

The following construction materials were initially selected for the assessment. Note that the materials described are not prescriptive. The construction materials used on the subject development should be selected to have similar performance characteristics as the ones detailed below so as not to affect the overall thermal performance rating of each apartment. The U-value and Solar Heat Gain Coefficient (SHGC) for the glazed systems is also indicated.

The wall construction of each residential dwelling is indicated in Table 1a below:

Table 1a: Wall Systems for each Residential Dwelling

Dwelling Envelope Wall	Wall Construction
External (the wall between outdoor environment and the dwelling)	Metal Cladding, Hebel, Concrete
Party (the wall between dwelling and the dwelling)	Hebel Panel
Enclosed Lobby (the wall between enclosed lobby and the dwelling)	Hebel Panel
Outdoor Lobby (the wall between outdoor lobby and the dwelling)	Hebel Panel
Staircore/Lift/Shfts (the wall between staircore/lift/shafts and the dwelling)	Concrete
Carpark (between carpark and the dwelling)	Concrete
To unconditioned spaces such as plant, garbage, service rooms etc. (the wall between the unconditioned space and the dwelling)	Concrete
Internal (the wall internal walls within the dwelling)	Plasterboard on Stud

- The floor coverings will be following:
 - Cork/parquetry to the living areas
 - Carpets or Cork/parquetry to the bedrooms
 - Tiles to the kitchen
 - Tiles to the wet areas
 - Cork/parquetry to the hallways
 - Cork/parquetry to the study rooms
 - Cork/parquetry to the other internal areas (walk in pantries etc.)
- The floors will be concrete slabs.
- The ceilings will be concrete above plasterboard.
- The roof will be waterproof membrane.
- Draught seals are to be installed to the windows and doors.
- Sealed exhaust fans are assumed in the kitchen and wet areas.

- Ceiling penetrations due to recessed luminaires has been assumed at a rate of 1 per 2.5m² as the lighting/ceiling plan is yet to be determined and is not indicated on the drawing set. A reassessment may be undertaken at a later stage once the lighting/ceiling plan is finalised.
- The glazing systems within the residential dwellings are split into two groups; Group A and Group B based on the system type indicated in Table 1b below.
- Note that for thermal modelling purposes, glazed systems that have a combination of Group A and Group B system types, the group system type that accounts for the majority of the glazed system area will be selected. If they are equal in area then the Group A system type will be selected. However, for specification they are based on the Group type.

Table 1b: Glazed System Grouping

Group A	Group B
Awning Window	Double Hung Window
Bifold Door	Fixed Window
Bifold Window	Louvre Window
Entry Door	Sliding Window
Casement Window	Sliding door
French Door	Stacker door
Tilt'n'Turn Window	
Hinged Door	

The result of the analysis, indicated in Table 3, indicate that several of the residential dwellings within the proposed development will not satisfy the individual thermal requirements of BASIX. Hence treatment is required to some of the residential dwellings of the development.

3.2.2 Results with Treatments

Further analysis of the proposed development resulted in some required treatments to achieve the BASIX requirements for thermal performance. The required treatments are listed in Tables 2 below:

Table 2a: Required Treatments for Building 1

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
10401	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10402	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10403	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10404	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10405	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10406	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10407	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10408	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10409	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10410	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10411	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10412	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10413	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10414	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10415	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10501	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10502	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10503	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
10504	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10505	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10506	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10507	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10508	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10509	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10510	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10511	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10512	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10513	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10514	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10515	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10601	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10602	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10603	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10604	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10605	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10606	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10607	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10608	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10609	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10610	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
10611	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10612	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10613	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10614	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10615	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10701	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10702	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10703	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10704	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10705	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10706	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10707	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10708	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10709	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10710	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10711	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10712	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10713	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10714	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10715	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10801	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10802	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
10803	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10804	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10805	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10806	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10807	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10808	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10809	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10810	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10811	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10812	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10813	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10814	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10815	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10901	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10902	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10903	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10904	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10905	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10906	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10907	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10908	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10909	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
10910	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10911	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10912	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10913	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
10914	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
10915	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11001	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11002	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11003	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11004	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11005	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11006	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11007	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11008	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11009	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11010	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11011	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11012	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11013	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11014	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11015	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11101	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
11102	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11103	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11104	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11105	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11106	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11107	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11108	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11109	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11110	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11111	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11112	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11113	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11114	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11115	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11201	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11202	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11203	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11204	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11205	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11206	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11207	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11208	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
11209	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11210	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11211	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11212	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11213	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11214	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11215	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11301	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11302	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11303	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11304	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11305	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11306	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11307	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11308	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11309	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11310	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11311	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11312	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11313	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11314	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11315	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
11401	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11402	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11403	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11404	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11405	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11406	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11407	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11408	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11409	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11410	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11411	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11412	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11413	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11414	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11415	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11501	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11502	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11503	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11504	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11505	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11506	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11507	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
11508	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11509	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11510	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11511	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11512	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11513	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11514	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11515	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11601	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11602	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11603	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11604	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11605	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11606	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11607	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11608	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11609	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11610	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11611	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11612	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11613	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11614	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
11615	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
11701	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11702	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11703	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11704	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11705	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11706	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11707	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
11708	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
11709	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
11710	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
11711	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11712	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11713	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11714	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11715	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
11801	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
11802	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
11803	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	3	-	-
11804	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
11805	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
11806	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	3	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
11811	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	3	-	Inclusion of a ceiling fan with a diameter of 900mm within the Kitchen/Living Zone.
11812	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
11813	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
11814	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
11815	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-

Table 2b: Required Treatments for Building 2

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
20401	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20402	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20403	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20404	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20405	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20406	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20407	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20408	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20501	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20502	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20503	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20504	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20505	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20506	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20507	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20508	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20601	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20602	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20603	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20604	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20605	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
20606	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20607	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20608	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20701	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20702	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20703	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20704	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20705	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20706	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20707	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20708	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20801	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20802	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20803	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20804	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20805	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20806	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20807	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20808	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20901	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20902	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20903	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
20904	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20905	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20906	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
20907	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
20908	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21001	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21002	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21003	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21004	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21005	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21006	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21007	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21008	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21101	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21102	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21103	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21104	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21105	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21106	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21107	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21108	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21201	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
21202	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21203	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21204	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21205	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21206	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21207	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21208	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21301	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21302	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21303	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21304	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21305	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21306	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21307	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21308	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21401	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21402	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21403	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21404	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21405	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21406	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21407	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
21408	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21501	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21502	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21503	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21504	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21505	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21506	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21507	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21508	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21601	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21602	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21603	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21604	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21605	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21606	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
21607	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21608	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
21701	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
21702	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	2.5	-	-
21703	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	2.5	-	-
21704	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	2.5	-	-
21705	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	2.5	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
21706	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	2.5	-	-
21707	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
21708	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-

Table 2c: Required Treatments for Building 3

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
30001	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30002	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30003	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30004	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30005	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	2.5	2	-
30201	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30202	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30203	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30204	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30205	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30301	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	2.5	-	-
30302	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	2.5	-	-
30303	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	2.5	-	-
30304	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	2.5	-	-
30305	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	2.5	-	-
30401	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30402	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	2.5	-	-
30403	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30404	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30405	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30406	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
30407	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30408	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30409	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30410	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30411	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30412	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30501	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30502	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30503	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30504	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30505	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30506	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30507	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30508	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30509	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30510	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30511	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30512	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	2	-
30601	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30602	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30603	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30604	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
30605	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30606	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30607	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30608	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30609	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30610	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30611	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30612	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30701	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30702	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30703	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30704	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30705	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30706	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30707	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30708	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30709	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30710	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30711	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30712	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30801	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30802	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
30803	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30804	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
30805	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30806	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30807	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30808	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30809	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30810	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30811	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30812	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30901	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30902	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30903	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30904	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
30905	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30906	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30907	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30908	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30909	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
30910	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30911	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
30912	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
31001	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31002	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31003	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31004	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31005	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31006	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31007	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31008	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31009	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31010	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31011	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31012	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31101	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31102	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31103	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31104	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31105	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31106	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31107	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31108	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31109	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31110	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
31111	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31112	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31201	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31202	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31203	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31204	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31205	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31206	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31207	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31208	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31209	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31210	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31211	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31212	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31301	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31302	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31303	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31304	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31305	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31306	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31307	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31308	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
31309	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31310	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31311	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31312	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31401	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31402	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31403	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31404	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31405	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31406	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31407	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31408	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31409	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31410	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31411	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31412	Group A: U-value = 3.10, SHGC = 0.27 Group B: U-value = 3.10, SHGC = 0.27	2.5	-	-	-
31501	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31502	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31503	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31504	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31505	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31506	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
31507	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31508	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31509	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31510	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31511	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31512	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31601	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31602	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31603	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31604	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31605	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31606	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31607	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31608	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31609	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31610	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31611	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31612	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31701	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31702	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31703	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31704	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
31705	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
31706	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
31707	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
31708	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
31709	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
31710	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
31711	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
31712	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
31801	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
31802	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
31803	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
31804	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
31805	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-

Table 2d: Required Treatments for Building 4

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.)). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
40401	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40402	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40403	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	Inclusion of a 1200mm diameter ceiling fan in the Kitchen/Living Zone
40404	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40405	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40410	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40411	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40412	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40413	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40414	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40415	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	Inclusion of a 1200mm diameter ceiling fan in the Kitchen/Living Zone
40416	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	Inclusion of a 900mm diameter ceiling fan in the Kitchen/Living Zone
40418	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40419	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	Inclusion of a 900mm diameter ceiling fan in the Kitchen/Living Zone
40420	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40421	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40422	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40423	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40426	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	Inclusion of a 900mm diameter ceiling fan in the Kitchen/Living Zone

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
40427	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	Inclusion of a 900mm diameter ceiling fan in the Kitchen/Living Zone
40428	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40429	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40430	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40431	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40501	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40502	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40503	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40504	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40505	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40506	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40507	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40508	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40509	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40510	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40511	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40512	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40513	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40514	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40515	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40516	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40517	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
40518	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40519	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40520	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40521	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40522	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40523	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40524	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40525	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40526	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40527	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40528	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40529	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40530	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40531	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40601	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40602	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40603	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40604	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40605	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40606	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40607	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40608	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
40609	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40610	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40611	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40612	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40613	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40614	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40615	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40616	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40617	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40618	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40619	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40620	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40621	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40622	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40623	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40624	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40625	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40626	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40627	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40628	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40629	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40630	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
40631	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40701	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40702	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40703	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40704	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40705	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40706	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40707	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40708	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40709	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40710	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40711	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40712	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40713	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40714	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40715	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40716	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40717	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40718	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40719	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40720	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40721	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
40722	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40723	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40724	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40725	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40726	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40727	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40728	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40729	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40730	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40731	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40801	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40802	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40803	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40804	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40805	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40806	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40807	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40808	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40809	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40810	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40811	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40812	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
40813	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40814	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40815	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40816	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40817	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40818	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40819	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40820	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40821	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40822	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40823	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40824	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40825	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40826	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40827	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40828	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40829	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40830	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40831	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40901	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40902	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40903	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
40904	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40905	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40906	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40907	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40908	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40909	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40910	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40911	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40912	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40913	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40914	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40915	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40916	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40917	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40918	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40919	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40920	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40921	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40922	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40923	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40924	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40925	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
40926	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40927	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40928	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40929	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40930	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
40931	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41001	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41002	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41003	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41004	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41005	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41006	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41007	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41008	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41009	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41010	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41011	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41012	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41013	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41014	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41015	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41016	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
41017	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41018	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41019	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41020	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41021	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41022	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41023	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41024	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41025	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41026	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41027	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41028	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41029	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41030	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41031	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41101	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41102	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41103	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41104	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41105	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41106	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41107	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/ liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
41108	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41109	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41110	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41111	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41112	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41113	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41114	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41115	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41116	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41117	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41118	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41119	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41120	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41121	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41122	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41123	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41124	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41125	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41126	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41127	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41128	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41129	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
41130	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41131	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41201	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41202	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41203	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41204	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41205	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41206	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41207	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41208	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41209	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41210	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41211	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41212	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41213	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41214	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41215	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41216	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41217	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41218	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41219	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41220	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
41221	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41222	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41223	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41224	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41225	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41226	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41227	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41228	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41229	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41230	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41231	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41301	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41302	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41303	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41304	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41305	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41306	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41307	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41308	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41309	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41310	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41311	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
41312	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41313	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41314	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41315	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41316	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41317	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41318	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41319	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41320	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41321	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41322	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41323	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41324	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41325	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41326	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41327	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41328	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41329	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41330	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41331	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41401	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41402	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
41403	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41404	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41405	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41406	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41407	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41408	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41409	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41410	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41411	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41412	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41413	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41414	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41419	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41420	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41421	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41422	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41423	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41501	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41502	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41503	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41504	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41505	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
41506	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41507	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41508	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41509	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41510	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41511	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41512	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41513	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41514	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41515	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	-	-	-
41601	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41602	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41603	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41604	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41605	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41606	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41607	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41608	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41609	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41610	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41611	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41612	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-

Unit Number	Glazing Thermal Specification (See Table 1b for group information)	Additional Wall Insulation in the dwelling envelope wall (to outdoor air, lobby, stair/liftcore, enclosed unconditioned spaces (plant, shafts etc.). (R-value)	Additional Ceiling Insulation to areas with outdoor air or enclosed unconditioned spaces above. (R-value)	Additional Floor Insulation to areas above outdoor air/ carpark/ or enclosed unconditioned spaces. (R-value)	Additional Treatments
41613	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41614	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41615	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41710	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41711	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41712	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41713	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41714	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-
41715	Group A: U-value = 2.60, SHGC = 0.50 Group B: U-value = 2.60, SHGC = 0.53	2.5	2.5	-	-

A number of glazed system selections were used in the analysis due to certain residential dwellings requiring better thermal performing glazed systems due to the design, orientation, shading and glaze to wall façade ratios. These are summarised as follows:

Glazed System Selection No. 1

- Group A: U-value = 3.1, SHGC = 0.27 (please refer to Table 1b above)
- Group B: U-value = 3.1, SHGC = 0.27 (please refer to Table 1b above)

Glazed System Selection No. 2

- Group A: U-value = 2.6, SHGC = 0.50 (please refer to Table 1b above)
- Group B: U-value = 2.6, SHGC = 0.53 (please refer to Table 1b above)

With these treatments in place the weighted average maximum heating and cooling loads are 20.0 MJ/m²/year for heating and 10.0 MJ/m²/year for cooling. Hence, with the required treatments listed above, the proposed development will satisfy the thermal performance requirements of BASIX.

Note the required additional insulation requirements in Table 2 above are valid for the current design as indicated in the architectural drawings and the envelope wall construction types of the residential dwellings as indicated in Table 1a (i.e. dwelling wall to outdoor air, lobby, unconditioned spaces such as stair/liftcore, neighbour etc.).

If there are changes to the dwelling envelope wall construction; e.g. the wall type is changed to another material or a wall is comprised of more than one wall types, then the required additional wall insulation requirement in Table 2 above may also vary. This is due to different wall construction types having different inherent R-values. The thermal modelling software combines the inherent R-value of the wall construction type for each wall (as indicated in Table 1a) and the associated wall insulation (as indicated in Table 2) to form an overall "Envelope Wall Total R-value" for each wall. Thus, if a different wall construction type that has a lower inherent R-value is used in lieu of those in Table 1a, then the wall insulation requirement would be increased to achieve a similar "Envelope Wall Total R-value". Note the opposite is also true for wall constructions with "higher" inherent wall construction R-values can result in a decrease in the wall insulation requirement.

The glazing types selected for the windows of the proposed development should at least satisfy the required performance data listed in this report. Reducing the amount of glazing in each unit is expected to significantly increase the thermal performance of each unit. Higher performing glass types than those listed in this report are also acceptable. That is, alternative glazing systems or specifications may be used if their U value is equivalent or lower, and the SHGC value is less than +/-10% than the U-value and SHGC value of the product specified in the table above as per the BASIX Thermal Comfort Protocol.

Table 3a: BERS Thermal Performance Results for Building 1

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
10401	34.4	21.4	19.4	7.5	26.9
10402	34.4	21.4	10.5	8.6	19.1
10403	34.4	21.4	23.2	7.9	31.1
10404	34.4	21.4	19.0	7.8	26.8
10405	34.4	21.4	27.0	10.7	37.7
10406	34.4	21.4	25.4	10.2	35.6
10407	34.4	21.4	15.9	15.4	31.3
10408	34.4	21.4	15.6	5.1	20.7
10409	34.4	21.4	15.4	5.0	20.4
10410	34.4	21.4	26.8	8.6	35.4
10411	34.4	21.4	25.9	11.5	37.4
10412	34.4	21.4	25.2	10.8	36.0
10413	34.4	21.4	28.1	9.8	37.9
10414	34.4	21.4	23.9	7.5	31.4
10415	34.4	21.4	13.8	9.8	23.6
10501	34.4	21.4	20.2	7.7	27.9
10502	34.4	21.4	11.0	8.4	19.4
10503	34.4	21.4	24.0	7.9	31.9
10504	34.4	21.4	19.5	7.7	27.2
10505	34.4	21.4	15.0	15.4	30.4
10506	34.4	21.4	26.1	10.0	36.1
10507	34.4	21.4	16.7	15.1	31.8
10508	34.4	21.4	14.9	5.3	20.2
10509	34.4	21.4	14.9	4.9	19.8
10510	34.4	21.4	25.3	8.7	34.0
10511	34.4	21.4	26.7	11.2	37.9
10512	34.4	21.4	26.0	10.7	36.7
10513	34.4	21.4	15.3	11.8	27.1
10514	34.4	21.4	23.8	7.6	31.4
10515	34.4	21.4	14.4	9.7	24.1
10601	34.4	21.4	20.8	7.8	28.6
10602	34.4	21.4	11.4	8.3	19.7

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
10603	34.4	21.4	24.5	8.0	32.5
10604	34.4	21.4	20.1	7.7	27.8
10605	34.4	21.4	15.4	15.0	30.4
10606	34.4	21.4	26.7	9.9	36.6
10607	34.4	21.4	17.3	15.0	32.3
10608	34.4	21.4	14.7	5.2	19.9
10609	34.4	21.4	14.6	5.0	19.6
10610	34.4	21.4	24.5	8.7	33.2
10611	34.4	21.4	16.2	16.5	32.7
10612	34.4	21.4	26.6	10.7	37.3
10613	34.4	21.4	15.6	11.9	27.5
10614	34.4	21.4	20.9	7.4	28.3
10615	34.4	21.4	14.8	9.7	24.5
10701	34.4	21.4	21.4	7.6	29.0
10702	34.4	21.4	11.8	8.5	20.3
10703	34.4	21.4	25.1	7.6	32.7
10704	34.4	21.4	20.6	7.7	28.3
10705	34.4	21.4	15.8	14.9	30.7
10706	34.4	21.4	27.2	9.7	36.9
10707	34.4	21.4	17.9	14.8	32.7
10708	34.4	21.4	14.8	5.2	20.0
10709	34.4	21.4	14.9	5.0	19.9
10710	34.4	21.4	24.8	8.9	33.7
10711	34.4	21.4	16.6	16.1	32.7
10712	34.4	21.4	12.5	13.8	26.3
10713	34.4	21.4	16.0	11.7	27.7
10714	34.4	21.4	20.9	7.2	28.1
10715	34.4	21.4	15.3	9.6	24.9
10801	34.4	21.4	22.0	7.6	29.6
10802	34.4	21.4	12.2	9.0	21.2
10803	34.4	21.4	25.7	7.8	33.5
10804	34.4	21.4	21.1	7.6	28.7
10805	34.4	21.4	16.2	14.7	30.9
10806	34.4	21.4	27.8	9.7	37.5

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
10807	34.4	21.4	18.5	14.7	33.2
10808	34.4	21.4	15.1	5.2	20.3
10809	34.4	21.4	15.2	5.0	20.2
10810	34.4	21.4	25.1	8.8	33.9
10811	34.4	21.4	17.0	16.2	33.2
10812	34.4	21.4	12.9	13.9	26.8
10813	34.4	21.4	16.3	11.8	28.1
10814	34.4	21.4	21.1	7.3	28.4
10815	34.4	21.4	15.7	9.5	25.2
10901	34.4	21.4	22.3	7.8	30.1
10902	34.4	21.4	12.5	8.8	21.3
10903	34.4	21.4	26.0	7.8	33.8
10904	34.4	21.4	21.5	7.7	29.2
10905	34.4	21.4	16.4	14.7	31.1
10906	34.4	21.4	28.2	9.6	37.8
10907	34.4	21.4	19.0	14.6	33.6
10908	34.4	21.4	15.3	5.2	20.5
10909	34.4	21.4	15.4	5.0	20.4
10910	34.4	21.4	25.4	9.2	34.6
10911	34.4	21.4	17.2	16.2	33.4
10912	34.4	21.4	13.1	13.8	26.9
10913	34.4	21.4	16.5	11.9	28.4
10914	34.4	21.4	21.3	7.2	28.5
10915	34.4	21.4	16.0	9.4	25.4
11001	34.4	21.4	22.7	7.8	30.5
11002	34.4	21.4	12.8	8.8	21.6
11003	34.4	21.4	26.4	7.6	34.0
11004	34.4	21.4	21.8	7.6	29.4
11005	34.4	21.4	16.7	14.7	31.4
11006	34.4	21.4	28.5	9.3	37.8
11007	34.4	21.4	19.4	14.7	34.1
11008	34.4	21.4	15.5	5.2	20.7
11009	34.4	21.4	15.6	4.9	20.5
11010	34.4	21.4	25.8	9.2	35.0

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
11011	34.4	21.4	17.5	16.0	33.5
11012	34.4	21.4	13.3	13.9	27.2
11013	34.4	21.4	16.7	11.9	28.6
11014	34.4	21.4	21.6	7.1	28.7
11015	34.4	21.4	16.3	9.4	25.7
11101	34.4	21.4	23.1	7.3	30.4
11102	34.4	21.4	13.1	8.8	21.9
11103	34.4	21.4	26.8	7.4	34.2
11104	34.4	21.4	22.2	7.7	29.9
11105	34.4	21.4	16.9	14.8	31.7
11106	34.4	21.4	15.8	13.1	28.9
11107	34.4	21.4	19.8	14.8	34.6
11108	34.4	21.4	15.8	5.3	21.1
11109	34.4	21.4	15.9	5.1	21.0
11110	34.4	21.4	26.2	9.2	35.4
11111	34.4	21.4	17.7	16.0	33.7
11112	34.4	21.4	13.5	14.0	27.5
11113	34.4	21.4	16.8	11.8	28.6
11114	34.4	21.4	21.9	7.2	29.1
11115	34.4	21.4	16.6	9.4	26.0
11201	34.4	21.4	23.5	7.3	30.8
11202	34.4	21.4	13.3	8.8	22.1
11203	34.4	21.4	27.2	7.3	34.5
11204	34.4	21.4	22.5	7.5	30.0
11205	34.4	21.4	17.2	14.9	32.1
11206	34.4	21.4	16.0	13.1	29.1
11207	34.4	21.4	20.2	15.3	35.5
11208	34.4	21.4	16.2	5.4	21.6
11209	34.4	21.4	16.1	4.7	20.8
11210	34.4	21.4	26.6	9.4	36.0
11211	34.4	21.4	18.0	15.8	33.8
11212	34.4	21.4	13.7	14.1	27.8
11213	34.4	21.4	16.9	11.9	28.8
11214	34.4	21.4	22.2	7.3	29.5

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
11215	34.4	21.4	17.0	9.4	26.4
11301	34.4	21.4	21.8	8.3	30.1
11302	34.4	21.4	13.6	8.8	22.4
11303	34.4	21.4	27.5	7.1	34.6
11304	34.4	21.4	22.9	7.5	30.4
11305	34.4	21.4	17.4	14.5	31.9
11306	34.4	21.4	16.2	13.1	29.3
11307	34.4	21.4	17.9	14.9	32.8
11308	34.4	21.4	15.3	5.6	20.9
11309	34.4	21.4	15.2	5.3	20.5
11310	34.4	21.4	22.6	9.3	31.9
11311	34.4	21.4	18.2	15.7	33.9
11312	34.4	21.4	13.9	13.8	27.7
11313	34.4	21.4	16.9	12.3	29.2
11314	34.4	21.4	22.4	7.3	29.7
11315	34.4	21.4	16.6	9.3	25.9
11401	34.4	21.4	22.0	8.3	30.3
11402	34.4	21.4	13.8	8.6	22.4
11403	34.4	21.4	27.6	6.8	34.4
11404	34.4	21.4	23.0	7.5	30.5
11405	34.4	21.4	17.5	14.4	31.9
11406	34.4	21.4	16.4	13.1	29.5
11407	34.4	21.4	18.0	14.8	32.8
11408	34.4	21.4	15.2	5.5	20.7
11409	34.4	21.4	15.0	5.3	20.3
11410	34.4	21.4	22.7	9.3	32.0
11411	34.4	21.4	18.4	15.5	33.9
11412	34.4	21.4	14.0	13.9	27.9
11413	34.4	21.4	16.8	13.1	29.9
11414	34.4	21.4	22.5	7.2	29.7
11415	34.4	21.4	16.7	9.1	25.8
11501	34.4	21.4	22.4	8.5	30.9
11502	34.4	21.4	14.1	8.9	23.0
11503	34.4	21.4	28.0	6.8	34.8

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
11504	34.4	21.4	23.3	7.7	31.0
11505	34.4	21.4	17.8	14.3	32.1
11506	34.4	21.4	16.6	13.0	29.6
11507	34.4	21.4	18.2	14.6	32.8
11508	34.4	21.4	15.4	5.3	20.7
11509	34.4	21.4	15.5	5.4	20.9
11510	34.4	21.4	22.9	9.7	32.6
11511	34.4	21.4	18.6	15.2	33.8
11512	34.4	21.4	14.3	13.7	28.0
11513	34.4	21.4	16.7	13.6	30.3
11514	34.4	21.4	22.6	7.4	30.0
11515	34.4	21.4	17.0	9.1	26.1
11601	34.4	21.4	22.6	8.7	31.3
11602	34.4	21.4	14.2	8.7	22.9
11603	34.4	21.4	28.1	6.8	34.9
11604	34.4	21.4	23.3	7.9	31.2
11605	34.4	21.4	17.9	14.4	32.3
11606	34.4	21.4	16.7	13.2	29.9
11607	34.4	21.4	18.3	14.5	32.8
11608	34.4	21.4	15.5	5.4	20.9
11609	34.4	21.4	15.5	5.2	20.7
11610	34.4	21.4	22.4	10.5	32.9
11611	34.4	21.4	18.7	15.2	33.9
11612	34.4	21.4	14.4	13.7	28.1
11613	34.4	21.4	16.5	14.0	30.5
11614	34.4	21.4	22.6	7.5	30.1
11615	34.4	21.4	17.1	9.1	26.2
11701	34.4	21.4	9.7	9.8	19.5
11702	34.4	21.4	5.4	11.1	16.5
11703	34.4	21.4	15.0	10.4	25.4
11704	34.4	21.4	11.7	11.1	22.8
11705	34.4	21.4	18.1	14.3	32.4
11706	34.4	21.4	17.0	12.7	29.7
11707	34.4	21.4	10.3	17.4	27.7

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
11708	34.4	21.4	11.8	6.0	17.8
11709	34.4	21.4	11.6	5.9	17.5
11710	34.4	21.4	9.8	11.4	21.2
11711	34.4	21.4	19.0	14.9	33.9
11712	34.4	21.4	14.6	14.0	28.6
11713	34.4	21.4	16.2	14.6	30.8
11714	34.4	21.4	10.2	10.5	20.7
11715	34.4	21.4	7.5	12.8	20.3
11801	34.4	21.4	14.6	8.1	22.7
11802	34.4	21.4	7.8	9.8	17.6
11803	34.4	21.4	21.2	9.5	30.7
11804	34.4	21.4	12.5	9.2	21.7
11805	34.4	21.4	23.4	10.7	34.1
11806	34.4	21.4	25.7	11.9	37.6
11811	34.4	21.4	28.0	8.9	36.9
11812	34.4	21.4	20.8	12.3	33.1
11813	34.4	21.4	22.4	12.7	35.1
11814	34.4	21.4	15.2	9.1	24.3
11815	34.4	21.4	9.8	10.5	20.3

Table 3b: BERS Thermal Performance Results for Building 2

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
20401	34.4	21.4	26.6	11.2	37.8
20402	34.4	21.4	17.4	6.5	23.9
20403	34.4	21.4	23.7	6.8	30.5
20404	34.4	21.4	22.2	5.8	28.0
20405	34.4	21.4	16.1	8.8	24.9
20406	34.4	21.4	9.2	12.0	21.2
20407	34.4	21.4	29.5	7.9	37.4
20408	34.4	21.4	28.1	9.6	37.7
20501	34.4	21.4	15.8	15.9	31.7
20502	34.4	21.4	17.9	6.5	24.4
20503	34.4	21.4	24.2	6.8	31.0
20504	34.4	21.4	20.7	6.0	26.7
20505	34.4	21.4	13.3	8.9	22.2
20506	34.4	21.4	9.7	11.7	21.4
20507	34.4	21.4	30.4	7.6	38.0
20508	34.4	21.4	18.4	13.0	31.4
20601	34.4	21.4	16.2	15.9	32.1
20602	34.4	21.4	18.3	6.5	24.8
20603	34.4	21.4	22.2	7.0	29.2
20604	34.4	21.4	13.1	5.9	19.0
20605	34.4	21.4	6.9	8.9	15.8
20606	34.4	21.4	10.1	11.5	21.6
20607	34.4	21.4	18.5	10.1	28.6
20608	34.4	21.4	18.8	13.0	31.8
20701	34.4	21.4	16.6	15.6	32.2
20702	34.4	21.4	18.8	6.5	25.3
20703	34.4	21.4	17.9	7.1	25.0
20704	34.4	21.4	8.9	5.8	14.7
20705	34.4	21.4	6.1	9.0	15.1
20706	34.4	21.4	10.5	11.3	21.8
20707	34.4	21.4	19.0	9.9	28.9
20708	34.4	21.4	19.2	13.0	32.2

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
20801	34.4	21.4	16.9	15.5	32.4
20802	34.4	21.4	19.2	6.5	25.7
20803	34.4	21.4	15.9	7.3	23.2
20804	34.4	21.4	7.6	5.8	13.4
20805	34.4	21.4	6.1	9.1	15.2
20806	34.4	21.4	10.8	11.1	21.9
20807	34.4	21.4	19.4	9.6	29.0
20808	34.4	21.4	19.5	12.7	32.2
20901	34.4	21.4	17.1	15.2	32.3
20902	34.4	21.4	19.4	6.5	25.9
20903	34.4	21.4	15.9	7.3	23.2
20904	34.4	21.4	7.6	5.9	13.5
20905	34.4	21.4	6.2	9.0	15.2
20906	34.4	21.4	11.1	10.9	22.0
20907	34.4	21.4	19.7	9.6	29.3
20908	34.4	21.4	19.8	12.7	32.5
21001	34.4	21.4	17.4	15.4	32.8
21002	34.4	21.4	19.7	6.5	26.2
21003	34.4	21.4	16.2	7.8	24.0
21004	34.4	21.4	7.8	6.0	13.8
21005	34.4	21.4	6.3	9.2	15.5
21006	34.4	21.4	11.3	10.6	21.9
21007	34.4	21.4	20.0	10.1	30.1
21008	34.4	21.4	20.0	12.5	32.5
21101	34.4	21.4	17.6	15.1	32.7
21102	34.4	21.4	19.9	6.4	26.3
21103	34.4	21.4	16.5	7.7	24.2
21104	34.4	21.4	8.1	5.6	13.7
21105	34.4	21.4	6.4	9.2	15.6
21106	34.4	21.4	11.6	10.6	22.2
21107	34.4	21.4	20.3	10.0	30.3
21108	34.4	21.4	20.3	12.3	32.6
21201	34.4	21.4	17.9	15.5	33.4
21202	34.4	21.4	20.1	6.4	26.5

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
21203	34.4	21.4	16.7	7.7	24.4
21204	34.4	21.4	8.3	5.9	14.2
21205	34.4	21.4	6.5	9.2	15.7
21206	34.4	21.4	11.8	10.6	22.4
21207	34.4	21.4	20.6	9.7	30.3
21208	34.4	21.4	20.5	12.3	32.8
21301	34.4	21.4	18.0	15.3	33.3
21302	34.4	21.4	20.3	6.3	26.6
21303	34.4	21.4	16.9	7.8	24.7
21304	34.4	21.4	8.5	5.8	14.3
21305	34.4	21.4	6.7	9.2	15.9
21306	34.4	21.4	12.1	10.4	22.5
21307	34.4	21.4	20.9	9.8	30.7
21308	34.4	21.4	20.7	12.3	33.0
21401	34.4	21.4	18.1	15.2	33.3
21402	34.4	21.4	20.2	6.4	26.6
21403	34.4	21.4	16.6	7.9	24.5
21404	34.4	21.4	8.6	5.7	14.3
21405	34.4	21.4	6.7	9.2	15.9
21406	34.4	21.4	12.3	10.7	23.0
21407	34.4	21.4	21.0	9.6	30.6
21408	34.4	21.4	20.8	12.2	33.0
21501	34.4	21.4	18.4	15.1	33.5
21502	34.4	21.4	20.1	6.3	26.4
21503	34.4	21.4	16.7	8.0	24.7
21504	34.4	21.4	8.8	5.5	14.3
21505	34.4	21.4	6.9	9.1	16.0
21506	34.4	21.4	12.5	10.6	23.1
21507	34.4	21.4	21.3	9.9	31.2
21508	34.4	21.4	21.1	12.1	33.2
21601	34.4	21.4	18.5	15.2	33.7
21602	34.4	21.4	19.7	6.4	26.1
21603	34.4	21.4	16.6	8.4	25.0
21604	34.4	21.4	8.9	5.8	14.7

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
21605	34.4	21.4	7.0	8.9	15.9
21606	34.4	21.4	12.6	10.5	23.1
21607	34.4	21.4	21.5	9.9	31.4
21608	34.4	21.4	21.2	12.1	33.3
21701	34.4	21.4	25.3	12.7	38.0
21702	34.4	21.4	29.2	6.0	35.2
21703	34.4	21.4	23.6	7.3	30.9
21704	34.4	21.4	15.2	5.1	20.3
21705	34.4	21.4	11.0	7.6	18.6
21706	34.4	21.4	18.8	9.2	28.0
21707	34.4	21.4	29.7	7.9	37.6
21708	34.4	21.4	28.4	9.3	37.7

Table 3c: BERS Thermal Performance Results for Building 3

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
30001	34.4	21.4	25.4	11.8	37.2
30002	34.4	21.4	27.3	10.7	38.0
30003	34.4	21.4	25.0	12.3	37.3
30004	34.4	21.4	22.2	12.6	34.8
30005	34.4	21.4	20.7	13.7	34.4
30201	34.4	21.4	7.9	20.4	28.3
30202	34.4	21.4	10.3	21.1	31.4
30203	34.4	21.4	9.6	20.4	30.0
30204	34.4	21.4	7.8	20.0	27.8
30205	34.4	21.4	21.6	14.9	36.5
30301	34.4	21.4	7.5	19.4	26.9
30302	34.4	21.4	11.2	18.8	30.0
30303	34.4	21.4	10.0	19.5	29.5
30304	34.4	21.4	8.3	19.2	27.5
30305	34.4	21.4	22.2	13.1	35.3
30401	34.4	21.4	26.5	10.8	37.3
30402	34.4	21.4	12.7	8.6	21.3
30403	34.4	21.4	20.0	7.6	27.6
30404	34.4	21.4	24.4	13.6	38.0
30405	34.4	21.4	19.1	18.1	37.2
30406	34.4	21.4	11.9	7.5	19.4
30407	34.4	21.4	13.2	7.2	20.4
30408	34.4	21.4	23.0	14.0	37.0
30409	34.4	21.4	25.4	12.5	37.9
30410	34.4	21.4	26.8	7.6	34.4
30411	34.4	21.4	23.6	8.8	32.4
30412	34.4	21.4	28.4	8.4	36.8
30501	34.4	21.4	26.3	11.1	37.4
30502	34.4	21.4	17.2	9.1	26.3
30503	34.4	21.4	22.6	6.4	29.0
30504	34.4	21.4	27.1	10.2	37.3
30505	34.4	21.4	16.3	11.9	28.2

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
30506	34.4	21.4	11.7	7.4	19.1
30507	34.4	21.4	12.0	7.7	19.7
30508	34.4	21.4	20.5	10.8	31.3
30509	34.4	21.4	26.5	10.5	37.0
30510	34.4	21.4	19.5	6.1	25.6
30511	34.4	21.4	21.9	6.3	28.2
30512	34.4	21.4	26.8	7.4	34.2
30601	34.4	21.4	26.1	10.8	36.9
30602	34.4	21.4	17.5	9.2	26.7
30603	34.4	21.4	22.1	6.5	28.6
30604	34.4	21.4	27.2	9.8	37.0
30605	34.4	21.4	16.5	11.9	28.4
30606	34.4	21.4	12.2	7.2	19.4
30607	34.4	21.4	10.9	8.0	18.9
30608	34.4	21.4	20.6	10.7	31.3
30609	34.4	21.4	26.6	10.2	36.8
30610	34.4	21.4	19.3	6.3	25.6
30611	34.4	21.4	21.6	6.3	27.9
30612	34.4	21.4	26.9	7.2	34.1
30701	34.4	21.4	26.7	10.7	37.4
30702	34.4	21.4	18.0	9.3	27.3
30703	34.4	21.4	22.6	6.2	28.8
30704	34.4	21.4	27.8	9.7	37.5
30705	34.4	21.4	16.9	12.0	28.9
30706	34.4	21.4	12.6	6.8	19.4
30707	34.4	21.4	11.4	7.8	19.2
30708	34.4	21.4	21.2	10.9	32.1
30709	34.4	21.4	27.2	10.1	37.3
30710	34.4	21.4	19.8	6.3	26.1
30711	34.4	21.4	22.1	6.3	28.4
30712	34.4	21.4	27.5	7.2	34.7
30801	34.4	21.4	27.2	10.7	37.9
30802	34.4	21.4	18.5	9.1	27.6
30803	34.4	21.4	23.2	6.2	29.4

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
30804	34.4	21.4	14.8	13.9	28.7
30805	34.4	21.4	17.3	11.9	29.2
30806	34.4	21.4	13.1	6.7	19.8
30807	34.4	21.4	11.8	7.7	19.5
30808	34.4	21.4	21.7	10.8	32.5
30809	34.4	21.4	27.7	10.3	38.0
30810	34.4	21.4	20.3	6.5	26.8
30811	34.4	21.4	22.6	6.1	28.7
30812	34.4	21.4	28.0	7.3	35.3
30901	34.4	21.4	27.6	10.4	38.0
30902	34.4	21.4	18.8	9.1	27.9
30903	34.4	21.4	23.5	6.1	29.6
30904	34.4	21.4	15.1	13.7	28.8
30905	34.4	21.4	17.7	12.1	29.8
30906	34.4	21.4	13.4	6.7	20.1
30907	34.4	21.4	12.1	7.8	19.9
30908	34.4	21.4	22.0	10.7	32.7
30909	34.4	21.4	15.0	13.5	28.5
30910	34.4	21.4	20.7	6.5	27.2
30911	34.4	21.4	22.9	6.2	29.1
30912	34.4	21.4	28.4	7.4	35.8
31001	34.4	21.4	15.8	13.8	29.6
31002	34.4	21.4	19.1	9.0	28.1
31003	34.4	21.4	23.9	6.2	30.1
31004	34.4	21.4	15.3	13.2	28.5
31005	34.4	21.4	17.9	12.0	29.9
31006	34.4	21.4	13.7	6.8	20.5
31007	34.4	21.4	12.4	7.8	20.2
31008	34.4	21.4	22.4	10.4	32.8
31009	34.4	21.4	15.2	13.8	29.0
31010	34.4	21.4	21.0	6.5	27.5
31011	34.4	21.4	23.3	6.2	29.5
31012	34.4	21.4	28.8	7.1	35.9
31101	34.4	21.4	16.0	14.0	30.0

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
31102	34.4	21.4	19.5	8.9	28.4
31103	34.4	21.4	24.2	6.5	30.7
31104	34.4	21.4	15.6	12.9	28.5
31105	34.4	21.4	18.2	12.0	30.2
31106	34.4	21.4	14.0	6.7	20.7
31107	34.4	21.4	12.7	7.6	20.3
31108	34.4	21.4	22.8	10.4	33.2
31109	34.4	21.4	15.5	13.9	29.4
31110	34.4	21.4	21.4	6.7	28.1
31111	34.4	21.4	23.6	6.0	29.6
31112	34.4	21.4	29.2	7.1	36.3
31201	34.4	21.4	16.3	13.7	30.0
31202	34.4	21.4	19.8	9.1	28.9
31203	34.4	21.4	24.6	6.3	30.9
31204	34.4	21.4	15.7	12.9	28.6
31205	34.4	21.4	18.6	11.9	30.5
31206	34.4	21.4	14.3	6.6	20.9
31207	34.4	21.4	13.0	7.7	20.7
31208	34.4	21.4	23.2	10.3	33.5
31209	34.4	21.4	15.7	13.9	29.6
31210	34.4	21.4	21.7	6.4	28.1
31211	34.4	21.4	23.9	6.1	30.0
31212	34.4	21.4	29.4	7.0	36.4
31301	34.4	21.4	16.6	13.8	30.4
31302	34.4	21.4	20.2	8.9	29.1
31303	34.4	21.4	24.9	6.2	31.1
31304	34.4	21.4	16.0	12.6	28.6
31305	34.4	21.4	18.9	12.0	30.9
31306	34.4	21.4	14.6	6.6	21.2
31307	34.4	21.4	13.3	7.5	20.8
31308	34.4	21.4	23.5	10.3	33.8
31309	34.4	21.4	16.0	13.7	29.7
31310	34.4	21.4	22.0	6.5	28.5
31311	34.4	21.4	24.2	6.2	30.4

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
31312	34.4	21.4	29.9	7.4	37.3
31401	34.4	21.4	16.7	13.7	30.4
31402	34.4	21.4	20.3	8.9	29.2
31403	34.4	21.4	25.1	6.2	31.3
31404	34.4	21.4	16.1	12.6	28.7
31405	34.4	21.4	19.1	11.8	30.9
31406	34.4	21.4	14.7	6.9	21.6
31407	34.4	21.4	13.4	7.4	20.8
31408	34.4	21.4	23.7	10.3	34.0
31409	34.4	21.4	16.1	13.4	29.5
31410	34.4	21.4	22.1	6.6	28.7
31411	34.4	21.4	24.3	6.3	30.6
31412	34.4	21.4	30.1	7.5	37.6
31501	34.4	21.4	17.0	13.7	30.7
31502	34.4	21.4	9.2	11.5	20.7
31503	34.4	21.4	13.0	8.0	21.0
31504	34.4	21.4	16.4	12.6	29.0
31505	34.4	21.4	11.3	15.9	27.2
31506	34.4	21.4	5.4	9.4	14.8
31507	34.4	21.4	5.3	10.3	15.6
31508	34.4	21.4	11.6	14.7	26.3
31509	34.4	21.4	16.1	13.2	29.3
31510	34.4	21.4	12.6	8.0	20.6
31511	34.4	21.4	13.3	7.6	20.9
31512	34.4	21.4	16.9	9.3	26.2
31601	34.4	21.4	17.1	13.5	30.6
31602	34.4	21.4	9.3	11.4	20.7
31603	34.4	21.4	13.1	8.1	21.2
31604	34.4	21.4	16.5	12.4	28.9
31605	34.4	21.4	11.4	15.2	26.6
31606	34.4	21.4	5.4	9.4	14.8
31607	34.4	21.4	5.4	10.2	15.6
31608	34.4	21.4	11.7	14.5	26.2
31609	34.4	21.4	16.3	13.1	29.4

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
31610	34.4	21.4	12.7	7.7	20.4
31611	34.4	21.4	13.4	7.9	21.3
31612	34.4	21.4	17.0	9.4	26.4
31701	34.4	21.4	17.4	13.4	30.8
31702	34.4	21.4	9.5	11.4	20.9
31703	34.4	21.4	13.3	8.1	21.4
31704	34.4	21.4	16.8	12.4	29.2
31705	34.4	21.4	11.6	15.4	27.0
31706	34.4	21.4	12.4	8.2	20.6
31707	34.4	21.4	12.2	8.2	20.4
31708	34.4	21.4	17.5	12.4	29.9
31709	34.4	21.4	22.5	11.5	34.0
31710	34.4	21.4	18.7	6.9	25.6
31711	34.4	21.4	21.7	6.8	28.5
31712	34.4	21.4	25.7	7.5	33.2
31801	34.4	21.4	26.2	11.4	37.6
31802	34.4	21.4	12.5	9.5	22.0
31803	34.4	21.4	19.0	7.5	26.5
31804	34.4	21.4	23.5	10.5	34.0
31805	34.4	21.4	26.4	11.5	37.9

Table 3d: BERS Thermal Performance Results for Building 4

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
40401	34.4	21.4	20.0	10.0	30.0
40402	34.4	21.4	20.0	10.0	30.0
40403	34.4	21.4	20.0	10.0	30.0
40404	34.4	21.4	20.0	10.0	30.0
40405	34.4	21.4	20.0	10.0	30.0
40410	34.4	21.4	20.0	10.0	30.0
40411	34.4	21.4	20.0	10.0	30.0
40412	34.4	21.4	20.0	10.0	30.0
40413	34.4	21.4	20.0	10.0	30.0
40414	34.4	21.4	20.0	10.0	30.0
40415	34.4	21.4	20.0	10.0	30.0
40416	34.4	21.4	20.0	10.0	30.0
40418	34.4	21.4	20.0	10.0	30.0
40419	34.4	21.4	20.0	10.0	30.0
40420	34.4	21.4	20.0	10.0	30.0
40421	34.4	21.4	20.0	10.0	30.0
40422	34.4	21.4	20.0	10.0	30.0
40423	34.4	21.4	20.0	10.0	30.0
40426	34.4	21.4	20.0	10.0	30.0
40427	34.4	21.4	20.0	10.0	30.0
40428	34.4	21.4	20.0	10.0	30.0
40429	34.4	21.4	20.0	10.0	30.0
40430	34.4	21.4	20.0	10.0	30.0
40431	34.4	21.4	20.0	10.0	30.0
40501	34.4	21.4	20.0	10.0	30.0
40502	34.4	21.4	20.0	10.0	30.0
40503	34.4	21.4	20.0	10.0	30.0
40504	34.4	21.4	20.0	10.0	30.0
40505	34.4	21.4	20.0	10.0	30.0
40506	34.4	21.4	20.0	10.0	30.0
40507	34.4	21.4	20.0	10.0	30.0
40508	34.4	21.4	20.0	10.0	30.0

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
40509	34.4	21.4	20.0	10.0	30.0
40510	34.4	21.4	20.0	10.0	30.0
40511	34.4	21.4	20.0	10.0	30.0
40512	34.4	21.4	20.0	10.0	30.0
40513	34.4	21.4	20.0	10.0	30.0
40514	34.4	21.4	20.0	10.0	30.0
40515	34.4	21.4	20.0	10.0	30.0
40516	34.4	21.4	20.0	10.0	30.0
40517	34.4	21.4	20.0	10.0	30.0
40518	34.4	21.4	20.0	10.0	30.0
40519	34.4	21.4	20.0	10.0	30.0
40520	34.4	21.4	20.0	10.0	30.0
40521	34.4	21.4	20.0	10.0	30.0
40522	34.4	21.4	20.0	10.0	30.0
40523	34.4	21.4	20.0	10.0	30.0
40524	34.4	21.4	20.0	10.0	30.0
40525	34.4	21.4	20.0	10.0	30.0
40526	34.4	21.4	20.0	10.0	30.0
40527	34.4	21.4	20.0	10.0	30.0
40528	34.4	21.4	20.0	10.0	30.0
40529	34.4	21.4	20.0	10.0	30.0
40530	34.4	21.4	20.0	10.0	30.0
40531	34.4	21.4	20.0	10.0	30.0
40601	34.4	21.4	20.0	10.0	30.0
40602	34.4	21.4	20.0	10.0	30.0
40603	34.4	21.4	20.0	10.0	30.0
40604	34.4	21.4	20.0	10.0	30.0
40605	34.4	21.4	20.0	10.0	30.0
40606	34.4	21.4	20.0	10.0	30.0
40607	34.4	21.4	20.0	10.0	30.0
40608	34.4	21.4	20.0	10.0	30.0
40609	34.4	21.4	20.0	10.0	30.0
40610	34.4	21.4	20.0	10.0	30.0
40611	34.4	21.4	20.0	10.0	30.0

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
40612	34.4	21.4	20.0	10.0	30.0
40613	34.4	21.4	20.0	10.0	30.0
40614	34.4	21.4	20.0	10.0	30.0
40615	34.4	21.4	20.0	10.0	30.0
40616	34.4	21.4	20.0	10.0	30.0
40617	34.4	21.4	20.0	10.0	30.0
40618	34.4	21.4	20.0	10.0	30.0
40619	34.4	21.4	20.0	10.0	30.0
40620	34.4	21.4	20.0	10.0	30.0
40621	34.4	21.4	20.0	10.0	30.0
40622	34.4	21.4	20.0	10.0	30.0
40623	34.4	21.4	20.0	10.0	30.0
40624	34.4	21.4	20.0	10.0	30.0
40625	34.4	21.4	20.0	10.0	30.0
40626	34.4	21.4	20.0	10.0	30.0
40627	34.4	21.4	20.0	10.0	30.0
40628	34.4	21.4	20.0	10.0	30.0
40629	34.4	21.4	20.0	10.0	30.0
40630	34.4	21.4	20.0	10.0	30.0
40631	34.4	21.4	20.0	10.0	30.0
40701	34.4	21.4	20.0	10.0	30.0
40702	34.4	21.4	20.0	10.0	30.0
40703	34.4	21.4	20.0	10.0	30.0
40704	34.4	21.4	20.0	10.0	30.0
40705	34.4	21.4	20.0	10.0	30.0
40706	34.4	21.4	20.0	10.0	30.0
40707	34.4	21.4	20.0	10.0	30.0
40708	34.4	21.4	20.0	10.0	30.0
40709	34.4	21.4	20.0	10.0	30.0
40710	34.4	21.4	20.0	10.0	30.0
40711	34.4	21.4	20.0	10.0	30.0
40712	34.4	21.4	20.0	10.0	30.0
40713	34.4	21.4	20.0	10.0	30.0
40714	34.4	21.4	20.0	10.0	30.0

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
40715	34.4	21.4	20.0	10.0	30.0
40716	34.4	21.4	20.0	10.0	30.0
40717	34.4	21.4	20.0	10.0	30.0
40718	34.4	21.4	20.0	10.0	30.0
40719	34.4	21.4	20.0	10.0	30.0
40720	34.4	21.4	20.0	10.0	30.0
40721	34.4	21.4	20.0	10.0	30.0
40722	34.4	21.4	20.0	10.0	30.0
40723	34.4	21.4	20.0	10.0	30.0
40724	34.4	21.4	20.0	10.0	30.0
40725	34.4	21.4	20.0	10.0	30.0
40726	34.4	21.4	20.0	10.0	30.0
40727	34.4	21.4	20.0	10.0	30.0
40728	34.4	21.4	20.0	10.0	30.0
40729	34.4	21.4	20.0	10.0	30.0
40730	34.4	21.4	20.0	10.0	30.0
40731	34.4	21.4	20.0	10.0	30.0
40801	34.4	21.4	20.0	10.0	30.0
40802	34.4	21.4	20.0	10.0	30.0
40803	34.4	21.4	20.0	10.0	30.0
40804	34.4	21.4	20.0	10.0	30.0
40805	34.4	21.4	20.0	10.0	30.0
40806	34.4	21.4	20.0	10.0	30.0
40807	34.4	21.4	20.0	10.0	30.0
40808	34.4	21.4	20.0	10.0	30.0
40809	34.4	21.4	20.0	10.0	30.0
40810	34.4	21.4	20.0	10.0	30.0
40811	34.4	21.4	20.0	10.0	30.0
40812	34.4	21.4	20.0	10.0	30.0
40813	34.4	21.4	20.0	10.0	30.0
40814	34.4	21.4	20.0	10.0	30.0
40815	34.4	21.4	20.0	10.0	30.0
40816	34.4	21.4	20.0	10.0	30.0
40817	34.4	21.4	20.0	10.0	30.0

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
40818	34.4	21.4	20.0	10.0	30.0
40819	34.4	21.4	20.0	10.0	30.0
40820	34.4	21.4	20.0	10.0	30.0
40821	34.4	21.4	20.0	10.0	30.0
40822	34.4	21.4	20.0	10.0	30.0
40823	34.4	21.4	20.0	10.0	30.0
40824	34.4	21.4	20.0	10.0	30.0
40825	34.4	21.4	20.0	10.0	30.0
40826	34.4	21.4	20.0	10.0	30.0
40827	34.4	21.4	20.0	10.0	30.0
40828	34.4	21.4	20.0	10.0	30.0
40829	34.4	21.4	20.0	10.0	30.0
40830	34.4	21.4	20.0	10.0	30.0
40831	34.4	21.4	20.0	10.0	30.0
40901	34.4	21.4	20.0	10.0	30.0
40902	34.4	21.4	20.0	10.0	30.0
40903	34.4	21.4	20.0	10.0	30.0
40904	34.4	21.4	20.0	10.0	30.0
40905	34.4	21.4	20.0	10.0	30.0
40906	34.4	21.4	20.0	10.0	30.0
40907	34.4	21.4	20.0	10.0	30.0
40908	34.4	21.4	20.0	10.0	30.0
40909	34.4	21.4	20.0	10.0	30.0
40910	34.4	21.4	20.0	10.0	30.0
40911	34.4	21.4	20.0	10.0	30.0
40912	34.4	21.4	20.0	10.0	30.0
40913	34.4	21.4	20.0	10.0	30.0
40914	34.4	21.4	20.0	10.0	30.0
40915	34.4	21.4	20.0	10.0	30.0
40916	34.4	21.4	20.0	10.0	30.0
40917	34.4	21.4	20.0	10.0	30.0
40918	34.4	21.4	20.0	10.0	30.0
40919	34.4	21.4	20.0	10.0	30.0
40920	34.4	21.4	20.0	10.0	30.0

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
40921	34.4	21.4	20.0	10.0	30.0
40922	34.4	21.4	20.0	10.0	30.0
40923	34.4	21.4	20.0	10.0	30.0
40924	34.4	21.4	20.0	10.0	30.0
40925	34.4	21.4	20.0	10.0	30.0
40926	34.4	21.4	20.0	10.0	30.0
40927	34.4	21.4	20.0	10.0	30.0
40928	34.4	21.4	20.0	10.0	30.0
40929	34.4	21.4	20.0	10.0	30.0
40930	34.4	21.4	20.0	10.0	30.0
40931	34.4	21.4	20.0	10.0	30.0
41001	34.4	21.4	20.0	10.0	30.0
41002	34.4	21.4	20.0	10.0	30.0
41003	34.4	21.4	20.0	10.0	30.0
41004	34.4	21.4	20.0	10.0	30.0
41005	34.4	21.4	20.0	10.0	30.0
41006	34.4	21.4	20.0	10.0	30.0
41007	34.4	21.4	20.0	10.0	30.0
41008	34.4	21.4	20.0	10.0	30.0
41009	34.4	21.4	20.0	10.0	30.0
41010	34.4	21.4	20.0	10.0	30.0
41011	34.4	21.4	20.0	10.0	30.0
41012	34.4	21.4	20.0	10.0	30.0
41013	34.4	21.4	20.0	10.0	30.0
41014	34.4	21.4	20.0	10.0	30.0
41015	34.4	21.4	20.0	10.0	30.0
41016	34.4	21.4	20.0	10.0	30.0
41017	34.4	21.4	20.0	10.0	30.0
41018	34.4	21.4	20.0	10.0	30.0
41019	34.4	21.4	20.0	10.0	30.0
41020	34.4	21.4	20.0	10.0	30.0
41021	34.4	21.4	20.0	10.0	30.0
41022	34.4	21.4	20.0	10.0	30.0
41023	34.4	21.4	20.0	10.0	30.0

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
41024	34.4	21.4	20.0	10.0	30.0
41025	34.4	21.4	20.0	10.0	30.0
41026	34.4	21.4	20.0	10.0	30.0
41027	34.4	21.4	20.0	10.0	30.0
41028	34.4	21.4	20.0	10.0	30.0
41029	34.4	21.4	20.0	10.0	30.0
41030	34.4	21.4	20.0	10.0	30.0
41031	34.4	21.4	20.0	10.0	30.0
41101	34.4	21.4	20.0	10.0	30.0
41102	34.4	21.4	20.0	10.0	30.0
41103	34.4	21.4	20.0	10.0	30.0
41104	34.4	21.4	20.0	10.0	30.0
41105	34.4	21.4	20.0	10.0	30.0
41106	34.4	21.4	20.0	10.0	30.0
41107	34.4	21.4	20.0	10.0	30.0
41108	34.4	21.4	20.0	10.0	30.0
41109	34.4	21.4	20.0	10.0	30.0
41110	34.4	21.4	20.0	10.0	30.0
41111	34.4	21.4	20.0	10.0	30.0
41112	34.4	21.4	20.0	10.0	30.0
41113	34.4	21.4	20.0	10.0	30.0
41114	34.4	21.4	20.0	10.0	30.0
41115	34.4	21.4	20.0	10.0	30.0
41116	34.4	21.4	20.0	10.0	30.0
41117	34.4	21.4	20.0	10.0	30.0
41118	34.4	21.4	20.0	10.0	30.0
41119	34.4	21.4	20.0	10.0	30.0
41120	34.4	21.4	20.0	10.0	30.0
41121	34.4	21.4	20.0	10.0	30.0
41122	34.4	21.4	20.0	10.0	30.0
41123	34.4	21.4	20.0	10.0	30.0
41124	34.4	21.4	20.0	10.0	30.0
41125	34.4	21.4	20.0	10.0	30.0
41126	34.4	21.4	20.0	10.0	30.0

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
41127	34.4	21.4	20.0	10.0	30.0
41128	34.4	21.4	20.0	10.0	30.0
41129	34.4	21.4	20.0	10.0	30.0
41130	34.4	21.4	20.0	10.0	30.0
41131	34.4	21.4	20.0	10.0	30.0
41201	34.4	21.4	20.0	10.0	30.0
41202	34.4	21.4	20.0	10.0	30.0
41203	34.4	21.4	20.0	10.0	30.0
41204	34.4	21.4	20.0	10.0	30.0
41205	34.4	21.4	20.0	10.0	30.0
41206	34.4	21.4	20.0	10.0	30.0
41207	34.4	21.4	20.0	10.0	30.0
41208	34.4	21.4	20.0	10.0	30.0
41209	34.4	21.4	20.0	10.0	30.0
41210	34.4	21.4	20.0	10.0	30.0
41211	34.4	21.4	20.0	10.0	30.0
41212	34.4	21.4	20.0	10.0	30.0
41213	34.4	21.4	20.0	10.0	30.0
41214	34.4	21.4	20.0	10.0	30.0
41215	34.4	21.4	20.0	10.0	30.0
41216	34.4	21.4	20.0	10.0	30.0
41217	34.4	21.4	20.0	10.0	30.0
41218	34.4	21.4	20.0	10.0	30.0
41219	34.4	21.4	20.0	10.0	30.0
41220	34.4	21.4	20.0	10.0	30.0
41221	34.4	21.4	20.0	10.0	30.0
41222	34.4	21.4	20.0	10.0	30.0
41223	34.4	21.4	20.0	10.0	30.0
41224	34.4	21.4	20.0	10.0	30.0
41225	34.4	21.4	20.0	10.0	30.0
41226	34.4	21.4	20.0	10.0	30.0
41227	34.4	21.4	20.0	10.0	30.0
41228	34.4	21.4	20.0	10.0	30.0
41229	34.4	21.4	20.0	10.0	30.0

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
41230	34.4	21.4	20.0	10.0	30.0
41231	34.4	21.4	20.0	10.0	30.0
41301	34.4	21.4	20.0	10.0	30.0
41302	34.4	21.4	20.0	10.0	30.0
41303	34.4	21.4	20.0	10.0	30.0
41304	34.4	21.4	20.0	10.0	30.0
41305	34.4	21.4	20.0	10.0	30.0
41306	34.4	21.4	20.0	10.0	30.0
41307	34.4	21.4	20.0	10.0	30.0
41308	34.4	21.4	20.0	10.0	30.0
41309	34.4	21.4	20.0	10.0	30.0
41310	34.4	21.4	20.0	10.0	30.0
41311	34.4	21.4	20.0	10.0	30.0
41312	34.4	21.4	20.0	10.0	30.0
41313	34.4	21.4	20.0	10.0	30.0
41314	34.4	21.4	20.0	10.0	30.0
41315	34.4	21.4	20.0	10.0	30.0
41316	34.4	21.4	20.0	10.0	30.0
41317	34.4	21.4	20.0	10.0	30.0
41318	34.4	21.4	20.0	10.0	30.0
41319	34.4	21.4	20.0	10.0	30.0
41320	34.4	21.4	20.0	10.0	30.0
41321	34.4	21.4	20.0	10.0	30.0
41322	34.4	21.4	20.0	10.0	30.0
41323	34.4	21.4	20.0	10.0	30.0
41324	34.4	21.4	20.0	10.0	30.0
41325	34.4	21.4	20.0	10.0	30.0
41326	34.4	21.4	20.0	10.0	30.0
41327	34.4	21.4	20.0	10.0	30.0
41328	34.4	21.4	20.0	10.0	30.0
41329	34.4	21.4	20.0	10.0	30.0
41330	34.4	21.4	20.0	10.0	30.0
41331	34.4	21.4	20.0	10.0	30.0
41401	34.4	21.4	20.0	10.0	30.0

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
41402	34.4	21.4	20.0	10.0	30.0
41403	34.4	21.4	20.0	10.0	30.0
41404	34.4	21.4	20.0	10.0	30.0
41405	34.4	21.4	20.0	10.0	30.0
41406	34.4	21.4	20.0	10.0	30.0
41407	34.4	21.4	20.0	10.0	30.0
41408	34.4	21.4	20.0	10.0	30.0
41409	34.4	21.4	20.0	10.0	30.0
41410	34.4	21.4	20.0	10.0	30.0
41411	34.4	21.4	20.0	10.0	30.0
41412	34.4	21.4	20.0	10.0	30.0
41413	34.4	21.4	20.0	10.0	30.0
41414	34.4	21.4	20.0	10.0	30.0
41419	34.4	21.4	20.0	10.0	30.0
41420	34.4	21.4	20.0	10.0	30.0
41421	34.4	21.4	20.0	10.0	30.0
41422	34.4	21.4	20.0	10.0	30.0
41423	34.4	21.4	20.0	10.0	30.0
41501	34.4	21.4	20.0	10.0	30.0
41502	34.4	21.4	20.0	10.0	30.0
41503	34.4	21.4	20.0	10.0	30.0
41504	34.4	21.4	20.0	10.0	30.0
41505	34.4	21.4	20.0	10.0	30.0
41506	34.4	21.4	20.0	10.0	30.0
41507	34.4	21.4	20.0	10.0	30.0
41508	34.4	21.4	20.0	10.0	30.0
41509	34.4	21.4	20.0	10.0	30.0
41510	34.4	21.4	20.0	10.0	30.0
41511	34.4	21.4	20.0	10.0	30.0
41512	34.4	21.4	20.0	10.0	30.0
41513	34.4	21.4	20.0	10.0	30.0
41514	34.4	21.4	20.0	10.0	30.0
41515	34.4	21.4	20.0	10.0	30.0
41601	34.4	21.4	20.0	10.0	30.0

Unit Number	BASIX Requirements (MJ/m2/year)		Final Results (MJ/m2/year) (with treatments)		
	Heating	Cooling	Heating	Cooling	Total
41602	34.4	21.4	20.0	10.0	30.0
41603	34.4	21.4	20.0	10.0	30.0
41604	34.4	21.4	20.0	10.0	30.0
41605	34.4	21.4	20.0	10.0	30.0
41606	34.4	21.4	20.0	10.0	30.0
41607	34.4	21.4	20.0	10.0	30.0
41608	34.4	21.4	20.0	10.0	30.0
41609	34.4	21.4	20.0	10.0	30.0
41610	34.4	21.4	20.0	10.0	30.0
41611	34.4	21.4	20.0	10.0	30.0
41612	34.4	21.4	20.0	10.0	30.0
41613	34.4	21.4	20.0	10.0	30.0
41614	34.4	21.4	20.0	10.0	30.0
41615	34.4	21.4	20.0	10.0	30.0
41710	34.4	21.4	20.0	10.0	30.0
41711	34.4	21.4	20.0	10.0	30.0
41712	34.4	21.4	20.0	10.0	30.0
41713	34.4	21.4	20.0	10.0	30.0
41714	34.4	21.4	20.0	10.0	30.0
41715	34.4	21.4	20.0	10.0	30.0

3.3 Energy

The minimum target score in BASIX to achieve energy usage compliance is 60%. The minimum score is achieved through the inclusion of the following;

3.3.1 Central Systems

- The central hot water systems are to be gas fired boiler system. All piping (internal and external to ringmain and supply riser) for the hot water systems are to include R1.0 (~38mm) insulation.
- The lift system in the development is to be gearless traction with VVVF motor, with a lift load capacity of between 1001kg and 1500kg.
- A photovoltaic system with a peak kW rated electrical output of 20kW is to be installed across the whole development.
- The outdoor swimming pool in the development will not be heated.
- The outdoor swimming pool pump is to be controlled by timer.

3.3.2 Common Areas

The BASIX requirements for the ventilation and lighting systems within the various common areas are listed in Table 4 and Table 5 below:

Table 4: Ventilation Systems

Common Area	Ventilation System Type	Efficiency Measure
B4-B1 Residential Carpark	Ventilation (supply + exhaust)	Carbon monoxide monitor + VSD fan
GL P Loading Dock	Ventilation (supply + exhaust)	Carbon monoxide monitor + VSD fan
B1 P Comms	Ventilation supply only	Thermostatically controlled
B3 Waste Rooms	Ventilation exhaust only	-
B1 P Bulky Storage	Ventilation exhaust only	-
GL P Resi Bin Holding	Ventilation exhaust only	-
L17 4 BTR Amenity	Air-conditioning system	Time Clocks or BMS controlled
B4-B1 P Fan rooms	Ventilation exhaust only	Interlocked to light
B2 P Fire control room	Ventilation exhaust only	Interlocked to light
B2 P Fire pump room	Ventilation exhaust only	Interlocked to light
B2 P Car wash plant (resi)	Ventilation exhaust only	Interlocked to light
B2-B1 P Services Rooms	Ventilation exhaust only	Interlocked to light
B2 P Sub Stations	No mechanical ventilation	-
B1 P CW + RW filtration + oil separation	Ventilation exhaust only	Interlocked to light
B1 P MSB Rooms	Ventilation exhaust only	Interlocked to light
B1 P Battery Room	Ventilation supply only	Interlocked to light
B1 P Water Pump Control Room	Ventilation exhaust only	Interlocked to light
GL P Gas meter & Reg	Ventilation exhaust only	Interlocked to light
L2 P Plant	No mechanical ventilation	-
G P Office	Air-conditioning system	Time Clocks or BMS controlled
B3-B2 Resi Storage Rooms	Ventilation supply only	Interlocked to light
B2 P Resi Bicycle Storage	Ventilation supply only	Interlocked to light
Ground Floor Residential Lobbies	Ventilation supply only	Time Clocks or BMS controlled
Basement Residential Lobbies	Ventilation supply only	Time Clocks or BMS controlled
Building 1 Tower Residential Lobbies	No mechanical ventilation	-
Building 2 Tower Residential Lobbies	No mechanical ventilation	-
Building 3 Tower Residential Lobbies	No mechanical ventilation	-
Building 4 Tower Residential Lobbies	No mechanical ventilation	-

Table 5: Lighting Systems

Common Area	Lighting System Type	Efficiency Measure
Lift Cars	L.E.D.	Connected to lift call button
B4-B1 Residential Carpark	L.E.D.	Time Clocks & Motion Sensors
GL P Loading Dock	L.E.D.	Time Clocks & Motion Sensors
B1 P Comms	L.E.D.	Manual switch on/off
B3 Waste Rooms	L.E.D.	Manual switch on/off
B1 P Bulky Storage	L.E.D.	Manual switch on/off
GL P Resi Bin Holding	L.E.D.	Manual switch on/off
L17 4 BTR Amenity	L.E.D.	Manual switch on/off
B4-B1 P Fan rooms	L.E.D.	Manual switch on/off
B2 P Fire control room	L.E.D.	Manual switch on/off
B2 P Fire pump room	L.E.D.	Manual switch on/off
B2 P Car wash plant (resi)	L.E.D.	Manual switch on/off
B2-B1 P Services Rooms	L.E.D.	Manual switch on/off
B2 P Sub Stations	L.E.D.	Manual switch on/off
B1 P CW + RW filtration + oil separation	L.E.D.	Manual switch on/off
B1 P MSB Rooms	L.E.D.	Manual switch on/off
B1 P Battery Room	L.E.D.	Manual switch on/off
B1 P Water Pump Control Room	L.E.D.	Manual switch on/off
GL P Gas meter & Reg	L.E.D.	Manual switch on/off
L2 P Plant	L.E.D.	Manual switch on/off
G P Office	L.E.D.	Manual switch on/off
B3-B2 Resi Storage Rooms	L.E.D.	Manual switch on/off
B2 P Resi Bicycle Storage	L.E.D.	Manual switch on/off
Ground Floor Residential Lobbies	L.E.D.	Time Clocks & Motion Sensors
Basement Residential Lobbies	L.E.D.	Time Clocks & Motion Sensors
Building 1 Tower Residential Lobbies	Ventilation exhaust only	Time Clocks & Motion Sensors
Building 2 Tower Residential Lobbies	Ventilation exhaust only	Time Clocks & Motion Sensors
Building 3 Tower Residential Lobbies	Ventilation exhaust only	Time Clocks & Motion Sensors
Building 4 Tower Residential Lobbies	Ventilation exhaust only	Time Clocks & Motion Sensors

3.3.3 Dwellings

- The bathroom exhaust fans within each residential dwelling are individual fans, ducted to façade and controlled by manual on/off switches.
- The kitchen exhaust fans within each residential dwelling are individual fans, ducted to façade and controlled by manual on/off switches.
- The laundry exhaust fans within each residential dwelling are individual fans, ducted to façade and controlled by manual on/off switches.
- Single-phase air conditioning systems are to be installed within each residential dwelling in the living and bedroom areas. The system is to have a minimum star rating (old label) of at least 3.5 for cooling and heating.
- The dwellings must be primarily lit by compact fluorescent, fluorescent or LED lamps (minimum 80% of light fittings).
- A gas cooktop and electric oven to be installed within each residential dwelling.
- Dishwasher units to be installed within each residential dwelling. The dishwasher units are to have an energy efficiency rating of at least 4.0 stars.
- Clothes dryer units to be installed within each residential dwelling. The clothes dryer units are to have an energy efficiency rating of at least 2.0 stars.

Note that if any of the above systems are to be substituted by less efficient systems, an update to the BASIX certificate would also be required.

CONCLUSION

A BASIX assessment of the proposed development located at 19A Evans Avenue, Eastlakes, Lidcombe has been carried out. The results of the assessment indicate that the development will satisfy the requirements of BASIX if all of the items outlined in this report are incorporated into the design of the development. If there are changes to the building design and construction a reassessment would be required.