

Façade Access Strategy Report – North Tower

Martin Place Metro

Macquarie

Stage ~~43~~ Design stage.

Prepared for
Lend Lease

Date: ~~4 February 15 September 2020~~19

Reference: 17032Aconex Reference: CSWSMP-MAC-SMN-AT-REP-99-99-10

Revision: ~~43~~

Surface Design

Document prepared by:

Surface Design Pty Ltd
ABN 19 570 343 498
68 York Street, SYDNEY NSW 2000 Australia
T: +61 2 9249 1400
E: info@surfacedesign.com.au

Document control

Revision	Date	Revision details	Author	Verifier	Approver
0	20/1/19	Draft issue	RM		
1	25/02/19	Updated to comments from Lend Lease and JPW	RM		
2	05/04/19	Updated	RM		
3	15/09/19	Updated	RM		
4	4/02/20	Stage 4 Design 75% Submission	RM		

A person using Surface Design documents or data accepts the risk of using the contents in hard or electronic form if not in the original hard copy and use for any purpose not agreed to in writing by Surface Design.

Contents

1.	Executive Summary	1
2.	Introduction	2
3.	Project Description	3
4.	Required Maintenance	4
4.1	Facade Maintenance	4
4.1.1	Light Maintenance	4
4.1.2	Heavy Maintenance	4
5.	Proposed Access Strategy	5
5.1	Influencing factors	5
5.2	North Tower façade access	6
5.3	North Tower Façade Access Summary	6
5.3.1	ZONE N1 and ZONE N2 - North tower façade	6
5.3.2	ZONE N3, N4 and N5 - Terrace, lower floor facade and awnings	8
5.3.3	ZONE N6 – Central Atrium space	9
5.3.4	ZONE N7 – Link Bridge, light well	9
5.3.5	ZONE N8 – Northern elements of 50 Martin Place	9
5.3.6	ZONE N9 – Internal face of lift core glazing	9
5.3.7	Tower BMU Systems (Zone N1 and N2)	10
Appendix A		12
	Relevant Architectural Drawings with all Zones marked up	12
Appendix B		13
	BMU Cycle time calculations (Zone N1 and N2)	13
Appendix C		14
	BMU additional information (restraint pins, BMU doors) for Zone N1 and N2	14
Appendix D		15
	Additional details for Terrace and Ground Plane access (Zones N3, N4 and N5)	15
Appendix E		16
	Additional details for Internal Atrium (Zone N6)	16
Appendix F		17
	Additional details for Lightwell and bridge (Zone N7 and N8)	17
Appendix G		18
	Additional details for Access within the lift core (Zone N9)	18
Appendix H		19
	Example images of BMU's and Access Equipment (for reference only)	19
Appendix I		20
	Codes and standards	20

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Facade Access Strategy Report - North Tower

1. Executive Summary	1
2. Introduction	2
3. Project Description	3
4. Required Maintenance	4
4.1 Facade Maintenance	4
4.1.1 Light Maintenance	4
4.1.2 Heavy Maintenance	4
5. Proposed Access Strategy	5
5.1 Influencing factors	5
5.2 North Tower façade access	6
5.3 North Tower Façade Access Summary	6
5.3.1 ZONE N1 and ZONE N2 – North tower façade	6
5.3.2 ZONE N3, N4 and N5 – Terrace, lower floor facade and awnings	8
5.3.3 ZONE N6 – Central and South Atrium space	9
5.3.4 ZONE N7 – Link Bridge, light well	9
5.3.5 ZONE N8 – Northern elements of 50 Martin Place	9
5.3.6 ZONE N9 – Internal face of lift core glazing	9
5.3.7 Tower BMU Systems (Zone N1 and N2)	10
Appendix A	12
Relevant Architectural Drawings with all Zones marked up	12
Appendix B	13
BMU Cycle time calculations (Zone N1 and N2)	13
Appendix C	15
BMU additional information (restraint pins, BMU doors) for Zone N1 and N2	15
Appendix D	16
Additional details for Terrace and Ground Plane access (Zones N3, N4 and N5)	16
Appendix E	17
Additional details for Internal Atrium (Zone N6)	17
Appendix F	18
Additional details for Lightwell and bridge (Zone N7 and N8)	18
Appendix G	19
Additional details for Access within the lift core (Zone N9)	19
Appendix H	20
Example images of BMU's and Access Equipment (for reference only)	20
Appendix I	21
Codes and standards	21

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

1. Executive Summary

Surface Design have been engaged as Façade and Façade Access Consultant by Lend Lease for the development at Martin Place Metro towers, Sydney.

This report describes the Façade Access Strategy for the North Tower, a separate report has been prepared for the South Tower.

This report relates to the external and internal facade access systems required for both heavy (including glass replacement) and light maintenance (including cleaning and sealant maintenance).

The design has been based on the Design drawings prepared by the architects (JPW).

The buildings are described in various zones and the access system options for each of these building zones are summarised below.

Most of the external facades for both towers are to be accessed via dedicated Building Maintenance Units (BMU's). With adequate design considerations, maintenance and operation, BMU access is generally more suited to the project for the tower for the external facades light and heavy maintenance.

The North Tower has been designed with a centrally located BMU at level 39. The BMU is to be concealed within the plant rooms when parked. The BMU includes an extendable mast or screw jack arrangement (to raise nominally 10 m vertical extension) and a four-stage telescopic and slewing boom nominally 45m at full extension and requires nominal 360° slewing capacity. When parked the BMU is anticipated to be nominally 4m wide and 20m long and park within the height of the plant room as allocated. The roof of the plant room is to either be an openable door element or attached to the BMU and to raise out above the building with the BMU. This door design is to be developed further. The use and function of the BMU is to be designed to consider safety, this includes access in and around generator exhaust to the east elevation at level 28, and to the flues at the roof dome.

The North Tower will have a second BMU at the south elevation of the Level 28 Plant room. This BMU is to include a shunt rig and/or rail system to extend horizontally through the south elevation façade (doors to be incorporated). When parked the BMU is to be concealed within the L28 plant room. The boom is to include telescopic boom, knuckle jibs and slewing rings to enable access to the extent of the façade below level 28.

Access to the internal face of glass within the western lift core is to be from the top of the lift cars as well as IRA access where relevant.

The terrace and lower floor facades may be accessed via EWP, industrial rope access (abseil) using monorail systems concealed in the soffits or temporary scaffold systems.

The north tower lower level awnings will require access from ground level using ladder and ladder hooks and with appropriate safety line systems. ~~Additionally~~ Additionally, the canopies to the north east corner and south corner are to be access from industrial rope access (abseil) using concealed monorail within the soffit. Access to the monorail in the soffit is to use concealed 'loop box' within the finishes zones to walls and/or columns with locations and details to be developed and agreed with the Architect.

The bridge and light well spaces to the south of the North Tower can be accessed via integrated Industrial Rope systems using permanently fixed monorail systems and rope fixing points.

The internal North Tower Atriums can be accessed via integrated Industrial Rope systems and EWP systems.

~~The southern atriums will include access via overhead monorail systems with integrated ledges for IRA personnel on the structural steel beams that support the facades. Further EWP systems can be used on the basis that there are no permanent obstructions in the fitout design such as fixed furniture or landscape, this is to be developed with the interior designers.~~

The design has considered safety in design requirements.

Lend Lease have sought market feedback on the BMU and access designs including detailed design input and costing for further review.

Appendix A outlines the current BMU proposals as documented. We have included example equipment as discussed with access contractor (Lend Lease Trade Partner).

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

2. Introduction

Surface Design has been engaged by Lend Lease to provide a Facade Access Strategy report for the building facades and interior atrium spaces of the proposed development at Martin Place Metro, Sydney CBD.

This report relates to the external and internal facade access systems for the North Tower that will be required to facilitate both ongoing building maintenance and external facade repairs.

Due to the varying geometries and floor plates of the entire development, a combination of different access systems will be required to gain access to all external areas needed for maintenance.

The access strategies that Surface Design has investigated and included within the design include:

- Building Maintenance Units
 - Industrial Rope access including through Recessed monorail systems or rope access points or davit arms
- Elevated work platforms/knuckle booms (including truck mounted cherry picker)
- Ladder access and safety lines
- Temporary scaffold

This report focuses on the access strategy and is not intended to be used as a specification for implementation. Separate Performance Specifications are already provided and will be developed during the Detailed Design Phases.

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

3. Project Description

The proposed development is located at Martin Place Metro, Sydney. The development is intended to include two high rise towers. The North Tower is being designed by JPW, The south is being designed by Tzannes Architects. Grimshaw Architects are the lead Architect for the station development underground. This report is related to the North Tower only.

For facade maintenance, the following areas need to be addressed, these have been labelled in Zones:

North Tower

- Zone N1 - Tower facades
- Zone N2 – Tower facades to south
- Zone N3 - Terrace facades including soffits
- Zone N4 – Ground floor facades
- Zone N5 – Awnings
- Zone N6 – Atrium (~~south and~~ central atriums)
- Zone N7 – Link bridge, light well and
- Zone N8 - Northern elements of 50 Martin Place
- Zone N9 – Internal face of the lift core glazing

Refer to Architectural drawings for geometry and façade types including drawings:

- ~~Drawing list to be added upon finalisation by~~ Refer to drawings by JPW

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

4. Required Maintenance

4.1 Facade Maintenance

Maintenance can be categorised into two sectors, light maintenance and heavy maintenance.

4.1.1 Light Maintenance

Light maintenance refers to:

- o Routine cleaning of all the different facades and finishes
- o Routine inspection of facade
- o Facade service life repairs (replacement of sealants, gaskets etc.)

As a reference, the frequency of cleaning of glass and frames is every 3 – 4 months whereas the frequency of cleaning masonry (if required) is yearly. The expected frequency of service life to sealing repairs is every 10 – 20 years. Light maintenance will need to occur internally and externally. Regular inspections of the façade components is required during light maintenance.

4.1.2 Heavy Maintenance

Heavy maintenance refers to any process of maintenance which requires mechanical lifting:

- o Replacement of materials (glass, cladding panels etc.)

The access system chosen for this purpose (eg. Lifting glass panels) will need to occur externally if internal measures are not viable. The choice of the final heavy maintenance strategy will be directly impacted by the size and weight of the panels. The heavy maintenance strategy must be able to support, and manoeuvre panel sizes up to 6.4m long.

The materials will be manoeuvred by the following equipment

- o Tower and podiums – BMU mounted lifting systems
- o Terraces – BMU and temporary scaffold (if required)
- o Ground floor – EWP or temporary scaffold (if required)

Plant equipment replacement

The BMU's are to be utilised for plant replacement, the design of these elements is ongoing.

The size and weight of these elements is to be confirmed and accommodated by the BMU lifting device. It may include components of the following:

- o Cooling towers located at roof plant room
- o Other minor plant equipment from roof plant room

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

5. Proposed Access Strategy

5.1 Influencing factors

The following are some factors that should be taken into consideration when selecting both maintenance equipment and access strategies:

- o Height of building
- o Wall geometry
- o Building feature elements (orientation, size and weight)
- o Potential obstructions and access points (rigging positions etc)
- o Cleaning regime (frequency, cycle times, material warranties)
- o Materials and finishes
- o Glass replacement methodology (internal and external)
- o Feature and other materials replacements
- o Cost of system
- o Integration with facade systems (restraint points and loads)
- o Garage and storage requirements
- o Compliance with legislation and authorities
- o Safety in design
- o Rescue methodology (injury, damage, breakdown or power outage situation)
- o Internal landing zones for emergency egress and access
- o Working above the public zones (ie footpaths and terrace)

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Facade Access Strategy Report - North Tower


5.2 North Tower façade access

The tower is 40 storeys high. The facades generally consist of an aluminium framed curtain wall system with glazing and integrated shading. The facades vary in geometry from vertical panels to sloped and faceted panels forming the geometry of the tower. The North Tower Roof encroaches on the height limitations of the project, thus needing a BMU system that can be used and stored discreetly with minimum disruption and below the height limitations.

5.3 North Tower Façade Access Summary

5.3.1 ZONE N1 and ZONE N2 - North tower façade

Refer to Appendix A, B, C and H for further information.

Access System	Installation/storage	Light maintenance (eg. Cleaning and sealant maintenance)	Heavy Maintenance (eg glass and plant replacement)
Zone N1 BMU 1 (level 40) <ul style="list-style-type: none">- BMU with telescoping mast and screw jacks for raised mast, and 4-stage telescoping and slewing (360°) jib (nominal 40m long)- Cradle and glass lifting equipment- Also plant room equipment lifting capacity required.- Soft Rope System	<ul style="list-style-type: none">- Large permanent system; needs to be stored/parked in the plant room.- Needs maintenance- Needs skilled personnel to operate- Door or attached façade to BMU to be incorporated.	Adequate	Adequate Lifting of glass to occur from street level using the BMU Is required for plant equipment maintenance replacement. To be designed for these loads as well as glass lifting loads
 <p>Zone N1 (in blue shading)</p>			


Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Facade Access Strategy Report - North Tower

<p>Zone N2</p> <p>BMU 2 (level 28 south)</p> <ul style="list-style-type: none">- BMU with shunting rig or rails, articulated knuckle and slewing 4 or 3-stage telescoping jib- Cradle and glass lifting equipment- Doors to be incorporated into the southern façade.- Soft Rope System	<ul style="list-style-type: none">- Large permanent system; needs to be stored/parked in the plant room.- Needs maintenance- Needs skilled personnel to operate- Door or attached façade to BMU to be incorporated.	<p>Adequate</p>	<p>Adequate</p> <p>Lifting of glass to occur from street level using the BMU.</p> <p>May be required for plant equipment maintenance replacement. To be designed for these loads as well as glass lifting loads.</p>
 <p>Zone N2 (in red shade)</p>			

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt


Formatted: Font: 7 pt, Not Hidden

5.3.2 ZONE N3, N4 and N5 - Terrace, lower floor facade and awnings

Refer to Appendix A, D and H for further information.
Note:

- o N3 is level 10 terrace.
- o N4 is ground floor facades
- o N5 is the awnings at the lower floors.

Access system	Installation/Storage	Light Maintenance	Heavy Maintenance
ZONE N3, N4 and N5 EWP access or temporary scaffold.	Hired or permanent stored on site.	Adequate where reach is possible, (consider scissor lift or cherry picker)	Adequate
ZONE N3, N4 Monorail IRA access to soffits	Permanently installed to soffits	Adequate	Adequate
ZONE N5 Awnings access from ladders and safety line on awnings. Canopies to the south east, north east and south west zones to be accessed from above with IRA using concealed monorail to soffit	Hired or permanent stored on site. Monorail installed to soffits with concealed 'loop box' to column or wall finishes zone as to be agreed with the architect for locations.	Adequate	Adequate



Zone N3 (in purple shade)
Zone N4 and N5 (in green shade)

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

5.3.3 ZONE N6 – Central ~~and South~~ Atrium space

Refer to Appendix A, E and H for further information.

Access System	Installation /Storage	Light Maintenance	Heavy Maintenance	Zone N6
Recessed monorail system and walkways	<p>Monorail need to be incorporated in the soffits of the atrium spaces.</p> <p>Access from floors for access to monorail system.</p> <p>Monorail system to be designed to allow access to all soffits (including for any services in soffits), balustrades and stairs.</p>	Adequate	Can be used to rig panels from ground level	<p>N6 as shaded in blue;</p>
EWP for maintenance	<p>Non-permanent</p> <p>Note that any fixed furniture or landscaping to be considered, this will required to be coordinate with the interior designers.</p>	Adequate for some levels	Adequate for some levels	

5.3.4 ZONE N7 – Link Bridge, light well

Refer to Appendix A, F and H for further information.

Refer to Appendix X, F and H for further information.			
Access System	Installation/Storage	Light Maintenance	Heavy Maintenance
Monorail system	<p>Monorail need to be incorporated near the top of the light well (as per existing monorails).</p> <p>Additional monorails required to the top edges of the bridge for access, typically double rope system to be adopted for safe access.</p> <p>Need opening from floors for access to monorail system, this requires relevant doors above the bridges.</p> <p>Note artwork in the light well to be considered, this require coordination with Macquarie and the artist.</p>	Adequate	Can be used to rig panels from ground level
Temporary scaffold	Hired equipment for large maintenance operations	Adequate although typically not required.	Adequate.

5.3.5 ZONE N8 – Northern elements of 50 Martin Place

Refer to Appendix A, F and H for further information.

Access System	Installation /Storage	Light Maintenance	Heavy Maintenance
Monorail system and fixed access points as per the existing systems in place.	<p>Monorail need to be incorporated near the top of the light well (as per existing monorails; to be coordinated with Zone N7)</p> <p>Need opening from floors for access to monorail system (refer Zone N7).</p> <p>Existing rope access systems to be maintained where possible.</p>	Adequate	Can be used to rig panels from ground level

5.3.6 ZONE N9 – Internal face of lift core glazing

Refer to Appendix A, G and H for further information.

Access System	Installation/Storage	Light Maintenance	Heavy Maintenance
Fixed rope access restraint points on the steel structure	Need opening from floors for access to rope access restraints on the steel structure.	Adequate	Can be used to rig panels from ground level
Stand on top of lift car	After hours working from the top of the lift car allows access to clean most of the internal glazing.	Adequate for most of the faces, noting that the steel structure may inhibit access to some surfaces.	Yes in combination with BMU.

Facade Access Strategy Report - North Tower

5.3.7 Tower BMU Systems (Zone N1 and N2)

The North Tower has been designed with a centrally located BMU at level 39. The BMU is to be concealed within the plant rooms when parked. The BMU includes an extendable mast or screw jack arrangement (to raise nominally 10m vertical extension) and a four-stage telescopic and slewing boom nominally 45m at full extension and requires nominal 360° slewing capacity. When parked the BMU is anticipated to be nominally 4m wide and 20m long. The roof of the plant room is to either be an openable door element or attached to the BMU and to raise out above the building with the BMU. This door design is to be developed further.

The use and function of the BMU is to be designed to consider safety, this includes access in and around generator exhaust to the east elevation at level 28, and to the flues at the roof dome.

The North tower will have a second BMU at the south elevation of the Level 28 Plant room. This BMU is to include a shunt rig and/or rail system to extend horizontally through the south elevation façade (doors to be incorporated in the facade). When parked the BMU is to be concealed within the L28 plant room. The boom is to include telescopic boom, knuckle jibs and slewing rings to enable access to the extent of the façade below level 28.

BMU Cycle times

The estimated BMU cycle times have been calculated and included in Appendix B.

The required cleaning regime of 4 times a year can be met with the two tower BMU's.

The below listed the general cycle times required for the key elements of the façade, also refer to the Mechanical Services documentation for the plant room equipment requiring replacement:

Element	Light Maintenance (cleaning, inspections)	Heavy maintenance (replacement etc)
DGU Glazing	Clean 4 times per year Inspect regularly, during cleaning cycle	Periodic in case of breakages. Life span for panels is nominally 20-30 years subject to performance of edge seals of DGU
Monolithic or laminated glass	Clean 4 times per year Inspect regularly, during cleaning cycle	Periodic in case of breakages. Life span for panels is nominally 20-30 years subject to performance of laminates
Aluminium cladding	Clean 4 times per year Inspect regularly, during cleaning cycle	Periodic in case of local damage. Life span for panels is nominally 50 years subject to performance of coatings
Aluminium sunshades	Clean 4 times per year Inspect regularly, during cleaning cycle	Periodic in case of local damage. Life span for panels is nominally 50 years subject to performance of coatings
Aluminium framing	Clean 4 times per year Inspect regularly, during cleaning cycle	Periodic in case of local damage. Life span for panels is nominally 50 years subject to performance of coatings
Aluminium louvers	Clean 4 times per year Inspect regularly, during cleaning cycle	Periodic in case of local damage. Life span for panels is nominally 50 years subject to performance of coatings
Stone cladding	Clean 4 times per year Inspect regularly, during cleaning cycle	Periodic in case of local damage. Life span for panels is nominally 50 years

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Facade Access Strategy Report - North Tower

Sealants/gaskets	Clean 4 times per year Inspect regularly, during cleaning cycle	Periodic in case of local damage. Life span for sealant and gaskets is nominally 20-30 years
Motors for operable windows and doors	Clean 4 times per year Inspect regularly, during cleaning cycle	Periodic in case of operation damage.

BMU Reaction loads to structure

Initial loadings have been provided for coordination with the structural engineer. These are to be confirmed and verified by the BMU contractors and coordinated with the Project Structural Engineer.

BMU Rescue strategy

A rescue strategy is to be developed for all access methods and in particular the BMU's. This strategy is to include consideration of the following:

- Reasons for rescue required:
 - Damage or break down of BMU system while in use
 - Injury of workers within the BMU
 - Power outage
 - Internal fire within the building during use of the BMU

Landing zones

Consider landing zones and mechanisms to lower or raise the BMU cradle, safely and efficiently

- A landing zone diagram is to be provided in BMU Performance Specification, the relevant plans have been listed below for clarity.
- Consider potential break through glass to allow rescue service prompt access to injured workers in the BMU

The key levels are:

- Level 10 terrace
- Level 1 and ground (noting the awnings on the eastern, northern and western elevation)

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Appendix A


Relevant Architectural Drawings with all Zones marked up

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden



Zone N1 (blue)
serviced by Roof
BMU

Note the flues, the BMU must avoid these, the BMU design and safe work method management strategy is to be developed to accommodate this.

Note the generator exhaust, the BMU must avoid these, the BMU design and safe work method statement is to be developed to accommodate this.

Zone N6 (Various
Atriums inside
building)

Zone N2 (red)
serviced by L28 BMU

Zone N3
(purple)
(terrace)

Zone N7 and N8
(Link Bridge, light
well and north
face of 50 Martin
Place)

Zone N4 (ground floor), N5 (awnings) (green)

NOT FOR CONSTRUCTION

SYDNEY METRO - MARTIN PLACE

EAST ELEVATION

40 Elevations

DESIGNED BY	BRUNN	DATE	14/01/2019
DRAWN BY	BRUNN	DATE	14/01/2019
CHECKED BY	BRUNN	DATE	14/01/2019
APPROVED BY	BRUNN	DATE	14/01/2019
STATUS	INTERIM ISSUE	SHEET	1 OF 1
PROJECT NO.	CSWSMP-MAC-SMN-AT-DRG-409900	DATE	14/01/2019

- DA - RL
FFL 194000
- L39
FFL 184280
- L38
FFL 179180
- L37
FFL 175050
- L36
FFL 171190
- L35
FFL 167250
- L34
FFL 163350
- L33
FFL 159450
- L32
FFL 155550
- L31
FFL 151650
- L30
FFL 147750
- L29
FFL 143850
- L28
FFL 139950
- L27

Zone N1 (blue)
serviced by Roof
BMU

- L22
FFL 114850
- L21
FFL 110950
- L20
FFL 107050
- L19
FFL 103150
- L18
FFL 99250
- L17
FFL 95350
- L16
FFL 91450
- L15
FFL 87550
- L14
FFL 83650
- L13
FFL 79750
- L12
FFL 75850
- L11
FFL 71950
- L10
FFL 68050
- L09
FFL 64150
- L08
FFL 60250
- L07
FFL 56350
- L06
FFL 52450
- L05
FFL 48550
- L04
FFL 44650
- L03
FFL 40750
- L02
FFL 36850
- L01
FFL 32950
- L00
FFL 29050
- L
FFL 25150

LEVEL 10 TERRACE

LATERAL BRACING
BEHIND FACADE
SHOWN DASHED

CSWSMP-MAG-SMN-AT-DRG-409911

SIGNAGE ZONE
SHOWN DASHED


CSWSMP-MAG-SMN-AT-DRG-509900

CSWSMP-MAG-SMN-AT-DRG-611241

Zone N6 (Various
Atriums inside
building)

Zone N3
(purple)
(terrace)


Zone N4 (ground floor), N5 (awnings) (green)



1:200 (@x10) 1:600 (@33%)

2000 0 5000 10000m

1:200(@x10)





General Notes:
Do not scale from drawing. Use marked dimensions. To be read in conjunction with the project brief. The drawing is to be immediately notified of any other discrepancies. Copyright on this drawing to be retained by the Architect.

DRAWING

IN COLOUR

Zoning (p) (te)				22-02-19		Transport for NSW Government		This is a public and the related information has been prepared by, or on the instruction of, Transport for NSW specifically for you and may only be used for the purpose for which it was prepared. It is not to be used for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will not use it for any other purpose. It is provided to you on the basis that you warrant that you will	
-----------------	--	--	--	----------	--	---------------------------------	--	---	--





Zone N1 (blue)
serviced by Roof
BMU

Zone N6 (Various
Atriums inside
building)


Zone N2 (red)
serviced by L28 BMU

Zone N3
(purple)
(terrace)

Zone N7 and N8
(Link Bridge, light
well and north
face of 50 Martin
Place)

DRAWING COLOUR CODED - PRINT ALL COPIES IN COLOUR

NOT FOR CONSTRUCTION



General Notes:
Do not scale from drawing. Use marked dimensions. To be read in conjunction with the project brief. The drawing is to be immediately notified of any other discrepancies. Copyright on this drawing to be retained by the Architect.

COORDINATE SYSTEM		REPORT DATE	SCALE
AND	DESCRIPTION	DESIGNED	VERIFIED
F	INTERIM ISSUE	22-02-19	APPROVED
DESIGN CHECK		DESIGNED	VERIFIED
NOT APPLICABLE - NOT METRO ISSUE		DESIGNED	VERIFIED
APPROVED		DESIGNED	VERIFIED
SYDNEY METRO - MARTIN PLACE SOUTH ELEVATION 40 Elevations		FILE NO.	SHEET 1 OF 1
CSWSMP-MAC-SMN-AT-DRG-409903		STATUS	INTERIM ISSUE
F		ISSUED BY	AO

Appendix B

BMU Cycle time calculations (Zone N1 and N2)

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

BMU 1

**Time to clean
(@ 3m²/min)
3m Cradle**

BMU 2

**Time to clean
(@ 3m²/min)
3m Cradle**

Drop description	Set up time per drop (min)	Freefall height	Time of free fall at 8m/min	Height of cleaning drop (m approx)	Time of drop (@ 2m/min)	Area per drop (m2)	Time to clean (@ 3m2/min)						Total Drops	Time to clean
							3m Cradle width	North	East	South	West			
Level 28 to 10	60	0	0	70.00	35.00	210.00	70.00	0.00	0.00	14.00	0.00	14.00	2310.00	
Level 10 to ground	60	70	8.75	40.00	20.00	120.00	40.00	0.00	8.00	0.00	8.00	16.00	2060.00	
	0	0	0	0.00	0.00	0.00	0.00	4.00	0.00	4.00	6.00	14.00	0.00	
Total time (min)													4370.00	
Hours													72.83	
Days (6 hours per day)													12.14	
Plus 100% downtime (bad weather etc)													24.28	

Appendix C

BMU additional information (restraint pins, BMU doors) for Zone N1 and N2

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden


Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Note the flues, the BMU must avoid these, the BMU design and safe work method management strategy is to be developed to accommodate this. Should the BMU design result in a 'blind spot' under the BMU, an alternative rope access strategy is to be included and developed for the project.

Note the generator exhaust, the BMU must avoid these, the BMU design and safe work method statement is to be developed to accommodate this.

The blue dotted lines indicate the levels where the BMU restraint pins are required, this is to be coordianted and confirmfed with the BMU contractor, nominally at every third floor and every second panel.




DRAWING COLOUR CODED - PRINT ALL COPIES IN COLOUR

COORDINATE SYSTEM			
AND	DESCRIPTION	DESIGNED	VERIFIED
F	INTERIM ISSUE	25.01.2019	25.01.2019
DATE	DATE	DATE	DATE

NSW	Transport
GOVERNMENT	for NSW
GRIMSHAW	

DESIGNED	VERIFIED	APPROVED
25.01.2019	25.01.2019	25.01.2019
DATE	DATE	DATE

SYDNEY METRO - MARTIN PLACE		
EAST ELEVATION		
BUILDING ELEVATIONS		
FILE NO.	SHEET: 1	OF 1
STATUS: INTERIM ISSUE		A0
DATE: 25.01.2019		
CS/SWMP-MAC-SHM-A1-DRG-4099001	F	EDMS No.
		</




NOT FOR CONSTRUCTION


[illegible]

General Notes:

Do not scale from drawing. Use marked dimensions. To be read in conjunction with all other Consultant's drawings. The Architect to be immediately notified of any other discrepancies. Copyright on this drawing to be retained by the Architect.




The blue dotted lines indicate the levels where the BMU restraint pins are required, this is to be coordianted and confirmfed with the BMU contractor, nominally at every third floor and every second panel.



DRAWING COLOUR CODED - PRINT ALL COPIES IN COLOUR

SYDNEY METRO - MARTIN PLACE			WEST ELEVATION			BUILDING ELEVATIONS		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
JPM			JPM			JPM		
J								




The blue dotted lines indicate the levels where the BMU restraint pins are required, this is to be coordianted and confirmfed with the BMU contractor, nominally at every third floor and every second panel.


DRAWING COLOUR CODED - PRINT ALL COPIES IN COLOUR

SYDNEY METRO - MARTIN PLACE			
SYDNEY METRO - MARTIN PLACE			
BUILDING ELEVATIONS			
SOUTH ELEVATION			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			
JPM			


Landing Zones (emergency egress) – North Tower




Landing Zones (emergency egress) – North Tower




Landing Zones (emergency egress) – North Tower





Typical Design Intent detail for concealed BMU restraint pin socket to typical facade spandrel

BMU restraint pin socket to the bottom of the mullion at the bottom of the vision panel



Typical Design Intent detail for concealed BMU restraint pin socket to typical South Lens facade spandrel



NOTES:

1. FOR ALL FINISHES REFER TO ARCHITECTS EXTERNAL FINISHES SCHEDULE
2. REFER TO FACADE PERFORMANCE SPECIFICATION DATED 15/02/2019 FOR ALL TECHNICAL REQUIREMENTS

FOR
INFORMATION
NOT FOR CONSTRUCTION

1	22/03/2019	FOR DISCUSSION	TZ		
0	01/03/2019	DRAFT	JR	RM	
Rev Date	Revision Details		Drn	Ver.	App.

Surface Design

ABN 19 570 343 498
68 York Street, Sydney
New South Wales 2000 Australia
T: +61 2 9249 1400 **E:** Info@surfacedesign.com.au

Architect:
GRIMSHAW
JPW
JOHNSON PILTON WALKER



Project: SYDNEY METRO MARTIN PLACE
OSD
NORTH TOWER

Drawing Title:

N-FT-04
TYPICAL MULLION VISION
ANGLE 1

Drawn TZ	Signed	Date	Verified	Signed	Date
Designed RM	Signed	Date	Approved	Signed	Date
Project No. 17032				Scale: 1:2	Sheet Size: A3
Drawing No. CSWSMP-MAC-SMN-FA-DRG-990451					Rev: 1

Appendix D


Additional details for Terrace and Ground Plane access (Zones N3, N4 and N5)

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden




Access to canopy use monorail above with loop box concealed to column/wall (location to be agreed with architect)

Access to awning use ladder rail and safety line (location/details to be agreed with architect)

Cleaning can be with IRA from monorail or extended poles from ground, or EWP on ground


East elevation ground floor



Concealed monorail above with loop box concealed to column/wall (location to be agreed with architect)

Cleaning can be with IRA from monorail or extended poles from ground, or EWP on ground

North elevation ground floor



Access to awning use ladder rail and safety line (location/details to be agreed with architect)

This 3D architectural rendering shows the ground floor of a building's west elevation. The building features a curved corner on the left, a series of large glass windows with vertical mullions, and a section with horizontal wooden cladding on the right. A white awning extends from the building. Red arrows point from text boxes to specific maintenance access points: one to the awning's edge, another to the window mullions, and a third to a small platform on the right. A white line runs along the base of the windows, and a blue rectangular area is visible on the ground in front of the building.

Access to canopy use monorail above with loop box concealed to column/wall (location to be agreed with architect)


Cleaning can be with IRA from monorail or extended poles from ground, or EWP on ground

West elevation ground floor

Access to soffit use monorail above with loop box concealed to column/wall (location to be agreed with architect)

Cleaning can be with IRA from monorail or extended poles from terrace, or EWP on terrace


North elevation terrace



Access to soffit use monorail above with loop box concealed to column/wall (location to be agreed with architect)

Cleaning can be with IRA from monorail or extended poles from terrace, or EWP on terrace


South elevation terrace



Cleaning from extended poles
from terrace, or EWP on
terrace

A 3D architectural rendering of a building's exterior. The building has multiple levels with balconies and windows. In the foreground, there is a terrace with a wooden fence made of vertical slats. A red arrow points from a text box in the upper right to a cleaning pole extending from the terrace level. The scene is set against a light blue sky.

South and east elevation terrace



Cleaning from extended poles
from terrace, or EWP on
terrace

A 3D architectural rendering of a building facade. The upper portion features a curved glass curtain wall with horizontal mullions. Below this, a terrace area is visible, characterized by a series of vertical wooden slats. A red arrow points from a text box to the terrace level. To the right, a blue glass-enclosed walkway or staircase is shown. The lower part of the image shows a grey concrete structure with rectangular openings.

South and west elevation terrace



BLUE - FROM BMU.



GREEN - FROM ROPE ACCESS RAIL.



PINK - FROM RESTRAINT SYSTEM




ORANGE - FROM E.W.P.




RED - FROM LNH POLE



YELLOW - FROM UFT CAR.




Note there will be optional allowance to bring EWP into this area as well as using the rope access.




FACADE ACCESS MARKUP - PODIUM;

PER MEETING 28/08/19




DRAWING COLOUR CODED - PRINT ALL COPIES IN COLOUR			
BLUE SHADE INDICATES METRO AREA			
L	North Tower Stage 3 Design	22-05-19	PB/22-05-19
K	Stage 3 Design	19-05-19	PB/19-05-19
J	AR051	18-04-19	MM/18-04-19
I	FOR REVIEW AR051	22-03-19	MM/22-03-19
AM	DESCRIPTION	DESIGNED	APPROVED
CO-ORDINATE SYSTEM	HEIGHT DATUM	SCALE	
GRIMSHAW			
This drawing and the related information have been prepared by, or at the request of, Transport for NSW for a specific purpose and are not to be used for any other purpose without the prior written consent of Transport for NSW. Transport for NSW does not provide any warranty, liability arising out of the use of the drawing or any of the related information for any purpose other than the intended purpose. The user assumes full responsibility for the use of the drawing and the related information and is not to be held responsible for any loss or damage arising from the use of the drawing or any of the related information.			
Dimensions: To be read as drawings. The Architect's Discrepancies, Copyright notice.			



DRAWING COLOUR CODED - PRINT ALL COPIES IN COLOUR			
BLUE SHADE INDICATES METRO AREA			
F	North Tower Stage 3 Design	22-05-19	PB/22-05-19
E	Stage 3 Design	19-05-19	PB/19-05-19
D	AR051	18-04-19	MM/18-04-19
C	GMP VE Baseline Set Update 3	15-06-18	MM/15-06-18
AM	DESCRIPTION	DESIGNED	APPROVED
CO-ORDINATE SYSTEM	HEIGHT DATUM	SCALE	
GRIMSHAW			
This drawing and the related information have been prepared by, or at the request of, Transport for NSW for a specific purpose and are not to be used for any other purpose without the prior written consent of Transport for NSW. Transport for NSW does not provide any warranty, liability arising out of the use of the drawing or any of the related information for any purpose other than the intended purpose. The user assumes full responsibility for the use of the drawing and the related information and is not to be held responsible for any loss or damage arising from the use of the drawing or any of the related information.			
Dimensions: To be read as drawings. The Architect's Discrepancies, Copyright notice.			


FACADE ACCESS MARKUP - PODIUM;

PER MEETING 28/08/19







FACADE ACCESS MARKUP - PODIUM;

PER MEETING 28/08/19



FACADE ACCESS MARKUP - PODIUM;

PER MEETING 28/08/19



INTERNAL ACCESS MARKUP - PODIUM;
PER MEETING 28/08/19

Appendix E

Additional details for Internal Atrium (Zone N6)

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden


Soffit mounted monorail for IRA access. Details and layout to be agreed with Architect.

Soffit mounted monorail for IRA access. Details and layout to be agreed with Architect.

Soffit mounted monorail for IRA access. Details and layout to be agreed with Architect.

Soffit mounted monorail for IRA access. Details and layout to be agreed with Architect.

Mid rise atrium



A 3D architectural rendering of a building facade, viewed from a low angle looking up. The building has multiple floors with a central vertical monorail system. The monorail consists of a series of white, cylindrical carriages connected by a track. Red arrows point from text boxes to specific parts of the monorail system. The building's facade is dark grey with blue-tinted glass panels. The sky is a clear blue.

Soffit mounted monorail for IRA access. Details and layout to be agreed with Architect.


Soffit mounted monorail for IRA access. Details and layout to be agreed with Architect.

Soffit mounted monorail for IRA access. Details and layout to be agreed with Architect.

Low rise atrium

	SMOKE DETECTOR
	RECESSED SPEAKER
	CONCEALED SPRINKLER
	RECESSED SPRINKLER
	EMERGENCY EXIT SIGN
	EMERGENCY LIGHT
	DOWN LIGHT
	LIGHT FIXTURE
	PASSIVE CHILLED BEAM
	ACCESS PANEL

1000 0 2500 5000mm
1:100(A0)



General Notes:

Do not scale from drawing. Use marked dimensions. To be read in conjunction with all other Consultants drawings. The Architect to be immediately notified of any other discrepancies. Copyright on this drawing to be retained by the Architect.

DRAWING COLOUR CODED - PRINT ALL COPIES IN COLOUR

E	North Tower Stage 4 WIP 1	30-08-19	PB/30-08-19	MM/30-08-19
D	North Tower Stage 3 Design	22-05-19	PB/22-05-19	MM/22-05-19
C	Stage 3 Design	10-05-19	PB/10-05-19	MM/10-05-19
B	ARDS1	18-04-19	18-04-19	18-04-19
AND	DESCRIPTION	DESIGNER SIGN./DATE	VERIFIED SIGN./DATE	APPROVED SIGN./DATE
CO-ORDINATE SYSTEM:		HEIGHT DATUM:	SCALE:	



This drawing and the related information have been prepared by, or at the request of, Transport for NSW for a specific purpose and may not be used for any purpose other than the purpose intended by Transport for NSW. Transport for NSW does not provide any warranties and accepts no liability arising out of the use of this drawing or any of the related information for any purpose other than the intended purpose. This drawing is protected by copyright and no part of this drawing may be reproduced in any form without the express written permission of Transport for NSW.			
JPW	JOHNSON PILTON WALKER	DRAWN	Author
		DESIGNED	Peter Blome
		CHECKED	Wayne Dickson
		VERIFIED	Wayne Dickson
		APPROVED	Paul van Ratingen
		DATE	11.04.19
		DATE	11.04.19
		DATE	11.04.19

NOT FOR CONSTRUCTION


SYDNEY METRO - MARTIN PLACE

LEVEL 11 REFLECTED CEILING PLAN
31 RCP

FILE No.	n/a	SHEET:	OF	A0
STATUS:	NORTH TOWER STAGE 4 DESIGN			
DRG No.	CSWSMP-MAC-SMN-AT-DRG-311100	EDMS No.		

	SMOKE DETECTOR
	RECESSED SPEAKER
	CONCEALED SPRINKLER
	RECESSED SPRINKLER
	EMERGENCY EXIT SIGN
	EMERGENCY LIGHT
	DOWN LIGHT
	LIGHT FIXTURE
	PASSIVE CHILLED BEAM
	ACCESS PANEL

1000 0 2500 5000mm
1:100(A0)



General Notes:

Do not scale from drawing. Use marked dimensions. To be read in conjunction with all other Consultants drawings. The Architect to be immediately notified of any other discrepancies. Copyright on this drawing to be retained by the Architect.

DRAWING COLOUR CODED - PRINT ALL COPIES IN COLOUR

D	North Tower Stage 4 WIP 1	30-08-19	PB/30-08-19	MM/30-08-19
C	North Tower Stage 3 Design	22-05-19	PB/22-05-19	MM/22-05-19
B	Stage 3 Design	10-05-19	PB/10-05-19	MM/10-05-19
A	ARDS1	18-04-19	18-04-19	18-04-19
AND	DESCRIPTION	DESIGNER SIGN./DATE	VERIFIED SIGN./DATE	APPROVED SIGN./DATE
COORDINATE SYSTEM:		HEIGHT DATUM:	SCALE:	



This drawing and the related information have been prepared by, or at the request of, Transport for NSW for a specific purpose and may not be used for any purpose other than the purpose intended by Transport for NSW. Transport for NSW does not provide any warranties and accepts no liability arising out of the use of this drawing or any of the related information for any purpose other than the intended purpose. This drawing is protected by copyright and no part of this drawing may be reproduced in any form without the express written permission of Transport for NSW.


DRAWN	Author	11.04.19
DESIGNED	Peter Blome	11.04.19
CHECKED	Wayne Dickerson	11.04.19
VERIFIED	Paul van Ratingen	11.04.19
APPROVED	Paul van Ratingen	11.04.19

NOT FOR CONSTRUCTION

SYDNEY METRO - MARTIN PLACE

LEVEL 14 REFLECTED CEILING PLAN
31 RCP

FILE No.	n/a	SHEET:	OF	A0
STATUS:	NORTH TOWER STAGE 4 DESIGN			
DRG No.	CSWSMP-MAC-SMN-AT-DRG-311400	EDMS No.		



REFLECTED CEILING PLAN LEGEND															
		MOUNT SENSOR													
		EMERGENCY LIGHT													
		SMOKE DETECTOR													
		RECESSED SPEAKER													
		EXPOSED SPRINKLER													
		CONCEALED SPRINKLER													
		RECESSED SPRINKLER													
		EMERGENCY EXIT SIGN													
		EMERGENCY LIGHT													
		DOWN LIGHT													
		LIGHT FIXTURE													
		PASSIVE CHILLED BEAM													
		ACCESS PANEL													
		DRENCHER													

Appendix F


Additional details for Lightwell and bridge (Zone N7 and N8)

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden



Access to top of bridge door to be integrated into level 11 above.
Monorail safety system to be adopted to access the top of the bridge (location to be agreed with architect)

Cleaning to the light well can be with IRA from monorail and access points above (location to be agreed with architect).
Note artwork to be confirmed by Macquarie.
Access to L5 bridge to be via monorails and rope access system, incorporate door to L6 above for access.

South elevation terrace

Appendix G


Additional details for Access within the lift core (Zone N9)

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden


Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden



Lift core, internal face Zone N9

West elevation



Appendix H

Example images of BMU's and Access Equipment (for reference only)


Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Examples – 200 George Street



Surface Design

Examples – 200 George Street


Project: 200 George Street

Supplier:

Jib: Max extended 25m

Obstruction: Parapet maximum height
7m

Surface Design



15.04.2016 10:22

Examples – 200 George Street



Surface Design

Examples – 200 George Street



Surface Design

Examples – 200 George Street



Surface Design

Examples – 200 George Street



Surface Design

Examples – 200 George Street terrace BMU



Surface Design

Examples – 1 Bligh Street



Examples – 1 Bligh Street



Examples – One Central Park



Examples – Aurora Place

BMU

The centralised maintenance system relies on one large crane type Building Maintenance Unit (BMU) located at the main roof level. This is capable of reaching all areas on the facade including both sides of the main sail as well as both sides of all projecting fins.

Weighing in the vicinity of 30 tonnes and operating from a fixed position, the unit sits on a heavy duty track which is located on structural steel supports just below the line of the sloping roof.

The BMU has a telescopic jib which can be extended to 55 metres with a luffing capacity enabling it to luff upward to reach over the main sail. It can also luff below horizontal so as to maintain the minimum 15m unrestrained cable length from the tip of the jib to the first restraint point on the east facade.

The method of restraint for the BMU is via lanyards, so that on the outer

face, sheaves on each lanyard allow a cable to pass through cleanly. On the inner face, a system comprising a nylon rope on separate spool, allows the cradle to be kept against the facade whilst the main support cables are free to move.

By using a 3D computer model of the building's design, the BMU can access all points on the facade below the main roof levels except for the two steps in the north elevation at approximately levels 12 and three. These are served by monorail mounted swing stages.

This is one of the largest units ever made and has to cope with extraordinary challenges such as a sloping roof and an inclined facade.



Surface Design



Surface Design



Project: Aurora Place

Supplier: Cox Gomyl

BMU garage: recessed raised platform

Jib: Max extended 55m

Obstruction: Sail maximum height 30m



Surface Design


Project: Q1 Gold Coast

Supplier: Cox Gomyl

BMU garage: Fixed rail platform

Jib: Max extended 22m

Obstruction: Sail maximum height 30m



Surface Design

Project: Torre Caja Madrid


Supplier: Cox Gomyl

BMU garage:

Jib: Articulated Max extended 55m

Obstruction: Under croft surfaces

Examples – Shanghai World Financial Centre




▲ Figure 2.3.4: This image shows Shanghai World Financial Center's BMUs, which are able to retract into the building to park. © Mori Building

however, despite minor differences, they are similar in functionality.

There are two BMUs for Zone 1 at level 42, the lowest platform launch location (see Figure 2.3.5). These BMUs feature track-mounted bottom slew machines with knuckle crossbars that allow the cradle to be slewed to either the left or right of the jib. They provide access to four drops each, through operable panels provided in the façade.

Two additional track-mounted machines are provided for Zone 2 at level 54 (see Figure 2.3.6). These machines are fitted with a double knuckle jib, which allows the cradle to be slewed to either the left or right of the main jib, and another slewing crossbar (see Figure 2.3.7). The double knuckle jibs and slewing crossbar provide additional flexibility so that these units can access two cradle drops on the vertical face of the building




▲ Figure 2.3.5: Side elevation of the level 42 BMU. © CoxGorriyl



Surface

Examples – Shanghai World Financial Centre



Surface Design

Examples – Evolution Tower, Moscow



Surface Design



Examples – Evolution Tower, Moscow



* Figure 2.8.9: The customized soft rope guiding system is used to provide stabilization for this system's dynamic set of movements. © Global BMU


Surface Design

Examples – Glass replacement



Surface Design

41AM Push Around Vertical Lift



Example EWP

QUESTIONS TO ASK

- What are the ground conditions in the work area?
- What are the floor load requirements and access to the site?
- What is the working height needed for the job?
- Is there 240V AC power available for charging?
- Is indoor and flat hard support surface needed?

KEY SELLING POINTS

- Work in tight and confined vertical areas
- 4 easy fit outriggers with interlock switch and telltale light indicating each outrigger is locked and set
- Base can be levelled on outriggers
- Dual chain vertical mast lift
- Non-marking solid tyres
- 1 x 12V DC deep cycle battery
- Removable SCR automatic battery charger for quick recharging

APPLICATIONS

- Facilities maintenance
- Electricians for lighting tube/globe replacements
- All maintenance work
- Factory fit outs in tight areas
- Ideal warehouse use between racking and narrow aisle areas
- Hospitals, schools and offices for suspended ceiling maintenance

SPECIFICATIONS

Performance:

Platform Height (max.)	12.34m
Working Height	14.34m
Lift Time	130 sec
Lower Time	55 sec
Platform Capacity Standard	135kg

Dimensions:

Stowed Length	1.46m
Stowed Height	2.64m
Height Tilted Back	2.00m
Stabiliser Footprint Length	2.14m
Stabiliser Footprint Width	2.17m

Platforms:

Standard Platform Type	Steel Rail/Alloy Floor
Overall Width	0.74m
Standard Platform Size - (WxL)	0.66 x 0.66m
Chassis Length	1.35m
Platform Entry Height	0.48m

Power:

Power Source	Battery
DC Voltage	12V
DC Power	93 Amp hr

Weights and Capabilities:

GVW AC	499kg
GVW DC	558kg

RAPTOR®

ROPE ACCESS RAIL SYSTEM

SAYFA
PROTECT

1300 301 755
SAYFA.COM.AU

Example monorail
system

ROPE ACCESS RAIL SYSTEM FOR EFFORTLESS MOBILITY

▲ MUST BE READ AND UNDERSTOOD PRIOR TO USE

SYSTEM CONTENTS

In-Action	2
Features	3
Operation	4
Limitations	5
Safe Use Procedure	6
Configurations	14
Maintenance	15
Technical	19
Design	20
Warranty	22
Specifications	23

SYSTEM OPERATION MANUAL



RAPTOR® ROPE ACCESS RAIL

Sayfa Group leads the industry in the design, installation and management of access, fall protection and ground safety systems.

The In-Action model demonstrates access, fall and ground protection requirements for a commercial building design.

Sayfa Group recommendations fulfill current workplace requirements for the safety of building maintenance subcontractors, employees and the general public.

#	DESCRIPTION	
1	3 SIXTY	Fall arrest anchors
2	TRAVEL 8	Roof or wall mount static lines
3	SENTRY	Roof mount guardrails
4	ON-TRAK	Roof walkways (yellow or grey)
5	PROTEX	Skylight protectors
6	RAPTOR	Abseil / Fall Arrest

#	DESCRIPTION	
7	KATT	Modular fixed ladders
8	VISTA	Modular fold down ladders
9	ALTO	Step ladders & step bridges
10	ALTO	Stairs & platforms
11	MODDEX	Handrails & balustrades
12	SKYDORE	Roof access hatches

For more information, please contact Sayfa Group directly.




IT'S THE SAYFA WAY

MULTI OPERATOR RAIL SYSTEM PROVIDING EFFORTLESS LATERAL MOBILITY & EASE OF OPERATION

FEATURES & BENEFITS


LONG SPAN SECTION

Spanning up to 6000mm using long span attachment




T-NUT MOUNT

Connects fixing brackets to rail system




SUSPENSION BRACKET

Provides connection of rail to support structure suspension system



MULTI DIRECTION TROLLEY

Alternative to the standard trolley which can be loaded multi direction




SEALED BEARING TROLLEY

Provides connection point for ropelines




RAIL SPLICE JOINER KIT

Used to join multiple rail sections together



MOUNTING SLOT

Provides adjustable positioning of mounting brackets



END STOP

Provides the trolley termination point




ROPE ACCESS TROLLEY

FOR EFFORTLESS MOBILITY

The robust sealed bearing trolley ensures effortless operator mobility when used as a rope access or fall arrest system. Lateral stabilising bearings allow the trolley to function normally when angled or side loading is required providing unlimited flexibility for positioning the rail to best suit the application and safety of the operator.

PATENTS AND DESIGN REGISTRATIONS APPLY



UNIQUE
PRODUCT FEATURE

OPERATION

MUST BE READ PRIOR TO USE

1. Prior to use, ensure all operating procedures have been read and understood.
2. This rope access system is only to be used by competent persons who have experience and training in the safe use of the system and associated equipment.
3. Ensure all workplace OH&S requirements are identified and understood. A risk assessment with a safe work method procedure must be completed and approved by management prior to work commencing.
4. This system requires periodic inspection and maintenance by a qualified rope access inspector. The system MUST NOT be used if the service date is overdue.
5. A rescue plan must be devised and be ready to be implemented prior to usage of a rope access system.
6. Authorisation to enter any risk area must be obtained from the work place manager prior to accessing.
7. Only approved rope access harness, gear and equipment certified to Australian Standard AS/NZS 4488, to be used with this system.
8. Visually inspect the system for damage prior to use. System must not be used if there is any deterioration or deformation of any components or structure to which the system is attached.
9. If the rope access system is damaged or has arrested a fall, discontinue use until it has been fully inspected and recertified by a competent height safety equipment inspector.
10. Ensure all fixings, fittings and components are securely attached. Any tightening, adjustment or replacement of components must be carried out by a competent height safety inspector.
11. Rope protectors required wherever rope lines pass over an edge.
12. Where rope lines will potentially damage an edge, then an edge protection device will be required to spread rope access loads during operation.
13. Persons must not be allowed to work alone during rope access operations in case emergency rescue assistance or first aid is required.
14. All applicable Australian Standards, OHS Acts & Regulations, and Codes of Practice & Guidelines must be read and obeyed when using this safety system.
15. This user manual does not in any way, replace the need for completion of a recognised rope access training course by a Registered Training Organisation (RTO).

⚠ Failure to follow all warnings, usage and maintenance instructions may result in serious injury or death.



LIMITATIONS

MUST BE READ PRIOR TO USE

1. Only to be used by competent persons with proof of training by a Registered Training Organisation (RTO) in the use of height safety and rope access systems.
2. Harness gear is susceptible to deterioration when exposed to chemicals or hazardous environments and must be approved by the manufacturer for use in these applications.

3. The Raptor rope access rail system is suitable for up to 4 persons per span. See table below:
RAPTOR RAIL SPAN TABLE - ROPE ACCESS

RAPTOR RAIL ONLY			RAPTOR RAIL WITH LONGSPAN SECTION		
No of Users Per Span	Max Span Length	Support Structure Design Load	No of Users Per Span	Max Span Length	Support Structure Design Load
1	4000mm	12kN	1	6000mm	12kN
2	3200mm	18kN	2	5500mm	18kN
3	2500mm	24kN	3	5200mm	24kN
4	2000mm	30kN	4	4200mm	30kN

4. Two attachment points are required per person. Multiple pairs of trolleys are required for additional users. For OH261 or OH273 trolleys, one is required per operator and for OH260 trolley, two are required per operator.

5. Operators of this system must be connected via a certified karabiners and abseil rope lines.
6. The system must be set up so that the operator will not load by more than 20 degrees from the surface to where rail is attached.
⚠ Loading beyond 20 degrees may cause the system to malfunction which could result in injury or death.
7. When the Raptor Rail is set up to be used as a fall arrest system, the retractable lanyard needs to be positioned at least 600mm above the operator's head to ensure correct fall arrest action of the system.
8. Do not tamper with system components.
9. This system is not to be used for tethering or lifting machinery or equipment.
10. The safety system must be recertified by a competent height safety inspector as recommended:
 - Non corrosive/mild environment - 12 monthly
 - Corrosive/harsh environment - 6 monthly (more frequent inspection may be required).

⚠ Sayfa recommends that persons using rope access systems do not work alone in case of an emergency and help is required.
Should any part of the system/equipment have been subjected to abnormal loading, use must be discontinued until replaced/recertified by a competent rope access inspector.



SAFE USE PROCEDURE

STEP 1

Ensure a proper rope access harness is used and once fitted that straps are properly adjusted to ensure firm but comfortable fit.

⚠ **Harness Gear must be certified to Australian Standards AS/NZS 4488**

⚠ **Ensure system (harness and rail) serviceability dates are current.**



STEP 2

Barricade area work zone, to ensure access by unauthorised persons is prohibited.



STEP 3

Ensure that the correct number of trolleys are in rail for number of operators using the system.



STEP 4

Attach working line and safety line to Raptor trolleys via certified karabiners.

⚠ **Ensure working line and safety line are attached separately.**



SAFE USE PROCEDURE

STEP 5

Check all attachment hardware and ropes.

- ⚠ **Rope access must always be done by two operators.**
- ⚠ **Any damage to the system must be reported to the workplace manager and removed or tagged out of service until recertified by a competent height safety inspector.**



STEP 6

Connect rope grab device (backup) to safety line.



STEP 7

Connect descender device to working line.

- ⚠ **Ensure all attachment hardware is correctly and securely attached, prior to moving into a 'Fall Zone'.**



STEP 8

Use a rope protection device wherever rope lines pass over edge.



SAFE USE PROCEDURE

STEP 9

Attach edge protection device (If necessary). See example below.

⚠️ **Required where ropes will likely damage superficial cladding.**



STEP 10

Attach foot strap with rope grab device to safety line.



STEP 11

Step into foot strap and climb over edge.

⚠️ **Operator must ensure the descender and backup device have been positioned correctly with no slack rope line between attachment point and operator.**



STEP 12

Remove foot strap rope grab device from safety line and attach to tool loop on harness.



SAFE USE PROCEDURE

STEP 13

Descend on rope lines to carry out work to be done on facade.

⚠ **Suitable protection maybe required to protect facade being worked on.**



ACCESS OVER EDGE

HIGH PARAPET - Using a portable ladder with parapet hooks

STEP 1

Retrieve portable ladder.



STEP 2

Locate ladder beside rope lines.

⚠ **Ensure hooks locate securely over parapet and base is secure.**



SAFE USE PROCEDURE

HIGH PARAPET (CONT.)

STEP 3

Connect rope grab device (backup) to safety line.



STEP 4

Climb ladder.



STEP 5

Straddle parapet.



STEP 6

Connect descender device to working line.


⚠️ Ensure all attachment hardware is correctly and securely attached prior to moving into a 'Fall Zone'.



SAFE USE PROCEDURE


EAVES GUTTER

When accessing over an eaves gutter use gutter edge protection device, see example below.



GLAZED BALUSTRADE



When accessing over glazed balustrade rope lines must be passed through vertical gap between balustrade panels of not less than 50mm wide, see sample below.




SAFE USE PROCEDURE

ATTACHMENT


OH 260 TROLLEY




OH 261 TROLLEY



OH 273 TROLLEY





NO. OF OPERATORS PER SPAN



SAFE USE PROCEDURE

EXAMPLES OF ABSEIL EDGE PROTECTION DEVICES



CONFIGURATIONS

OH1 RAPTOR RAIL, PURLIN MOUNT - INLINE



OH2 RAPTOR RAIL, PURLIN MOUNT - ACROSS



OH3 RAPTOR RAIL, FLUSH MOUNT



OH4 RAPTOR RAIL, SIDE MOUNT



OH5 RAPTOR RAIL, SUSPENDED



OH6 RAPTOR RAIL SYSTEM, METAL DECK MOUNT




MAINTENANCE

1. This system needs to be checked and recertified by a competent height safety inspector every 12 months for non corrosive environments or 6 monthly for corrosive or harsh environments. (To be determined by specialist depending on severity of surrounding conditions.)
2. Never clean using acids or other chemicals that could damage the system components.
3. The identification label must be completed confirming installation, certification and recertification of the system.
4. Harness gear and equipment must be maintained and stored in a dry, protected area, away from acids and ultra violet rays which cause material fibres to break down and reduce their safety and life expectancy.
5. Any deterioration or damage to the system or equipment must be reported to the person in control of the workplace and relevant corrective action undertaken.
6. Maintenance inspections must be clearly documented. Any non-conformance must be clearly identified and tagged 'Do Not Use' until corrective action by a competent person has been completed.
7. Where the rail system is mounted into concrete using friction fit anchorages and will be loaded in tension during operation, a load test will need to be carried out, to half the design load of the system.

The Raptor Rail System may be configured in 2 different ways:


1. ACCESSABLE STRUCTURE AND RAPTOR ATTACHMENT HARDWARE - VISUAL ASSESSMENT

In this application, all the components and fixings must be checked according to the procedure as set out on the pages 6 to 10. The structure must be capable of the required loads and be certified by an engineer unless it is clear to a competent person that the structure is suitably adequate.



2. NO ACCESS TO STRUCTURE AND RAPTOR ATTACHMENT HARDWARE - LOAD TESTING

(Sayfa always recommends that ceiling hatches are installed for inspection purposes, where possible)



In this application the only way to check the system in accordance with Australian Standards is via a load test. The load test will involve loading the rail to half the design load, (see span table on page 5) onto the trolley, ideally directly under the rail support structure. The rail/trolley can be loaded using a block and tackle system or can be loaded using weights. The load must be held for a minimum of 3 minutes with no failure or evidence of support structure movement of the system.

Frequency of the load testing is dependent on the environment in which the system is installed and should be determined by a competent person.

Recommended minimum testing

- Non corrosive / mild environment - 3 years
- Corrosive / harsh environment - 12 monthly

⚠ Recertification should be based on structural engineer report confirming project installation compliance and suitability.

MAINTENANCE




The checklist below outlines key checking criteria required to ensure the safe use of this system. Any item of concern not shown on the checklist must be noted on the maintenance report and brought to the attention of the workplace manager.

Items ticked PASS - **YES** means they conform with the required checking criteria and are suitable for normal use until the next recertification date. System data plates must be updated showing current check date and next check date.

Item ticked PASS - **NO** means they do not conform to the required checking criteria. These items must be clearly tagged 'Do Not Use' and the required corrective actions put in place. The maintenance report must clearly document all non-conforming criteria.

⚠ This system must be maintained by a competent height safety inspector trained in the safe use and maintenance of this system.






SYSTEM MAINTENANCE CHECKLIST

COMPONENT	INSPECTION CRITERIA	PASS Y / N	CORRECTIVE ACTION	COMPLETION DATE
TROLLEY CODE: OH260/OH261/ OH273 	Check all bearing axles and middle bearing bolts are secure			
	There must be no deformation in the connection plate			
	Make sure bearings do not show signs of wear			
	Trolley must run freely in the track ⚠ Raptor trolley is designed with a 'fail safe' axle arrangement. Should the trolley not run freely and possibly 'jam' inside the rail it is likely that the bearing axle is working loose.			
END STOP CODE: OH265 	Check all bolts/nuts are secure (18Nm)			
	Ensure there is no sign of damage to the end stop			
SUSPENSION COMPONENTS 	Check all bolts/nuts are secure (18Nm) ⚠ Friction fit anchors into concrete will need to be load tested to half the design load and applied for 2 minutes with no sign of movement or failure.			
	Check for any signs of structure break down or damage ⚠ Should the system attachment structure not be accessible, a load test will be required to check correct performance. (See page 9 for structure checking and testing.)			

⚠ A record of system maintenance recertification and necessary repairs must be kept by the workplace manager

MAINTENANCE

SYSTEM MAINTENANCE CHECKLIST

COMPONENT	INSPECTION CRITERIA	PASS Y / N	CORRECTIVE ACTION	COMPLETION DATE
U-BRACKET CODE: OH260.10/20 	Check all bolts/nuts are secure (18Nm)			
	Check for any signs of deformation in the U-bracket			
SPLICE JOIN CODE: OH262 	Check all bolts/nuts/ grub screws are secure (18Nm)			
	Check for any signs of deformation in the splice join			
	Max permissible gap between rail joins - 4mm			
T-NUT CODE: OH264 	Check all bolts/ T-Nuts are secure (18Nm for M10 bolts 25Nm for M12)			
RAIL CODE: OH250 	Check bearing travel flanges on the rail are not bent/ damaged and free from grime			
	Max opening between travel flanges - 19mm			
	Check for signs of excessive load or damage to the rail			
DECK MOUNT BRACKET & PLATE CODE: OH253 	Check min of 3 x 14kg tek screws into roof structure			
	Check min of 9 x 8mm Bulb Tite rivets into roof deck			
	Check min 2 x M14 bolt sets connecting bracket to plate			
	Check angle of rope does not exceed 20°. See diagram			

TECHNICAL

SYSTEM REQUIREMENTS

The worker must wear a certified rope access harness when connected to the Raptor Rail compliant with AS/NZS 4488.

Harness connectors must be rated to at least 12kN. Non-compatible connectors may unintentionally disengage (roll-out). Karabiners supplied with proprietary systems must not be removed or substituted with any other component.


INSPECTION AND MAINTENANCE

Inspection and recertification of abseil systems and equipment is required at least every 12 months by competent person in accordance with manufacturer's specifications and requirements of Australian Standard AS/NZS 4488.


IMPORTANT NOTE

Failure to supply and/or install Sayfa proprietary products in accordance with Australian Standards compliance codes, Sayfa specifications and instructions voids complete system certification and/or warranty.

TYPICAL ABSEIL SET-UP DIAGRAM




TYPICAL ABSEIL OPERATOR DIAGRAM



Code	Description	Minimum ut Strength
A	Primary anchor	12kN
B	Counterweighted anchor (sometimes called a "needle") - temporary	12kN
C	Diversion	12kN
D	Re-anchor (re-belay)	12kN
E	Deviation	6kN
F	Lateral restraint	2kN
G	Improvised using sling (in the cases above, use of a steel column and a lift motor room has been made but sometimes other devices are used) - temporary	12kN
H	Aid route	12kN
I	Edge protection	-
J	Dead weight anchor - temporary	12kN
K	Davit (primary anchor)	12kN

TECHNICAL

IMPORTANT - TYPICAL LOADINGS FOR ABSEIL ROPE LINES




Note: Diagram for illustration purposes only

- All structural loadings/forces on parapets, awnings, sunshades, or canopies to be calculated and authorised by a qualified engineer.
- Any awning, sunshade or canopy less than 3.0M below top of parapet/roof level must be trafficable.
- Any structural componentry required will need to be allowed for and provided by others.
- For any abseiling anchorages placed within 2.0M of fall edge, adequate fall protection must be provided for operator to access and attach safely.
- Adequate protection for sharp or fragile edges to be provided by the abseiler.
- Layout of fall protection and abseil devices is critical.
- All products/systems to comply with relevant Australian Standards; OH & S Regulations and Codes of Practice.
- Any davit system will require engineer's approval.


DESIGN

ABSEIL LAYOUT OPTIONS - PLAN VIEW

OPTION 1




OPTION 2




DESIGN

MOUNTING OPTIONS


OVERHEAD MOUNT



SIDE MOUNT



ROOF MOUNT



TROLLEY OPTIONS


OH 260

Trolley - Standard

- 15kN rated

- 1.5kg

 For overhead applications

 2 trolleys required per operator for rope access use.




OH 261


Trolley - Multi Direction

- 15kN rated

- Dual attachment

- 2.6kg

 For parapet and roof deck mount applications




OH 273

Trolley - Offset

- 15kN rated

- Dual attachment

- 2.6kg

 For wall and floor mount applications



WARRANTY

WARRANTY PERIOD ON THIS SYSTEM - 10 YEARS FROM DATE OF PURCHASE

Should you have a warranty claim as a result of a defect the following procedure must be followed:

Identify the following information:

- The product/system name and code number.
- The date of purchase/installation.
- Installation company details.
- The installation identification number.
- The name of the company using this system.
- A description of the defect/warranty claim.
- The periodic system maintenance report.

Forward the above information
to sales@sayfa.com.au or contact technical
helpline, 1300 301 755.

TERMS & CONDITIONS

- All warranty claims must be made in writing within 14 days of the appearance of the defect.
- Incorrect installation or work done by a non accredited Sayfa system installer will void all warranty rights.
- Systems that have been installed using non proprietary equipment will void all warranties.
- System roof/cladding penetration seals are not covered in this warranty.
- Systems/components that have not been maintained in accordance with manufacturer's/legislative requirements will void warranty.
- Systems used by incompetent persons or use with non compatible accessories ie. harness gear, lanyards, travellers, fall arrestors etc. will void warranty.
- Systems/components used for purposes other than their intended use will void warranty.
- General wear and tear is expected and will depend on the frequency of use and is not covered by warranty.

NEVER HAS SAFETY
IN THE WORKPLACE
HAD A HIGHER PRIORITY

DISCLAIMER

All product specifications and technical descriptions, recommendations and other information provided, are given as general guidance and advice, and are to be read in conjunction with Sayfa Group installation instructions and any other data available and applicable to each particular standard product or system. Use of such data is however the user's sole responsibility, taking into account the intended application and actual conditions existing on the particular worksite. Consequent selection of the right product for any particular use, remains the user's ultimate responsibility. Sayfa Group is therefore not obligated or liable for any direct or indirect, incidental or consequential damages, losses or expenses in connection with, or by reason of the suitability and use of or otherwise, any product or system for any purpose. Implied warranties of merchantability or fitness for any particular purpose, are specifically excluded.

All Sayfa Group products must be installed and used by competent personnel trained in the selection, safe use and maintenance of fall arrest systems and equipment by a registered training organisation (RTO). Installation not in accordance with Sayfa Group requirements or the use of non Sayfa Group components will void all certification and warranties.

Suitability of support structure and design layout of system is the responsibility of the installer and should be verified by a competent person trained by a Registered Training Organisation (RTO) in the selection, safe use and maintenance of fall arrest systems and equipment or approved by a structural engineer to ensure conformance.

Sayfa Group maintains a policy of continuous improvement and development, and therefore reserves the right to modify, amend or otherwise alter product and system designs and specifications, models and part numbers, colours and pricing etc without prior notice. Errors and omissions are excepted, and Sayfa Group accepts no liability for incorrect information, errors or omissions.

TECHNICAL SPECIFICATION

SYSTEM CODE

RAPTOR RAIL SYSTEM - ROPE ACCESS OH 250

TECHNICAL DATA

MATERIALS

- Rail – profiled hi-tensile aluminum
- Trolley – stainless steel including 6 sealed bearings
- Mounting Brackets – profiled stainless steel and/or aluminium
- Mounting Fixings – M12 stainless steel fixings

FIXINGS (into support structure)

- Steel fixing – M12 bolt or threaded stud
 - Concrete fixing – M12 mechanical concrete anchor
- Note: May vary depending on application

WEIGHT

- 4.5kg / per linear metre of rail section

WORKING LOAD LIMIT

- Single person use – 180kg per trolley (user/equipment)
- Maximum horizontal pitch for safe use – 3°
- Support structure integrity, suitability and fixing method to be assessed and determined by a competent person prior to installation

RAPTOR RAIL SPAN TABLE (FOR ROPE ACCESS USE)

RAPTOR RAIL ONLY			RAPTOR RAIL WITH LONGSPAN SUPPORT		
No of Users Per Span	Max Span Length	Support Structure Design Load	No of Users Per Span	Max Span Length	Support Structure Design Load
1	4000mm	12kN	1	6000mm	12kN
2	3200mm	18kN	2	5500mm	28kN
3	2500mm	24kN	3	5200mm	24kN
4	2000mm	30kN	4	4200mm	30kN

COMPLIANCE

Raptor Rail for abseil use is designed to comply with Australian Standards AS/NZS4488 and relevant statutory OHS Codes of Practice/Guidelines. (Refer instruction manual.)

TESTING

Testing and performance based on requirements of Australian Standard

- AS/NZS 4488

PRODUCT WARRANTY

10 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations. (Refer instruction manual.)

INSPECTION AND MAINTENANCE

Inspection and certification every 12 months by a height safety equipment inspector in accordance with manufacturer's specifications and requirements of Australian Standard AS/NZS181.1:2009 (Refer instruction manual.)

IMPORTANT NOTE

Failure to supply and/or install proprietary product in accordance with above standards and codes, specifications and instructions voids complete system certification and/or warranty.





1029 MOUNTAIN HWY
BORONIA VIC 3155
AUSTRALIA

T 1300 301 755
F 1300 881 092
E INFO@SAYFA.COM.AU

FOR MORE INFORMATION
VISIT SAYFA.COM.AU



THE SAYFA GROUP

WE SAVE LIVES!

This is our Mission, and it drives our Vision to BRING EVERY WORKER HOME SAFELY.

Sayfa Group leads the industry in the design, installation and management of access, fall protection and ground safety systems. As an Australian owned company, we engineer and rigorously test our proprietary systems to exceed national and international standards. Simple installation and easy to use systems are our key drivers for ensuring maximum effectiveness, improved safety and compliance with Occupational Health and Safety standards in the workplace.

OUR VALUES

We are governed by the following principles in everything we do:

- A** – Accountability / Totally responsible and answerable for our actions.
- L** – Loyalty / Steadfast and dependable based on our values in our dealings with one another.
- I** – Integrity / Honest and sincere, we do what we say, on time every time.
- V** – Value Driven / Increase what's of value in view of a win win plan for all.
- E** – Enthusiastic / Motivated and inspired to continuously perform better.

COMMITMENT

We are passionate about our work with every product a testament to our commitment of world class safety, quality and performance. Our obligation is to live up to our own high standards as well as those of our customers and stakeholders ensuring total peace of mind.



PRODUCT IS OWNED BY THE SAYFA GROUP.
THE SAYFA GROUP CONSISTS OF:





Example self
retracting lifeline



Miller® Falcon™ Edge Self-Retracting Lifeline

When the Job Takes You to the Edge: Depend on Miller

Do You Know Where Your Edges Are?

In work environments of every variety, edges at height are much more common than people are aware of. Simply look around any construction site and note the many different edges that exist such as edges of a floor, roof or formwork.

Honeywell estimates that as many as 80% of fall-protection users have applications in which a lifeline will come in contact with an edge in the event of a fall. Without protection designed for edges, traditional lifelines risk being severed and the force upon the worker is significantly increased. Bottom line – know where your edges are and ensure you are using the proper fall protection to protect yourself against these dangerous hazards – your life depends on it.



Application images show an anchorage connection with a 5-ft lateral offset and a 5-ft set-back.
See instruction manual for additional information

New Leading Edge Safety Standards

As awareness of this threat is increasingly on the rise, new safety standards have been defined. ANSI Z359.14-2014 & CSA Z259.2.2-17 require leading edge connecting devices to meet criteria such as:

- Edge radius as sharp as 0.005 in (0.13 mm) (ANSI) & 0.010 in (0.25 mm) (CSA)
- Safe for users connected at foot level
- Used anytime the device is anchored below the harness back D-ring (CSA)
- Requires an integral shock-absorber attached to the end of the lifeline connected to the worker

The Versatility You Need. The Safety You Depend On.

Designed for performance in edge applications, Falcon Edge SRLs offer versatility, reliability, and maximum safety.

Safe

- Designed for sharp edge applications with an edge radius of ≥ 0.005 in (0.13 mm)
- Provides protection in applications that require anchoring at foot level
- Meets many stringent safety standards, including ANSI Z359.14 SRL-LE & CSA Z259.2.2 Class SRL-LE

Versatile

- **Perfectly suits your personal profile, with the capacity to support user weights up to *420-lbs. in all connections at foot level and above** (*up to 375-lbs. Canada only)
- Provides protection for all working at height situations – horizontal, vertical, mounted overhead, anchored at foot level and work near edges
- Available in 20, 30, and 50-ft. working lengths to cover a wide range of applications
- **Models available for welding applications include a shock absorber cover that is flame retardant and resistant to weld splatter**

Reliable

- **Durable design with corrosion resistant internal components extend service life and lowers cost of ownership**
- **Up to 30% lighter than competitive models for easier installation and transportation to reduce worker fatigue and increase productivity**
- Thicker galvanized cable (7/32") increases durability to lower cost of ownership
- **Equipped with RFID for efficient asset and inspection tracking**
- Repairable with quick turnaround time, lowers cost of ownership and increases productivity

* Rated for up to a 375-lbs. (170 kg) user in all connections when tested to CSA Z259.2.2-17



- ① **Steel Double Locking Carabiner**
Steel carabiner (and tagline) included for **easier connection and installation.**

- ② **Built-in Handle**
Built-in, ergonomically-designed molded handle on 30-ft. & 50-ft. models **provides easy installation and transportation**

- ③ **Dual Swivels**
Dual swivels at top of unit and on snap hook **increase mobility** and minimize lifeline from twisting during use

- ④ **High Impact Resistant Nylon Housing**
Withstands the harsh rigors of the toughest applications for **increased durability to extend service life and to lower cost of ownership**

- ⑤ **Unique Side Payout Design**
Reduces wear on the entry guide bushing and cable providing smooth operation with less drag to **increase user mobility.** Internal entry guide bushing and roller prevent cable from cutting into housing for **increased durability**

- ⑥ **Integral Shock Absorber**
Integral shock absorber connected to the worker ensures the lifeline is kept intact if a fall were to occur over an edge to **increase safety**

- ⑦ **RFID Technology**
RFID for **easy and efficient asset tracking**

- ⑧ **Durable Shock Absorber Cover**
Ballistic nylon shock absorber cover for **increased durability** (flame retardant shock absorber cover for welding applications also available).

Miller® Falcon™ Edge Self-Retracting Lifelines

Galvanized Steel Cable Lifeline with Integrated Shock Absorber, Carabiner, and Tagline.

SKU	Length	Lifeline Connector	Unit Weight (Lbs.)
MP20G-LE	20-ft. (6 m)	Steel Locking Swivel Snap Hook	11.0 lbs. (5 kg)
MP30G-LE	30-ft. (9 m)		14.3 lbs. (7 kg)
MP50G-LE	50-ft. (15 m)		17.4 lbs. (8 kg)

Galvanized Steel Cable Lifeline with Integrated Shock Absorber with flame retardant cover for welding applications, Carabiner, and Tagline.

SKU	Length	Lifeline Connector	Unit Weight (Lbs.)
MP20G-LEK	20-ft. (6 m)	Steel Locking Swivel Snap Hook	11.0 lbs. (5 kg)
MP30G-LEK	30-ft. (9 m)		14.3 lbs. (7 kg)
MP50G-LEK	50-ft. (15 m)		17.4 lbs. (8 kg)

Honeywell has your back with a full range of leading edge self-retracting lifelines and personal fall limiters, including the Miller® TurboLite™ Edge Series.



Limitless Possibilities. Ask the Expert.

Technical Service: 800.873.5242
www.millerfallprotection.com

Honeywell Industrial Safety

900 Douglas Pike
Smithfield, RI 02917

USA:

Phone: 800.430.5490

Fax: 800.322.1330

www.honeywellsafety.com



Canada:

Phone: 888.212.7233


Fax: 888.667.8477

LMFEB
© 2017 Honeywell International Inc.

Honeywell



Ultimate Design Load 15kN



NOT FOR CONSTRUCTION

All Hot Dip Galvanized or 316 Stainless Steel

Example loop box

Vertical Rope Access Anchor Point "Loop-Box"



Karabiner
P. 1300 222 300
e. info@karabiner.com.au
w. www.karabiner.com.au

This information remains at all time the property of Hangard Group Pty Ltd (karabiner) and is not to be copied or transmitted in any format without written consent of Hangard Group Pty Ltd

DRAWN	ABDUL	SCALE: VARIES	DRAWING No.	PLOT DATE	REV.
CHECKED	AF	Job No A1215	01	000	04
DATE	04.12.2009				

Example

Horizontal anchor device ALTIRAIL

- ▲ Sales brochure
- ▲ Technical data sheets
- ▲ Conformity
- ▲ Operating instructions
- ▲ Identification and check sheets

Horizontal fall arrest rail system **ALTIRAIL**




Photo Credit VERTIC NL

PRODUCT ADVANTAGES

- ▲ Ideally suited for use in raised installation, on the under-surface of the roof, or when the fall clearance is incompatible with a cable system
- ▲ Ideal for working at a distance, or in association with a high weight block
- ▲ Various routes may be used, thanks to the switch which enables continuous movement
- ▲ Reduced height of fall owing to the rigidity of the system
- ▲ Can be installed on the majority of the roofs, thanks to the ALTIFIX supports suitable for the rail system

Can be specially bent upon request



Several possible uses



Lateral circulation



Circulation on the top of the rail



Overhead position

Recommendations for use



Maxi 2 users
per interval

D = 4 meters for using the rail only as a fall arrest system

D = 2 meters recommended for suspension use

Ball bearing carriage

The mobile VERTIC carriage is made to roll under load. It allows mobility when working in suspension, or associated with a self-retractable lanyard.





R.CF3



ALTIRAIL/CABLE combined configuration

For special applications where there is no support available, the rail may be attached to a cable.



MOTORIZED SWITCH

Ensures the safety of warehouses with a significant height. The switch can be used and activated at a distance thanks to a remote control.




COMPOSANTS ALTIRAIL®

Aluminium rail

Supplied in 3m length, drilled and milled.

R.RAIL3



R.AIG3D/R.AIG4D



Switches

Allow a continuity of movement, and the change of circulation of the carriage. Available in 3 or 4 directions.

Entry/Exit piece for carriage

Can be installed at any location on the rail, to allow the installation of the different carriages.

R.RO



R.CF2



Rail carriage with rollers

The mobile VERTIC carriage is fitted with multiple rollers to provide perfect movement, whatever position is used.


Retractable end stop

This end stop enables the carriage to be fitted at the end of the rail. Automatic locking.

R.BE



R.A90E/R.A90S



90° corner for lateral movement

Interior or exterior angle to allow the carriage to circulate sideways.

Fixed end stop

Blocks the carriage at the end, securing the system. Finishes the extremity of the rail nicely.

R.EXTF



R.A90S2 / R.A90E2



90° corners for movement on under surface

Interior or exterior angle to allow the carriage to circulate under-surface.


Rail coupling block

Allows assembling two lengths of rails. The 4 pins ensure a perfect lining up of the rail.

R.ECL



R.EQ-G



Mounting angle

Allows mounting the rail on a facade, when circulation is done under-surface.

Opening support

Made of copper-aluminium, it facilitates the fitting and removal of the rail. Also permits free expansion of the rail.

R.SUP



R.PS



Safety sign

Must be installed at the access of the system. Allows the identification and the control of the system.



TECHNICAL DATA SHEETS

TECHNICAL DATA SHEET : ALTIRAIL


(16/02/16)

ALUMINIUM RAIL R.RAIL (3/1/1.5)

Product picture



Product technical drawing



Technical features

- Material properties : Aluminium 6060 T5
- Standard finish : natural
(optional anodized finish upon request
Ref R.PVA)
- Standard length : 3m
(other possible lengths : 1m, 1,5 m)
- Weight : 2.07 kg/ml (therefore 6.2kg for L=3m)


Advantages

- Custom bending possible.
- Specific lengths cuts can be done in our workshop
(upon order).
- Cutting and drilling on site is possible using the
specific tool, ref.: R.OUTIL

Assembling features

- Span between supports recommended = 4 meters.
- This distance will be reduced to 2 meters for an
installation dedicated to work in suspension.
- The 4 grooved pins in the peripheral holes ensure a
perfect alignment of the rails at junctions.

Installation application



**Drilling with 8.5 mm drill bit
Milling with 16.5 mm to 90°mm drill**


TECHNICAL DATA SHEET : ALTIRAIL

(16/02/16)


ENTRY/EXIT PIECE FOR RUNNER

R.RO

Product picture



Product technical drawing



Technical features

- Material properties of opening part : stainless steel
- Material pins : Steel with Geomet treatment
- Weight : 1kg


Advantages

- Allows the connection of the carriage on the location selected.
- Also used as rail connector plate.

Assembling features

- Attached between 2 rail parts instead of the connector plate (ref R.ECL).

Installation application




RETRACTABLE END STOP R.BE

Product picture



Product technical drawing



Technical features

- Material properties :
Flanges : aluminium
Jointbars : acier traité Geomet
Bolts : Geomet treated steel
- Weight : 700 g
- Breaking resistance > 2200daN


Advantages

- Automatic closure of the end stop.
- Its ergonomic design allows ease of use in all configurations of rail installation.
- Easy of installation.

Assembling features

- The R.BE is sold with the jointbar system.
- Attached directly to the rail extremity with double drilling, using the 4 M8x14 FHC bolts provided.

Installation application



TECHNICAL DATA SHEET : ALTIRAIL


(16/02/16)

FIXED RAIL END STOP R.EXTF

Product picture



Product technical drawing




Technical features

- Material properties :
 - End stop : PU (plastic)
 - End piece : Composite
 - Bolts : Stainless steel
 - Weight : 80 g

Advantages

- The endpiece allows perfect finishing of the rail end.
- 2 PU stops and 2 stainless steel spacers are blocking the runner at the extremity, to secure the system.

Assembling features



Installation application




RAIL JOINT BAR R.ECL

Product picture



Product technical drawing



Technical features

- Material properties : steel with Geomet treatment
- Pre-coated bolts with thread lock substance
- Weight : 450 g


Advantages

- The position of the splice plate relative to the supports does not matter because of its stiffness and strength.
- The 4 grooved pins ensure perfect alignment of the rails.
- The bolts are pre-coated with thread lock, providing a reliable security against loosening.

Assembling features

- The rails have two sets of 4 milling holes at each end for a quick and simple mounting.
- Attached with 8 M8x14 FHC bolts that lodge in the milling holes.

Installation application



TECHNICAL DATA SHEET : ALTIRAIL


(16/02/16)

RAIL SUPPORT R.SUP

Product picture



Product technical drawing



Technical features

- Material properties : cupro-aluminum
- Finish : grey painting
- Weight : 750 g

Advantages

- Corrosion resistant.
- The rail is free to expand.
- Possible installation in any positions.

Installation application

- The R.SUP is made of 2 pre-assembled parts with 2 CHC M8x30 bolts and 2 lock nuts.
- Attached with M12 bolt (not supplied).

Maximum span between 2 supports recommended:

- 4 m for safety
- 2 m for suspension work

Installation application

2 CHC M8x30 stainless steel bolts


R.SUP part 1

4 centring pins

M12 anchor hole

R.SUP part 2

2 lock nuts




3 DIRECTION SWITCH R.AIG3D

Product picture



Product technical drawing



Technical features

- Material properties :
 - Central block : Aluminium
 - Support : Stainless steel
- Weight : 8 Kg


Advantages

- The 3D switch allows a circulation of the operator in all directions without ever disconnecting from the fall arrest system.
- The manual rotation of the central block is easy.
- The indexing system positions correctly the switch for a good circulation of the runner.

Assembling features

- Can be installed directly on a concrete support or on steel by 2 M12 fixings.
- Can also be installed on posts PST1 or ALTIFIX.

Operating principle




MOBILE RUNNER R.CF2

Product picture



Product technical drawing



Technical features

- Material properties :
 - Body : aluminium
 - Axis and shackle : stainless steel
 - Rollers : cupro-aluminium
- Finish : black anodization
- Weight : 420 g
- Exceed EN 795D : 2012 standard


Advantages

- The one-piece body with two safety hooks ensures a high level of security.
- The combination of two types of rollers allows good circulation of the runner in all installation configurations.

Using features

- The runner can be left permanently on the rail or connected on the end part of this one, thanks to a retractable end stop.

Exploded view



TECHNICAL DATA SHEET : ALTIRAIL


(16/02/16)

BALL BEARING RUNNER R.CF3

Product picture



Product technical drawing



Technical features

- Material properties :
 - Body : serie 7 aluminium
 - Axis and shackle : Stainless steel 316L
 - Ball bearings : stainless steel 316L
- Finish : orange anodizing
- Weight : 370 g
- Exceed standard : EN 795D : 2012


Advantages

- Runner intended to run under loads.**
- Provides a great mobility when working in suspension, or associated with self retractable lanyards.
- Totally compatible with all products from the range ALTIRAIL.

Using features

- The runner can be left permanently on the rail or connected thanks to an optional opening system. It can also be connected with a retractable end stop attached at the end of the rail.

Using application



TECHNICAL DATA SHEET : INTERFACES


(16/02/16)

STEEL ANGLE BRACKET R.EQG

Product picture



Product technical drawing



Technical features

- Material properties : hot-dipped galvanised steel
- Weight : 0.765 kg

Advantages


- The R.EQG allows façade installations.
- Long slot of 20 mm enables installation adjustment in the attachment hole.

Product compatibility


- Can be used with VERTIC systems : BATILIGNE and ALTIRAIL.
- Installed with M12 bolt on metal structures or adhesive bolts in concrete.

Installation applications

With **BATILIGNE** system



With **ALTIRAIL** system



TECHNICAL DATA SHEET : ALTIRAIL

(16/02/16)

SAFETY SIGN AND LABEL R.PS

Product picture



Panel 1 : « Compulsory PPE »

Product Labels



Panel 2 : « Rail labels »

Technical features

- Matériel properties of panel 1 : expanded PVC 3 mm
- Matériel properties of panel 2 : aluminium
- Weight : 76 g

Advantages


- 13 mm diameter hole for fixing with M12 bolts.
- Several languages included in the kit.

A full kit includes:


- 1 panel « Compulsory PPE » to be installed at the access point near the system.
- Several sticking labels « languages » to be chosen among several languages.



- 1 pannel « Rail labels » including 3 « systems » labels to chose from, to install directly at the access point near the system.




Installation application



Example ladder
hook

SAYFA
systems

KATT[®]
LADDER SUPPORTS



Wall Mount



Gutter/Parapet Mount

KATT[®] LADDER SUPPORT BRACKETS

Katt Ladder Support Brackets are designed to provide a secure attachment point for portable ladders when accessing a roof. The support bracket prevents movement of portable ladder in any direction.

- > Simple installation using standard fixings
- > Prevents sideways movement and ladder foot slip
- > High strength stainless steel construction
- > Low aesthetic profile, minimal visual impact

SPECIFICATION CODE

Katt Ladder Support Bracket (LD401) – Wall Mount type

Katt Ladder Support Bracket (LD402) – Gutter & Parapet Mount type

Specification Summary

Supply and install the Katt Ladder Support Bracket as per manufacturer, Sayfa Systems, recommendations. Support bracket to incorporate ladder tie off points and variable fixing location penetrations. The support bracket must be adaptable to varied locations with allowance for specific profiling of the bracket attachment plate to suit the application. (Refer instruction manual.)

System Applications

- > Portable ladder anti slip device for personnel accessing roofs and other areas for maintenance

Technical Data

Material

Profiled stainless steel (with option for powder coating)

Dimensions

Length – 470mm (profiled section)

Width – 150mm (profiled section)

Weight

Wall mount – 2.30kg

Gutter/Parapet mount – 3.70kg

Fixings

Timber fixing – 14g type 17 Tek screw

Metal fixing – M8 stainless steel bolt set

Concrete fixing – M8/ 75mm mechanical concrete anchor

Metal roof deck fixing – 8mm construction grade Bulbrite rivet

Composite panel fixing – 8mm construction grade Bulbrite rivet (Refer instruction manual.)

Working Load Limit

Recommended for single person use with approved portable ladder – max user weight 120kg.

- > Support structure integrity, suitability and fixing method to be assessed and determined by a competent person prior to installation.

Compliance

Katt Ladder Support Brackets are designed and manufactured generally in accordance with requirements of Australian Standards AS1657:1992 and AS/NZS1891.4:2009 and relevant statutory OHS Codes of Practice/Guidelines.

Testing

Testing and performance based on single person use (max 120kg) using an Australian Standards approved portable ladder.

Product Warranty

3 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations. (Refer instruction manual.)

Inspection and Maintenance

Visual inspection for any damage or loose fixings must be done periodically and prior to use. No certified maintenance required. Basic wear/tear preventative maintenance is recommended, as per manufacturer's specifications and recommendations (Refer instruction manual.)

Important Note

Failure to supply and/or install proprietary product in accordance with above specification and installation/usage guidelines voids complete system certification and/or warranty.

Technical Support

Sayfa Systems

T \ 1300 301 755

F \ 1300 881 092

E \ technical@sayfa.com.au

W \ www.sayfa.com.au

Designed and manufactured by Sayfa Systems

KARARAIL

Operating Instructions



Horizontal Anchor Device System

Compliance: The KARARAIL system complies with:

Certificate issued by:




EN 795-D : 2012
+ CEN TS 16415 :2013



DEKRA EXAM GmbH
Prüflaboratorium für
Bauteilsicherheit
Dinnendahlstraße 9
D-44809 Bochum
Allemagne


Parts Lists



R.RAIL1,5 R.RAIL3		R.A90S		R.R0	
R.EXTF		R.A90E		R.CF3	
R.BE		R.A90S2		R.CF2	
R.ECL		R.A90E2		R.CB2	
R.aig3D		R.ASPECIF		R.PS	
R.aig4D		R.SUP			

KARARAIL

Markings



1. A sign specifying that personal protective equipment against fall from a height must be worn at all times is placed at the rail's access.
2. A sign is fixed on the fall arrest rail with the following information:
 - System name
 - Product description
 - Standard
 - The system's identification number
 - Pictogram: read manual!
 - Maximum number of people that can connect simultaneously.
 - Manufacturer's name.
3. Badge indication the periodic inspection's date and the location of the badge on the safety sign.
(4A, B and C) Trolley Marking.

Operating Principle

Maximum 2 users between supports.

Maximum 4 m pole distance reduced to 2m for work in suspension.


The KARARAIL system has been designed and certified to be used with the trolley ref. R.CF2, R.CF3 and R.CB2.

Insertion of the trolley on the rail with a retractable end stop R.BE (1a) or with an entry / exit piece R.RO (1b).
(2a & 2b) Connection of the fall arrest link (Complaint to EN 353-2, EN 355 or EN 360) with a connector complaint to EN 362.

(3) Once connected to the rail, the trolley moves freely along the support, in both directions. Unhooking won't be necessary to get over the intermediate and angle parts.

(4) Switch use.

WARNING: Before disconnecting of the KARARAIL system, the operator must ensure to be safe: area of collective protection or connected to another fall arrest system.





Information

These instructions are designed for the KARARAIL system's users. Before use, they must be read and understood. Should a doubt, a problem in understanding or a problem that is not dealt with in this document arise, please refer to a VERTIC representative or to VERTIC's technical services. These instructions must be always at the user's hand. If the product is sold outside of the first country of destination (France) it is crucial for the user's safety that the seller provides the operating instructions, the instructions regarding maintenance, periodic checks and repairs that must be drafted in the language of country where the product is to be used. Any activity at height is dangerous and can cause accidents, severe or fatal injuries. You are liable for the use and for the training to the use of the appropriate equipment. Before using the product, the information contained in these operating instructions must therefore be read and understood. The failure to comply with any of the warnings contained herein may cause severe or fatal injuries. For security reasons, the user must be in good health, and must not be under the influence of medicines, alcohol or drugs. Workers using a piece of personal protective equipment must have been appropriately trained, in compliance with the European directive 89/656, Section II, Article 4, §8.

Operating Instructions

Technical Description

The KARARAIL system is a horizontal (max. inclination 15°) rigid anchor support compliant to the EN 795:2012 standard and CEN/TS 16415:2013.

This system is designed to arrest the fall of one or several workers and should not be used for carrying heavy duty.

It is designed for a maximum of 2 users between 2 supports (maximum 4 m pole distance reduced to 2 m for work in suspension).

The KARARAIL system must be used with appropriate equipment and limiting the dynamic force exerted on the user to a maximum of 6 kN.

The user should wear an integral safety harness compliant to the EN361 standard.

The user connects to the KARARAIL's system with a trolley type R.CF2, R.CF3 or R.CB2 (one runner per user).

Important – Prevention:

Before any use

At height, your life depends on the equipment you use. Any doubt regarding the device safety must be reported to the manufacturer and to the installation manager.

The durability of the support should be verified according to the use.



A rescue plan must be implemented to face any emergency that may occur during work.

The KARARAIL system must preferably be located above the user.

The stopping distance of the used fall arrest link must be compatible with the clearance available on site.

When an adjustable link is used, the worker must optimize its length so as to limit the possible fall height and to reduce the risk of pendulum movement.

Calculation of the Necessary Fall Clearance (NFC):

Rail deflection (approx.. 1 m)

+ Lanyard length LL

+ Lanyard energy absorber deployment DLAbs

+ User height t (usually 1.80m)

– Rail height H

+ Safety distance 1m

= Necessary Fall Clearance

Use the KARARAIL system with the following PPE against fall from a height:

- EN 355 compliant lanyards with shock absorber
- EN 353-2 mobile rope fall arresters
- EN 360 compliant retractable type fall arresters
- EN 358 and EN 361 compliant full body harnesses and work positioning belts

Control – Checks

Check that the safety rail's operating instructions are put up on the provided sign.

Check that the fall arrest system you have is compliant and compatible with those recommended for the use of the KARARAIL system.

Check that the controls and periodic maintenance of the rail system are up to date (see image (3)).

Visually and functionally check the whole rail system. To do this, use the KARARAIL system's identification and verification card.

After a fall, the rail must not be used before being controlled and being brought back into conformity by a person authorized by the manufacturer.

Service Time - Disposal

For the VERTIC products made of plastics and textile, the maximum service life is 10 years from the date of manufacture. The service life is not limited for metal products.

ATTENTION: an exceptional event can lead to a disposal of the product after only one use (operating type and intensity, operating environment: aggressive environments, marine environment, cutting edges,



extreme temperatures, chemicals, etc.)

A product has to be disposed of when:

- It is more than 10 years old and is made of plastics or textile,
- It has been subjected to an important fall (or effort),
- The outcome of the product checks is not satisfactory,
- You doubt this reliability,
- You don't know its complete operating history,
- Its use has become obsolete (legal, standard, technical changes or incompatibility with other devices, etc.).

These products must be destroyed to avoid future use.

System Receipt and Guarantee

The product guarantee begins at the delivery date of the material or the completion date from Vertic. It lasts 10 years subject to the annual maintenance has been performed by Alpik or any other company approved by VERTIC. VERTIC warrants this product against defects in materials or workmanship. Are excluded from the guarantee: normal wear, oxidation, modifications or repairs, improper storage, poor maintenance, damage due to accidents, negligence, and uses for which this product is not intended.

Maintenance and Overhaul

Any modification or addition to the equipment is forbidden without the manufacturer's prior written consent.

Any repair of the system components must be done in compliance with VERTIC's procedures. In case of doubt regarding the product's state, replace it by a genuine VERTIC part.

A dirty product must be washed and rinsed with water, and then dried. It must not be put into contact with corrosive or aggressive materials and must not be stored at extreme temperatures. Any chemical product or solvent can affect the system components' resistance. If the equipment may be in contact with such products, please let us know the exact names of the chemical components and we will tell you what to do after an adequate study.

VERTIC guarantees this product against any material or manufacturing defect. The following are excluded from the guarantee:


normal wear, oxidation, changes or repairs, bad storage, bad maintenance, damages due to accidents, negligence or uses for which the product is not designed.



It is advised to have an authorized person check the KARARAIL safety system state at least once a year in the strict respect of VERTIC's procedures. Such periodic and regular checks are necessary because the user's safety is linked to the continuous efficiency and resistance of the equipment. The control and its results must be filed in a maintenance manual through the identification and verification card provided by VERTIC. The ALPIC company can also care about these maintenance and verification operations



Example glass manipulator





Example rope restraint
points for IRA



Example EWP's, scissor lift and knuckle boom

Example spider boom
EWP





WATERFED POLE REACH GUIDE

SWIFT

45ft, 55ft, 65ft and 80ft
poles

Mini Pole (9ft)
(perfect for abutting
& cradle work)

Glyder

25ft, 30ft, 35ft and
40ft poles

GRATER

17ft, 21ft, 24ft, 28ft
and 32ft poles

Appendix I

Codes and standards

The design and installation of a façade access system needs to comply with the following Codes, Standards and Guidelines as a minimum:

Workcover - Guidelines For Building Façade Access Systems (or equivalent)

Access from fixed or portable structures:

AS 1657 Fixed platforms, walkways, stairways and ladders - Design, construction and installation.

AS/NZS 4576 Guidelines for scaffolding.

AS/NZS 1892 Portable ladders.

Personnel Lifting Equipment

AS 2550.10 Cranes-safe use, Part 10: Evaluating work platforms.

Industrial Rope Access

AS/NZS 4488.1 Industrial rope access system, Part 1: Specifications.

AS/NZS 4488.2 Industrial rope access systems, Part 2: Selection, use and maintenance.

Industrial Rope Access Association IRAA - Industry Code on Industrial rope access technique - September 2000.

Fall Arrest System

AS/NZS 1891.1 Industrial fall-arrest systems and devices, Part 1: Safety belts and harnesses.

AS/NZS 1891.2 Industrial fall-arrest systems and devices, Part 2: Horizontal lifeline and rail systems.

AS/NZS 1891.3 Industrial fall-arrest systems and devices, Part 3 Fall-arrest devices.

AS/NZS 1891.4 Industrial fall-arrest systems and devices, Part 4: Selection, use and maintenance.

Safe Work Australia – Code of practice: Managing the risk of falls at workplace

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden

Formatted: Font: 7 pt

Formatted: Font: 7 pt, Not Hidden