

**snowyhydro**

**Jacobs**

## Hunter Power Project - Final Design

Updated Air Quality Impact Assessment

Rev 3

4 August 2022



## Hunter Power Project - Final Design

Project No: IS354501  
Document Title: Updated Air Quality Impact Assessment  
Document No.: Hunter Power Project  
Revision: Rev 3  
Date: 4 August 2022  
Client Name: Snowy Hydro Limited  
Project Manager: K Ivanusic  
Author: M Pickett  
File Name: IS354501\_Detailed design\_Air Quality Assessment\_rev3

Jacobs Group (Australia) Pty Limited  
ABN 37 001 024 095  
Level 4, 12 Stewart Avenue  
Newcastle West, NSW 2302  
PO Box 2147  
Dangar, NSW 2309  
Australia  
T +61 2 4979 2600  
F +61 2 4979 2666  
www.jacobs.com

© Copyright 2021 Jacobs Group (Australia) Pty Limited. The concepts and information contained in this document are the property of Jacobs. Use or copying of this document in whole or in part without the written permission of Jacobs constitutes an infringement of copyright.

Limitation: This document has been prepared on behalf of, and for the exclusive use of Jacobs' client, and is subject to, and issued in accordance with, the provisions of the contract between Jacobs and the client. Jacobs has relied upon, and presumed accurate, information provided by the client and/or from other sources. Except as otherwise stated in the report, Jacobs has not attempted to verify the accuracy or completeness of all such information provided. Jacobs accepts no liability or responsibility whatsoever for, or in respect of, any use of, or reliance upon, this document by any third party.

### Document history and status

| Revision | Date       | Description | Author                 | Checked               | Reviewed | Approved   |
|----------|------------|-------------|------------------------|-----------------------|----------|------------|
| Rev 1    | 24/06/2022 | Draft       | S Putland<br>M Pickett | M Pickett             | M Luger  |            |
| Rev 2    | 28/07/2022 | Final draft | S Putland              | M Pickett<br>T Colman | M Luger  |            |
| Rev 3    | 04/08/2022 | Final       | S Putland              | I Smith               | M Luger  | K Ivanusic |

## Contents

|                                                                                    |            |
|------------------------------------------------------------------------------------|------------|
| <b>Glossary</b> .....                                                              | <b>vi</b>  |
| <b>Executive summary</b> .....                                                     | <b>vii</b> |
| <b>1. Introduction</b> .....                                                       | <b>1</b>   |
| 1.1 Project overview .....                                                         | 1          |
| 1.2 Air quality context .....                                                      | 2          |
| 1.3 Performance outcome .....                                                      | 2          |
| 1.4 Secretary's Environmental Assessment Requirements (SEARs) .....                | 3          |
| 1.5 Report structure.....                                                          | 3          |
| <b>2. Project description</b> .....                                                | <b>4</b>   |
| 2.1 Overview .....                                                                 | 4          |
| 2.2 Site layout .....                                                              | 4          |
| 2.3 Site activity .....                                                            | 6          |
| 2.4 Gas Turbine air emissions .....                                                | 9          |
| 2.5 Air emissions inventory.....                                                   | 11         |
| 2.6 Construction activity .....                                                    | 12         |
| <b>3. Air quality standards</b> .....                                              | <b>14</b>  |
| 3.1 Overview .....                                                                 | 14         |
| 3.2 NSW Protection of the Environment Operations Act 1997 .....                    | 14         |
| 3.3 NSW Protection of the Environment Operations (Clean Air) Regulation 2010 ..... | 14         |
| 3.4 NSW ambient air quality impact assessment criteria.....                        | 15         |
| 3.5 National Environment Protection (Ambient Air Quality) Measure .....            | 16         |
| <b>4. Existing environment</b> .....                                               | <b>17</b>  |
| 4.1 Local setting.....                                                             | 17         |
| 4.2 Sensitive receptors .....                                                      | 18         |
| 4.3 Local meteorology .....                                                        | 18         |
| 4.4 Existing air quality.....                                                      | 21         |
| <b>5. Assessment methodology</b> .....                                             | <b>29</b>  |
| 5.1 Overview .....                                                                 | 29         |
| 5.2 Substances for assessment .....                                                | 29         |
| 5.3 Capacity factor .....                                                          | 29         |
| 5.4 Meteorological modelling .....                                                 | 29         |
| 5.5 Calpuff modelling.....                                                         | 31         |
| 5.6 Peak-to-mean ratio.....                                                        | 32         |
| 5.7 NO <sub>x</sub> to NO <sub>2</sub> conversion: OLM technique .....             | 33         |
| 5.8 NSW EPA ozone assessment .....                                                 | 33         |
| 5.9 Airborne particulate matter .....                                              | 34         |
| <b>6. Results</b> .....                                                            | <b>35</b>  |
| 6.1 Overview .....                                                                 | 35         |

|     |                                                                   |    |
|-----|-------------------------------------------------------------------|----|
| 6.2 | Calpuff results for carbon monoxide .....                         | 36 |
| 6.3 | Calpuff results for sulphur dioxide.....                          | 40 |
| 6.4 | Calpuff results for particulate matter as PM <sub>2.5</sub> ..... | 45 |
| 6.5 | Calpuff results for nitrogen dioxide.....                         | 48 |
| 6.6 | Calpuff results for hydrocarbons (VOCs).....                      | 53 |
| 6.7 | Ozone assessment.....                                             | 56 |
| 6.8 | Plant start-up and shut-down.....                                 | 59 |
| 7.  | <b>Conclusion</b> .....                                           | 61 |
| 8.  | <b>References</b> .....                                           | 63 |

#### Appendix A. Power Station Arrangement – OCGT F-Class Layout

#### Appendix B. Comparisons of Meteorological Data

#### Appendix C. Environmental Representative Endorsement

### List of figures

|                                                                                                                                                                |    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Figure 2-1: Regional Setting of Project (star indicates approximate location of the Project Site).....                                                         | 4  |
| Figure 2-2: Project Site Layout (refer Appendix A for further detail).....                                                                                     | 5  |
| Figure 2-3: Aerial View of Aluminium Smelter prior to demolition to North-East (M. Pickett; 6 March 2005) .....                                                | 6  |
| Figure 2-4: Schematic of Simple (or Open) Cycle Gas Turbine.....                                                                                               | 7  |
| Figure 4-1: Air quality study area with terrain elevation contours and sensitive receptors.....                                                                | 17 |
| Figure 4-2: Annual wind roses: EPA Beresfield 2015-2019.....                                                                                                   | 20 |
| Figure 4-3: Map of DPIE air monitoring stations in Lower Hunter.....                                                                                           | 22 |
| Figure 4-4: Measured 24-hour average PM <sub>2.5</sub> concentrations at Beresfield .....                                                                      | 24 |
| Figure 4-5: Measured NO <sub>2</sub> to NO <sub>x</sub> ratios from hourly data collected at Beresfield (2015 to 2019) .....                                   | 25 |
| Figure 6-1: Maximum 15-minute average CO GLC (mg/m <sup>3</sup> ): natural gas (top) and diesel (bottom).....                                                  | 36 |
| Figure 6-2: Maximum 1-hour average CO GLC (mg/m <sup>3</sup> ): natural gas (top) and diesel (bottom) .....                                                    | 37 |
| Figure 6-3: Maximum 8-hour average CO GLC (mg/m <sup>3</sup> ): natural gas (top) and diesel (bottom) .....                                                    | 38 |
| Figure 6-4: Maximum 10-minute average SO <sub>2</sub> GLC (µg/m <sup>3</sup> ): natural gas (top) and diesel (bottom) .....                                    | 40 |
| Figure 6-5: Maximum 1-hour average SO <sub>2</sub> GLC (µg/m <sup>3</sup> ): natural gas (top) and diesel (bottom).....                                        | 41 |
| Figure 6-6: Maximum 24-hour average SO <sub>2</sub> GLC (µg/m <sup>3</sup> ): natural gas (top) and diesel (bottom) .....                                      | 42 |
| Figure 6-7: Annual average SO <sub>2</sub> GLC (µg/m <sup>3</sup> ): natural gas (top) and diesel (bottom) .....                                               | 43 |
| Figure 6-8: Maximum 24-hour average PM <sub>2.5</sub> GLC (µg/m <sup>3</sup> ): natural gas (top) and diesel (bottom).....                                     | 45 |
| Figure 6-9: Annual average PM <sub>2.5</sub> GLC (µg/m <sup>3</sup> ): natural gas (top) and diesel (bottom).....                                              | 46 |
| Figure 6-10: 24-hour average PM <sub>2.5</sub> background and modelled Project concentrations for worst case discrete receptor (diesel-fuelled case) .....     | 48 |
| Figure 6-11: Maximum 1-hour average NO <sub>2</sub> GLC (µg/m <sup>3</sup> ): natural gas (top) and diesel (bottom).....                                       | 49 |
| Figure 6-12: Annual average NO <sub>2</sub> GLC (µg/m <sup>3</sup> ): natural gas (top) and diesel (bottom).....                                               | 50 |
| Figure 6-13: Hourly average NO <sub>2</sub> background and modelled Project concentrations for worst case discrete receptor (diesel-fuelled case) .....        | 52 |
| Figure 6-14: 99.9 <sup>th</sup> PC 1-hour average CH <sub>2</sub> O GLC (µg/m <sup>3</sup> ): natural gas (top) and diesel (bottom).....                       | 53 |
| Figure 6-15: 99.9 <sup>th</sup> PC one-hour average GLCs: natural gas-acrolein (µg/m <sup>3</sup> ) (top); and B(a)P-diesel (µg/m <sup>3</sup> ) (bottom)..... | 54 |
| Figure 6-16: NSW DPIE (2020) results for daily maximum 1-hour average O <sub>3</sub> concentration (ppb) .....                                                 | 57 |
| Figure 6-17: DPIE Beresfield maximum 1-hour and 4-hour average O <sub>3</sub> concentration (ppb) .....                                                        | 58 |
| Figure 6-18: DPIE Beresfield maximum 8-hour average O <sub>3</sub> concentration (ppb) .....                                                                   | 58 |

## List of tables

|                                                                                                                                           |    |
|-------------------------------------------------------------------------------------------------------------------------------------------|----|
| Table 1.1: SEARs relevant to this assessment.....                                                                                         | 3  |
| Table 2.1: Project – Main Operating Parameters.....                                                                                       | 8  |
| Table 2.2: Project – Air Emissions modelling inputs and regulatory limits.....                                                            | 10 |
| Table 2.3: Project Air Emissions Parameters.....                                                                                          | 11 |
| Table 3.1: NSW Group 6 Standard for scheduled premises: air emissions limits for electricity generation .....                             | 14 |
| Table 3.2: NSW EPA air quality impact assessment criteria.....                                                                            | 15 |
| Table 3.3: National ambient air quality monitoring standards (2021).....                                                                  | 16 |
| Table 3.4: National ambient air quality monitoring standards (from 2025).....                                                             | 16 |
| Table 4.1: Sensitive receptor locations (indicative) identified for assessment.....                                                       | 18 |
| Table 4.2: Annual statistics from DPIE Beresfield meteorological data 2015-2019.....                                                      | 19 |
| Table 4.3: DPIE Beresfield, Newcastle and Wallsend air monitoring parameters.....                                                         | 21 |
| Table 4.4: Summary of measured CO concentrations: DPIE Newcastle (mg/m <sup>3</sup> ) .....                                               | 23 |
| Table 4.5: Summary of measured SO <sub>2</sub> concentrations: DPIE Beresfield (µg/m <sup>3</sup> ).....                                  | 23 |
| Table 4.6: Summary of measured PM <sub>2.5</sub> concentrations: DPIE Beresfield (µg/m <sup>3</sup> ) .....                               | 24 |
| Table 4.7: Summary of measured NO <sub>2</sub> concentrations: DPIE Beresfield.....                                                       | 25 |
| Table 4.8: Summary of measured O <sub>3</sub> concentrations: DPIE Beresfield.....                                                        | 26 |
| Table 4.9: Summary of some NSW formaldehyde measurements.....                                                                             | 26 |
| Table 4.10: Summary of some NSW measurements of PAHs as B(a)P.....                                                                        | 27 |
| Table 5.1: TAPM meteorological modelling parameters .....                                                                                 | 30 |
| Table 5.2: Calmet meteorological modelling parameters.....                                                                                | 31 |
| Table 5.3: Calpuff air pollutant dispersion modelling parameters.....                                                                     | 32 |
| Table 5.4: Calculated Peak-to-Mean Ratios used in assessment.....                                                                         | 33 |
| Table 6.1: Summary of Calpuff results for CO: natural gas-fuelled and 100% load (mg/m <sup>3</sup> ).....                                 | 39 |
| Table 6.2: Summary of Calpuff results for CO: diesel-fuelled; 100% load (mg/m <sup>3</sup> ) .....                                        | 39 |
| Table 6.3: Summary of Calpuff results for SO <sub>2</sub> : natural gas-fuelled; 100% load (µg/m <sup>3</sup> ) .....                     | 44 |
| Table 6.4: Summary of Calpuff results for SO <sub>2</sub> : diesel-fuelled; 100% load (µg/m <sup>3</sup> ).....                           | 44 |
| Table 6.5: Summary of Calpuff results for PM <sub>2.5</sub> : natural gas-fuelled; 100% load (µg/m <sup>3</sup> ) .....                   | 47 |
| Table 6.6: Summary of Calpuff results for PM <sub>2.5</sub> : diesel-fuelled; 100% load (µg/m <sup>3</sup> ).....                         | 47 |
| Table 6.7: Summary of Calpuff results for NO <sub>2</sub> : natural gas-fuelled; 100% load (µg/m <sup>3</sup> ).....                      | 51 |
| Table 6.8: Summary of Calpuff results for NO <sub>2</sub> : diesel-fuelled; 100% load (µg/m <sup>3</sup> ) .....                          | 51 |
| Table 6.9: Summary of Calpuff results: 99.9 <sup>th</sup> percentile 1h-average VOCs: natural gas-fuelled case (µg/m <sup>3</sup> ) ..... | 55 |
| Table 6.10: Summary of Calpuff results for 99.9 <sup>th</sup> percentile 1h-average VOCs: diesel-fuelled case (µg/m <sup>3</sup> ) .....  | 55 |
| Table 6.11: Ozone attainment area determination.....                                                                                      | 56 |
| Table 6.12: Results from Level 1 screening assessment tool.....                                                                           | 56 |
| Table 6.13: Gas turbine operating and air emissions parameters: 50% and 100% loads .....                                                  | 60 |
| Table 6.14: Results of Calpuff sensitivity tests: 50% and 100% loads.....                                                                 | 60 |

## Glossary

| Abbreviation       | Expansion / definition                                                                                                                                                                                                                                                                                 |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AHD                | Australian Height Datum                                                                                                                                                                                                                                                                                |
| ANSTO              | Australian Nuclear Science and Technology Organisation                                                                                                                                                                                                                                                 |
| B(a)P              | Benzo(a)Pyrene, a commonly used indicator for Polycyclic Aromatic Hydrocarbons                                                                                                                                                                                                                         |
| CEMP               | Construction Environment Management Plan                                                                                                                                                                                                                                                               |
| Diesel             | The term 'diesel' was used given it will be the most likely fuel delivered to the Project Site, although the back-up fuel could be another form of distillate. The diesel fuel sulphur content used for this assessment is detailed in this report.                                                    |
| Distillate         | The term 'distillate' includes various heating oils and diesel fuel. The main distillate classifications are Nos. 1, 2, and 4 fuel oils, and Nos. 1, 2, and 4 diesel fuels. Kerosene is also a distillate, similar to No. 1 oils, but is often listed separately for statistical purposes (PEI, 2021). |
| DLE                | Dry Low Emission                                                                                                                                                                                                                                                                                       |
| DPIE               | Department of Planning, Industry and Environment                                                                                                                                                                                                                                                       |
| EETM               | Emissions Estimation Technique Manual, published by the NPI                                                                                                                                                                                                                                            |
| EIS                | Environmental Impact Statement                                                                                                                                                                                                                                                                         |
| EPA                | NSW Environment Protection Authority                                                                                                                                                                                                                                                                   |
| EP&A Act           | Environmental Planning and Assessment Act 1979 (NSW)                                                                                                                                                                                                                                                   |
| EP&A Regulation    | Environmental Planning and Assessment Regulation (2000)                                                                                                                                                                                                                                                |
| GDA                | Geocentric Datum of Australia e.g. GDA 2020 and GDA 94                                                                                                                                                                                                                                                 |
| GLC                | Ground Level Concentration                                                                                                                                                                                                                                                                             |
| ISO                | International Organization for Standardization                                                                                                                                                                                                                                                         |
| Jacobs             | Jacobs Group (Australia) Pty Ltd                                                                                                                                                                                                                                                                       |
| MW                 | MegaWatt (one million Watts) – a unit of power                                                                                                                                                                                                                                                         |
| NG                 | Natural Gas                                                                                                                                                                                                                                                                                            |
| OCGT               | Open Cycle Gas Turbine                                                                                                                                                                                                                                                                                 |
| NMA                | Newcastle Metropolitan Area                                                                                                                                                                                                                                                                            |
| NO                 | Molecular formula for nitric oxide                                                                                                                                                                                                                                                                     |
| NO <sub>2</sub>    | Molecular formula for nitrogen dioxide                                                                                                                                                                                                                                                                 |
| NO <sub>x</sub>    | Molecular formula for oxides of nitrogen                                                                                                                                                                                                                                                               |
| NPI                | National Pollutant Inventory                                                                                                                                                                                                                                                                           |
| PAH                | Polycyclic Aromatic Hydrocarbon(s) e.g. see B(a)P                                                                                                                                                                                                                                                      |
| PEOA               | Protection of the Environment Operations Act                                                                                                                                                                                                                                                           |
| PM <sub>2.5</sub>  | Particulate Matter 2.5 – airborne particles with an equivalent aerodynamic diameter of <= 2.5 micron (µm)                                                                                                                                                                                              |
| PM <sub>10</sub>   | Particulate Matter 10 – airborne particles with an equivalent aerodynamic diameter of <= 10 micron (µm)                                                                                                                                                                                                |
| Project            | Development of a gas-fired power station at Kurri Kurri NSW                                                                                                                                                                                                                                            |
| SEAR               | Secretary's Environmental Assessment Requirements                                                                                                                                                                                                                                                      |
| Sensitive receptor | A location where people are likely to work or reside; this may include a dwelling, school, hospital, office or public recreational area (EPA, 2016).                                                                                                                                                   |
| Snowy Hydro        | Snowy Hydro Limited                                                                                                                                                                                                                                                                                    |
| SO <sub>2</sub>    | Molecular formula for sulphur dioxide                                                                                                                                                                                                                                                                  |
| U.S. EPA           | United States Environmental Protection Agency                                                                                                                                                                                                                                                          |
| VOC                | Volatile Organic Compound – a hydrocarbon                                                                                                                                                                                                                                                              |



## Executive summary

The purpose of this Updated Air Quality Impact Assessment for the Hunter Power Project (the Project) is to satisfy Infrastructure Approval condition B5 which requires an updated air quality assessment report based on the final plant design. The air quality modelling undertaken includes both the increased stack height and updated emission characteristics associated with the proposed final design. This report is an update of the Air Quality Impact Assessment that supported the Hunter Power Project Environmental Impact Statement (Jacobs, 2021a) (the Project EIS) response to submissions (Jacobs, 2021b).

The Project was approved as SSI-12590060 by the then Minister for Planning and Public Spaces on 17 December 2021. The approved Project involves the development of a gas-fired power station comprising two open cycle gas turbines (OCGT) with a nominal capacity of up to 750 megawatts (MW), an electrical switchyard and associated supporting infrastructure. The gas turbines would primarily be fired on natural gas with the use of diesel fuel as a backup. The Project will operate as a “peak load” generation facility supplying electricity at short notice when there is a requirement in the National Electricity Market (NEM).

Since the Project’s approval, Mitsubishi Heavy Industries (MHI) has been engaged as the main equipment supplier by Snowy Hydro and the detailed design of the gas turbines is in place. Two changes to the design affecting the air quality assessment include the increase of the exhaust stack height to 60 m in order to comply with the project noise criteria specified in the Infrastructure Approval conditions and Environment Protection Licence 21627, and the capacity of the power station has been reduced to 660 MW due to limitations of the 132kV transmission network.

The Project comprises an Open Cycle Gas Turbine power station located at Loxford, NSW which is approximately three kilometres north of Kurri Kurri in the Lower Hunter region. The chief objective of this assessment was to determine the potential air quality impacts that may occur as a result of power station operations.

Air quality impacts from construction of the power station are expected to be insignificant and temporary. Commonly used dust and odour control measures will be used to minimise air emissions due to construction activities. The Project Site has good separation from sensitive receptors such as residential residences.

The Project will have a capacity factor of up to 10 per cent of each year on natural gas fuel and two per cent on diesel fuel. However, it is expected that likely operations would result in a capacity factor of approximately two per cent. Modelling of continuous emissions from the Project was undertaken to test every hour of an annual meteorological simulation – this was a conservative approach taken for the assessment.

The ‘baseline’ or existing air quality situation for this assessment does not include emissions from the former Kurri Kurri aluminium smelter with its associated effects on local air quality, that ceased production in 2012. The baseline for this assessment covered the post-smelter period of 2015 to 2019 (with 2019 heavily affected by bushfire smoke).

The key air pollutants associated with the Project are: carbon monoxide (CO), nitrogen dioxide (NO<sub>2</sub>), sulphur dioxide (SO<sub>2</sub>), particulate matter as PM<sub>2.5</sub> and the hydrocarbons or Volatile Organic Compounds (VOCs): formaldehyde and acrolein when the power station is fuelled by natural gas, and formaldehyde and Benzo(a)pyrene (B(a)P) when fuelled by diesel.

A detailed review of the existing environment was carried out including an analysis of measured concentrations of ‘criteria’ air pollutants and their indicators (CO, NO<sub>2</sub>, SO<sub>2</sub> and PM<sub>2.5</sub>), from representative monitoring stations. The following conclusions were made in relation to the existing air quality and meteorological conditions:

- Wind patterns in the vicinity of the Project Site are characteristic of the Lower Hunter Valley, with prevailing winds from the west-northwest.
- Measured CO, NO<sub>2</sub> and SO<sub>2</sub> concentrations have been consistently below NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) air quality impact assessment criteria.

- Measured ozone ( $O_3$ ) concentrations occasionally exceed assessment criteria, with higher  $O_3$  concentrations caused by mainly  $NO_x$  emissions from road traffic, bushfires and controlled burns and other sources, during warmer weather (sunny conditions); e.g., NSW DPIE (2020).
- Measured  $PM_{2.5}$  levels increased across NSW and the Hunter region from 2017 to 2019 due to the effects of drought including dust storms, smoke from bushfires and hazard reduction burning. These events adversely influenced air quality with multiple days observed when  $PM_{2.5}$  concentrations exceeded EPA assessment criteria.

Model predictions were assessed at selected sensitive receptors located near the Project Site, which were considered as representative of the worst case sensitive receptor locations. The key outcomes of the air quality assessment were:

- The Project will meet NSW Government, *Protection of the Environment Operations (Clean Air) Regulation 2010* requirements for air pollutant concentrations in the exhaust gases.
- Operation of the Project will lead to small increases of ambient (ground level) concentrations of the air pollutants: CO,  $NO_2$ ,  $SO_2$ ,  $PM_{2.5}$  and the VOCs: formaldehyde, acrolein and Polycyclic Aromatic Hydrocarbons (as BaP); these small increases are predicted to not cause significant air quality impacts, by comparisons with their NSW EPA impact assessment criteria.
- The predicted changes in concentrations of key air quality indicators due to the Project are within the range of historically measured fluctuations in maximum concentrations for the region.
- The air pollutants of concern are those where background levels are already high; i.e.,  $NO_2$  (because  $O_3$  levels are high) and  $PM_{2.5}$ . However, modelling showed that the Project would not cause additional exceedances of criteria.

Based on modelling, increases in  $NO_2$  concentrations due to the Project are unlikely to cause exceedances of  $NO_2$  criteria. However,  $O_3$  background levels are high, and any additional  $NO_x$  emissions represent an increase to regional  $NO_x$  that contribute to the formation of  $O_3$  in the wider region. A detailed photochemical modelling study was outside the scope of this assessment. However, it would be reasonable to assume the power station  $NO_x$  emissions would have the effect of slightly reducing  $O_3$  levels in its immediate vicinity ( $O_3$  destruction), but contributing to a very slight increase in regional  $O_3$  levels.

The assessment demonstrated by modelling that  $PM_{2.5}$  contributions due to the Project would be negligible relative to air quality criteria. Concentrations of  $PM_{2.5}$ , including with potential contributions from the Project, would continue to be within the range of historically measured fluctuations in maximum concentrations for the region. This means that in a year when the Hunter Valley is not affected by bushfires, emissions from the Project are very unlikely to cause exceedances of  $PM_{2.5}$  criteria. In a year affected by bushfires, measurements of  $PM_{2.5}$  in the Hunter Valley will reflect the influence of bushfire smoke.

The assessment demonstrated that Project operations, whether fuelled by natural gas or diesel, would not be expected to cause adverse air quality impacts in the vicinity of the Project Site nor in the wider Lower Hunter region. This conclusion was based on modelling procedures undertaken in accordance with NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) and which conservatively assumed that the power station would be operating continuously. The implementation of 'best practice' gas turbine engineering technology for the Project, such as using Dry Low Emission (DLE) combustion system when operating on gas and Water Injection (WI) control technology when operating on diesel will minimise  $NO_x$  emissions and air quality impacts.

The air quality modelling undertaken showed that the proposed final design will result in a reduction in air quality impacts compared to the approved project.



# 1. Introduction

## 1.1 Project overview

The Hunter Power Project (the Project) was approved as SSI-12590060 by the then Minister for Planning and Public Spaces on 17 December 2021 under the NSW Environmental Planning and Assessment Act 1979 (EP&A Act).

Since the Project's approval, Mitsubishi Heavy Industries (MHI) has been engaged as the main equipment supplier by Snowy Hydro and the detailed design of the gas turbines is in place. Two changes to the design affecting the air quality assessment include the increase of the exhaust stack height to 60 m in order to comply with the project noise criteria specified in the Infrastructure Approval conditions and Environment Protection Licence 21627, and the capacity of the power station has been reduced to 660 MW due to limitations of the 132kV transmission network.

The purpose of this Updated Air Quality Impact Assessment is to satisfy Infrastructure Approval condition B5 which requires an updated air quality assessment report based on the final plant design. The air quality modelling undertaken includes both the increased stack height and updated emission characteristics associated with the proposed final design. This report is an update of the Air Quality Impact Assessment that supported the Hunter Power Project Environmental Impact Statement (Jacobs, 2021a) (the Project EIS) response to submissions (Jacobs, 2021b).

The Project Site is located in Loxford in the Hunter Valley within the Cessnock City Council local government area (LGA), approximately three km north of the town of Kurri Kurri, 30 km north-west of Newcastle CBD and 125 km north of Sydney. A regional map showing the Project's location is provided in Figure 2-1. The Project Site forms part of the decommissioned Kurri Kurri aluminium smelter site, owned by Hydro Aluminium Kurri Kurri Pty Ltd (Hydro Aluminium), that ceased operation in late 2012 and permanently closed in 2014.

The Project involves the construction and operation of a open cycle gas turbine (OCGT) power station and electrical switchyard, together with other associated supporting infrastructure. The power station would have a capacity of up to approximately 660 Megawatts (MW) generated by two heavy duty gas turbines. Although primarily a natural gas fuelled power station, diesel operations are also expected as required if there were a constraint or unavailability in the natural gas system and there was a need to supply electricity to the National Electricity Market (NEM).

The Project would operate as a peak load generation facility supplying electricity at short notice when there is a requirement in the NEM. The major supporting infrastructure that is part of the Project would be a 132 kV electrical switchyard located within the Project Site. The Project would connect into existing 132 kV electricity transmission infrastructure located adjacent to the Project Site. A new gas lateral pipeline and gas receiving station will also be required and this would be developed by a third party and be subject to a separate environmental assessment and planning approval.

Other ancillary elements of the Project include:

- Storage tanks and other water management infrastructure for potable water and demineralised water
- Fire water storage tanks and firefighting equipment such as hydrants and pumps
- Maintenance laydown areas
- Stormwater basin
- Diesel fuel storage tanks and truck unloading facilities
- Site access roads and car parking
- Office/administration, amenities, workshop/storage areas.

Construction and installation of the gas turbines are yet to commence. Earthworks activities commenced in early 2022 and the Project is intended to be operational by the end of 2023, with some operation potentially commencing by August 2023.

## 1.2 Air quality context

The power station will be fuelled by natural gas normally, with diesel used as a backup fuel. This might include up to six months of diesel-only operation during 2023 before the natural gas supply to the Project Site is completed. The power output by the power station and air pollutant emissions profile will be different for each fuel type.

The Project approval is for a capacity factor of up to 10 per cent of each year on natural gas fuel and two per cent on diesel fuel. However, it is expected that likely operations would result in a capacity factor of approximately two per cent. For the purpose of this assessment the predicted air emissions from the Project were assessed in accordance with Environment Protection Authority (EPA) modelling assessment requirements (EPA, 2016), which meant the effects of air emissions were tested for every hour of a simulated meteorological year; a conservative approach.

Typical air pollutants of concern for natural gas fuelled open cycle gas turbine power stations are: nitrogen dioxide (NO<sub>2</sub>), and some hydrocarbons, known as Volatile Organic Compounds (VOCs). Indirectly, emissions of oxides of nitrogen (NO<sub>x</sub>), VOCs, and carbon monoxide (CO), contribute to the photochemical formation of ozone (O<sub>3</sub>) in the ambient atmosphere. Emissions of some other air pollutants, such as CO and sulphur dioxide (SO<sub>2</sub>) are of less concern in that they are unlikely to lead to high concentrations relative to their corresponding ambient air quality standards / criteria.

Typical air pollutants of concern for diesel fuelled open cycle gas turbine power stations are: NO<sub>2</sub>, some VOCs, and some small airborne particles or 'aerosols', measured in the ambient atmosphere as PM<sub>10</sub> and PM<sub>2.5</sub>. Emissions of SO<sub>2</sub> may be of concern depending on sulphur content of the fuel, and if background SO<sub>2</sub> levels are already high.

The Project Site is located in the small suburb of Loxford, north of Kurri Kurri, in the Lower Hunter Valley, with relatively flat terrain in the vicinity of the Project Site. Most of the sensitive receptors closest to the Project Site are isolated residences.

The nearest ambient air quality and meteorological monitoring station to the Project Site is EPA's Beresfield monitoring station, located approximately 16.7 km east of the Project Site. Review of the EPA Beresfield data, (refer Section 4.4), revealed higher risk air pollutant emissions for the Project were expected to be:

- NO<sub>x</sub> – the formation of NO<sub>2</sub> will contribute to already high levels of O<sub>3</sub> (on both natural gas and diesel-fuelled operations)
- PM<sub>10</sub> and PM<sub>2.5</sub> – existing levels of airborne particulate matter are high and exceed their air quality (monitoring) standards every year. The majority of the high PM<sub>10</sub> and PM<sub>2.5</sub> levels were due to the effects of drought including due to dust storms, and smoke from bushfires and controlled burns (*New South Wales Annual Compliance Report 2019, National Environment Protection (Ambient Air Quality) Measure*). In particular, very high concentrations of PM<sub>10</sub> and PM<sub>2.5</sub> were experienced in the last months of 2019 due to bushfires in the Lower Hunter Valley. Emissions from industry and road vehicles in the Newcastle and Lower Hunter regions also contribute to these high levels.

## 1.3 Performance outcome

The desired performance outcome for the Project relating to air quality is to minimise air quality impacts to reduce risks to human health and the environment to the greatest extent practicable through the design, construction and operation of the Project.

## 1.4 Secretary's Environmental Assessment Requirements (SEARs)

An Environmental Impact Statement (EIS) for the Project has been prepared under Division 5.2 of the *Environmental Planning and Assessment Act 1979* (EP&A Act). The Air Quality Impact Assessment (Jacobs, 2021b) was prepared to support the EIS. It addressed the relevant sections of the Secretary's Environmental Assessment Requirements (SEARs) issued on 5 February 2021 (SSI 12590060) and agency and other stakeholder comments received during exhibition of the EIS. Table 1.1 outlines the SEARs relevant to the assessment.

Table 1.1: SEARs relevant to this assessment

| Secretary's requirement                                                                                                                                                                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Air quality</b> – including an assessment of likely air quality impacts of the project in accordance with the <i>Approved Methods for the Modelling and Assessment of Air Pollutants in NSW</i> (NSW EPA, 2016), including an assessment of scenarios where the project operates on diesel fuel |
| <b>Air quality</b> – including ability to comply with the relevant regulatory framework, specifically the <i>Protection of the Environment Operations Act 1997</i> and the <i>Protection of the Environment Operations (Clean Air) Regulation 2010</i>                                             |

As described in Section 1.1, the Hunter Power Project (the Project) was approved as SSI-12590060 by the then Minister for Planning and Public Spaces on 17 December 2021. The purpose of this Air Quality Impact Assessment is to satisfy Infrastructure Approval condition B5 which requires an updated air quality assessment report based on the final plant design. The air quality modelling undertaken includes both the increased stack height and updated emission characteristics associated with the proposed final design. This report is an update of the Air Quality Impact Assessment that supported the *Hunter Power Project Environmental Impact Statement* (Jacobs, 2021a) (the Project EIS) *response to submissions* (Jacobs, 2021b).

## 1.5 Report structure

The report is structured by the sections listed in the following points:

- Section 1, Introduction – introduces the Project with a summary of the Project background, Project description, performance outcomes, SEARs and purpose of this revised report
- Section 2, Gas Turbine Power Station – sets out the predicted Project air emissions inventory, and selection of air pollutants for air quality impact assessment
- Section 3, Ambient Air Quality Standards – sets out the NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) impact assessment criteria for the air pollutants identified in Section 2
- Section 4, Existing Environment – describes of key features of the existing environment including surrounding land uses, sensitive receptors, local meteorology, and existing air quality. The section sets out the results of a review of background levels of hydrocarbons identified for this assessment
- Section 5, Assessment Methodology – overview of the methods used to assess the potential for air quality impacts due to the Project, based on modelling
- Section 6, Results – sets out the model results for 9600 grid receptors and 16 discrete receptors in accordance with the requirements of NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016)
- Section 7, Conclusion – provides a concise conclusion of the results of the assessment.

## 2. Project description

### 2.1 Overview

The Project Site is located in Loxford (as shown by the star symbol in Figure 2-1), which is approximately three km north of the township of Kurri Kurri, and approximately 14 km west of Beresfield and Thornton (see vector shown in Figure 2-1). Relatively shallow terrain exists across most of the local area, shown by the relief shading in the image.




Figure 2-1: Regional Setting of Project (star indicates approximate location of the Project Site)


The remaining sub-sections of this section describe the Project including the Project air emissions estimates used for assessment by dispersion modelling, and explains the selection of pollutants for assessment.

### 2.2 Site layout

A conceptual layout of the Project Site showing the locations of the two OCGT stacks is provided in Figure 2-2. Additional details are provided in Appendix A.

The Project Site forms part of the former Hydro Aluminium Kurri Kurri Pty Ltd aluminium smelter site, which operated from 1969 to 2012, before closing in 2014. Figure 2-3 shows a historical aerial view of the aluminium smelter (M. Pickett, 6 March 2005). Since the closure of the aluminium smelter, extensive remediation works were undertaken including demolition of existing structures, asbestos removal and recycling of waste materials (Jacobs, 2020).





- Proposal Site
- Asset protection zone
- Detention basin
- Sealed roadway
- Crushed rock
- Landscaping
- Grass / Road base
- 1 Proposed Switchyard Area
- 2 Proposed Plant Area
- 3 Proposed Buffer Area

0 100 200 m

1:4,000 at A4  
GDA2020 MGA Zone 56

**Data sources:**  
Jacobs  
Metromap (Aerometrex) 2020  
NSW Spatial Services





Figure 2-3: Aerial View of Aluminium Smelter prior to demolition to North-East (M. Pickett; 6 March 2005)

## **2.3 Site activity**

### **2.3.1 Overview**

The gas turbine technology for the Project is two industrial frame heavy duty F-Class units in OCGT configuration. The nominal electrical output of the gas turbines under International Organization for Standardization (ISO) conditions at the Project Site is expected to be up to approximately 660 MW. Key Project parameters include:

- The Project will be developed as two OCGT units with operations expected to commence by approximately August 2023 for the first unit, potentially on diesel fuel initially, with dual fuel and both units operational by December 2023
- Primarily the gas turbines will be fuelled by natural gas with the use of diesel fuel as a back-up (see Glossary for definitions for diesel and distillate).

### **2.3.2 Open cycle gas turbine operation**

Open Cycle Gas Turbine operations generate electricity through the combustion of natural gas and/or diesel (or liquid distillate fuel) within a gas turbine. Gas turbines comprise a compressor, combustion chamber, turbine and electricity generator. Air is compressed to a high pressure before being admitted into the combustion chamber. Natural gas or diesel fuel is then injected into the combustion chamber where combustion occurs at high temperatures and the gases expand. The resulting mixture of pressurised hot gas is admitted to a turbine where aerodynamic blades cause a rotor to turn thus generating mechanical power, and subsequently, electrical power via the generator. In the open cycle configuration hot exhaust gases are vented directly to atmosphere through an exhaust stack. A schematic diagram of the process is provided in Figure 2-4 (Jacobs, 2020).






Figure 2-4: Schematic of Simple (or Open) Cycle Gas Turbine

### 2.3.3 Best practice technology

Snowy Hydro has considered the technologies available for controlling emissions from gas turbine plants of the size proposed in this Project. The best available and appropriate control technology for these units is to utilise Dry Low Emissions (DLE) burners on the gas turbines for use when firing natural gas fuel and using Water Injection (WI) control technology in the gas turbine burners when firing diesel fuel.

Post combustion technologies such as Selective Catalytic Reduction (SCR) have been installed on some combined cycle gas turbine plants, diesel power stations and even on certain open cycle gas turbine power stations. Coupling a F Class gas turbine in combined cycle configuration with a SCR system is seen to be technically possible however presents some engineering, safety and commercial risks that would require very specific and detailed design and careful selection of materials mainly as a result of the high gas exhaust temperatures seen in F Class gas turbines. There is very limited successful operational experience using SCR technology with F Class open cycle gas turbines and commercially it is not considered feasible. The Project is already implementing the use of DLE burners which is considered a best practice approach and this technology would be able to comply with the emission requirements for the Project.

An overview of other control technologies (SCR, SNCR, SCONOX) is provided, however, are typically not technically and commercially practical for OCGT plants for some of the below reasons. Similar conclusions were also drawn by the Proponents for the Newcastle Power Station EIS, Appendix C (April 2020) and the Tallawarra Stage B Gas Turbine Power Station Modification Environmental Assessment report (June 2020).

#### Selective Catalytic Reduction (SCR)

- The technique is based on the reduction of NO<sub>x</sub> to nitrogen in a catalytic bed by reaction with ammonia (in a general aqueous solution). This is a post combustion control treatment.
- A SCR process requires additional land for the site and would produce additional noise and use of consumables
- The high velocity of the exhaust in an open cycle gas turbine is a significant technical difficulty for the removal of contaminants, compared to gas turbines in combined cycle configuration where the exhaust velocity and temperatures are reduced significantly
- The optimum operating temperature for SCR is 300-450°C. This is not suitable for the large industrial open cycle gas turbines proposed for this project as the exhaust temperature is well above this (typically 600°C-650°C).

- There are additional health and safety risks for storage, handling and emissions of ammonia and additional emissions of particulate matter (GER 4172 "Gas Turbine NO<sub>x</sub> Emissions Approaching Zero – Is it Worth the Price?")
- This technique may be costly in the case of plants operated between 500 h/yr and 1500 h/yr and even more so for plants operated <500 h/yr (European Commission, 2017). Considering this Project is expected to operate in the vicinity of 350 hours per year, which is below the lower threshold as indicated in the European Commission (2017), the commercial suitability for this technology reduces further.
- There is limited commercial experience of SCR on large frame OCGTs internationally and no experience of SCR on OCGTs in the Australian national electricity market.

#### Selective Non-catalytic reduction (SNCR)

- The technique is based on the reduction of NO<sub>x</sub> to nitrogen by reaction with ammonia or urea at a high temperature, without the need of a catalyst. This is a post combustion control treatment
- The required operating temperature window is between 800°C and 1000°C for optimal reaction. This is not suitable for the OCGT proposed for this Project as the exhaust temperature is well below this (typically 600-650°C).
- This technology is not recommended by the European Commission (2017) for OCGTs
- No commercial experience of this technology on gas turbine installations in Australia or internationally

#### SCONO<sub>x</sub><sup>TM</sup>

- Use of a single catalyst that operates by simultaneously oxidising CO to CO<sub>2</sub>, NO to NO<sub>2</sub>, and then absorbing NO<sub>2</sub> onto its surface through the use of a potassium carbonate absorber coating. This technique does not require ammonia injection.
- The optimum operating temperature for SCONO<sub>x</sub><sup>TM</sup> is 150-370°C. This is again not suitable for the open cycle gas turbines proposed for this Project as the exhaust temperature is well above this (typical 600-650°C).
- Performance is highly sensitive to even small amounts of sulphur in the gas fuel
- This technology is not recommended by the European Commission (2017) for OCGTs
- No commercial experience of this technology in gas turbines over 100MW globally

It is noted that all industrial frame open cycle gas fired power stations in Australia use Dry Low NO<sub>x</sub> when gas-fired and water injection when diesel fired, in the same manner as proposed for the Hunter Power Project.

### 2.3.4 Operations and scenarios

The main operating parameters based on the detailed design for the Project considered relevant for the air quality assessment are listed in Table 2.1.

Table 2.1: Project – Main Operating Parameters

| Parameter                   | Value / Details                                        | Comments                                                                                                                                                                                       |
|-----------------------------|--------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Plant Type                  | Open Cycle                                             | -                                                                                                                                                                                              |
| Gas Turbine class           | F Class industrial                                     | Cold end drive, static starter                                                                                                                                                                 |
| Number of gas turbines      | Two                                                    |                                                                                                                                                                                                |
| Targeted Net Plant Capacity | Up to approximately 660 MW                             | Ambient conditions 15°C, 60% Relative Humidity (natural gas fuel)                                                                                                                              |
| Plant Operation             | Peaking                                                | ISO standard peak load rating to apply as per ISO 3977-2                                                                                                                                       |
| Facility load               | Approximate minimum load of 50% to maximum load (100%) | Approximate minimum load of 50% defined as a lower gas turbine load where reliable and safe operation occurs while still satisfying the required air emissions and noise limits for the plant. |

| Parameter                                | Value / Details                                                                                                                                                  | Comments                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Capacity factor                          | Capacity factor: 10% on natural gas (approximately 1,051 hours per year); and 2% on diesel (approximately 175 hours per year)<br>Total combined for Project: 12% | Normal operations will be fuelled by natural gas with diesel as backup fuel.<br>The Capacity Factors adopted assume 100% load operation.<br>It is expected that likely operation of the Project would result in a total Capacity Factor of two per cent in any given year and some of this time at reduced load.<br>Modelling of continuous emissions from the Project was undertaken to test every hour of an annual meteorological simulation. |
| Maximum likely diesel-fuelled operations | 10 hours/day if required                                                                                                                                         | At full load. Actual operation is expected to be less.                                                                                                                                                                                                                                                                                                                                                                                           |
| Emissions control                        | Yes                                                                                                                                                              | Dry-Low-Emission combustors on natural gas, water injection on diesel                                                                                                                                                                                                                                                                                                                                                                            |
| Emergency diesel generator               | Yes                                                                                                                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Design plant life                        | 30 years                                                                                                                                                         | Minimum design life for Mechanical and Electrical components <sup>1</sup> .                                                                                                                                                                                                                                                                                                                                                                      |
| Cold start to full Load duration         | Approximately 30 minutes                                                                                                                                         | The NSW <i>Protection of the Environment Operations (Clean Air) Regulation</i> excludes concentration standards for start-up and shut-down periods (paragraph 56).                                                                                                                                                                                                                                                                               |

## 2.4 Gas Turbine air emissions

### 2.4.1 NO<sub>x</sub>, CO and PM<sub>10</sub>

The gas turbine (GT) technology option being considered for the Project will meet, and sometimes do better than, the NSW air emission limits when operating at maximum load (100 per cent), and indicative minimum load of 50 per cent, and between those loads. The GTs will be fitted with Dry Low Emissions combustors which result in low NO<sub>x</sub> emissions (within the limits) when firing on natural gas. When operating on diesel fuel, the GTs will use water injection to assist with control of emissions of oxides of nitrogen (NO<sub>x</sub>).

The Project GTs operating at maximum, stable operating load will meet the air emissions limits listed in Table 2.2. Note some of these are common technology limits used in industry and are better (lower) than NSW Government air emissions limits specified in the NSW *Protection of the Environment Operations (Clean Air) Regulation 2010*; see also Section 3.3.

The emissions parameters used as inputs to the air quality assessment in Table 2.2 and Table 2.3 are based on the final design of the plant and includes emission specifications (emission rates and concentrations) based on manufacturer performance guarantees, as required by the Project Approval and EPL 21627.

<sup>1</sup> Note, civil and structural components will be designed for a 50 year life.

Table 2.2: Project – Air Emissions modelling inputs and regulatory limits

| Substance and parameter                                 | Project modelling inputs         | Regulatory Limits*                      | Comments                                                                                                                                                                                                                                  |
|---------------------------------------------------------|----------------------------------|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Natural gas fuel</b>                                 |                                  |                                         |                                                                                                                                                                                                                                           |
| Oxides of nitrogen (NO <sub>x</sub> )<br>1-hour average | 51.3 mg/Nm <sup>3</sup> (25 ppm) | 70 mg/Nm <sup>3</sup> (34 ppm)          | Dry Low Emissions (DLE). Subject to a minimum load (typically 50-55%). NO <sub>x</sub> expressed as nitrogen dioxide (NO <sub>2</sub> ) based on 15% O <sub>2</sub> , dry condition, temperature 0 °C and standard air pressure 1013 hPa. |
| Carbon monoxide (CO)<br>1-hour average                  | 7 mg/Nm <sup>3</sup> (5.6 ppm)   | N/A                                     | The <i>Protection of the Environment Operations (Clean Air) Regulation 2010</i> prescribes no limits for CO for GTs.<br><br>15% O <sub>2</sub> , dry condition, temperature 0 °C and standard air pressure 1013 hPa.                      |
| Particulate Matter 10 (PM <sub>10</sub> )               | 5 mg/Nm <sup>3</sup>             | N/A                                     |                                                                                                                                                                                                                                           |
| <b>Diesel fuel</b>                                      |                                  |                                         |                                                                                                                                                                                                                                           |
| NO <sub>x</sub> , 1-hour average                        | 86.2 mg/Nm <sup>3</sup> (42 ppm) | 90 mg/Nm <sup>3</sup> (44 ppm)          | Water-injected for NO <sub>x</sub> management. NO <sub>x</sub> expressed as nitrogen dioxide (NO <sub>2</sub> ) based on 15% O <sub>2</sub> , dry condition, temperature 0 °C and standard air pressure 1013 hPa.                         |
| CO, 1-hour average                                      | 63 mg/Nm <sup>3</sup> (50 ppm)   | N/A                                     | The <i>Protection of the Environment Operations (Clean Air) Regulation 2010</i> prescribes no limits for CO for GTs.<br><br>15% O <sub>2</sub> , dry condition, temperature 0 °C and standard air pressure 1013 hPa.                      |
| Particulate Matter 10 (PM <sub>10</sub> )               | 10 mg/Nm <sup>3</sup>            | 50 mg/Nm <sup>3</sup> (Total Particles) |                                                                                                                                                                                                                                           |

\*NSW Government, *Protection of the Environment Operations (Clean Air) Regulation 2010*.

#### 2.4.2 NO<sub>x</sub> emissions control by DLE

Gas turbine Dry Low Emission technology burns the majority of fuel at (relatively) cool, lean conditions to minimise NO<sub>x</sub> production. The fuel-air mixture is pre-mixed before entering the combustion chamber, and the lean mixture lowers flame temperature and reduces NO<sub>x</sub> emission (Boyce, 2012). This approach lowers the NO<sub>x</sub> emissions from the GT without the need for water-injection or steam-injection when operating on natural gas. The use of DLE technology allows NO<sub>x</sub> concentrations to be lowered to 25 ppm, as confirmed with the equipment manufacturer, Mitsubishi Heavy Industries, selected for the Project.



### 2.4.3 Natural gas and diesel fuel sulphur content

Estimates for the sulphur contents of the natural gas and diesel fuels to be used by the Project were required for calculating exhaust emissions of sulphur dioxide (SO<sub>2</sub>) by the GTs. As a conservative step in the assessment, the natural gas sulphur content adopted for this assessment was 50 mg/m<sup>3</sup>, which is the maximum total sulphur allowed in typical natural gas as specified in the Australian Standard AS 4564:2011 – *Specification for general purpose natural gas* and also as referenced in the Australian Energy Market Operator (AEMO) Gas Quality Guidelines. The actual sulphur content in typical natural gas used by Project is expected to be significantly less than this.

The sulphur limit for diesel fuel used by Project will be below 10 mg/kg, which is the maximum allowed for Automotive Diesel.

It is noted the *Protection of the Environment Operations (Clean Air) Regulation 2010* sulphur limit is much higher, 25 g/kg, for an in-stack emission limit applicable for outside the Newcastle Metropolitan Area. (The Project Site in Loxford is outside the Newcastle Metropolitan Area). However, such a high sulphur-content fuel is unlikely to be delivered to Australia in the future.

## 2.5 Air emissions inventory

This section outlines the air emissions inventory adopted for the assessment. The air emissions parameters used as input parameters to the dispersion model, Calpuff, are detailed in Section 5 describing the assessment methodology.

Parameters for the Project OCGT stacks (such as exhaust temperature, exit velocity, stack dimensions, and air emissions concentrations and rates) are listed in Table 2.3. The gas turbine related input parameters were sourced from the selected equipment supplier Mitsubishi Heavy Industries (Table 2.3). Annual NO<sub>x</sub> emissions can be of interest for a gas turbine Project because of the potential to contribute to regional ozone formation. This regional ozone is created in the presence of sunlight and background air pollutants by the air emissions from many sources. Assuming a capacity factor of up to 10 per cent of each year on natural gas fuel and two per cent on diesel fuel, the annual NO<sub>x</sub> emission is calculated to be 139 tonnes per annum.

Table 2.3: Project Air Emissions Parameters

| Parameter                                         | Units | Gas Fuel                               | Diesel Fuel | Comment                                                                                                     |
|---------------------------------------------------|-------|----------------------------------------|-------------|-------------------------------------------------------------------------------------------------------------|
| <b>Gas Turbine Exhaust Stack</b>                  |       |                                        |             |                                                                                                             |
| Easting, GDA2020                                  | m     | Unit 1: 357,520<br>Unit 2: 357,510     |             | Geocentric Datum of Australia 2020                                                                          |
| Northing, GDA2020                                 | m     | Unit 1: 6,371,471<br>Unit 2: 6,371,402 |             | Geocentric Datum of Australia 2020                                                                          |
| Height above ground level of the top of the stack | m     | 60                                     | 60          | Data from selected equipment supplier                                                                       |
| Estimated stack tip diameter                      | m     | 7.5                                    | 7.5         | Data from selected equipment supplier                                                                       |
| Base elevation                                    | m AHD | 14.4                                   | 14.8        | Estimated ground level at the exhaust stacks within the Project Site (metres above Australian Height Datum) |
| <b>Estimated Exhaust Gas Composition</b>          |       |                                        |             |                                                                                                             |
| Oxygen (O <sub>2</sub> )                          | wt%   | 12.66                                  | 13.76       | Source: Approximate exhaust gas composition based on data received from                                     |
| Carbon Dioxide (CO <sub>2</sub> )                 | wt%   | 6.90                                   | 7.57        |                                                                                                             |
| Water (H <sub>2</sub> O)                          | wt%   | 6.37                                   | 5.75        |                                                                                                             |

| Parameter                              | Units              | Gas Fuel       | Diesel Fuel     | Comment                                                                                                                   |
|----------------------------------------|--------------------|----------------|-----------------|---------------------------------------------------------------------------------------------------------------------------|
| Nitrogen (N <sub>2</sub> )             | wt%                | 72.77          | 71.64           | selected equipment supplier – 15°C @ 60% RH                                                                               |
| Argon (Ar)                             | wt%                | 1.30           | 1.28            |                                                                                                                           |
| Total                                  | wt%                | 100.00         | 100.00          |                                                                                                                           |
| GT Load                                | %                  | 100            | 100             |                                                                                                                           |
| Exhaust flow rate                      | m <sup>3</sup> /s  | 1,802.2        | 1,738.2         | Source: Approximate flow rate based on data received from selected equipment supplier – 15°C @ 60% RH                     |
| Exhaust Temperature                    | °C                 | 650            | 525             | Source: Approximate temperature based on data received from selected equipment supplier – 15°C @ 60% RH                   |
| Exhaust Velocity                       | m/s                | 40.8           | 39.3            | Source: Approximate velocity based on assumed diameter and data received from selected equipment supplier – 15°C @ 60% RH |
| Nitrogen Oxides (NO <sub>x</sub> )     | ppm                | 25             | 42              | Data from selected equipment supplier                                                                                     |
|                                        | g/s                | 35.3           | 58.6            | Calculated based on dry flue gas at actual O <sub>2</sub> % (i.e. <15% O <sub>2</sub> )                                   |
| Carbon Monoxide (CO)                   | ppm                | 5.6            | 50.5            | Data from selected equipment supplier                                                                                     |
|                                        | g/s                | 4.8            | 42.8            | Calculated based on dry flue gas at actual O <sub>2</sub> % (i.e. <15% O <sub>2</sub> )                                   |
| Sulphur Dioxides (SO <sub>x</sub> )    | ppmvd              | 1.7 (dry, 0°C) | 0.24 (dry, 0°C) | Data from selected equipment supplier                                                                                     |
|                                        | g/s                | 3.2            | 0.5             | Calculated based on dry flue gas at actual O <sub>2</sub> % i.e. <15% O <sub>2</sub>                                      |
| Particulate Matter (PM <sub>10</sub> ) | mg/Nm <sup>3</sup> | 5.0            | 10              | Data from selected equipment supplier                                                                                     |
|                                        | g/s                | 3.4            | 6.8             | Calculated based on dry flue gas at actual O <sub>2</sub> % i.e. <15% O <sub>2</sub>                                      |

## 2.6 Construction activity

Construction of the Project will include temporary, localised air quality effects due to some dust emissions from construction activities and some engine exhaust emissions from construction vehicles and machinery. The engine exhaust emissions will be insignificant; comparable to public vehicle use on nearby roads and highways. For the control of dust (and potentially odour) emissions from the Project Site, management measures will be implemented and maintained throughout the construction phase as detailed in a Construction Environment Management Plan (CEMP).

Specifically, dust emissions are expected from the following construction activities:

- Vegetation clearing within the switchyard area
- Earthworks including site preparation and excavations
- Movement of spoil and fill around the Project Site
- Ground disturbance by movement of construction vehicles and heavy plant and machinery
- Concreting work
- Establishment of site landscaping.

A CEMP will detail the air emissions management measures commonly used to suppress dust (and potentially odour) to minimise air quality impacts. These measures will include preparation and implementation of a Soil and Water Management Plan, an Erosion and Sediment Control Plan, and dust suppression techniques such as progressive rehabilitation of disturbed ground and water sprays. In the event of air quality impacts being identified during construction, the CEMP is expected to rule that construction activities will be ceased until emissions are controlled.

Also, the CEMP will detail the air emissions management measures to minimise air emissions from vehicle and machinery engine exhaust emissions. Such measures will include, for example, requiring all construction vehicles, plant and machinery to be used on-site to be properly maintained including service records, and pre-start checklists completed.

In conclusion, air quality impacts due to construction of the Project are expected to be insignificant and temporary. Commonly used dust and odour control measures will be used to minimise air pollutant emissions. The construction site has good separation from sensitive receptors such as residences.

### 3. Air quality standards

#### 3.1 Overview

The purpose of this section is to set out the NSW emissions limits and ambient air quality assessment criteria relevant to the Project. New national ambient air quality monitoring standards are also listed which may have a bearing on NSW emissions limits and assessment criteria in the future.

#### 3.2 NSW Protection of the Environment Operations Act 1997

The NSW POEO Act 1997 is the primary piece of legislation for the regulation of potential pollution impacts associated with 'scheduled activities' in NSW. Scheduled activities are those defined in Schedule 1 of the Act. Clause 17 (Electricity generation) of the Act applies to electricity plant that uses a gas turbine and is situated in the metropolitan area or LGA of Port Stephens, Maitland, Cessnock, Singleton, Wollondilly or Kiama. The Project is located within the Cessnock LGA and so this schedule applies to the Project.

The Project is a scheduled activity because, as a metropolitan electricity works (gas turbines), it will burn more than 20 MegaJoule (MJ) of fuel per second. This means a licence is required for the premises (the activity is premises-based).

In relation to standards of air impurities not to be exceeded (Clause 128), air emissions at any point must be within concentrations prescribed by the regulations. The next sub-section sets out these concentrations relevant for the assessment.

#### 3.3 NSW Protection of the Environment Operations (Clean Air) Regulation 2010

##### 3.3.1 Air emissions limits

The NSW *Protection of the Environment Operations (Clean Air) Regulation 2010*, contains provisions for the regulation of emissions to air. The air emissions limits relevant for the Project are the 'Group 6 Standard' for scheduled premises; they are listed in Table 3.1. (Comparisons with the Project data were provided in Table 2.2).

Table 3.1: NSW Group 6 Standard for scheduled premises: air emissions limits for electricity generation

| Substance                           | Natural Gas                 | Diesel                                                        |
|-------------------------------------|-----------------------------|---------------------------------------------------------------|
| Solid Particles (Total)             | --                          | 50 mg/m <sup>3</sup>                                          |
| Nitrogen dioxide (NO <sub>2</sub> ) | 70 mg/m <sup>3</sup>        | 90 mg/m <sup>3</sup>                                          |
| Reference conditions                | Dry, 273 K (0 °C), 1013 hPa |                                                               |
| Smoke                               | --                          | Ringelman 1 or 20% opacity; or,<br>Ringelman 3 or 60% opacity |

##### 3.3.2 Fuel sulphur content

The Project is located within the Cessnock LGA; the relevant *Protection of the Environment Operations (Clean Air) Regulation 2010* fuel sulphur content limit is 2.5 per cent by weight (2.5 g/kg). This is substantially higher than the sulphur content expected for the fuels to be used by Project; see Section 2.4.3.



### 3.3.3 Exemptions

Exemptions to the *Protection of the Environment Operations (Clean Air) Regulation 2010* concentration standards include start-up and shutdown periods (paragraph 56), however practicable means must still be used to prevent and minimise air pollution.

## 3.4 NSW ambient air quality impact assessment criteria

This section sets out the NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) ambient air quality assessment criteria relevant to the assessment; i.e., the air pollutants identified for assessment in Section 1.1. The criteria are listed in Table 3.2.

Table 3.2: NSW EPA air quality impact assessment criteria

| Substance                                                                                                                   | Statistic                                    | Concentration          |
|-----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|------------------------|
| Main air pollutants – from EPA (2016) Table 7.1, impact assessment criteria, inclusive of background levels                 |                                              |                        |
| Sulphur dioxide (SO <sub>2</sub> )                                                                                          | Maximum 10-minute average                    | 712 µg/m <sup>3</sup>  |
|                                                                                                                             | Maximum 1-hour average                       | 570 µg/m <sup>3</sup>  |
|                                                                                                                             | Maximum 24-hour average                      | 228 µg/m <sup>3</sup>  |
|                                                                                                                             | Maximum annual average                       | 60 µg/m <sup>3</sup>   |
| Nitrogen dioxide (NO <sub>2</sub> )                                                                                         | Maximum 1-hour average                       | 246 µg/m <sup>3</sup>  |
|                                                                                                                             | Maximum 24-hour average                      | 62 µg/m <sup>3</sup>   |
| Photochemical oxidants (as ozone; O <sub>3</sub> )                                                                          | Maximum 1-hour average                       | 214 µg/m <sup>3</sup>  |
|                                                                                                                             | Maximum 4-hour average                       | 171 µg/m <sup>3</sup>  |
| Particulate Matter as PM <sub>2.5</sub>                                                                                     | Maximum 24-hour average                      | 25 µg/m <sup>3</sup>   |
|                                                                                                                             | Maximum annual average                       | 8 µg/m <sup>3</sup>    |
| Particulate Matter as PM <sub>10</sub>                                                                                      | Maximum 24-hour average                      | 50 µg/m <sup>3</sup>   |
|                                                                                                                             | Maximum annual average                       | 25 µg/m <sup>3</sup>   |
| Carbon monoxide (CO)                                                                                                        | Maximum 15-minute average                    | 100 mg/m <sup>3</sup>  |
|                                                                                                                             | Maximum 1-hour average                       | 30 mg/m <sup>3</sup>   |
|                                                                                                                             | Maximum 8-hour average                       | 10 mg/m <sup>3</sup>   |
| Volatile Organic Compounds (VOCs) – from EPA (2016) Table 7.2a, principal toxic air pollutants, Project only contributions. |                                              |                        |
| Gas volumes expressed at 25°C and 1 atmosphere (101.325 kPa).                                                               |                                              |                        |
| Acrolein                                                                                                                    | 99.9 <sup>th</sup> percentile 1-hour average | 0.42 µg/m <sup>3</sup> |
| Formaldehyde                                                                                                                | 99.9 <sup>th</sup> percentile 1-hour average | 20 µg/m <sup>3</sup>   |
| Polycyclic Aromatic Hydrocarbons (PAH) as Benzo(a)Pyrene (B(a)P)                                                            | 99.9 <sup>th</sup> percentile 1-hour average | 0.4 µg/m <sup>3</sup>  |

### 3.5 National Environment Protection (Ambient Air Quality) Measure

The National Environment Protection Council (NEPC) produces National Environment Protection Measures (NEPMs). The national environment protection goals of the recently updated *National Environment Protection (Ambient Air Quality) Measure* (referred to in this report as 'the NEPM'), are to achieve the national environmental protection standards listed in Table 3.3 (NEPC, 2021a).

Table 3.3: National ambient air quality monitoring standards (2021)

| Pollutant         | Statistic                                   | Maximum concentration standard         |
|-------------------|---------------------------------------------|----------------------------------------|
| CO                | Maximum 8-hour average (rolling 1hr. avg.)  | 9.0 ppm (11 mg/m <sup>3</sup> at 0°C)  |
| NO <sub>2</sub>   | Maximum 1-hour average                      | 80 ppb (164 µg/m <sup>3</sup> at 0°C)  |
|                   | Annual average                              | 15 ppb (31 µg/m <sup>3</sup> at 0°C)   |
| O <sub>3</sub>    | Maximum 8-hour average (rolling 1 hr. avg.) | 65 ppb (139 µg/m <sup>3</sup> at 0°C)  |
| SO <sub>2</sub>   | Maximum 1-hour average                      | 100 ppb (286 µg/m <sup>3</sup> at 0°C) |
|                   | Annual average                              | 20 ppb (57 µg/m <sup>3</sup> at 0°C)   |
| PM <sub>10</sub>  | Maximum 24-hour average                     | 50 µg/m <sup>3</sup>                   |
|                   | Annual average                              | 25 µg/m <sup>3</sup>                   |
| PM <sub>2.5</sub> | Maximum 24-hour average                     | 25 µg/m <sup>3</sup>                   |
|                   | Annual average                              | 8 µg/m <sup>3</sup>                    |

Additional tightening of standards for SO<sub>2</sub> and PM<sub>2.5</sub> applies from 1 January 2025 as listed in Table 3.4.

Table 3.4: National ambient air quality monitoring standards (from 2025)

| Pollutant         | Statistic               | Maximum concentration standard        |
|-------------------|-------------------------|---------------------------------------|
| SO <sub>2</sub>   | Maximum 1-hour average  | 75 ppb (214 µg/m <sup>3</sup> at 0°C) |
| PM <sub>2.5</sub> | Maximum 24-hour average | 20 µg/m <sup>3</sup>                  |
|                   | Annual average          | 7 µg/m <sup>3</sup>                   |

It is noted the NEPM standards are not NSW impact assessment criteria – they are used by the participating jurisdictions to assess air quality in the regions using data acquired by performance monitoring stations. Also, from a Ministers notice about the changes (NEPC, 2021b):

*"... The Explanatory Statement clarifies this intent of the NEPM as a standard for reporting representative ambient air quality within an airshed, and not as a regulatory standard. The AAQ NEPM does not constrain a jurisdiction's ability to manage local or regional air quality issues."*

However, air quality guidelines and policies developed by the states, in time, tend to align with the NEPM monitoring standards. As such these may have a bearing on NSW emissions limits and assessment criteria in the future.

## 4. Existing environment

### 4.1 Local setting

The Project Site is located at the former Kurri Kurri aluminium smelter site, which ceased operation in late 2012 and was permanently closed in 2014, and is now in the process of being demolished. The Project Site is approximately three km north of the township of Kurri Kurri, and approximately 15 km west of Beresfield (see Figure 2-1). The Project Site is bordered by forested areas to the north and west and small urban areas, each approximately three km away to the east and south: Cliftleigh to the east, and Heddon Greta to the south-east, the northern parts of Kurri Kurri south, and Weston south-west. There are a number of isolated residences within a 2.5 km radius of the Project Site, primarily in the southern half.

The terrain in the immediate vicinity of the Project Site is relatively flat, following the Swamp Creek river valley to the north-east towards Maitland. There are some hilly areas to the north-west and south-east. A 100 m high hill lies some 7.7 km south-southwest of the Project Site (see Figure 4-1). Figure 4-1 shows the location of the Project Site (yellow cross), terrain elevation contours (green, yellow and orange) and sensitive receptor locations identified for assessment (numbered green squares).




Figure 4-1: Air quality study area with terrain elevation contours and sensitive receptors

The 'base map' constructed for this assessment (Figure 4-1) is aligned north-south, with Geocentric Datum of Australia 2020 (GDA2020) northings (metres) labelled on the vertical axis, and eastings (metres) on the horizontal axis. Practically for this assessment there are no differences between GDA2020 and preceding GDA94 co-ordinate locations, which are only approximately 1-2 m apart in this study area. More details about the air quality study area are provided in Section 5.

## 4.2 Sensitive receptors

A sensitive receptor is where people are likely to work or reside and therefore have the potential to experience an air quality impact – the NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) definition for a 'sensitive receptor' is provided in the Glossary. Potentially sensitive receptor locations, mainly isolated residences, were identified for use in this assessment using satellite imagery and are shown in Table 4.1 and Figure 4-1). These sensitive receptors were considered to be representative of locations potentially experiencing worst-case air quality impacts due to the Project because they were nearest to the Project Site.

Table 4.1: Sensitive receptor locations (indicative) identified for assessment

| No. | Easting (m) | Northing (m) | Description                     |
|-----|-------------|--------------|---------------------------------|
| 1   | 358086      | 6370341      | Residence                       |
| 2   | 357748      | 6369983      | Residence                       |
| 3   | 358636      | 6370028      | Residence                       |
| 4   | 359178      | 6370182      | School; TAFE NSW – Kurri Kurri  |
| 5   | 359161      | 6370579      | Farmhouse; Bowditch Ave.        |
| 6   | 360689      | 6370984      | Residence                       |
| 7   | 360286      | 6370603      | Residence                       |
| 8   | 360157      | 6369986      | Residence                       |
| 9   | 361486      | 6372171      | Residence                       |
| 10  | 360220      | 6373188      | Farmhouse                       |
| 11  | 358945      | 6369119      | Residence                       |
| 12  | 358289      | 6368815      | School; Kurri Kurri High School |
| 13  | 356482      | 6369542      | Residence; Amarillo             |
| 14  | 356566      | 6370702      | Residence; Bishops Bridge Road  |
| 15  | 356089      | 6371047      | Residence                       |
| 16  | 355748      | 6371678      | Residence                       |

## 4.3 Local meteorology

Meteorological conditions are important for determining the direction and rate at which emissions from a source disperse. Key meteorological requirements of air dispersion models are, typically, hourly records of wind speed, wind direction, temperature and atmospheric stability. For air quality assessments, a minimum of one year of hourly data is usually required, which means that almost all possible meteorological conditions, including seasonal variations, are considered in the model simulations.

NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) prescribes the minimum requirements for meteorological data that are to be used in dispersion modelling. At least one year of 'site-specific' data should be used. If 'site-specific' data are not available then 'site-representative' data, correlated against at least five years of data, are acceptable. The meteorological data must also be at least 90 per cent complete. For this Project, meteorological data collected from the Department of Planning, Industry and Environment (DPIE) Beresfield air quality monitoring station were analysed in order to identify a representative year for this assessment (*Current and Forecast Air Quality* (NSW DPIE, 2021); see also Section 4.4.1. The process for identifying a representative meteorological year involved comparing hourly wind data and wind patterns over the 5-year period 2015 to 2019. The range of statistics from the data collected at

DPIE Beresfield from 2015 to 2019 are listed in Table 4.2. These data show that the wind speed statistics do not vary significantly from year to year.

Table 4.2: Annual statistics from DPIE Beresfield meteorological data 2015-2019

| Statistic                                                   | 2015 | 2016 | 2017 | 2018 | 2019 |
|-------------------------------------------------------------|------|------|------|------|------|
| Fraction complete (%)                                       | 99   | 98   | 85   | 100  | 99   |
| Mean wind speed (m/s)                                       | 2.5  | 2.8  | 2.3  | 2.4  | 2.4  |
| 99 <sup>th</sup> percentile 1-hour average wind speed (m/s) | 9.6  | 11.2 | 8.9  | 9.8  | 10.2 |
| Fraction of calms (%)                                       | 4.0  | 4.2  | 4.0  | 4.9  | 4.7  |
| Fraction of winds >6 m/s (%)                                | 5.9  | 9.9  | 3.8  | 5.1  | 6.5  |

The annual wind patterns for each year from 2015 to 2019 are shown by the wind roses in Figure 4-2; created using hourly average wind speed and wind direction data from DPIE Beresfield. From inspection of these wind roses the most common winds in the area are from the west-northwest. This pattern of winds is common for the Lower Hunter Valley and reflects the influence of the northwest to southeast alignment of the Hunter Valley. It is clear that the wind patterns were similar in all five years. This suggests that wind patterns do not vary significantly from year to year, and potentially the data from any of the years presented could be used as a representative year for assessment purposes.






Figure 4-2: Annual wind roses: EPA Beresfield 2015-2019

## 4.4 Existing air quality

### 4.4.1 Overview

The DPIE established a network of monitoring stations across NSW to understand current air quality conditions and impacts, and to help identify programs to improve air quality (*Current and Forecast Air Quality* (NSW DPIE, 2021)). The nearest DPIE stations to the Project study area are illustrated in Figure 4-3 (from *Current and Forecast Air Quality* (NSW DPIE, 2021)); Beresfield is closest to Kurri Kurri. DPIE data from Beresfield were examined and compared with air quality (monitoring) standards to describe existing air quality conditions for key air pollutants relevant to this assessment.


Parameters measured at DPIE Beresfield, Newcastle and Wallsend monitoring stations are listed in Table 4.3. Carbon monoxide (CO) is not measured at Beresfield, so the CO data used for this assessment were obtained from the next nearest station, Newcastle. It is noted Newcastle and Beresfield air quality monitoring data are affected more by emissions from road vehicles than the Kurri Kurri locality, so the selection of these data as representative of Kurri Kurri, is conservative (the concentrations at Newcastle and Beresfield are expected to be slightly higher than at Kurri Kurri).

Table 4.3: DPIE Beresfield, Newcastle and Wallsend air monitoring parameters

| Air Monitoring Station | Distance and Direction                  | Measured Parameters                                                                                         |
|------------------------|-----------------------------------------|-------------------------------------------------------------------------------------------------------------|
| DPIE Beresfield        | Approx. 17 km to east of Kurri Kurri    | Meteorology, NO <sub>2</sub> , O <sub>3</sub> , SO <sub>2</sub> , PM <sub>10</sub> , PM <sub>2.5</sub>      |
| DPIE Newcastle         | Approx. 27 km south-east of Kurri Kurri | Meteorology, NO <sub>2</sub> , O <sub>3</sub> , SO <sub>2</sub> , PM <sub>10</sub> , PM <sub>2.5</sub> , CO |
| DPIE Wallsend          | Approx. 21 km south-east of Kurri Kurri | Meteorology, NO <sub>2</sub> , O <sub>3</sub> , SO <sub>2</sub> , PM <sub>10</sub> , PM <sub>2.5</sub>      |

Monitoring data completeness is important for assessment, with a 90 per cent capture rate preferred. DPIE data capture in the Lower Hunter has been excellent; capture rates for most national reporting parameters have been well in excess of 90 per cent since 2011 (*New South Wales Annual Compliance Report 2019, National Environment Protection (Ambient Air Quality) Measure*). Over 2015-2019, only the hourly average data capture for CO in 2015 (Newcastle), was less than 90 per cent.

In this section, the units used for air pollutant concentrations were converted from volumetric units e.g. parts per billion (ppb), to mass units e.g. microgram per cubic metre ( $\mu\text{g}/\text{m}^3$ ). The temperature used for the conversion was 25 degrees Celsius (25 °C), which is reflective of conditions in the Hunter Valley; e.g., mean minimum and maximum temperatures at Maitland are 12°C and 25°C.



- Proposal location
- DPIE air monitoring stations in Lower Hunter
- Recreation areas
- Waterbodies

0 5 10 km

1:150,000 at A4  
Coordinate System: GDA2020 MGA Zone 56

**Data sources:**  
Jacobs  
NSW Spatial Services  
DPIE (NSW Gov., 2021; 26 Jan., 2021)



**Figure 4-3** Map of DPIE air monitoring stations in Lower Hunter



#### 4.4.2 Carbon monoxide

The nearest CO monitoring station to Kurri Kurri is DPIE Newcastle; a summary of CO concentrations from 2015 to 2019 is provided in Table 4.4. These results show that CO concentrations have been consistently below NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) impact assessment criteria. The trend in 8-hourly average CO has been slightly downwards since 2009 (*New South Wales Annual Compliance Report 2019, National Environment Protection (Ambient Air Quality) Measure*).

Table 4.4: Summary of measured CO concentrations: DPIE Newcastle (mg/m<sup>3</sup>)

| Statistic and criterion                   | 2015 | 2016 | 2017 | 2018 | 2019 |
|-------------------------------------------|------|------|------|------|------|
| Max. 1-hour average; 30 mg/m <sup>3</sup> | 2.0  | 2.4  | 1.6  | 1.4  | 2.2  |
| Max. 8-hour average; 10 mg/m <sup>3</sup> | 1.7  | 1.6  | 1.3  | 1.2  | 1.7  |

\* Temperature 25°C used to convert DPIE data to mass concentrations (see Section 4.4.1); reflective of Lower Hunter conditions.

#### 4.4.3 Sulphur dioxide

A summary of SO<sub>2</sub> concentrations measured at DPIE Beresfield from 2015 to 2019 is provided in Table 4.5, from an analysis of results provided by *New South Wales Annual Compliance Report 2019, National Environment Protection (Ambient Air Quality) Measure*. Normally background SO<sub>2</sub> concentrations are small, of the order 1 ppb; hence these results show that SO<sub>2</sub> concentrations in the Lower Hunter are likely influenced by industrial sources in the Hunter Valley, such as coal-fired power stations. However, at Beresfield the concentrations have been consistently below the NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) impact assessment criteria each year. Analysis of the SO<sub>2</sub> trends in the Lower Hunter since 2009 shows no clear change in SO<sub>2</sub> levels over the past decade (*New South Wales Annual Compliance Report 2019, National Environment Protection (Ambient Air Quality) Measure*).

Table 4.5: Summary of measured SO<sub>2</sub> concentrations: DPIE Beresfield (µg/m<sup>3</sup>)

| Statistic and criterion                     | 2015 | 2016 | 2017 | 2018 | 2019 |
|---------------------------------------------|------|------|------|------|------|
| Max. 1-hour average; 570 µg/m <sup>3</sup>  | 215  | 86   | 141  | 183  | 178  |
| Max. 24-hour average; 228 µg/m <sup>3</sup> | 21   | 21   | 21   | 18   | 24   |
| Annual average; 60 µg/m <sup>3</sup>        | 2.6  | 2.6  | 5.2  | 5.2  | 5.2  |

\* Temperature 25°C used to convert DPIE data to mass concentrations (see Section 4.4.1); reflective of Lower Hunter conditions.

#### 4.4.4 Particulate matter as PM<sub>2.5</sub>

A time-series of 24-hour average PM<sub>2.5</sub> concentrations measured at DPIE Beresfield over 2015–2019 is provided in Figure 4-4. The corresponding NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) assessment criterion of 25 µg/m<sup>3</sup>, which came into effect on 20<sup>th</sup> January 2017, is also displayed (red-dashed line). The measured PM<sub>2.5</sub> exceeded the impact assessment criterion on some days over 2015–2019, with the increased exceedances in 2019 due to bushfire smoke and raised dust (*Fine particle pollution peaks during bushfires* (ANSTO, 2020) and *New South Wales Annual Compliance Report 2019, National Environment Protection (Ambient Air Quality) Measure*). There are no clear trends in the PM<sub>2.5</sub> measurements in the Lower Hunter since 2009 (*New South Wales Annual Compliance Report 2019, National Environment Protection (Ambient Air Quality) Measure*), which appear to have been heavily influenced by bushfire smoke in 2009, 2013, 2015, 2016 and 2019.




Figure 4-4: Measured 24-hour average PM<sub>2.5</sub> concentrations at Beresfield

A statistical summary of the PM<sub>2.5</sub> measurements at Beresfield over 2015 to 2019 is provided in Table 4.6.

Table 4.6: Summary of measured PM<sub>2.5</sub> concentrations: DPIE Beresfield (µg/m<sup>3</sup>)

| Statistic and criterion                    | 2015 | 2016 | 2017 | 2018 | 2019 |
|--------------------------------------------|------|------|------|------|------|
| Max. 24-hour average; 25 µg/m <sup>3</sup> | 26   | 28   | 19   | 25   | 101  |
| Number of days above 25 µg/m <sup>3</sup>  | 1    | 1    | 0    | 0    | 23   |
| Annual average; 8 µg/m <sup>3</sup> *      | 7.4  | 7.4  | 7.6  | 8.7  | 12.2 |

\* Maximum annual average introduced by EPA for 2017 onwards.

#### 4.4.5 Oxides of nitrogen

This assessment included dispersion modelling of NO<sub>x</sub> emissions from the Project, however NO<sub>2</sub> is the pollutant of interest for comparison with the air quality criteria. A first step in the assessment was to determine the general NO<sub>2</sub> vs. NO<sub>x</sub> relationship in the ambient air environment in the study area.

Inspection of ambient NO<sub>x</sub> monitoring data shows that for most (possibly all) localities the NO<sub>2</sub> fraction is inversely proportional to the total NO<sub>x</sub>. This means that maximum NO<sub>x</sub> concentrations are associated with the lowest NO<sub>2</sub> concentrations. Typically as the NO<sub>x</sub> concentration increases the NO<sub>2</sub>/NO<sub>x</sub> fraction decreases to a minimum. The NO<sub>2</sub>/NO<sub>x</sub> ratios for DPIE Beresfield, (hourly average data 2015-2019), are shown plotted against total NO<sub>x</sub> in Figure 4-5; the plot includes an exponential fit. The average NO<sub>2</sub>/NO<sub>x</sub> fraction for these data is 68 per cent. For the highest NO<sub>x</sub> concentrations greater than 300 µg/m<sup>3</sup> the NO<sub>2</sub> concentration is less than 20 per cent.






Figure 4-5: Measured NO<sub>2</sub> to NO<sub>x</sub> ratios from hourly data collected at Beresfield (2015 to 2019)

An explanation for the pattern shown in Figure 4-5 is as follows: during the high-temperature combustion of fossil fuels such as natural gas and diesel there will be a variety of NO<sub>x</sub> formed including NO and NO<sub>2</sub>. At the point of emission, NO comprises the greatest proportion of the total NO<sub>x</sub>. Typically NO comprises approximately 90 per cent by volume, the remainder being NO<sub>2</sub>. The NO<sub>2</sub> is linked to adverse health effects, hence the assessment criteria for NO<sub>2</sub>. Within a few hours however, in the presence of O<sub>3</sub> and sunlight, most of the NO converts to NO<sub>2</sub>, but by the time this has occurred the NO<sub>2</sub> is likely well dispersed to lower, less harmful concentrations.

#### 4.4.6 Nitrogen dioxide and ozone

A statistical summary of the measured NO<sub>2</sub> concentrations at DPIE Beresfield over 2015–2019 is provided in Table 4.7. These data show the NO<sub>2</sub> concentrations have been consistently below NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) impact assessment criteria. Analysis of the trends for NO<sub>2</sub> show no clear change since 2009 (*New South Wales Annual Compliance Report 2019, National Environment Protection (Ambient Air Quality) Measure*).

Table 4.7: Summary of measured NO<sub>2</sub> concentrations: DPIE Beresfield

| Statistic and criterion                    | 2015 | 2016 | 2017 | 2018 | 2019 |
|--------------------------------------------|------|------|------|------|------|
| Max. 1-hour average; 246 µg/m <sup>3</sup> | 92   | 77   | 75   | 75   | 105  |
| Annual average; 62 µg/m <sup>3</sup>       | 17   | 15   | 16   | 17   | 15   |

\* Temperature 25°C used to convert DPIE data to mass concentrations (see Section 4.4.1); reflective of Lower Hunter conditions.

A marker for photochemical smog is ozone (O<sub>3</sub>), which is formed from many air pollution sources in a region such as the Hunter Valley. Predictions of O<sub>3</sub> concentrations require regional photochemical modelling, which was outside the scope of this assessment. While O<sub>3</sub> was not required to be assessed for the Project, industrial

emissions of NO<sub>x</sub> and other pollutants contribute to the formation of O<sub>3</sub>. As such a statistical summary of the Beresfield O<sub>3</sub> measurements is provided in Table 4.8, from an analysis of data provided by *Protection of the Environment Operations (Clean Air) Regulation 2010*. These results show that exceedences of the NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) criteria for O<sub>3</sub> is a more significant air quality issue than for NO<sub>2</sub>, and demonstrates why NO<sub>x</sub> minimisation by industry is important even though exceedences of the NO<sub>2</sub> criteria are unlikely—at least in the Lower Hunter. Analysis of the trend data for O<sub>3</sub> (*New South Wales Annual Compliance Report 2019, National Environment Protection (Ambient Air Quality) Measure*), and more recent monitoring data, shows an increase in O<sub>3</sub> levels. The most likely explanation is emissions from bushfires in 2018–2019 (*New South Wales Annual Compliance Report 2019, National Environment Protection (Ambient Air Quality) Measure*).

Table 4.8: Summary of measured O<sub>3</sub> concentrations: DPIE Beresfield

| Statistic and criterion                    | 2015 | 2016 | 2017 | 2018 | 2019 |
|--------------------------------------------|------|------|------|------|------|
| Max. 1-hour average; 214 µg/m <sup>3</sup> | 151  | 167  | 163  | 210  | 247  |
| Max. 4-hour average; 171 µg/m <sup>3</sup> | 131  | 133  | 155  | 175  | 210  |

\* Temperature 25°C used to convert DPIE data to mass concentrations (see Section 4.4.1); reflective of Lower Hunter conditions.

#### 4.4.7 Hydrocarbons (VOCs) for assessment

The selection of VOCs for assessment is described in Section 5.2. The selected VOCs were, for the combustion of natural gas in gas turbines: formaldehyde and acrolein; and for the combustion of diesel fuel by gas turbines: PAHs as B(a)P and formaldehyde.

While NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) does not require background levels of individual VOCs to be included as part of cumulative impact assessments, reviews of the concentrations of VOCs selected for assessment were provided as additional information in the following sub-sections. These background concentrations assist with the interpretation of the assessment results.

#### 4.4.8 VOCs: Formaldehyde

In Australia, formaldehyde is not measured very often, and generally only as part of a wider research campaign; e.g., Keywood et al. (2019), Guerette et al. (2019). A summary of a brief review of formaldehyde measurements focussing on NSW is provided in Table 4.9. The Measurements of Urban, Marine and Biogenic Air (MUMBA) monitoring campaign was undertaken in Wollongong over the 2012–2013 summer. The most detailed (hourly average) MUMBA dataset was identified as being most representative of formaldehyde concentrations in the Lower Hunter region.

Table 4.9: Summary of some NSW formaldehyde measurements

| Parameter                                                                 | Formaldehyde concentration | Source                         |
|---------------------------------------------------------------------------|----------------------------|--------------------------------|
| MUMBA (Wollongong), 1025 hourly average measurements, Dec 2012 – Feb 2013 |                            | Guerette et al. (2019)         |
| range                                                                     | 0.09–8.69 ppb              |                                |
| mean                                                                      | 1.19 ppb                   | Calculated using MUMBA dataset |
| Sydney Particle Study I; summer 2011                                      |                            | Keywood et al. (2019)          |
| 1-hour average, typical low                                               | 2–3 ppb                    |                                |
| 1-hour average, typical high                                              | 10–20 ppb                  |                                |
| Sydney Particle Study II; autumn 2012                                     |                            | Keywood et al. (2019)          |
| 1-hour average, typical low                                               | 0.5 ppb                    |                                |

| Parameter                                | Formaldehyde concentration | Source                       |
|------------------------------------------|----------------------------|------------------------------|
| 1-hour average, typical high             | 4–6 ppb                    |                              |
| EPA Sydney 2008-2009                     |                            | NEPC (2019)                  |
| Annual average (Rozelle and Turrella)    | 1.6 ppb                    |                              |
| Max. 24-hour average (Rozelle, Turrella) | 3.2 ppb, 4.4 ppb           |                              |
| Australia, general                       |                            | Australian Government (2006) |
| Natural background annual average        | 1 ppb                      |                              |
| Maximum 24-hour average                  | 2 ppb                      |                              |

#### 4.4.9 VOCs: PAHs as B(a)P

Measurements of airborne Polycyclic Aromatic Hydrocarbons (PAHs) in Australia are rare, with results obtained only from relatively short measurement campaigns, generally undertaken many years apart. Commonly, PAH measurements are reported as Benzo(a)Pyrene (B(a)P) for comparisons with ambient air quality standards specified in this way. A summary of some relevant NSW measurements of PAHs as B(a)P is provided in Table 4.10. In winter, many localities in rural NSW, and parts of Sydney, are affected by smoke due to domestic wood burners, especially during temperature inversion conditions at night. This has the effect of elevating concentrations of PAHs in winter; e.g., *Ambient Concentrations of Polycyclic Aromatic Hydrocarbon Species in NSW* (NSW DEC, 2004).

Table 4.10: Summary of some NSW measurements of PAHs as B(a)P

| Parameter                                  | B(a)P concentration      | Source                                                                                          |
|--------------------------------------------|--------------------------|-------------------------------------------------------------------------------------------------|
| Sydney, Turrella Oct. 2008 – Sep. 2009     |                          | NEPC (2010); NEPC (2019)                                                                        |
| Annual average                             | 0.21 ng/m <sup>3</sup>   |                                                                                                 |
| Maximum 24-hour average                    | 0.40 ng/m <sup>3</sup>   |                                                                                                 |
| Mayfield, Mar 2010 – Jan 2011              |                          | <i>Lower Hunter Ambient Air Quality Review of Available Data</i> (NSW OEH, 2012)                |
| Annual average (56 meas.)                  | < 0.08 ng/m <sup>3</sup> | No meas. above limit of detection.                                                              |
| Max. 24h avg.                              | < 0.08 ng/m <sup>3</sup> | No meas. above limit of detection.                                                              |
| Beresfield, 1997–2001 winters (10 samples) |                          | <i>Ambient Concentrations of Polycyclic Aromatic Hydrocarbon Species in NSW</i> (NSW DEC, 2004) |
| Mean                                       | 0.15 ng/m <sup>3</sup>   |                                                                                                 |
| Max. 24h avg.                              | 0.52 ng/m <sup>3</sup>   |                                                                                                 |
| Beresfield, 1997–2001 summers (3 samples)  |                          | <i>Ambient Concentrations of Polycyclic Aromatic Hydrocarbon Species in NSW</i> (NSW DEC, 2004) |
| Mean                                       | 0.03 ng/m <sup>3</sup>   |                                                                                                 |
| Max. 24h avg.                              | 0.05 ng/m <sup>3</sup>   |                                                                                                 |

#### 4.4.10 VOCs: Acrolein

The *Lower Hunter Ambient Air Quality Review of Available Data* (NSW OEH, 2012) recognised acrolein as a 'priority industrial pollutant' for the Newcastle Local Government Area, although ranked with a lower priority than PAHs, benzene and arsenic. Measurements of acrolein are rare in Australia and limited to relatively short measurement campaigns.

The CSIRO *Methane and Volatile Organic Compound Emissions in New South Wales* (2016) review of VOCs for the NSW EPA measured acrolein in a number of different environments, for which a typical background concentration was 1 ppb. However, these measurements were affected by sources such as vehicle traffic, wastewater treatment plants, and cattle feedlots. From the broader review of acrolein measurements by the U.S. DHHS (2007), a better estimate for background acrolein levels in a rural environment is 0.1 ppb (0.23  $\mu\text{g}/\text{m}^3$  at 25°C).



## 5. Assessment methodology

### 5.1 Overview

The potential air quality impacts of the Project were determined from results of computer-based dispersion modelling. This section describes important features and parameters used in the meteorological and air pollutant dispersion modelling that formed the basis of this assessment. This section provides a focus on site-specific parameters that affected the modelling. The assessment was undertaken in accordance with the procedures detailed in NSW *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* EPA (2016), which includes guidelines for the preparation of meteorological data, reporting requirements and the use of air quality assessment criteria to assess the significance of model-predicted air quality impacts. The modelling was based on the use of the Calmet and Calpuff models, with model settings following the guidance of *Generic Guidance and Optimum Model Settings for the CALPUFF Modeling System for Inclusion into the 'Approved Methods for the Modeling and Assessments of Air Pollutants in NSW, Australia'* (Barclay and Scire for NSW Office of Environment and Heritage (2011)).

The key part of the NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) assessment process comprises comparisons of the model results for Ground Level Concentrations (GLCs) with the impact assessment criteria listed in Section 3.4.

### 5.2 Substances for assessment

The substances for assessment were selected by a review of National Pollutant Inventory (NPI) emissions factors (Australian Government, 2008), and corresponding U.S. EPA 'AP-42' data (U.S. EPA, 2004). The purpose of the review was to check (approximately) the air emissions data provided by the GT manufacturers, and to fill in some data gaps. The air emissions data were compared with the NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) air quality assessment criteria to select the air pollutants for assessment. From this review the hydrocarbons selected for assessment were: formaldehyde and acrolein for natural gas-fuelled GTs and PAHs as B(a)P and formaldehyde for diesel-fuelled GTs.

### 5.3 Capacity factor

The power station will not operate continuously throughout any year. The 'Capacity Factor' is an estimate of the fraction of time that a power station is expected to operate. The Capacity Factor for the Project, as a 'peaker plant', has been assumed to be 12 per cent for the purposes of assessment. However, it is expected that likely operation of the Project would result in a total Capacity Factor of two per cent in any given year, and some of this time at reduced load.

The air pollutant emission rates used as input to the modelling for this assessment were used to test every hourly condition of the simulated meteorological year. The purpose of this was to not limit the Project's operation to any particular season, month, or hour of the day. For that reason the assessment results for sub-hourly and hourly average assessment parameters (such as maximum, ambient, hourly average NO<sub>2</sub> concentration), were conservative (high). Further, the Project is not expected to operate for a period as long as 24 hours in one instance, so the assessment results for 24-hour (daily) averages, such as the maximum 24-hour average PM<sub>2.5</sub> concentrations, were even more conservative. Similarly, the annual average assessment results due the Project were the most conservative of all the assessment results.

### 5.4 Meteorological modelling

#### 5.4.1 Purpose

The main task of the meteorological modelling was to produce a three-dimensional, hourly-varying, meteorological database to be the foundation and input for the subsequent air pollutant dispersion modelling. Three-dimensional, hourly average wind vectors covering a large study area were key parameters. To assist with

this process, high quality measurements of wind speed, wind direction and other meteorological parameters were available for the Lower Hunter (see Section 4.3). Some of these local observations were used to strongly influence the meteorological dataset created as input for dispersion modelling.

#### 5.4.2 Selection of simulation year

In Section 4.3 it was determined the wind patterns in the Hunter Valley are similar each year – the data from any of the years analysed in detail (DPIE meteorological data 2015–2019), could have been used as a representative meteorological simulation year for the assessment. The simulation year selected for modelling was 2018, as the air quality monitoring data for 2019, (also required model inputs), were heavily affected by smoke from fires; e.g., see Figure 4-4.

#### 5.4.3 TAPM and Calmet modelling

The Air Pollution Model (TAPM), developed at CSIRO Atmospheric Research, was used to generate, primarily, upper air data for the air quality study area. The significant and practical advantage of TAPM is that it eliminates the need for site-specific meteorological observations to be used as input to an air (pollutant) dispersion model. The model predicts surface and upper air flows important to local-scale air pollution, such as sea breezes and terrain-induced flows, against a background of larger-scale meteorology provided by synoptic analyses (Hurley, 2008a; Hurley et al. 2008b; Hurley et al. 2008).

For this air quality study, TAPM was used to generate hourly-varying surface and upper-air meteorological data over the Project study area, using the DPIE Beresfield surface measurements for 2018 as input. Modifications were made to default land use parameters for some grid cells in the Project study area to better reflect the local land use identified using vertical imagery, especially along Swamp Creek.

Hourly average wind speed and wind direction observational data from the DPIE Beresfield monitoring station were used in 'data assimilation' mode, to force TAPM to produce meteorological results to be similar to the observations at ground-level. The surface winds produced by TAPM for Beresfield were compared with the observational data to confirm proper assimilation. Subsequently these data were used as input to Calmet to produce an hourly-varying, three-dimensional, meteorological dataset for the air quality study area. (The air dispersion model used, Calpuff, required an input dataset from its meteorological model, Calmet).

Calmet is a meteorological model that develops hourly wind and temperature fields on a three-dimensional gridded modelling domain. Atmospheric mixing (boundary) layer heights are calculated for each grid point, on an hourly basis. The diagnostic wind field generator accounts for slope flows, kinematic terrain effects, terrain blocking effects, and a micrometeorological model for overland and overwater boundary layers (Scire et al., 2000a). Summaries of some of the key input parameters used for the meteorological modelling are provided in Table 5.1 (TAPM) and Table 5.2 (Calmet).

Table 5.1: TAPM meteorological modelling parameters

| Parameter                 | Value                                                                                                                                                                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of grids (spacing) | Four grids with horizontal resolution: 30 km, 10 km, 3 km, 1 km                                                                                                                                                                                                            |
| Number of grid points     | 25 x 25 x 25: inner grid horizontal size 25 km x 25 km; and 25 vertical layers at the following heights (metres above ground level): 10, 25, 50, 100, 150, 200, 250, 300, 400, 500, 600, 750, 1000, 1250, 1500, 1750, 2000, 2500, 3000, 3500, 4000, 5000, 6000, 7000, 8000 |
| Year(s) of analysis       | 2018 & 2019 – 2018 was selected as the simulation year due air quality monitoring data affected by bushfire smoke late in 2019                                                                                                                                             |
| Centre of analysis        | Latitude 32.78333° S, Longitude 151.4833° E (near Project site)<br>Easting 357.967 km; Northing 6371.714 km (practically GDA 2020)                                                                                                                                         |
| Terrain data source       | Default TAPM terrain data                                                                                                                                                                                                                                                  |
| Land use modifications    | Land use codes modified to improve characterisation of Swamp Creek near site                                                                                                                                                                                               |

| Parameter                        | Value                                                                                      |
|----------------------------------|--------------------------------------------------------------------------------------------|
| Meteorological data assimilation | DPIE Beresfield meteorological data; measured hourly average wind speed and wind direction |

Table 5.2: Calmet meteorological modelling parameters

| Parameter                      | Value                                                                                                                                                                                                                                                           |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Terrain data source(s)         | 1 second (30 metre) Shuttle Radar Topography Mission data                                                                                                                                                                                                       |
| Land use data source(s)        | Digitised using a vertical image                                                                                                                                                                                                                                |
| Meteorological grid domain     | 30 km x 20 km                                                                                                                                                                                                                                                   |
| Meteorological grid resolution | 250 metres                                                                                                                                                                                                                                                      |
| Meteorological grid dimensions | 120 x 80 horizontal grid points<br>9 vertical layers: 0, 20, 40, 80, 160, 320, 700, 1200, 1500 & 2000 metres                                                                                                                                                    |
| Meteorological grid origin     | East 343.000 km; North 6362.000 km (MGA Zone 56)                                                                                                                                                                                                                |
| RMAX1, RMAX2, RMAX3            | Maximum radius of influence over land in: surface layer (RMAX1 = 5 km); aloft (RMAX2 = 20 km); and over water (RMAX3 = 20 km)                                                                                                                                   |
| RMIN, R1, R2                   | Minimum radius of influence used in wind field interpolation (RMIN = 0.1 km)<br>Relative weighting of first guess field and observations in surface layer (R1 = 0.5 km)<br>Relative weighting of first guess field and observations in layers aloft (R2 = 1 km) |
| TERRAD                         | Radius of influence of terrain (TERRAD = 5.0 km)                                                                                                                                                                                                                |
| Surface station                | TAPM-generated surface and upper air station files output for Kurri: E 358.0 km, N 6371.7 km                                                                                                                                                                    |

Calmet results for the surface winds and other meteorological parameters were extracted at the Project Site location and compared with the Beresfield measurements, which confirmed the modelled data over the whole grid was of sufficient quality to be used for the assessment. These comparisons are provided in Appendix B.

## 5.5 Calpuff modelling

The air dispersion model Calpuff, developed by Scire et al. (2000b), was selected for use for the air pollutant dispersion modelling for this Project. Calpuff is an air pollutant transport and dispersion model that advects puffs of material emitted from modelled sources, simulating the time evolution of dispersion and transformation processes. Calpuff is a non-steady-state Lagrangian Gaussian puff model including modules for: complex terrain effects, coastal interaction effects, building downwash, and wet and dry removal of pollutants as they contact the ground surface.

The model accounts for effects such as spatial variability of meteorological conditions, dispersion over a variety of spatially varying land surfaces, plume fumigation, and low wind speed dispersion (EPA, 2016). Calpuff includes algorithms for air pollutant dispersion including the use of turbulence-based dispersion coefficients derived from similarity theory or observations; e.g., *Generic Guidance and Optimum Model Settings for the CALPUFF Modeling System for Inclusion into the 'Approved Methods for the Modeling and Assessments of Air Pollutants in NSW, Australia'* (Barclay and Scire for NSW Office of Environment and Heritage (2011); NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016).

The key part of the NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) assessment process comprises comparisons of the model results for Ground Level Concentrations (GLCs) with the impact assessment criteria listed in Section 3.4.

The Calpuff settings used for the Project followed the general guidance for using the model by Barclay and Scire (2011). Wake effects due to the layout and heights of the Project infrastructure were included. The Project gas turbine exhaust stacks were included as point sources (emissions parameters were detailed in Section 2.5).

Table 5.3: Calpuff air pollutant dispersion modelling parameters

| Parameter                            | Value                                                                                                                                                                                                                                                                                     |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Computational grid domain            | 30 km east-west by 20 km north-south<br>120 x 80 horizontal grid receptors, resolution 250 metres, giving 9600 grid receptors<br>Additional 16 discrete receptors representing sensitive receptor locations<br>9 height layers: 0, 20, 40, 80, 160, 320, 700, 1200, 1500, 2000 metres     |
| Input surface meteorological data    | Kurri Kurri surface location data produced by TAPM with assimilation of Beresfield surface wind measurements.                                                                                                                                                                             |
| Input upper-air meteorological data  | Kurri upper air station data produced by TAPM including with assimilation of Beresfield surface wind measurements. Vertical layer bias settings were biased towards the surface observations (settings: -1, -0.8, -0.6, -0.4, -0.2, 0, 0, 0, 0).                                          |
| Simulation year                      | All hours of 2018 (except final hour – Calmet stop)                                                                                                                                                                                                                                       |
| Chemical species modelled            | NO <sub>x</sub> , SO <sub>2</sub> , CO, VOCs as xylene, PM <sub>2.5</sub> , with gaseous dry deposition calculations included (PM <sub>2.5</sub> did not include deposition, so results for ground-level concentrations are conservative).                                                |
| Building height profile wake effects | PRIME method used to simulate building downwash, and stack tip downwash activated                                                                                                                                                                                                         |
| Dispersion option                    | Dispersion coefficients from internally calculated sigma-v, sigma-w using micrometeorological variables ( $u^*$ , $w^*$ , $L$ , etc.). Standard Calpuff routines to compute turbulence sigma-v and sigma-w using micrometeorological variables; for more details see Scire et al. (2000b) |
| Terrain adjustment                   | Partial plume path adjustment                                                                                                                                                                                                                                                             |
| Number of sources                    | Two point sources – GT stacks, heights 60 metres (see Section 2.5 for details).                                                                                                                                                                                                           |

## 5.6 Peak-to-mean ratio

The Calpuff modelling was limited to hourly average data; the main simulation involved the processing of a simulated year of meteorological and air dispersion data, or 8760 hours of simulations. Outputs from the modelling therefore were also limited to hourly averages, such as air pollutant concentrations. Some of the NSW EPA (2016) *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* air quality assessment criteria had sub-hourly averaging periods (Section 3.4), as such a method was needed to convert hourly-average GLCs due to point source emissions to a sub-hourly average GLC. Also, hourly-average concentrations for the ambient (separate) air pollutant concentrations, which could be from any source type (point, volume, etc.), were then converted to a sub-hourly average GLC. To do this Peak-to-Mean Ratios (PMR) were calculated using the peak concentration ( $C_p$ ) and mean concentration ( $C_m$ ) using equation (1),

$$C_p = C_m(t_p/t_m)^p, \quad (1)$$

where  $t_p$  is the averaging period of the peak concentration, and  $t_m$  is the averaging period of the 'mean' concentration (the latter all one-hour averages for the Project assessment), and  $p$  is an exponent determined by Borgas (2000). The values of the exponents and calculated PMRs used for this assessment are listed in Table 5.4.

Table 5.4: Calculated Peak-to-Mean Ratios used in assessment

| Parameter                                                              | Point source | General source |
|------------------------------------------------------------------------|--------------|----------------|
| Exponent 'p'                                                           | 0.353        | 0.1            |
| PMR: 10-minute average e.g. SO <sub>2</sub> (from mean 1-hour average) | 1.88         | 1.20           |
| PMR: 15-minute average e.g. CO (from mean 1-hour average)              | 1.63         | 1.15           |

## 5.7 NO<sub>x</sub> to NO<sub>2</sub> conversion: OLM technique

Some background information to the air chemistry involved in the conversion of ambient NO<sub>x</sub> to NO<sub>2</sub> was provided in Section 4.4.5 (ambient NO<sub>x</sub>) and Section 4.4.6 (ambient O<sub>3</sub>). This sub-section explains how model results for dispersed NO<sub>x</sub> were converted to NO<sub>2</sub> GLCs using hourly background NO<sub>2</sub> and O<sub>3</sub> data; the technique is known as the Ozone Limiting Method (OLM), detailed in NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016).

The OLM was used to predict NO<sub>2</sub> GLCs. The method assumes all the available O<sub>3</sub> reacts with NO using all available (ambient) O<sub>3</sub> or NO. NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) warns the method assumes an instant reaction whereas in the atmosphere, the reaction takes place over a number of hours. The NO<sub>2</sub> concentration [NO<sub>2</sub>] at a point, in any hour, is determined by,

$$[\text{NO}_2] = 10\% [\text{NO}_x]^P + \text{minimum} \{90\% [\text{NO}_x]^P \text{ or } 46/48 \times [\text{O}_3]^B\} + [\text{NO}_2]^B, \quad (2)$$

where [NO<sub>x</sub>]<sup>P</sup> is the model-predicted NO<sub>x</sub> concentration, [O<sub>3</sub>]<sup>B</sup> is the background or measured O<sub>3</sub> concentration in that hour, and [NO<sub>2</sub>]<sup>B</sup> the background NO<sub>2</sub> concentration in that hour (units all µg/m<sup>3</sup>); e.g., NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016). The background NO<sub>2</sub> and O<sub>3</sub> data used for these calculations for the assessment were obtained from the DPIE Beresfield monitoring station.

## 5.8 NSW EPA ozone assessment

While the method described in Section 5.7 is adequate for estimating maximum NO<sub>2</sub> concentrations, the interplay between NO<sub>2</sub> and ozone (O<sub>3</sub>) formation by photochemical processes in the ambient atmosphere is more complex. The photochemical production of O<sub>3</sub> involves many emissions sources, many air pollutants, and usually covers a large study area; e.g., see the modelling studies of the NSW Greater Metropolitan Region (GMR) by Duc et al. (2018), NSW DPIE (2020); and Duc et al. (2021).

Inspection of the NSW DPIE (2020) results for O<sub>3</sub> across the GMR indicates a single power generation source in the Lower Hunter region would contribute O<sub>3</sub> concentrations of up to approximately 1 ppb (e.g. 2 µg/m<sup>3</sup> at 20°C), with typical background O<sub>3</sub> concentrations being approximately 20 ppb (e.g. 40 µg/m<sup>3</sup> at 20°C). While a sophisticated photochemical modelling study of the Newcastle-Lower Hunter airshed was outside the scope of this study, increased O<sub>3</sub> concentrations associated with the Project were estimated using the NSW EPA's *Tiered Procedure for Estimating Ground-Level Ozone Impacts from Stationary Sources* (NSW EPA, 2011).

A summary of the NSW EPA (2011) procedure is provided in the following points:

- O<sub>3</sub> monitoring data for the region of interest (Lower Hunter for this Project), is used to determine whether the Project was in an 'Ozone Attainment Area' (affirmative in this case).
- If the source emissions are above an emission threshold a 'Level 1' screening assessment is triggered using the 'Screening Tool' (Microsoft spreadsheet) provided online: <https://www.epa.nsw.gov.au/-/media/epa/corporate-site/resources/air/150507-ozone-procedure-tool.xls?la=en&hash=2FDD721DC550AB6E3B3560B8499FD475128ADF7A>, accessed 18 July 2021.
- The Screening Tool estimates increases in 1-hour and 4-hour average ground-level O<sub>3</sub> concentrations for a source specified by its daily emissions of methane, CO, NO<sub>x</sub> and/or VOCs, and using O<sub>3</sub> monitoring data.



- The resulting increases are compared with calculated maximum allowable O<sub>3</sub> increments, and a determination made if further more detailed studies are required.

The results of the NSW EPA (2011) ozone procedure are described in Section 6.7.

## **5.9 Airborne particulate matter**

The results for airborne particulate matter as PM<sub>10</sub> were not assessed as nearly all the particles are expected to be in the PM<sub>2.5</sub> size range (Australian Government, 2008). Also, the assessment of particulate emissions as PM<sub>2.5</sub> was more conservative than PM<sub>10</sub> given that the PM<sub>2.5</sub> standards are lower (Section 3.4).

## 6. Results

### 6.1 Overview

This section provides the Calpuff results for Ground Level Concentrations as contour plots in accordance with NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016), and summary tables and discussions of results. The results are provided for the Project based on the maximum (100 per cent) load case, which was determined by sensitivity testing with Calpuff to be the worst-case operating scenario (i.e. the 50 per cent load case was tested by modelling also).

The Project is for a capacity factor of up to 10 per cent on natural gas fuel and two per cent on diesel fuel. However, it is expected that likely operations would result in a capacity factor of approximately two per cent. Modelling of continuous emissions from the Project was undertaken to test every hour of an annual meteorological simulation – this was a conservative approach taken for the assessment.

Also, annual average GLCs were reported as calculated from the continuous emissions estimates; i.e. not reduced to account for the capacity factors. The reason for this was the annual averages were very small, and immaterial to the outcomes of the assessment.

A Level 2 air quality impact assessment was carried out for SO<sub>2</sub>, NO<sub>2</sub>, PM<sub>2.5</sub> and CO using contemporaneous measurements and model data in accordance with the NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) modelling assessment guideline. Level 2 assessments for these substances are conducted using the data and steps listed in the following points:

- Ambient air monitoring data (hourly averages) included at least one year of continuous measurements and were contemporaneous with the meteorological data used for dispersion modelling
- The dispersion model prediction for each receptor, for each hour, was added to the corresponding estimate for the background concentration in that hour to obtain the total concentration
- The maximum total concentrations in each hour, for each receptor, were compared with criteria for the substances tested.

For Level 2 assessment of the air pollutants, the model-predicted 99.9<sup>th</sup>-percentile hourly average concentrations, (without background estimates), and these were compared with the impact assessment criteria at and beyond the Project boundaries (in this case at all 9600 grid receptor and 16 discrete receptor locations on the modelling grid). The 16 discrete receptor locations represent the 16 sensitive receptors identified in Section 4.2.

The modelling grid used to define the base map used for the contour plots was detailed in Section 5.5. The axes are labelled with GDA 2020 northings in units of metres (labelled in black on vertical axis), and eastings (m) on the horizontal axis. Units for the GLCs are mg/m<sup>3</sup> for the CO results, and µg/m<sup>3</sup> for all other results.

## 6.2 Calpuff results for carbon monoxide

### 6.2.1 Calpuff results: maximum 15-minute average CO GLC

The Calpuff results for maximum 15-minute average CO GLCs ( $\text{mg}/\text{m}^3$ ) for the 9600 grid receptors are depicted in the figures below (natural gas–top; diesel–bottom); Project contributions only.




Figure 6-1: Maximum 15-minute average CO GLC ( $\text{mg}/\text{m}^3$ ): natural gas (top) and diesel (bottom)



### 6.2.2 Calpuff results: maximum 1-hour average CO GLC

The Calpuff results for maximum 1-hour average CO GLCs ( $\text{mg}/\text{m}^3$ ) for the 9600 grid receptors are depicted in the figures below (natural gas–top; diesel–bottom); Project contributions only.




Figure 6-2: Maximum 1-hour average CO GLC ( $\text{mg}/\text{m}^3$ ): natural gas (top) and diesel (bottom)



### 6.2.3 Calpuff results: maximum 8-hour average CO GLC

The Calpuff results for maximum eight-hour average CO GLCs ( $\text{mg}/\text{m}^3$ ) for the 9600 grid receptors are depicted in the figures below (natural gas–top; diesel–bottom); Project contributions only.




Figure 6-3: Maximum 8-hour average CO GLC ( $\text{mg}/\text{m}^3$ ): natural gas (top) and diesel (bottom)



#### 6.2.4 Summary and analysis of results: CO

This section provides a summary of all Calpuff results for CO for the 9600 Grid Receptors (GR) and the worst case (highest) results for the 16 Discrete Receptors (DR). Summaries of Calpuff results for CO for the OCGT's operating at 100 per cent load are provided in Table 6.1 (natural gas-fuelled case); and Table 6.2 (diesel-fuelled case). The units for all CO concentrations are mg/m<sup>3</sup>. There were no CO measurements data available for EPA Beresfield, so EPA Newcastle data were used as background. The notes apply to both tables.

Table 6.1: Summary of Calpuff results for CO: natural gas-fuelled and 100% load (mg/m<sup>3</sup>)

| Average period         | NSW Assessment Criterion | Max. background | Project max. GR result including background | Project max. DR result including background | Max. assessment result as fraction of Criterion |
|------------------------|--------------------------|-----------------|---------------------------------------------|---------------------------------------------|-------------------------------------------------|
| 15-minute <sup>1</sup> | 100                      | 1.578           | 1.578                                       | 1.578                                       | 1.58%                                           |
| 1 hour                 | 30                       | 1.374           | 1.374                                       | 1.374                                       | 4.58%                                           |
| 8 hour <sup>2</sup>    | 10                       | 0.987           | 0.988                                       | 0.987                                       | 9.88%                                           |

Table 6.2: Summary of Calpuff results for CO: diesel-fuelled; 100% load (mg/m<sup>3</sup>)

| Average period         | NSW Assessment Criterion | Max. background | Project max. GR result including background | Project max. DR result including background | Max. assessment result as fraction of Criterion |
|------------------------|--------------------------|-----------------|---------------------------------------------|---------------------------------------------|-------------------------------------------------|
| 15-minute <sup>1</sup> | 100                      | 1.578           | 1.579                                       | 1.578                                       | 1.58%                                           |
| 1 hour                 | 30                       | 1.374           | 1.374                                       | 1.374                                       | 4.58%                                           |
| 8 hour <sup>2</sup>    | 10                       | 0.987           | 0.988                                       | 0.988                                       | 9.88%                                           |

1. 15-minute averages for CO estimated from hourly averages using Peak-to-Mean Ratios (PMR): 1.63 (point sources, from Calpuff results for hourly average GLCs); and 1.20 (volume sources, from monitoring results for hourly average GLCs); see Section 5.6.

2. NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) assessment criterion is a standard (step-wise) 8-hour average. The corresponding NEPM standard is a rolling 8-hour average (NEPC, 2016).

The Calpuff results for cumulative, ambient CO concentrations due to emissions from the Project including background CO are low in comparison to the impact assessment criteria. The results for maxima (columns four and five) are very similar to background (column three) because the modelled contributions due to the Project were very small. The results indicate there is no significant risk of air quality impacts due to CO emissions from the Project operating at 100 per cent load, whether fuelled by natural gas or diesel, at any time of the year.

The updated modelling indicates that the detailed design has had negligible effect on ground level concentrations of CO, when compared with the air quality modelling results produced for the Project EIS.

## 6.3 Calpuff results for sulphur dioxide

### 6.3.1 Calpuff results: maximum 10-minute average SO<sub>2</sub> GLC

The Calpuff results for maximum 10-minute average SO<sub>2</sub> GLCs ( $\mu\text{g}/\text{m}^3$ ) for the 9600 grid receptors are depicted in the figures below (natural gas–top; diesel–bottom); Project contributions only.





Figure 6-4: Maximum 10-minute average SO<sub>2</sub> GLC ( $\mu\text{g}/\text{m}^3$ ): natural gas (top) and diesel (bottom)




The Calpuff results for maximum one-hour average SO<sub>2</sub> GLCs (µg/m<sup>3</sup>) for the 9600 grid receptors are depicted in the figures below (natural gas-top; diesel-bottom); Project contributions only.





### 6.3.3 Calpuff results: maximum 24-average SO<sub>2</sub> GLC

The Calpuff results for maximum 24-hour average SO<sub>2</sub> GLCs ( $\mu\text{g}/\text{m}^3$ ) for the 9600 grid receptors are depicted in the figures below (natural gas–top; diesel–bottom); Project contributions only.





### 6.3.4 Calpuff results: annual average SO<sub>2</sub> GLC

The Calpuff results for annual average SO<sub>2</sub> GLCs ( $\mu\text{g}/\text{m}^3$ ) for the 9600 grid receptors are depicted in the figures below (natural gas–top; diesel–bottom); Project contributions only.




Figure 6-7: Annual average SO<sub>2</sub> GLC ( $\mu\text{g}/\text{m}^3$ ): natural gas (top) and diesel (bottom)

### 6.3.5 Summary and Analysis of results: SO<sub>2</sub>

This section provides a summary of all Calpuff results for SO<sub>2</sub> for the 9600 Grid Receptors (GR) and the worst case (highest) results for the 16 sensitive receivers (referred to in the model as Discrete Receptors (DR). Summaries of Calpuff results for SO<sub>2</sub> for the OCGT's operating at 100 per cent load are provided in Table 6.3 (natural gas-fuelled); and Table 6.4 (diesel-fuelled). The units for all SO<sub>2</sub> concentrations are µg/m<sup>3</sup>. The notes apply to both tables.

Table 6.3: Summary of Calpuff results for SO<sub>2</sub>: natural gas-fuelled; 100% load (µg/m<sup>3</sup>)

| Average period         | NSW Assessment Criterion | Max. background | Project max. GR result including background | Project max. DR result including background | Max. assessment result as fraction of Criterion |
|------------------------|--------------------------|-----------------|---------------------------------------------|---------------------------------------------|-------------------------------------------------|
| 10 minute <sup>1</sup> | 712                      | 219.257         | 219.960                                     | 219.310                                     | 30.89%                                          |
| 1 hour                 | 570                      | 183.290         | 183.720                                     | 183.320                                     | 32.19%                                          |
| 24 hour                | 228                      | 18.765          | 18.844                                      | 18.771                                      | 8.25%                                           |
| annual                 | 60                       | 4.204           | 4.221                                       | 4.215                                       | 7.03%                                           |

Table 6.4: Summary of Calpuff results for SO<sub>2</sub>: diesel-fuelled; 100% load (µg/m<sup>3</sup>)

| Average period         | NSW Assessment Criterion | Max. background | Project max. GR result including background | Project max. DR result including background | Max. assessment result as fraction of Criterion |
|------------------------|--------------------------|-----------------|---------------------------------------------|---------------------------------------------|-------------------------------------------------|
| 10 minute <sup>1</sup> | 712                      | 219.257         | 219.370                                     | 219.270                                     | 30.81%                                          |
| 1 hour                 | 570                      | 183.290         | 183.360                                     | 183.300                                     | 32.17%                                          |
| 24 hour                | 228                      | 18.765          | 18.777                                      | 18.765                                      | 8.24%                                           |
| annual                 | 60                       | 4.204           | 4.207                                       | 4.206                                       | 7.01%                                           |

1. 10-minute averages for SO<sub>2</sub> estimated from hourly averages using Peak-to-Mean Ratios (PMR): 1.88 (point sources, from Calpuff results for hourly average GLCs); and 1.20 (volume sources, from monitoring results for hourly average GLCs); see Section 5.6.

Note: Temperature 25°C.

The Calpuff results for cumulative, ambient SO<sub>2</sub> concentrations due to emissions from the Project, including estimates for background SO<sub>2</sub>, are low in comparison to the impact assessment criteria. The results for maxima (columns 4 & 5) are very similar to background (column 3) because the modelled contributions due to the Project were very small. The results indicate there is no significant risk of air quality impacts due to SO<sub>2</sub> emissions from the Project operating at 100 per cent load, whether natural gas-fuelled or diesel-fuelled, at any time of the year.

The updated modelling therefore indicates that the detailed design has had negligible effect on ground level concentrations of SO<sub>2</sub>, when compared with the air quality modelling results produced for the Project EIS.



## 6.4 Calpuff results for particulate matter as PM<sub>2.5</sub>

### 6.4.1 Calpuff results: maximum 24-hour average PM<sub>2.5</sub> GLC

The Calpuff results for maximum 24-hour average PM<sub>2.5</sub> GLCs ( $\mu\text{g}/\text{m}^3$ ) for the 9600 grid receptors are depicted in the figures below (natural gas-top; diesel-bottom); Project contributions only.




Figure 6-8: Maximum 24-hour average PM<sub>2.5</sub> GLC ( $\mu\text{g}/\text{m}^3$ ): natural gas (top) and diesel (bottom)



#### 6.4.2 Calpuff results: annual average PM<sub>2.5</sub> GLC

The Calpuff results for annual average PM<sub>2.5</sub> GLCs ( $\mu\text{g}/\text{m}^3$ ) for the 9600 grid receptors are depicted in the figures below (natural gas–top; diesel–bottom); Project contributions only.




Figure 6-9: Annual average PM<sub>2.5</sub> GLC ( $\mu\text{g}/\text{m}^3$ ): natural gas (top) and diesel (bottom)



### 6.4.3 Summary and analysis of results: PM<sub>2.5</sub>

This section provides a summary of all Calpuff results for PM<sub>2.5</sub> for the 9600 Grid Receptors (GR) and the worst case (highest) results for the 16 sensitive receivers (referred to in the model as Discrete Receptors (DR)). Summaries of Calpuff results for PM<sub>2.5</sub> for the OCGT's operating at 100 per cent load are provided in Table 6.5 (natural gas-fuelled); and Table 6.6 (diesel-fuelled). The units for all PM<sub>2.5</sub> concentrations are µg/m<sup>3</sup>. The notes apply to both tables.

Table 6.5: Summary of Calpuff results for PM<sub>2.5</sub>: natural gas-fuelled; 100% load (µg/m<sup>3</sup>)

| Average period | NSW Assessment Criterion | Max. background | Project max. GR result including background | Project max. DR result including background | Max. assessment result as fraction of Criterion |
|----------------|--------------------------|-----------------|---------------------------------------------|---------------------------------------------|-------------------------------------------------|
| 24 hours       | 25                       | 24.917          | 25.133                                      | 25.020                                      | 100.53%                                         |
| Annual         | 8                        | 8.670           | 8.686                                       | 8.680                                       | 108.58%                                         |

Table 6.6: Summary of Calpuff results for PM<sub>2.5</sub>: diesel-fuelled; 100% load (µg/m<sup>3</sup>)

| Average period | NSW Assessment Criterion | Max. background | Project max. GR result including background | Project max. DR result including background | Max. assessment result as fraction of Criterion |
|----------------|--------------------------|-----------------|---------------------------------------------|---------------------------------------------|-------------------------------------------------|
| 24 hours       | 25                       | 24.917          | 25.391                                      | 25.126                                      | 101.56%                                         |
| Annual         | 8                        | 8.670           | 8.708                                       | 8.695                                       | 108.85%                                         |

1. Note the results for PM<sub>2.5</sub> are high due to existing, high background levels. The contributions due to the Project are 'very small' (annual averages), and 'small' (maximum 24-hour averages), relative to the criteria.

As can be seen from the model results, PM<sub>2.5</sub> contributions due to the Project would be negligible relative to air quality criteria and background concentrations. Concentrations of PM<sub>2.5</sub>, including with potential contributions from the Project, would continue to be within the range of historically measured fluctuations in maximum concentrations for the region. Table 4.6 and Figure 4-4 showed the 24-hour average PM<sub>2.5</sub> concentrations measured at DPIE Beresfield monitoring station over 2015–2019. Over this 5-year period, exceedences of the PM<sub>2.5</sub> criteria occurred in all years except 2017. Reasons for the higher measured concentrations over this 5-year period were bushfire smoke and raised dust (the latter due to periods of higher wind speeds). All the predicted increases due to the Project are insignificant in relation to these background concentrations.

The worst-case DR results for 24-hour average PM<sub>2.5</sub> were obtained for the diesel-fuelled case; these are illustrated further by the time series plot shown in Figure 6-10. (The corresponding worst case DR results for the natural gas-fuelled case have a very similar appearance when plotted in this way). The plot shows results for 24-hourly average PM<sub>2.5</sub> concentrations (µg/m<sup>3</sup>) for all 365 days of 2018: modelled results of the Project concentrations are shown in blue (without background); the background (EPA Beresfield) results are shown in yellow, which clearly dominate the results, and the NSW Assessment Criterion is shown in red (25 µg/m<sup>3</sup>).

The updated modelling shows a very small reduction in ground level concentrations of PM<sub>2.5</sub>, for the detailed design when compared with the Proposal design assessed in the Project EIS.




Figure 6-10: 24-hour average PM<sub>2.5</sub> background and modelled Project concentrations for worst case discrete receptor (diesel-fuelled case)

## 6.5 Calpuff results for nitrogen dioxide

### 6.5.1 Calpuff results: maximum 1-hour average NO<sub>2</sub> GLC

The Calpuff results for maximum hourly average NO<sub>2</sub> GLCs (µg/m<sup>3</sup>) for the 9600 grid receptors are depicted in the figures below (natural gas-top; diesel-bottom); Project contributions only. Further analysis of the modelled NO<sub>x</sub> results is provided in Section 6.5.3.




Figure 6-11: Maximum 1-hour average NO<sub>2</sub> GLC (µg/m<sup>3</sup>): natural gas (top) and diesel (bottom)



### 6.5.2 Calpuff results: annual average NO<sub>2</sub> GLC

The Calpuff results for annual average NO<sub>2</sub> GLCs ( $\mu\text{g}/\text{m}^3$ ) for the 9600 grid receptors are depicted in the figures below (natural gas–top; diesel–bottom); Project contributions only. Further analysis of the modelled NO<sub>x</sub> results is provided in Section 6.5.3.




Figure 6-12: Annual average NO<sub>2</sub> GLC ( $\mu\text{g}/\text{m}^3$ ): natural gas (top) and diesel (bottom)

### 6.5.3 Summary and Analysis of results: NO<sub>2</sub>

This section provides a summary of all Calpuff results for NO<sub>2</sub> for the 9600 Grid Receptors (GR) and the worst case (highest) results for the 16 sensitive receivers (referred to in the model as Discrete Receptors (DR)). Summaries of Calpuff results for NO<sub>2</sub> for the OCGT's operating at 100 per cent load are provided in Table 6.7 (natural gas-fuelled); and Table 6.8 (diesel-fuelled). The notes apply to both tables.

Table 6.7: Summary of Calpuff results for NO<sub>2</sub>: natural gas-fuelled; 100% load (µg/m<sup>3</sup>)

| Average period | NSW Assessment Criterion | Max. background | Project max. GR result including background | Project max. DR result including background | Max. assessment result as fraction of Criterion |
|----------------|--------------------------|-----------------|---------------------------------------------|---------------------------------------------|-------------------------------------------------|
| 1h             | 246                      | 75.209          | 86.798                                      | 75.209                                      | 35.28%                                          |
| Annual         | 62                       | 16.054          | 16.072                                      | 16.159                                      | 26.06%                                          |

Table 6.8: Summary of Calpuff results for NO<sub>2</sub>: diesel-fuelled; 100% load (µg/m<sup>3</sup>)

| Average period | NSW Assessment Criterion | Max. background | Project max. GR result including background | Project max. DR result including background | Max. assessment result as fraction of Criterion |
|----------------|--------------------------|-----------------|---------------------------------------------|---------------------------------------------|-------------------------------------------------|
| 1h             | 246                      | 75.209          | 94.147                                      | 75.209                                      | 38.27%                                          |
| Annual         | 62                       | 16.054          | 16.088                                      | 16.259                                      | 26.22%                                          |

1. The estimate of the NO<sub>2</sub>/NO<sub>x</sub> ratio (10%) used to analyse the GR results was determined by tuning the results for the GRs plus a statistical estimate for background NO<sub>2</sub> to the results obtained by the more involved OLM Level 2 assessment method. The tuning led to the selection of a NO<sub>2</sub>/NO<sub>x</sub> ratio of 10% for the Project contributions with the 99<sup>th</sup> percentile 1-hour average background NO<sub>2</sub> concentration. The purpose of this tuning procedure was to select a NO<sub>2</sub>/NO<sub>x</sub> ratio for plotting the Project NO<sub>2</sub> contributions; i.e., the contour plots in this section. Note that this ratio is different to the NO<sub>2</sub>/NO<sub>x</sub> ratio of around 20%-30% generally observed for higher NO<sub>x</sub> concentrations.

The results for NO<sub>2</sub> were determined using the Ozone Limiting Method (refer Section 5.7), which combined the Calpuff results for NO<sub>x</sub> dispersion at ground level with EPA Beresfield monitoring data for NO<sub>2</sub> and O<sub>3</sub>. There were no predicted exceedances of the impact assessment criteria for NO<sub>2</sub>. Many of the results for maxima (columns four and five) were very similar to background (column three) because most of the modelled contributions due to the Project were small.

The worst-case DR results for hourly average NO<sub>2</sub> were obtained for the diesel-fuelled case; these are illustrated further by the time series plot shown in Figure 6-13. (The corresponding worst case DR results for the natural gas-fuelled case have a very similar appearance when plotted in this way). The plot shows results for hourly average NO<sub>2</sub> concentrations (µg/m<sup>3</sup>) for all 8760 hours of 2018: modelled results of the Project concentrations are shown in blue (without background); background (EPA Beresfield) concentrations are shown in yellow, which clearly dominate the results, and the NSW Assessment Criterion is shown in red (246 µg/m<sup>3</sup>).

The updated modelling therefore indicates that apart from a very minor increase in the 1-hour NO<sub>2</sub> concentration for natural gas operation, the detailed design has had negligible effect on ground level concentrations of NO<sub>2</sub>, when compared with the air quality modelling results produced for the Project EIS.




Figure 6-13: Hourly average NO<sub>2</sub> background and modelled Project concentrations for worst case discrete receptor (diesel-fuelled case)



## 6.6 Calpuff results for hydrocarbons (VOCs)

### 6.6.1 Calpuff results: 99.9<sup>th</sup> percentile one-hour average CH<sub>2</sub>O GLC

The Calpuff results for 99.9<sup>th</sup> percentile (PC) one-hour average formaldehyde (CH<sub>2</sub>O) GLCs ( $\mu\text{g}/\text{m}^3$ ) for the 9600 grid receptors are depicted in the figures below (natural gas–top; diesel–bottom); Project contributions only.




Figure 6-14: 99.9<sup>th</sup> PC 1-hour average CH<sub>2</sub>O GLC ( $\mu\text{g}/\text{m}^3$ ): natural gas (top) and diesel (bottom)



### 6.6.2 Calpuff results: 99.9<sup>th</sup> percentile 1-hour average acrolein and B(a)P GLC

The Calpuff results for the 9600 grid receptors for the following two cases are depicted in the figure below, for the Project contributions only: (1) 99.9<sup>th</sup> percentile (PC) one-hour average acrolein GLCs ( $\mu\text{g}/\text{m}^3$ ) for the natural gas fuel case only; and (2) 99.9<sup>th</sup> percentile (PC) one-hour average B(a)P GLCs ( $\mu\text{g}/\text{m}^3$ ) for the diesel fuel case only.




Figure 6-15: 99.9<sup>th</sup> PC one-hour average GLCs: natural gas–acrolein ( $\mu\text{g}/\text{m}^3$ ) (top); and B(a)P–diesel ( $\mu\text{g}/\text{m}^3$ ) (bottom)

### 6.6.3 Summary and analysis of VOCs results

This section provides a summary of Calpuff results for the 9600 Grid Receptors (GR) and the worst case (highest) results for the 16 sensitive receivers (referred to in the model as Discrete Receptors (DR)), for the highest risk VOCs identified for the Project: formaldehyde (CH<sub>2</sub>O) and acrolein for the natural gas fuel case (Table 6.9), and CH<sub>2</sub>O and PAH as B(a)P for the diesel fuel case (Table 6.10). The units for all VOC concentrations are µg/m<sup>3</sup>.

In accordance with the *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* Level 2 assessment method, comparisons of model results with criteria for the VOCs do not include estimates for background i.e. is not 'cumulative'. (The estimates for background VOC concentrations in Section 4.4.6 provided context only for this assessment).

Table 6.9: Summary of Calpuff results: 99.9<sup>th</sup> percentile 1h-average VOCs: natural gas-fuelled case (µg/m<sup>3</sup>)

| VOC          | NSW Assessment Criterion | Estimated background | Project GR result excluding background | Project DR result excluding background | Max. assessment result (Project); fraction of Criterion |
|--------------|--------------------------|----------------------|----------------------------------------|----------------------------------------|---------------------------------------------------------|
| formaldehyde | 20                       | 2.7                  | 0.078                                  | 0.036                                  | 0.39%                                                   |
| acrolein     | 0.42                     | 0.3                  | 0.001                                  | <0.001                                 | 0.17%                                                   |

Table 6.10: Summary of Calpuff results for 99.9<sup>th</sup> percentile 1h-average VOCs: diesel-fuelled case (µg/m<sup>3</sup>)

| VOC          | NSW Assessment Criterion | Estimated background | Project GR result excluding background | Project DR result excluding background | Max. assessment result (Project); fraction of Criterion |
|--------------|--------------------------|----------------------|----------------------------------------|----------------------------------------|---------------------------------------------------------|
| formaldehyde | 20                       | 2.7                  | 0.023                                  | 0.013                                  | 0.11%                                                   |
| PAH as B(a)P | 0.4                      | 0.001                | 0.003                                  | 0.002                                  | 0.82%                                                   |

There were no predicted exceedances of the impact assessment criteria for formaldehyde (20 µg/m<sup>3</sup>). The background formaldehyde concentrations are significantly higher than predicted contributions due to the Project.

There were no predicted exceedances of the impact assessment criteria for acrolein (0.42 µg/m<sup>3</sup>) and B(a)P (0.4 µg/m<sup>3</sup>). The background acrolein concentrations are significantly higher than predicted contributions due to the Project. Project contributions of B(a)P are greater than background, but overall the B(a)P concentrations are very low, of the order one per cent of the criteria. In summary, the risk of air quality impacts due to VOC emissions from the Project is very low.

The revised modelling therefore indicates that the detailed design has resulted in a very slight reduction in ground level concentrations of VOC, when compared with the air quality modelling results produced for the Project EIS.



## 6.7 Ozone assessment

This section describes the results of an O<sub>3</sub> assessment undertaken using the NSW EPA's *Tiered Procedure for Estimating Ground-Level Ozone Impacts from Stationary Sources* (NSW EPA, 2011); see Section 5.8. The conclusion is the O<sub>3</sub> contributions caused by the Project are likely to be negligible.

Comparisons of maximum O<sub>3</sub> concentrations measured by DPIE Beresfield over 2016–2020 inclusive were used to determine that the Project Site is in a NSW EPA (2011) specified ozone non-attainment area; i.e., the background O<sub>3</sub> levels are relatively high; a summary of the results is provided in Table 6.11.

Table 6.11: Ozone attainment area determination

| Parameter                        | Max. 1h O <sub>3</sub> (ppb)                                                                                                                                              | Max. 4h O <sub>3</sub> (ppb) | Notes                                                          |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|----------------------------------------------------------------|
| Average of maxima 2016–2020      | 98.9                                                                                                                                                                      | 83.8                         | High results related to bushfire emissions                     |
| NEPM standards (NEPC, 2016) x82% | 82                                                                                                                                                                        | 65.6                         | EPA (2011) referred to the equivalent of NEPC (2016) standards |
| Result                           | Project air quality study area in Lower Hunter is an ozone non-attainment area because the concentrations exceeded the NSW EPA (2011) thresholds (82% of NEPM standards). |                              |                                                                |

The second step was to compare the Project's annual NO<sub>x</sub>/VOC emissions with the threshold of 90 tonnes/year. The NO<sub>x</sub> emission from the Project would be approximately 149 tonnes per year using a capacity factor of 12%, (10% on natural gas and 2% on diesel). The capacity factor estimate used here was for this calculation only, and triggered a 'Level 1' assessment using the Level 1 screening tool. DPIE measurements of O<sub>3</sub> from Beresfield, Newcastle and Wallsend over a five-year period, 2016–2020 inclusive, were used as input to the tool; the results are detailed in Table 6.12.

Table 6.12: Results from Level 1 screening assessment tool

| Parameter                                       | Project result, NG fuel | Project result, diesel fuel | Assessment result                             |
|-------------------------------------------------|-------------------------|-----------------------------|-----------------------------------------------|
| Maximum 1-hour average O <sub>3</sub> increment | 2.0 ppb                 | 3.2 ppb                     | Greater than screening impact level (0.5 ppb) |
| Maximum 4-hour average O <sub>3</sub> increment | 1.3 ppb                 | 2.0 ppb                     | Greater than screening impact level (0.5 ppb) |

The results for the maximum increments listed in Table 6.12 exceed the screening impact levels of 0.5 ppb, and also the maximum allowable increment for ozone non-attainment areas, which is 1 ppb. As such some further investigations were carried out.

First, to place these ozone increments determined for the Project into context, recent NSW DPIE (2020) results for O<sub>3</sub> in the NSW GMR, using sophisticated photochemical modelling techniques, are shown in Figure 6-16. These show that even in the power generation intensive regions of Sydney and Wollongong, power stations cause increases in the O<sub>3</sub> concentrations of approximately 1 ppb only over the study area; i.e., small concentrations similar to those determined for this project. In Figure 6-16, note the contributions from power stations (approx. 0.1–1 ppb) and other human-made sources (approx. 1–10 ppb) are lower than typical background values (natural sources, approx. 18.4–22.0 ppb). These model results by DPIE (2020) are assumed to provide more accurate O<sub>3</sub> concentrations than the results of the EPA NSW (2011) tool listed in Table 6.12.

It is noted that the new NEPM replaces the maximum hourly and 4-hourly average O<sub>3</sub> standards with a single maximum 8-hour average (see Section 3.5). Measurements of 8-hour average O<sub>3</sub> concentrations at the DPIE Beresfield monitoring station exceed the new standard (65 ppb), due to bushfires, road traffic, other industrial sources, and the natural background. These exceedences can be expected to continue in future, but the current Beresfield dataset shows they should be rare; i.e., approximately 1–2 exceedences per year. Again using the NSW EPA (2011) method it is expected the 8-hour average O<sub>3</sub> contribution from the project will be less than 1 ppb (approximately 2 µg/m<sup>3</sup>); in summary, a minimal increase in O<sub>3</sub> levels is expected in future due to the Project.






Figure 6-16: NSW DPIE (2020) results for daily maximum 1-hour average O<sub>3</sub> concentration (ppb)

As a final illustration, the O<sub>3</sub> measurements at DPIE Beresfield over 2016-2020 are shown in Figure 6-17 (1-hour and 4-hour averages); and Figure 6-18 (rolling 8-hour averages). These results are typical of the variations in O<sub>3</sub> concentrations throughout the Lower Hunter. The peaks in the O<sub>3</sub> concentrations that can be clearly seen to occur in the summer months are very likely due to emissions from bushfires, road traffic, and other sources, superimposed on background levels typically around 20 ppb. Variations in the O<sub>3</sub> concentrations such as these occur all over the Lower Hunter region, and other parts of the NSW GMR. In comparison the maximum O<sub>3</sub> contributions calculated for the Project (0-3 ppb), are small, rare, and will occur in very few locations in comparison. In addition, these Project increments will not be at levels that would be likely to cause additional exceedances over background levels.

Figure 6-17: DPIE Beresfield maximum 1-hour and 4-hour average O<sub>3</sub> concentration (ppb)Figure 6-18: DPIE Beresfield maximum 8-hour average O<sub>3</sub> concentration (ppb)



## 6.8 Plant start-up and shut-down

The purpose of this section is to provide an assessment of plant start-up and shut-down, and variable load operations. This section has not been updated as the detailed design is consistent with the concept design assessed in the original Air Quality assessment that clearly indicated that the 100% load value to be the worst case as shown in Table 6.14.

For this peaker plant, the OCGT starts will occur for a fraction of a year. Specifically, based on 1000 operating hours in a year; i.e. capacity factor 11.4%, and run-times including start-ups varying between 1-4 hours, then the number of starts will vary between approximately 250 and 1000 per year. With a start-up duration to full load of 30 minutes, the time spent on starts (and with corresponding start-up emissions) equates to between 1% and 6% of a year (NG and diesel use).

An estimated F-Class GT ramp-up time from start to maximum speed is 20 minutes, at which point the GT is placed under load. From the 20-minute mark, the time to ramp up from zero to full load is approximately 10 minutes, making a total of 30 minutes from engine start to full load.

A summary of typical air emissions behaviour (i.e. mass emission rates) during start-up of the GT class assessed for this project is provided in the following points:

- NG-fuelled GT, typical start-up behaviour over 60 minutes:
  - CO emission increases to a peak approximately 15 minutes after ignition, then drops back rapidly to its 100% load value at approximately 20 minutes after ignition. The start-hour average CO concentration is expected to be greater than the 100% load value, however in relation to air quality impact this will be insignificant as the ambient air quality standard for CO is a rolling 8-hour average, and the predicted ambient CO concentrations are low in any case (see summary of results in Section 6.2.4).
  - NO<sub>x</sub> emission ramps approximately linearly to its 100% load value, potentially with some peaks in the NO<sub>x</sub> in the first 30 minutes. The start-hour average NO<sub>x</sub> concentration is expected to be less than or approximately equal to the 100% load value (immaterial to this assessment).
  - The SO<sub>x</sub> and PM<sub>10</sub> emissions ramp up approximately linearly to their maximum load values, so the emissions are low during start-up. The start-hour average concentrations for both substances are less than their 100% load values (immaterial to this assessment).
- Diesel-fuelled GT, typical start-up behaviour over 60 minutes:
  - CO emission increases to a peak approximately 15 minutes after ignition, then drops back rapidly to its 100% load value at approximately 20 minutes after ignition. The start-hour average CO concentration is expected to be greater than the 100% load value, however in relation to air quality impact this will be insignificant as the ambient air quality standard for CO is a rolling 8-hour average, and the predicted ambient CO concentrations are low in any case (see summary of results in Section 6.2.4), and diesel fuel starts will be rare (2% capacity factor vs. 10% capacity factor for NG).
  - NO<sub>x</sub> emission increases to a peak approximately 20 minutes after ignition, then drops back rapidly to its 100% load value about 5 minutes later. In this case the start-hour average NO<sub>x</sub> concentration is expected to be higher than the 100% load value, however this represents a low risk of air quality impact because the predicted ambient NO<sub>2</sub> concentrations are low (see summary of results for NO<sub>2</sub> in Section 6.5.3), and diesel fuel starts will be rare (2% capacity factor vs. 10% capacity factor for NG).
  - The SO<sub>x</sub> and PM<sub>10</sub> emissions ramp up approximately linearly to their maximum load values, so the emissions are low during start-up. The start-hour average concentrations for both substances are less than their 100% load values (immaterial to this assessment).

Calpuff sensitivity testing was undertaken for the OCGT emissions characteristics for the 50% load case to investigate the air quality effects associated with (1) plant start-up; and (2) running the plant continuously at half-load (Section 2.3.4). The emissions parameters for the GTs at 100% load and 50% load were detailed in Section 2.5; a summary of some of the main differences between these two scenarios is provided in Table 6.13.

Table 6.13: Gas turbine operating and air emissions parameters: 50% and 100% loads

| Fuel scenario and parameter                         | 50% load                  | 100% load                 |
|-----------------------------------------------------|---------------------------|---------------------------|
| <b>NG fuelled GT</b>                                |                           |                           |
| Exhaust flow rate at exhaust temperature            | 1,298.9 m <sup>3</sup> /s | 1,884.5 m <sup>3</sup> /s |
| Exhaust temperature                                 | 673.6 °C                  | 650 °C                    |
| Exhaust velocity                                    | 17.2 m/s                  | 40.8 m/s                  |
| NO <sub>x</sub> emission rate                       | 20.5 g/s                  | 35.3 g/s                  |
| CO emission rate                                    | 5.0 g/s                   | 4.8 g/s                   |
| SO <sub>x</sub> (as SO <sub>2</sub> ) emission rate | 1.61 g/s                  | 3.2 g/s                   |
| PM <sub>10</sub> emission rate                      | 1.9 g/s                   | 3.4 g/s                   |
| <b>Diesel fuelled GT</b>                            |                           |                           |
| Exhaust flow rate at exhaust temperature            | 1,223.0 m <sup>3</sup> /s | 1,666.6 m <sup>3</sup> /s |
| Exhaust temperature                                 | 591.4 °C                  | 525 °C                    |
| Exhaust velocity                                    | 16.2 m/s                  | 39.3 m/s                  |
| NO <sub>x</sub> emission rate                       | 33.4 g/s                  | 58.6 g/s                  |
| CO emission rate                                    | 24.2 g/s                  | 42.8 g/s                  |
| SO <sub>x</sub> (as SO <sub>2</sub> ) emission rate | 0.25 g/s                  | 0.5 g/s                   |
| PM <sub>10</sub> emission rate                      | 3.7 g/s                   | 6.8 g/s                   |

The Calpuff sensitivity tests showed the model-predicted GLCs for the 50% load case were lower than for the full-load case, even though the exit velocities were lower for half-load (Table 6.13). As such the main focus of this assessment was on the worst case operation; i.e., the 100% load case. The results of the sensitivity tests are provided in Table 6.14.

Table 6.14: Results of Calpuff sensitivity tests: 50% and 100% loads

| Fuel scenario and parameter                                                                        | 50% load | 100% load |
|----------------------------------------------------------------------------------------------------|----------|-----------|
| <i>NG fuelled GT – Calpuff results for max. 1h-average GLC – top result for grid receptors</i>     |          |           |
| CO (mg/m <sup>3</sup> )                                                                            | 0.03     | 0.063     |
| SO <sub>2</sub> (µg/m <sup>3</sup> )                                                               | 9.72     | 19.7      |
| <i>Diesel fuelled GT – Calpuff results for max. 1h-average GLC – top result for grid receptors</i> |          |           |
| CO (mg/m <sup>3</sup> )                                                                            | 0.143    | 0.313     |
| SO <sub>2</sub> (µg/m <sup>3</sup> )                                                               | 1.47     | 3.2       |

OCGT plant shut-down involves reducing then cutting the fuel supply to the gas turbines, with shut-down duration estimated to be approximately 20 minutes from full-load to 'flame-off'. The emissions during shut-down are expected to be insignificant in comparison with other operating modes; i.e., causing ground-level concentrations of air pollutants lower than predicted by modelling for this assessment, and were not considered further for this assessment.

## 7. Conclusion

An updated assessment of air pollutant emissions associated with the Project has been completed based on the final design of the gas turbines to determine the potential change in ambient air quality that may occur as a result of operation of the Project.

The key air pollutants associated with the Project are: carbon monoxide (CO), nitrogen dioxide (NO<sub>2</sub>), sulphur dioxide (SO<sub>2</sub>), particulate matter as PM<sub>2.5</sub> and the hydrocarbons or Volatile Organic Compounds (VOCs): formaldehyde and acrolein when the power station is fuelled by natural gas, and formaldehyde and Benzo(a)pyrene (B(a)P) when fuelled by diesel.

In relation to air emissions from the Project, the key air quality issues identified were due to existing high background levels of PM<sub>2.5</sub> and O<sub>3</sub>.

A detailed review of the existing environment was carried out including an analysis of measured concentrations of key air quality indicators (CO, NO<sub>2</sub>, and PM<sub>2.5</sub>) from representative monitoring stations. The following conclusions were made in relation to the existing air quality and meteorological conditions:

- Wind patterns in the vicinity of the Project are characteristic of the Lower Hunter Valley, with the prevailing winds being from the west-northwest
- Measured CO, NO<sub>2</sub> and SO<sub>2</sub> concentrations have been consistently below NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) air quality impact assessment criteria
- Measured O<sub>3</sub> occasionally exceed assessment criteria nearly every year, typically due to emissions from bushfires and controlled burns
- Measured PM<sub>2.5</sub> levels increased across NSW and the Hunter region from 2017 to 2019 due to dust from the widespread intense drought, and smoke from bushfires and hazard reduction burning. These events adversely influenced air quality with multiple days observed when PM<sub>2.5</sub> concentrations exceeded EPA assessment criteria.

Model predictions were assessed at selected sensitive receptors located near the Project Site, and these were considered as representative of the worst case sensitive receptor locations in the Lower Hunter. The key outcomes of the air quality assessment were:

- The Project will meet NSW Government requirements for air pollutant concentrations in the exhaust gases
- Operation of the power station will lead to small increases, relative to air quality criteria, in ambient (ground level) concentrations of the air pollutants: CO, NO<sub>2</sub>, SO<sub>2</sub>, PM<sub>2.5</sub> and the VOCs: formaldehyde, acrolein and PAHs as B(a)P
- The air pollutants of concern are those where background levels are already high; i.e., NO<sub>2</sub> (because O<sub>3</sub> levels are high) and PM<sub>2.5</sub>
- Modelling predicts the Project will meet NSW Government requirements for ground level concentrations for air pollutants CO, NO<sub>2</sub>, SO<sub>2</sub>, PM<sub>2.5</sub> and the VOCs: formaldehyde, acrolein and PAHs as B(a)P
- While during extreme events, such as bushfires, there is the potential for ground level concentrations of PM<sub>2.5</sub> to be above the GLC criteria, the Project is not predicted to cause any additional exceedances due to its negligible contribution.

Based on modelling, increases in NO<sub>2</sub> concentrations due to the Project are unlikely to cause exceedences of NO<sub>2</sub> criteria. However, O<sub>3</sub> background levels are high, and any additional NO<sub>x</sub> emissions represent an increase to regional NO<sub>x</sub> that contribute to the formation of O<sub>3</sub> in the wider region. A detailed photochemical modelling study was outside the scope of this study. However, it would be reasonable to assume the power station NO<sub>x</sub> emissions would have the effect of slightly reducing O<sub>3</sub> levels in its immediate vicinity (O<sub>3</sub> destruction), but contributing to a very slight increase in regional O<sub>3</sub> levels. The model results show that PM<sub>2.5</sub> contributions due to



the Project would be negligible relative to air quality criteria. Concentrations of PM<sub>2.5</sub>, including with potential contributions from the Project, would continue to be within the range of historically measured fluctuations in maximum concentrations for the region. This means that in a year not affected by bushfires, emissions from the Project are very unlikely to cause exceedances of PM<sub>2.5</sub> criteria. In a year affected by bushfires, measurements of PM<sub>2.5</sub> will be representative of the high concentrations due to bushfire smoke.

The assessment demonstrated the Project's operations, whether fuelled by natural gas or diesel, are not expected to cause adverse air quality impacts in the vicinity of the Project Site nor in the wider Lower Hunter region. This conclusion was based on modelling procedures undertaken in accordance with NSW EPA *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales* (2016) and which conservatively assumed that the power station would be operating continuously. The implementation of 'best practice' gas turbine engineering technology for the Project, such as Dry Low Emission (DLE) combustion system to minimise NO<sub>x</sub> emissions, will minimise air quality impacts.

The revised modelling therefore indicates that the detailed design has resulted in negligible changes to slight reductions in ground level concentrations of pollutants, when compared with the air quality modelling results produced for the Project EIS.

## 8. References

- Australian Government (2006): Australian Government, Department of Health and Aging, *Priority Existing Chemical Assessment Report No. 28, Formaldehyde*, National Industrial Chemicals Notification and Assessment Scheme, November 2006.
- Australian Government (2008): Australian Government, National Pollutant Inventory, *Emission Estimation Technique Manual for Combustion Engines*, Version 3.0, Department of the Environment, Water, Heritage and the Arts, 2008.
- ANSTO (2020): Australian Nuclear Science and Technology Organisation, *Fine particle pollution peaks during bushfires*, Published 12<sup>th</sup> May 2020 by ANSTO Staff, <https://www.ansto.gov.au/news/fine-particle-pollution-peaks-during-bushfires>, web page accessed by Jacobs 29 Jan 2021.
- J. Barclay and J. Scire, *Generic Guidance and Optimum Model Settings for the CALPUFF Modeling System for Inclusion into the 'Approved Methods for the Modeling and Assessments of Air Pollutants in NSW, Australia'*, Prepared For: NSW Office of Environment and Heritage, Sydney Australia, Atmospheric Studies Group, TRC Environmental Corporation, March 2011.
- Borgas (2000): M. Borgas, *The mathematics of whiffs and pongs*, presented at Enviro2000 Odour Conference, Clean Air Society of Australia and New Zealand, Sydney, 9-13 April 2000.
- Boyce (2012): Meherwan P. Boyce, *Gas Turbine Engineering Handbook*, Fourth Edition, Elsevier, 2012.
- CSIRO (2016): Day, S., Tibbett, A., Sestak, S., Knight, C., Marvig, P., McGarry, S., Weir, S., White, S., Armand, S., van Holst, J., Fry, R., Dell'Amico, M., Halliburton, B., Azzi, M. *Methane and Volatile Organic Compound Emissions in New South Wales*. CSIRO, Australia, 2016. H. N. Duc, L.T.-C. Chang, T. Trieu, D. Salter and Y. Scorgie, *Source Contributions to Ozone Formation in the New South Wales Greater Metropolitan Region, Australia*. *Atmosphere*, 9, 443 (32 pages), 13 November 2018.
- H. Duc, D. Salter, M. Azzi, N. Jiang, L. Warren, M. Riley, S. White, T. Trieu, L. Chang, and X. Barthelemy, *The Effect of Lockdown Period during CoViD-19 Pandemic on Air Quality in Sydney Region*. Department of Planning, Industry and Environment NSW, Australia, CASANZ 2021 – Online, 17-21 May 2021.
- Environ (2011): ENVIRON Australia Pty Ltd., *Tiered Procedure for Estimating Ground-Level Ozone Impacts from Stationary Sources*, Prepared for: Office of Environment and Heritage, September 2011.
- EPA (2016): NSW Environment Protection Authority, *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales*, State of NSW and Environment Protection Authority, August 2005, minor revisions November 2016, published January 2017.
- EPA (2019): NSW Environment Protection Authority, *About air pollution*, <https://www.epa.nsw.gov.au/your-environment/air/air-nsw-overview/about-air-pollution>, July 2019 (web page accessed 21 January 2021).
- EPA (2021): NSW Environment Protection Authority, *NSW State of Environment, Air Quality*, (Current), <https://soe.epa.nsw.gov.au/all-themes/climate-and-air/air-quality>, accessed 22 January 2021.
- European Commission (2017): Best Available Techniques (BAT) reference Document for Large Combustion Plants [LCP BREF 2017]; EUR 28836 EN; doi:10.2760/949. Prepared by the European Integrated Pollution Prevention and Control Bureau. Available at: <http://www.eipie.eu/the-sevilla-process/lcp-bref> and <http://www.eipie.eu/storage/files/Ref%204.pdf>
- Guerette, E., Paton-Walsh, C., Galbally, I., Molloy, S., Lawson, S., Kubistin, D., Buchholz, R., Griffith, D. W.T., Langenfelds, R. L., Krummel, P. B., Loh, Z., Chambers, S., Griffiths, A., Keywood, M., Selleck, P., Dominick, D., Humphries, R. & Wilson, S. R., *Composition of clean marine air and biogenic influences on VOCs during the MUMBA campaign*. *Atmosphere*, 10 (7), 383-1-383-30, 2019.

Hurley (2008a). P. Hurley, *TAPM V4. User Manual*, CSIRO Marine and Atmospheric Research Internal Report No. 5, October 2008.

Hurley (2008b). P. Hurley, *TAPM V4. Part 1: Technical Description*, CSIRO Marine and Atmospheric Research, Paper No. 25, October 2008.

Hurley, P., M. Edwards and A. Luhar, *TAPM V4. Part 2: Summary of Some Verification Studies*, CSIRO Marine and Atmospheric Research Paper No. 26, October 2008.

Jacobs (2020): Jacobs, *Kurri Kurri OCGT Gas Fired Power Station*, Environmental and Planning Scoping Report, 18 December 2020.

Jacobs (2021a): Hunter Power Station – Environmental Impact Statement, 22 April, 2021.

Jacobs (2021b): Hunter Power Station – Response to Submissions: Air quality Impact Assessment, 30 July 2021.

Keywood, M., Selleck, P., Reisen, F., Cohen, D., Chambers, S., Cheng, M., Cope, M., Crumeyrolle, S., Dunne, E., Emmerson, K., Fedele, R., Galbally, I., Gillett, R., Griffiths, A., Guerette, E.-A., Harnwell, J., Humphries, R., Lawson, S., Miljevic, B., Molloy, S., Powell, J., Simmons, J., Ristovski, Z., and Ward, J. *Comprehensive aerosol and gas data set from the Sydney Particle Study*, Earth Syst. Sci. Data, 11, pp.1883–1903, 2019.

NEPC (2016): National Environment Protection Council, *National Environment Protection (Ambient Air Quality) Measure*, prepared by the Department of the Environment, Federal Register of Legislative Instruments F2016C00215, prepared 25/02/2016.

NEPC (2019): National Environment Protection Council, *Annual Report 2017-2018*, Commonwealth of Australia and each Australian state and territory, 2019.

NEPC (2021a): National Environment Protection Council, *National Environment Protection (Ambient Air Quality) Measure*, prepared by the Office of Parliamentary Counsel, Canberra, Authorised Version F2021C00475, registered 26/05/2021.

NEPC (2021b): National Environment Protection Council, *Key Changes to the Ambient Air Quality Measure agreed by Ministers April 2021*, <http://www.nepc.gov.au/nepms/ambient-air-quality/variation-ambient-air-quality-nepm-ozone-nitrogen-dioxide-and-sulfur>, accessed 16 July 2021.

NSW DPEI (2020): NSW Department of Planning, Industry and Environment, *Air Quality Study for the NSW Greater Metropolitan Region, A Sydney Air Quality Study Program Report*. Environment, Energy and Science, DPIE, EES 2020/0488, November 2020.

NSW EPA (2016): NSW Environment Protection Authority, *Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales*, EPA 2016/0666, August 2005, minor revisions November 2016, published January 2017.

NSW Gov. (2004): NSW Government, *Ambient Concentrations of Polycyclic Aromatic Hydrocarbon Species in NSW*, Ambient Air Quality Research Project (1996–2001), Internal working paper no. 3, Atmospheric Science Section, Department of Environment and Conservation (NSW), December 2004.

NSW Gov. (2012): NSW Government, *Lower Hunter Ambient Air Quality Review of Available Data*, State of NSW and Office of Environment and Heritage, 2012.

NSW Gov. (2020a): NSW Government, *Protection of the Environment Operations (Clean Air) Regulation 2010*, Current version 8 January 2019, file last modified 25 March 2020, accessed by Jacobs 12 November 2020.

NSW Gov. (2020b): NSW Government, Department of Planning, Industry and Environment, *New South Wales Annual Compliance Report 2018, National Environment Protection (Ambient Air Quality) Measure*, 2020.



NSW Gov. (2020c): NSW Government, Department of Planning, Industry and Environment, *New South Wales Annual Compliance Report 2019*, 12 November 2020, <https://www.environment.nsw.gov.au/topics/air/nsw-air-quality-statements/annual-air-quality-statement-2019>, website accessed by Jacobs 29 Jan 2021.

NSW Gov. (2021): NSW Government, Department of Planning, Industry and Environment, *Current and Forecast Air Quality*, <https://www.dpie.nsw.gov.au/air-quality>, website accessed Dec 2020 and Jan 2021.

PEI (2021): Petroleum Equipment Institute, *Distillate*, [www.pei.org/wiki/distillate](http://www.pei.org/wiki/distillate), accessed 23 Jan 2021.

Scire et al. (2000a): J.S. Scire, F.R. Robe, M.E. Fernau, R.J. Yamartino, *A User's Guide for the CALMET Meteorological Model (Version 5)*, Earth Tech Inc., January 2000.


Scire et al. (2000b): J.S. Scire, D.G. Strimaitis, R.J. Yamartino, *A User's Guide for the CALPUFF Dispersion Model (Version 5)*, Earth Tech Inc., January 2000.

Teal Group Corporation, *Mitsubishi Hitachi Power Systems M501/M701*, Heavy Industrial Gas Turbines, November 2019.

U.S. DHHS (2004): U.S. Department of Health and Human Services, *Toxicological Profile for Acrolein*, Public Health Service, Agency for Toxic Substances and Disease Registry, August 2007.

U.S. EPA (2004): U.S. Environmental Protection Agency, AP-42, Vol. I, 3.1: *Stationary Gas Turbines*, Final Section - Supplement F, April 2000, <https://www.epa.gov/air-emissions-factors-and-quantification/ap-42-fifth-edition-volume-i-chapter-3-stationary-0>, accessed 24 January 2021.


## **Appendix A. Power Station Arrangement – OCGT F-Class Layout**



| POWER ISLAND (GT1 AND GT2) |                                    |       |
|----------------------------|------------------------------------|-------|
| NUMBER                     | EQUIPMENT DESCRIPTION              | QTY   |
| 1                          | GAS TURBINES                       | 2-OFF |
| 2                          | GT GENERATOR                       | 2-OFF |
| 3                          | GT FUEL GAS UNITS                  | 2-OFF |
| 4                          | GT FUEL OIL UNITS                  | 2-OFF |
| 5                          | EXHAUST STACKS                     | 2-OFF |
| 6                          | CLOSED CYCLE COOLING WATER COOLERS | 2-OFF |
| 7                          | ELECTRICAL CONTROL PACKAGES        | 2-OFF |
| 8                          | GTG TRANSFORMERS                   | 2-OFF |
| 9                          | GT UNIT TRANSFORMERS               | 2-OFF |
| 10                         | GT INLET AIR SILENCERS             | 2-OFF |
| 11                         | GT INLET AIR FILTERS               | 2-OFF |
| 12                         | FIN FAN COOLERS                    | 2-OFF |
| 13                         | POWER ISLAND OILY WATER PITS       | 2-OFF |
| 14                         | NATURAL GAS KNOCK-OUT DRUM         | 2-OFF |
| 15                         | NATURAL GAS DRIPS TANK             | 2-OFF |
| 16                         | NATURAL GAS FILTER COALESCER       | 2-OFF |

| BALANCE OF PLANT |                                                                      |       |
|------------------|----------------------------------------------------------------------|-------|
| NUMBER           | EQUIPMENT DESCRIPTION                                                | QTY   |
| 101              | FIRE WATER PUMPS                                                     | 2-OFF |
| 102              | DIESEL UNLOADING PUMPS                                               | 2-OFF |
| 103              | DIESEL FORWARDING PUMPS                                              | 3-OFF |
| 104              | DEMIN PLANT                                                          | 2-OFF |
| 105              | CHEMICAL AND EQUIPMENT STORE                                         | 1-OFF |
| 106              | DIESEL BUND AREA                                                     | 1-OFF |
| 107              | H <sub>2</sub> STORAGE & PRESSURE REDUCTION PANELS                   | 1-OFF |
| 108              | CO <sub>2</sub> & N <sub>2</sub> STORAGE & PRESSURE REDUCTION PANELS | 2-OFF |
| 109              | PLANT & INSTRUMENT AIR                                               | 1-OFF |
| 110              | NEUTRALISATION PIT                                                   | 1-OFF |
| 111              | PLANT OILY WATER PIT                                                 | 1-OFF |
| 112              | PLANT TRANSFORMERS                                                   | 3-OFF |
| 113              | APA GAS RECEIVING STATION                                            | 1-OFF |
| 114              | DIESEL STORAGE                                                       | 2-OFF |
| 115              | DEMIN WATER STORAGE                                                  | 1-OFF |
| 116              | DEMIN WATER PUMPS                                                    | 3-OFF |
| 117              | SERVICE WATER STORAGE                                                | 1-OFF |
| 118              | SERVICE WATER PUMPS                                                  | 3-OFF |
| 119              | EMERGENCY DIESEL GENERATOR                                           | 1-OFF |
| 120              | SWITCHROOM                                                           | 1-OFF |
| 121              | TANKER UNLOADING BAY                                                 | 1-OFF |
| 122              | FIRE WATER TANKS                                                     | 2-OFF |
| 123              | ADMIN BUILDING                                                       | 1-OFF |
| 124              | WORKSHOP BUILDING                                                    | 1-OFF |

PLAN VIEW  
Scale 1:500



ISSUED FOR INFORMATION ONLY

|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|



## Appendix B. Comparisons of Meteorological Data

The purpose of this Appendix is to provide some of the key results of comparisons between modelled and measured meteorological data. The purpose was to confirm the Calmet data were of appropriate quality for use as input to the air pollutant dispersion model, Calpuff, for the air quality impact assessment (see Section 5.4.3).

Calmet meteorological model results for surface winds and other meteorological parameters for the Project Site location were compared with measurements at the DPIE Beresfield monitoring station, for the simulation year, 2018.

Annual and seasonal wind roses created from Calmet results for hourly average wind speed and wind direction, extracted from a point near the Project Site location, are provided in Figure B.1. The corresponding wind roses created from hourly average measurements at Beresfield, are shown in Figure B.2. While there are some differences, some of which can be explained by variations in land use and terrain between Beresfield and Kurri, Calmet has captured the annual and seasonal wind patterns very well. Differences between conditions at the Project site and Beresfield would be expected based on the separation (approximately 17 km) and differences in local terrain and landuse.

A statistical summary of wind speed and temperature statistics is provided in Table B1. Calmet has modelled the hourly average temperatures accurately, except underestimated the higher temperatures, which would have no significant effect on the assessment results. The Calmet results for wind speed at Kurri also compare well with the Beresfield measurements, except the higher wind speeds have been underestimated. Some underestimation of wind speed is acceptable for an air quality assessment as lower wind speeds are worse for air pollutant dispersion. However, overall, the Calmet results for wind speed, which were based on TAPM modelling with data assimilation from Beresfield, were as expected; i.e., reflective of the measurements.

**Table B1.** Statistical summary of hourly average temperature and wind speed: Calmet and measurements

| Parameter<br>(1-hour averages) | Calmet<br>Temperature for<br>Project site (°C) | Measured<br>Temperature at<br>Beresfield (°C) | Calmet wind speed<br>for Project site<br>(m/s) | Measured wind<br>speed at Beresfield<br>(m/s) |
|--------------------------------|------------------------------------------------|-----------------------------------------------|------------------------------------------------|-----------------------------------------------|
| No. of records                 | 8759                                           | 8673                                          | 8759                                           | 8733                                          |
| Data capture                   | 100.0%                                         | 99.0%                                         | 100.0%                                         | 99.7%                                         |
| Maximum                        | 39.9                                           | 43.9                                          | 9.8                                            | 13.1                                          |
| 99 <sup>th</sup> percentile    | 32.4                                           | 35.0                                          | 7.6                                            | 9.8                                           |
| 90 <sup>th</sup> percentile    | 25.6                                           | 26.5                                          | 4.2                                            | 4.5                                           |
| 70 <sup>th</sup> percentile    | 21.0                                           | 21.5                                          | 2.8                                            | 2.8                                           |
| Median                         | 18.1                                           | 18.2                                          | 2.0                                            | 1.9                                           |
| Average                        | 18.0                                           | 18.2                                          | 2.4                                            | 2.4                                           |
| minimum                        | 3.5                                            | 1.5                                           | 0.1                                            | 0.0                                           |

The atmospheric boundary layer height or Mixing Layer Height (MLH) is the lowest layer of the troposphere in contact with the ground, characterised by turbulence and mixing. The MLH is important for air pollutant dispersion modelling, as the top of the mixing layer essentially forms the lid on the atmospheric volume available for dispersion of air pollutants. In summer, due to solar heating and convection, a typical MLH is approximately 2000–3000 metres, whereas in winter a typical MLH is much lower; e.g., 1000 metres is typical. Models such as Calmet calculate the MLH, so these may be reviewed as a check on data quality.

Examples of Calmet results for hourly average MLH produced for this assessment are shown in Figure B3 (mid-summer), and Figure B4 (mid-winter). As expected, the summer MLH are in an appropriate range, 2000–3000 metres, and the winter MLH are lower. Also as expected, the calculated MLH increases during daylight hours, and nearly vanishes at night, and increases with increasing temperatures and wind speeds. To conclude, reviews


of the meteorological data such as these, and others (not shown in this report), demonstrated that the Calmet results did not exhibit any anomalies that would compromise the dispersion modelling. The meteorological data from Calmet were therefore determined to be of sufficient quality to be used as input to Calpuff for the air quality assessment.

## Annual and seasonal wind roses: EPA Beresfield 2018




**Figure B1.** Annual and seasonal wind roses – Beresfield 2018 observations






**Figure B2.** Annual and seasonal wind roses: Kurri 2018 – Calmet model results



**Figure B3.** Summer example, Kurri: Calmet results for hourly average temperature, wind speed and MLH



**Figure B4.** Winter example, Kurri: Calmet results for hourly average temperature, wind speed and MLH

## **Appendix C. Environmental Representative Endorsement**



Ian Smith  
Project Manager  
Snowy Hydro Limited  
Monaro Highway  
Cooma, NSW, 2630

15 August 2022

REF: UPDATED AQIA REV 3

Dear Ian,

**RE: Hunter Power Project -Final Design: Updated Air Quality Impact Assessment Rev 3 (4 August 2022)**

I refer to Snowy Hydro Limited's (SHL) submission of the following document required by Condition B5 of the Hunter Power Project (Kurri Kurri Gas-Fired Power Station) Infrastructure Approval (SSI 12590060) for review and endorsement by the Environmental Representative:

- Hunter Power Project -Final Design: Updated Air Quality Impact Assessment rev 3 (4 August 2022) (Updated AQIA)

It is noted that:

- The Updated AQIA has been developed by Jacobs Group Australia (Jacobs) on behalf of SHL to address the final design verification requirements of the Infrastructure Approval including satisfying Condition B5.
- As required by Condition B5, the Updated AQIA identifies any changes in air quality emissions characteristics and associated impacts due to design variations between the conceptual and final detailed design.
- The ER review did not include a technical review of the Updated Air Quality Impact Assessment outputs, nor assess the accuracy of the remodelling of emissions.
- Following the review, the document is considered to contain information required by the Conditions of Approval (SSI 12590060) in relation to the final design verification (Condition B5).

Notwithstanding the above, as the approved Environmental Representative for the Hunter Power Project (Kurri Kurri Gas-Fired Power Station) and as required by Conditions A23(a), the Updated Air Quality Impact Assessment Rev 3 (4 August 2022) is endorsed for submission to the Secretary for consideration and approval.

Snowy Hydro Limited and their contractors must continue to obtain and comply with any relevant approval, licence or permit required for the works; complying with relevant Conditions of Approval as they relate to the works; and appropriate notifications being issued prior to the works.

Yours sincerely



Greg Byrnes  
Environmental Representative – Hunter Power Project (Kurri Kurri Gas-Fired Power Station)