

Appendix A

Bore Completion Report

Drilling and completion report

Stage 1 Groundwater Monitoring Network | Snowy 2.0

Prepared for Snowy Hydro Limited | 19 April 2018



Drilling and completion report

Stage 1 Groundwater Monitoring Network | Snowy 2.0

Prepared for Snowy Hydro Limited | 19 April 2018

Ground Floor, Suite 01, 20 Chandos Street
St Leonards, NSW, 2065

T +61 2 9493 9500

F +61 2 9493 9599

E info@emmconsulting.com.au

www.emmconsulting.com.au

Drilling and completion report

Final

Report J17188RP29 | Prepared for Snowy Hydro Limited | 19 April 2018

Prepared by **James Duggleby**

Approved by **Sean Cassidy**

Position Principal Hydrogeologist

Position Senior Hydrogeologist

Signature



Signature



Date 19 April 2018

Date 19 April 2018

This report has been prepared in accordance with the brief provided by the client and has relied upon the information collected at the time and under the conditions specified in the report. All findings, conclusions or recommendations contained in the report are based on the aforementioned circumstances. The report is for the use of the client and no responsibility will be taken for its use by other parties. The client may, at its discretion, use the report to inform regulators and the public.

© Reproduction of this report for educational or other non-commercial purposes is authorised without prior written permission from EMM provided the source is fully acknowledged. Reproduction of this report for resale or other commercial purposes is prohibited without EMM's prior written permission.

Document Control

Version	Date	Prepared by	Reviewed by
1	19 April 2018	James Duggleby	Sean Cassidy



T +61 (0)2 9493 9500 | F +61 (0)2 9493 9599

Ground Floor | Suite 01 | 20 Chandos Street | St Leonards | New South Wales | 2065 | Australia

www.emmconsulting.com.au

Table of contents

Chapter 1	Introduction	1
1.1	Project overview	1
1.2	Groundwater Assessment	1
<hr/>		
Chapter 2	Drilling program	3
2.1	Monitoring bore network	3
2.2	Monitoring bore licence	7
2.3	Drilling and construction specifications	7
2.3.1	Overview	7
2.3.2	Drilling	7
<hr/>		
Chapter 3	Field testing	9
3.1	Hydraulic conductivity testing	9
3.2	Groundwater levels	9
3.3	Groundwater quality monitoring	10
3.3.1	Sampling methodology	10
3.3.2	Results	10
<hr/>		
Chapter 4	Conclusions	15
<hr/>		
References		17
<hr/>		

Appendices

A	Geological and bore construction logs
B	Monitoring bore licence
C	Form A's
D	Water quality laboratory certificates

Tables

2.1	Stage 1 groundwater monitoring bores	5
3.1	Hydraulic conductivity results for Stage 1 monitoring bores	9
3.2	Analytical suite	10
3.3	Mean groundwater quality results (February 2018 – April 2018)	11

Tables

3.4	Dominant major ion chemistry for each groundwater system	13
-----	--	----

Figures

2.1	Typical nested groundwater monitoring site	4
2.2	Monitoring bore locations	6

1 Introduction

1.1 Project overview

Snowy Hydro Limited (Snowy Hydro) proposes to develop Snowy 2.0, a large scale pumped hydro-electric storage and generation project which would increase hydro-electric capacity within the existing Snowy Mountains Hydro-electric Scheme (Snowy Scheme). This would be achieved by establishing a new underground hydro-electric power station that would increase the generation capacity of the Snowy Scheme by almost 50%, providing an additional 2,000 megawatts (MW) generating capacity, and providing approximately 350 gigawatts hours (GWh) of storage available to the National Electricity Market (NEM) at any one time, which is critical to ensuring system security as Australia transitions to a decarbonised NEM. Snowy 2.0 would link the existing Tantangara and Talbingo reservoirs within the Snowy Scheme through a series of underground tunnels and hydro-electric power station.

Snowy 2.0 has been declared to be Critical State Significant Infrastructure (CSSI) by the NSW Minister for Planning under the provisions of the NSW Environmental Planning and Assessment Act 1979 (EP&A Act) and is defined in Clause 9 of Schedule 5 of the State Environmental Planning Policy (State and Regional Development) 2011 (SRD SEPP). Separate applications and environmental impact statements (EIS) for different phases of Snowy 2.0 are being submitted under Part 5, Division 5.2 of the EP&A Act. The application for Exploratory Works is the first application for Snowy 2.0.

The purpose of the Exploratory Works for Snowy 2.0 is primarily to gain a greater understanding of the conditions at the proposed location of the power station, approximately 850 metres (m) below ground level. Understanding factors such as rock conditions, ground temperature and stress conditions is essential to confirm the suitability of the site for the underground power station.

1.2 Groundwater Assessment

The collection of field data is important for the accurate representation of hydrogeological conceptual and numerical groundwater flow models, which will inform the Groundwater Assessment in support of the EIS for the Exploratory Works. This assessment covers all issues relating to site water management, groundwater, and surface water and their related environmental and other uses.

A comprehensive groundwater monitoring network has been installed to provide hydrogeological field data which will be used to characterise the groundwater regime in and around the project area.

The report details the drilling and completion of the Stage 1 groundwater monitoring network, installed by EMM Consulting Pty Ltd (EMM) in consultation with NSW Department of Industry: Water (DoI Water) between January and April 2018.

2 Drilling program

2.1 Monitoring bore network

The Stage 1 groundwater monitoring network includes conventional groundwater monitoring bores, vibrating wire piezometers (VWPs), and shallow drive point piezometers located within and in the vicinity of the project area. Project monitoring bores and VWPs are positioned to provide spatial coverage, investigate the major hydrogeological environments, and monitor potentially sensitive features. Specifically, the groundwater monitoring network was designed to:

- identify and characterise water bearing units in the project area, with particular focus on characterising groundwater flow and quality;
- provide spatial representation and flux of pressure heads across the project area to investigate potential vertical hydraulic gradients and connectivity between water bearing units;
- investigate the potential for surface water–groundwater interaction; and
- monitor potential sensitive features, including alpine bogs, Yarrangobilly River, Murrumbidgee River, Tantangara Creek, Gooandra Creek and potential groundwater dependent ecosystems.

The network comprises 20 monitoring bores, including conventional standpipe piezometers and nested monitoring sites, at 11 locations. Nested monitoring bores are installed at selected monitoring locations allowing multiple hydrogeological systems to be monitored in close proximity. Each nested site comprises a minimum of two monitoring bores with screened sections targeting major water bearing zones in the basalt, alluvium and underlying competent fractured volcanic and metasedimentary rock.

These installations allow assessment of the groundwater characteristics and the complex relationship occurring between shallow and deep groundwater systems at the same location. A schematic of a nested groundwater monitoring site is shown on Figure 2.1.

A summary of the installed monitoring bores is provided in Table 2.1, with locations shown on Figure 2.2 and bore construction logs provided in Appendix A.





Figure 2.1 Typical nested groundwater monitoring site


Table 2.1 Stage 1 groundwater monitoring bores

Bore ID	Easting ¹	Northing ¹	Ground level (mAHD) ²	Total depth (mgl) ³	Screen (mgl)	Monitored formation	Lithology
TMB01A	627670.5	6038074.1	581.2	15	11-14	Boraig Group	Igimbrite
TMB01B	627677.7	6038070.0	581.8	72	63-69	Ravine Formation	Siltstone
TMB02A	634554.0	6038586.4	1469.6	15	11-14	Gooandra Volcanics	Basalt
TMB02B	634548.5	6038606.6	1472.3	200	191-197	Gooandra Volcanics	Chloritic schist
TMB03A	636224.2	6038504.3	1477.7	34	29.5-32.5	Gooandra Volcanics	Basalt
TMB03B	636215.2	6038505.1	1477.6	150	141-147	Gooandra Volcanics	Chloritic schist
TMB03C	636220.7	6038495.1	1478	250	237-249	Gooandra Volcanics	Chloritic schist
TMB04	639018.2	6038261.2	1345.8	200	191-197	Gooandra Volcanics	Chloritic schist
TMB05A	628370.7	6039896.0	601.7	19	12-18	Ravine Formation	Weathered siltstone
TMB05B	628370.9	6039896.0	601.7	77	68-74	Ravine Formation	Siltstone
MB01B	637059.5	6040238.0	1464.4	7.5	5.3-6.8	Tertiary Basalt	Basalt
MB01C	637065.7	6040245.3	1464.0	53	45-51	Gooandra Volcanics	Chloritic schist
MB02	634310.5	6033304.1	1386.7	150	141-147	Gooandra Volcanics	Chloritic schist
MB03	637491.0	6043212.7	1373.0	100	92-98	Gooandra Volcanics	Chloritic schist
MB04A	640023.4	6047809.3	1330.0	30	23-29	Gooandra Volcanics	Basalt
MB04B	640023.7	6047817.4	1330.0	102.5	93.5-99.5	Gooandra Volcanics	Chloritic schist
MB06A	628723.4	6048391.5	1145.4	14	9-12	Boraig Group	Igimbrite
MB06B	628719.8	6048397.0	1145.5	72	64-70	Boraig Group	Igimbrite
MB07A	641051.0	6042294.1	1265.0	15	10-13	Tantangara Formation	Weathered siltstone
MB07B	641042.9	6042294.0	1265.0	60	51-57	Tantangara Formation	Sandstone

Notes: 1. Coordinates in MGA 94 (Zone 55);
2. mAHD = metres Australian Height Datum; and
3. mgl = metres below ground level.



Source: EMM (2018); Snowy Hydro (2018); SMEC (2018); DFSI (2017); LPMA (2011)



KEY

- | | | |
|---|---|---|
| ■ Groundwater monitoring bore | — Indicative communications cable location | ■ Scheme storage |
| — Talbingo access road upgrade | — Exploration tunnel and portal | ■ Kosciuszko National Park |
| — Middle Bay Wharf access road | □ Exploratory tunnel portal and construction pad envelope | ■ Other NPWS reserve |
| — Lower Lobs Hole Ravine Road upgrade | — Main road | ■ State forest |
| — Lobs Hole Ravine Road upgrade | — Local road | |
| — Mine Trail Road upgrade | - - - Vehicular track | |
| — Mine Trail Road extension | — Perennial watercourse | |
| — Dead Mans Fire Trail upgrade | | |

Groundwater monitoring locations

Snowy 2.0
Drilling and completion report
Stage 1 Groundwater Monitoring Network
Figure 2.2



T:\Jobs\2017\171188 - Snowy Hydro 2.0\GIS02 Maps_EIS_EWITechReports_WIAWIAEW007_GWMIN_20180411_02.mxd 19/04/2018

2.2 Monitoring bore licence

A test (monitoring bore) licence (40BL192701) under the Water Act 1912 was obtained by Snowy Hydro from DoI Water prior to the commencement of the drilling program (Appendix B). Form A: Particulars of Completed Works forms (drilling completion forms) were submitted to DoI Water following monitoring bore installation and are included in Appendix C.

2.3 Drilling and construction specifications

2.3.1 Overview

Highland Drilling was engaged by EMM to undertake borehole drilling and monitoring bore construction and installation. EMM provided the design and specification, and undertook project management and hydrogeological supervision during the drilling program.

All monitoring bores were drilled and constructed in accordance with the *Minimum Construction Requirements for Water Bores in Australia* (NUDLC 2012). Drilling and construction was a minimal impact temporary activity with the final constructed bore presenting at the surface as a 100 millimetre (mm) high, 1 x 1 m concrete slab and flush galvanised steel gatic plate (see Figure 2.1).

2.3.2 Drilling

Boreholes were drilled using an open hole (rotary percussion) technique using air (under pressure) to evacuate cuttings from the borehole during drilling. This drilling method ensured water quality and indicative yields could be recorded throughout the drilling process without contamination or interference.

All water produced from the bores during drilling was controlled in a series of above ground tanks and disposed of in accordance with the Snowy 2.0 Review of Environmental Factors (REF) (SHL 2018). Water for drilling was sourced from licensed supply in the Snowy Hydro village of Cabramurra. There were no instances of uncontrolled release of water; water was discharged only when it met the water quality limits specified in the REF. All drilling fluids and water that did not comply with REF limits was contained in above-ground tanks and disposed of at a licensed waste facility.

Geology was logged at 1 m intervals and instantaneous water flow recorded at the end of each drill rod (every 6 m) once drilling had penetrated the water table. Water quality physico-chemical parameters were measured using a calibrated YSI™ water quality meter and included temperature, Electrical Conductivity (EC), pH, Dissolved Oxygen (DO), Total Dissolved Solids (TDS) and Oxidation Reduction Potential (ORP). The parameters concentrations are shown on the geological bore logs in Appendix A.

Airlift development was continuous during drilling and the boreholes were further developed once the target depth was reached until the discharge water was free of sediment and the water quality physico-chemical parameters stabilised.

The bores were designed such that the screened section of the monitoring bores was aligned with the target water bearing zone. A washed and graded (3 to 5 mm) gravel filter pack was installed in the annulus around the screen and extended a minimum of 3 m above the screened section.

Coated bentonite pellets were installed 3 to 5 m above the gravel pack. Blue metal gravel backfill was placed above the bentonite seal and finally a cement grout mix was then injected in a controlled manner to seal the annulus to the ground surface. The bentonite seal and cement grout ensure hydraulic isolation of the screened section preventing any flow of groundwater through the annulus of the bore.

3 Field testing

3.1 Hydraulic conductivity testing

Falling and rising head ('slug') tests were conducted at most monitoring bores to estimate the horizontal hydraulic conductivity of the screened water bearing zone.

A falling head test is achieved by introducing a 'slug' device to displace the water column within the monitoring bore causing the water level to instantaneously rise and water to flow from the bore into the aquifer via the well screen (Butler 1998). The water level decay is recorded until the water level has returned to static level.

A rising head test is then conducted where the slug is removed causing a reduction in the bore water level with respect to the screened formation. Water then moves from the formation into the bore via the well screen. The water level recovery is recorded until the water level has returned to static level.

Hydraulic testing results (K values) from the installed Stage 1 bores are shown in Table 3.1.

Table 3.1 Hydraulic conductivity results for Stage 1 monitoring bores

Monitoring Bore	Formation	Average Hydraulic conductivity (K) (m/day) ¹
TMB01A	Boraig Group	3.27
TMB01B	Ravine Formation	0.00034
TMB02A	Gooandra Volcanics	0.11
TMB02B	Gooandra Volcanics	0.59
TMB05A	Ravine Formation	0.13
TMB05B	Ravine Formation	0.006
MB01B	Tertiary Basalt	11.4
MB01C	Gooandra Volcanics	41.9
MB02	Gooandra Volcanics	0.037
MB03	Gooandra Volcanics	4.2
MB04A	Gooandra Volcanics	0.013
MB04B	Gooandra Volcanics	0.017
MB07A	Tantangara Formation	55.1
MB07B	Tantangara Formation	0.013

Note: 1. Average values calculated from analysis of falling and rising head tests.

3.2 Groundwater levels

Groundwater level monitoring began in January 2018 at MB01B/C and has expanded to include all 20 monitoring bores as the bores have been progressively drilled and constructed.

SolinstTM pressure transducers and data loggers are installed in all the project groundwater monitoring bores and record groundwater level fluctuations every six hours. When the loggers were downloaded, manual groundwater level measurements were also recorded to calibrate the logger data. A barometric data logger installed above the water table at TMB02A records changes in atmospheric pressure. Data

from this logger is used to correct for the effects of changing barometric pressure and barometric efficiency on groundwater levels.

3.3 Groundwater quality monitoring

3.3.1 Sampling methodology

An initial round of groundwater quality monitoring was completed following each monitoring bore installation. Groundwater quality monitoring is then scheduled to continue at a monthly frequency.

The groundwater sampling method used across the monitoring network has been selected based on the hydraulic conductivity of the screened formations. Dedicated low-flow double valve pumps have been installed in each the screen section of each monitoring bores. During sampling, water quality parameters (including pH, temperature and electrical conductivity (EC)) are measured during purging and pumping to monitor water quality changes, and to indicate representative groundwater suitable for sampling and analysis.

Water quality samples were collected in laboratory provided sample bottles, with appropriate preservation. Samples undergoing dissolved metal analysis were filtered through a 0.45 µm filter in the field before collection in nitric acid preserved plastic sample bottles. Samples were stored on ice and sent to the laboratory under appropriate chain-of-custody protocols.

Groundwater samples are analysed by ALS for either the standard or comprehensive suite of analytes shown in Table 3.2.

Table 3.2 Analytical suite

Suite	Analytes
Physico-chemical properties	Field parameters (pH, EC, redox potential, DO, temperature) EC, TDS, TSS
Major ions	calcium, magnesium, sodium, potassium, sulphate, chloride, alkalinity
Dissolved metals	arsenic, cadmium, chromium, copper, fluoride, lead, magnesium, nickel, zinc
Nutrients	ammonia as N, nitrite as N, nitrate as N, reactive phosphorous, phosphorous, total phosphorus

Field and laboratory QA/QC procedures are used to establish accurate, reliable and precise results. Some QA/QC procedures included: analysis of unstable parameters in the field, calibration of equipment, submitting laboratory samples within holding times, collection of blind duplicate samples, keeping samples chilled and wearing gloves during sampling.

3.3.2 Results

Groundwater quality results collected between February 2018 and April 2018 are presented as an average for each monitoring site in Table 3.3. Laboratory certificates are presented in Appendix D.

Table 3.3 Mean groundwater quality results (February 2018 – April 2018)

Analyte	Units	ANZECC/ ARMCANZ 99% protection	MB01B	MB01C	MB02	MB03	MB04A	MB04B	TMB02A	TMB02B	TMB03A	TMB03B	TMB04	TMB05A	TMB05B	MB07A	MB07B
Formation			Tertiary basalt	Gooandra Volcanics	Gooandra Volcanics	Gooandra Volcanics	Gooandra Volcanics (w)	Gooandra Volcanics	Gooandra Volcanics (w)	Gooandra Volcanics (w)	Gooandra Volcanics (w)	Gooandra Volcanics	Gooandra Volcanics	Ravine Beds (w)	Ravine Beds	Tantangara Formation (w)	Tantangara Formation
Field analytes																	
pH	-	6.5-7.5	6	7.94	7.01	6.6	7.715	8.97	5.8	8.24	6.3	7.64	8.57	8.18	9.18	7.32	9.34
EC ¹	µS/cm	30-350	95.85	183	138	144	261	553	35.3	132	99.8	206	80.2	948	613	59	437
Temperature	°C	-	13.2	9.7	10.5	13.3	12.7	10	10.9	11	10.9	9.7	9.2	18.2	18.8	10.3	13.1
Dissolved oxygen	mg/L	-	4.48	-	-	4.44	4.5	-	-	-	-	-	-	-	-	-	-
Laboratory analytes																	
TDS ²	mg/L	-	269	127	79	121.5	193	1015	98	80	110	138	56	627	484	94	312
Major ions																	
Calcium	mg/L	-	8.5	14	16	13	29.5	8.5	4	13	6.5	18	9	35	6	4	55
Chloride	mg/L	-	1	1	3	4	5.5	45	0.5	0.5	5.5	4	0.5	9	10	1	5
Magnesium	mg/L	-	4.5	6	2	4.5	2.5	1	0.5	2	3	2.5	0.5	8	4	2	4
Sodium	mg/L	-	5.5	9	3	5.5	14.5	108.5	1	7	6	11	3	148	142	3	13
Potassium	mg/L	-	0.05	1	0.05	9	1.5	2	0.5	0.5	1	3	0.5	11	8	0.5	3
Sulfate	mg/L	-	5	13	14	7.5	60.5	86	6	8	6	18.5	5	348	22	9	158
Fluoride	mg/L	-	0.005	0.05	0.1	0.005	0.4	0.55	0.05	0.2	0.1	0.45	0.05	1.1	1.5	0.05	0.5
Alkalinity																	
Bicarbonate as CaCO ₃	mg/L	-	53	81	45.5	67	59	128	12	56	38.5	74	33	117	198	18	22
Carbonate as CaCO ₃	mg/L	-	0.5	0.5	0.05	0.5	0.5	5	0.5	0.5	0.5	0.5	0.5	0.5	128	0.5	0.5
Hydroxide as CaCO ₃	µg/L	-	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500
Total as CaCO ₃	mg/L	-	53	81	45.5	67	59	130.5	12	56	38.5	74	33	117	326	18	22
Total metals																	
Arsenic	mg/L	-	0.0005	0.009	0.0005	0.0005	0.001	0.002	0.0005	0.004	0.001	0.0145	0.0005	0.01	0.011	0.0005	0.002
Cadmium	mg/L	0.00006	0.00005	0.00005	0.00005	0.00005	0.00005	0.00005	0.00005	0.00005	0.0001	0.00005	0.00005	0.00005	0.0005	0.00005	0.00005
Chromium (III+VI)	mg/L	-	0.0005	0.0005	0.0005	0.002	0.002	0.0005	0.001	0.0005	0.0005	0.0005	0.002	0.003	0.013	0.0005	0.002
Copper	mg/L	0.001	0.066	0.0005	0.0045	0.054	0.0475	0.006	0.009	0.007	0.007	0.048	0.101	0.004	0.003	0.007	0.098
Mercury	mg/L	0.00006	0.00005	0.00005	0.00005	0.0011	0.00005	0.00005	0.00005	0.00005	0.00005	0.00005	0.00005	0.00005	0.00005	0.00005	0.00005
Nickel	mg/L	0.008	0.007	0.0005	0.002	0.003	0.003	0.002	0.002	0.001	0.0025	0.003	0.002	0.001	0.003	0.002	0.002
Zinc	mg/L	0.0024	0.148	0.00025	0.039	0.0705	0.116	0.018	0.037	0.015	0.0405	0.0655	0.119	0.007	0.012	0.027	0.105
Lead	mg/L	0.001	0.007	0.005	0.001	0.005	0.004	0.002	0.002	0.001	0.001	0.005	0.006	0.0005	0.0005	0.001	0.005
Nutrients																	
Ammonia as N	mg/L	-	1.95	0.6	1.6	1.4	0.75	0.9	0.5	0.6	0.35	0.3	0.5	0.3	0.08	0.6	0.6
Kjeldahl Nitrogen Total	mg/L	-	0.6	0.4	0.2	0.25	0.35	0.55	0.7	0.2	0.2	0.45	0.2	0.6	0.3	0.2	1
Nitrate (as N)	mg/L	-	0.035	0.005	0.08	0.25	0.52	0.66	0.005	0.01	0.01	0.03	0.04	0.03	0.2	0.17	0.005
Nitrite (as N)	mg/L	-	0.005	0.005	0.005	0.005	0.01	0.005	0.005	0.005	0.005	0.005	0.005	0.005	0.005	0.005	0.06
Nitrogen (Total)	mg/L	2.5	6	4	2.5	5.5	9	9	7	2	2	4.5	2	6	5	4	11
Phosphorus	mg/L	-	16.915	0.11	0.05	0.54	0.185	0.665	0.09	0.07	0.1	0.075	0.13	0.66	0.03	0.18	1.66

Notes: 1. EC = electrical conductivity; and
2. TDS = total dissolved solids.

The groundwater quality results are reasonably comparable between the different target formations across the larger Snowy 2.0 project area. The pH is slightly alkaline, averaging 7.5. Salinity varies across the Snowy 2.0 project area, fresher (201 $\mu\text{S}/\text{cm}$) to the east of Long Plain Fault across the plateau area and marginal (780 $\mu\text{S}/\text{cm}$) west of the fault, within the Ravine Beds and the Exploratory Works project area. There is a range of total suspended solids values; this is likely associated with bore construction rather than groundwater quality.

The dominant water type for each monitored formation is shown in Table 3.4. The dominant hydrochemical water type in the Ravine Beds (within the Exploratory Works project area) was Ca-Na-SO₄-CaCO₃. The strong sodium component in the Ravine Beds (siltstone) is likely the result of the original marine deposition within the incised ravine area.

The predominant hydrochemical water type in the Gooandra Volcanics, the dominant monitored lithology east of the Long Plain Fault is Ca-SO₄-CaCO₃. Natural sources of sulfate include rock weathering, specifically dissolution of pyrite, input from volcanoes and biochemical processes (Herojeet et al 2013). This corresponds with the mineralogy of the volcanic rocks across the plateau area.

Table 3.4 Dominant major ion chemistry for each groundwater system

Groundwater system	Water type
Tertiary basalt	Mg-Ca-Na-SO ₄
Gooandra Volcanics	Ca- SO ₄ -CaCO ₃
Gooandra Volcanics (weathered)	Ca- SO ₄ -CaCO ₃
Tantangara Formation	Ca- SO ₄ -CaCO ₃
Ravine Beds	Ca-Na-SO ₄ -CaCO ₃

Concentrations of most dissolved metals are typically low for most samples collected from each groundwater system, with many measurements below detection limits. This is typical of groundwater with reasonably neutral pH.

4 Conclusions

A Stage 1 network of 20 groundwater monitoring bores was installed at 11 sites between January and April 2018. The network includes conventional standpipe piezometers and nested monitoring sites. Nested monitoring bores are installed at selected monitoring locations allowing multiple hydrogeological systems to be monitored in close proximity. Each nested site comprises a minimum of two monitoring bores with screened sections targeting major water bearing zones in the basalt, alluvium and underlying competent fractured volcanic and metasedimentary rock.

On completion each bore was subject to a program of field testing including permeability testing (raising and falling head tests) and a water sampling program. Data loggers are installed in each bore set to record groundwater level fluctuations every six hours.

References

Butler, J.J., Jr. 1988, *Pumping tests in nonuniform aquifers—the radially symmetric case*, Journal of Hydrology, vol. 101, pp. 15-30.

NUDLC 2012, *Minimum Construction Requirements for Water Bores in Australia National Third edition*, Australian Government National Water Commission, Uniform Drillers Licensing Committee.

Appendix A

Geological and bore construction logs



www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: MB01B

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 18/01/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1464.4 mAHD

Drilling method: Air rotary

Easting: 637059.5

Hydrogeologist: S Cassidy

Northing: 6040238.0

Static Water Level: 3.5 mbgl


Screened Formation: Tertiary Basalt

Date: 18/01/18

Total depth: 12 mbgl

Screened depth: 5.3 - 6.8 m

Casing: 50 mm PVC





www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: MB01C

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 16/01/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1464.0 mAHD

Drilling method: Air rotary

Easting: 637065.7

Hydrogeologist: S Cassidy

Northing: 6040245.3

Static Water Level: 21.5 mbgl

Screened Formation: Gooandra Volcanics


Date: 16/01/18


Total depth: 52 mbgl


Screened depth: 45 - 51 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes









www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: MB02

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 12/02/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1386.7 mAHD

Drilling method: Air rotary

Easting: 634310.5

Hydrogeologist: K Maher

Northing: 6033304.1

Static Water Level: 6.05 mbgl

Screened Formation: Gooandra Volcanics


Date: 26/02/18


Total depth: 150 mbgl

Screened depth: 141 - 147 m


Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes





Gooandra Volcanics





Gooandra Volcanics


Gooandra Volcanics

Blue metal gravel backfill (5-8mm wash)

50mm blank PN18 U-PVC casing (threaded)









www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: MB03

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 22/01/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1373.0 mAHD

Drilling method: Air rotary

Easting: 637491

Hydrogeologist: S Cassidy

Northing: 6043212.7

Static Water Level: 5.715 mbgl

Screened Formation: Gooandra Volcanics


Date: 6/02/18


Total depth: 101 mbgl


Screened depth: 92 - 98 m


Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes










100




Water Cut: 2.5 L/s, EC:
85.4 μ S/cm, pH: 8.25

5 1/2 inch diameter
borehole

Gravel pack (5mm
wash)

50mm blank PN18
U-PVC sump
(threaded)





www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: MB04A

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 6/02/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1330.0 mAHD

Drilling method: Air rotary

Easting: 640023.4

Hydrogeologist: G Jimenez

Northing: 6047809.3

Static Water Level: 21.87 mbgl

Screened Formation: Gooandra Volcanics


Date: 7/02/18


Total depth: 30 mbgl

Screened depth: 23 - 29 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes







www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: MB04B

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 5/02/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1330.0 mAHD

Drilling method: Air rotary

Easting: 640023.7

Hydrogeologist: K Maher

Northing: 6047817.4

Static Water Level: 48.81 mbgl

Screened Formation: Gooandra Volcanics


Date: 7/02/18


Total depth: 102.5 mbgl

Screened depth: 93.5 - 99.5 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes





BASALT dark bluish black, light yellowish green


BASALT dark bluish black, light yellowish green, minor orange-pink orthoclase or possible intrusion

BASALT dark bluish black, hard drilling, soft zone @ 64 m

Gooandra Volcanics

Blue metal gravel backfill (5-8mm wash)

50mm blank PN18



Gooandra Volcanics

Gooandra Volcanics

Blue metal gravel backfill (5-8mm wash)

50mm blank PN18 U-PVC casing (threaded)

5 1/2 inch diameter borehole

Temp: 10.6°C, DO: 20.7%, DO: 2.29 ppm, EC: 249.6 µS/cm, TDS: 191.1 g/L, pH: 10.69, ORP: 85.2 mV

Water Cut: <0.1 L/s, Temp: 21°C, DO: 47.9%, DO: 4.27 ppm, EC: 96.9 µS/cm, TDS: 63.05 g/L, pH: 9.61, ORP: 43.4 mV

BASALT dark bluish black, light yellowish green

BASALT dark bluish black

48

50

52

54

56

58

60

62


64


66

68

70

72







WATER MONITORING BORE LOG

Bore ID: MB06A

www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 5/04/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1145.4 mAHD

Drilling method: Air rotary

Easting: 628723.4

Hydrogeologist: K Maher

Northing: 6048391.5

Static Water Level: 4.57 mbgl

Screened Formation: Boraig Group


Date: 5/04/18

Total depth: 14 mbgl

Screened depth: 9 - 12 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes





WATER MONITORING BORE LOG

Bore ID: MB06B

www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 4/04/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1145.4 mAHD

Drilling method: Air rotary

Easting: 628719.8

Hydrogeologist: K Maher

Northing: 6048397.0

Static Water Level: 4.51 mbgl

Screened Formation: Boraig Group


Date: 5/04/18


Total depth: 72 mbgl


Screened depth: 64 - 70 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes









www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: MB07A

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 22/02/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1265.0 mAHD

Drilling method: Air rotary

Easting: 641051.0

Hydrogeologist: K Maher

Northing: 6042294.1

Static Water Level: 8.85 mbgl


Screened Formation: Tantangara Formation Date: 23/02/18

Total depth: 14 mbgl

Screened depth: 10 - 13 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes





www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: MB07B

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 21/01/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1265.0 mAHD

Drilling method: Air rotary

Easting: 641042.9

Hydrogeologist: K Maher

Northing: 6042294.0

Static Water Level: 9.09 mbgl

Screened Formation: Tantangara Formation


Date: 23/02/18


Total depth: 60 mbgl


Screened depth: 51 - 57 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes









www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: TMB01A

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 22/03/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 581.2 mAHD

Drilling method: Air rotary

Easting: 627670.5

Hydrogeologist: K Maher

Northing: 6038074.1

Static Water Level: 5.1 mbgl

Screened Formation: Boraig Group

Date: 27/03/18

Total depth: 14 mbgl

Screened depth: 11 - 14 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes
0		SOIL medium reddish brown			
0 - 4		COLLUVIUM pebbly to cobbly, river gravels			
4 - 8.5		IGNIMBRITE medium reddish purple, UNKNOWN, light to medium green			
8.5 - 9.5		TUFF light creamy green, IGNIMBRITE, 20% medium reddish purple			
9.5 - 11		IGNIMBRITE medium reddish purple, UNKNOWN, medium green			
11 - 14		IGNIMBRITE medium reddish purple, UNKNOWN, medium green	Water Cut: 0.1 L/s, Temp: 24.9°C, DO: 52.7%, DO: 4.31 ppm, EC: 642 µS/cm, TDS: 416 g/L, pH: 8.08, ORP: 29.3 mV		



www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: TMB01B

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 22/03/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 581.8 mAHD

Drilling method: Air rotary

Easting: 627677.7

Hydrogeologist: K Maher

Northing: 6038070.0

Static Water Level: 6.1 mbgl

Screened Formation: Ravine Beds


Date: 27/03/18


Total depth: 72 mbgl


Screened depth: 63 - 69 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes









www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: TMB02A

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 26/02/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1469.6m AHD

Drilling method: Air rotary

Easting: 634554.0

Hydrogeologist: K Maher

Northing: 6038586.4

Static Water Level: 5.6 mbgl

Screened Formation: Gooandra Volcanics

Date: 26/02/18

Total depth: 15 mbgl

Screened depth: 11 - 14 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes
0		SOIL dark brown			
0 - 2		CLAY light yellowish brown, highly weathered			
2 - 4		CLAY medium orange, extremely weathered			
4 - 8		CLAY medium yellowish brown, highly weathered			
8 - 11		CLAY medium yellowish brown, highly weathered			
11 - 14			Water Cut: 0.3 L/s		



WATER MONITORING BORE LOG

Bore ID: TMB02B

www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 1/03/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1472.3 mAHD

Drilling method: Air rotary

Easting: 634548.5

Hydrogeologist: K Maher

Northing: 6038606.6

Static Water Level: 7.13 mbgl

Screened Formation: Gooandra Volcanics


Date: 1/03/18


Total depth: 200 mbgl


Screened depth: 191 - 197 m


Casing: 50 mm PVC


Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes











100
102
104
106
108
110
112
114
116
118
120
122
124
126

Gooandra Volcanics

GREENSCHIST medium greyish green, platy, micaceous, phyllitic sheen; (?), 10% pinkish orange, slightly oxidised, intrusive, (?)

METABASALT medium to dark greyish green, QUARTZ, 2%

GREENSCHIST medium to dark greyish green, rare rose quartz, slightly micaceous

GREENSCHIST medium to dark greyish green, micaceous, platy; rare%quartz


Water Cut: 2 L/s, Temp: 9.9°C, DO: 66.7%, DO: 7.54 ppm, EC: 66.1 μS/cm, TDS: 42.9 g/L, pH: 8.69, ORP: 117.7 mV

Water Cut: 2.2 L/s, Temp: 10.1°C, DO: 65.9%, DO: 7.42 ppm, EC: 66.9 μS/cm, TDS: 43.55 g/L, pH: 8.69, ORP: 121.6 mV

Water Cut: 2.5 L/s, Temp: 10.2°C, DO: 68.3%, DO: 7.68 ppm, EC: 72.1 μS/cm, TDS: 46.8 g/L, pH: 8.84, ORP: 107.3 mV

Water Cut: 3 L/s, Temp: 10.1°C, DO: 65.2%, DO: 7.34 ppm, EC: 76.5 μS/cm, TDS: 49.4 g/L, pH: 8.75, ORP: 116.4 mV

Blue metal gravel backfill (5-8mm wash)
50mm blank PN18 U-PVC casing (threaded)
5 1/2 inch diameter borehole



Blue metal gravel backfill (5-8mm wash)

50mm blank PN18 U-PVC casing (threaded)

5 1/2 inch diameter borehole

Gooandra Volcanics

Gooandra Volcanics


Water Cut: 3 L/s, Temp: 11.3°C, DO: 69.2%, DO: 7.57 ppm, EC: 70 µS/cm, TDS: 45.6 g/L, pH: 8.63, ORP: 105.8 mV


Water Cut: 3 L/s, Temp: 10.2°C, DO: 68%, DO: 7.66 ppm, EC: 67.4 µS/cm, TDS: 43.55 g/L, pH: 8.49, ORP: 137.4 mV

Water Cut: 3 L/s, Temp: 10.2°C, DO: 67.2%, DO: 7.53 ppm, EC: 70.8 µS/cm, TDS: 46.15 g/L, pH: 8.67, ORP: 137.3 mV

Water Cut: 3 L/s, Temp: 10.3°C, DO: 64.8%, DO: 7.25 ppm, EC: 54.9 µS/cm, TDS: 35.75 g/L, pH: 8.38, ORP: 143 mV

128
130
132
134
136
138
140
142
144
146
148
150
152







www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: TMB03A

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 31/01/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1477.7 mAHD

Drilling method: Air rotary

Easting: 636224.2

Hydrogeologist: K Maher

Northing: 6038504.3

Static Water Level: 11.87 mbgl

Screened Formation: Gooandra Volcanics


Date: 6/02/18


Total depth: 34 mbgl

Screened depth: 29.5 - 32.5 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes







www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

WATER MONITORING BORE LOG

Bore ID: TMB03B

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 30/01/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1477.6 mAHD

Drilling method: Air rotary

Easting: 636215.2

Hydrogeologist: K Maher

Northing: 6038505.1

Static Water Level: 17.685 mbgl

Screened Formation: Gooandra Volcanics


Date: 6/02/18


Total depth: 150 mbgl

Screened depth: 141 - 147 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes





GREENSCHIST light to medium greenish grey, QUARTZ, 5% abundant, pyrite, crystals up to 1 mm

Gooandra Volcanics


Water Cut: 1 L/s

Water Cut: 1 L/s, Temp: 17.8°C, DO: 19.7%, DO: 1.87 ppm, EC: 72.7 μS/cm, TDS: 47.45 g/L, pH: 6.91, ORP: -0.2 mV

Water Cut: 2.5 L/s, Temp: 14.6°C, DO: 48.7%, DO: 4.95 ppm, EC: 73.9 μS/cm, TDS: 48.1 g/L, pH: 6.43, ORP: 9.9 mV

6 inch steel surface casing






Water Cut: 2.5 L/s,
 Temp: 14.3°C, DO:
 50.5%, DO: 5.14 ppm,
 EC: 68.1 µS/cm, TDS:
 44.2 g/L, pH: 6.45,
 ORP: -12.2 mV


Water Cut: 2.5 L/s,
 Temp: 15.3°C, DO:
 49.6%, DO: 4.98 ppm,
 EC: 63.2 µS/cm, TDS:
 40.95 g/L, pH: 6.58,
 ORP: -20.4 mV


Water Cut: 2.85 L/s,
 Temp: 15.2°C, DO:
 42.4%, DO: 4.25 ppm,
 EC: 65.6 µS/cm, TDS:
 40.95 g/L, pH: 7.47

Blue metal gravel
 backfill (5-8mm wash)

50mm blank PN18
 U-PVC casing
 (threaded)









WATER MONITORING BORE LOG

Bore ID: TMB03C

www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 3/03/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1478 mAHD

Drilling method: Air rotary

Easting: 636220.7

Hydrogeologist: I Frawley

Northing: 6038495.1

Static Water Level: 21.94 mbgl

Screened Formation: Gooandra Volcanics


Date: 20/03/18


Total depth: 250 mbgl


Screened depth: 237 - 249 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes







74
76
78
80
82
84
86
88
90
92
94
96
98



Gooandra Volcanics

METABASALT medium greenish grey, abundant, sulphides, crystals increase in size, up to 1 mm, rare quartz


METABASALT medium greenish grey, abundant, sulphides, pyrite crystals < 1 mm, rare quartz @ 110 m


Water Cut: 1 L/s, Temp: 15°C, DO: 66.1%, DO: 6.68 ppm, EC: 63.3 μS/cm, TDS: 41.6 g/L, pH: 7.04, ORP: 14.8 mV


Water Cut: 1.5 L/s, Temp: 15.7°C, DO: 64.5%, DO: 6.4 ppm, EC: 59.8 μS/cm, TDS: 39 g/L, pH: 7.33, ORP: -9.3 mV

Water Cut: 1.5 L/s, Temp: 17.1°C, DO: 65.2%, DO: 6.3 ppm, EC: 89.5 μS/cm, TDS: 58.5 g/L, pH: 7.69, ORP: -6.3 mV









Blue metal gravel backfill (5-8mm wash)

5 1/2 " welded steel casing

7 1/2 inch diameter borehole

Water Cut: 2 L/s, Temp: 15.3°C, DO: 69.1%, DO: 6.91 ppm, EC: 111.7 µS/cm, TDS: 72.15 g/L, pH: 7.65, ORP: 60.4 mV

Water Cut: 3 L/s, Temp: 13.7°C, DO: 67%, DO: 6.94 ppm, EC: 105.1 µS/cm, TDS: 68.25 g/L, pH: 7.21, ORP: 7.31 mV


Water Cut: 4 L/s, Temp: 13°C, DO: 69.6%, DO: 7.33 ppm, EC: 98.1 µS/cm, TDS: 63.7 g/L, pH: 7.35, ORP: 51 mV

Gooandra Volcanics

METABASALT medium to dark greenish grey, SCHIST, 2% dark blackish grey, moderate, sulphides, rare, quartz

METABASALT medium to dark greenish grey, moderate, sulphides

METABASALT medium to dark greenish grey, moderate, sulphides, moderate, quartz



METABASALT medium to dark greenish grey, moderate, sulphides

Water Cut: 5 L/s, Temp: 13.7°C, DO: 59.2%, DO: 6.15 ppm, EC: 94.5 µS/cm, TDS: 61.75 g/L, pH: 7.47, ORP: 24.4 mV

Water Cut: 5 L/s, Temp: 12.7°C, DO: 71.7%, DO: 7.59 ppm, EC: 102.8 µS/cm, TDS: 66.95 g/L, pH: 7.27, ORP: 29.3 mV

Water Cut: 5 L/s, Temp: 14.2°C, DO: 68.1%, DO: 6.99 ppm, EC: 85.1 µS/cm, TDS: 52.52 g/L, pH: 7.45, ORP: -1.2 mV


Water Cut: 5 L/s, Temp: 11.8°C, DO: 65.3%, DO: 7.08 ppm, EC: 92.9 µS/cm, TDS: 60.45 g/L, pH: 6.63, ORP: 7.08 mV


Water Cut: 5 L/s, Temp: 11.7°C, DO: 66.1%, DO: 7.16 ppm, EC: 90.7 µS/cm, TDS: 59.15 g/L, pH: 7.18, ORP: 68.7 mV

Blue metal gravel backfill (5-8mm wash)

5 1/2 " welded steel casing

7 1/2 inch diameter borehole







WATER MONITORING BORE LOG

Bore ID: TMB04

www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 16/02/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 1345.8 mAHD

Drilling method: Air rotary

Easting: 639018.2

Hydrogeologist: I Frawley

Northing: 6038261.2

Static Water Level: 17.02 mbgl

Screened Formation: Gooandra Volcanics


Date: 21/02/18


Total depth: 200 mbgl


Screened depth: 191 - 197 m


Casing: 50 mm PVC


Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes






















WATER MONITORING BORE LOG

Bore ID: TMB05A

www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 3/03/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 601.7 mAHD

Drilling method: Air rotary

Easting: 628370.9

Hydrogeologist: K Maher

Northing: 6039896

Static Water Level: 3.1 mbgl

Screened Formation: Ravine Beds


Date:


Total depth: 21 mbgl

Screened depth: 12 - 18 m

Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes







WATER MONITORING BORE LOG

Bore ID: TMB05B

www.emmconsulting.com.au

Suite 01, 20 Chandos Street
St Leonards NSW 2065
T: 02 9493 9500
F: 02 9493 9599

Client: Snowy Hydro

Project: Snowy Hydro 2.0

Date completed: 14/03/18

Project number: J17188

Drilling contractor: Highland Drilling

Elevation: 601.7 mAHD

Drilling method: Air rotary

Easting: 628370.7

Hydrogeologist: K Maher

Northing: 6039896

Static Water Level: 3.2 mbgl

Screened Formation: Ravine Beds


Date:


Total depth: 77 mbgl


Screened depth: 68 - 74 m


Casing: 50 mm PVC

Depth (mbgl)	Lithology Graphic	Description	Water Quality	Bore Completion Diagram	
				Diagram	Design notes









Appendix B

Monitoring bore licence



Contact Gerrod Webb
Phone 02 6953 9826
Fax 02 6953 9888
Date 22/12/20017

Snowy Hydro Limited
PO Box 332
Cooma NSW 2630

Our ref 40BL192707

Dear Sir/Madam

Subject: Monitoring Bore application

Please find enclosed Monitoring bore licence's for Parish of Pinbeyan, County of Buccleuch and a description of the works, terms, limitations and conditions under which the license is issued.

Condition (2) of the license applies whether the bore is successful or not and it is the Driller's responsibility to supply the information. Two completed 'Form A's' must be returned to you. One copy is to be retained by you, and the original returned to the this office with details of any water analysis and pumping tests carried out.

The 'Form A' requests a sketch of the location of the bore site together with the lot number and boundaries.

The referenced license is for exploration only. Any bore which is to be converted to a production bore will require an application for an approval Prior to construction. Compliance with metering conditions and an appropriate access license together with the appropriate fees is required for any approval for irrigation/commercial purposes.

If you have any queries regarding the above, please contact me on (02) 6953 9888 or email gerrod.webb@waternsw.com.au.

Yours sincerely

A handwritten signature in black ink that reads "Gerrod Webb".


Water Regulation Officer
Water NSW

NSW Office of Water

Murrumbidgee Region
Po Box 156
2198 Irrigation Way East
Leeton NSW 2705
Phone: (02) 69512611

BORE LICENSE CERTIFICATE UNDER SECTION 115 OF THE WATER ACT, 1912

40BL192701



Snowy Hydro Limited
Po Box 332
Cooma NSW 2630

LICENSE NUMBER
40BL192701
DATE LICENSE VALID FROM
22-Dec-2017
DATE LICENSE VALID TO
PERPETUITY
FEE
\$0.00

ABN 72189919072 GST NIL

LOCATION OF WORKS

Portion(s) or Lot/Section/DP	PARISH	COUNTY
Reserve - National Park	Pinbeyan	Buccleuch

TYPE OF WORKS	PURPOSE(S) FOR WHICH WATER MAY BE USED
Bore - Monitoring	Monitoring Bore

CONDITIONS APPLYING TO THIS LICENSE ARE

As shown on the attached Condition Statement

ORIGINAL

NSW Office of Water**CONDITIONS STATEMENT REFERRED TO ON
40BL192701
ISSUED UNDER PART V OF THE WATER ACT, 1912
ON 22-Dec-2017**

- (1) THE LICENCE SHALL LAPSE IF THE WORK IS NOT COMMENCED AND COMPLETED WITHIN THREE YEARS OF THE DATE OF THE ISSUE OF THE LICENCE.
- (2) THE LICENSEE SHALL WITHIN TWO MONTHS OF COMPLETION OR AFTER THE ISSUE OF THE LICENSE IF THE WORK IS EXISTING, FURNISH TO NSW OFFICE OF WATER:-
- (A) DETAILS OF THE WORK SET OUT IN THE ATTACHED FORM "A" (MUST BE COMPLETED BY A DRILLER).
- (B) A PLAN SHOWING ACCURATELY THE LOCATION OF THE WORK, IN RELATION TO PORTION AND PROPERTY BOUNDARIES.
- (C) A ONE LITRE WATER SAMPLE FOR ALL LICENCES OTHER THAN THOSE FOR STOCK, DOMESTIC, TEST BORES AND FARMING PURPOSES.
- (D) DETAILS OF ANY WATER ANALYSIS AND/OR PUMPING TESTS.
- (3) THE LICENSEE SHALL ALLOW NSW OFFICE OF WATER OR ANY PERSON AUTHORISED BY IT, FULL AND FREE ACCESS TO THE WORKS, EITHER DURING OR AFTER CONSTRUCTION, FOR THE PURPOSE OF CARRYING OUT INSPECTION OR TEST OF THE WORKS AND ITS FITTINGS AND SHALL CARRY OUT ANY WORK OR ALTERATIONS DEEMED NECESSARY BY THE DEPARTMENT FOR THE PROTECTION AND PROPER MAINTENANCE OF THE WORKS, OR THE CONTROL OF THE WATER EXTRACTED AND FOR THE PROTECTION OF THE QUALITY AND THE PREVENTION FROM POLLUTION OR CONTAMINATION OF SUB-SURFACE WATER.
- (4) IF A WORK IS ABANDONED AT ANY TIME THE LICENSEE SHALL NOTIFY NSW OFFICE OF WATER THAT THE WORK HAS BEEN ABANDONED AND SEAL OFF THE AQUIFER BY:-
- (A) BACKFILLING THE WORK TO GROUND LEVEL WITH CLAY OR CEMENT AFTER WITHDRAWING THE CASING (LINING); OR
- (B) SUCH METHODS AS AGREED TO OR DIRECTED BY NSW OFFICE OF WATER.
- (5) IF THE BORE AUTHORISED BY THIS LICENSE IS LINED WITH STEEL OR PLASTIC CASING THE INSIDE DIAMETER OF THAT CASING SHALL NOT EXCEED 220 MM.
- (6) WATER SHALL NOT BE PUMPED FROM THE BORE AUTHORISED BY THIS LICENSE FOR ANY PURPOSE OTHER THAN GROUNDWATER INVESTIGATION.

End Of Conditions

PROCEDURES – FORM A

1. The landholder must obtain an approval from the NSW Office of Water before a bore can be constructed
2. The department will forward the following to the landholder
 - Approval letter with the regional contact officer and regional address for return of the completed form A
 - The approval with the condition statement
 - Form A
3. The landholder makes arrangements with the driller to sink and construct the bore. *(A work plan and contractual agreement by both parties, prior to commencement of construction work is highly recommended. The agreement should include arrangements for obtaining the completed Form A)*
4. The driller must sight the approval before constructing the bore. (The approval number must be recorded on the Form A, and any subsequent enquiry or correspondence in relation to this bore with the Department should quote the approval number)
5. The driller is required to complete the Form A (during/after bore construction). The completed form needs to be co-signed by both the driller and landholder.
6. The landholder forwards the completed co-signed Form A to the departments regional office as nominated in the approval letter.

Notes:

- (i) *The landholder is advised to make a copy of the completed/signed Form A before despatch to the department*
- (ii) *The landholder must forward the completed Form A to the department, or else future actions relating to the licenced work such as renewal may not proceed.*
- (iii) *Driller will not be forced to keep copies of Form A's for inclusion with applications for driller licence renewals. For future driller licence renewals, drillers will be asked to specify the bores they have constructed (by providing the bore licence number), and the department will review the recorded details against the bore from the corporate database.*

- (iv) If drillers require a copy of the completed Form A for their personal records, then they should make the appropriate arrangements to obtain a copy.*
7. Department staff will transfer the data contained in the Form A into the departments Ground Water System.
 8. The original Form A should be placed in the bore licence file and retained by the regional office.



Driller's Licence No: **1**

Class of Licence:

Driller's Name:

Assistant Driller:

Contractor:

New bore Replacement bore

Deepened Enlarged

Reconditioned Other (specify)

Final Depth m

Work Licence No: **2**

Name of Licensee:

Intended Use:

Completion Date:

DRILLING DETAILS **3**

From (m)	To (m)	Hole Diameter (mm)	Drilling Method
			See Code 3

WATER BEARING ZONES **4**

From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative			See Code 4	Hrs	min	Cond (µS/cm)

CASING / LINER DETAILS **5**

Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing	Casing support method
Code 5					Code 5	See Code 5
						Type of casing bottom
						See Code 5
						Centralisers installed (Yes/No)
						(indicate on sketch)
						Sump installed (Yes/No)
						From <input type="text"/> m To <input type="text"/> m
						Pressure cemented (Yes/No)
						From <input type="text"/> m To <input type="text"/> m
						Casing Protector cemented in place

WATER ENTRY DESIGN **6**

General							Screen	Slot Details		
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type	Fixing	Aperture (mm)	Length (mm)	Width (mm)	Alignment
Code 5					See Code 6	See Code 5				See Code 6

GRAVEL PACK **7**

Type	Grade	Grain size (mm)		Depth (m)		Quantity	
		From	To	From	To	Litres	m ³
Rounded	Graded						
Crushed	Ungraded						
Bentonite/Grout seal (Yes/No)							
Method of placement of Gravel Pack		See Code 7					

For Departmental use only: **GW**

Work Licence No: _____

BORE DEVELOPMENT 8

Chemical used for breaking down drilling mud (Yes/No) Name: _____

Method	Bailing/Surging <input type="checkbox"/>	Jetting <input type="checkbox"/>	Airlifting <input type="checkbox"/>	Backwashing <input type="checkbox"/>	Pumping <input type="checkbox"/>	Other: _____
Duration	_____ hrs	_____ hrs	_____ hrs	_____ hrs	_____ hrs	_____ hrs

DISINFECTION ON COMPLETION 9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION 10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								
Height of measuring point above ground level _____ m		Test Method _____		See Code 4				

WORK PARTLY BACKFILLED OR ABANDONED 11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other 12

Lot No _____ DP No _____ 13

Work Location Co ordinates

Easting _____ Northing _____ Zone **54**

GPS: (Yes/No) >> AMG/AGD or MGA/GDA (See explanation)

Longitude _____ Latitude _____

Please mark the work site with "X" on the CLID provided map.
Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

<p>Driller: _____</p> <p>Date: _____</p>	<p>Licensee: _____</p> <p>Date: _____</p>
--	---

CODE TABLES

DRILLING METHOD

3

1	Auger - Hollow Flight	9	Rotary - Percussion - (Down Hole Hammer)
2	Auger - Solid Flight	10	Rotary - Percussion - Foam injection
3	Cable Tool - Drill and Drive Casing	11	Rotary - Reverse circulation - Air
4	Cable Tool - Mud stabilised	12	Rotary - Reverse circulation - Mud
5	Rotary Air	13	Rotary - Coring
6	Rotary - Air/foam	14	Jetted - Air
7	Rotary - Mud	15	Jetted - Water
8	Rotary - Water	16	Other - See page 2, N0 11

WATER BEARING ZONE

4

TEST METHOD				FLOW MEASURING DEVICE			
1	Airlift	6	Pump - Helical Rotor	A	Container of known volume	F	Weir - Rectangular
2	Bailer	7	Pump - Jet	B	Flow meter	G	Weir - V Notch - 60°
3	Pump - Centrifugal	8	Pump - Turbine	C	Flume	H	Weir - V Notch - 90°
4	Pump - Cylinder	9	Freeflow	D	Orifice, plate & manometer	I	Other
5	Pump - Electric submersible			E	Ultra sonic meter		

CASING / LINER DETAILS

5

MATERIAL				METHOD OF FIXING			
1	A.B.S.	6	PVC - Class 12	11	Steel - Stainless	1	Glued
2	Aluminium	7	PVC - Class 15	12	Steel - Stainless 304	2	Kwik-lock
3	Concrete cylinder	8	PVC - Class 18	13	Steel - Stainless 316	3	Packer
4	Fibre glass (FRP)	9	Steel - ERW	14	Other	4	Riveted
5	PVC - Class 9	10	Steel - Galvanised			5	Screwed
						6	Welded - Butt
						7	Welded - Collar
						8	Other

CASING SUPPORT METHOD

TYPE OF CASING BOTTOM

1	Driven into small hole	5	Held in clamp	1	Open end	5	Casing shoe
2	Seated on bottom	6	Other	2	End cap	6	Wash down shoe
3	Seated on backfill			3	Plug - concrete	7	Cementing shoe
4	Cemented			4	Plug - wood	8	Other

WATER ENTRY DESIGN

6

OPENING TYPE				SLOT ALIGNMENT			
1	Casing - Bridge slot	7	Casing - Plasma-cut slot	D	Diagonal		
2	Casing - Drilled holes	8	Casing - Perforated in hole	H	Horizontal		
3	Casing - Hand sawn slot	9	Screen - gauze / mesh	V	Vertical		
4	Casing - Louvre slot	10	Screen - round wire	For MATERIAL and FIXING Codes Please refer to CASING DETAILS code table			
5	Casing - Machine slotted	11	Screen - wedge wire				
6	Casing - Oxy cut slot						

GRAVEL PACK - METHOD OF PLACEMENT

7

1	Poured or shovelled into annulus	2	Placed through tremie pipe	3	Reverse circulated
---	----------------------------------	---	----------------------------	---	--------------------

WORK PARTLY BACKFILLED OR ABANDONED - SEALING MATERIAL

11

1	Cement grout	3	Bentonite	5	Clay	7	Gravel
2	Concrete	4	Drilled cuttings	6	Sand	8	Coarse stone

DRILLER'S ROCK STRATA DESCRIPTION

15

Reporting sequence	1	2	3	4	To save confusion, write the full name of colour and abbreviate the following: light = lt, dark = dk, fine grained = fg, medium grained = mg, coarse grained = cg. Texture can relate to weathered, fractured, broken, hard, soft etc.
	Rock type	Colour	Grain size	Texture	
Example	Sandstone	Dk Grey	mg	Fractured	

Appendix C

Form A's



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	150 m	

Work Licence No:	TMB03B	2
Name of Licensee:	Snowy Hydro 2.0 Project	
Intended Use:	Monitoring Bore	
Completion Date:	30-01-18	

DRILLING DETAILS 3			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method
0	2	254	See Code 3
2	39	160	5
39	150	140	16
			9

WATER BEARING ZONES 4											
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)
schedule	attached					See Code 4					

CASING / LINER DETAILS 5													
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing	Casing support method		Type of casing bottom					
Code 5					Code 5	See Code 5	2	See Code 5 2					
9	168	4.8	0	39	6	Centralisers installed {Yes/No}	No	(indicate on sketch)					
8	60.2	5	0	141	5	Sump installed {Yes/No}	Yes	From	147	m	To	150	m
8	60.2	5	147	150	5	Pressure cemented {Yes/No}	No	From		m	To		m
Casing Protector cemented in place													

WATER ENTRY DESIGN 6										
General							Screen	Slot Details		
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type	Fixing	Aperture (mm)	Length (mm)	Width (mm)	Alignment
Code 5					See Code 6	See Code 5				See Code 6
8	60.2	5	141	147	5	5	0.4	20	10	H

GRAVEL PACK 7									
Type		Grade	Grain size (mm)		Depth (m)		Quantity		
			From	To	From	To	Litres	m ³	
Rounded	<input checked="" type="checkbox"/>	Graded	<input checked="" type="checkbox"/>	3	5	135	150		
Crushed	<input type="checkbox"/>	Ungraded	<input type="checkbox"/>						
Bentonite/Grout seal (Yes/No)			Yes		132	135			
Method of placement of Gravel Pack			See Code 7		1				

For Departmental use only: **G W**

Work Licence No: TMB03B

BORE DEVELOPMENT 8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs 0.5 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION 9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION 10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								

Height of measuring point above ground level _____ m Test Method _____ See Code 4

WORK PARTLY BACKFILLED OR ABANDONED 11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ 12

Lot No _____ DP No _____ 13

Work Location Co ordinates Easting **6368507** Northing **6038507** Zone _____

GPS: (Yes/No) Yes >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____ Licensee: _____

Date: _____ Date: _____



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	34 m	

Work Licence No:	TMB03A	2	
Name of Licensee:	Snowy Hydro 2.0 Project		
Intended Use:	Monitoring Bore		
Completion Date:	31-01-18		
DRILLING DETAILS			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method
0	34	140	See Code 3
			9

WATER BEARING ZONES											
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)
33	34		11.9	0.1	0.1	See Code 4			15		37.7

CASING / LINER DETAILS											
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing	Casing support method					
Code 5					Code 5	See Code 5					
8	60.2	5	0	29.5	5	Type of casing bottom					
8	60.2	5	32.5	34	5	See Code 5					
						Centralisers installed (Yes/No)	No	(indicate on sketch)			
						Sump installed (Yes/No)	Yes	From	32.5 m	To	34 m
						Pressure cemented (Yes/No)	No	From		To	
						Casing Protector cemented in place					

WATER ENTRY DESIGN										
General							Screen	Slot Details		
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type	Fixing	Aperture (mm)	Length (mm)	Width (mm)	Alignment
Code 5					See Code 6	See Code 5				See Code 6
8	60.2	5	29.5	32.5	5	5	0.4	20	10	H

GRAVEL PACK									
Type		Grade		Grain size (mm)		Depth (m)		Quantity	
				From	To	From	To	Litres	m ³
Rounded	<input checked="" type="checkbox"/>	Graded	<input checked="" type="checkbox"/>	3	5	26.5	34		
Crushed	<input type="checkbox"/>	Ungraded	<input type="checkbox"/>						
Bentonite/Grout seal (Yes/No)				Yes		23.5	26.5		
Method of placement of Gravel Pack				See Code 7		1			

For Departmental use only: **GW**



Work Licence No: TMB03A

BORE DEVELOPMENT 8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs _____ 0.5 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION 9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION 10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								

Height of measuring point above ground level _____ m Test Method _____ See Code 4

WORK PARTLY BACKFILLED OR ABANDONED 11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ 12

Work Location Co ordinates 13

Lot No _____ DP No _____

Easting **636224** Northing **6038505** Zone _____

GPS: (Yes/No) >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____ **Licensee:** _____

Date: _____ **Date:** _____



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	201 m	

Work Licence No:	TMB02B	2	
Name of Licensee:	Snowy Mountains Hydro		
Intended Use:	Monitoring Bore		
Completion Date:	01-03-18		
DRILLING DETAILS			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method
0	1.3	254	See Code 3
1.3	41	200	2
41	201	140	9

WATER BEARING ZONES											
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)
see		attached				See Code 4					

CASING / LINER DETAILS													
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing	Casing support method		Type of casing bottom					
Code 5					Code 5	See Code 5	2	See Code 5					
9	219.1	4.8	0	1.3	8	Centralisers installed (Yes/No)	No	(indicate on sketch)					
9	168	4.8	0	41	6	Sump installed (Yes/No)	Yes	From	197	m	To	201	m
8	60.2	5	0	191	5	Pressure cemented (Yes/No)	No	From		m	To		m
8	60.2	5	197	201	5	Casing Protector cemented in place							

WATER ENTRY DESIGN										
General							Screen	Slot Details		
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type	Fixing	Aperture (mm)	Length (mm)	Width (mm)	Alignment
Code 5					See Code 6	See Code 5				See Code 6
8	60.2	5	191	197	5	5	1	20	10	H

GRAVEL PACK									
Type	Grade	Grain size (mm)		Depth (m)		Quantity			
		From	To	From	To	Litres	m ³		
Rounded	<input checked="" type="checkbox"/>	Graded	<input checked="" type="checkbox"/>	3	5	188	200		
Crushed	<input type="checkbox"/>	Ungraded	<input type="checkbox"/>						
Bentonite/Grout seal (Yes/No)		Yes				185	188		
Method of placement of Gravel Pack				See Code 7	1				

For Departmental use only: **GW**

Work Licence No: TMB02B

BORE DEVELOPMENT 8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs _____ 1 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION 9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION 10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								

Height of measuring point above ground level _____ m Test Method _____ See Code 4

WORK PARTLY BACKFILLED OR ABANDONED 11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other 12

Lot No _____ DP No _____ 13

Work Location Co ordinates Easting Northing Zone

GPS: (Yes/No) Yes >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____ **Licensee:** _____

Date: _____ **Date:** _____

Work Licence No: TMB02B

DRILLER'S ROCK/STRATA DESCRIPTION (LITHOLOGY)			WORK CONSTRUCTION SKETCH
Depth		Description <div style="border: 1px solid black; padding: 2px;">See Code 15</div>	
From (m)	To (m)		
0	1	Dark Brown Soil	
1	24	Light to medium caly thinly bedded weathered	
24	200	medium green/grey metasediments	

WORK NOT CONSTRUCTED BY DRILLING RIG							
Method of excavation: Hand dug <input type="checkbox"/> Back hoe <input type="checkbox"/> Dragline <input type="checkbox"/> Dozer <input type="checkbox"/> Other <input type="text"/>							
Depth (m)	Length (m)	Width (m)	Diameter (m)	Lining material	Dimensions of liner (m)	From Depth (m)	To Depth (m)

Please attach copies of the following if available			
Geologist log (Yes/No) <input type="checkbox"/>	Laboratory analysis of water Sample (Yes/No) <input type="checkbox"/>	Pumping test(s) (Yes/No) <input type="checkbox"/>	
Geophysical log (Yes/No) <input type="checkbox"/>	Sieve analysis of aquifer material (Yes/No) <input type="checkbox"/>	Installed Pump details (Yes/No) <input type="checkbox"/>	



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	15 m	

Work Licence No:	TMB02A	2	
Name of Licensee:	Snowy Mountains Hydro		
Intended Use:	Monitoring Bore		
Completion Date:	26-02-18		
DRILLING DETAILS			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method
0	15	160	See Code 3
			9

WATER BEARING ZONES											
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)
12	13	1	5.6	0.3	0.3	1 A			15	20.3	

CASING / LINER DETAILS											
Material	OD	Wall Thickness	From	To	Method Fixing	Casing support method					
Code 5	(mm)	(mm)	(m)	(m)	Code 5	See Code 5					
5	60.2	5	0	10.7	5	Type of casing bottom					
5	60.2	5	13.7	15	5	See Code 5					
						Centralisers installed (Yes/No)	No	(indicate on sketch)			
						Sump installed (Yes/No)	Yes	From	13.7 m	To	15 m
						Pressure cemented (Yes/No)	No	From	m	To	m
Casing Protector cemented in place											

WATER ENTRY DESIGN										
General							Screen	Slot Details		
Material	OD	Wall Thickness	From	To	Opening type	Fixing	Aperture	Length	Width	Alignment
Code 5	(mm)	(mm)	(m)	(m)	See Code 6	See Code 5	(mm)	(mm)	(mm)	See Code 6
5	60.2	5	10.7	13.7	5	5	1	20	10	H

GRAVEL PACK									
Type	Grade	Grain size (mm)		Depth (m)		Quantity			
		From	To	From	To	Litres	m ³		
Rounded	<input checked="" type="checkbox"/>	Graded	<input checked="" type="checkbox"/>	3	5	7.7	15		
Crushed	<input type="checkbox"/>	Ungraded	<input type="checkbox"/>						
Bentonite/Grout seal (Yes/No)		Yes				4.7	7.7		
Method of placement of Gravel Pack				See Code 7		1			

For Departmental use only: **GW**



Work Licence No: TMB02A

BORE DEVELOPMENT 8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs 0.25 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION 9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION 10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								

Height of measuring point above ground level _____ m Test Method _____ See Code 4

WORK PARTLY BACKFILLED OR ABANDONED 11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ 12

Work Location Co ordinates 13

Lot No _____ DP No _____

Easting **633550** Northing **6038604** Zone _____

GPS: (Yes/No) >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
 Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____

Licensee: _____

Date: _____

Date: _____

Work Licence No: TMB02A

DRILLER'S ROCK/STRATA DESCRIPTION (LITHOLOGY)			WORK CONSTRUCTION SKETCH
Depth		Description <div style="border: 1px solid black; padding: 2px;">See Code 15</div>	
From (m)	To (m)		
0	1	Dark Brown Soil	
1	3	Light Yellow-Brown Clay	
3	8	Medium Orange Clay	
8	15	Medium Yellow-Brown Clay	

15

WORK NOT CONSTRUCTED BY DRILLING RIG							
Method of excavation: Hand dug <input type="checkbox"/> Back hoe <input type="checkbox"/> Dragline <input type="checkbox"/> Dozer <input type="checkbox"/> Other <input type="text"/>							
Depth (m)	Length (m)	Width (m)	Diameter (m)	Lining material	Dimensions of liner (m)	From Depth (m)	To Depth (m)

16

Please attach copies of the following if available			
Geologist log (Yes/No) <input type="checkbox"/>	Laboratory analysis of water Sample (Yes/No) <input type="checkbox"/>	Pumping test(s) (Yes/No) <input type="checkbox"/>	
Geophysical log (Yes/No) <input type="checkbox"/>	Sieve analysis of aquifer material (Yes/No) <input type="checkbox"/>	Installed Pump details (Yes/No) <input type="checkbox"/>	

17



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	60.5 m	

Work Licence No:	MB07B	2	
Name of Licensee:	Snowy Mountains Hydro		
Intended Use:	Monitoring Bore		
Completion Date:	23-02-18		
DRILLING DETAILS			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method
0	23	200	See Code 3
23	60.5	140	9

WATER BEARING ZONES											
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)
22	23	1	9	0.2	0.2	1 A			15	2534	
36	37	1		0.1	0.3	1 A			15	2151	
48	49	1		0.1	0.4	1 A			15	989	

CASING / LINER DETAILS													
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing	Casing support method		Type of casing bottom					
Code 5					Code 5	See Code 5		See Code 5					
5	160.25	6.7	0	23	1	Centralisers installed (Yes/No) No		(indicate on sketch)					
8	60.2	5	0	51	5	Sump installed (Yes/No) Yes		From	57	m	To	60	m
8	60.2	5	57	60	5	Pressure cemented (Yes/No) No		From		m	To		m
Casing Protector cemented in place													

WATER ENTRY DESIGN										
General							Screen	Slot Details		
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type	Fixing	Aperture (mm)	Length (mm)	Width (mm)	Alignment
Code 5					See Code 6	See Code 5				See Code 6
8	60.2	5	51	57	5	5	1	20	10	H

GRAVEL PACK									
Type		Grade	Grain size (mm)		Depth (m)		Quantity		
			From	To	From	To	Litres	m ³	
Rounded	<input checked="" type="checkbox"/>	Graded	<input checked="" type="checkbox"/>	3	5	48	60		
Crushed	<input type="checkbox"/>	Ungraded	<input type="checkbox"/>						
Bentonite/Grout seal (Yes/No)			Yes		45	48			
Method of placement of Gravel Pack			See Code 7		1				

For Departmental use only: **GW**



Work Licence No: MB07B

BORE DEVELOPMENT 8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs 0.5 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION 9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION 10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								

Height of measuring point above ground level _____ m Test Method _____ See Code 4

WORK PARTLY BACKFILLED OR ABANDONED 11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ 12

Lot No _____ DP No _____ 13

Work Location Co ordinates Easting **641039** Northing **6042296** Zone _____

GPS: (Yes/No) >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
 Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____ **Licensee:** _____

Date: _____ **Date:** _____



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	14 m	

Work Licence No:	MB07A	2
Name of Licensee:	Snowy Mountains Hydro	
Intended Use:	Monitoring Bore	
Completion Date:	23-02-18	

DRILLING DETAILS 3			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method
0	14	160	See Code 3 9

WATER BEARING ZONES 4											
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)
11	12	1	8.85	0.3	0.3	See Code 4 1 A			15	101	
13	14	1		0.5	0.8	1 A			15	60.3	

CASING / LINER DETAILS 5													
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing	Casing support method		Type of casing bottom					
Code 5					Code 5	See Code 5	2	See Code 5 2					
8	60.2	5	0	10	5	Centralisers installed (Yes/No)	No	(indicate on sketch)					
8	60.2	5	13	14	5	Sump installed (Yes/No)	Yes	From	13	m	To	14	m
						Pressure cemented (Yes/No)	No	From		m	To		m
Casing Protector cemented in place													

WATER ENTRY DESIGN 6										
General							Screen	Slot Details		
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type	Fixing	Aperture (mm)	Length (mm)	Width (mm)	Alignment
Code 5					See Code 6	See Code 5	(mm)	(mm)	(mm)	See Code 6
8	60.2	5	10	13	5	5	1	20	10	H

GRAVEL PACK 7									
Type		Grade		Grain size (mm)		Depth (m)		Quantity	
				From	To	From	To	Litres	m ³
Rounded	<input checked="" type="checkbox"/>	Graded	<input checked="" type="checkbox"/>	3	5	7	14		
Crushed	<input type="checkbox"/>	Ungraded	<input type="checkbox"/>						
Bentonite/Grout seal (Yes/No)				Yes		4	7		
Method of placement of Gravel Pack				See Code 7		1			

For Departmental use only: **GW**



Work Licence No: MB07A

BORE DEVELOPMENT 8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs 0.5 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION 9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION 10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								

Height of measuring point above ground level _____ m Test Method _____ See Code 4

WORK PARTLY BACKFILLED OR ABANDONED 11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ 12

Work Location Co ordinates 13

Lot No _____ DP No _____

Easting **641050** Northing **6042295** Zone _____

GPS: (Yes/No) Yes >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____ **Licensee:** _____

Date: _____ **Date:** _____

Work Licence No: MB07A

DRILLER'S ROCK/STRATA DESCRIPTION (LITHOLOGY)			WORK CONSTRUCTION SKETCH
Depth		Description See Code 15	
From (m)	To (m)		
0	1	Soil	
1	5	Reddish Brown Clay	
5	6	Chert (?)	
6	12	Weatheredv silt stone	
12	14	Siltstone	

15

WORK NOT CONSTRUCTED BY DRILLING RIG							
Method of excavation: Hand dug <input type="checkbox"/> Back hoe <input type="checkbox"/> Dragline <input type="checkbox"/> Dozer <input type="checkbox"/> Other <input type="text"/>							
Depth (m)	Length (m)	Width (m)	Diameter (m)	Lining material	Dimensions of liner (m)	From Depth (m)	To Depth (m)

16

Please attach copies of the following if available			
Geologist log (Yes/No) <input type="checkbox"/>	Laboratory analysis of water Sample (Yes/No) <input type="checkbox"/>	Pumping test(s) (Yes/No) <input type="checkbox"/>	
Geophysical log (Yes/No) <input type="checkbox"/>	Sieve analysis of aquifer material (Yes/No) <input type="checkbox"/>	Installed Pump details (Yes/No) <input type="checkbox"/>	

17

Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	101 m	

Work Licence No:	MB03	2	
Name of Licensee:	Snowy Hydro 2.0 Project		
Intended Use:	Monitoring Bore		
Completion Date:	24-01-18		
DRILLING DETAILS			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method
0	16	200	See Code 3
16	101	140	9

WATER BEARING ZONES											4
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)
see		attached		schedule		See Code 4					

CASING / LINER DETAILS											5			
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing	Casing support method								
Code 5					Code 5	See Code 5		2						
						Type of casing bottom		See Code 5						
5	160.25	6.7	0	18	1	Centralisers installed (Yes/No)		No (indicate on sketch)						
8	60.2	5	0	92	5	Sump installed (Yes/No)		Yes	From	98	m	To	101	m
8	60.2	5	98	101	5	Pressure cemented (Yes/No)		No	From		m	To		m
Casing Protector cemented in place														

WATER ENTRY DESIGN											6
General							Screen	Slot Details			
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type	Fixing	Aperture (mm)	Length (mm)	Width (mm)	Alignment	
Code 5					See Code 6	See Code 5				See Code 6	
8	60.2	5	92	98	5	5	0.4	20	10	H	

GRAVEL PACK											7
Type		Grade		Grain size (mm)		Depth (m)		Quantity			
Rounded	<input checked="" type="checkbox"/>	Graded	<input checked="" type="checkbox"/>	From	To	From	To	Litres	m ³		
Crushed	<input type="checkbox"/>	Ungraded	<input type="checkbox"/>	3	5	89	101				
Bentonite/Grout seal (Yes/No)			Yes			86	89				
Method of placement of Gravel Pack				See Code 7		1					

For Departmental use only: **G W**



Work Licence No: MB03

BORE DEVELOPMENT 8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs 0.5 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION 9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION 10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								

Height of measuring point above ground level _____ m Test Method _____ See Code 4

WORK PARTLY BACKFILLED OR ABANDONED 11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ 12

Work Location Co ordinates 13

Lot No _____ DP No _____

Easting **637490** Northing **6043212** Zone _____

GPS: (Yes/No) >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
 Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____ Licensee: _____

Date: _____ Date: _____



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	53 m	

Work Licence No:	MB01C	2	
Name of Licensee:	Snowy Mountains Hydro		
Intended Use:	Monitoring Bore		
Completion Date:	16-01-18		
DRILLING DETAILS			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method
0	11	200	See Code 3
11	53	140	9

WATER BEARING ZONES												4
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)		
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)	
attached	schedule					See Code 4						

CASING / LINER DETAILS												5	
Material	OD	Wall Thickness	From	To	Method Fixing	Casing support method						See Code 5	2
Code 5	(mm)	(mm)	(m)	(m)	Code 5	Type of casing bottom						See Code 5	2
8	60.2	5	0	45	5	Centralisers installed (Yes/No)	No	(indicate on sketch)					
8	60.2	5	51	52	5	Sump installed (Yes/No)	Yes	From	51	m	To	52	m
9	168	4.8	0	10.3	6	Pressure cemented (Yes/No)	No	From		m	To		m
Casing Protector cemented in place													

WATER ENTRY DESIGN											6
General							Screen	Slot Details			
Material	OD	Wall Thickness	From	To	Opening type	Fixing	Aperture	Length	Width	Alignment	
Code 5	(mm)	(mm)	(m)	(m)	See Code 6	See Code 5	(mm)	(mm)	(mm)	See Code 6	
8	60.2	5	45	51	5	5	0.4	20	10	H	

GRAVEL PACK										7
Type		Grade		Grain size (mm)		Depth (m)		Quantity		
				From	To	From	To	Litres	m ³	
Rounded	<input checked="" type="checkbox"/>	Graded	<input checked="" type="checkbox"/>	3	5	41	52			
Crushed	<input type="checkbox"/>	Ungraded	<input type="checkbox"/>							
Bentonite/Grout seal (Yes/No)				Yes		36	41			
Method of placement of Gravel Pack				See Code 7		1				

For Departmental use only: **G W**

Work Licence No: MB01C

BORE DEVELOPMENT 8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs 0.5 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION 9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION 10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								

Height of measuring point above ground level _____ m Test Method _____ See Code 4

WORK PARTLY BACKFILLED OR ABANDONED 11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ 12

Lot No _____ DP No _____ 13

Work Location Co ordinates Easting **637069** Northing **6040249** Zone _____

GPS: (Yes/No) >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____ Licensee: _____

Date: _____ Date: _____

Work Licence No: MB01C

DRILLER'S ROCK/STRATA DESCRIPTION (LITHOLOGY)			WORK CONSTRUCTION SKETCH
Depth		Description	
From (m)	To (m)		
		See Code 15	<div style="border: 1px solid black; width: 100px; height: 100px; margin: auto;"></div>
0	2	Regolith orange brown gravels, sand	
2	10	Extremely unconsolidated basalt, gravels	
10	30	Fractured Metamorphosed basalt, FG, pale grey/blue	
30	36	Clayey metamorphosed shale, grey/black	
36	53	green schist, FG, darg grey/green	

15

WORK NOT CONSTRUCTED BY DRILLING RIG							
Method of excavation: Hand dug <input type="checkbox"/> Back hoe <input type="checkbox"/> Dragline <input type="checkbox"/> Dozer <input type="checkbox"/> Other <input type="text"/>							
Depth (m)	Length (m)	Width (m)	Diameter (m)	Lining material	Dimensions of liner (m)	From Depth (m)	To Depth (m)

16

Please attach copies of the following if available			
Geologist log (Yes/No) <input type="checkbox"/>	Laboratory analysis of water Sample (Yes/No) <input type="checkbox"/>	Pumping test(s) (Yes/No) <input type="checkbox"/>	
Geophysical log (Yes/No) <input type="checkbox"/>	Sieve analysis of aquifer material (Yes/No) <input type="checkbox"/>	Installed Pump details (Yes/No) <input type="checkbox"/>	

17



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	11.5 m	

Work Licence No:	MB01B	2	
Name of Licensee:	Snowy Mountains Hydro		
Intended Use:	Monitoring Bore		
Completion Date:	18-01-18		
DRILLING DETAILS			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method
0	11.5	140	See Code 3 9

WATER BEARING ZONES											4
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)
4	5	1	3.5	0.8	0.8	See Code 4 1 A			15	122.1	

CASING / LINER DETAILS											5
Material	OD	Wall Thickness	From	To	Method Fixing	Casing support method					See Code 5 2
Code 5	(mm)	(mm)	(m)	(m)	Code 5	Type of casing bottom					See Code 5 2
8	60.2	5	0	5.3	5	Centralisers installed (Yes/No)	No	(indicate on sketch)			
8	60.2	5	6.8	7	5	Sump installed (Yes/No)	Yes	From	6.8 m	To	7 m
						Pressure cemented (Yes/No)	No	From	m	To	m
Casing Protector cemented in place											

WATER ENTRY DESIGN											6
General							Screen	Slot Details			
Material	OD	Wall Thickness	From	To	Opening type	Fixing	Aperture	Length	Width	Alignment	
Code 5	(mm)	(mm)	(m)	(m)	See Code 6	See Code 5	(mm)	(mm)	(mm)	See Code 6	
8	60.2	5	5.3	6.8	5	5	0.4	20	10	H	

GRAVEL PACK											7
Type		Grade		Grain size (mm)		Depth (m)		Quantity			
				From	To	From	To	Litres	m ³		
Rounded	<input checked="" type="checkbox"/>	Graded	<input checked="" type="checkbox"/>	3	5	4.2	7				
Crushed	<input type="checkbox"/>	Ungraded	<input type="checkbox"/>								
Bentonite/Grout seal (Yes/No)				Yes		2.5	4.2				
Method of placement of Gravel Pack				See Code 7		1					

For Departmental use only: **GW**



Work Licence No: MB01B

BORE DEVELOPMENT 8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs 0.5 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION 9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION 10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								

Height of measuring point above ground level _____ m Test Method _____ See Code 4

WORK PARTLY BACKFILLED OR ABANDONED 11

Original depth of work: 11 m Is work partly backfilled: (Yes/No) Yes

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		
4	7	11			

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ 12

Work Location Co ordinates 13

Lot No _____ DP No _____

Easting 637055 Northing 6040240 Zone _____

GPS: (Yes/No) Yes >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
 Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____ Licensee: _____

Date: _____ Date: _____

Work Licence No: MB01B

DRILLER'S ROCK/STRATA DESCRIPTION (LITHOLOGY)			WORK CONSTRUCTION SKETCH
Depth		Description	
From (m)	To (m)		
0	2	Regolith, brown/orange clay	<div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">See Code 15</div>
2	11.5	Extremely unconsolidated basalt, gravels	

15

WORK NOT CONSTRUCTED BY DRILLING RIG							
Method of excavation: Hand dug <input type="checkbox"/> Back hoe <input type="checkbox"/> Dragline <input type="checkbox"/> Dozer <input type="checkbox"/> Other <input type="text"/>							
Depth (m)	Length (m)	Width (m)	Diameter (m)	Lining material	Dimensions of liner (m)	From Depth (m)	To Depth (m)

16

Please attach copies of the following if available			
Geologist log (Yes/No) <input type="checkbox"/>	Laboratory analysis of water Sample (Yes/No) <input type="checkbox"/>	Pumping test(s) (Yes/No) <input type="checkbox"/>	
Geophysical log (Yes/No) <input type="checkbox"/>	Sieve analysis of aquifer material (Yes/No) <input type="checkbox"/>	Installed Pump details (Yes/No) <input type="checkbox"/>	

17



Driller's Licence No:	DL 1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	200 m	

Work Licence No:	TMB04	2
Name of Licensee:	Snowy Mountains Hydro	
Intended Use:	Monitoring Bore	
Completion Date:	19-02-18	

DRILLING DETAILS				3
From (m)	To (m)	Hole Diameter (mm)	Drilling Method	
0	30	200	See Code 3	9
30	200	140		9

WATER BEARING ZONES												4
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)		
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)	
ee		attached				See Code 4						

CASING / LINER DETAILS												5	
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing	Casing support method						See Code 5	2
Code 5					Code 5	Type of casing bottom						See Code 5	2
5	160.25	6.7	0	30	1	Centralisers installed {Yes/No}	No	(indicate on sketch)					
8	60.2	5	0	191	5	Sump installed {Yes/No}	Yes	From	197 m	To	200 m	m	
8	60.2	5	197	200	5	Pressure cemented {Yes/No}	No	From		To		m	
Casing Protector cemented in place													

WATER ENTRY DESIGN											6
General							Screen	Slot Details			
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type	Fixing	Aperture (mm)	Length (mm)	Width (mm)	Alignment	
Code 5					See Code 6	See Code 5				See Code 6	
8	60.2	5	191	197	5	5	1	20	10	H	

GRAVEL PACK										7
Type	Grade	Grain size (mm)		Depth (m)		Quantity				
		From	To	From	To	Litres	m ³			
Rounded	X	Graded	X	3	5	188	200			
Crushed		Ungraded								
Bentonite/Grout seal (Yes/No)		Yes				185	188			
Method of placement of Gravel Pack				See Code 7		1				

For Departmental use only: **GW**



Work Licence No: TMB04

BORE DEVELOPMENT

8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs 1 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION

9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION

10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								

Height of measuring point above ground level _____ m Test Method _____ See Code 4

WORK PARTLY BACKFILLED OR ABANDONED

11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ **12**

Lot No _____ DP No _____ **13**

Work Location Co ordinates Easting 634541 Northing 6038599 Zone 55

GPS: (Yes/No) Yes >> AMG/AGD or MGA/GDA (See explanation)


Please mark the work site with "X" on the CLID provided map.
 Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____
 Date: _____

Licensee: _____
 Date: _____

Work Licence No: TMB04

DRILLER'S ROCK/STRATA DESCRIPTION (LITHOLOGY)			15
Depth		Description	
From (m)	To (m)		
		See Code 15	WORK CONSTRUCTION SKETCH 
0	1.00	SOIL orange, fill/spoil	
1.00	8.00	CLAY medium orangey brown, extremely weathered	
8.00	27.00	CLAY medium to dark reddish brown, extremely weathered	
27.00	200.00	BASALT light bluish grey, extremely weathered	

WORK NOT CONSTRUCTED BY DRILLING RIG								16	
Method of excavation:									
Hand dug	<input type="checkbox"/>	Back hoe	<input type="checkbox"/>	Dragline	<input type="checkbox"/>	Dozer	<input type="checkbox"/>	Other	<input type="text"/>
Depth (m)	Length (m)	Width (m)	Diameter (m)	Lining material	Dimensions of liner (m)	From Depth (m)	To Depth (m)		

Please attach copies of the following if available						17		
Geologist log	(Yes/No)	<input type="checkbox"/>	Laboratory analysis of water Sample	(Yes/No)	<input type="checkbox"/>	Pumping test(s)	(Yes/No)	<input type="checkbox"/>
Geophysical log	(Yes/No)	<input type="checkbox"/>	Sieve analysis of aquifer material	(Yes/No)	<input type="checkbox"/>	Installed Pump details	(Yes/No)	<input type="checkbox"/>



Driller's Licence No:	DL 1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	72 m	

Work Licence No:	MB06B	2
Name of Licensee:	Snowy Mountains Hydro	
Intended Use:	Monitoring Bore	
Completion Date:	04-04-18	

DRILLING DETAILS				3
From (m)	To (m)	Hole Diameter (mm)	Drilling Method	
0	25	200	See Code 3	9
30	72	140		9

WATER BEARING ZONES												4
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)		
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)	
see		attached				See Code 4						

CASING / LINER DETAILS												5	
Material	OD	Wall Thickness	From	To	Method Fixing	Casing support method						See Code 5	2
Code 5	(mm)	(mm)	(m)	(m)	Code 5	Type of casing bottom						See Code 5	2
5	160.25	6.7	0	25	1	Centralisers installed {Yes/No}	No	(indicate on sketch)					
8	60.2	5	0	64	5	Sump installed {Yes/No}	Yes	From	70 m	To	72 m		
8	60.2	5	70	72	5	Pressure cemented {Yes/No}	No	From		To			
Casing Protector cemented in place													

WATER ENTRY DESIGN											6
General							Screen	Slot Details			
Material	OD	Wall Thickness	From	To	Opening type	Fixing	Aperture	Length	Width	Alignment	
Code 5	(mm)	(mm)	(m)	(m)	See Code 6	See Code 5	(mm)	(mm)	(mm)	See Code 6	
8	60.2	5	64	70	5	5	1	20	10	H	

GRAVEL PACK										7
Type	Grade	Grain size (mm)		Depth (m)		Quantity				
		From	To	From	To	Litres	m ³			
Rounded	X	Graded	X	3	5	60	72			
Crushed		Ungraded								
Bentonite/Grout seal (Yes/No)		Yes				56	60			
Method of placement of Gravel Pack				See Code 7		1				

For Departmental use only: **GW**



Work Licence No: MB06B

BORE DEVELOPMENT

8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs _____ 1 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION

9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION

10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								
Height of measuring point above ground level			m	Test Method			See Code 4	

WORK PARTLY BACKFILLED OR ABANDONED

11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ **12**

Lot No _____ DP No _____ **13**

Work Location Co ordinates Easting **628719** Northing **6048397** Zone **55**

GPS: (Yes/No) Yes >> AMG/AGD or MGA/GDA (See explanation)


Please mark the work site with "X" on the CLID provided map.
 Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____
 Date: _____

Licensee: _____
 Date: _____

Work Licence No: MB06B

DRILLER'S ROCK/STRATA DESCRIPTION (LITHOLOGY)			15
Depth		Description	
From (m)	To (m)		
		See Code 15	WORK CONSTRUCTION SKETCH 
0.00	1.00	SOIL dark brown	
1.00	19.00	VOLCANIC ROCK, UNDIFFERENTIATED dark reddish orange, extremely weathered, CLAY, 30% dark reddish orange	
19.00	32.00	VOLCANIC ROCK, UNDIFFERENTIATED orangey brown, highly weathered	
32.00	72.00	VOLCANIC ROCK, UNDIFFERENTIATED dark blackish grey, fresh	

WORK NOT CONSTRUCTED BY DRILLING RIG								16
Method of excavation: Hand dug <input type="checkbox"/> Back hoe <input type="checkbox"/> Dragline <input type="checkbox"/> Dozer <input type="checkbox"/> Other <input type="text"/>								
Depth (m)	Length (m)	Width (m)	Diameter (m)	Lining material	Dimensions of liner (m)	From Depth (m)	To Depth (m)	

Please attach copies of the following if available						17
Geologist log	(Yes/No) <input type="checkbox"/>	Laboratory analysis of water Sample	(Yes/No) <input type="checkbox"/>	Pumping test(s)	(Yes/No) <input type="checkbox"/>	
Geophysical log	(Yes/No) <input type="checkbox"/>	Sieve analysis of aquifer material	(Yes/No) <input type="checkbox"/>	Installed Pump details	(Yes/No) <input type="checkbox"/>	



Driller's Licence No:	DL 1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	14 m	

Work Licence No:	MB06A	2	
Name of Licensee:	Snowy Mountains Hydro		
Intended Use:	Monitoring Bore		
Completion Date:	05-04-18		
DRILLING DETAILS			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method
0	14	140	See Code 3
			9

WATER BEARING ZONES												4
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method		D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative	See Code 4			Hrs	min	Cond (µS/cm)	TDS (mg/L)
10	11	1	4.51	0.2	0.2	1	A			15	88.2	

CASING / LINER DETAILS												5	
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing	Casing support method							
Code 5	8	60.2	5	0	9	5	See Code 5 2						
						Type of casing bottom							
						See Code 5 2							
						Centralisers installed {Yes/No}	No	(indicate on sketch)					
						Sump installed {Yes/No}	Yes	From	12	m	To	14	m
						Pressure cemented {Yes/No}	No	From		m	To		m
						Casing Protector cemented in place							

WATER ENTRY DESIGN											6
General							Screen	Slot Details			
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type	Fixing	Aperture (mm)	Length (mm)	Width (mm)	Alignment	
Code 5	8	60.2	5	9	12	5	5	1	20	10	See Code 6

GRAVEL PACK										7
Type	Grade	Grain size (mm)		Depth (m)		Quantity				
		From	To	From	To	Litres	m ³			
Rounded	X	Graded	X	3	5	6	14			
Crushed		Ungraded								
Bentonite/Grout seal (Yes/No)		Yes				3	6			
Method of placement of Gravel Pack				See Code 7		1				

For Departmental use only: **GW**



Work Licence No: MB06A

BORE DEVELOPMENT

8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs _____ 1 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION

9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION

10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								
Height of measuring point above ground level			m	Test Method			See Code 4	

WORK PARTLY BACKFILLED OR ABANDONED

11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ **12**

Lot No _____ DP No _____ **13**

Work Location Co ordinates Easting **628723** Northing **6048391** Zone **55**

GPS: (Yes/No) Yes >> AMG/AGD or MGA/GDA (See explanation)


Please mark the work site with "X" on the CLID provided map.
 Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____
 Date: _____

Licensee: _____
 Date: _____

Work Licence No: MB06A

DRILLER'S ROCK/STRATA DESCRIPTION (LITHOLOGY)			15
Depth		Description	WORK CONSTRUCTION SKETCH
From (m)	To (m)		
0.00	1.00	SOIL dark brown	
1.00	14.00	VOLCANIC ROCK, dark reddish orange,	

WORK NOT CONSTRUCTED BY DRILLING RIG								16
Method of excavation: Hand dug <input type="checkbox"/> Back hoe <input type="checkbox"/> Dragline <input type="checkbox"/> Dozer <input type="checkbox"/> Other <input type="text"/>								
Depth (m)	Length (m)	Width (m)	Diameter (m)	Lining material	Dimensions of liner (m)	From Depth (m)	To Depth (m)	

Please attach copies of the following if available						17
Geologist log	(Yes/No) <input type="checkbox"/>	Laboratory analysis of water Sample	(Yes/No) <input type="checkbox"/>	Pumping test(s)	(Yes/No) <input type="checkbox"/>	
Geophysical log	(Yes/No) <input type="checkbox"/>	Sieve analysis of aquifer material	(Yes/No) <input type="checkbox"/>	Installed Pump details	(Yes/No) <input type="checkbox"/>	



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	102 m	

Work Licence No:	MB04B	2	
Name of Licensee:	Snowy Hudro 2.0 Project		
Intended Use:	Monitoring Bore		
Completion Date:	05-02-18		
DRILLING DETAILS			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method
0	10	200	See Code 3
10	102	140	9

WATER BEARING ZONES											
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)
53	54		48.8	0.05	0.05	1 A		0.5		147.4	

CASING / LINER DETAILS											
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing	Casing support method		Type of casing bottom			
Code 5					Code 5	See Code 5		See Code 5			
8	60.2	5	0	93.5	5	Centralisers installed (Yes/No)		(indicate on sketch)			
8	60.2	5	99.5	102.5	5	Sump installed (Yes/No)		From	99.5 m	To	103 m
5	160.25	6.7	0	18	1	Pressure cemented (Yes/No)		From		To	
Casing Protector cemented in place											

WATER ENTRY DESIGN										
General							Screen	Slot Details		
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type	Fixing	Aperture (mm)	Length (mm)	Width (mm)	Alignment
Code 5					See Code 6	See Code 5				See Code 6
8	60.2	5	93.5	99.5	5	5	1	20	10	H

GRAVEL PACK									
Type		Grade		Grain size (mm)		Depth (m)		Quantity	
				From	To	From	To	Litres	m ³
Rounded	<input checked="" type="checkbox"/>	Graded	<input checked="" type="checkbox"/>	3	5	90.5	102.5		
Crushed	<input type="checkbox"/>	Ungraded	<input type="checkbox"/>						
Bentonite/Grout seal (Yes/No)				Yes		87.5	90.5		
Method of placement of Gravel Pack				See Code 7		1			

For Departmental use only: **GW**



Work Licence No: MB04B

BORE DEVELOPMENT 8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs 0.5 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION 9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION 10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								

Height of measuring point above ground level _____ m Test Method _____ See Code 4

WORK PARTLY BACKFILLED OR ABANDONED 11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ 12

Work Location Co ordinates 13

Lot No _____ DP No _____

Easting **640023** Northing **6047820** Zone _____

GPS: (Yes/No) Yes >> AMG/AGD or MGA/GDA (See explanation)


Please mark the work site with "X" on the CLID provided map.
Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____ **Licensee:** _____

Date: _____ **Date:** _____

Work Licence No: MB04B

DRILLER'S ROCK/STRATA DESCRIPTION (LITHOLOGY)			WORK CONSTRUCTION SKETCH
Depth		Description See Code 15	
From (m)	To (m)		
0	1	Soil	
1	2	Weathered Basalt	
2	3	Moderately Weathered Basalt	
3	78	Basalt	
78	102.5	Fine Sandstone/Siltstone	

15

WORK NOT CONSTRUCTED BY DRILLING RIG							
Method of excavation: Hand dug <input type="checkbox"/> Back hoe <input type="checkbox"/> Dragline <input type="checkbox"/> Dozer <input type="checkbox"/> Other <input type="text"/>							
Depth (m)	Length (m)	Width (m)	Diameter (m)	Lining material	Dimensions of liner (m)	From Depth (m)	To Depth (m)

16

Please attach copies of the following if available			
Geologist log (Yes/No) <input type="checkbox"/>	Laboratory analysis of water Sample (Yes/No) <input type="checkbox"/>	Pumping test(s) (Yes/No) <input type="checkbox"/>	
Geophysical log (Yes/No) <input type="checkbox"/>	Sieve analysis of aquifer material (Yes/No) <input type="checkbox"/>	Installed Pump details (Yes/No) <input type="checkbox"/>	

17



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	30.5 m	

Work Licence No:	MB04A	2	
Name of Licensee:	Snowy Hudro 2.0 Project		
Intended Use:	Monitoring Bore		
Completion Date:	07-02-18		
DRILLING DETAILS			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method
0	5	200	See Code 3
5	30.5	140	9

WATER BEARING ZONES											
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)
Nil						See Code 4					

CASING / LINER DETAILS													
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing	Casing support method							
Code 5					Code 5	See Code 5							
8	60.2	5	0	23	5	Type of casing bottom							
8	60.2	5	29	30	5	Centralisers installed (Yes/No)		No	(indicate on sketch)				
5	160.25	6.7	0	5	1	Sump installed (Yes/No)		Yes	From	29	m To	30	m
						Pressure cemented (Yes/No)		No	From		m To		m
Casing Protector cemented in place													

WATER ENTRY DESIGN										
General							Screen	Slot Details		
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type	Fixing	Aperture (mm)	Length (mm)	Width (mm)	Alignment
Code 5					See Code 6	See Code 5				See Code 6
8	60.2	5	23	29	5	5	1	20	10	H

GRAVEL PACK									
Type		Grade	Grain size (mm)		Depth (m)		Quantity		
			From	To	From	To	Litres	m ³	
Rounded	<input checked="" type="checkbox"/>	Graded	<input checked="" type="checkbox"/>	3	5	18	30		
Crushed	<input type="checkbox"/>	Ungraded	<input type="checkbox"/>						
Bentonite/Grout seal (Yes/No)			Yes			17	18		
Method of placement of Gravel Pack			See Code 7		1				

For Departmental use only: **GW**



Work Licence No: MB04A

BORE DEVELOPMENT 8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs _____ 0.5 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION 9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION 10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								

Height of measuring point above ground level _____ m Test Method _____ See Code 4

WORK PARTLY BACKFILLED OR ABANDONED 11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ 12

Work Location Co ordinates 13

Lot No _____ DP No _____

Easting Northing Zone _____

GPS: (Yes/No) Yes >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____ **Licensee:** _____

Date: _____ **Date:** _____

Work Licence No: MB04A

DRILLER'S ROCK/STRATA DESCRIPTION (LITHOLOGY)			WORK CONSTRUCTION SKETCH
Depth		Description See Code 15	
From (m)	To (m)		
0	1	Soil	
1	30.5	Basalt	

15

WORK NOT CONSTRUCTED BY DRILLING RIG							
Method of excavation: Hand dug <input type="checkbox"/> Back hoe <input type="checkbox"/> Dragline <input type="checkbox"/> Dozer <input type="checkbox"/> Other <input type="text"/>							
Depth (m)	Length (m)	Width (m)	Diameter (m)	Lining material	Dimensions of liner (m)	From Depth (m)	To Depth (m)

16

Please attach copies of the following if available			
Geologist log (Yes/No) <input type="checkbox"/>	Laboratory analysis of water Sample (Yes/No) <input type="checkbox"/>	Pumping test(s) (Yes/No) <input type="checkbox"/>	
Geophysical log (Yes/No) <input type="checkbox"/>	Sieve analysis of aquifer material (Yes/No) <input type="checkbox"/>	Installed Pump details (Yes/No) <input type="checkbox"/>	

17



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	150.5 m	

Work Licence No:	MB02	2
Name of Licensee:	Snowy Hydro 2.0 Project	
Intended Use:	Monitoring Bore	
Completion Date:		

DRILLING DETAILS				3
From (m)	To (m)	Hole Diameter (mm)	Drilling Method	
0	12	200	See Code 3	9
12	150.5	140		9

WATER BEARING ZONES												4
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)		
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)	
						See Code 4						

CASING / LINER DETAILS												5	
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing	Casing support method						See Code 5	2
Code 5					Code 5	Type of casing bottom						See Code 5	2
5	160.25	6.7	0	12	1	Centralisers installed {Yes/No}	No	(indicate on sketch)					
8	60.2	5	0	141	5	Sump installed {Yes/No}	Yes	From	147	m	To	150	m
8	60.2	5	147	150	5	Pressure cemented {Yes/No}	No	From		m	To		m
Casing Protector cemented in place													

WATER ENTRY DESIGN											6
General							Screen	Slot Details			
Material	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type	Fixing	Aperture (mm)	Length (mm)	Width (mm)	Alignment	
Code 5					See Code 6	See Code 5				See Code 6	
8	60.2	5	141	147	5	5	0.4	20	10	H	

GRAVEL PACK										7
Type	Grade	Grain size (mm)		Depth (m)		Quantity				
		From	To	From	To	Litres	m ³			
Rounded	X	Graded	X	3	5	138	150	151	0.151	
Crushed		Ungraded								
Bentonite/Grout seal (Yes/No)		Yes				135	138			
Method of placement of Gravel Pack				See Code 7		1				

For Departmental use only: **GW**



Work Licence No: MB02

BORE DEVELOPMENT

8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs 0.5 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION

9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION

10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								
Height of measuring point above ground level			m	Test Method			See Code 4	

WORK PARTLY BACKFILLED OR ABANDONED

11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ **12**

Lot No _____ DP No _____ **13**

Work Location Co ordinates Easting 634310 Northing 6033303 Zone 55

GPS: (Yes/No) Yes >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
 Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____
 Date: _____

Licensee: _____
 Date: _____



Driller's Licence No:	DL 1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	251 m	

Work Licence No:	TMB03C	2
Name of Licensee:	Snowy Mountains Hydro	
Intended Use:	Monitoring Bore	
Completion Date:	15-03-18	

DRILLING DETAILS 3			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method (See Code 3)
0	37	219.1	16
37	251	190.5	9

WATER BEARING ZONES 4											
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method (See Code 4)	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)

CASING / LINER DETAILS 5											
Material (Code 5)	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing (Code 5)	Casing support method (See Code 5)		Type of casing bottom (See Code 5)			
9	219.1	6.35	0	37	6	3		1			
9	139.7	5	0	238.8	6	Centralisers installed {Yes/No}	No	(indicate on sketch)			
9	139.7	5	250.8	251	6	Sump installed {Yes/No}	Yes	From 250.8 m	To 251 m		
						Pressure cemented {Yes/No}	No	From	m	To	m
Casing Protector cemented in place											

WATER ENTRY DESIGN 6										
General							Screen	Slot Details		
Material (Code 5)	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type (See Code 6)	Fixing (See Code 5)	Aperture (mm)	Length (mm)	Width (mm)	Alignment (See Code 6)
9	139.7	5	238.8	250.8	7	6	1	100	200	H

GRAVEL PACK 7									
Type	Grade	Grain size (mm)		Depth (m)		Quantity		Litres	m ³
		From	To	From	To				
Rounded	X	Graded	X	3	5	231	251		
Crushed		Ungraded							
Bentonite/Grout seal (Yes/No)		No				226	231		
Method of placement of Gravel Pack				See Code 7		1			

For Departmental use only: **GW**



Work Licence No: TMB03C

BORE DEVELOPMENT

8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs 0.5 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION

9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION

10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								
Height of measuring point above ground level			m	Test Method			See Code 4	

WORK PARTLY BACKFILLED OR ABANDONED

11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ **12**

Lot No _____ DP No _____ **13**

Work Location Co ordinates Easting 636237 Northing 6038498 Zone 55

GPS: (Yes/No) >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
 Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____
 Date: _____

Licensee: _____
 Date: _____

Work Licence No: TMB03C

DRILLER'S ROCK/STRATA DESCRIPTION (LITHOLOGY)			15
Depth		Description <div style="border: 1px solid black; padding: 2px;">See Code 15</div>	WORK CONSTRUCTION SKETCH
From (m)	To (m)		
0	0.5	Soil	
0.5	16	Clay (decomposed basalt/metabasalt)	
16	111	Metabasalt	
111	112	Greenschist	
112	220	Metabasalt	
220	225	Greenschist	
225	251	Metabasalt	

WORK NOT CONSTRUCTED BY DRILLING RIG								16
Method of excavation: Hand dug <input type="checkbox"/> Back hoe <input type="checkbox"/> Dragline <input type="checkbox"/> Dozer <input type="checkbox"/> Other <input style="width: 100px;" type="text"/>								
Depth (m)	Length (m)	Width (m)	Diameter (m)	Lining material	Dimensions of liner (m)	From Depth (m)	To Depth (m)	

Please attach copies of the following if available						17
Geologist log	(Yes/No) <input type="checkbox"/>	Laboratory analysis of water Sample	(Yes/No) <input type="checkbox"/>	Pumping test(s)	(Yes/No) <input type="checkbox"/>	
Geophysical log	(Yes/No) <input type="checkbox"/>	Sieve analysis of aquifer material	(Yes/No) <input type="checkbox"/>	Installed Pump details	(Yes/No) <input type="checkbox"/>	



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	72 m	

Work Licence No:	TMB01B	2
Name of Licensee:	Snowy Mountains Hydro	
Intended Use:	Monitoring Bore	
Completion Date:	22-03-18	

DRILLING DETAILS				3
From (m)	To (m)	Hole Diameter (mm)	Drilling Method	
0	9.5	168	See Code 3	16
9.5	72	140		9

WATER BEARING ZONES												4
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method	D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)		
				Individual Aquifer	Cumulative			Hrs	min	Cond (µS/cm)	TDS (mg/L)	
						See Code 4						

CASING / LINER DETAILS												5	
Material	OD	Wall Thickness	From	To	Method Fixing	Casing support method						See Code 5	2
Code 5	(mm)	(mm)	(m)	(m)	Code 5	Type of casing bottom						See Code 5	2
9	168	4.8	0	9.5	6	Centralisers installed {Yes/No}	No	(indicate on sketch)					
8	60.2	5	0	63	5	Sump installed {Yes/No}	Yes	From	69	m	To	72	m
8	60.2	5	69	72	5	Pressure cemented {Yes/No}	No	From		m	To		m
						Casing Protector cemented in place							

WATER ENTRY DESIGN											6
General							Screen	Slot Details			
Material	OD	Wall Thickness	From	To	Opening type	Fixing	Aperture	Length	Width	Alignment	
Code 5	(mm)	(mm)	(m)	(m)	See Code 6	See Code 5	(mm)	(mm)	(mm)	See Code 6	
8	60.2	5	63	69	5	5	0.4	20	10	H	

GRAVEL PACK										7
Type	Grade	Grain size (mm)		Depth (m)		Quantity		Litres	m ³	
		From	To	From	To					
Rounded	<input checked="" type="checkbox"/>	Graded	<input checked="" type="checkbox"/>	3	5	60	72			
Crushed	<input type="checkbox"/>	Ungraded	<input type="checkbox"/>							
Bentonite/Grout seal (Yes/No)		Yes				57	60			
Method of placement of Gravel Pack				See Code 7	1					

For Departmental use only: **GW**



Work Licence No: TMB01B

BORE DEVELOPMENT

8

Chemical used for breaking down drilling mud (Yes/No) No Name: _____

Method Bailing/Surging Jetting Airlifting Backwashing Pumping Other: _____

Duration _____ hrs _____ hrs 0.5 hrs _____ hrs _____ hrs _____ hrs

DISINFECTION ON COMPLETION

9

Chemical(s) used	Quantity applied (Litres)	Method of application

PUMPING TESTS ON COMPLETION

10

Test type	Date	Pump intake depth (m)	Initial Water Level (SWL) (m)	Pumping rate (L/s)	Water Level at end of pumping (DDL) (m)	Duration of Test (hrs)	Recovery	
							Water level (m)	Time taken (hrs) (mins)
Multi stage (stepped drawdown)	Stage 1							
	Stage 2							
	Stage 3							
	Stage 4							
Single stage (constant rate)								
Height of measuring point above ground level			m	Test Method			See Code 4	

WORK PARTLY BACKFILLED OR ABANDONED

11

Original depth of work: _____ m Is work partly backfilled: (Yes/No)

Is work abandoned: (Yes/No) Method of abandonment: Backfilled Plugged Capped

Has any casing been left in the work (Yes/No) From _____ m To _____ m

Sealing / fill type	From depth (m)	To depth (m)	Sealing / fill type	From depth (m)	To depth (m)
See Code 11			See Code 11		

Site chosen by: Hydrogeologist Geologist Driller Diviner Client Other _____ **12**

Lot No _____ DP No _____ **13**

Work Location Co ordinates Easting 627690 Northing 6038072 Zone 55

GPS: (Yes/No) >> AMG/AGD or MGA/GDA (See explanation)

Please mark the work site with "X" on the CLID provided map.
 Indicate also the distances in metres from two (2) adjacent boundaries, and attach the map to this Form A package.

Signatures:

Driller: _____ Licensee: _____

Date: _____ Date: _____



Driller's Licence No:	DL1913	1
Class of Licence:	Class 4	
Driller's Name:	Ian Palk	
Assistant Driller:	Ashley Wills	
Contractor:	Highland Drilling PL	
New bore	<input checked="" type="checkbox"/>	Replacement bore <input type="checkbox"/>
Deepened	<input type="checkbox"/>	Enlarged <input type="checkbox"/>
Reconditioned	<input type="checkbox"/>	Other (specify) <input type="checkbox"/>
Final Depth	15 m	

Work Licence No:	TMB01A	2
Name of Licensee:	Snowy Mountains Hydro	
Intended Use:	Monitoring Bore	
Completion Date:	22-03-18	

DRILLING DETAILS 3			
From (m)	To (m)	Hole Diameter (mm)	Drilling Method (See Code 3)
0	4	168	16
4	15	140	9

WATER BEARING ZONES 4												
From (m)	To (m)	Thickness (m)	S W L (m)	Estimated Yield (L/s)		Test method (See Code 4)		D D L at end of test (m)	Duration		Salinity (Conductivity or TDS)	
				Individual Aquifer	Cumulative	Hrs	min		Cond (µS/cm)	TDS (mg/L)		
12	13	1	5.07	0.1	0.1	1	A		15	642		
14	15	1		0.1	0.2	1	A		15	650		

CASING / LINER DETAILS 5											
Material (Code 5)	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Method Fixing (Code 5)	Casing support method (See Code 5)		Type of casing bottom (See Code 5)			
9	168	4.8	0	4	6	Centralisers installed {Yes/No}	No	(indicate on sketch)			
8	60.2	5	0	11	5	Sump installed {Yes/No}	Yes	From	14 m	To	15 m
8	60.2	5	14	15	5	Pressure cemented {Yes/No}	No	From		To	
Casing Protector cemented in place											

WATER ENTRY DESIGN 6										
General							Screen	Slot Details		
Material (Code 5)	OD (mm)	Wall Thickness (mm)	From (m)	To (m)	Opening type (See Code 6)	Fixing (See Code 5)	Aperture (mm)	Length (mm)	Width (mm)	Alignment (See Code 6)
8	60.2	5	11	14	5	5	0.4	20	10	H

GRAVEL PACK 7									
Type	Grade	Grain size (mm)		Depth (m)		Quantity			
		From	To	From	To	Litres	m ³		
Rounded	X	Graded	X	3	5	6	15		
Crushed		Ungraded							
Bentonite/Grout seal (Yes/No)		Yes				3	6		
Method of placement of Gravel Pack				See Code 7		1			

For Departmental use only: **GW**

Appendix D

Water quality laboratory certificates

CERTIFICATE OF ANALYSIS

Work Order : **ES1805343**
Client : **EMM CONSULTING PTY LTD**
Contact : MR SEAN CASSIDY
Address : Ground Floor Suite 1 20 Chandos Street
 St Leonards NSW NSW 2065
Telephone : +61 02 9493 9500
Project : J17188 Snowy Hydro 2.0
Order number : ----
C-O-C number : ----
Sampler : IMOGEN FRAWLEY, SEAN CASSIDY
Site : ----
Quote number : SY/068/18
No. of samples received : 16
No. of samples analysed : 16

Page : 1 of 14
Laboratory : Environmental Division Sydney
Contact : Customer Services ES
Address : 277-289 Woodpark Road Smithfield NSW Australia 2164
Telephone : +61-2-8784 8555
Date Samples Received : 20-Feb-2018 09:00
Date Analysis Commenced : 20-Feb-2018
Issue Date : 26-Feb-2018 17:36



This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results
- Surrogate Control Limits

Additional information pertinent to this report will be found in the following separate attachments: Quality Control Report, QA/QC Compliance Assessment to assist with Quality Review and Sample Receipt Notification.

Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

<i>Signatories</i>	<i>Position</i>	<i>Accreditation Category</i>
Ankit Joshi	Inorganic Chemist	Sydney Inorganics, Smithfield, NSW
Celine Conceicao	Senior Spectroscopist	Sydney Inorganics, Smithfield, NSW
Edwandy Fadjar	Organic Coordinator	Sydney Organics, Smithfield, NSW
Ivan Taylor	Analyst	Sydney Inorganics, Smithfield, NSW
Sanjeshni Jyoti	Senior Chemist Volatiles	Sydney Organics, Smithfield, NSW



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key : CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.
LOR = Limit of reporting
^ = This result is computed from individual analyte detections at or above the level of reporting
ø = ALS is not NATA accredited for these tests.
~ = Indicates an estimated value.

- EK057G: LOR raised for Nitrite on sample 1 due to sample matrix.
- TDS by method EA-015 may bias high for various samples due to the presence of fine particulate matter, which may pass through the prescribed GF/C paper.
- TDS by method EA-015 may bias high for sample 4 due to the presence of fine particulate matter, which may pass through the prescribed GF/C paper.
- Benzo(a)pyrene Toxicity Equivalent Quotient (TEQ) is the sum total of the concentration of the eight carcinogenic PAHs multiplied by their Toxicity Equivalence Factor (TEF) relative to Benzo(a)pyrene. TEF values are provided in brackets as follows: Benz(a)anthracene (0.1), Chrysene (0.01), Benzo(b+j) & Benzo(k)fluoranthene (0.1), Benzo(a)pyrene (1.0), Indeno(1.2.3.cd)pyrene (0.1), Dibenz(a.h)anthracene (1.0), Benzo(g.h.i)perylene (0.01). Less than LOR results for 'TEQ Zero' are treated as zero.



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	MB04B	MB04A	MB03	MB01B	SW08
Client sampling date / time				14-Feb-2018 14:15	14-Feb-2018 00:00	13-Feb-2018 16:10	13-Feb-2018 00:00	14-Feb-2018 14:20	
Compound	CAS Number	LOR	Unit	ES1805343-001	ES1805343-002	ES1805343-003	ES1805343-004	ES1805343-005	
				Result	Result	Result	Result	Result	
EA015: Total Dissolved Solids dried at 180 ± 5 °C									
Total Dissolved Solids @180°C	----	10	mg/L	----	----	136	----	----	
Total Dissolved Solids @180°C	----	10	mg/L	1090	176	----	274	103	
EA025: Total Suspended Solids dried at 104 ± 2°C									
Suspended Solids (SS)	----	5	mg/L	----	----	----	----	<5	
ED037P: Alkalinity by PC Titrator									
Hydroxide Alkalinity as CaCO3	DMO-210-001	1	mg/L	<1	<1	<1	<1	<1	
Carbonate Alkalinity as CaCO3	3812-32-6	1	mg/L	<1	<1	<1	<1	<1	
Bicarbonate Alkalinity as CaCO3	71-52-3	1	mg/L	130	57	81	67	86	
Total Alkalinity as CaCO3	----	1	mg/L	130	57	81	67	86	
ED041G: Sulfate (Turbidimetric) as SO4 2- by DA									
Sulfate as SO4 - Turbidimetric	14808-79-8	1	mg/L	84	43	12	5	<1	
ED045G: Chloride by Discrete Analyser									
Chloride	16887-00-6	1	mg/L	53	6	7	1	<1	
ED093F: Dissolved Major Cations									
Calcium	7440-70-2	1	mg/L	12	26	17	11	25	
Magnesium	7439-95-4	1	mg/L	1	2	5	6	2	
Sodium	7440-23-5	1	mg/L	114	14	7	5	3	
Potassium	7440-09-7	1	mg/L	2	1	9	<1	<1	
EG020F: Dissolved Metals by ICP-MS									
Arsenic	7440-38-2	0.001	mg/L	0.002	0.001	<0.001	<0.001	----	
Cadmium	7440-43-9	0.0001	mg/L	<0.0001	<0.0001	<0.0001	<0.0001	----	
Chromium	7440-47-3	0.001	mg/L	<0.001	<0.001	<0.001	<0.001	----	
Copper	7440-50-8	0.001	mg/L	0.002	0.007	0.004	0.006	----	
Nickel	7440-02-0	0.001	mg/L	<0.001	<0.001	<0.001	<0.001	----	
Lead	7439-92-1	0.001	mg/L	<0.001	<0.001	<0.001	<0.001	----	
Zinc	7440-66-6	0.005	mg/L	0.006	<0.005	0.020	<0.005	----	
EG020T: Total Metals by ICP-MS									
Arsenic	7440-38-2	0.001	mg/L	----	----	----	----	<0.001	
Cadmium	7440-43-9	0.0001	mg/L	----	----	----	----	<0.0001	
Chromium	7440-47-3	0.001	mg/L	----	----	----	----	<0.001	
Copper	7440-50-8	0.001	mg/L	----	----	----	----	<0.001	
Nickel	7440-02-0	0.001	mg/L	----	----	----	----	<0.001	
Lead	7439-92-1	0.001	mg/L	----	----	----	----	<0.001	
Zinc	7440-66-6	0.005	mg/L	----	----	----	----	<0.005	



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	MB04B	MB04A	MB03	MB01B	SW08
Client sampling date / time				14-Feb-2018 14:15	14-Feb-2018 00:00	13-Feb-2018 16:10	13-Feb-2018 00:00	14-Feb-2018 14:20	
Compound	CAS Number	LOR	Unit	ES1805343-001	ES1805343-002	ES1805343-003	ES1805343-004	ES1805343-005	
				Result	Result	Result	Result	Result	
EG035F: Dissolved Mercury by FIMS									
Mercury	7439-97-6	0.0001	mg/L	<0.0001	<0.0001	0.0011	<0.0001	----	
EG035T: Total Recoverable Mercury by FIMS									
Mercury	7439-97-6	0.0001	mg/L	----	----	----	----	<0.0001	
EK040P: Fluoride by PC Titrator									
Fluoride	16984-48-8	0.1	mg/L	0.5	0.4	<0.1	<0.1	<0.1	
EK055G: Ammonia as N by Discrete Analyser									
Ammonia as N	7664-41-7	0.01	mg/L	0.02	0.02	<0.01	0.03	<0.01	
EK057G: Nitrite as N by Discrete Analyser									
Nitrite as N	14797-65-0	0.01	mg/L	<0.10	<0.01	<0.01	<0.01	<0.01	
EK058G: Nitrate as N by Discrete Analyser									
Nitrate as N	14797-55-8	0.01	mg/L	0.66	0.38	0.26	0.05	0.04	
EK059G: Nitrite plus Nitrate as N (NOx) by Discrete Analyser									
Nitrite + Nitrate as N	----	0.01	mg/L	0.66	0.38	0.26	0.05	0.04	
EK061G: Total Kjeldahl Nitrogen By Discrete Analyser									
Total Kjeldahl Nitrogen as N	----	0.1	mg/L	0.9	0.5	0.2	0.8	<0.1	
EK062G: Total Nitrogen as N (TKN + NOx) by Discrete Analyser									
^ Total Nitrogen as N	----	0.1	mg/L	1.6	0.9	0.5	0.8	<0.1	
EK067G: Total Phosphorus as P by Discrete Analyser									
Total Phosphorus as P	----	0.01	mg/L	0.19	0.29	1.02	31.9	0.02	
EN055: Ionic Balance									
Total Anions	----	0.01	meq/L	5.84	2.20	2.06	1.47	1.72	
Total Cations	----	0.01	meq/L	5.69	2.10	1.79	1.26	1.54	
Ionic Balance	----	0.01	%	1.30	----	----	----	----	



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	SW07	SW05	SW04	SW06	TMB03A
Client sampling date / time				14-Feb-2018 16:00	14-Feb-2018 14:50	14-Feb-2018 10:20	13-Feb-2018 17:00	15-Feb-2018 00:00	
Compound	CAS Number	LOR	Unit	ES1805343-006	ES1805343-007	ES1805343-008	ES1805343-009	ES1805343-010	
				Result	Result	Result	Result	Result	
EA015: Total Dissolved Solids dried at 180 ± 5 °C									
Total Dissolved Solids @180°C	----	10	mg/L	----	----	----	51	----	
Total Dissolved Solids @180°C	----	10	mg/L	71	21	25	----	84	
EA025: Total Suspended Solids dried at 104 ± 2°C									
Suspended Solids (SS)	----	5	mg/L	----	----	----	<5	----	
Suspended Solids (SS)	----	5	mg/L	<5	<5	<5	----	----	
ED037P: Alkalinity by PC Titrator									
Hydroxide Alkalinity as CaCO3	DMO-210-001	1	mg/L	<1	<1	<1	<1	<1	
Carbonate Alkalinity as CaCO3	3812-32-6	1	mg/L	<1	<1	<1	<1	<1	
Bicarbonate Alkalinity as CaCO3	71-52-3	1	mg/L	68	15	17	29	43	
Total Alkalinity as CaCO3	----	1	mg/L	68	15	17	29	43	
ED041G: Sulfate (Turbidimetric) as SO4 2- by DA									
Sulfate as SO4 - Turbidimetric	14808-79-8	1	mg/L	4	<1	<1	<1	6	
ED045G: Chloride by Discrete Analyser									
Chloride	16887-00-6	1	mg/L	<1	<1	<1	<1	6	
ED093F: Dissolved Major Cations									
Calcium	7440-70-2	1	mg/L	20	1	3	5	8	
Magnesium	7439-95-4	1	mg/L	3	<1	1	1	3	
Sodium	7440-23-5	1	mg/L	4	1	2	4	6	
Potassium	7440-09-7	1	mg/L	<1	<1	<1	<1	1	
EG020F: Dissolved Metals by ICP-MS									
Arsenic	7440-38-2	0.001	mg/L	----	----	----	----	0.001	
Cadmium	7440-43-9	0.0001	mg/L	----	----	----	----	<0.0001	
Chromium	7440-47-3	0.001	mg/L	----	----	----	----	<0.001	
Copper	7440-50-8	0.001	mg/L	----	----	----	----	0.006	
Nickel	7440-02-0	0.001	mg/L	----	----	----	----	0.001	
Lead	7439-92-1	0.001	mg/L	----	----	----	----	<0.001	
Zinc	7440-66-6	0.005	mg/L	----	----	----	----	0.025	
EG020T: Total Metals by ICP-MS									
Arsenic	7440-38-2	0.001	mg/L	<0.001	<0.001	<0.001	<0.001	----	
Cadmium	7440-43-9	0.0001	mg/L	<0.0001	<0.0001	<0.0001	<0.0001	----	
Chromium	7440-47-3	0.001	mg/L	<0.001	<0.001	<0.001	<0.001	----	
Copper	7440-50-8	0.001	mg/L	<0.001	<0.001	<0.001	<0.001	----	
Nickel	7440-02-0	0.001	mg/L	<0.001	<0.001	<0.001	<0.001	----	
Lead	7439-92-1	0.001	mg/L	<0.001	<0.001	<0.001	<0.001	----	



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	SW07	SW05	SW04	SW06	TMB03A
Client sampling date / time				14-Feb-2018 16:00	14-Feb-2018 14:50	14-Feb-2018 10:20	13-Feb-2018 17:00	15-Feb-2018 00:00	
Compound	CAS Number	LOR	Unit	ES1805343-006	ES1805343-007	ES1805343-008	ES1805343-009	ES1805343-010	
				Result	Result	Result	Result	Result	
EG020T: Total Metals by ICP-MS - Continued									
Zinc	7440-66-6	0.005	mg/L	<0.005	<0.005	<0.005	<0.005	----	
EG035F: Dissolved Mercury by FIMS									
Mercury	7439-97-6	0.0001	mg/L	----	----	----	----	<0.0001	
EG035T: Total Recoverable Mercury by FIMS									
Mercury	7439-97-6	0.0001	mg/L	<0.0001	<0.0001	<0.0001	<0.0001	----	
EK040P: Fluoride by PC Titrator									
Fluoride	16984-48-8	0.1	mg/L	0.6	<0.1	<0.1	<0.1	0.1	
EK055G: Ammonia as N by Discrete Analyser									
Ammonia as N	7664-41-7	0.01	mg/L	<0.01	<0.01	<0.01	<0.01	0.02	
EK057G: Nitrite as N by Discrete Analyser									
Nitrite as N	14797-65-0	0.01	mg/L	<0.01	<0.01	<0.01	<0.01	<0.01	
EK058G: Nitrate as N by Discrete Analyser									
Nitrate as N	14797-55-8	0.01	mg/L	1.92	0.02	0.31	0.03	0.01	
EK059G: Nitrite plus Nitrate as N (NOx) by Discrete Analyser									
Nitrite + Nitrate as N	----	0.01	mg/L	1.92	0.02	0.31	0.03	0.01	
EK061G: Total Kjeldahl Nitrogen By Discrete Analyser									
Total Kjeldahl Nitrogen as N	----	0.1	mg/L	<0.1	0.1	<0.1	<0.1	0.2	
EK062G: Total Nitrogen as N (TKN + NOx) by Discrete Analyser									
^ Total Nitrogen as N	----	0.1	mg/L	1.9	0.1	0.3	<0.1	0.2	
EK067G: Total Phosphorus as P by Discrete Analyser									
Total Phosphorus as P	----	0.01	mg/L	<0.01	<0.01	<0.01	<0.01	0.09	
EN055: Ionic Balance									
Total Anions	----	0.01	meq/L	1.44	0.30	0.34	0.58	1.15	
Total Cations	----	0.01	meq/L	1.42	0.09	0.32	0.50	0.93	



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	TMB03B	MB02	SW02	SW01	QA1
Client sampling date / time				15-Feb-2018 00:00	15-Feb-2018 00:00	15-Feb-2018 00:00	16-Feb-2018 00:00	16-Feb-2018 00:00	
Compound	CAS Number	LOR	Unit	ES1805343-011	ES1805343-012	ES1805343-013	ES1805343-014	ES1805343-015	
				Result	Result	Result	Result	Result	
EA015: Total Dissolved Solids dried at 180 ± 5 °C									
Total Dissolved Solids @180°C	----	10	mg/L	97	68	40	54	43	
EA025: Total Suspended Solids dried at 104 ± 2°C									
Suspended Solids (SS)	----	5	mg/L	----	----	16	7	<5	
ED037P: Alkalinity by PC Titrator									
Hydroxide Alkalinity as CaCO3	DMO-210-001	1	mg/L	<1	<1	<1	<1	<1	
Carbonate Alkalinity as CaCO3	3812-32-6	1	mg/L	<1	<1	<1	<1	<1	
Bicarbonate Alkalinity as CaCO3	71-52-3	1	mg/L	75	45	26	31	33	
Total Alkalinity as CaCO3	----	1	mg/L	75	45	26	31	33	
ED041G: Sulfate (Turbidimetric) as SO4 2- by DA									
Sulfate as SO4 - Turbidimetric	14808-79-8	1	mg/L	11	14	<1	<1	<1	
ED045G: Chloride by Discrete Analyser									
Chloride	16887-00-6	1	mg/L	4	<1	1	<1	<1	
ED093F: Dissolved Major Cations									
Calcium	7440-70-2	1	mg/L	20	17	5	5	5	
Magnesium	7439-95-4	1	mg/L	2	2	3	3	3	
Sodium	7440-23-5	1	mg/L	8	2	<1	11	2	
Potassium	7440-09-7	1	mg/L	4	<1	<1	<1	<1	
EG020F: Dissolved Metals by ICP-MS									
Arsenic	7440-38-2	0.001	mg/L	0.015	<0.001	----	----	<0.001	
Cadmium	7440-43-9	0.0001	mg/L	<0.0001	<0.0001	----	----	<0.0001	
Chromium	7440-47-3	0.001	mg/L	<0.001	<0.001	----	----	<0.001	
Copper	7440-50-8	0.001	mg/L	0.006	0.002	----	----	<0.001	
Nickel	7440-02-0	0.001	mg/L	<0.001	<0.001	----	----	<0.001	
Lead	7439-92-1	0.001	mg/L	<0.001	<0.001	----	----	<0.001	
Zinc	7440-66-6	0.005	mg/L	0.015	0.049	----	----	<0.005	
EG020T: Total Metals by ICP-MS									
Arsenic	7440-38-2	0.001	mg/L	----	----	<0.001	<0.001	----	
Cadmium	7440-43-9	0.0001	mg/L	----	----	<0.0001	<0.0001	----	
Chromium	7440-47-3	0.001	mg/L	----	----	<0.001	<0.001	----	
Copper	7440-50-8	0.001	mg/L	----	----	<0.001	<0.001	----	
Nickel	7440-02-0	0.001	mg/L	----	----	0.002	<0.001	----	
Lead	7439-92-1	0.001	mg/L	----	----	<0.001	<0.001	----	
Zinc	7440-66-6	0.005	mg/L	----	----	<0.005	0.005	----	
EG035F: Dissolved Mercury by FIMS									



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	TMB03B	MB02	SW02	SW01	QA1
Client sampling date / time				15-Feb-2018 00:00	15-Feb-2018 00:00	15-Feb-2018 00:00	16-Feb-2018 00:00	16-Feb-2018 00:00	
Compound	CAS Number	LOR	Unit	ES1805343-011	ES1805343-012	ES1805343-013	ES1805343-014	ES1805343-015	
				Result	Result	Result	Result	Result	
EG035F: Dissolved Mercury by FIMS - Continued									
Mercury	7439-97-6	0.0001	mg/L	<0.0001	<0.0001	----	----	<0.0001	
EG035T: Total Recoverable Mercury by FIMS									
Mercury	7439-97-6	0.0001	mg/L	----	----	<0.0001	<0.0001	----	
EK040P: Fluoride by PC Titrator									
Fluoride	16984-48-8	0.1	mg/L	0.6	<0.1	<0.1	<0.1	<0.1	
EK055G: Ammonia as N by Discrete Analyser									
Ammonia as N	7664-41-7	0.01	mg/L	0.02	<0.01	0.01	<0.01	<0.01	
EK057G: Nitrite as N by Discrete Analyser									
Nitrite as N	14797-65-0	0.01	mg/L	<0.01	<0.01	<0.01	<0.01	<0.01	
EK058G: Nitrate as N by Discrete Analyser									
Nitrate as N	14797-55-8	0.01	mg/L	0.03	0.08	0.03	0.04	0.05	
EK059G: Nitrite plus Nitrate as N (NOx) by Discrete Analyser									
Nitrite + Nitrate as N	----	0.01	mg/L	0.03	0.08	0.03	0.04	0.05	
EK061G: Total Kjeldahl Nitrogen By Discrete Analyser									
Total Kjeldahl Nitrogen as N	----	0.1	mg/L	0.7	0.2	0.3	0.1	0.1	
EK062G: Total Nitrogen as N (TKN + NOx) by Discrete Analyser									
^ Total Nitrogen as N	----	0.1	mg/L	0.7	0.3	0.3	0.1	0.2	
EK067G: Total Phosphorus as P by Discrete Analyser									
Total Phosphorus as P	----	0.01	mg/L	0.10	0.05	0.05	0.01	0.01	
EN055: Ionic Balance									
Total Anions	----	0.01	meq/L	1.84	1.19	0.55	0.62	0.66	
Total Cations	----	0.01	meq/L	1.61	1.10	0.50	0.97	0.58	
EP075(SIM)B: Polynuclear Aromatic Hydrocarbons									
Naphthalene	91-20-3	1.0	µg/L	----	----	----	----	<1.0	
Acenaphthylene	208-96-8	1.0	µg/L	----	----	----	----	<1.0	
Acenaphthene	83-32-9	1.0	µg/L	----	----	----	----	<1.0	
Fluorene	86-73-7	1.0	µg/L	----	----	----	----	<1.0	
Phenanthrene	85-01-8	1.0	µg/L	----	----	----	----	<1.0	
Anthracene	120-12-7	1.0	µg/L	----	----	----	----	<1.0	
Fluoranthene	206-44-0	1.0	µg/L	----	----	----	----	<1.0	
Pyrene	129-00-0	1.0	µg/L	----	----	----	----	<1.0	
Benzo(a)anthracene	56-55-3	1.0	µg/L	----	----	----	----	<1.0	
Chrysene	218-01-9	1.0	µg/L	----	----	----	----	<1.0	



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	TMB03B	MB02	SW02	SW01	QA1
Client sampling date / time				15-Feb-2018 00:00	15-Feb-2018 00:00	15-Feb-2018 00:00	16-Feb-2018 00:00	16-Feb-2018 00:00	
Compound	CAS Number	LOR	Unit	ES1805343-011	ES1805343-012	ES1805343-013	ES1805343-014	ES1805343-015	
				Result	Result	Result	Result	Result	
EP075(SIM)B: Polynuclear Aromatic Hydrocarbons - Continued									
Benzo(b+j)fluoranthene	205-99-2 205-82-3	1.0	µg/L	----	----	----	----	<1.0	
Benzo(k)fluoranthene	207-08-9	1.0	µg/L	----	----	----	----	<1.0	
Benzo(a)pyrene	50-32-8	0.5	µg/L	----	----	----	----	<0.5	
Indeno(1.2.3.cd)pyrene	193-39-5	1.0	µg/L	----	----	----	----	<1.0	
Dibenz(a.h)anthracene	53-70-3	1.0	µg/L	----	----	----	----	<1.0	
Benzo(g.h.i)perylene	191-24-2	1.0	µg/L	----	----	----	----	<1.0	
^ Sum of polycyclic aromatic hydrocarbons	----	0.5	µg/L	----	----	----	----	<0.5	
^ Benzo(a)pyrene TEQ (zero)	----	0.5	µg/L	----	----	----	----	<0.5	
EP080/071: Total Petroleum Hydrocarbons									
C6 - C9 Fraction	----	20	µg/L	----	----	----	----	<20	
C10 - C14 Fraction	----	50	µg/L	----	----	----	----	<50	
C15 - C28 Fraction	----	100	µg/L	----	----	----	----	<100	
C29 - C36 Fraction	----	50	µg/L	----	----	----	----	<50	
^ C10 - C36 Fraction (sum)	----	50	µg/L	----	----	----	----	<50	
EP080/071: Total Recoverable Hydrocarbons - NEPM 2013 Fractions									
C6 - C10 Fraction	C6_C10	20	µg/L	----	----	----	----	<20	
^ C6 - C10 Fraction minus BTEX (F1)	C6_C10-BTEX	20	µg/L	----	----	----	----	<20	
>C10 - C16 Fraction	----	100	µg/L	----	----	----	----	<100	
>C16 - C34 Fraction	----	100	µg/L	----	----	----	----	<100	
>C34 - C40 Fraction	----	100	µg/L	----	----	----	----	<100	
^ >C10 - C40 Fraction (sum)	----	100	µg/L	----	----	----	----	<100	
^ >C10 - C16 Fraction minus Naphthalene (F2)	----	100	µg/L	----	----	----	----	<100	
EP080: BTEXN									
Benzene	71-43-2	1	µg/L	----	----	----	----	<1	
Toluene	108-88-3	2	µg/L	----	----	----	----	<2	
Ethylbenzene	100-41-4	2	µg/L	----	----	----	----	<2	
meta- & para-Xylene	108-38-3 106-42-3	2	µg/L	----	----	----	----	<2	
ortho-Xylene	95-47-6	2	µg/L	----	----	----	----	<2	
^ Total Xylenes	----	2	µg/L	----	----	----	----	<2	
^ Sum of BTEX	----	1	µg/L	----	----	----	----	<1	
Naphthalene	91-20-3	5	µg/L	----	----	----	----	<5	
EP075(SIM)S: Phenolic Compound Surrogates									



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	TMB03B	MB02	SW02	SW01	QA1
Client sampling date / time				15-Feb-2018 00:00	15-Feb-2018 00:00	15-Feb-2018 00:00	16-Feb-2018 00:00	16-Feb-2018 00:00	
Compound	CAS Number	LOR	Unit	ES1805343-011	ES1805343-012	ES1805343-013	ES1805343-014	ES1805343-015	
				Result	Result	Result	Result	Result	
EP075(SIM)S: Phenolic Compound Surrogates - Continued									
Phenol-d6	13127-88-3	1.0	%	----	----	----	----	31.1	
2-Chlorophenol-D4	93951-73-6	1.0	%	----	----	----	----	68.0	
2.4.6-Tribromophenol	118-79-6	1.0	%	----	----	----	----	59.6	
EP075(SIM)T: PAH Surrogates									
2-Fluorobiphenyl	321-60-8	1.0	%	----	----	----	----	82.4	
Anthracene-d10	1719-06-8	1.0	%	----	----	----	----	102	
4-Terphenyl-d14	1718-51-0	1.0	%	----	----	----	----	99.0	
EP080S: TPH(V)/BTEX Surrogates									
1.2-Dichloroethane-D4	17060-07-0	2	%	----	----	----	----	107	
Toluene-D8	2037-26-5	2	%	----	----	----	----	109	
4-Bromofluorobenzene	460-00-4	2	%	----	----	----	----	105	



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)		Client sample ID			QA2	----	----	----	----
Client sampling date / time		16-Feb-2018 00:00			----	----	----	----	----
Compound	CAS Number	LOR	Unit	ES1805343-016	-----	-----	-----	-----	-----
				Result	----	----	----	----	----
EA015: Total Dissolved Solids dried at 180 ± 5 °C									
Total Dissolved Solids @180°C	----	10	mg/L	53	----	----	----	----	----
EA025: Total Suspended Solids dried at 104 ± 2°C									
Suspended Solids (SS)	----	5	mg/L	<5	----	----	----	----	----
ED037P: Alkalinity by PC Titrator									
Hydroxide Alkalinity as CaCO3	DMO-210-001	1	mg/L	<1	----	----	----	----	----
Carbonate Alkalinity as CaCO3	3812-32-6	1	mg/L	<1	----	----	----	----	----
Bicarbonate Alkalinity as CaCO3	71-52-3	1	mg/L	33	----	----	----	----	----
Total Alkalinity as CaCO3	----	1	mg/L	33	----	----	----	----	----
ED041G: Sulfate (Turbidimetric) as SO4 2- by DA									
Sulfate as SO4 - Turbidimetric	14808-79-8	1	mg/L	<1	----	----	----	----	----
ED045G: Chloride by Discrete Analyser									
Chloride	16887-00-6	1	mg/L	<1	----	----	----	----	----
ED093F: Dissolved Major Cations									
Calcium	7440-70-2	1	mg/L	5	----	----	----	----	----
Magnesium	7439-95-4	1	mg/L	3	----	----	----	----	----
Sodium	7440-23-5	1	mg/L	2	----	----	----	----	----
Potassium	7440-09-7	1	mg/L	<1	----	----	----	----	----
EG020F: Dissolved Metals by ICP-MS									
Arsenic	7440-38-2	0.001	mg/L	<0.001	----	----	----	----	----
Cadmium	7440-43-9	0.0001	mg/L	<0.0001	----	----	----	----	----
Chromium	7440-47-3	0.001	mg/L	<0.001	----	----	----	----	----
Copper	7440-50-8	0.001	mg/L	<0.001	----	----	----	----	----
Nickel	7440-02-0	0.001	mg/L	<0.001	----	----	----	----	----
Lead	7439-92-1	0.001	mg/L	<0.001	----	----	----	----	----
Zinc	7440-66-6	0.005	mg/L	<0.005	----	----	----	----	----
EG035F: Dissolved Mercury by FIMS									
Mercury	7439-97-6	0.0001	mg/L	<0.0001	----	----	----	----	----
EK040P: Fluoride by PC Titrator									
Fluoride	16984-48-8	0.1	mg/L	<0.1	----	----	----	----	----
EK055G: Ammonia as N by Discrete Analyser									
Ammonia as N	7664-41-7	0.01	mg/L	<0.01	----	----	----	----	----
EK057G: Nitrite as N by Discrete Analyser									
Nitrite as N	14797-65-0	0.01	mg/L	<0.01	----	----	----	----	----



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)		Client sample ID			QA2	----	----	----	----
Client sampling date / time		16-Feb-2018 00:00			----	----	----	----	----
Compound	CAS Number	LOR	Unit	ES1805343-016	-----	-----	-----	-----	-----
				Result	----	----	----	----	----
EK058G: Nitrate as N by Discrete Analyser									
Nitrate as N	14797-55-8	0.01	mg/L	0.04	----	----	----	----	----
EK059G: Nitrite plus Nitrate as N (NOx) by Discrete Analyser									
Nitrite + Nitrate as N	----	0.01	mg/L	0.04	----	----	----	----	----
EK061G: Total Kjeldahl Nitrogen By Discrete Analyser									
Total Kjeldahl Nitrogen as N	----	0.1	mg/L	0.1	----	----	----	----	----
EK062G: Total Nitrogen as N (TKN + NOx) by Discrete Analyser									
^ Total Nitrogen as N	----	0.1	mg/L	0.1	----	----	----	----	----
EK067G: Total Phosphorus as P by Discrete Analyser									
Total Phosphorus as P	----	0.01	mg/L	0.02	----	----	----	----	----
EN055: Ionic Balance									
Total Anions	----	0.01	meq/L	0.66	----	----	----	----	----
Total Cations	----	0.01	meq/L	0.58	----	----	----	----	----
EP075(SIM)B: Polynuclear Aromatic Hydrocarbons									
Naphthalene	91-20-3	1.0	µg/L	<1.0	----	----	----	----	----
Acenaphthylene	208-96-8	1.0	µg/L	<1.0	----	----	----	----	----
Acenaphthene	83-32-9	1.0	µg/L	<1.0	----	----	----	----	----
Fluorene	86-73-7	1.0	µg/L	<1.0	----	----	----	----	----
Phenanthrene	85-01-8	1.0	µg/L	<1.0	----	----	----	----	----
Anthracene	120-12-7	1.0	µg/L	<1.0	----	----	----	----	----
Fluoranthene	206-44-0	1.0	µg/L	<1.0	----	----	----	----	----
Pyrene	129-00-0	1.0	µg/L	<1.0	----	----	----	----	----
Benz(a)anthracene	56-55-3	1.0	µg/L	<1.0	----	----	----	----	----
Chrysene	218-01-9	1.0	µg/L	<1.0	----	----	----	----	----
Benzo(b+)fluoranthene	205-99-2 205-82-3	1.0	µg/L	<1.0	----	----	----	----	----
Benzo(k)fluoranthene	207-08-9	1.0	µg/L	<1.0	----	----	----	----	----
Benzo(a)pyrene	50-32-8	0.5	µg/L	<0.5	----	----	----	----	----
Indeno(1.2.3.cd)pyrene	193-39-5	1.0	µg/L	<1.0	----	----	----	----	----
Dibenz(a.h)anthracene	53-70-3	1.0	µg/L	<1.0	----	----	----	----	----
Benzo(g.h.i)perylene	191-24-2	1.0	µg/L	<1.0	----	----	----	----	----
^ Sum of polycyclic aromatic hydrocarbons	----	0.5	µg/L	<0.5	----	----	----	----	----
^ Benzo(a)pyrene TEQ (zero)	----	0.5	µg/L	<0.5	----	----	----	----	----
EP080/071: Total Petroleum Hydrocarbons									
C6 - C9 Fraction	----	20	µg/L	<20	----	----	----	----	----
C10 - C14 Fraction	----	50	µg/L	<50	----	----	----	----	----



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	QA2	----	----	----	----
Client sampling date / time				16-Feb-2018 00:00	----	----	----	----	
Compound	CAS Number	LOR	Unit	ES1805343-016	-----	-----	-----	-----	
				Result	----	----	----	----	
EP080/071: Total Petroleum Hydrocarbons - Continued									
C15 - C28 Fraction	----	100	µg/L	<100	----	----	----	----	
C29 - C36 Fraction	----	50	µg/L	<50	----	----	----	----	
^ C10 - C36 Fraction (sum)	----	50	µg/L	<50	----	----	----	----	
EP080/071: Total Recoverable Hydrocarbons - NEPM 2013 Fractions									
C6 - C10 Fraction	C6_C10	20	µg/L	<20	----	----	----	----	
^ C6 - C10 Fraction minus BTEX (F1)	C6_C10-BTEX	20	µg/L	<20	----	----	----	----	
>C10 - C16 Fraction	----	100	µg/L	<100	----	----	----	----	
>C16 - C34 Fraction	----	100	µg/L	<100	----	----	----	----	
>C34 - C40 Fraction	----	100	µg/L	<100	----	----	----	----	
^ >C10 - C40 Fraction (sum)	----	100	µg/L	<100	----	----	----	----	
^ >C10 - C16 Fraction minus Naphthalene (F2)	----	100	µg/L	<100	----	----	----	----	
EP080: BTEXN									
Benzene	71-43-2	1	µg/L	<1	----	----	----	----	
Toluene	108-88-3	2	µg/L	<2	----	----	----	----	
Ethylbenzene	100-41-4	2	µg/L	<2	----	----	----	----	
meta- & para-Xylene	108-38-3 106-42-3	2	µg/L	<2	----	----	----	----	
ortho-Xylene	95-47-6	2	µg/L	<2	----	----	----	----	
^ Total Xylenes	----	2	µg/L	<2	----	----	----	----	
^ Sum of BTEX	----	1	µg/L	<1	----	----	----	----	
Naphthalene	91-20-3	5	µg/L	<5	----	----	----	----	
EP075(SIM)S: Phenolic Compound Surrogates									
Phenol-d6	13127-88-3	1.0	%	29.7	----	----	----	----	
2-Chlorophenol-D4	93951-73-6	1.0	%	64.1	----	----	----	----	
2,4,6-Tribromophenol	118-79-6	1.0	%	58.6	----	----	----	----	
EP075(SIM)T: PAH Surrogates									
2-Fluorobiphenyl	321-60-8	1.0	%	79.2	----	----	----	----	
Anthracene-d10	1719-06-8	1.0	%	102	----	----	----	----	
4-Terphenyl-d14	1718-51-0	1.0	%	101	----	----	----	----	
EP080S: TPH(V)/BTEX Surrogates									
1,2-Dichloroethane-D4	17060-07-0	2	%	99.9	----	----	----	----	
Toluene-D8	2037-26-5	2	%	81.8	----	----	----	----	
4-Bromofluorobenzene	460-00-4	2	%	86.8	----	----	----	----	



Surrogate Control Limits

Sub-Matrix: WATER		Recovery Limits (%)	
Compound	CAS Number	Low	High
EP075(SIM)S: Phenolic Compound Surrogates			
Phenol-d6	13127-88-3	10	44
2-Chlorophenol-D4	93951-73-6	14	94
2,4,6-Tribromophenol	118-79-6	17	125
EP075(SIM)T: PAH Surrogates			
2-Fluorobiphenyl	321-60-8	20	104
Anthracene-d10	1719-06-8	27	113
4-Terphenyl-d14	1718-51-0	32	112
EP080S: TPH(V)/BTEX Surrogates			
1,2-Dichloroethane-D4	17060-07-0	71	137
Toluene-D8	2037-26-5	79	131
4-Bromofluorobenzene	460-00-4	70	128

CERTIFICATE OF ANALYSIS

Work Order	: EM1805147	Page	: 1 of 12
Client	: EMM CONSULTING PTY LTD	Laboratory	: Environmental Division Melbourne
Contact	: MR SEAN CASSIDY	Contact	: Customer Services EM
Address	: 1/4 87 WICKHAM TERRACE SPRING HILL QLD 4000	Address	: 4 Westall Rd Springvale VIC Australia 3171
Telephone	: +61 02 9493 9500	Telephone	: +61-3-8549 9600
Project	: EMM # - J17188	Date Samples Received	: 23-Mar-2018 16:30
Order number	:	Date Analysis Commenced	: 23-Mar-2018
C-O-C number	: ----	Issue Date	: 04-Apr-2018 18:51
Sampler	: DANIEL CONDON (HT)		
Site	: Snowy Mountains		
Quote number	: EN/222/17		
No. of samples received	: 16		
No. of samples analysed	: 15		



This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results
- Surrogate Control Limits

Additional information pertinent to this report will be found in the following separate attachments: Quality Control Report, QA/QC Compliance Assessment to assist with Quality Review and Sample Receipt Notification.

Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

<i>Signatories</i>	<i>Position</i>	<i>Accreditation Category</i>
Dilani Fernando	Senior Inorganic Chemist	Melbourne Inorganics, Springvale, VIC
Nancy Wang	2IC Organic Chemist	Melbourne Organics, Springvale, VIC
Nikki Stepniewski	Senior Inorganic Instrument Chemist	Melbourne Inorganics, Springvale, VIC



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key : CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.
LOR = Limit of reporting
^ = This result is computed from individual analyte detections at or above the level of reporting
ø = ALS is not NATA accredited for these tests.
~ = Indicates an estimated value.

- EA015H: EM1805147 #1, #6-7 and #9 TDS by method EA-015 may bias high due to the presence of fine particulate matter, which may pass through the prescribed GF/C paper.
- EK057G: Results for EM1805147-008 have been confirmed by re-preparation and re-analysis.
- ED093F:EM1805147_006 has been confirmed for major cations by re-preparation and re-analysis.
- TDS by method EA-015 may bias high for EM1805147 #11 and 12 due to the presence of fine particulate matter, which may pass through the prescribed GF/C paper.
- Ionic Balance out of acceptable limits for sample #6 due to analytes not quantified in this report. Major anions and major cations have been confirmed by re-preparation and re-analysis.
- Ionic balances were calculated using: major anions - chloride, alkalinity and sulfate; and major cations - calcium, magnesium, potassium and sodium.
- ED045G: The presence of thiocyanate can positively contribute to the chloride result, thereby may bias results higher than expected. Results should be scrutinised accordingly.
- EK040-P: EM1805146 #13 Poor matrix spike recovery for fluoride due to sample matrix. Confirmed by re-extraction and re-analysis.



Analytical Results

Sub-Matrix: TRIP BLANK (Matrix: WATER)		Client sample ID			TRIP BLANK	----	----	----	----
Client sampling date / time		22-Mar-2018 00:00			----	----	----	----	
Compound	CAS Number	LOR	Unit	EM1805147-015	-----	-----	-----	-----	
				Result	----	----	----	----	
EP074A: Monocyclic Aromatic Hydrocarbons									
Benzene	71-43-2	1	µg/L	<1	----	----	----	----	
Toluene	108-88-3	2	µg/L	<2	----	----	----	----	
Ethylbenzene	100-41-4	2	µg/L	<2	----	----	----	----	
meta- & para-Xylene	108-38-3 106-42-3	2	µg/L	<2	----	----	----	----	
Styrene	100-42-5	5	µg/L	<5	----	----	----	----	
ortho-Xylene	95-47-6	2	µg/L	<2	----	----	----	----	
Isopropylbenzene	98-82-8	5	µg/L	<5	----	----	----	----	
n-Propylbenzene	103-65-1	5	µg/L	<5	----	----	----	----	
1,3,5-Trimethylbenzene	108-67-8	5	µg/L	<5	----	----	----	----	
sec-Butylbenzene	135-98-8	5	µg/L	<5	----	----	----	----	
1,2,4-Trimethylbenzene	95-63-6	5	µg/L	<5	----	----	----	----	
tert-Butylbenzene	98-06-6	5	µg/L	<5	----	----	----	----	
p-Isopropyltoluene	99-87-6	5	µg/L	<5	----	----	----	----	
n-Butylbenzene	104-51-8	5	µg/L	<5	----	----	----	----	
EP074B: Oxygenated Compounds									
Vinyl Acetate	108-05-4	50	µg/L	<50	----	----	----	----	
2-Butanone (MEK)	78-93-3	50	µg/L	<50	----	----	----	----	
4-Methyl-2-pentanone (MIBK)	108-10-1	50	µg/L	<50	----	----	----	----	
2-Hexanone (MBK)	591-78-6	50	µg/L	<50	----	----	----	----	
EP074C: Sulfonated Compounds									
Carbon disulfide	75-15-0	5	µg/L	<5	----	----	----	----	
EP074D: Fumigants									
2,2-Dichloropropane	594-20-7	5	µg/L	<5	----	----	----	----	
1,2-Dichloropropane	78-87-5	5	µg/L	<5	----	----	----	----	
cis-1,3-Dichloropropylene	10061-01-5	5	µg/L	<5	----	----	----	----	
trans-1,3-Dichloropropylene	10061-02-6	5	µg/L	<5	----	----	----	----	
1,2-Dibromoethane (EDB)	106-93-4	5	µg/L	<5	----	----	----	----	
EP074E: Halogenated Aliphatic Compounds									
Dichlorodifluoromethane	75-71-8	50	µg/L	<50	----	----	----	----	
Chloromethane	74-87-3	50	µg/L	<50	----	----	----	----	
Vinyl chloride	75-01-4	50	µg/L	<50	----	----	----	----	
Bromomethane	74-83-9	50	µg/L	<50	----	----	----	----	
Chloroethane	75-00-3	50	µg/L	<50	----	----	----	----	
Trichlorofluoromethane	75-69-4	50	µg/L	<50	----	----	----	----	



Analytical Results

Sub-Matrix: TRIP BLANK (Matrix: WATER)				Client sample ID	TRIP BLANK	----	----	----	----
Client sampling date / time				22-Mar-2018 00:00	----	----	----	----	----
Compound	CAS Number	LOR	Unit	EM1805147-015	-----	-----	-----	-----	-----
				Result	----	----	----	----	----
EP074E: Halogenated Aliphatic Compounds - Continued									
1.1-Dichloroethene	75-35-4	5	µg/L	<5	----	----	----	----	----
Iodomethane	74-88-4	5	µg/L	<5	----	----	----	----	----
trans-1.2-Dichloroethene	156-60-5	5	µg/L	<5	----	----	----	----	----
1.1-Dichloroethane	75-34-3	5	µg/L	<5	----	----	----	----	----
cis-1.2-Dichloroethene	156-59-2	5	µg/L	<5	----	----	----	----	----
1.1.1-Trichloroethane	71-55-6	5	µg/L	<5	----	----	----	----	----
1.1-Dichloropropylene	563-58-6	5	µg/L	<5	----	----	----	----	----
Carbon Tetrachloride	56-23-5	5	µg/L	<5	----	----	----	----	----
1.2-Dichloroethane	107-06-2	5	µg/L	<5	----	----	----	----	----
Trichloroethene	79-01-6	5	µg/L	<5	----	----	----	----	----
Dibromomethane	74-95-3	5	µg/L	<5	----	----	----	----	----
1.1.2-Trichloroethane	79-00-5	5	µg/L	<5	----	----	----	----	----
1.3-Dichloropropane	142-28-9	5	µg/L	<5	----	----	----	----	----
Tetrachloroethene	127-18-4	5	µg/L	<5	----	----	----	----	----
1.1.1.2-Tetrachloroethane	630-20-6	5	µg/L	<5	----	----	----	----	----
trans-1.4-Dichloro-2-butene	110-57-6	5	µg/L	<5	----	----	----	----	----
cis-1.4-Dichloro-2-butene	1476-11-5	5	µg/L	<5	----	----	----	----	----
1.1.2.2-Tetrachloroethane	79-34-5	5	µg/L	<5	----	----	----	----	----
1.2.3-Trichloropropane	96-18-4	5	µg/L	<5	----	----	----	----	----
Pentachloroethane	76-01-7	5	µg/L	<5	----	----	----	----	----
1.2-Dibromo-3-chloropropane	96-12-8	5	µg/L	<5	----	----	----	----	----
Hexachlorobutadiene	87-68-3	5	µg/L	<5	----	----	----	----	----
EP074F: Halogenated Aromatic Compounds									
Chlorobenzene	108-90-7	5	µg/L	<5	----	----	----	----	----
Bromobenzene	108-86-1	5	µg/L	<5	----	----	----	----	----
2-Chlorotoluene	95-49-8	5	µg/L	<5	----	----	----	----	----
4-Chlorotoluene	106-43-4	5	µg/L	<5	----	----	----	----	----
1.3-Dichlorobenzene	541-73-1	5	µg/L	<5	----	----	----	----	----
1.4-Dichlorobenzene	106-46-7	5	µg/L	<5	----	----	----	----	----
1.2-Dichlorobenzene	95-50-1	5	µg/L	<5	----	----	----	----	----
1.2.4-Trichlorobenzene	120-82-1	5	µg/L	<5	----	----	----	----	----
1.2.3-Trichlorobenzene	87-61-6	5	µg/L	<5	----	----	----	----	----
EP074G: Trihalomethanes									
Chloroform	67-66-3	5	µg/L	<5	----	----	----	----	----



Analytical Results

Sub-Matrix: TRIP BLANK (Matrix: WATER)				Client sample ID	TRIP BLANK	----	----	----	----
Client sampling date / time				22-Mar-2018 00:00	----	----	----	----	
Compound	CAS Number	LOR	Unit	EM1805147-015	-----	-----	-----	-----	
				Result	----	----	----	----	
EP074G: Trihalomethanes - Continued									
Bromodichloromethane	75-27-4	5	µg/L	<5	----	----	----	----	
Dibromochloromethane	124-48-1	5	µg/L	<5	----	----	----	----	
Bromoform	75-25-2	5	µg/L	<5	----	----	----	----	
EP074H: Naphthalene									
Naphthalene	91-20-3	5	µg/L	<5	----	----	----	----	
EP074S: VOC Surrogates									
1,2-Dichloroethane-D4	17060-07-0	5	%	107	----	----	----	----	
Toluene-D8	2037-26-5	5	%	107	----	----	----	----	
4-Bromofluorobenzene	460-00-4	5	%	112	----	----	----	----	



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	MB01B	MB01C	MB02	MB03	MB04A
Client sampling date / time				22-Mar-2018 00:00	22-Mar-2018 00:00	20-Mar-2018 00:00	21-Mar-2018 00:00	21-Mar-2018 00:00	
Compound	CAS Number	LOR	Unit	EM1805147-001	EM1805147-002	EM1805147-003	EM1805147-004	EM1805147-005	
				Result	Result	Result	Result	Result	
EA015: Total Dissolved Solids dried at 180 ± 5 °C									
Total Dissolved Solids @180°C	----	10	mg/L	264	127	90	107	210	
ED037P: Alkalinity by PC Titrator									
Hydroxide Alkalinity as CaCO3	DMO-210-001	1	mg/L	<1	<1	<1	<1	<1	
Carbonate Alkalinity as CaCO3	3812-32-6	1	mg/L	<1	<1	<1	<1	<1	
Bicarbonate Alkalinity as CaCO3	71-52-3	1	mg/L	39	81	46	53	61	
Total Alkalinity as CaCO3	----	1	mg/L	39	81	46	53	61	
ED041G: Sulfate (Turbidimetric) as SO4 2- by DA									
Sulfate as SO4 - Turbidimetric	14808-79-8	1	mg/L	<1	13	14	3	78	
ED045G: Chloride by Discrete Analyser									
Chloride	16887-00-6	1	mg/L	1	1	3	1	5	
ED093F: Dissolved Major Cations									
Calcium	7440-70-2	1	mg/L	6	14	15	9	33	
Magnesium	7439-95-4	1	mg/L	3	6	2	4	3	
Sodium	7440-23-5	1	mg/L	6	9	4	4	15	
Potassium	7440-09-7	1	mg/L	<1	1	<1	<1	2	
EG020F: Dissolved Metals by ICP-MS									
Arsenic	7440-38-2	0.001	mg/L	<0.001	0.009	<0.001	<0.001	<0.001	
Cadmium	7440-43-9	0.0001	mg/L	<0.0001	<0.0001	<0.0001	<0.0001	<0.0001	
Chromium	7440-47-3	0.001	mg/L	0.001	<0.001	0.001	0.002	0.002	
Copper	7440-50-8	0.001	mg/L	0.126	<0.001	0.007	0.104	0.088	
Nickel	7440-02-0	0.001	mg/L	0.007	<0.001	0.002	0.003	0.003	
Lead	7439-92-1	0.001	mg/L	0.007	<0.001	0.001	0.005	0.004	
Zinc	7440-66-6	0.005	mg/L	0.148	<0.005	0.029	0.121	0.116	
EG035F: Dissolved Mercury by FIMS									
Mercury	7439-97-6	0.0001	mg/L	<0.0001	<0.0001	<0.0001	<0.0001	<0.0001	
EK040P: Fluoride by PC Titrator									
Fluoride	16984-48-8	0.1	mg/L	<0.1	<0.1	0.1	<0.1	0.4	
EK055G: Ammonia as N by Discrete Analyser									
Ammonia as N	7664-41-7	0.01	mg/L	0.36	0.06	0.16	0.14	0.13	
EK057G: Nitrite as N by Discrete Analyser									
Nitrite as N	14797-65-0	0.01	mg/L	<0.01	<0.01	<0.01	<0.01	0.01	
EK058G: Nitrate as N by Discrete Analyser									
Nitrate as N	14797-55-8	0.01	mg/L	0.02	<0.01	<0.01	0.25	0.66	



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	MB01B	MB01C	MB02	MB03	MB04A
Client sampling date / time				22-Mar-2018 00:00	22-Mar-2018 00:00	20-Mar-2018 00:00	21-Mar-2018 00:00	21-Mar-2018 00:00	
Compound	CAS Number	LOR	Unit	EM1805147-001	EM1805147-002	EM1805147-003	EM1805147-004	EM1805147-005	
				Result	Result	Result	Result	Result	
EK059G: Nitrite plus Nitrate as N (NOx) by Discrete Analyser									
Nitrite + Nitrate as N	----	0.01	mg/L	0.02	<0.01	<0.01	0.25	0.67	
EK061G: Total Kjeldahl Nitrogen By Discrete Analyser									
Total Kjeldahl Nitrogen as N	----	0.1	mg/L	0.4	0.4	0.2	0.3	0.2	
EK062G: Total Nitrogen as N (TKN + NOx) by Discrete Analyser									
^ Total Nitrogen as N	----	0.1	mg/L	0.4	0.4	0.2	0.6	0.9	
EK067G: Total Phosphorus as P by Discrete Analyser									
Total Phosphorus as P	----	0.01	mg/L	1.93	0.11	0.05	0.07	0.08	
EN055: Ionic Balance									
Total Anions	----	0.01	meq/L	0.81	1.92	1.30	1.15	2.98	
Total Cations	----	0.01	meq/L	0.81	1.61	1.09	0.95	2.60	
Ionic Balance	----	0.01	%	<0.01	----	----	----	----	



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	MB04B	MB07A	MB07B	TMB02A	TMB02B
Client sampling date / time				21-Mar-2018 00:00	22-Mar-2018 00:00	22-Mar-2018 00:00	20-Mar-2018 00:00	20-Mar-2018 00:00	
Compound	CAS Number	LOR	Unit	EM1805147-006	EM1805147-007	EM1805147-008	EM1805147-009	EM1805147-010	
				Result	Result	Result	Result	Result	
EA015: Total Dissolved Solids dried at 180 ± 5 °C									
Total Dissolved Solids @180°C	----	10	mg/L	----	----	----	98	80	
Total Dissolved Solids @180°C	----	10	mg/L	940	94	312	----	----	
ED037P: Alkalinity by PC Titrator									
Hydroxide Alkalinity as CaCO3	DMO-210-001	1	mg/L	<1	<1	<1	<1	<1	
Carbonate Alkalinity as CaCO3	3812-32-6	1	mg/L	5	<1	<1	<1	<1	
Bicarbonate Alkalinity as CaCO3	71-52-3	1	mg/L	126	18	22	12	56	
Total Alkalinity as CaCO3	----	1	mg/L	131	18	22	12	56	
ED041G: Sulfate (Turbidimetric) as SO4 2- by DA									
Sulfate as SO4 - Turbidimetric	14808-79-8	1	mg/L	88	9	158	6	8	
ED045G: Chloride by Discrete Analyser									
Chloride	16887-00-6	1	mg/L	37	1	5	<1	<1	
ED093F: Dissolved Major Cations									
Calcium	7440-70-2	1	mg/L	5	4	55	4	13	
Magnesium	7439-95-4	1	mg/L	1	2	4	<1	2	
Sodium	7440-23-5	1	mg/L	103	3	13	1	7	
Potassium	7440-09-7	1	mg/L	2	<1	3	<1	<1	
EG020F: Dissolved Metals by ICP-MS									
Arsenic	7440-38-2	0.001	mg/L	0.002	<0.001	0.002	<0.001	0.004	
Cadmium	7440-43-9	0.0001	mg/L	<0.0001	<0.0001	<0.0001	<0.0001	<0.0001	
Chromium	7440-47-3	0.001	mg/L	<0.001	<0.001	0.002	0.001	<0.001	
Copper	7440-50-8	0.001	mg/L	0.010	0.007	0.098	0.009	0.007	
Nickel	7440-02-0	0.001	mg/L	0.002	0.002	0.002	0.002	0.001	
Lead	7439-92-1	0.001	mg/L	0.002	0.001	0.005	0.002	0.001	
Zinc	7440-66-6	0.005	mg/L	0.030	0.027	0.105	0.037	0.015	
EG035F: Dissolved Mercury by FIMS									
Mercury	7439-97-6	0.0001	mg/L	<0.0001	<0.0001	<0.0001	<0.0001	<0.0001	
EK040P: Fluoride by PC Titrator									
Fluoride	16984-48-8	0.1	mg/L	0.6	<0.1	0.5	<0.1	0.2	
EK055G: Ammonia as N by Discrete Analyser									
Ammonia as N	7664-41-7	0.01	mg/L	0.16	0.06	0.06	0.05	0.06	
EK057G: Nitrite as N by Discrete Analyser									
Nitrite as N	14797-65-0	0.01	mg/L	<0.01	<0.01	0.06	<0.01	<0.01	
EK058G: Nitrate as N by Discrete Analyser									



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	MB04B	MB07A	MB07B	TMB02A	TMB02B
Client sampling date / time				21-Mar-2018 00:00	22-Mar-2018 00:00	22-Mar-2018 00:00	20-Mar-2018 00:00	20-Mar-2018 00:00	
Compound	CAS Number	LOR	Unit	EM1805147-006	EM1805147-007	EM1805147-008	EM1805147-009	EM1805147-010	
				Result	Result	Result	Result	Result	
EK058G: Nitrate as N by Discrete Analyser - Continued									
Nitrate as N	14797-55-8	0.01	mg/L	<0.01	0.17	<0.01	<0.01	0.01	
EK059G: Nitrite plus Nitrate as N (NOx) by Discrete Analyser									
Nitrite + Nitrate as N	----	0.01	mg/L	<0.01	0.17	0.06	<0.01	0.01	
EK061G: Total Kjeldahl Nitrogen By Discrete Analyser									
Total Kjeldahl Nitrogen as N	----	0.1	mg/L	0.2	0.2	1.0	0.7	0.2	
EK062G: Total Nitrogen as N (TKN + NOx) by Discrete Analyser									
^ Total Nitrogen as N	----	0.1	mg/L	0.2	0.4	1.1	0.7	0.2	
EK067G: Total Phosphorus as P by Discrete Analyser									
Total Phosphorus as P	----	0.01	mg/L	1.14	0.18	1.66	0.09	0.07	
EN055: Ionic Balance									
Total Anions	----	0.01	meq/L	5.49	0.58	3.87	0.36	1.28	
Total Cations	----	0.01	meq/L	4.86	0.49	3.72	0.24	1.12	
Ionic Balance	----	0.01	%	6.08	----	2.03	----	----	



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	TMB03A	TMB03B	TMB04	QA01	----
Client sampling date / time				20-Mar-2018 00:00	20-Mar-2018 00:00	21-Mar-2018 00:00	22-Mar-2018 00:00	----	
Compound	CAS Number	LOR	Unit	EM1805147-011	EM1805147-012	EM1805147-013	EM1805147-014	-----	
				Result	Result	Result	Result	----	
EA015: Total Dissolved Solids dried at 180 ± 5 °C									
Total Dissolved Solids @180°C	----	10	mg/L	136	179	56	124	----	
ED037P: Alkalinity by PC Titrator									
Hydroxide Alkalinity as CaCO3	DMO-210-001	1	mg/L	<1	<1	<1	<1	----	
Carbonate Alkalinity as CaCO3	3812-32-6	1	mg/L	<1	<1	<1	<1	----	
Bicarbonate Alkalinity as CaCO3	71-52-3	1	mg/L	34	73	33	80	----	
Total Alkalinity as CaCO3	----	1	mg/L	34	73	33	80	----	
ED041G: Sulfate (Turbidimetric) as SO4 2- by DA									
Sulfate as SO4 - Turbidimetric	14808-79-8	1	mg/L	6	26	5	13	----	
ED045G: Chloride by Discrete Analyser									
Chloride	16887-00-6	1	mg/L	5	4	<1	1	----	
ED093F: Dissolved Major Cations									
Calcium	7440-70-2	1	mg/L	5	16	9	14	----	
Magnesium	7439-95-4	1	mg/L	3	3	<1	6	----	
Sodium	7440-23-5	1	mg/L	6	14	3	9	----	
Potassium	7440-09-7	1	mg/L	1	2	<1	1	----	
EG020F: Dissolved Metals by ICP-MS									
Arsenic	7440-38-2	0.001	mg/L	<0.001	0.014	<0.001	0.008	----	
Cadmium	7440-43-9	0.0001	mg/L	0.0001	<0.0001	<0.0001	<0.0001	----	
Chromium	7440-47-3	0.001	mg/L	<0.001	<0.001	0.002	<0.001	----	
Copper	7440-50-8	0.001	mg/L	0.008	0.090	0.101	<0.001	----	
Nickel	7440-02-0	0.001	mg/L	0.004	0.003	0.002	0.002	----	
Lead	7439-92-1	0.001	mg/L	0.001	0.005	0.006	0.001	----	
Zinc	7440-66-6	0.005	mg/L	0.056	0.116	0.119	<0.005	----	
EG035F: Dissolved Mercury by FIMS									
Mercury	7439-97-6	0.0001	mg/L	<0.0001	<0.0001	<0.0001	<0.0001	----	
EK040P: Fluoride by PC Titrator									
Fluoride	16984-48-8	0.1	mg/L	0.1	0.3	<0.1	<0.1	----	
EK055G: Ammonia as N by Discrete Analyser									
Ammonia as N	7664-41-7	0.01	mg/L	0.05	0.04	0.05	0.06	----	
EK057G: Nitrite as N by Discrete Analyser									
Nitrite as N	14797-65-0	0.01	mg/L	<0.01	<0.01	<0.01	<0.01	----	
EK058G: Nitrate as N by Discrete Analyser									
Nitrate as N	14797-55-8	0.01	mg/L	<0.01	<0.01	0.04	<0.01	----	



Analytical Results

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID	TMB03A	TMB03B	TMB04	QA01	----
Client sampling date / time				20-Mar-2018 00:00	20-Mar-2018 00:00	21-Mar-2018 00:00	22-Mar-2018 00:00	----	----
Compound	CAS Number	LOR	Unit	EM1805147-011	EM1805147-012	EM1805147-013	EM1805147-014	-----	----
				Result	Result	Result	Result	----	----
EK059G: Nitrite plus Nitrate as N (NOx) by Discrete Analyser									
Nitrite + Nitrate as N	----	0.01	mg/L	<0.01	<0.01	0.04	<0.01	----	----
EK061G: Total Kjeldahl Nitrogen By Discrete Analyser									
Total Kjeldahl Nitrogen as N	----	0.1	mg/L	0.2	0.2	0.2	0.5	----	----
EK062G: Total Nitrogen as N (TKN + NOx) by Discrete Analyser									
^ Total Nitrogen as N	----	0.1	mg/L	0.2	0.2	0.2	0.5	----	----
EK067G: Total Phosphorus as P by Discrete Analyser									
Total Phosphorus as P	----	0.01	mg/L	0.11	0.05	0.13	0.09	----	----
EN055: Ionic Balance									
Total Anions	----	0.01	meq/L	0.94	2.11	0.76	1.90	----	----
Total Cations	----	0.01	meq/L	0.78	1.70	0.58	1.61	----	----



Surrogate Control Limits

Sub-Matrix: TRIP BLANK		Recovery Limits (%)	
Compound	CAS Number	Low	High
EP074S: VOC Surrogates			
1,2-Dichloroethane-D4	17060-07-0	72	132
Toluene-D8	2037-26-5	77	132
4-Bromofluorobenzene	460-00-4	67	131



SYDNEY

Ground floor, Suite 01, 20 Chandos Street
St Leonards, New South Wales, 2065
T 02 9493 9500 F 02 9493 9599

NEWCASTLE

Level 1, Suite 6, 146 Hunter Street
Newcastle, New South Wales, 2300
T 02 4907 4800 F 02 4907 4899

BRISBANE

Level 4, Suite 01, 87 Wickham Terrace
Spring Hill, Queensland, 4000
T 07 3839 1800 F 07 3839 1866



Appendix B

Peer review modelling report

INDEPENDENT REVIEW STATEMENT

ATTENTION:	Dr Doug Weatherill, Associate Groundwater Modeller, EMM Consulting	
FROM:	Hugh Middlemis, Principal Groundwater Engineer, Hydrogeologic Pty Ltd	
REFERENCES:	18 May 2018	EMM ref: Snowy 2.0 (J17188)
	HGL job#: 61.065	
SUBJECT:	Peer Review of Snowy 2.0 Early Works Groundwater Model - Calibration stage	

1. SUMMARY

This brief statement summarises the outcomes of an independent review of the calibration of the Snowy 2.0 Early Works numerical groundwater model that was developed by EMM Consulting to support environmental assessments for the Snowy 2.0 feasibility study.

This review was conducted in accordance with the best practice principles of the Australian Groundwater Modelling Guideline (Barnett et al. 2012), which suggests a compliance checklist to summarise review outcomes; this is presented as Table 1.

The review was conducted progressively (i.e. consistent with the guidelines) through a series of consultations with the EMM Consulting hydrogeology and modelling teams at the conceptualisation and model design stages (including a site visit on 13th February 2018), and at the model calibration and early works prediction stage. While the model report documentation is not yet available, the model data set and results were inspected in detail on 17th May 2018 at the EMM offices in Adelaide.

It is my professional opinion that the Snowy 2.0 Early Works groundwater model has been developed consistent with best practice, including careful model design and acceptable calibration to the available groundwater levels and with consideration of river baseflow estimates. The Snowy 2.0 model is suitable for early works scenario modelling and assessment of drawdown and catchment water balance impacts.

The Modflow-USG package was used to design a detailed variable grid, with minimum cell sizes of 12.5 m near mapped streams and the tunnel alignment, with 8 additional sub-layers either side of the tunnel, and with pinching out of unnecessary layers and/or cells remote from such features.

The boundary conditions, recharge, surface-groundwater interactions and parameters applied are reasonable, with a bias towards conservative assumptions where warranted (e.g. adopting a storage depletion setup rather than regional groundwater throughflow, in cognisance of the limited data set).

The model performance across the 16 monitoring bore sites meets statistical criteria (mainly due to the large range in elevations), with residual values of less than 4 metres in 4 of the 16 bores, but 11-17 metres in 6 other bores, and a slight bias to over-predict levels. The steady state (long term average) predictions are robustly benchmarked by the steady state calibration, but the results of the transient predictions of progressive early works tunnelling are subject to more uncertainty as there is no time series groundwater level data for transient calibration. Model sensitivity/uncertainty scenarios have been run, again with conservative parameter settings.

The ongoing hydrogeological investigations will provide additional data for future model refinements and improvements in performance (e.g. to reduce residuals and improve river baseflow calibration) and for more extensive uncertainty analysis.

Table 1 - Groundwater Model Compliance Checklist: 10-point essential summary - Snowy 2.0 model

Question	Y/N	Comments re Snowy 2.0 Early Works groundwater model
1. Are the model objectives and model confidence level classification clearly stated?	Yes	Class 2 model confidence level is justifiable (see Table 2 below)
2. Are the objectives satisfied?	Yes	Competent model design and calibration to groundwater levels at 16 bores, and estimated Yarrangobilly River baseflow, demonstrating fitness for purpose of early works impact assessment scenarios (drawdowns & catchment water balances).
3. Is the conceptual model consistent with objectives and confidence level?	Yes	Conceptualisation is sound, consistent with data on fractured rock aquifer system and weathered shallow regolith, and with early works investigations objectives and Class 2 confidence level. Information available from existing Snowy Hydro scheme was used to guide investigations and benchmark model results.
4. Is the conceptual model based on all available data, presented clearly and reviewed by an appropriate reviewer?	Yes	Report is not yet available, but available information has been considered carefully. Additional monitoring bores have been drilled and tested and there has been detailed consultation with Snowy Hydro and geotechnical experts. Experienced hydrogeologists and modellers have reviewed available data and new investigations, conceptualisation, model design and outcomes.
5. Does the model design conform to best practice?	Yes	The model software, design, extent, grid and parameters are a good example of best practice design and execution. The limited data set is acknowledged, and a conservative approach has been applied such that potential impacts would be over-estimated.
6. Is the model calibration satisfactory?	Yes	Steady state model calibration statistical performance is good (1.1% SRMS error), mainly due to large range in elevations. Residual values are less than 4 metres in 4 of the 16 bores, but 11-17 metres in 6 other bores, and there is a slight bias to over-predict levels. Transient calibration or verification not possible with the limited data set and time available.
7. Are the calibrated parameter values and estimated fluxes plausible?	Yes	Model parameter values are consistent with drilling and testing information, and fluxes were benchmarked to baseflow estimates and existing tunnel drainage estimates. Model recharge flux inputs considered several analytical methods, plus estimates from BoM AWRA and regional modelling in Victoria that involved extensions into NSW (Ensym project). Evapo-transpiration flux estimates based on BoM data, with spatial variations for plateau (eastern) or ravine (western) conditions.
8. Do the model predictions conform to best practice?	Yes	Predicted drawdown at water table shown to be limited except where there is shallow cover over tunnel (e.g. <100m), and steady state predicted tunnel max. inflow ~3.5 L/s (~1 L/s/km); all consistent with observations in existing Snowy Hydro scheme.
9. Is the uncertainty associated with the simulations/predictions reported?	Yes	The hydrogeological conceptualisation, model design and review process considered conceptual and measurement uncertainties, such as geology, faulting, rainfall recharge, surface drainage network, baseflow and differences between the plateau (eastern) and ravine (western) areas). Report not yet available.
10. Is the model fit for purpose?	Yes	My professional opinion is that the Snowy 2.0 model is a sound example of best practice in design and execution. The Snowy 2.0 model is suitable for early works scenario modelling of drawdown effects due to tunnel construction and effects on catchment water balances (for licensing purposes).

2. Model Confidence Level Classification

The Snowy 2.0 groundwater model report was not available when this review report was written, so the “**model confidence level**” criteria (Barnett et al. 2012, Section 2 and Table 2-1) is not yet documented. However, the modelling team indicated the aim is for a Class 2 model (suitable for impact assessment).

This review conducted an independent assessment (Table 2) based on a method recommended in the draft NCGRT report on groundwater modelling uncertainty (Middlemis and Peeters, 2018, in review). Some of the attributes cannot be scored definitively in this case (at this stage) as only the early works calibration and predictions have been run, and the report is not yet available. Table 2 indicates that the Snowy 2.0 model exhibits a few Class 1 attributes, but more Class 2 attributes, and a roughly equal number of Class 3 attributes. An overall Class 2 model confidence level has been achieved, confirming the Snowy 2.0 model as suitable for impact assessment scenario modelling.

Table 2 - Snowy 2.0 early works groundwater model (calibration) confidence level

Class	Data	Calibration	Prediction	Quantitative Indicators
1 (simple)	~ Not much.	✓ Transient not possible. S/state ok	Timeframe >> Calibration	? Timeframe >10x
	~ Sparse coverage.	Large error statistic.	Long stress periods.	? Stresses >5x
	✓ No metered usage.	~ Inadequate data spread.	✓ Poor/no validation.	Mass balance > 1% (or one-off 5%)
	Low resolution topo DEM. Poor aquifer geometry.	Targets incompatible with model purpose.	~ Transient prediction but steady-state calibration.	Properties <> field values. No review by Hydro/Modeller.
2 (impact assessment)	~ Some.	Partial performance.	✓ Timeframe > Calibration	? Timeframe = 3-10x
	OK coverage.	Some long term trends wrong.	Long stress periods.	? Stresses = 2-5x
	Some usage data/low volumes.	✓ Short time record.	OK validation.	Mass balance < 1%
	~ Baseflow estimates ~ Some K & S measurements.	✓ Weak seasonal match. Or no seasonal trends.	X Transient calib. & pred'n (or S/state cal/pred).	Some properties <> field values. Review by Hydrogeologist.
	✓ Some high res. topo DEM &/or ~ some aquifer geometry.	No use of targets compatible with model purpose (heads & fluxes).	✓ New stresses not in calibration.	Some coarse discretisation in key areas of grid or at key times.
3 (complex simulator)	Lots, with good coverage.	✓ Good performance stats.	Timeframe ~ Calibration	Timeframe < 3x
	Good metered usage info.	Most long term trends matched.	✓ Similar stress periods.	Stresses < 2x
	✓ Local climate data (or SILO)	Most seasonal matches OK.	Good validation.	✓ Mass balance < 0.5%
	Kh, Kv & Sy measurements from range of tests.	✓ Present day data targets.	✓ Calib. & prediction consistent (transient or steady-state).	✓ Properties ~ field measurements.
	✓ High resolution DEM all areas.	✓ Head & Flux targets used to constrain calibration.	~ Similar stresses to those in calibration. (climate)	✓ No coarse discretisation in key areas (grid or time).
	Good aquifer geometry.			✓ Review by experienced Modeller.

(after Table 2-1 of Barnett et al (2012) Australian Groundwater Modelling Guideline)

3. Conclusion

This review finds that the Snowy 2.0 groundwater model is fit for the purpose of early works scenario modelling of drawdown effects due to tunnel construction and effects on catchment water balances.

Yours sincerely, Hydrogeologic Pty Ltd

Hugh

Hugh Middlemis (Principal Groundwater Engineer)

Declaration: For the record, the reviewer (Hugh Middlemis) is an engineer, hydrogeologist and independent modelling specialist with more than 37 **years' experience**. **Hugh was principal author of the** first Australian groundwater modelling guidelines (Middlemis et al, 2001) that formed the basis for the latest guidelines (Barnett et al. 2012) and was awarded a Churchill Fellowship in 2004 to benchmark groundwater modelling best practice. No potential conflict of interest is identified.

4. References

- Barnett B, Townley L, Post V, Evans R, Hunt R, Peeters L, Richardson S, Werner A, Knapton A and Boronkay A. (2012). Australian Groundwater Modelling Guidelines. Waterlines report 82, National Water Commission, Canberra. <http://webarchive.nla.gov.au/gov/20160615064846/http://archive.nwc.gov.au/library/waterlines/82>.
- Middlemis H, Walker G, Peeters L, Richardson S, Hayes P, Moore C. (2018; in review). Groundwater Modelling Uncertainty - Implications for decision-making. Workshop Summary Report, National Centre for Groundwater Research and Training, Australia.
- Middlemis H, Merrick N, Ross J, and Rozlapa K. (2001). Groundwater Flow Modelling Guideline. Prepared for Murray-Darling Basin Commission by Aquaterra, January 2001. URL: www.mdba.gov.au/sites/default/files/archived/mbdc-GW-reports/2175_GW_flow_modelling_guideline.pdf







OFFICE LOCATIONS

SYDNEY

Ground Floor, Suite 01, 20 Chandos Street
St Leonards NSW 2065
T 02 9493 9500
F 02 9493 9599

NEWCASTLE

Level 1, Suite 6, 146 Hunter Street
Newcastle NSW 2300
T 02 4907 4800
F 02 4907 4899

BRISBANE

Level 10, Suite 01, 87 Wickham Terrace
Spring Hill QLD 4000
T 07 3839 1800
F 07 3839 1866

ADELAIDE

Level 1, 70 Pirie Street
Adelaide SA 5000
T 08 8232 2253