


SEDIMENT AND EROSION NOTES

- B1. THIS PLAN TO BE READ IN CONJUNCTION WITH SEDIMENT AND EROSION CONTROL DETAILS AS SHOWN
- B2. THE CONTRACTOR SHALL IMPLEMENT ALL SOIL EROSION AND SEDIMENT CONTROL MEASURES AS NECESSARY AND TO THE SATISFACTION OF COUNCIL PRIOR TO THE COMMENCEMENT OF AND DURING CONSTRUCTION. NO DISTURBANCE TO THE SITE SHALL BE PERMITTED OTHER THAN IN THE IMMEDIATE AREA OF THE WORKS AND NO MATERIAL SHALL BE REMOVED FROM THE SITE WITHOUT COUNCIL'S APPROVAL. ALL SEDIMENT AND EROSION CONTROL DEVICES TO BE INSTALLED AND MAINTAINED IN ACCORDANCE WITH STANDARDS OUTLINED IN NSW DEPARTMENT OF HOUSING'S "MANAGING URBAN STORMWATER - SOILS AND CONSTRUCTIONS".
- B3. TOPSOIL SHALL BE STRIPPED AND STOCKPILED OUTSIDE HAZARD AREAS SUCH AS DRAINAGE LINES. THIS TOPSOIL IS TO BE RESPREAD LATER ON AREAS TO BE REVEGETATED AND STABILISED ONLY, (I.E. ALL FOOTPATHS, BATTERS, SITE REGARDING AREAS, BASINS AND CATCHDRAINS). TOPSOIL SHALL NOT BE RESPREAD ON ANY OTHER AREAS UNLESS SPECIFICALLY INSTRUCTED BY THE SUPERINTENDENT. IF THEY ARE TO REMAIN FOR LONGER THAN ONE MONTH STOCKPILES SHALL BE PROTECTED FROM EROSION BY COVERING THEM WITH A MULCH AND HYDROSEEDING AND, IF NECESSARY, BY LOCATING BANKS OR DRAINS DOWNSTREAM OF A STOCKPILE TO RETARD SILT LADEN RUNOFF.
- B4. THE CONTRACTOR SHALL REGULARLY MAINTAIN ALL SEDIMENT AND EROSION CONTROL DEVICES AND REMOVE ACCUMULATED SILT FROM SUCH DEVICES SUCH THAT MORE THAN 60% OF THEIR CAPACITY IS LOST. ALL THE SILT IS TO BE PLACED OUTSIDE THE LIMIT OF WORKS. THE PERIOD FOR MAINTAINING THESE DEVICES SHALL BE AT LEAST UNTIL ALL DISTURBED AREAS ARE REVEGETATED AND FURTHER AS MAY BE DIRECTED BY THE SUPERINTENDENT OR COUNCIL.
- B5. VEHICULAR TRAFFIC SHALL BE CONTROLLED DURING CONSTRUCTION CONFINING ACCESS WHERE POSSIBLE TO NOMINATED STABILISED ACCESS POINTS.
- B6. THE CONTRACTOR SHALL IMPLEMENT DUST CONTROL BY REGULAR WETTING DOWN (BUT NOT SATURATING) DISTURBED AREA.
- B7. PROVIDE AND MAINTAIN SILT TRAPS AROUND ALL SURFACE INLET PITS UNTIL CATCHMENTS ARE REVEGETATED OR PAVED.
- B8. REVEGETATE ALL TRENCHES IMMEDIATELY UPON COMPLETION OF BACKFILLING.
- B9. ALL DRAINAGE PIPE INLETS TO BE CAPPED UNTIL: A) DOWNPIPES CONNECTED B) PITS CONSTRUCTED AND PROTECTED WITH SILT BARRIER
- B10. HAYBAILS & SILT FENCE MAINTENANCE INSPECTION TO BE CARRIED OUT **EVERY 3 MONTHS.**

LEGEND



STORMWATER SEDIMENT TRAPS AT ALL PROPOSED PIT INLETS



TEMPORARY CONSTRUCTION VEHICLE EXIT

'A' CLASS HOARDING

SEDIMENT CONTROL FENCE



STOCKPILE AREA



SANDBAG KERB INLET SEDIMENT TRAP



TEMPORARY SEDIMENT BASIN

APPROVAL ISSUE

NOT TO BE USED FOR CONSTRUCTION

REVISIONS:			COPYRIGHT © THIS DRAWING IS COPYRIGHT AND THE PROPERTY OF VDM NSW PTY LTD IT MUST NOT BE	
				RETAINED, COPIED OR USED WITHOUT THE AUTHORITY OF VDM NSW PTY LTD. DISCLAIMER THIS DRAWING AND ITS CONTENTS ARE ELECTRONICALLY GENERATED, ARE CONFIDENTIAL AN MAY ONLY BE USED FOR THE PURPOSE FOR WHICH THEY WERE INTENDED. VDM PTY LTD WILL NOT ACCEPT RESPONSIBILITY FOR ANY CONSEQUENCES ARISING FROM THE USE OF THE DRAWING FOR OTHER THAN ITS INTENDED PURPOSE OR WHERE THE DRAWING HAS BEEN
D C B A	UPDATED PLANS TO REFLECT CMP SITE ACCESS ISSUED FOR APPROVAL AMENDED PRELIMINARY	N.T. N.T. N.T. N.T.	05.03.13 04.03.13 02.04.12 12.03.12	3.13 3.13 ALTERED, AMENDED OR CHANGED EITHER MANUALLY OR ELECTRONICALLY BY ANY THIRD IN NOTE THIS IS AN UNCONTROLLED DOCUMENT ISSUED FOR INFORMATION PURPOSES ONLY, UNLE THE CHECKED SECTIONS ARE SIGNED OR COMPLETED. FIGURED DIMENSIONS TAKE
No	REVISION DESCRIPTION	DRAWN	DATE	PRIOR TO COMMENCING ANY ON-SITE OR OFF-SITE WORKS OR FABRICATION. IF IN DOUBT - AS



LEVEL 5, 35-37 CHANDOS STREET, ST LEONARDS, N.S.W. 2065 Telephone: 61-2-9436 0433 Fax: 61-2-9436 1370

www.vdmgroup.com.au

CROWN INTERNATIONAL HOLDING GROUP LVL 11, 68 ALFRED STREET MILSONS POINT NSW 2061

RICE DAUBNEY LVL 1, 110 WALKER STREET NORTH SYDNEY NSW 2060 EASTLAKES NSW 2018 **EROSION & SEDIMENT CONTROL**

EASTLAKES TOWN CENTRE

GARDENERS ROAD

RJB			
DESIGNER:			
NT			
DRAFTSPERSON:	FEBRUARY 2012		
NT			
SCALE:	SHEET SIZE:		
1:750	A1		
JOB No.:	DRAWING No.:	REVISION:	
SY121-012	DA010	D	