




SOURROUNDING STREETS
Luminaire Schedule

EXISTING SCHEDULE:

Kent Street: Type H1 & H1A

Previous Kensington Street Proposal: Type H6


Date: 21.02.2012
Revision : J

| | | | | | | | | | | | | | |
|-----|--|--|------|----------------------------------|---|-----|----------------|-------|----------|------|-------------------------|--|---|
| H1 |  | 95W LED pole mounted asymmetric flat beam distribution, c/w pole system mounting bracket & accessories | Bega | 7954 | 1 | 95W | Warm white LED | 3000K | graphite | IP66 | Electronic Control Gear | 6.5m Pole Mounted Recessed rag-bolt mount. Coordinate with builder for installation. | Confirm structural requirements for rag-bolt assembly mounting details Pole Height - 6.5m |
| H1A |  | 95W LED outrigger pole mounted asymmetric flat beam distribution, c/w single 2.5m outrigger arm and pole system mounting bracket & accessories | Bega | 7954 + 7774 outrigger arm (2.5m) | 1 | 95W | Warm white LED | 3000K | graphite | IP66 | Electronic Control Gear | 6.5m pole + 2.5m outrigger arm mounted Pole Mounted Recessed rag-bolt mount. Coordinate with builder for installation. | Confirm structural requirements for rag-bolt assembly mounting details Pole Height - 6.5m Outrigger arm length - 2.5m |
| H6 |  | 40W LED post top symmetrical distribution luminaire. | Bega | 7911 | 1 | 40W | Warm white LED | 3000K | graphite | IP65 | Electronic Control Gear | 5m Pole Mounted Recessed rag-bolt mount. Coordinate with builder for installation. | Confirm structural requirements for rag-bolt assembly mounting details Pole Height - 5m |

SUGGESTED LANEWAY ALTERNATIVES
SHAREDWAY - KENSINGTON LANE

WALL MOUNTED LIGHTING



NIAGARA LANE, MELBOURNE

SUSPENDED LIGHTING



COPENGAHEN, DENMARK



SYDNEY UNIVERSITY

WALL MOUNTED LIGHTING



SUSPENDED LIGHTING



MELBOURNE LANEWAY LIGHTING

BLOCK 6 & 7 LIGHTING CONSIDERATIONS
SITE THROUGH LINKS & BLOCK 6 & 7 COURTYARDS



HOWARD LANE, PERTH