


Appendix A

Traffic surveys

Tuesday, 7 December 2010

Austraffic

Survey Start	6:00 AM	16:00 PM
Intersection Type	T Junction	
Intersection No.	10	
North Approach	Moorebank Avenue	
East Approach		
South Approach	Moorebank Avenue	
West Approach	Bapaume Road	
Date	7/12/10	
Classification	Light Heavy	

[illegible]

TIME PERIOD	VEHICLE MOVEMENT												VEHICLE MOVEMENT												GRAND TOTAL												
	1			2			3			4			5			6			7			8				9			10			11			12		
	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ		Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ			
16:00 - 16:15	5	0	5	219	9	228																264	13	277	0	0	0	3	1	4		19	0	19	510	23	533
16:15 - 16:30	4	0	4	212	11	223																145	4	149	1	1	2	6	0	6		18	0	18	386	16	402
16:30 - 16:45	3	0	3	252	4	256																127	4	131	0	0	0	10	0	10		27	0	27	419	8	427
16:45 - 17:00	3	0	3	236	6	242																122	2	124	0	0	0	2	0	2		15	1	16	378	9	387
17:00 - 17:15	2	0	2	303	13	316																133	7	140	0	0	0	15	0	15		21	0	21	474	20	494
17:15 - 17:30	4	1	5	306	5	311																112	6	118	0	0	0	3	0	3		20	1	21	445	15	460
17:30 - 17:45	3	0	3	313	7	320																102	4	106	0	0	0	3	0	3		14	0	14	435	11	446
17:45 - 18:00	6	1	7	325	11	336																90	3	93	0	0	0	1	0	1		13	2	15	435	17	452
18:00 - 18:15	5	1	6	306	11	317																87	1	88	0	0	0	1	0	1		16	1	17	415	14	429
18:15 - 18:30	5	0	5	228	6	234																111	3	114	1	0	1	2	0	2		5	0	5	352	9	361
18:30 - 18:45	2	0	2	264	5	269																81	0	81	1	0	1	3	0	3		4	4	0	355	7	362
18:45 - 19:00	0	0	0	166	1	167																68	2	70	1	0	0	0	0	0		3	0	3	228	20	248
Σ	42	3	45	3130	89	3219																1442	51	1493	4	1	5	39	1	40		186	5	190	4482	150	4992


TIME PERIOD	VEHICLE MOVEMENT												VEHICLE MOVEMENT												GRAND TOTAL					
	1		2		3		4		5		6		7		8		9		10		11		12							
	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy						
6:00 - 7:00	66	2	68	387	25	412	2	87	2	892	13	1	2	851	42	893	16	0	16	0	1	1	2	0	2	1477	82	1559		
6:15 - 7:15	66	2	70	540	37	577								925	42	967	16	0	16	0	1	1	2	2	0	2	1477	82	1559	
6:30 - 7:30	78	16	94	777	65	842								925	42	967	16	0	16	0	1	1	2	2	0	2	1477	82	1559	
6:45 - 7:45	78	16	94	777	65	842								925	42	967	16	0	16	0	1	1	2	2	0	2	1477	82	1559	
7:00 - 7:00	66	2	1	61	659	42	701							925	54	104	14	0	14	0	1	1	2	4	1	5	1699	98	1797	
7:15 - 7:30	66	2	1	63	566	39	603							1015	50	1075	18	0	18	0	1	1	2	4	1	5	1699	98	1797	
7:30 - 7:30	63	73	73	76	494	33	527							1013	57	1071	21	0	21	0	1	1	2	5	10	12	1614	95	1709	
7:45 - 8:45	91	2	93	465	37	502								1000	50	1052	26	0	26	0	4	0	4	0	4	0	4	1596	94	1690
8:00 - 8:00	90	2	2	424	34	458								940	42	982	26	0	26	0	4	0	4	0	4	0	4	1412	92	1504

TIME PERIOD	VEHICLE MOVEMENT												VEHICLE MOVEMENT												GRAND TOTAL						
	1		2		3		4		5		6		7		8		9		10		11		12								
	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy							
16:00 - 17:00	1	15	13	20	949										658	1	681							80	1093						
16:15 - 17:05	12	0	12	1003	34	1037									527	17	544	1	1	2	23	0	23	73	91	1	92	1657	93	1710	
16:30 - 17:40	12	1	13	1097	26	1126									494	10	513	0	0	0	20	0	20	0	80	2	86	1716	50	1766	
16:45 - 17:45	2	1	13	1158	3	1163									469	18	3	1169	18	0	13	0	13	0	82	2	84	1753	53	1806	
17:00 - 18:00	15	2	17	1247	36	1183									437	20	513	0	0	0	12	0	12	0	78	3	81	1789	51	1850	
17:15 - 18:15	15	3	21	1256	34	1284									361	14	1208	0	0	0	12	0	12	0	40	3	43	1802	54	1856	
17:30 - 18:30	19	2	21	1172	35	1207									390	11	401	1	0	1	7	0	7	0	48	3	51	1637	51	1688	
17:45 - 18:45	16	2	20	1123	33	1156									369	9	378	2	0	2	7	0	7	0	38	3	41	1557	47	1604	
18:00 - 19:00	12	1	13	964	22	987									317	36	327	36	0	36	0	28	0	28	0	40	3	43	1587	46	1633

Tuesday, 7 December 2010

Austraffic

Survey Start	6:00	AM	16:00	PM
Intersection Type	Cross Junction			
Intersection No.	11			
North Approach	Moorebank Avenue			
East Approach	Military Site Access 1			
South Approach	Moorebank Avenue			
West Approach	Military Site Access 1			
Date	7/12/10			
Classification	Light	Heavy		



TIME PERIOD		VEHICLE MOVEMENT																								GRAND TOTAL						
		1		2		3		4		5		6		7		8		9		10		11		12								
		Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy							
6:00	- 6:15	1	0	1	44	0	44	0	0	0	0	0	0	0	0	0	260	9	269	1	0	1	0	0	0	1	307	9	316			
6:15	- 6:30	0	0	0	71	2	73	0	0	0	0	0	0	0	0	0	264	13	277	1	0	1	1	0	0	0	0	384	15	399		
6:30	- 6:45	0	0	0	64	0	64	0	0	0	0	0	115	0	115	0	277	20	297	2	2	0	0	0	0	0	0	324	16	340		
6:45	- 7:00	0	0	0	157	4	161	0	0	0	0	0	0	0	0	0	266	9	275	2	0	0	0	0	0	0	0	438	17	455		
7:00	- 7:15	3	0	3	174	7	181	0	0	0	0	0	0	0	0	0	261	5	266	3	0	3	0	0	0	0	0	441	17	458		
7:15	- 7:30	6	0	6	178	7	185	0	0	0	0	0	0	0	0	0	265	10	275	3	0	3	1	0	0	1	0	454	17	471		
7:30	- 7:45	5	0	5	137	7	144	0	0	0	0	0	0	0	0	0	255	9	264	6	0	6	0	0	0	0	1	0	404	16	420	
7:45	- 8:00	2	0	2	110	8	118	0	0	0	0	0	0	0	0	0	268	8	276	2	0	2	5	0	5	0	0	2	389	16	405	
8:00	- 8:15	6	0	6	103	5	108	0	0	0	0	0	0	0	0	0	261	8	269	2	0	2	0	0	0	0	3	0	376	13	389	
8:15	- 8:30	4	0	4	77	7	84	0	0	0	0	0	0	0	0	0	267	26	293	2	0	2	2	0	2	0	0	1	343	14	357	
8:30	- 8:45	1	0	1	95	6	101	0	0	0	0	0	0	0	0	0	212	12	224	2	0	2	0	0	0	0	0	0	312	12	324	
8:45	- 9:00	1	0	1	62	5	67	0	0	0	0	0	0	0	0	0	171	9	180	0	0	0	1	1	0	1	0	0	235	14	249	
Σ		29	0	29	1323	64	1387	0	0	0	0	0	0	0	0	0	3018	109	3127	26	0	26	11	0	11	0	0	9	0	448	173	4599

TIME PERIOD	VEHICLE MOVEMENT																								GRAND TOTAL						
	1		2		3		4		5		6		7		8		9		10		11		12								
	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy							
16:00 - 16:15	0	0	251	2	253	0	0	0	0	0	0	0	0	0	227	3	230	0	0	21	0	21	0	0	8	0	8	507	5	512	
16:15 - 16:30	1	0	1	264	12	276	0	0	0	0	0	0	0	0	142	2	144	1	0	1	5	0	5	0	6	0	6	419	14	433	
16:30 - 16:45	2	0	2	266	10	270	0	0	0	0	0	0	0	0	113	3	114	0	0	1	1	0	0	0	3	0	3	406	0	413	
16:45 - 17:00	1	1	1	265	281	0	0	1	0	295	0	0	0	0	90	2	100	0	0	2	0	2	0	0	1	0	1	387	0	395	
17:00 - 17:15	0	0	0	325	13	338	0	0	0	0	0	0	0	0	105	3	107	0	0	0	0	0	0	0	6	0	6	436	0	442	
17:15 - 17:30	0	0	0	314	6	320	0	0	0	0	0	0	0	0	98	3	101	0	0	0	1	1	0	1	0	1	1	414	9	423	
17:30 - 17:45	0	0	0	316	8	324	0	0	0	0	0	0	0	0	104	3	107	0	0	0	2	0	2	0	0	2	0	424	11	435	
17:45 - 18:00	0	0	0	372	7	379	0	0	0	0	0	0	0	0	90	2	92	1	0	1	1	0	1	0	0	0	0	464	9	473	
18:00 - 18:15	0	0	0	324	15	339	0	0	0	0	0	0	0	0	91	3	94	1	0	1	2	0	2	0	0	3	0	421	18	439	
18:15 - 18:30	0	0	0	327	10	337	0	0	0	0	0	0	0	0	84	1	85	1	0	0	0	0	0	0	0	3	0	415	11	426	
18:30 - 18:45	0	0	0	321	6	327	0	0	0	0	0	0	0	0	64	1	65	0	0	0	0	0	0	0	0	0	0	395	7	402	
18:45 - 19:00	0	0	0	183	3	186	0	0	0	0	0	0	0	0	58	1	59	0	0	0	1	0	1	0	0	0	0	0	242	0	242
Σ	4	0	4	3568	92	3660	0	0	0	0	0	0	0	0	1274	24	1298	5	0	5	36	0	36	0	0	33	0	4029	116	5036	


TIME PERIOD	VEHICLE MOVEMENT												VEHICLE MOVEMENT												GRAND TOTAL
	1		2		3		4		5		6		7		8		9		10		11		12		
	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	
6:00 - 7:00	0	0	1	367	19	399	0	0	0	0	0	0	0	0	1067	1108	6	8	1	0	0	0	1493	56	
7:00 - 8:00	0	0	0	317	19	336	0	0	0	0	0	0	0	0	1088	1105	6	8	1	0	0	0	1567	36	
8:00 - 9:00	0	0	0	517	19	536	0	0	0	0	0	0	0	0	1268	1341	10	10	1	0	0	0	1772	15	
9:00 - 10:00	0	0	0	367	19	386	0	0	0	0	0	0	0	0	1067	1108	6	8	1	0	0	0	1493	56	
10:00 - 11:00	0	0	0	517	19	536	0	0	0	0	0	0	0	0	1268	1341	10	10	1	0	0	0	1772	15	
11:00 - 12:00	0	0	0	367	19	386	0	0	0	0	0	0	0	0	1067	1108	6	8	1	0	0	0	1493	56	
12:00 - 1:00	0	0	0	517	19	536	0	0	0	0	0	0	0	0	1268	1341	10	10	1	0	0	0	1772	15	
1:00 - 2:00	0	0	0	367	19	386	0	0	0	0	0	0	0	0	1067	1108	6	8	1	0	0	0	1493	56	
2:00 - 3:00	0	0	0	517	19	536	0	0	0	0	0	0	0	0	1268	1341	10	10	1	0	0	0	1772	15	
3:00 - 4:00	0	0	0	367	19	386	0	0	0	0	0	0	0	0	1067	1108	6	8	1	0	0	0	1493	56	
4:00 - 5:00	0	0	0	517	19	536	0	0	0	0	0	0	0	0	1268	1341	10	10	1	0	0	0	1772	15	
5:00 - 6:00	0	0	0	367	19	386	0	0	0	0	0	0	0	0	1067	1108	6	8	1	0	0	0	1493	56	
6:00 - 7:00	0	0	0	517	19	536	0	0	0	0	0	0	0	0	1268	1341	10	10	1	0	0	0	1772	15	
7:00 - 8:00	0	0	0	367	19	386	0	0	0	0	0	0	0	0	1067	1108	6	8	1	0	0	0	1493	56	
8:00 - 9:00	0	0	0	517	19	536	0	0	0	0	0	0	0	0	1268	1341	10	10	1	0	0	0	1772	15	
9:00 - 10:00	0	0	0	367	19	386	0	0	0	0	0	0	0	0	1067	1108	6	8	1	0	0	0	1493	56	
10:00 - 11:00	0	0	0	517	19	536	0	0	0	0	0	0	0	0	1268	1341	10	10	1	0	0	0	1772	15	
11:00 - 12:00	0	0	0	367	19	386	0	0	0	0	0	0	0	0	1067	1108	6	8	1	0	0	0	1493	56	
12:00 - 1:00	0	0	0	517	19	536	0	0	0	0	0	0	0	0	1268	1341	10	10	1	0	0	0	1772	15	
1:00 - 2:00	0	0	0	367	19	386	0	0	0	0	0	0	0	0	1067	1108	6	8	1	0	0	0	1493	56	
2:00 - 3:00	0	0	0	517	19	536	0	0	0	0	0	0	0	0	1268	1341</									

TIME PERIOD	VEHICLE MOVEMENT												VEHICLE MOVEMENT												GRAND TOTAL					
	1		2		3		4		5		6		7		8		9		10		11		12							
	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ						
16:00 - 17:00	4	0	4	1096	11	1110	0	0	0	0	0	0	0	0	0	580	5	585	2	0	2	29	0	0	29	18	1719	42	1761	
16:15 - 17:15	4	0	4	1160	35	1195	0	0	0	0	0	0	0	0	0	458	7	465	2	0	2	8	0	0	10	16	1618	42	1660	
16:30 - 17:30	4	0	4	1224	18	1242	0	0	0	0	0	0	0	0	0	412	8	420	1	1	2	11	0	0	12	16	1639	42	1681	
16:45 - 17:45	3	0	3	1240	33	1273	0	0	0	0	0	0	0	0	0	405	10	415	0	0	0	4	0	0	4	9	1661	43	1704	
16:00 - 18:00	0	0	0	3327	34	3361	0	0	0	0	0	0	0	0	0	0	397	10	407	1	0	1	5	0	0	5	9	1698	44	1742
17:00 - 18:00	0	0	0	1233	13	1246	0	0	0	0	0	0	0	0	0	0	382	13	395	2	2	4	0	0	4	8	1684	45	1729	
17:30 - 18:30	0	0	0	1339	40	1379	0	0	0	0	0	0	0	0	0	0	369	9	378	3	3	5	0	0	8	8	1674	45	1719	
17:45 - 18:45	0	0	0	1444	38	1482	0	0	0	0	0	0	0	0	0	0	329	7	336	3	3	5	0	0	6	6	1685	45	1730	
18:00 - 18:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	309	29	338	0	0	0	0	0	0	0	0	1623	46	1669

Tuesday, 7 December 2010

Austraffic

Survey Start	6:00 AM	16:00 PM
Intersection Type	T Junction	
Intersection No.	12	
North Approach	Moorebank Avenue	
East Approach		
South Approach	Moorebank Avenue	
West Approach	Chatham Avenue	
Date	7/12/10	
Classification	Light Heavy	

[illegible]

TIME PERIOD	VEHICLE MOVEMENT															VEHICLE MOVEMENT															GRAND TOTAL						
	1			2			3			4			5			6			7			8			9			10				11			12		
	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ		Light	Heavy	Σ			
16:00 - 16:15	7	0	7	280	4	284													112	2	114	2	0	2	18	0	18			49	0	49	468	6	474		
16:15 - 16:30	3	0	3	300	13	313													106	2	108	2	0	2	4	0	4			17	0	17	432	15	447		
16:30 - 16:45	3	0	3	290	4	294													81	2	83	1	0	1	7	0	7			13	0	13	395	6	401		
16:45 - 17:00	4	0	4	297	5	302													73	3	76	2	0	2	4	0	4			12	0	12	392	8	400		
17:00 - 17:15	8	0	8	302	29	329													82	2	85	0	0	0	3	0	3			14	3	17	409	8	417		
17:15 - 17:30	3	0	3	298	8	306													87	1	88	5	0	5	2	0	2			12	0	12	437	7	444		
17:30 - 17:45	7	0	7	306	6	312													81	1	84	4	0	4	0	0	0			6	0	6	406	7	413		
17:45 - 18:00	6	0	6	349	8	357													79	2	81	0	0	0	4	0	4			4	0	4	442	10	452		
18:00 - 18:15	9	0	9	324	15	339													85	3	88	1	0	1	2	0	2			3	0	3	424	18	442		
18:15 - 18:30	8	0	8	339	10	349													72	0	72	1	0	1	0	0	0			5	0	5	425	10	435		
18:30 - 18:45	2	0	2	321	3	325													55	0	55	5	1	6	0	0	0			3	0	3	387	8	395		
18:45 - 19:00	1	0	1	194	5	195													54	1	55	1	0	1	2	0	2			7	0	7	259	26	285		
Σ	61	0	61	3630	89	3719													569	21	590	20	0	20	46	0	46			145	1	146	4871	111	4982		

TIME PERIOD	VEHICLE MOVEMENT												VEHICLE MOVEMENT												GRAND TOTAL		Peak				
	1		2		3		4		5		6		7		8		9		10		11		12								
	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy					
6:00 - 7:00	1	65	20	1	247									1118	41	1159		22								1452	0	1501			
6:15 - 7:15	66	1	89	915	12	327								1113	36	1149	34	0	1	1	2				13	0	13	1564	50	1614	
6:30 - 7:30	111	2	115	366	16	384								1114	38	1167	40	0	40						14	0	14	1667	52	1720	
6:45 - 7:45	119	120												1067	1125	39	39	6	2	11						20	0	20	1671	54	1725
7:00 - 8:00	112	1	113	374	21	395								1082	26	1108	32	0	32	11	3	14				20	1	21	1631	52	1683
8:15 - 9:00	340				281									1071	26	1100	26	0	26	14						17	1	18	1665	44	1719
7:30 - 8:30	55	1	56	322	22	344								1046	26	1072	18	2	20	1	1	22				22	2	24	1484	54	1538
7:45 - 8:45	43	1	44	309	20	329								991	25	1016	19	2	21	18	0	18				22	3	25	1405	51	1456
8:00 - 9:00				219	23	242								839	23	862	31	2	33							22	3	25	1381	51	1432

TIME PERIOD	VEHICLE MOVEMENT												VEHICLE MOVEMENT												GRAND TOTAL				
	1		2		3		4		5		6		7		8		9		10		11		12						
	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy			
16:00 - 17:00	17	0	17	1367	29	1193									372	9	381							91	1687	5	1722		
16:15 - 17:15	18	0	18	1189	29	1218									342	10	352	5	0	5	18	0		56	1	57	1628	40	1668
16:30 - 17:30	18	0	18	1217	24	1261									329	9	338	8	0	8	16	0		51	1	52	1634	34	1687
16:45 - 17:45	18	0	18	1253	309	839									339	8	347	3	11	14	0	0		56	4	61	1544	779	1779
17:00 - 18:00	24	0	24	1285	29	1314									331	7	338	9	0	9	9	0		56	1	57	1693	34	1767
17:15 - 18:15	24	0	24	1307	97	1344									344	7	349	9	0	9	0	0		56	1	57	1699	34	1769
17:30 - 18:30	30	0	30	1318	39	1357									346	6	352	6	0	6	6	0		18	0	18	1697	45	1742
17:45 - 18:45	25	0	25	1333	37	1370									291	6	297	3	0	3	6	0		15	0	15	1673	43	1716
18:00 - 19:00	0	0	0	1119	2	1121									2612	0	2612	0	0	0	0	0		18	0	18	2250	44	2322

Austraffic


U-TURNS		VEHICLE MOVEMENT															
		NORTHBOUND				EASTBOUND				SOUTHBOUND				WESTBOUND			
		Light		Heavy	Σ	Light		Heavy	Σ	Light		Heavy	Σ	Light		Heavy	Σ
TIME PERIOD																	
6:00	6:15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
6:15	6:30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
6:30	6:45	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0	2
6:45	7:00	0	0	0	0	0	0	0	0	0	0	0	0	2	0	2	2
7:00	7:15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:15	7:30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:30	7:45	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:45	8:00	0	0	0	0	0	0	0	0	0	0	0	0	2	2	4	0
8:00	8:15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
8:15	8:30	0	0	0	0	0	0	0	0	0	0	0	0	4	1	5	0
8:30	8:45	0	0	0	0	0	0	0	0	0	0	0	0	3	3	0	3
8:45	9:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Σ		0	0	0	0	0	0	0	0	0	0	0	0	28	5	33	0

TIME PERIOD	VEHICLE MOVEMENT															
	NORTHBOUND				EASTBOUND				SOUTHBOUND				WESTBOUND			
	Light	Heavy	Σ	%	Light	Heavy	Σ	%	Light	Heavy	Σ	%	Light	Heavy	Σ	%
16:00	16:15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
16:15	16:30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
16:30	16:45	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
16:45	17:00	0	0	0	0	0	0	1	0	0	0	11	1	1	12	1
17:00	17:15	0	0	0	0	0	0	0	0	0	0	2	2	0	2	2
17:15	17:30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
17:30	17:45	0	0	0	0	0	0	1	1	0	0	0	4	0	4	4
17:45	18:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
18:00	18:15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
18:15	18:30	0	0	0	0	0	0	0	0	0	0	0	4	4	8	8
18:30	18:45	0	0	0	0	0	0	0	0	0	0	0	3	3	0	0
18:45	19:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Σ		0	0	0	0	0	0	2	2	0	0	4	0	49	4	53

[illegible]

TIME PERIOD	VEHICLE MOVEMENT											
	NORTHBOUND			EASTBOUND			SOUTHBOUND			WESTBOUND		
	Light	Heavy	C	Light	Heavy	C	Light	Heavy	C	Light	Heavy	C
15:00	0	17:00	0	0	0	0	0	0	0	0	0	0
16:15	0	0	0	0	0	0	0	0	0	24	1	0
16:45	0	0	0	0	0	0	0	0	0	25	1	0
17:00	0	0	0	0	0	0	0	0	0	25	1	0
17:15	0	0	0	0	0	0	0	0	0	25	1	0
17:30	0	0	0	0	0	0	0	0	0	17	0	0
17:45	0	0	0	0	0	0	0	0	0	16	0	0
18:00	0	0	0	1	0	0	0	0	0	16	0	0
18:15	0	0	0	1	0	0	0	0	0	16	0	0
18:30	0	0	0	0	0	0	0	0	0	16	0	0
18:45	0	0	0	0	0	0	0	0	0	10	0	0
19:00	0	0	0	0	0	0	0	0	0	9	0	0
19:15	0	0	0	0	0	0	0	0	0	9	0	0
19:30	0	0	0	0	0	0	0	0	0	10	0	0
19:45	0	0	0	0	0	0	0	0	0	9	0	0
20:00	0	0	0	0	0	0	0	0	0	9	0	0

Tuesday, 7 December 2010

[illegible]

TIME PERIOD		VEHICLE MOVEMENT											
		NORTHBOUND			EASTBOUND			SOUTHBOUND			WESTBOUND		
		Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ
16:00	16:15	0	0	0	0	0	0	0	0	0	0	0	0
16:15	16:30	0	0	0	0	0	0	0	0	0	0	0	0
16:30	16:45	0	0	0	0	0	0	0	0	0	0	0	0
16:45	17:00	0	0	0	0	0	0	0	0	0	0	0	0
17:00	17:15	0	0	0	0	0	0	0	0	0	0	0	0
17:15	17:30	0	0	0	0	0	0	0	0	0	0	0	0
17:30	17:45	0	0	0	0	0	1	0	0	0	0	0	0
17:45	18:00	0	0	0	0	0	2	0	0	0	0	0	0
18:00	18:15	0	0	0	0	0	2	0	0	0	0	0	0
18:15	18:30	0	0	0	0	1	0	0	0	0	0	0	0
18:30	18:45	0	0	0	0	0	0	0	0	0	0	0	0
18:45	19:00	0	0	0	0	0	0	0	0	0	0	0	0
Σ		0	0	0	0	0	6	0	0	0	0	0	0


	TIME PERIOD	VEHICLE MOVEMENT											
		NORTHBOUND			EASTBOUND			SOUTHBOUND			WESTBOUND		
		Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ
	6:00 - 7:00	0	0	0	1	0	1	0	0	0	0	0	0
	6:15 - 7:15	0	0	0	1	0	1	0	0	0	0	0	0
	6:30 - 7:30	0	0	0	1	0	1	0	0	0	0	0	0
	6:45 - 7:45	0	0	0	1	0	1	0	0	0	0	0	0
	7:00 - 8:00	0	0	0	1	0	1	0	0	0	0	0	0
	7:15 - 8:15	0	0	0	0	0	0	0	0	0	0	0	0
	7:30 - 8:30	0	0	0	1	0	1	0	0	0	0	0	0
	7:45 - 8:45	0	0	0	1	0	1	0	0	0	0	0	0
	8:00 - 9:00	0	0	0	1	0	1	0	0	0	0	0	0

TIME PERIOD	VEHICLE MOVEMENT											
	NORTHBOUND			EASTBOUND			SOUTHBOUND			WESTBOUND		
	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ
16:00 - 17:00	0	0	0	1	0	1	0	0	0	0	0	0
16:15 - 17:15	0	0	0	1	0	1	0	0	0	0	0	0
16:30 - 17:30	0	0	0	0	0	0	0	0	0	0	0	0
16:45 - 17:45	0	0	0	0	0	0	0	0	0	0	0	0
17:00 - 18:00	0	0	0	2	0	2	0	0	0	0	0	0
17:15 - 18:15	0	0	0	2	0	2	0	0	0	0	0	0
17:30 - 18:30	0	0	0	4	0	4	0	0	0	0	0	0
17:45 - 18:45	0	0	0	3	0	3	0	0	0	0	0	0
18:00 - 19:00	0	0	0	3	0	3	0	0	0	0	0	0

Tuesday, 18 March 2014

Survey Start	6:00 AM	16:00 PM
Intersection Type	Cross Junction	
Intersection No.	2	
North Approach	Copeland Street	
East Approach	Elizabeth Drive	
South Approach	Copeland Street	
West Approach	Elizabeth Drive	

Classification **Light Heavy**



TIME PERIOD		VEHICLE MOVEMENT																								GRAND TOTAL													
		1			2			3			4			5			6			7			8				9			10			11			12			
		Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ		Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ				
6:00	6:15	26	4	30	225	13	288	1	0	1	12	26	38	0	29	1	0	0	0	0	0	475	38	513	30	1	91	2	6	95	74	7	76	93	8	811	106	917	
6:15	6:30	37	5	42	338	26	362	3	0	3	21	12	19	5	24	0	1	0	0	0	512	34	546	38	0	36	105	10	7	97	103	8	811	116	927				
6:30	6:45	45	4	49	335	27	362	6	3	9	16	0	16	27	3	30	0	2	2	0	567	35	592	29	2	31	86	3	89	112	2	114	96	7	103	130	88	1477	
6:45	7:00	30	5	35	270	20	290	0	0	0	10	10	16	26	0	26	0	0	0	0	567	36	603	23	0	32	122	3	125	133	2	135	136	8	144	161	100	1548	
7:00	7:15	58	7	65	270	28	302	6	0	6	9	0	19	0	19	0	0	0	0	0	597	36	633	23	0	32	122	3	125	133	2	135	136	8	144	161	100	1548	
7:15	7:30	59	7	66	305	27	332	11	0	11	18	5	21	63	9	72	1	0	0	0	525	39	564	14	3	17	70	6	76	175	7	182	127	17	1396	114	1509		
7:30	7:45	58	7	65	307	26	333	12	0	12	16	4	24	63	9	78	1	1	2	0	1	599	21	580	27	3	28	79	7	86	167	4	171	99	10	109	1427	85	1212
7:45	8:00	54	6	60	282	25	307	15	0	15	23	2	25	58	10	68	0	0	0	0	512	34	546	38	0	36	105	10	7	97	103	8	811	116	927				
8:00	8:15	78	10	88	344	34	378	18	0	18	26	5	31	10	16	26	0	0	0	0	512	34	546	38	0	36	105	10	7	97	103	8	811	116	927				
8:15	8:30	60	7	67	322	35	357	18	1	19	24	0	24	102	5	107	10	0	0	0	454	33	487	31	1	32	105	7	112	224	5	229	127	5	132	1474	90	1614	
8:30	8:45	69	7	76	399	39	438	27	0	27	36	1	37	96	3	99	9	0	0	0	0	546	36	402	17	3	20	109	13	129	247	4	256	129	8	137	1504	118	1622
8:45	9:00	69	7	76	399	39	438	27	0	27	36	1	37	96	3	99	9	0	0	0	0	546	36	402	17														
Σ		649	68	714	823	354	1477	158	6	163	274	15	289	754	69	819	49	57	1	0	1	5946	300	6329	37	29	345	1156	70	1229	307	62	609	1412	98	1507	2027	1512	1777

TIME PERIOD		VEHICLE MOVEMENT																								VEHICLE MOVEMENT																								GRAND TOTAL	
		1		2		3		4		5		6		7		8		9		10		11		12																											
		Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy																										
16:00	16:15	134	8	142	473	20	493	18	0	18	36	1	37	236	7	243	21	0	21	0	0	294	26	320	69	3	72	80	0	80	130	7	137	56	3	59	1547	75	122												
16:15	16:30	203	4	207	508	25	533	15	0	15	41	2	43	198	4	202	22	0	22	0	0	322	27	349	67	7	74	85	3	88	128	6	134	67	4	71	1657	80	173												
16:30	16:45	165	11	176	528	20	547	17	1	18	31	0	31	205	5	210	24	27	0	27	0	0	325	17	342	60	7	64	76	4	80	117	6	123	73	32	77	1545	68	174											
16:45	17:00	165	10	175	520	18	537	17	0	17	32	0	32	205	5	210	24	27	0	27	0	0	325	17	342	60	7	64	76	4	80	117	6	123	73	32	77	1545	68	174											
17:00	17:15	188	4	192	515	15	530	12	0	12	40	0	40	200	6	206	21	0	21	0	0	284	17	301	55	5	57	74	7	78	97	5	102	55	65	1594	62	116													
17:15	17:30	229	6	235	501	9	510	11	0	11	43	0	43	230	4	234	23	23	0	23	0	0	350	13	363	69	6	72	85	6	90	106	11	117	72	23	85	1687	47	174											
17:30	17:45	188	7	195	495	12	507	9	2	11	26	1	27	208	4	212	22	0	22	0	0	369	14	323	65	1	66	71	7	71	106	4	110	47	48	1546	56	159													
17:45	18:00	173	3	176	473	12	487	14	0	14	34	1	35	265	14	279	22	0	22	0	0	287	11	290	85	0	85	77	2	79	120	4	124	65	72	1515	57	1572													
18:00	18:15	194	4	198	490	13	503	6	0	6	39	0	39	182	4	186	19	0	19	0	0	289	9	298	66	1	67	82	3	85	96	6	75	1352	43	1475															
18:15	18:30	207	2	210	503	10	513	5	0	5	15	14	0	14	181	6	187	16	0	16	0	0	327	13	341	67	6	69	75	7	75	89	5	104	56	62	1448	59	1507												
18:30	18:45	155	1	156	430	4	434	18	0	18	31	5	36	211	2	213	18	0	18	0	0	277	14	291	63	6	69	75	8	83	90	6	97	118	47	1128	43	1171													
18:45	19:00	125	3	128	360	10	376	8	0	8	9	21	1	22	98	5	103	12	0	12	0	0	273	24	231	63	13	63	73	7	73	75	7	78	63	67	1128	43	1171												
Σ		2138	59	2195	5791	186	5877	151	6	157	968	6	374	2322	69	2391	249	2	251	0	0	0	3574	173	3774	827	39	856	874	15	889	1291	56	1347	760	51	811	8343	652	1895											


TIME PERIOD	VEHICLE MOVEMENT												VEHICLE MOVEMENT												GRAND TOTAL	Peak									
	1		2		3		4		5		6		7		8		9		10		11		12												
	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy													
6:00 - 7:00	145	144	1772	98	1270	27	4	81	2	66	107	15	123	4	4	13	0	0	0	0	2031	128	2189	125	11	131	389	23	409	438	15	472	473	339	513
7:00 - 8:00	115	159	15	174	2274	14	370	27	4	81	2	73	147	19	15	4	13	0	0	0	2176	128	2189	125	11	131	389	23	409	438	15	462	508	367	503
8:00 - 9:00	7	15	184	14	1184	14	370	27	4	81	2	73	147	19	15	4	13	0	0	0	2176	128	2189	125	11	131	389	23	409	438	15	462	508	367	503
9:00 - 10:00	8	15	184	14	1184	14	370	27	4	81	2	73	147	19	15	4	13	0	0	0	2176	128	2189	125	11	131	389	23	409	438	15	462	508	367	503
10:00 - 11:00	8	15	184	14	1184	14	370	27	4	81	2	73	147	19	15	4	13	0	0	0	2176	128	2189	125	11	131	389	23	409	438	15	462	508	367	503
11:00 - 12:00	8	15	184	14	1184	14	370	27	4	81	2	73	147	19	15	4	13	0	0	0	2176	128	2189	125	11	131	389	23	409	438	15	462	508	367	503
12:00 - 1:00	8	15	184	14	1184	14	370	27	4	81	2	73	147	19	15	4	13	0	0	0	2176	128	2189	125	11	131	389	23	409	438	15	462	508	367	503
1:00 - 2:00	8	15	184	14	1184	14	370	27	4	81	2	73	147	19	15	4	13	0	0	0	2176	128	2189	125	11	131	389	23	409	438	15	462	508	367	503
2:00 - 3:00	8	15	184	14	1184	14	370	27	4	81	2	73	147	19	15	4	13	0	0	0	2176	128	2189	125	11	131	389	23	409	438	15	462	508	367	503
3:00 - 4:00	8	15	184	14	1184	14	370	27	4	81	2	73	147	19	15	4	13	0	0	0	2176	128	2189	125	11	131	389	23	409	438	15	462	508	367	503
4:00 - 5:00	8	15	184	14	1184	14	370	27	4	81	2	73	147	19	15	4	13	0	0	0	2176	128	2189	125	11	131	389	23	409	438	15	462	508	367	503
5:00 - 6:00	8	15	184	14	1184	14	370	27	4	81	2	73	147	19	15	4	13	0	0	0	2176	128	2189	125	11	131	389	23	409	438	15	462	508	367	503

TIME PERIOD	VEHICLE MOVEMENT																								GRAND TOTAL			
	1		2		3		4		5		6		7		8		9		10		11		12					
	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy				
15:00 - 17:00	710	26	736	208	613	232	66	145	248	870	102	104	9	130	1350	222	16	274	297	602	624	269	287	633	288	6803		
17:00 - 18:00	146	24	170	68	209	78	219	60	2	61	149	2	153	807	25	104	0	0	0	259	460	0	0	268	657	272	519	
18:00 - 19:00	284	24	308	24	312	24	312	24	3	38	100	0	130	669	0	105	0	0	0	273	479	0	0	273	500	237	616	
19:00 - 20:00	174	24	198	24	202	24	202	24	0	0	0	0	0	0	0	0	0	0	0	273	479	0	0	273	500	237	616	
20:00 - 21:00	178	20	198	14	212	14	212	14	4	50	131	2	132	923	26	85	88	0	0	0	249	429	0	0	249	429	209	638
21:00 - 22:00	180	20	200	14	214	14	214	14	4	50	131	2	132	923	26	85	88	0	0	0	249	429	0	0	249	429	209	638
22:00 - 23:00	180	20	200	14	214	14	214	14	4	50	131	2	132	923	26	85	88	0	0	0	249	429	0	0	249	429	209	638
23:00 - 00:00	180	20	200	14	214	14	214	14	4	50	131	2	132	923	26	85	88	0	0	0	249	429	0	0	249	429	209	638
00:00 - 01:00	180	20	200	14	214	14	214	14	4	50	131	2	132	923	26	85	88	0	0	0	249	429	0	0	249	429	209	638
01:00 - 02:00	180	20	200	14	214	14	214	14	4	50	131	2	132	923	26	85	88	0	0	0	249	429	0	0	249	429	209	638
02:00 - 03:00	180	20	200	14	214	14	214	14	4	50	131	2	132	923	26	85	88	0	0	0	249	429	0	0	249	429	209	638
03:00 - 04:00	180	20	200	14	214	14	214	14	4	50	131	2	132	923	26	85	88	0	0	0	249	429	0	0	249	429	209	638
04:00 - 05:00	180	20	200	14	214	14	214	14	4	50	131	2	132	923	26	85	88	0	0	0	249	429	0	0	249	429	209	638
05:00 - 06:00	180	20	200	14	214	14	214	14	4	50	131	2	132	923	26	85	88	0	0	0	249	429	0	0	249	429	209	638
06:00 - 07:00	180	20	200	14	214	14	214	14	4	50	131	2	132	923	26	85	88	0	0	0	249	429	0	0	249	429	209	638

Tuesday, 18 March 2014

Survey Start	6:00 AM	16:00 PM
Intersection Type	Cross Junction	
Intersection No.	3	
North Approach	Copeland Street	
East Approach	Memorial Avenue	
South Approach	Copeland Street	
West Approach	Memorial Avenue	

Classification **Light Heavy**



TIME PERIOD		VEHICLE MOVEMENT																								GRAND TOTAL														
		1		2		3		4		5		6		7		8		9		10		11		12																
		Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy															
16:00	16:15	36	1	37	600	21	621	38	0	38	39	3	42	59	4	63	13	0	13	38	5	43	342	27	369	26	0	26	29	0	29	39	2	41	14	0	14	1273	63	1336
16:15	16:30	41	4	45	582	28	590	24	2	26	46	4	50	50	2	52	15	0	15	29	0	29	349	28	367	28	2	30	31	0	31	43	1	44	21	25	1272	73	1345	
16:30	16:45	32	1	33	614	24	638	35	1	36	34	1	35	54	1	55	13	0	13	33	0	33	343	24	367	24	1	25	39	0	39	27	1	28	17	14	1338	55	1393	
16:45	17:00	18	42	60	614	24	638	35	1	36	34	1	35	54	1	55	13	0	13	33	0	33	343	24	367	24	1	25	39	0	39	27	1	28	17	14	1338	55	1393	
17:00	17:15	42	1	43	652	20	672	31	1	32	32	3	35	53	1	54	12	0	12	18	5	23	28	25	317	20	0	20	36	0	36	34	1	35	18	0	18	1357	46	1403
17:15	17:30	49	0	49	663	14	677	38	2	38	37	3	40	56	4	60	10	0	10	26	0	26	373	15	388	27	0	27	26	0	26	48	0	48	10	0	10	1299	56	1355
17:30	17:45	47	1	48	557	18	575	38	1	39	32	2	34	50	0	50	5	0	5	27	0	27	318	15	333	31	0	31	17	0	17	39	1	40	24	0	24	1195	36	1231
17:45	18:00	45	1	46	520	15	535	24	0	24	45	0	45	64	0	64	10	0	10	26	0	26	327	14	341	27	0	27	27	0	27	41	0	41	16	1	17	1172	31	1203
18:00	18:15	55	1	56	540	21	561	45	0	45	38	2	40	53	1	54	12	0	12	31	1	31	322	13	335	26	1	27	24	0	24	44	1	45	30	0	30	1220	40	1260
18:15	18:30	45	1	46	525	13	538	39	1	40	31	1	32	48	11	59	11	0	11	30	0	30	314	13	327	24	1	25	22	0	22	45	0	45	20	0	20	1179	29	1208
18:30	18:45	40	0	40	450	11	461	33	0	33	40	0	40	37	24	58	10	0	10	23	0	23	300	24	324	24	1	25	22	0	22	45	0	45	20	0	20	1159	20	1179
18:45	19:00	38	0	38	373	11	384	36	1	37	41	1	42	56	0	56	5	0	5	23	0	23	274	7	241	30	0	30	20	0	20	39	0	39	24	0	24	819	29	848
Σ		526	9	535	6591	229	6820	406	9	415	498	24	522	645	15	661	123	0	123	335	5	340	878	215	4093	345	4	349	30	0	330	484	8	492	23	3	236	4193	521	1415


TIME PERIOD	VEHICLE MOVEMENT												VEHICLE MOVEMENT												GRAND TOTAL	Peak												
	1			2			3			4			5			6			7			8					9			10			11			12		
	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ			Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ			
16:00 - 17:00	15	5	174	2393	92	2496	327	3	327	137	12	180	229	7	236	50	127	5	132	1307	1484	133	3	118	136	4	138	168	4	172	7	75	5145	2297	5382			
16:15 - 17:15	174	5	174	2445	91	2436	314	4	312	109	12	180	223	4	221	49	8	49	107	1340	1499	1439	107	3	110	143	3	143	16	143	163	4	170	77	27	5145	2232	5338
16:30 - 17:30	174	5	174	2445	91	2436	314	4	312	109	12	180	223	4	221	49	8	49	107	1340	1499	1439	107	3	110	143	3	143	16	143	163	4	170	77	27	5145	2232	5338
16:45 - 17:45	174	5	174	2445	91	2436	314	4	312	109	12	180	223	4	221	49	8	49	107	1340	1499	1439	107	3	110	143	3	143	16	143	163	4	170	77	27	5145	2232	5338
17:00 - 18:00	180	3	180	2330	67	2297	120	4	124	146	8	154	223	5	228	37	0	37	87	9	1311	166	1379	105	0	105	168	2	168	162	2	164	68	99	4999	156	5055	
17:15 - 18:15	180	3	180	2330	67	2297	120	4	124	146	8	154	223	5	228	37	0	37	87	9	1311	166	1379	105	0	105	168	2	168	162	2	164	68	99	4999	156	5055	
17:30 - 18:30	180	3	180	2330	67	2297	120	4	124	146	8	154	223	5	228	37	0	37	87	9	1311	166	1379	105	0	105	168	2	168	162	2	164	68	99	4999	156	5055	
17:45 - 18:45	180	3	180	2330	67	2297	120	4	124	146	8	154	223	5	228	37	0	37	87	9	1311	166	1379	105	0	105	168	2	168	162	2	164	68	99	4999	156	5055	
18:00 - 19:00	180	3	180	2330	67	2297	120	4	124	146	8	154	223	5	228	37	0	37	87	9	1311	166	1379	105	0	105	168	2	168	162	2	164	68	99	4999	156	5055	
18:15 - 19:15	180	3	180	2330	67	2297	120	4	124	146	8	154	223	5	228	37	0	37	87	9	1311	166	1379	105	0	105	168	2	168	162	2	164	68	99	4999	156	5055	
18:30 - 19:30	180	3	180	2330	67	2297	120	4	124	146	8	154	223	5	228	37	0	37	87	9	1311	166	1379	105	0	105	168	2	168	162	2	164	68	99	4999	156	5055	

Tuesday, 18 March 2014

Survey Start	6:00 AM	16:00 PM
Intersection Type	Cross Junction	
Intersection No.	4	
North Approach	Copeland Street	
East Approach	Macquaire Street	
South Approach	Hume Highway	
West Approach	Hoxton Park Road	

Date 18/03/14

Classification **Light Heavy**



TIME PERIOD		VEHICLE MOVEMENT												VEHICLE MOVEMENT												GRAND TOTAL													
		1			2			3			4			5			6			7			8				9			10			11			12			
		Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ		Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ				
18:00	16:15	50	4	54	508	18	576	38	0	0	0	0	142	7	155	143	3	142	105	3	108	351	24	349	20	2	22	75	2	77	127	129	83	4	47	1632	75	1607	
18:15	16:30	40	4	44	525	20	545	25	1	26	0	0	146	8	154	143	3	144	100	1	101	365	27	376	27	5	32	51	2	53	113	2	115	43	6	49	1586	76	1662
18:30	16:45	40	4	52	584	20	604	29	3	32	0	0	139	7	146	164	2	166	111	3	114	340	24	364	43	46	78	2	80	128	7	135	96	2	58	1737	77	1814	
18:45	17:00	40	4	52	584	20	604	29	3	32	0	0	139	7	146	164	2	166	111	3	114	340	24	364	43	46	78	2	80	128	7	135	96	2	58	1737	77	1814	
18:45	17:00	40	4	52	584	20	604	29	3	32	0	0	139	7	146	164	2	166	111	3	114	340	24	364	43	46	78	2	80	128	7	135	96	2	58	1737	77	1814	
18:45	17:00	40	4	52	584	20	604	29	3	32	0	0	139	7	146	164	2	166	111	3	114	340	24	364	43	46	78	2	80	128	7	135	96	2	58	1737	77	1814	
18:45	17:00	40	4	52	584	20	604	29	3	32	0	0	139	7	146	164	2	166	111	3	114	340	24	364	43	46	78	2	80	128	7	135	96	2	58	1737	77	1814	
18:45	17:00	40	4	52	584	20	604	29	3	32	0	0	139	7	146	164	2	166	111	3	114	340	24	364	43	46	78	2	80	128	7	135	96	2	58	1737	77	1814	
18:45	17:00	40	4	52	584	20	604	29	3	32	0	0	139	7	146	164	2	166	111	3	114	340	24	364	43	46	78	2	80	128	7	135	96	2	58	1737	77	1814	
18:45	17:00	40	4	52	584	20	604	29	3	32	0	0	139	7	146	164	2	166	111	3	114	340	24	364	43	46	78	2	80	128	7	135	96	2	58	1737	77	1814	
18:45	17:00	40	4	52	584	20	604	29	3	32	0	0	139	7	146	164	2	166	111	3	114	340	24	364	43	46	78	2	80	128	7	135	96	2	58	1737	77	1814	


TIME PERIOD	VEHICLE MOVEMENT																								GRAND TOTAL																				
	1			2			3			4			5			6			7			8				9			10			11			12										
	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ		Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ											
18:00	17:00	180	5	195	2296	78	2374	109	5	114	0	0	572	35	605	600	8	610	411	5	416	0	0	418	1348	91	1439	122	12	134	2796	5	2801	52	2853	512	17	529	216	231	6060	288	6612		
18:15	17:15	169	15	184	2341	74	2415	6	102	0	0	0	562	35	597	633	633	61	694	5	699	0	0	614	988	5	993	120	10	130	2715	26	2741	58	2799	513	18	531	167	17	200	6810	383	6613	
18:30	17:30	169	15	184	2341	74	2415	6	102	0	0	0	562	35	597	633	633	61	694	5	699	0	0	614	988	5	993	120	10	130	2715	26	2741	58	2799	513	18	531	167	17	200	6810	383	6613	
18:45	17:45	181	12	193	2607	58	2665	8	85	0	0	0	576	150	726	610	610	8	618	0	618	0	0	626	866	6	872	100	10	110	2621	32	2653	54	2707	321	33	551	104	551	104	20	6747	202	6949
17:00	18:00	1120	0	1120	2324	56	2380	83	7	90	0	0	0	576	15	591	634	634	6	640	0	640	0	0	646	976	2	978	100	10	110	2521	32	2553	54	2607	321	33	551	104	551	104	20	6949	
17:15	18:15	1120	0	1120	2324	56	2380	83	7	90	0	0	0	576	15	591	634	634	6	640	0	640	0	0	646	976	2	978	100	10	110	2521	32	2553	54	2607	321	33	551	104	551	104	20	6949	
17:30	18:30	227	6	233	2191	57	2248	0	0	88	0	0	0	576	150	726	610	610	8	618	0	618	0	0	626	866	6	872	100	10	110	2621	32	2653	54	2707	321	33	551	104	551	104	20	6747	
17:45	18:45	227	6	233	2191	57	2248	0	0	88	0	0	0	576	150	726	610	610	8	618	0	618	0	0	626	866	6	872	100	10	110	2621	32	2653	54	2707	321	33	551	104	551	104	20	6747	
18:00	19:00	240	8	248	1980	80	2060	80	5	85	0	0	0	572	15	587	634	634	6	640	0	640	0	0	646	976	2	978	100	10	110	2521	32	2553	54	2607	321	33	551	104	551	104	20	6949	
18:15	19:15	240	8	248	1980	80	2060	80	5	85	0	0	0	572	15	587	634	634	6	640	0	640	0	0	646	976	2	978	100	10	110	2521	32	2553	54	2607	321	33	551	104	551	104	20	6949	

Tuesday, 18 March 2014

Survey Start	6:00 AM	16:00 PM
Intersection Type	Cross Junction	
Intersection No.	5	
North Approach	Hume Highway	
East Approach	Congressional Drive	
South Approach	Hume Highway	
West Approach	Reilly Street	

Date 18/03/14

Classification **Light Heavy**



TIME PERIOD	VEHICLE MOVEMENT																VEHICLE MOVEMENT																GRAND TOTAL																		
	1		2		3		4		5		6		7		8		9		10		11		12		13		14		15		16																				
	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy																					
6.00 - 6.15	4	0	4	282	12	294	2	0	2	12	0	12	1	0	1	2	0	2	3	0	3	476	19	495	11	0	11	37	0	37	1	0	1	12	0	12	0	0	0	0	0	0	0	843	31	874					
6.15 - 6.30	6	0	6	354	28	382	0	0	0	9	0	9	2	0	2	7	0	7	0	0	2	642	36	678	12	0	12	31	1	32	0	0	0	0	9	1	10	0	0	0	0	0	0	0	0	1074	66	1140			
6.30 - 6.45	8	1	9	405	37	442	1	1	2	16	0	16	1	0	1	4	1	5	0	0	0	653	27	680	9	0	9	57	3	60	0	0	0	0	9	0	9	0	0	0	0	0	0	0	0	0	1163	70	1233		
6.45 - 7.00	12	0	12	367	27	394	2	1	3	11	0	11	2	0	2	5	0	5	1	1	1	716	32	748	15	1	16	34	4	38	1	0	1	14	0	14	0	0	0	0	0	0	0	0	0	0	1180	65	1245		
7.00 - 7.15	2	0	2	314	38	352	2	0	2	19	0	19	1	0	1	5	1	6	1	1	1	745	40	785	12	1	13	50	0	50	0	0	0	0	10	1	11	0	0	0	0	1	0	1	0	0	0	1162	81	1243	
7.15 - 7.30	7	0	7	353	21	374	2	0	2	15	0	15	1	0	1	8	1	9	1	1	1	745	30	775	15	1	16	51	1	52	1	0	1	15	2	17	0	0	0	0	0	0	1	0	1	0	0	0	1215	56	1271
7.30 - 7.45	14	0	14	345	28	373	0	0	0	10	0	10	3	0	3	6	1	7	4	0	4	677	22	699	13	0	13	49	1	50	1	0	1	16	0	16	0	0	0	0	2	0	2	0	0	0	0	1140	52	1192	
7.45 - 8.00	10	0	10	325	25	350	6	0	6	18	2	20	7	0	7	7	1	8	1	2	2	622	11	633	12	0	12	50	0	50	3	0	3	20	1	21	0	0	0	0	0	0	0	0	0	0	0	1081	41	1122	
8.00 - 8.15	15	1	16	354	28	382	4	0	4	15	1	16	13	1	14	14	0	14	2	0	2	697	27	724	19	1	20	43	1	44	1	1	2	18	1	19	0	0	0	0	0	0	0	0	0	0	0	1195	62	1257	
8.15 - 8.30	32	0	32	393	30	423	7	0	7	17	0	17	8	0	8	11	0	11	3	3	3	628	30	658	10	1	11	56	3	59	4	0	4	31	2	33	0	0	0	0	0	0	0	0	0	0	0	0	1200	66	1266
8.30 - 8.45	26	0	26	380	30	410	9	1	10	20	0	20	8	1	9	7	0	7	5	5	5	646	30	676	26	0	26	47	0	47	2	0	2	21	0	21	0	0	0	0	0	0	0	0	0	0	0	1197	62	1259	
8.45 - 9.00	28	0	28	370	29	399	12	3	15	10	1	11	6	2	8	6	0	6	7	0	7	627	36	663	15	0	15	54	3	57	6	0	6	23	0	23	0	0	0	0	0	0	0	0	0	0	0	0	1164	74	1238
Σ	164	2	166	4242	333	4575	47	6	53	172	4	176	53	4	57	82	5	87	30	1	31	7874	340	8214	169	5	174	559	17	576	20	1	21	198	8	206	0	0	0	0	0	0	4	0	4	0	0	0	13614	726	14340


[illegible][illegible]

TIME PERIOD	VEHICLE MOVEMENT																VEHICLE MOVEMENT																GRAND TOTAL		Peak											
	1		2		3		4		5		6		7		8		9		10		11		12		13		14		15		16															
	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy	Σ	Light	Heavy				Σ										
16:00 - 17:00	165	3	168	3024	80	3104	56	1	57	41	0	41	19	0	19	34	1	35	21	1	22	1787	99	1886	201	6	207	220	5	225	24	1	25	37	1	38	0	0	0	0	5629	198	5827			
16:15 - 17:15	165	3	168	3032	82	3114	57	0	57	42	0	42	22	0	22	37	1	38	22	0	22	1791	92	1883	196	5	201	211	5	216	28	1	29	45	0	45	1	0	1	0	0	5597	199	5796		
16:30 - 17:30	165	3	168	3053	83	3136	58	0	58	42	0	42	23	0	23	39	1	40	22	1	23	1798	93	1891	202	6	208	212	5	217	28	1	29	45	0	45	1	0	1	0	0	5630	200	5830		
16:45 - 17:45	146	2	147	3158	62	3220	59	0	59	40	0	40	25	0	25	39	1	40	22	1	23	1793	92	1885	215	0	215	216	2	218	21	0	21	51	0	51	0	1	0	1	0	0	5753	140	5893	
17:00 - 18:00	163	2	165	3134	58	3193	67	0	67	42	0	42	23	1	24	39	1	40	24	1	25	1775	65	1840	209	1	210	209	1	209	23	0	23	49	2	51	0	2	0	2	0	0	5767	124	5891	
17:15 - 18:15	155	2	157	3034	55	3089	69	0	69	43	0	43	21	1	22	38	0	38	22	1	23	1828	57	1885	212	1	213	201	1	202	25	0	25	48	0	48	1	0	1	0	2	0	0	5699	118	5817
17:30 - 18:30	159	4	163	2931	54	2985	63	0	63	45	0	45	22	0	22	33	0	33	23	0	23	1865	48	1913	201	2	203	181	1	182	26	0	26	55	0	55	0	2	0	0	0	5426	110	5536		
17:45 - 18:45	150	4	154	2824	50	2874	63	0	63	45	0	45	22	0	22	33	0	33	23	0	23	1784	49	1833	202	2	204	182	1	183	26	0	26	55	0	55	0	2	0	0	0	5426	110	5536		
18:00 - 19:00	120	3	123	2229	62	2291	46	0	46	44	0	44	22	0	22	26	0	26	20	0	20	1662	45	1707	155	1	156	139	2	141	24	0	24	47	0	47	0	2	0	2	0	0	4536	113	4649	

Tuesday, 18 March 2014

Survey Start	6:00 AM	16:00 PM
Intersection Type	Cross Junction	
Intersection No.	13	
North Approach	Governor Macquire Drive	
East Approach	Newbridge Road	
South Approach	Brickmakers Drive	
West Approach	Newbridge Road	

Classification **Light Heavy**



TIME PERIOD	VEHICLE MOVEMENT																VEHICLE MOVEMENT																GRAND TOTAL																			
	1		2		3		4		5		6		7		8		9		10		11		12		13		14		15		16																					
	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy																				
16:00 - 17:00	128	39	167	194	1	195	360	23	383	556	67	623	1938	111	2049	497	4	501	207	5	212	73	3	76	10	1	11	3	0	3	1252	98	1350	127	22	149	0	0	0	0	1	0	1	0	0	0	2	0	2	5348	374	5722
16:15 - 17:15	147	37	184	227	1	228	395	24	419	548	60	608	2025	122	2147	542	7	549	202	4	206	72	3	75	6	0	6	3	0	3	1330	93	1423	117	23	140	0	0	0	0	1	0	1	0	0	1	5616	374	5990			
16:30 - 17:30	156	37	193	232	1	243	433	16	449	554	63	617	2049	144	2193	541	8	549	212	2	209	61	3	75	6	0	6	3	0	3	1409	91	1500	119	24	140	0	0	0	0	1	0	1	0	0	1	5914	374	6288			
16:45 - 17:45	162	35	197	244	2	246	422	13	435	577	59	636	2091	79	2170	555	6	561	184	3	187	78	3	81	11	0	0	0	0	2	1477	90	1567	109	22	131	0	0	0	0	1	0	1	0	0	1	5914	312	6226			
17:00 - 18:00	157	21	178	216	2	218	408	12	420	556	59	615	2090	81	2171	556	5	561	172	3	175	60	2	62	8	0	8	4	0	4	1498	89	1587	113	20	133	0	0	0	0	0	0	0	0	0	0	5838	294	6132			
17:15 - 18:15	152	14	166	175	2	177	378	9	387	593	58	651	2016	76	2092	546	5	551	167	1	168	59	1	60	8	0	8	5	0	5	1366	83	1449	110	17	127	0	0	0	0	0	0	1	0	1	5576	266	5842				
17:30 - 18:30	132	13	145	131	0	131	308	11	319	595	50	645	1941	67	2028	555	7	562	138	1	159	57	2	59	6	0	6	8	0	8	1233	73	1306	114	16	130	0	0	0	0	0	0	0	0	0	1	5239	260	5499			
17:45 - 18:45	107	10	118	107	0	107	238	10	248	557	50	607	1913	54	2007	547	6	557	153	0	153	54	1	55	8	0	8	5	0	5	1250	67	1317	112	14	126	0	0	0	0	0	0	0	0	0	5193	260	5453				
18:00 - 19:00	102	10	112	116	0	112	239	11	250	554	41	595	1555	77	1632	485	6	491	149	0	149	69	2	71	8	0	8	5	0	6	903	50	953	101	19	110	0	0	0	0	0	0	2	0	2	4287	209	4496				

Appendix B

Intersection performance indicators

The operation of key intersections within was assessed using the SIDRA intersection modelling software. SIDRA calculates intersection performance measures including:

- level of service (LoS)
- degree of saturation (DoS)
- average delay
- queue length.

Level of Service (LoS)

Level of Service (LoS) is a basic performance parameter used to describe the operation of an intersection. Levels of service range from A (indicating good intersection operation) to F (indicating over-saturated conditions with long delays and queues). At signalised intersections, the LoS criteria are related to average intersection delay (seconds per vehicle). At priority controlled (give-way and stop controlled) and roundabout intersections, the LoS is based on the modelled delay (seconds per vehicle) for the most delayed movement (refer to Table 1).

Degree of saturation (DoS)

The Degree of Saturation (DoS) is the ratio of demand flow to capacity, and therefore has no unit. As it approaches 1.0, extensive queues and delays could be expected. For a satisfactory situation, DoS should be less than the nominated practical degree of saturation, usually 0.9. The intersection DoS is based on the movement with the highest value.

Average vehicle delay

This is the difference between interrupted and uninterrupted travel times through the intersection and is measured in seconds per vehicle. At signalised intersections the average intersection delay is usually reported. At priority controlled intersections and roundabouts, the average delay for the most delayed movement is usually reported.

Queue length

Queue length is measured in metres reflecting the number of vehicles waiting at the stop line and is usually quoted as the 95th percentile back of queue, which is the value below which 95% of all observed queue lengths fall. It reflects the number of vehicles per traffic lane at the start of the green period, when traffic starts moving again after a red signal. The intersection queue length is usually taken from the movement with the longest queue length.

Table 1 Level of Service criteria for intersections

Level of Service	Average delay (seconds per vehicle)	Traffic signals, roundabout	Give Way and stop signs
A	Less than 14	Good operation	Good operation
B	15 to 28	Good with acceptable delays and spare capacity	Acceptable delays and spare capacity
C	29 to 42	Satisfactory	Satisfactory, but accident study required
D	43 to 56	Operating near capacity	Near capacity and accident study required
E	57 to 70	At capacity. At signals, incidents would cause excessive delays. Roundabouts require other control mode.	At capacity; requires other control mode
F	Greater than 71	Unsatisfactory with excessive queuing	Unsatisfactory with excessive queuing; requires other control mode

Source: RMS Guide to Traffic Generating Developments, 2002

Appendix C

2014 existing year SIDRA results

1. 2014 Existing year – Moorebank Avenue

I-01 Intersection of Moorebank Avenue and Bapaume Road

MOVEMENT SUMMARY

▽ Site: I-01 2014 BASE AM

Intersection of Moorebank Avenue and Bapaume Road

2014 BASE AM PEAK 6:45 am - 7:45 am

Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
1	L2	19	0.0	0.010	8.2	LOS A	0.0	0.0	0.00	0.67	36.0
2	T1	1053	5.3	0.558	0.0	LOS A	0.0	0.0	0.00	0.00	59.8
Approach		1072	5.2	0.558	0.2	NA	0.0	0.0	0.00	0.01	59.1
North: Moorebank Avenue (S)											
8	T1	824	5.4	0.333	3.8	LOS A	3.8	27.8	0.24	0.08	50.7
9	R2	80	1.3	0.333	24.0	LOS B	3.8	27.8	1.00	0.32	34.1
Approach		904	5.0	0.333	5.6	NA	3.8	27.8	0.31	0.10	48.6
West: Bapaume Road (W)											
10	L2	3	33.3	0.018	27.5	LOS B	0.1	0.5	0.84	0.92	26.2
12	R2	1	0.0	0.057	183.7	LOS F	0.1	1.0	0.98	0.99	6.2
Approach		4	25.0	0.057	66.5	LOS E	0.1	1.0	0.87	0.94	14.5
All Vehicles		1980	5.2	0.558	2.8	NA	3.8	27.8	0.14	0.05	51.5

MOVEMENT SUMMARY

▽ Site: I-01 2014 BASE PM

Intersection of Moorebank Avenue and Bapaume Road

2014 BASE AM PEAK 5:00 pm - 6:00 pm

Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h	
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.001	8.2	LOS A	0.0	0.0	0.00	0.67	36.0
2	T1	521	4.4	0.275	0.0	LOS A	0.0	0.0	0.00	0.00	59.9
Approach		522	4.4	0.275	0.0	NA	0.0	0.0	0.00	0.00	59.9
North: Moorebank Avenue (S)											
8	T1	1388	2.8	0.375	2.6	LOS A	5.6	40.2	0.33	0.01	52.1
9	R2	19	11.1	0.375	13.6	LOS A	5.6	40.2	0.69	0.03	45.7
Approach		1407	2.9	0.375	2.8	NA	5.6	40.2	0.34	0.01	52.0
West: Bapaume Road (W)											
10	L2	88	3.6	0.135	11.8	LOS A	0.5	3.8	0.53	0.79	38.5
12	R2	13	0.0	0.422	165.1	LOS F	1.2	8.5	0.98	1.02	6.8
Approach		101	3.1	0.422	31.0	LOS C	1.2	8.5	0.59	0.81	24.4
All Vehicles		2031	3.3	0.422	3.5	NA	5.6	40.2	0.26	0.05	50.3

I-02 Intersection of Moorebank Avenue and Anzac Road

MOVEMENT SUMMARY



Site: I-02 2014 BASE AM

Intersection of Moorebank Avenue and Anzac Road

2014 BASE AM PEAK 6:45 am - 7:45 am

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
2	T1	895	3.4	0.690	10.6	LOS A	26.7	192.7	0.66	0.61	44.3
3	R2	334	3.5	0.642	23.3	LOS B	11.2	80.9	0.71	0.82	36.5
Approach		1228	3.4	0.690	14.0	LOS A	26.7	192.7	0.67	0.67	41.9
East: Anzac Road (E)											
4	L2	218	3.4	0.688	53.2	LOS D	10.7	77.3	0.99	0.85	24.3
6	R2	192	13.7	0.648	52.4	LOS D	9.3	72.9	0.98	0.83	24.6
Approach		409	8.2	0.688	52.8	LOS D	10.7	77.3	0.99	0.84	24.5
North: Moorebank Avenue (N)											
7	L2	263	10.0	0.172	8.3	LOS A	0.9	7.1	0.15	0.63	35.8
8	T1	565	3.4	0.329	6.9	LOS A	8.7	62.5	0.42	0.37	35.7
Approach		828	5.5	0.329	7.3	LOS A	8.7	62.5	0.34	0.45	35.7
All Vehicles		2466	4.9	0.690	18.2	LOS B	26.7	192.7	0.61	0.62	35.6

PHASING SUMMARY



Site: I-02 2014 BASE AM


Intersection of Moorebank Avenue and Anzac Road

2014 BASE AM PEAK 6:45 am - 7:45 am

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C
Phase Change Time (sec)	0	76
Green Time (sec)	70	21
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	76	27
Phase Split	74 %	26 %



MOVEMENT SUMMARY



Site: I-02 2014 BASE PM

Intersection of Moorebank Avenue and Anzac Road

2014 BASE AM PEAK 5:00 pm - 6:00 pm

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
2	T1	280	3.8	0.242	10.4	LOS A	6.8	48.8	0.49	0.42	45.0
3	R2	169	1.2	0.935	89.8	LOS F	13.3	94.0	1.00	1.13	17.3
Approach		449	2.8	0.935	40.3	LOS C	13.3	94.0	0.68	0.69	28.0
East: Anzac Road (E)											
4	L2	407	2.3	0.791	51.0	LOS D	21.5	153.4	0.99	0.90	24.9
6	R2	272	5.8	0.598	47.3	LOS D	13.0	95.3	0.93	0.83	26.1
Approach		679	3.7	0.791	49.5	LOS D	21.5	153.4	0.97	0.87	25.4
North: Moorebank Avenue (N)											
7	L2	289	4.0	0.180	8.3	LOS A	1.0	7.4	0.14	0.65	35.8
8	T1	1109	2.5	0.716	14.5	LOS A	30.7	219.3	0.69	0.62	25.4
Approach		1399	2.8	0.716	13.2	LOS A	30.7	219.3	0.57	0.63	27.0
All Vehicles		2527	3.0	0.935	27.8	LOS B	30.7	219.3	0.70	0.71	26.6

PHASING SUMMARY



Site: I-02 2014 BASE PM


Intersection of Moorebank Avenue and Anzac Road

2014 BASE AM PEAK 5:00 pm - 6:00 pm

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C
Phase Change Time (sec)	0	73
Green Time (sec)	67	31
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	73	37
Phase Split	66 %	34 %



I-03 Intersection of Moorebank Avenue and Defence Support Access

MOVEMENT SUMMARY

 **Site: I-03 2014 BASE AM**

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2014 BASE AM PEAK 6:45 am - 7:45 am

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
1	L2	16	0.0	0.010	8.6	LOS A	0.0	0.3	0.14	0.67	46.5
2	T1	1220	3.0	0.835	8.2	LOS A	35.2	253.1	0.70	0.67	44.4
Approach		1236	3.0	0.835	8.2	LOS A	35.2	253.1	0.70	0.67	44.4
North: Moorebank Avenue (N)											
8	T1	729	3.8	0.491	6.4	LOS A	12.2	88.1	0.46	0.43	49.0
9	R2	16	0.0	0.491	15.7	LOS B	12.2	88.1	0.52	0.48	47.6
Approach		745	3.7	0.491	6.6	LOS A	12.2	88.1	0.47	0.43	48.9
West: Military Access 1 (W)											
10	L2	2	0.0	0.020	49.6	LOS D	0.1	0.9	0.93	0.64	11.9
12	R2	1	0.0	0.020	49.7	LOS D	0.1	0.9	0.93	0.64	11.9
Approach		3	0.0	0.020	49.6	LOS D	0.1	0.9	0.93	0.64	11.9
All Vehicles		1984	3.2	0.835	7.7	LOS A	35.2	253.1	0.61	0.58	46.1

PHASING SUMMARY

 **Site: I-03 2014 BASE AM**

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2014 BASE AM PEAK 6:45 am - 7:45 am

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Phase Change Time (sec)	0	75
Green Time (sec)	69	9
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	75	15
Phase Split	83 %	17 %



MOVEMENT SUMMARY

 **Site: I-03 2014 BASE PM**

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2014 BASE AM PEAK 5:00 pm - 6:00 pm

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.001	8.6	LOS A	0.0	0.0	0.14	0.66	46.6
2	T1	440	2.4	0.299	3.4	LOS A	5.7	41.0	0.33	0.29	52.2
Approach		441	2.4	0.299	3.4	LOS A	5.7	41.0	0.32	0.29	52.2
North: Moorebank Avenue (N)											
8	T1	1497	2.5	0.961	32.5	LOS C	57.1	408.6	0.58	0.76	30.8
9	R2	1	0.0	0.961	48.8	LOS D	57.1	408.6	0.66	0.89	27.6
Approach		1498	2.5	0.961	32.5	LOS C	57.1	408.6	0.58	0.76	30.8
West: Military Access 1 (W)											
10	L2	9	0.0	0.087	50.5	LOS D	0.6	4.0	0.95	0.69	11.7
12	R2	4	0.0	0.087	50.6	LOS D	0.6	4.0	0.95	0.69	11.7
Approach		14	0.0	0.087	50.5	LOS D	0.6	4.0	0.95	0.69	11.7
All Vehicles		1953	2.5	0.961	26.0	LOS B	57.1	408.6	0.53	0.65	33.3

PHASING SUMMARY

 **Site: I-03 2014 BASE PM**

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2014 BASE AM PEAK 5:00 pm - 6:00 pm

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Phase Change Time (sec)	0	75
Green Time (sec)	69	9
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	75	15
Phase Split	83 %	17 %



I-04 Intersection of Moorebank Avenue and DNSDC Access

MOVEMENT SUMMARY

 **Site: I-04 2014 BASE AM**

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2014 BASE AM PEAK 6:45 am - 7:45 am

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
2	T1	1265	2.6	0.696	5.4	LOS A	19.6	140.0	0.52	0.48	50.0
3	R2	22	0.0	0.696	14.2	LOS A	19.6	140.0	0.58	0.55	48.9
Approach		1287	2.5	0.696	5.5	LOS A	19.6	140.0	0.52	0.48	49.9
East: DNSDC Access (W)											
4	L2	5	20.0	0.037	45.8	LOS D	0.2	1.6	0.94	0.65	26.5
6	R2	7	14.3	0.039	43.5	LOS D	0.3	2.1	0.92	0.66	27.2
Approach		13	16.7	0.039	44.5	LOS D	0.3	2.1	0.93	0.66	26.9
North: Moorebank Avenue (N)											
7	L2	93	6.8	0.062	8.7	LOS A	0.3	2.2	0.17	0.66	46.4
8	T1	599	3.5	0.426	4.3	LOS A	8.8	63.8	0.41	0.37	50.5
Approach		692	4.0	0.426	4.9	LOS A	8.8	63.8	0.38	0.41	49.9
West: Carpark Access (W)											
10	L2	1	0.0	0.005	42.5	LOS C	0.0	0.3	0.90	0.60	12.9
12	R2	1	0.0	0.007	45.1	LOS D	0.0	0.3	0.93	0.60	12.1
Approach		2	0.0	0.007	43.8	LOS D	0.0	0.3	0.92	0.60	12.5
All Vehicles		1994	3.1	0.696	5.6	LOS A	19.6	140.0	0.47	0.46	49.6

PHASING SUMMARY

 **Site: I-04 2014 BASE AM**


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2014 BASE AM PEAK 6:45 am - 7:45 am

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Phase Change Time (sec)	0	65
Green Time (sec)	59	9
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	65	15
Phase Split	81 %	19 %



MOVEMENT SUMMARY



Site: I-04 2014 BASE PM

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2014 BASE AM PEAK 5:00 pm - 6:00 pm

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMov	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
		Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
2	T1	407	2.1	0.202	3.2	LOS A	4.2	29.8	0.27	0.23	53.9
3	R2	1	0.0	0.202	11.7	LOS A	4.2	29.8	0.29	0.25	53.3
Approach		408	2.1	0.202	3.2	LOS A	4.2	29.8	0.27	0.23	53.9
East: DNSDC Access (W)											
4	L2	4	0.0	0.042	63.6	LOS E	0.2	1.6	0.97	0.64	21.8
6	R2	22	9.5	0.161	61.2	LOS E	1.2	8.7	0.96	0.71	22.3
Approach		26	8.0	0.161	61.6	LOS E	1.2	8.7	0.96	0.70	22.2
North: Moorebank Avenue (N)											
7	L2	6	16.7	0.004	8.5	LOS A	0.0	0.2	0.11	0.60	46.7
8	T1	1468	2.2	0.948	28.7	LOS C	83.9	598.2	0.89	0.97	29.3
Approach		1475	2.3	0.948	28.6	LOS C	83.9	598.2	0.88	0.97	29.3
West: Carpark Access (W)											
10	L2	6	0.0	0.042	59.6	LOS E	0.3	2.2	0.95	0.66	9.8
12	R2	3	0.0	0.031	63.5	LOS E	0.2	1.2	0.97	0.63	9.1
Approach		9	0.0	0.042	60.9	LOS E	0.3	2.2	0.95	0.65	9.6
All Vehicles		1919	2.3	0.948	23.8	LOS B	83.9	598.2	0.75	0.81	32.7

PHASING SUMMARY



Site: I-04 2014 BASE PM


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2014 BASE AM PEAK 5:00 pm - 6:00 pm

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Phase Change Time (sec)	0	95
Green Time (sec)	89	9
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	95	15
Phase Split	86 %	14 %



I-05 Intersection of Moorebank Avenue and Chatham Avenue

MOVEMENT SUMMARY

 **Site: I-05 2014 BASE AM**

Intersection of Moorebank Avenue and Chatham Avenue

2014 BASE AM PEAK 6:45 am - 7:45 am

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
1	L2	43	0.0	0.028	9.8	LOS A	0.4	2.6	0.18	0.69	47.3
2	T1	1272	2.5	0.979	53.0	LOS D	90.3	645.9	0.97	1.17	23.5
Approach		1315	2.4	0.979	51.6	LOS D	90.3	645.9	0.95	1.15	23.9
North: Moorebank Avenue (N)											
8	T1	443	4.8	0.290	2.8	LOS A	5.8	42.2	0.27	0.24	54.5
9	R2	132	0.8	0.713	61.2	LOS E	7.3	51.8	1.00	0.95	22.2
Approach		575	3.8	0.713	16.1	LOS B	7.3	51.8	0.44	0.40	41.0
West: Chatham Avenue (W)											
10	L2	17	6.3	0.155	57.6	LOS E	1.4	11.3	0.94	0.72	20.6
12	R2	12	27.3	0.155	57.7	LOS E	1.4	11.3	0.94	0.72	20.6
Approach		28	14.8	0.155	57.6	LOS E	1.4	11.3	0.94	0.72	20.6
All Vehicles		1918	3.0	0.979	41.1	LOS C	90.3	645.9	0.79	0.92	27.3

PHASING SUMMARY

 **Site: I-05 2014 BASE AM**


Intersection of Moorebank Avenue and Chatham Avenue

2014 BASE AM PEAK 6:45 am - 7:45 am

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Phase Change Time (sec)	0	83	95
Green Time (sec)	77	6	9
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	83	12	15
Phase Split	75 %	11 %	14 %



MOVEMENT SUMMARY

 **Site: I-05 2014 BASE PM**

Intersection of Moorebank Avenue and Chatham Avenue

2014 BASE AM PEAK 5:00 pm - 6:00 pm

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	9	0.0	0.006	9.9	LOS A	0.1	0.6	0.19	0.67	47.2
2	T1	365	2.0	0.288	7.1	LOS A	7.1	50.7	0.44	0.38	48.5
Approach		375	2.0	0.288	7.2	LOS A	7.1	50.7	0.43	0.39	48.4
North: Moorebank Avenue (N)											
8	T1	1444	2.2	0.981	47.6	LOS D	93.8	669.2	0.92	1.15	25.0
9	R2	26	0.0	0.037	13.0	LOS A	0.4	2.6	0.36	0.72	44.1
Approach		1471	2.1	0.981	47.0	LOS D	93.8	669.2	0.91	1.14	25.2
West: Chatham Avenue (W)											
10	L2	40	2.6	0.180	48.2	LOS D	2.1	15.2	0.90	0.75	23.1
12	R2	9	0.0	0.180	48.3	LOS D	2.1	15.2	0.90	0.75	23.1
Approach		49	2.1	0.180	48.2	LOS D	2.1	15.2	0.90	0.75	23.1
All Vehicles		1895	2.1	0.981	39.2	LOS C	93.8	669.2	0.82	0.98	27.8

PHASING SUMMARY

 **Site: I-05 2014 BASE PM**


Intersection of Moorebank Avenue and Chatham Avenue

2014 BASE AM PEAK 5:00 pm - 6:00 pm

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Phase Change Time (sec)	0	73	85
Green Time (sec)	67	6	9
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	73	12	15
Phase Split	73 %	12 %	15 %



2. 2014 Existing year – On the wider road network

I-01 Intersection of the Hume Highway and Orange Grove Road

MOVEMENT SUMMARY



Site: I-01 2014 BASE AM

Hume Highway / Orange Grove Road

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
NorthEast: Hume Highway (NE)											
25	T1	877	11.3	0.623	22.1	LOS B	17.2	132.2	0.81	0.73	37.1
26	R2	354	10.1	0.876	84.4	LOS F	14.9	113.5	1.00	0.91	24.2
Approach		1231	10.9	0.876	40.0	LOS C	17.2	132.2	0.86	0.78	30.8
NorthWest: Orange Grove Road (NW)											
27	L2	525	6.6	0.612	9.1	LOS A	7.5	55.6	0.22	0.63	51.4
29	R2	1163	6.6	0.858	67.3	LOS E	29.8	220.3	0.98	0.89	24.6
Approach		1688	6.6	0.858	49.2	LOS D	29.8	220.3	0.75	0.81	30.0
SouthWest: Hume Highway (SW)											
30	L2	1119	6.5	0.391	10.9	LOS A	11.2	83.0	0.31	0.69	52.8
31	T1	1936	4.9	0.695	19.5	LOS B	28.9	210.8	0.59	0.54	42.8
Approach		3055	5.5	0.695	16.4	LOS B	28.9	210.8	0.49	0.59	46.6
All Vehicles		5974	6.9	0.876	30.5	LOS C	29.8	220.3	0.64	0.69	36.3

PHASING SUMMARY



Site: I-01 2014 BASE AM


Hume Highway / Orange Grove Road

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	86	109
Green Time (sec)	79	16	35
Yellow Time (sec)	5	4	5
All-Red Time (sec)	2	2	2
Phase Time (sec)	86	22	42
Phase Split	57 %	15 %	28 %



MOVEMENT SUMMARY



Site: I-01 2014 BASE PM

Hume Highway / Orange Grove Road

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
NorthEast: Hume Highway (NE)											
25	T1	1605	3.3	0.828	22.8	LOS B	32.4	233.5	0.79	0.75	36.7
26	R2	754	2.8	0.862	44.2	LOS D	17.5	125.5	1.00	0.93	34.4
Approach		2359	3.1	0.862	29.6	LOS C	32.4	233.5	0.85	0.81	35.7
NorthWest: Orange Grove Road (NW)											
27	L2	365	4.3	0.337	11.0	LOS A	5.2	37.6	0.23	0.62	50.4
29	R2	1252	3.1	0.956	82.7	LOS F	37.4	269.0	1.00	0.98	21.8
Approach		1617	3.4	0.956	66.5	LOS E	37.4	269.0	0.83	0.90	25.4
SouthWest: Hume Highway (SW)											
30	L2	1208	3.0	0.713	19.2	LOS B	18.2	130.9	0.76	0.82	46.0
31	T1	1029	5.3	0.925	72.3	LOS F	31.7	231.6	1.00	1.04	20.9
Approach		2238	4.0	0.925	43.6	LOS D	31.7	231.6	0.87	0.92	31.3
All Vehicles		6214	3.5	0.956	44.3	LOS D	37.4	269.0	0.85	0.87	30.6

PHASING SUMMARY



Site: I-01 2014 BASE PM


Hume Highway / Orange Grove Road

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C	D
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	53	81	124
Green Time (sec)	47	21	37	19
Yellow Time (sec)	5	4	5	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	54	27	44	25
Phase Split	36 %	18 %	29 %	17 %



I-02 Intersection of the Hume Highway and Elizabeth Drive

MOVEMENT SUMMARY



Site: I-02 2014 BASE AM

Hume Highway / Elizabeth Drive

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h	
South: Hume Highway (S)											
1	L2	116	5.5	0.128	21.1	LOS B	2.9	21.5	0.38	0.67	37.4
2	T1	2066	6.3	0.792	35.4	LOS C	40.4	298.3	0.85	0.76	27.5
Approach		2182	6.2	0.808	34.6	LOS C	40.4	298.3	0.82	0.76	28.0
East: Elizabeth Drive (E)											
4	L2	34	6.2	0.362	59.6	LOS E	8.5	62.8	0.90	0.81	18.6
5	T1	412	5.9	0.362	55.8	LOS D	9.7	71.3	0.89	0.82	23.8
6	R2	133	2.4	0.641	75.0	LOS F	9.6	68.3	1.00	0.81	15.2
Approach		578	5.1	0.641	60.4	LOS E	9.7	71.3	0.91	0.81	21.2
North: Hume Highway (N)											
7	L2	76	2.8	0.567	24.6	LOS B	19.5	146.0	0.55	0.53	32.4
8	T1	1578	8.7	0.567	18.0	LOS B	19.5	146.0	0.53	0.49	37.3
9	R2	305	9.7	1.098	187.9	LOS F	18.5	140.5	1.00	1.25	9.7
Approach		1959	8.7	1.098	44.7	LOS D	19.5	146.0	0.60	0.61	24.4
West: Elizabeth Drive (W)											
10	L2	544	5.4	0.918	72.4	LOS F	42.7	312.5	1.00	0.95	19.4
11	T1	929	3.1	0.922	74.3	LOS F	37.0	266.1	1.00	1.02	18.5
12	R2	436	6.5	1.083	179.8	LOS F	26.3	194.1	1.00	1.25	10.1
Approach		1909	4.5	1.083	97.8	LOS F	42.7	312.5	1.00	1.05	15.6
All Vehicles		6628	6.4	1.098	58.1	LOS E	42.7	312.5	0.82	0.80	21.2

PHASING SUMMARY



Site: I-02 2014 BASE AM


Hume Highway / Elizabeth Drive

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	D	F	A	E
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	68	91	132
Green Time (sec)	62	17	35	12
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	68	23	41	18
Phase Split	45 %	15 %	27 %	12 %



MOVEMENT SUMMARY



Site: I-02 2014 BASE PM

Hume Highway / Elizabeth Drive

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	286	4.4	0.426	39.9	LOS C	13.2	95.8	0.68	0.77	28.4
2	T1	1419	4.8	0.819	51.7	LOS D	32.3	235.2	0.94	0.86	22.0
Approach		1705	4.8	0.819	49.7	LOS D	32.3	235.2	0.90	0.85	23.0
East: Elizabeth Drive (E)											
4	L2	109	1.0	0.817	73.1	LOS F	23.0	163.3	1.00	0.92	16.1
5	T1	938	2.5	0.817	67.8	LOS E	28.2	201.6	1.00	0.92	20.8
6	R2	146	0.0	0.985	114.7	LOS F	13.8	96.3	1.00	1.14	11.1
Approach		1194	2.0	0.985	74.0	LOS F	28.2	201.6	1.00	0.94	18.7
North: Hume Highway (N)											
7	L2	61	5.2	0.785	20.1	LOS B	30.1	216.0	0.60	0.57	35.9
8	T1	2247	2.9	0.785	14.5	LOS B	30.8	220.9	0.60	0.56	40.3
9	R2	857	2.9	0.818	65.8	LOS E	29.7	212.9	0.98	0.89	21.5
Approach		3165	3.0	0.818	28.5	LOS C	30.8	220.9	0.70	0.65	31.7
West: Elizabeth Drive (W)											
10	L2	307	6.5	0.406	33.0	LOS C	12.4	91.8	0.60	0.75	30.1
11	T1	493	4.7	0.630	60.0	LOS E	15.9	115.6	0.93	0.80	21.3
12	R2	287	2.6	0.985	116.1	LOS F	13.5	96.8	1.00	1.09	14.3
Approach		1087	4.6	0.985	67.2	LOS E	15.9	115.6	0.86	0.86	20.3
All Vehicles		7152	3.5	0.985	47.0	LOS D	32.3	235.2	0.82	0.78	24.4

PHASING SUMMARY



Site: I-02 2014 BASE PM


Hume Highway / Elizabeth Drive

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	D	F	A	E
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	53	71	108
Green Time (sec)	47	12	31	36
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	53	18	37	42
Phase Split	35 %	12 %	25 %	28 %



I-03 Intersection of the Hume Highway and Memorial Avenue

MOVEMENT SUMMARY



Site: I-03 2014 BASE AM

Hume Highway / Memorial Avenue

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h	
South: Hume Highway (S)											
1	L2	138	1.5	0.839	40.6	LOS C	42.1	310.4	0.89	0.84	34.3
2	T1	1848	7.2	0.839	32.8	LOS C	42.2	313.8	0.82	0.77	34.1
3	R2	235	0.0	0.998	121.0	LOS F	23.1	161.6	1.00	1.08	15.2
Approach		2221	6.1	0.998	42.6	LOS D	42.2	313.8	0.84	0.81	30.3
East: Memorial Avenue (E)											
4	L2	22	19.0	1.001	123.6	LOS F	13.7	101.8	1.00	1.19	15.2
5	T1	137	5.4	1.001	118.9	LOS F	13.7	101.8	1.00	1.19	14.8
6	R2	107	12.7	1.001	123.6	LOS F	12.4	95.4	1.00	1.19	10.9
Approach		266	9.5	1.001	121.2	LOS F	13.7	101.8	1.00	1.19	13.3
North: Hume Highway (N)											
7	L2	104	6.1	0.088	12.3	LOS A	2.2	16.4	0.35	0.64	39.5
8	T1	1542	11.1	0.646	26.7	LOS B	24.9	191.1	0.67	0.60	37.2
9	R2	87	3.6	0.381	71.5	LOS F	6.0	43.1	0.96	0.78	21.5
Approach		1734	10.4	0.646	28.1	LOS B	24.9	191.1	0.67	0.61	36.0
West: Memorial Avenue (W)											
10	L2	109	2.9	1.004	106.4	LOS F	26.3	187.2	1.00	1.18	16.8
11	T1	393	1.6	1.004	109.2	LOS F	34.4	245.0	1.00	1.21	15.6
12	R2	139	3.0	1.004	120.7	LOS F	34.4	245.0	1.00	1.23	18.9
Approach		641	2.1	1.004	111.2	LOS F	34.4	245.0	1.00	1.21	16.6
All Vehicles		4862	7.3	1.004	50.8	LOS D	42.2	313.8	0.81	0.81	27.1

PHASING SUMMARY



Site: I-03 2014 BASE AM


Hume Highway / Memorial Avenue

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	F
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	75	108	125
Green Time (sec)	69	27	11	19
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	75	33	17	25
Phase Split	50 %	22 %	11 %	17 %



MOVEMENT SUMMARY



Site: I-03 2014 BASE PM

Hume Highway / Memorial Avenue

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	113	0.9	0.717	40.6	LOS C	29.8	217.3	0.82	0.77	34.3
2	T1	1522	5.7	0.717	32.8	LOS C	30.3	222.2	0.77	0.70	34.1
3	R2	109	0.0	0.737	83.1	LOS F	8.3	58.3	1.00	0.84	19.7
Approach		1744	5.0	0.737	36.4	LOS C	30.3	222.2	0.79	0.72	32.7
East: Memorial Avenue (E)											
4	L2	46	0.0	1.180	258.8	LOS F	36.3	258.4	1.00	1.67	8.4
5	T1	247	2.6	1.180	254.3	LOS F	36.3	258.4	1.00	1.65	8.2
6	R2	180	6.4	1.180	259.2	LOS F	33.4	245.0	1.00	1.58	5.9
Approach		474	3.8	1.180	256.6	LOS F	36.3	258.4	1.00	1.62	7.4
North: Hume Highway (N)											
7	L2	140	3.0	0.082	8.0	LOS A	1.7	12.5	0.23	0.61	43.9
8	T1	2696	3.0	0.830	10.0	LOS A	35.9	257.8	0.50	0.46	48.8
9	R2	197	2.1	0.747	51.6	LOS D	8.8	62.7	1.00	0.88	25.7
Approach		3033	3.0	0.830	12.6	LOS A	35.9	257.8	0.52	0.49	45.9
West: Memorial Avenue (W)											
10	L2	71	1.5	0.770	69.3	LOS E	12.5	88.7	1.00	0.92	22.2
11	T1	179	1.2	0.770	66.7	LOS E	15.7	110.1	1.00	0.91	21.0
12	R2	145	0.0	0.770	74.5	LOS F	15.7	110.1	1.00	0.89	25.0
Approach		395	0.8	0.770	70.1	LOS E	15.7	110.1	1.00	0.90	22.8
All Vehicles		5645	3.5	1.180	44.5	LOS D	36.3	258.4	0.68	0.69	29.0

PHASING SUMMARY



Site: I-03 2014 BASE PM


Hume Highway / Memorial Avenue

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	D	E	F
Reference Phase	Yes	No	No	No	No
Phase Change Time (sec)	0	70	82	110	132
Green Time (sec)	64	6	22	16	12
Yellow Time (sec)	4	4	4	4	4
All-Red Time (sec)	2	2	2	2	2
Phase Time (sec)	70	12	28	22	18
Phase Split	47 %	8 %	19 %	15 %	12 %



I-04 Intersection of the Hume Highway and Hoxton Park Drive

MOVEMENT SUMMARY



Site: I-04 2014 BASE AM

Hume Highway / Hoxton Park Road / Macquarie Street

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles										
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV %	Average Delay v/c	Level of Service	95% Back of Queue Vehicles	Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Hume Highway (S)										
1	L2	76	6.9	0.060	LOS A	0.3	1.9	0.05	0.56	52.5
2	T1	1917	5.1	0.714	LOS B	30.9	225.7	0.69	0.63	41.1
3	R2	1046	1.9	0.931	LOS D	26.6	189.5	1.00	0.98	25.8
Approach		3039	4.1	0.931	LOS C	30.9	225.7	0.78	0.75	35.3
East: Macquarie Street (E)										
4	L2	286	5.9	0.185	LOS B	4.4	32.4	0.65	0.72	38.8
5	T1	389	4.6	0.812	LOS F	14.9	108.1	1.00	0.92	23.5
Approach		676	5.1	0.812	LOS D	14.9	108.1	0.85	0.84	27.7
North: Hume Highway (N)										
7	L2	177	15.5	0.831	LOS E	33.7	257.4	0.95	0.99	26.5
8	T1	1326	8.1	0.831	LOS D	35.8	267.9	0.93	0.89	30.1
9	R2	184	19.4	0.941	LOS F	16.3	133.1	1.00	1.05	22.2
Approach		1687	10.1	0.941	LOS E	35.8	267.9	0.94	0.92	28.5
West: Hoxton Park Road (W)										
10	L2	267	16.1	0.463	LOS D	15.1	120.4	0.83	0.81	32.8
11	T1	997	4.2	0.804	LOS D	22.6	164.1	0.94	0.87	27.7
12	R2	324	3.2	0.918	LOS F	14.6	105.2	1.00	0.95	23.0
Approach		1588	6.0	0.918	LOS E	22.6	164.1	0.93	0.88	27.3
All Vehicles		6991	6.1	0.941	LOS D	35.8	267.9	0.86	0.83	30.6

PHASING SUMMARY



Site: I-04 2014 BASE AM


Hume Highway / Hoxton Park Road / Macquarie Street

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	E	D	F
Reference Phase	Yes	No	No	No	No
Phase Change Time (sec)	0	51	79	101	126
Green Time (sec)	45	22	16	19	18
Yellow Time (sec)	4	4	4	4	4
All-Red Time (sec)	2	2	2	2	2
Phase Time (sec)	51	28	22	25	24
Phase Split	34 %	19 %	15 %	17 %	16 %



MOVEMENT SUMMARY



Site: I-04 2014 BASE PM

Hume Highway / Hoxton Park Road / Macquarie Street

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
							Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	151	5.6	0.124	8.5	LOS A	1.2	8.6	0.12	0.58	51.1
2	T1	1504	5.2	0.572	22.4	LOS B	21.1	154.0	0.59	0.53	42.4
3	R2	416	1.3	0.921	93.2	LOS F	17.4	123.1	1.00	0.99	18.4
Approach		2071	4.4	0.921	35.6	LOS C	21.1	154.0	0.64	0.62	35.4
East: Macquarie Street (E)											
4	L2	700	1.5	0.906	67.5	LOS E	23.4	166.0	0.82	0.90	22.7
5	T1	612	3.3	0.941	84.6	LOS F	25.6	183.9	1.00	1.05	21.7
Approach		1312	2.3	0.941	75.5	LOS F	25.6	183.9	0.91	0.97	22.2
North: Hume Highway (N)											
7	L2	94	5.6	0.851	18.2	LOS B	39.0	279.8	0.63	0.63	45.4
8	T1	2585	2.6	0.851	12.8	LOS A	41.7	298.3	0.59	0.56	48.4
9	R2	219	6.7	1.158	241.6	LOS F	30.9	228.9	1.00	1.42	11.9
Approach		2898	3.1	1.158	30.2	LOS C	41.7	298.3	0.62	0.63	38.5
West: Hoxton Park Road (W)											
10	L2	226	3.7	0.361	44.5	LOS D	12.2	88.3	0.79	0.79	33.6
11	T1	595	3.9	0.364	45.5	LOS D	11.5	82.9	0.84	0.71	30.8
12	R2	327	1.6	1.036	119.8	LOS F	18.8	133.5	1.00	1.09	18.9
Approach		1148	3.2	1.036	66.5	LOS E	18.8	133.5	0.88	0.83	26.3
All Vehicles		7428	3.3	1.158	45.3	LOS D	41.7	298.3	0.72	0.72	31.8

PHASING SUMMARY



Site: I-04 2014 BASE PM

Hume Highway / Hoxton Park Road / Macquarie Street

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase times specified by the user

Sequence: TCS 405 PM


Movement Class: All Movement Classes

Input Sequence: A, E, D, F

Output Sequence: A, E, D, F

Phase Timing Results

Phase	A	E	D	F
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	79	99	128
Green Time (sec)	73	14	23	16
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	79	20	29	22
Phase Split	53 %	13 %	19 %	15 %



I-05 Intersection of the Hume Highway and Reilly Street

MOVEMENT SUMMARY



Site: I-05 2014 BASE AM

Hume Highway / Reilly Street

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Hume Highway (S)											
1	L2	73	2.9	0.821	17.9	LOS B	37.8	272.8	0.59	0.57	43.7
2	T1	2833	3.6	0.821	11.7	LOS A	37.8	272.8	0.57	0.54	46.0
3	R2	13	8.3	0.076	20.1	LOS B	0.4	3.0	0.45	0.66	38.4
Approach		2918	3.6	0.821	11.8	LOS A	37.8	272.8	0.57	0.54	45.8
East: Congressional Drive (E)											
4	L2	42	2.5	0.234	59.6	LOS E	5.1	36.7	0.89	0.73	24.4
5	T1	40	5.3	0.234	55.0	LOS D	5.1	36.7	0.89	0.73	23.9
6	R2	77	4.1	0.348	66.1	LOS E	5.1	37.0	0.93	0.77	18.9
Approach		159	4.0	0.348	61.6	LOS E	5.1	37.0	0.91	0.75	21.7
North: Hume Highway (N)											
7	L2	28	3.7	0.482	15.4	LOS B	19.9	147.6	0.47	0.45	41.5
8	T1	1647	7.2	0.482	9.5	LOS A	20.0	148.4	0.45	0.42	48.1
9	R2	88	1.2	0.596	32.3	LOS C	4.7	33.4	0.99	0.85	30.7
Approach		1764	6.9	0.596	10.7	LOS A	20.0	148.4	0.48	0.44	46.6
West: Reilly Street (W)											
10	L2	99	4.3	0.231	50.5	LOS D	6.3	45.7	0.82	0.75	24.4
11	T1	12	9.1	0.231	45.9	LOS D	6.3	45.7	0.82	0.75	25.6
12	R2	211	2.0	0.892	85.8	LOS F	17.5	124.3	1.00	1.00	21.0
Approach		321	3.0	0.892	73.5	LOS F	17.5	124.3	0.94	0.91	22.0
All Vehicles		5162	4.7	0.892	16.8	LOS B	37.8	272.8	0.57	0.53	41.4

PHASING SUMMARY



Site: I-05 2014 BASE AM


Hume Highway / Reilly Street

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E2
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	100	137
Green Time (sec)	94	31	7
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	100	37	13
Phase Split	67 %	25 %	9 %



MOVEMENT SUMMARY



Site: I-05 2014 BASE PM

Hume Highway / Reilly Street

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Hume Highway (S)											
1	L2	219	0.5	0.629	19.3	LOS B	23.7	170.7	0.50	0.55	42.0
2	T1	1955	4.5	0.629	11.3	LOS A	23.7	170.7	0.43	0.42	46.0
3	R2	21	5.0	0.371	28.0	LOS B	1.0	7.1	0.59	0.72	34.4
Approach		2195	4.1	0.629	12.2	LOS A	23.7	170.7	0.44	0.44	45.3
East: Congressional Drive (E)											
4	L2	36	2.9	0.163	59.6	LOS E	3.5	24.8	0.88	0.72	24.3
5	T1	21	0.0	0.163	55.0	LOS D	3.5	24.8	0.88	0.72	23.8
6	R2	44	0.0	0.179	62.1	LOS E	2.8	19.5	0.89	0.74	19.8
Approach		101	1.0	0.179	59.7	LOS E	3.5	24.8	0.88	0.73	22.3
North: Hume Highway (N)											
7	L2	62	0.0	0.916	13.1	LOS A	39.3	279.9	0.44	0.45	43.7
8	T1	3367	2.3	0.916	8.9	LOS A	39.3	279.9	0.35	0.37	48.6
9	R2	163	1.3	0.784	44.7	LOS D	10.4	73.3	1.00	0.97	26.5
Approach		3593	2.2	0.916	10.6	LOS A	39.3	279.9	0.38	0.39	46.7
West: Reilly Street (W)											
10	L2	56	0.0	0.190	53.9	LOS D	4.8	33.9	0.84	0.72	24.0
11	T1	27	0.0	0.190	49.3	LOS D	4.8	33.9	0.84	0.72	25.0
12	R2	232	1.8	0.932	94.6	LOS F	20.4	145.3	1.00	1.05	19.8
Approach		315	1.3	0.932	83.5	LOS F	20.4	145.3	0.96	0.96	20.7
All Vehicles		6203	2.8	0.932	15.7	LOS B	39.3	279.9	0.44	0.44	42.3

PHASING SUMMARY



Site: I-05 2014 BASE PM


Hume Highway / Reilly Street

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E2
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	98	135
Green Time (sec)	92	31	9
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	98	37	15
Phase Split	65 %	25 %	10 %



I-06 Intersection of Newbridge Road and Moorebank Avenue

MOVEMENT SUMMARY



Site: I-06 2014 BASE AM



Network: 2014 BASE AM

Newbridge Road / Moorebank Avenue

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Arrival Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV	Total	HV				Vehicles	Distance			
		veh/h	%	veh/h	%				veh	m			
South: Moorebank Avenue (S)													
1	L2	1202	3.2	1202	3.2	0.620	18.7	LOS B	12.8	91.9	0.55	0.81	42.5
3	R2	1060	9.0	1060	9.0	0.623	14.8	LOS B	12.1	91.3	0.38	0.67	52.8
Approach		2262	5.9	2262	5.9	0.623	16.9	LOS B	12.8	91.9	0.47	0.75	48.0
East: Newbridge Road (E)													
4	L2	453	19.8	453	19.8	0.376	17.1	LOS B	4.8	39.2	0.63	0.76	52.9
5	T1	691	5.2	691	5.2	0.902	69.9	LOS E	25.4	186.0	1.00	1.03	37.9
Approach		1143	11.0	1143	11.0	0.902	49.0	LOS D	25.4	186.0	0.85	0.92	41.4
West: Newbridge Road (W)													
11	T1	1121	6.4	1121	6.4	0.603	8.8	LOS A	12.4	91.3	0.37	0.33	63.3
12	R2	572	7.4	572	7.4	0.874	49.9	LOS D	14.8	109.8	1.00	0.95	26.8
Approach		1693	6.7	1693	6.7	0.874	22.6	LOS B	14.8	109.8	0.58	0.54	52.0
All Vehicles		5098	7.3	5098	7.3	0.902	26.0	LOS B	25.4	186.0	0.60	0.72	47.3

PHASING SUMMARY



Site: I-06 2014 BASE AM



Network: 2014 BASE AM


Newbridge Road / Moorebank Avenue

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C	D
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	33	55	116
Green Time (sec)	27	16	55	11
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	33	22	61	17
Phase Split	25 %	17 %	46 %	13 %



MOVEMENT SUMMARY



Site: I-06 2014 BASE PM



Network: 2014 BASE PM

Newbridge Road / Moorebank Avenue

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 116 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo	Demand Flows		Arrival Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV	Total	HV				Vehicles	Distance		per veh	km/h
		veh/h	%	veh/h	%	v/c	sec		veh	m			
South: Moorebank Avenue (S)													
1	L2	700	3.3	700	3.3	0.400	21.4	LOS B	9.4	67.6	0.51	0.72	40.6
3	R2	697	10.7	697	10.7	0.901	51.5	LOS D	17.1	130.6	1.00	0.94	35.5
Approach		1397	7.0	1397	7.0	0.901	36.4	LOS C	17.1	130.6	0.76	0.83	37.3
East: Newbridge Road (E)													
4	L2	1048	5.1	1048	5.1	0.682	26.2	LOS B	23.4	171.3	0.73	0.82	46.6
5	T1	1132	4.7	1132	4.7	0.760	36.2	LOS C	26.9	196.1	0.90	0.80	48.7
Approach		2180	4.9	2180	4.9	0.760	31.4	LOS C	26.9	196.1	0.82	0.81	47.9
West: Newbridge Road (W)													
11	T1	918	3.8	918	3.8	0.359	8.6	LOS A	11.0	79.4	0.46	0.41	63.4
12	R2	947	2.7	947	2.7	0.887	43.4	LOS D	26.6	190.3	0.97	0.92	29.1
Approach		1865	3.2	1865	3.2	0.887	26.3	LOS B	26.6	190.3	0.72	0.67	47.7
All Vehicles		5442	4.9	5442	4.9	0.901	30.9	LOS C	26.9	196.1	0.77	0.77	45.3

PHASING SUMMARY



Site: I-06 2014 BASE PM



Network: 2014 BASE PM


Newbridge Road / Moorebank Avenue

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 116 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	44	76
Green Time (sec)	38	26	34
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	44	32	40
Phase Split	38 %	28 %	34 %



I-07 Intersection of Moorebank Avenue and Heathcote Road

MOVEMENT SUMMARY



Site: I-07 2014 BASE AM



Network: 2014 BASE AM

Moorebank Avenue / Heathcote Road

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Arrival Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV	Total	HV				Vehicles	Distance			
		veh/h	%	veh/h	%				veh	m			
South: Moorebank Avenue (S)													
2	T1	1524	5.7	1524	5.7	0.838	12.1	LOS A	29.9	219.5	0.58	0.55	35.4
3	R2	20	21.1	20	21.1	0.183	71.8	LOS F	1.3	10.6	0.98	0.71	30.5
Approach		1544	5.9	1544	5.9	0.838	12.9	LOS A	29.9	219.5	0.59	0.55	35.1
East: Heathcote Road (E)													
4	L2	22	57.1	22	57.1	0.934	81.7	LOS F	31.7	239.0	1.00	1.04	27.4
6	R2	735	6.0	735	6.0	0.934	71.3	LOS F	31.7	239.0	1.00	0.99	27.8
Approach		757	7.5	757	7.5	0.934	71.6	LOS F	31.7	239.0	1.00	0.99	27.8
North: Moorebank Avenue (N)													
7	L2	513	7.8	513	7.8	0.300	10.4	LOS A	9.5	71.0	0.52	0.70	51.6
8	T1	540	17.0	540	17.0	0.305	20.5	LOS B	10.1	81.0	0.63	0.54	31.2
Approach		1053	12.5	1053	12.5	0.305	15.6	LOS B	10.1	81.0	0.58	0.62	44.1
All Vehicles		3354	8.3	3354	8.3	0.934	27.0	LOS B	31.7	239.0	0.68	0.67	34.3

PHASING SUMMARY



Site: I-07 2014 BASE AM



Network: 2014 BASE AM


Moorebank Avenue / Heathcote Road

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Phase Timing Results

Phase	B	A	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	15	88
Green Time (sec)	9	67	39
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	15	73	45
Phase Split	11 %	55 %	34 %



MOVEMENT SUMMARY



Site: I-07 2014 BASE PM



Network: 2014 BASE PM

Moorebank Avenue / Heathcote Road

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 116 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo	Demand Flows		Arrival Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV	Total	HV				Vehicles	Distance		per veh	km/h
		veh/h	%	veh/h	%	v/c	sec		veh	m			
South: Moorebank Avenue (S)													
2	T1	858	8.3	858	8.3	0.636	13.6	LOS A	17.2	129.0	0.65	0.59	33.7
3	R2	38	8.3	38	8.3	0.313	64.1	LOS E	2.2	16.2	0.99	0.73	32.3
Approach		896	8.3	896	8.3	0.636	15.7	LOS B	17.2	129.0	0.66	0.59	33.4
East: Heathcote Road (E)													
4	L2	64	19.7	64	19.7	0.890	49.7	LOS D	23.7	176.2	0.99	0.94	35.2
6	R2	544	5.0	544	5.0	0.890	45.9	LOS D	23.7	176.2	0.95	0.90	34.3
Approach		608	6.6	608	6.6	0.890	46.3	LOS D	23.7	176.2	0.95	0.90	34.5
North: Moorebank Avenue (N)													
7	L2	760	3.6	760	3.6	0.356	7.5	LOS A	5.0	36.2	0.24	0.61	53.8
8	T1	1235	4.1	1235	4.1	0.628	6.1	LOS A	10.4	75.2	0.32	0.29	47.1
Approach		1995	3.9	1995	3.9	0.628	6.6	LOS A	10.4	75.2	0.29	0.41	51.2
All Vehicles		3499	5.5	3499	5.5	0.890	15.8	LOS B	23.7	176.2	0.50	0.54	42.3

PHASING SUMMARY



Site: I-07 2014 BASE PM



Network: 2014 BASE PM


Moorebank Avenue / Heathcote Road

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 116 seconds (User-Given Phase Times)

Phase Timing Results

Phase	B	A	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	14	80
Green Time (sec)	8	60	30
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	14	66	36
Phase Split	12 %	57 %	31 %



I-08 Intersection of Moorebank Avenue and Industry Park Access

MOVEMENT SUMMARY



Site: I-08 2014 BASE AM

Moorebank Avenue / Industry Park Access

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	76	1.4	0.063	8.0	LOS A	0.8	5.4	0.29	0.62	41.7
2	T1	1540	4.9	0.529	4.7	LOS A	14.3	104.5	0.42	0.39	54.4
Approach		1616	4.8	0.529	4.9	LOS A	14.3	104.5	0.41	0.40	53.7
North: Moorebank Avenue (N)											
8	T1	521	16.2	0.192	3.3	LOS A	3.4	26.8	0.29	0.25	56.0
9	R2	52	38.8	0.441	17.9	LOS B	1.5	13.6	0.55	0.72	30.8
Approach		573	18.2	0.441	4.6	LOS A	3.4	26.8	0.31	0.29	53.3
West: Industry Park Access (W)											
10	L2	20	63.2	0.076	4.6	LOS A	0.2	2.7	0.31	0.39	30.3
12	R2	47	71.1	0.250	48.3	LOS D	1.6	18.1	0.94	0.71	23.4
Approach		67	68.7	0.250	35.4	LOS C	1.6	18.1	0.76	0.62	24.7
All Vehicles		2256	10.1	0.529	5.7	LOS A	14.3	104.5	0.40	0.38	52.0

PHASING SUMMARY



Site: I-08 2014 BASE AM


Moorebank Avenue / Industry Park Access

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C
Reference Phase	Yes	No
Phase Change Time (sec)	0	83
Green Time (sec)	77	11
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	83	17
Phase Split	83 %	17 %



MOVEMENT SUMMARY



Site: I-08 2014 BASE PM

Moorebank Avenue / Industry Park Access

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 65 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles veh	Distance m			
		veh/h	%								
South: Moorebank Avenue (S)											
1	L2	7	14.3	0.006	6.5	LOS A	0.0	0.2	0.21	0.57	42.8
2	T1	883	7.6	0.343	4.3	LOS A	5.6	42.0	0.43	0.38	54.8
Approach		891	7.7	0.343	4.3	LOS A	5.6	42.0	0.43	0.38	54.7
North: Moorebank Avenue (N)											
8	T1	1281	3.9	0.486	5.0	LOS A	9.4	68.0	0.50	0.45	54.1
9	R2	22	61.9	0.089	12.5	LOS A	0.3	3.4	0.44	0.65	34.0
Approach		1303	4.8	0.486	5.1	LOS A	9.4	68.0	0.50	0.45	53.8
West: Industry Park Access (W)											
10	L2	28	14.8	0.045	3.1	LOS A	0.2	1.4	0.30	0.39	35.6
12	R2	160	9.2	0.373	32.0	LOS C	2.5	18.8	0.96	0.75	28.3
Approach		188	10.1	0.373	27.7	LOS B	2.5	18.8	0.86	0.70	28.9
All Vehicles		2382	6.3	0.486	6.6	LOS A	9.4	68.0	0.50	0.45	50.9

PHASING SUMMARY



Site: I-08 2014 BASE PM


Moorebank Avenue / Industry Park Access

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 65 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C
Reference Phase	Yes	No
Phase Change Time (sec)	0	51
Green Time (sec)	45	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	51	14
Phase Split	78 %	22 %



I-09 Intersection of Moorebank Avenue and Church Road

MOVEMENT SUMMARY

▽ Site: I-09 2014 BASE AM

Moorebank Avenue / Church Road
2014 BASE AM PEAK 7:45 am - 8:45 am
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
2	T1	1704	6.4	0.552	2.3	LOS A	8.1	59.8	0.24	0.10	57.2
3	R2	228	7.8	0.552	14.7	LOS B	8.1	59.8	1.00	0.42	46.1
Approach		1933	6.6	0.690	3.8	NA	8.1	59.8	0.33	0.14	55.6
East: Church Road (E)											
4	L2	171	14.2	0.184	6.3	LOS A	0.7	5.7	0.40	0.62	48.1
6	R2	6	0.0	0.125	67.4	LOS E	0.3	2.2	0.97	0.99	26.6
Approach		177	13.7	0.184	8.5	LOS A	0.7	5.7	0.42	0.63	46.7
North: Moorebank Avenue (N)											
7	L2	27	0.0	0.164	5.6	LOS A	0.0	0.0	0.00	0.06	57.7
8	T1	538	21.1	0.164	0.0	LOS A	0.0	0.0	0.00	0.03	59.6
Approach		565	20.1	0.164	0.3	NA	0.0	0.0	0.00	0.03	59.5
All Vehicles		2675	9.9	0.690	3.4	NA	8.1	59.8	0.27	0.15	55.7

MOVEMENT SUMMARY

▽ Site: I-09 2014 BASE PM

Moorebank Avenue / Church Road
2014 BASE PM PEAK 4:30 pm - 5:30 pm
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
2	T1	918	11.9	0.394	4.8	LOS A	5.2	40.4	0.22	0.07	55.2
3	R2	84	11.3	0.394	26.8	LOS B	5.2	40.4	1.00	0.33	40.1
Approach		1002	11.9	0.394	6.6	NA	5.2	40.4	0.29	0.10	53.4
East: Church Road (E)											
4	L2	361	4.4	0.913	84.2	LOS F	25.2	183.1	1.00	2.46	23.7
6	R2	1	0.0	0.027	91.7	LOS F	0.1	0.5	0.97	0.99	22.5
Approach		362	4.4	0.913	84.3	LOS F	25.2	183.1	1.00	2.46	23.7
North: Moorebank Avenue (N)											
7	L2	12	9.1	0.754	6.1	LOS A	0.0	0.0	0.00	0.01	57.0
8	T1	1415	4.5	0.754	0.5	LOS A	0.0	0.0	0.00	0.00	59.0
Approach		1426	4.6	0.754	0.5	NA	0.0	0.0	0.00	0.00	58.9
All Vehicles		2791	7.2	0.913	13.6	NA	25.2	183.1	0.23	0.36	47.7

I-10 Intersection of Heathcote Road and Nuwarra Road

MOVEMENT SUMMARY



Site: I-10 2014 BASE AM

Heathcote Road / Nuwarra Road / Wattle Grove Drive

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 131 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
SouthEast: Heathcote Road (SE)											
4	L2	189	1.1	0.127	7.5	LOS A	2.0	14.4	0.23	0.61	49.0
5	T1	1419	5.3	0.832	27.2	LOS B	35.5	259.8	0.79	0.73	41.2
6	R2	486	3.2	0.952	62.8	LOS E	13.4	96.4	1.00	1.04	29.6
Approach		2095	4.4	0.952	33.7	LOS C	35.5	259.8	0.79	0.79	37.9
NorthEast: Nuwarra Road (NE)											
7	L2	333	4.7	0.361	16.6	LOS B	9.9	71.9	0.55	0.73	46.6
8	T1	197	8.6	0.317	52.2	LOS D	5.6	42.0	0.92	0.73	26.5
9	R2	384	5.8	1.041	174.0	LOS F	24.6	180.7	1.00	1.32	15.1
Approach		914	6.0	1.041	90.4	LOS F	24.6	180.7	0.82	0.98	22.9
NorthWest: Heathcote Road (NW)											
10	L2	208	12.1	0.275	21.0	LOS B	6.2	48.0	0.67	0.75	42.9
11	T1	841	11.5	0.740	34.1	LOS C	21.5	165.7	0.80	0.70	38.2
12	R2	195	6.5	0.653	72.0	LOS F	6.4	47.2	1.00	0.81	20.5
Approach		1244	10.8	0.740	37.8	LOS C	21.5	165.7	0.81	0.72	35.6
SouthWest: Wattle Grove Drive (SW)											
1	L2	459	2.1	0.560	32.5	LOS C	20.4	145.6	0.84	0.95	31.2
2	T1	458	4.4	0.625	56.0	LOS D	13.7	99.8	0.98	0.82	25.2
3	R2	212	4.0	1.027	125.4	LOS F	19.8	143.1	1.00	1.24	14.6
Approach		1128	3.4	1.027	59.5	LOS E	20.4	145.6	0.93	0.95	23.7
All Vehicles		5381	5.9	1.041	49.7	LOS D	35.5	259.8	0.83	0.84	30.9

PHASING SUMMARY



Site: I-10 2014 BASE AM


Heathcote Road / Nuwarra Road / Wattle Grove Drive

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 131 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	D	E	G
Reference Phase	Yes	No	No	No	No
Phase Change Time (sec)	0	54	67	86	114
Green Time (sec)	48	7	13	22	11
Yellow Time (sec)	4	4	4	4	4
All-Red Time (sec)	2	2	2	2	2
Phase Time (sec)	54	13	19	28	17
Phase Split	41 %	10 %	15 %	21 %	13 %



MOVEMENT SUMMARY



Site: I-10 2014 BASE PM

Heathcote Road / Nuwarra Road / Wattle Grove Drive

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 139 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
SouthEast: Heathcote Road (SE)											
4	L2	283	2.6	0.232	13.0	LOS A	6.7	48.3	0.41	0.67	44.2
5	T1	1098	5.5	0.754	34.4	LOS C	29.6	216.9	0.83	0.74	38.0
6	R2	395	3.2	0.944	94.6	LOS F	16.3	117.0	1.00	1.05	23.6
Approach		1776	4.5	0.944	44.3	LOS D	29.6	216.9	0.80	0.80	33.6
NorthEast: Nuwarra Road (NE)											
7	L2	513	2.5	0.656	36.4	LOS C	23.1	165.4	0.85	0.97	37.4
8	T1	541	1.2	0.830	64.6	LOS E	19.6	138.7	1.00	0.93	23.3
9	R2	467	6.1	0.936	86.4	LOS F	19.6	144.2	1.00	1.00	24.2
Approach		1521	3.1	0.936	61.8	LOS E	23.1	165.4	0.95	0.97	27.7
NorthWest: Heathcote Road (NW)											
10	L2	209	6.0	0.193	21.9	LOS B	6.9	50.9	0.53	0.72	42.6
11	T1	1317	2.7	0.936	53.1	LOS D	45.6	326.8	0.87	0.93	31.7
12	R2	379	1.9	0.838	76.5	LOS F	14.1	100.0	1.00	0.90	19.7
Approach		1905	2.9	0.936	54.3	LOS D	45.6	326.8	0.86	0.90	30.1
SouthWest: Wattle Grove Drive (SW)											
1	L2	252	1.7	0.291	22.9	LOS B	10.1	72.1	0.66	0.74	35.8
2	T1	278	1.1	0.378	55.7	LOS D	8.4	59.2	0.93	0.76	25.2
3	R2	261	1.2	0.970	99.2	LOS F	22.4	158.5	1.00	1.11	17.3
Approach		791	1.3	0.970	59.6	LOS E	22.4	158.5	0.87	0.87	23.7
All Vehicles		5993	3.2	0.970	54.0	LOS D	45.6	326.8	0.87	0.88	29.6

PHASING SUMMARY



Site: I-10 2014 BASE PM


Heathcote Road / Nuwarra Road / Wattle Grove Drive

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 139 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	G
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	61	87	117
Green Time (sec)	55	20	24	16
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	61	26	30	22
Phase Split	44 %	19 %	22 %	16 %



I-11 Intersection of Newbridge Road and Nuwarra Road

MOVEMENT SUMMARY

 **Site: I-11 2014 BASE AM**

Newbridge Road / Nuwarra Road

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c sec	Level of Service	95% Back of Queue Vehicles veh	Prop. Queued Distance m	Effective Stop Rate per veh	Average Speed km/h
South: Nuwarra Road (S)									
1	L2	27	7.7	0.528	LOS D	17.8	127.1	0.87	38.2
2	T1	294	1.8	0.528	LOS D	17.8	127.1	0.87	31.7
3	R2	683	6.8	0.991	LOS F	35.9	265.8	1.00	22.8
Approach		1004	5.3	0.991	LOS F	35.9	265.8	0.96	25.2
East: Newbridge Road (E)									
4	L2	255	17.8	0.438	LOS B	11.3	90.0	0.62	48.4
5	T1	871	11.4	0.438	LOS B	12.9	99.4	0.56	53.1
Approach		1125	12.8	0.438	LOS B	12.9	99.4	0.57	52.0
North: Nuwarra Road (N)									
7	L2	6	0.0	0.761	LOS F	7.1	50.3	1.00	26.7
8	T1	122	0.9	0.952	LOS F	11.4	82.3	1.00	24.9
9	R2	106	5.0	0.952	LOS F	11.4	82.3	1.00	24.6
Approach		235	2.7	0.952	LOS F	11.4	82.3	1.00	24.8
West: Newbridge Road (W)									
10	L2	234	2.3	0.836	LOS C	35.7	263.5	0.88	36.9
11	T1	1668	9.0	0.890	LOS C	42.4	319.7	0.89	45.0
Approach		1902	8.1	0.890	LOS C	42.4	319.7	0.89	43.8
All Vehicles		4266	8.4	0.991	LOS D	42.4	319.7	0.83	37.7

PHASING SUMMARY

 **Site: I-11 2014 BASE AM**


Newbridge Road / Nuwarra Road

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	89
Green Time (sec)	66	11	45
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	17	51
Phase Split	51 %	12 %	36 %



MOVEMENT SUMMARY



Site: I-11 2014 BASE PM

Newbridge Road / Nuwarra Road

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Nuwarra Road (S)											
1	L2	48	6.5	0.641	66.9	LOS E	11.9	85.0	0.99	0.82	32.8
2	T1	134	0.8	0.641	62.5	LOS E	11.9	85.0	0.99	0.82	29.8
3	R2	457	6.2	0.856	77.4	LOS F	16.9	124.5	1.00	0.93	28.5
Approach		639	5.1	0.856	73.5	LOS F	16.9	124.5	1.00	0.90	29.1
East: Newbridge Road (E)											
4	L2	655	4.5	0.628	13.6	LOS A	16.0	116.6	0.37	0.68	53.1
5	T1	1838	5.8	0.628	12.2	LOS A	24.2	178.0	0.47	0.47	58.6
Approach		2493	5.4	0.628	12.6	LOS A	24.2	178.0	0.44	0.52	57.2
North: Nuwarra Road (N)											
7	L2	15	0.0	0.766	70.4	LOS E	14.6	102.9	1.00	0.90	30.2
8	T1	258	0.8	0.957	72.8	LOS F	20.3	143.2	1.00	0.95	27.9
9	R2	178	1.2	0.957	96.3	LOS F	20.3	143.2	1.00	1.10	26.2
Approach		451	0.9	0.957	82.0	LOS F	20.3	143.2	1.00	1.01	27.2
West: Newbridge Road (W)											
10	L2	82	0.0	0.395	18.2	LOS B	10.5	77.2	0.40	0.43	50.2
11	T1	1271	7.8	0.449	11.2	LOS A	11.3	84.4	0.38	0.36	59.5
Approach		1353	7.3	0.449	11.6	LOS A	11.3	84.4	0.38	0.36	58.8
All Vehicles		4935	5.5	0.957	26.5	LOS B	24.2	178.0	0.55	0.57	47.3

PHASING SUMMARY



Site: I-11 2014 BASE PM


Newbridge Road / Nuwarra Road

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	87	113
Green Time (sec)	81	20	21
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	87	26	27
Phase Split	62 %	19 %	19 %



I-12 Intersection of Newbridge Road and Governor Macquarie Drive

MOVEMENT SUMMARY



Site: I-12 2014 BASE AM

Newbridge Road / Governor Macquarie Drive

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Brickmakers Drive (S)											
1	L2	9	0.0	0.763	72.0	LOS F	13.0	91.7	1.00	0.89	26.5
2	T1	177	1.2	0.763	67.7	LOS E	13.0	91.7	1.00	0.89	26.2
3	R2	571	1.1	0.982	102.4	LOS F	24.7	174.7	1.00	1.12	26.7
Approach		757	1.1	0.982	93.9	LOS F	24.7	174.7	1.00	1.06	26.6
East: Newbridge Road (E)											
4	L2	183	2.9	0.132	7.5	LOS A	1.4	9.9	0.16	0.63	58.3
5	T1	1001	10.9	0.292	12.4	LOS A	10.1	77.5	0.49	0.43	60.8
6	R2	585	10.3	0.809	72.0	LOS F	20.3	154.6	1.00	0.88	36.0
Approach		1769	9.9	0.809	31.6	LOS C	20.3	154.6	0.62	0.60	49.2
North: Governor Macquarie Drive (N)											
7	L2	614	8.9	0.586	50.4	LOS D	17.8	133.9	0.91	0.83	40.8
8	T1	116	2.7	0.470	63.5	LOS E	7.5	53.6	0.97	0.78	27.1
9	R2	141	35.1	0.831	80.5	LOS F	10.5	95.4	1.00	0.93	28.2
Approach		871	12.3	0.831	57.0	LOS E	17.8	133.9	0.93	0.84	37.0
West: Newbridge Road (W)											
10	L2	115	31.2	0.908	51.2	LOS D	52.4	399.7	0.97	0.96	37.4
11	T1	2239	6.8	0.908	43.5	LOS D	53.7	397.4	0.96	0.95	45.8
12	R2	4	25.0	0.022	32.1	LOS C	0.2	1.4	0.60	0.66	38.2
Approach		2358	8.0	0.908	43.8	LOS D	53.7	399.7	0.96	0.95	45.4
All Vehicles		5755	8.3	0.982	48.6	LOS D	53.7	399.7	0.86	0.84	41.9

PHASING SUMMARY



Site: I-12 2014 BASE AM


Newbridge Road / Governor Macquarie Drive

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	G1
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	66	88	112
Green Time (sec)	60	16	18	22
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	66	22	24	28
Phase Split	47 %	16 %	17 %	20 %



MOVEMENT SUMMARY



Site: I-12 2014 BASE PM

Newbridge Road / Governor Macquarie Drive

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Brickmakers Drive (S)											
1	L2	8	0.0	0.450	68.6	LOS E	5.9	43.2	0.98	0.77	27.2
2	T1	82	5.1	0.450	64.5	LOS E	5.9	43.2	0.98	0.77	26.9
3	R2	219	1.0	0.519	69.0	LOS E	7.2	51.0	0.99	0.79	32.8
Approach		309	2.0	0.519	67.8	LOS E	7.2	51.0	0.98	0.78	31.3
East: Newbridge Road (E)											
4	L2	578	1.5	0.420	9.2	LOS A	6.7	47.8	0.27	0.68	57.2
5	T1	2273	4.4	0.693	15.2	LOS B	36.4	264.2	0.64	0.59	59.1
6	R2	641	11.2	1.023	133.8	LOS F	32.6	249.9	1.00	1.12	26.0
Approach		3492	5.2	1.023	36.0	LOS C	36.4	264.2	0.65	0.70	47.4
North: Governor Macquarie Drive (N)											
7	L2	473	3.6	0.371	47.4	LOS D	12.7	91.4	0.84	0.80	41.9
8	T1	265	0.8	0.851	73.0	LOS F	19.0	133.8	1.00	0.94	25.2
9	R2	203	19.2	0.963	101.0	LOS F	17.4	141.9	1.00	1.06	25.1
Approach		941	6.2	0.963	66.2	LOS E	19.0	141.9	0.92	0.89	33.2
West: Newbridge Road (W)											
10	L2	151	16.8	0.628	35.6	LOS C	26.2	197.3	0.74	0.71	43.1
11	T1	1579	6.1	0.628	28.0	LOS B	26.2	197.3	0.72	0.65	52.1
12	R2	3	0.0	0.043	39.7	LOS C	0.1	1.0	0.67	0.68	35.1
Approach		1733	7.0	0.628	28.7	LOS C	26.2	197.3	0.72	0.66	51.3
All Vehicles		6475	5.7	1.023	39.9	LOS C	36.4	264.2	0.72	0.72	45.0

PHASING SUMMARY



Site: I-12 2014 BASE PM


Newbridge Road / Governor Macquarie Drive

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	G1
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	67	89	110
Green Time (sec)	61	16	15	24
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	67	22	21	30
Phase Split	48 %	16 %	15 %	21 %



I-13 Intersection of Moorebank Avenue and M5 Motorway

MOVEMENT SUMMARY

 **Site: I-13 2014 BASE AM**

Moorebank Avenue / the M5 Motorway

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 74 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	255	11.2	0.217	8.8	LOS A	2.7	20.7	0.40	0.66	50.6
2	T1	576	4.2	0.660	29.2	LOS C	9.9	71.5	0.96	0.83	39.3
3	R2	257	2.9	0.358	32.7	LOS C	4.4	31.9	0.89	0.77	37.0
Approach		1087	5.5	0.660	25.2	LOS B	9.9	71.5	0.81	0.77	40.8
East: M5 Motorway on&off ramp (E)											
4	L2	219	7.2	0.209	7.6	LOS A	1.5	11.4	0.35	0.65	51.8
6	R2	224	6.1	0.233	28.7	LOS C	3.2	23.7	0.82	0.75	40.5
Approach		443	6.7	0.233	18.3	LOS B	3.2	23.7	0.59	0.70	45.1
North: Moorebank Avenue (N)											
7	L2	43	48.8	0.042	7.5	LOS A	0.3	2.5	0.26	0.59	51.4
8	T1	143	12.5	0.173	25.1	LOS B	2.1	16.4	0.84	0.65	41.2
9	R2	409	26.2	0.699	36.2	LOS C	8.5	73.1	0.96	0.84	36.9
Approach		596	24.6	0.699	31.5	LOS C	8.5	73.1	0.88	0.78	38.6
West: M5 Motorway on&off ramp (W)											
10	L2	1462	8.2	0.833	6.1	LOS A	0.0	0.0	0.00	0.52	54.1
12	R2	324	4.2	0.333	29.5	LOS C	4.8	34.8	0.85	0.77	38.8
Approach		1786	7.5	0.833	10.3	LOS A	4.8	34.8	0.15	0.57	50.8
All Vehicles		3913	9.4	0.833	18.6	LOS B	9.9	73.1	0.50	0.67	45.1

PHASING SUMMARY

 **Site: I-13 2014 BASE AM**


Moorebank Avenue / the M5 Motorway

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 74 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	E	F
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	24	51
Green Time (sec)	17	20	16
Yellow Time (sec)	4	4	4
All-Red Time (sec)	3	3	3
Phase Time (sec)	24	27	23
Phase Split	32 %	36 %	31 %



MOVEMENT SUMMARY



Site: I-13 2014 BASE PM

Moorebank Avenue / the M5 Motorway

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 94 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	271	3.1	0.320	16.5	LOS B	6.2	44.6	0.62	0.74	45.6
2	T1	151	7.7	0.381	44.1	LOS D	3.4	25.1	0.97	0.75	33.3
3	R2	234	2.3	0.194	27.6	LOS B	4.0	28.7	0.72	0.74	39.3
Approach		655	3.9	0.381	26.8	LOS B	6.2	44.6	0.74	0.74	39.9
East: M5 Motorway on&off ramp (E)											
4	L2	332	2.9	0.335	9.9	LOS A	4.6	32.9	0.47	0.69	50.1
6	R2	73	21.7	0.133	42.3	LOS C	1.4	12.0	0.88	0.72	35.0
Approach		404	6.3	0.335	15.8	LOS B	4.6	32.9	0.54	0.70	46.2
North: Moorebank Avenue (N)											
7	L2	109	6.7	0.084	6.7	LOS A	0.6	4.8	0.22	0.60	53.1
8	T1	609	3.6	0.654	35.0	LOS C	12.8	92.3	0.96	0.81	36.7
9	R2	1321	7.4	0.880	38.4	LOS C	28.4	211.5	0.99	1.03	36.3
Approach		2040	6.2	0.880	35.7	LOS C	28.4	211.5	0.94	0.94	37.1
West: M5 Motorway on&off ramp (W)											
10	L2	546	15.2	0.326	5.8	LOS A	0.0	0.0	0.00	0.52	54.3
12	R2	221	3.8	0.359	43.8	LOS D	4.6	33.3	0.93	0.78	33.2
Approach		767	11.9	0.359	16.7	LOS B	4.6	33.3	0.27	0.59	46.5
All Vehicles		3866	7.0	0.880	28.3	LOS B	28.4	211.5	0.73	0.81	40.0

PHASING SUMMARY



Site: I-13 2014 BASE PM


Moorebank Avenue / the M5 Motorway

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 94 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	E	F
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	17	30	53
Green Time (sec)	10	6	16	34
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	3	3	3	3
Phase Time (sec)	17	13	23	41
Phase Split	18 %	14 %	24 %	44 %



I-14 Intersection of M5 Motorway and Hume Highway

MOVEMENT SUMMARY

 **Site: I-14 2014 BASE AM**

M5 Motorway / Hume Highway

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 159 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows	Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed	
		Total veh/h	HV %			v/c	sec				Vehicles veh
South: Hume Highway (S)											
2	T1	3674	4.5	0.886	2.0	LOS A	18.4	133.7	0.22	0.21	58.4
3	R2	553	4.2	0.761	37.2	LOS C	13.2	96.0	0.95	0.83	39.8
Approach		4226	4.5	0.886	6.6	LOS A	18.4	133.7	0.31	0.29	55.0
East: M5 Motorway on&off-ramp (E)											
4	L2	288	6.6	0.115	30.3	LOS C	4.1	30.0	0.59	0.70	42.0
6	R2	1001	3.9	1.030	144.1	LOS F	38.2	276.2	1.00	1.13	15.2
Approach		1289	4.5	1.030	118.7	LOS F	38.2	276.2	0.91	1.04	18.8
North: Hume Highway (N)											
7	L2	604	5.9	0.447	10.1	LOS A	12.9	94.9	0.37	0.68	48.9
8	T1	1140	7.0	0.463	28.1	LOS B	16.4	121.8	0.61	0.53	43.5
Approach		1744	6.6	0.463	21.8	LOS B	16.4	121.8	0.53	0.58	44.8
All Vehicles		7260	5.0	1.030	30.2	LOS C	38.2	276.2	0.47	0.49	41.5

PHASING SUMMARY

 **Site: I-14 2014 BASE AM**


M5 Motorway / Hume Highway

2014 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 159 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C	D
Reference Phase	No	No	No	Yes
Phase Change Time (sec)	20	97	123	0
Green Time (sec)	70	19	29	13
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	3	3	3	3
Phase Time (sec)	77	26	36	20
Phase Split	48 %	16 %	23 %	13 %



MOVEMENT SUMMARY



Site: I-14 2014 BASE PM

M5 Motorway / Hume Highway

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 159 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
2	T1	2325	3.8	0.568	2.0	LOS A	5.7	40.9	0.11	0.10	58.4
3	R2	349	1.8	0.891	82.9	LOS F	14.3	101.8	1.00	0.91	28.2
Approach		2675	3.5	0.891	12.6	LOS A	14.3	101.8	0.22	0.20	51.2
East: M5 Motorway on&off-ramp (E)											
4	L2	1167	3.6	0.836	59.7	LOS E	38.9	280.4	0.91	0.89	32.8
6	R2	936	3.6	0.884	84.4	LOS F	26.3	189.9	1.00	0.95	21.9
Approach		2103	3.6	0.884	70.7	LOS F	38.9	280.4	0.95	0.92	28.0
North: Hume Highway (N)											
7	L2	743	2.1	0.518	8.8	LOS A	14.8	105.7	0.36	0.68	50.0
8	T1	2613	2.7	0.803	18.8	LOS B	41.2	294.9	0.68	0.63	47.8
Approach		3356	2.6	0.803	16.6	LOS B	41.2	294.9	0.61	0.64	48.2
All Vehicles		8134	3.1	0.891	29.3	LOS C	41.2	294.9	0.57	0.57	41.9

PHASING SUMMARY



Site: I-14 2014 BASE PM


M5 Motorway / Hume Highway

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 159 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	97	121
Green Time (sec)	90	17	31
Yellow Time (sec)	4	4	4
All-Red Time (sec)	3	3	3
Phase Time (sec)	97	24	38
Phase Split	61 %	15 %	24 %



I-15 Intersection of Cambridge Avenue and Canterbury Road

MOVEMENT SUMMARY



Site: I-15 2014 BASE AM

Canterbury Road / Cambridge Avenue / Glenfield Road

2014 BASE AM PEAK 7:45 am - 8:45 am

Roundabout

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
							Vehicles veh	Distance m			
South: Canterbury Road (S)											
1	L2	357	3.5	0.369	5.3	LOS A	2.0	14.4	0.48	0.60	53.4
2	T1	6	0.0	0.617	5.1	LOS A	4.8	34.0	0.58	0.70	51.8
3	R2	788	2.1	0.617	10.5	LOS A	4.8	34.0	0.58	0.70	51.9
Approach		1152	2.6	0.617	8.8	LOS A	4.8	34.0	0.55	0.67	52.3
East: Cambridge Avenue (E)											
4	L2	235	3.1	0.125	3.5	LOS A	0.0	0.0	0.00	0.43	56.5
5	T1	63	8.3	0.063	5.0	LOS A	0.3	2.5	0.47	0.55	53.6
6	R2	42	10.0	0.063	10.3	LOS A	0.3	2.5	0.47	0.58	53.8
Approach		340	5.0	0.125	4.6	LOS A	0.3	2.5	0.15	0.47	55.6
North: Railway Parade (N)											
7	L2	239	3.1	0.364	10.2	LOS A	2.4	16.9	0.86	0.93	51.0
8	T1	3	33.3	0.290	11.5	LOS A	1.6	11.8	0.82	0.93	48.2
9	R2	136	8.5	0.290	16.8	LOS B	1.6	11.8	0.82	0.93	47.2
Approach		378	5.3	0.364	12.6	LOS A	2.4	16.9	0.84	0.93	49.6
West: Glenfield Road (W)											
10	L2	281	5.2	0.510	10.9	LOS A	4.3	31.8	0.90	0.98	49.3
11	T1	141	6.7	0.510	11.2	LOS A	4.3	31.8	0.90	1.00	49.4
12	R2	254	5.8	0.510	17.4	LOS B	4.0	29.7	0.89	1.03	47.4
Approach		676	5.8	0.510	13.4	LOS A	4.3	31.8	0.89	1.00	48.6
All Vehicles		2545	4.1	0.617	10.0	LOS A	4.8	34.0	0.63	0.77	51.4

MOVEMENT SUMMARY



Site: I-15 2014 BASE PM

Canterbury Road / Cambridge Avenue / Glenfield Road

2014 BASE PM PEAK 4:30 pm - 5:30 pm

Roundabout

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
							Vehicles veh	Distance m			
South: Canterbury Road (S)											
1	L2	237	2.2	0.264	6.2	LOS A	1.3	9.2	0.59	0.72	53.0
2	T1	5	0.0	0.240	5.7	LOS A	1.2	8.5	0.57	0.77	51.9
3	R2	240	1.3	0.240	11.1	LOS A	1.2	8.5	0.57	0.77	52.0
Approach		482	1.7	0.264	8.6	LOS A	1.3	9.2	0.58	0.75	52.4
East: Cambridge Avenue (E)											
4	L2	908	2.3	0.480	3.5	LOS A	0.0	0.0	0.00	0.43	56.4
5	T1	201	7.9	0.280	5.8	LOS A	1.8	12.7	0.58	0.64	52.8
6	R2	252	0.8	0.280	10.9	LOS A	1.8	12.7	0.60	0.68	53.0
Approach		1361	2.9	0.480	5.2	LOS A	1.8	12.7	0.20	0.51	55.2
North: Railway Parade (N)											
7	L2	81	1.3	0.103	6.5	LOS A	0.5	3.3	0.57	0.68	53.8
8	T1	1	0.0	0.161	6.0	LOS A	0.8	6.0	0.58	0.76	51.8
9	R2	153	8.3	0.161	11.4	LOS A	0.8	6.0	0.58	0.76	50.7
Approach		235	5.8	0.161	9.7	LOS A	0.8	6.0	0.57	0.73	51.8
West: Glenfield Road (W)											
10	L2	205	4.6	0.274	6.4	LOS A	1.4	10.5	0.58	0.68	52.8
11	T1	37	0.0	0.274	6.3	LOS A	1.4	10.5	0.58	0.68	54.9
12	R2	359	3.8	0.342	11.4	LOS A	2.0	14.5	0.60	0.76	50.7
Approach		601	3.9	0.342	9.4	LOS A	2.0	14.5	0.59	0.73	51.6
Vehicles		2679	3.1	0.480	7.2	LOS A	2.0	14.5	0.39	0.62	53.6

Appendix D

2015 SIDRA results with and
without Moorebank IMT

1. 2015 Future traffic with Moorebank IMT development (Early Works)

I-01 Intersection of Moorebank Avenue and Bapaume Road

MOVEMENT SUMMARY

▽ Site: I-01 2015 FU MINT AM

Intersection of Moorebank Avenue and Bapaume Road

2015 Future with MINT AM PEAK

Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	23	0.0	0.012	8.2	LOS A	0.0	0.0	0.00	0.67	36.0
2	T1	1086	5.6	0.577	0.0	LOS A	0.0	0.0	0.00	0.00	59.8
Approach		1109	5.5	0.577	0.2	NA	0.0	0.0	0.00	0.01	59.0
North: Moorebank Avenue (S)											
8	T1	775	6.3	0.344	2.9	LOS A	3.2	23.1	0.17	0.08	52.7
9	R2	88	2.4	0.344	25.2	LOS B	3.2	23.1	1.00	0.45	32.9
Approach		863	5.9	0.344	5.2	NA	3.2	23.1	0.25	0.11	49.6
West: Bapaume Road (W)											
10	L2	4	50.0	0.033	35.0	LOS C	0.1	1.0	0.87	0.93	22.7
12	R2	1	0.0	0.060	193.8	LOS F	0.2	1.1	0.98	0.99	5.9
Approach		5	40.0	0.060	66.8	LOS E	0.2	1.1	0.89	0.95	14.5
All Vehicles		1978	5.7	0.577	2.6	NA	3.2	23.1	0.11	0.06	52.3

MOVEMENT SUMMARY

▽ Site: I-01 2015 FU MINT PM

Intersection of Moorebank Avenue and Bapaume Road

2015 Future with MINT PM PEAK

Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.001	8.2	LOS A	0.0	0.0	0.00	0.67	36.0
2	T1	572	5.0	0.303	0.0	LOS A	0.0	0.0	0.00	0.00	59.9
Approach		573	5.0	0.303	0.0	NA	0.0	0.0	0.00	0.00	59.9
North: Moorebank Avenue (S)											
8	T1	1383	3.1	0.377	3.2	LOS A	6.1	44.3	0.37	0.01	51.4
9	R2	20	15.8	0.377	14.7	LOS B	6.1	44.3	0.77	0.03	44.6
Approach		1403	3.3	0.377	3.3	NA	6.1	44.3	0.37	0.01	51.3
West: Bapaume Road (W)											
10	L2	97	4.3	0.160	12.5	LOS A	0.6	4.5	0.56	0.82	37.8
12	R2	17	0.0	0.616	220.7	LOS F	1.9	13.0	0.99	1.05	5.2
Approach		114	3.7	0.616	43.4	LOS D	1.9	13.0	0.63	0.86	19.7
All Vehicles		2089	3.8	0.616	4.6	NA	6.1	44.3	0.29	0.06	48.4

I-02 Intersection of Moorebank Avenue and Anzac Road

MOVEMENT SUMMARY



Site: I-02 2015 FU MINT AM

Intersection of Moorebank Avenue and Anzac Road

2015 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Total	Flows HV	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
2	T1	919	3.9	0.711	10.9	LOS A	28.2	204.2	0.67	0.62	44.0
3	R2	346	3.3	0.620	22.4	LOS B	11.2	80.6	0.68	0.82	37.1
Approach		1265	3.7	0.711	14.0	LOS A	28.2	204.2	0.68	0.68	41.9
East: Anzac Road (E)											
4	L2	187	3.9	0.594	51.5	LOS D	8.9	64.5	0.97	0.82	24.8
6	R2	194	13.6	0.655	52.5	LOS D	9.4	73.8	0.98	0.83	24.6
Approach		381	8.8	0.655	52.0	LOS D	9.4	73.8	0.98	0.83	24.7
North: Moorebank Avenue (N)											
7	L2	274	10.0	0.179	8.3	LOS A	1.0	7.4	0.15	0.63	35.7
8	T1	505	4.4	0.296	6.7	LOS A	7.5	54.7	0.41	0.36	36.1
Approach		779	6.4	0.296	7.3	LOS A	7.5	54.7	0.32	0.45	36.0
All Vehicles		2425	5.4	0.711	17.8	LOS B	28.2	204.2	0.61	0.63	36.0

PHASING SUMMARY



Site: I-02 2015 FU MINT AM


Intersection of Moorebank Avenue and Anzac Road

2015 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C
Phase Change Time (sec)	0	76
Green Time (sec)	70	21
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	76	27
Phase Split	74 %	26 %



MOVEMENT SUMMARY



Site: I-02 2015 FU MINT PM

Intersection of Moorebank Avenue and Anzac Road

2015 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
2	T1	314	4.7	0.272	10.6	LOS A	7.7	56.4	0.50	0.43	44.7
3	R2	176	1.2	0.966	103.0	LOS F	14.9	105.6	1.00	1.18	15.6
Approach		489	3.4	0.966	43.8	LOS D	14.9	105.6	0.68	0.70	26.8
East: Anzac Road (E)											
4	L2	412	2.3	0.799	51.5	LOS D	21.9	156.4	0.99	0.91	24.8
6	R2	279	5.7	0.614	47.5	LOS D	13.4	98.2	0.94	0.84	26.0
Approach		691	3.7	0.799	49.9	LOS D	21.9	156.4	0.97	0.88	25.3
North: Moorebank Avenue (N)											
7	L2	292	4.0	0.181	8.3	LOS A	1.0	7.4	0.14	0.65	35.8
8	T1	1105	2.9	0.715	14.5	LOS A	30.5	219.0	0.69	0.62	25.4
Approach		1397	3.1	0.715	13.2	LOS A	30.5	219.0	0.57	0.63	27.0
All Vehicles		2577	3.3	0.966	28.8	LOS C	30.5	219.0	0.70	0.71	26.2

PHASING SUMMARY



Site: I-02 2015 FU MINT PM


Intersection of Moorebank Avenue and Anzac Road

2015 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C
Phase Change Time (sec)	0	73
Green Time (sec)	67	31
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	73	37
Phase Split	66 %	34 %



I-03 Intersection of Moorebank Avenue and Defence Support Access

MOVEMENT SUMMARY



Site: I-03 2015 FU MINT AM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2015 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	8	0.0	0.005	8.6	LOS A	0.0	0.2	0.14	0.67	46.5
2	T1	1263	3.6	0.866	12.1	LOS A	42.8	308.7	0.76	0.75	40.4
Approach		1272	3.6	0.866	12.1	LOS A	42.8	308.7	0.75	0.75	40.4
North: Moorebank Avenue (N)											
8	T1	616	4.6	0.494	9.2	LOS A	12.1	88.1	0.53	0.48	45.8
9	R2	23	13.6	0.494	19.8	LOS B	12.1	88.1	0.62	0.57	43.3
Approach		639	4.9	0.494	9.6	LOS A	12.1	88.1	0.53	0.49	45.7
West: Military Access 1 (W)											
10	L2	4	75.0	0.048	51.0	LOS D	0.2	2.4	0.94	0.65	11.6
12	R2	1	0.0	0.048	51.1	LOS D	0.2	2.4	0.94	0.65	11.6
Approach		5	60.0	0.048	51.0	LOS D	0.2	2.4	0.94	0.65	11.6
All Vehicles		1916	4.2	0.866	11.4	LOS A	42.8	308.7	0.68	0.66	42.1

PHASING SUMMARY



Site: I-03 2015 FU MINT AM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2015 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Phase Change Time (sec)	0	75
Green Time (sec)	69	9
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	75	15
Phase Split	83 %	17 %



MOVEMENT SUMMARY



Site: I-03 2015 FU MINT PM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2015 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.001	8.6	LOS A	0.0	0.0	0.14	0.66	46.6
2	T1	466	3.2	0.318	3.4	LOS A	6.2	44.6	0.33	0.30	52.1
Approach		467	3.2	0.318	3.4	LOS A	6.2	44.6	0.33	0.30	52.1
North: Moorebank Avenue (N)											
8	T1	1492	2.7	0.967	35.2	LOS C	59.3	425.4	0.59	0.78	29.6
9	R2	4	75.0	0.967	52.4	LOS D	59.3	425.4	0.67	0.93	26.4
Approach		1496	2.9	0.967	35.3	LOS C	59.3	425.4	0.59	0.78	29.6
West: Military Access 1 (W)											
10	L2	23	13.6	0.217	51.7	LOS D	1.4	10.4	0.96	0.72	11.5
12	R2	8	0.0	0.217	51.8	LOS D	1.4	10.4	0.96	0.72	11.5
Approach		32	10.0	0.217	51.7	LOS D	1.4	10.4	0.96	0.72	11.5
All Vehicles		1995	3.1	0.967	28.1	LOS B	59.3	425.4	0.53	0.67	32.2

PHASING SUMMARY



Site: I-03 2015 FU MINT PM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2015 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Phase Change Time (sec)	0	75
Green Time (sec)	69	9
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	75	15
Phase Split	83 %	17 %



I-04 Intersection of Moorebank Avenue and DNSDC Access

MOVEMENT SUMMARY



Site: I-04 2015 FU MINT AM

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2015 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
2	T1	1272	3.6	0.705	5.4	LOS A	19.7	142.2	0.52	0.48	49.9
3	R2	22	0.0	0.705	14.3	LOS A	19.7	142.2	0.59	0.55	48.9
Approach		1294	3.5	0.705	5.5	LOS A	19.7	142.2	0.52	0.48	49.9
East: DNSDC Access (W)											
4	L2	5	20.0	0.037	45.8	LOS D	0.2	1.6	0.94	0.65	26.5
6	R2	7	14.3	0.039	43.5	LOS D	0.3	2.1	0.92	0.66	27.2
Approach		13	16.7	0.039	44.5	LOS D	0.3	2.1	0.93	0.66	26.9
North: Moorebank Avenue (N)											
7	L2	94	6.7	0.062	8.7	LOS A	0.3	2.3	0.17	0.66	46.4
8	T1	522	4.2	0.373	4.0	LOS A	7.3	52.9	0.39	0.35	50.9
Approach		616	4.6	0.373	4.8	LOS A	7.3	52.9	0.36	0.40	50.2
West: Carpark Access (W)											
10	L2	1	0.0	0.005	42.5	LOS C	0.0	0.3	0.90	0.60	12.9
12	R2	1	0.0	0.007	45.1	LOS D	0.0	0.3	0.93	0.60	12.1
Approach		2	0.0	0.007	43.8	LOS D	0.0	0.3	0.92	0.60	12.5
All Vehicles		1924	3.9	0.705	5.6	LOS A	19.7	142.2	0.47	0.46	49.6

PHASING SUMMARY



Site: I-04 2015 FU MINT AM


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2015 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Phase Change Time (sec)	0	65
Green Time (sec)	59	9
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	65	15
Phase Split	81 %	19 %



MOVEMENT SUMMARY

 **Site: I-04 2015 FU MINT PM**

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2015 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
2	T1	466	3.2	0.232	3.3	LOS A	4.9	35.5	0.28	0.24	53.7
3	R2	1	0.0	0.232	11.8	LOS A	4.9	35.5	0.30	0.26	53.1
Approach		467	3.2	0.232	3.3	LOS A	4.9	35.5	0.28	0.24	53.7
East: DNSDC Access (W)											
4	L2	4	0.0	0.042	63.6	LOS E	0.2	1.6	0.97	0.64	21.8
6	R2	22	9.5	0.157	61.1	LOS E	1.2	8.7	0.96	0.71	22.3
Approach		26	8.0	0.157	61.5	LOS E	1.2	8.7	0.96	0.70	22.2
North: Moorebank Avenue (N)											
7	L2	6	16.7	0.004	8.5	LOS A	0.0	0.2	0.11	0.60	46.7
8	T1	1494	2.6	0.966	37.9	LOS C	96.9	693.3	0.95	1.08	25.5
Approach		1500	2.7	0.966	37.7	LOS C	96.9	693.3	0.94	1.08	25.5
West: Carpark Access (W)											
10	L2	1	0.0	0.007	58.7	LOS E	0.1	0.4	0.94	0.60	9.9
12	R2	1	0.0	0.010	62.9	LOS E	0.1	0.4	0.96	0.59	9.2
Approach		2	0.0	0.010	60.8	LOS E	0.1	0.4	0.95	0.59	9.5
All Vehicles		1996	2.8	0.966	30.0	LOS C	96.9	693.3	0.79	0.88	29.6

PHASING SUMMARY

 **Site: I-04 2015 FU MINT PM**


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2015 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Phase Change Time (sec)	0	95
Green Time (sec)	89	9
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	95	15
Phase Split	86 %	14 %



I-05 Intersection of Moorebank Avenue and Chatham Avenue

MOVEMENT SUMMARY



Site: I-05 2015 FU MINT AM

Intersection of Moorebank Avenue and Chatham Avenue

2015 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Total	Flows HV	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	5	0.0	0.003	9.7	LOS A	0.0	0.3	0.17	0.67	47.3
2	T1	1292	3.3	0.971	48.9	LOS D	91.2	657.0	1.00	1.17	24.6
Approach		1297	3.3	0.971	48.7	LOS D	91.2	657.0	1.00	1.16	24.6
North: Moorebank Avenue (N)											
8	T1	514	4.1	0.337	2.9	LOS A	7.0	51.1	0.28	0.25	54.2
9	R2	14	15.4	0.083	52.5	LOS D	0.7	5.3	0.91	0.70	24.4
Approach		527	4.4	0.337	4.2	LOS A	7.0	51.1	0.30	0.27	52.6
West: Chatham Avenue (W)											
10	L2	3	66.7	0.023	52.4	LOS D	0.2	2.0	0.88	0.64	21.9
12	R2	1	0.0	0.023	52.5	LOS D	0.2	2.0	0.88	0.64	21.9
Approach		4	50.0	0.023	52.4	LOS D	0.2	2.0	0.88	0.64	21.9
All Vehicles		1828	3.7	0.971	35.9	LOS C	91.2	657.0	0.80	0.90	29.1

PHASING SUMMARY



Site: I-05 2015 FU MINT AM


Intersection of Moorebank Avenue and Chatham Avenue

2015 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Phase Change Time (sec)	0	83	95
Green Time (sec)	77	6	9
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	83	12	15
Phase Split	75 %	11 %	14 %



MOVEMENT SUMMARY



Site: I-05 2015 FU MINT PM

Intersection of Moorebank Avenue and Chatham Avenue

2015 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.001	9.9	LOS A	0.0	0.1	0.18	0.66	47.2
2	T1	453	2.8	0.353	7.5	LOS A	9.4	67.2	0.46	0.41	47.9
Approach		454	2.8	0.353	7.5	LOS A	9.4	67.2	0.46	0.41	47.9
North: Moorebank Avenue (N)											
8	T1	1496	2.5	0.992	54.9	LOS D	109.2	780.2	1.00	1.26	23.0
9	R2	3	66.7	0.007	13.8	LOS A	0.0	0.5	0.38	0.54	43.3
Approach		1499	2.6	0.992	54.8	LOS D	109.2	780.2	1.00	1.26	23.0
West: Chatham Avenue (W)											
10	L2	14	15.4	0.081	49.3	LOS D	0.8	6.3	0.90	0.70	22.8
12	R2	5	0.0	0.081	49.5	LOS D	0.8	6.3	0.90	0.70	22.8
Approach		19	11.1	0.081	49.4	LOS D	0.8	6.3	0.90	0.70	22.8
All Vehicles		1972	2.7	0.992	43.9	LOS D	109.2	780.2	0.87	1.06	26.2

PHASING SUMMARY



Site: I-05 2015 FU MINT PM


Intersection of Moorebank Avenue and Chatham Avenue

2015 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Phase Change Time (sec)	0	73	85
Green Time (sec)	67	6	9
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	73	12	15
Phase Split	73 %	12 %	15 %



2. 2015 Future traffic without Moorebank IMT development (Do-nothing scenario)

I-01 Intersection of Moorebank Avenue and Bapaume Road

MOVEMENT SUMMARY



Site: I-01 2015 DN BASE AM

Intersection of Moorebank Avenue and Bapaume Road
2015 Do-nothing AM PEAK
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
1	L2	19	0.0	0.010	5.5	LOS A	0.0	0.0	0.00	0.58	45.1
2	T1	1082	5.3	0.574	0.0	LOS A	0.0	0.0	0.00	0.00	59.8
Approach		1101	5.2	0.574	0.1	NA	0.0	0.0	0.00	0.01	59.5
North: Moorebank Avenue (S)											
8	T1	839	5.4	0.344	3.9	LOS A	4.0	29.1	0.23	0.08	51.9
9	R2	81	1.3	0.344	22.7	LOS B	4.0	29.1	1.00	0.33	38.3
Approach		920	5.0	0.344	5.6	NA	4.0	29.1	0.30	0.10	49.9
West: Bapaume Road (W)											
10	L2	3	33.3	0.020	27.0	LOS B	0.1	0.6	0.85	0.94	33.0
12	R2	1	0.0	0.066	206.7	LOS F	0.2	1.2	0.98	0.99	5.6
Approach		4	25.0	0.066	71.9	LOS F	0.2	1.2	0.88	0.95	18.3
All Vehicles		2025	5.1	0.574	2.8	NA	4.0	29.1	0.14	0.05	54.4

MOVEMENT SUMMARY



Site: I-01 2015 DN BASE PM

Intersection of Moorebank Avenue and Bapaume Road
2015 Do-nothing PM PEAK
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.001	5.5	LOS A	0.0	0.0	0.00	0.58	45.1
2	T1	540	4.5	0.285	0.0	LOS A	0.0	0.0	0.00	0.00	59.9
Approach		541	4.5	0.285	0.0	NA	0.0	0.0	0.00	0.00	59.9
North: Moorebank Avenue (S)											
8	T1	1398	2.8	0.378	2.8	LOS A	5.8	41.7	0.35	0.01	54.4
9	R2	19	11.1	0.378	11.4	LOS A	5.8	41.7	0.72	0.02	47.9
Approach		1417	2.9	0.378	2.9	NA	5.8	41.7	0.35	0.01	54.3
West: Bapaume Road (W)											
10	L2	89	3.5	0.140	9.4	LOS A	0.5	3.9	0.54	0.76	45.9
12	R2	13	0.0	0.448	176.2	LOS F	1.3	9.0	0.98	1.02	6.4
Approach		102	3.1	0.448	30.1	LOS C	1.3	9.0	0.60	0.79	31.2
All Vehicles		2060	3.3	0.448	3.5	NA	5.8	41.7	0.27	0.05	53.2

I-02 Intersection of Moorebank Avenue and Anzac Road

MOVEMENT SUMMARY



Site: I-02 2015 DN BASE AM

Intersection of Moorebank Avenue and Anzac Road

2015 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
2	T1	912	3.5	0.684	9.5	LOS A	26.0	187.5	0.63	0.58	47.8
3	R2	346	3.3	0.535	25.3	LOS B	13.1	94.5	0.84	0.83	41.5
Approach		1258	3.4	0.684	13.8	LOS A	26.0	187.5	0.69	0.65	45.1
East: Anzac Road (E)											
4	L2	219	3.4	0.265	24.0	LOS B	6.7	48.6	0.66	0.75	42.1
6	R2	193	13.7	0.733	54.0	LOS D	9.9	77.3	1.00	0.87	21.0
Approach		412	8.2	0.733	38.1	LOS C	9.9	77.3	0.82	0.81	31.2
North: Moorebank Avenue (N)											
7	L2	274	10.0	0.179	6.1	LOS A	0.9	7.2	0.15	0.59	49.8
8	T1	569	3.3	0.527	22.4	LOS B	15.9	114.3	0.76	0.65	37.4
Approach		843	5.5	0.527	17.1	LOS B	15.9	114.3	0.56	0.63	40.7
All Vehicles		2513	4.9	0.733	18.9	LOS B	26.0	187.5	0.67	0.67	40.4

PHASING SUMMARY



Site: I-02 2015 DN BASE AM


Intersection of Moorebank Avenue and Anzac Road

2015 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	50	78
Green Time (sec)	44	22	19
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	50	28	25
Phase Split	49 %	27 %	24 %



MOVEMENT SUMMARY



Site: I-02 2015 DN BASE PM

Intersection of Moorebank Avenue and Anzac Road

2015 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles veh	Distance m			
		veh/h	%								
South: Moorebank Avenue (S)											
2	T1	282	3.7	0.236	9.5	LOS A	6.5	46.9	0.47	0.40	47.8
3	R2	171	1.2	0.788	58.5	LOS E	9.7	68.5	1.00	1.00	30.2
Approach		453	2.8	0.788	27.9	LOS B	9.7	68.5	0.67	0.63	37.0
East: Anzac Road (E)											
4	L2	419	2.3	0.615	35.8	LOS C	18.3	130.5	0.87	0.84	37.1
6	R2	279	5.7	0.661	47.2	LOS D	13.8	101.0	0.96	0.84	22.5
Approach		698	3.6	0.661	40.3	LOS C	18.3	130.5	0.91	0.84	31.2
North: Moorebank Avenue (N)											
7	L2	291	4.0	0.181	6.0	LOS A	1.0	7.3	0.14	0.59	50.2
8	T1	1117	2.5	0.847	25.1	LOS B	41.4	295.6	0.85	0.80	35.7
Approach		1407	2.8	0.847	21.2	LOS B	41.4	295.6	0.70	0.76	38.0
All Vehicles		2558	3.0	0.847	27.6	LOS B	41.4	295.6	0.75	0.76	35.3

PHASING SUMMARY



Site: I-02 2015 DN BASE PM


Intersection of Moorebank Avenue and Anzac Road

2015 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	63	75
Green Time (sec)	57	6	29
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	63	12	35
Phase Split	57 %	11 %	32 %



I-03 Intersection of Moorebank Avenue and Defence Support Access

MOVEMENT SUMMARY



Site: I-03 2015 DN BASE AM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2015 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	16	0.0	0.010	6.0	LOS A	0.0	0.3	0.14	0.59	46.8
2	T1	1242	3.1	0.838	7.8	LOS A	35.4	254.5	0.69	0.66	52.5
Approach		1258	3.0	0.838	7.8	LOS A	35.4	254.5	0.69	0.66	52.4
North: Moorebank Avenue (N)											
8	T1	735	3.7	0.487	6.0	LOS A	11.9	86.2	0.45	0.41	54.0
9	R2	16	0.0	0.487	12.5	LOS A	11.9	86.2	0.51	0.46	31.1
Approach		751	3.6	0.487	6.1	LOS A	11.9	86.2	0.45	0.41	53.4
West: Military Access 1 (W)											
10	L2	2	0.0	0.023	48.3	LOS D	0.1	0.9	0.94	0.63	25.5
12	R2	1	0.0	0.023	48.2	LOS D	0.1	0.9	0.94	0.63	22.8
Approach		3	0.0	0.023	48.3	LOS D	0.1	0.9	0.94	0.63	24.6
All Vehicles		2012	3.2	0.838	7.3	LOS A	35.4	254.5	0.60	0.57	52.7

PHASING SUMMARY



Site: I-03 2015 DN BASE AM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2015 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	76
Green Time (sec)	70	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	76	14
Phase Split	84 %	16 %



MOVEMENT SUMMARY



Site: I-03 2015 DN BASE PM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2015 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles veh	Distance m			
		veh/h	%								
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.001	6.0	LOS A	0.0	0.0	0.14	0.58	46.8
2	T1	443	2.4	0.297	3.1	LOS A	5.5	39.4	0.31	0.28	56.8
Approach		444	2.4	0.297	3.1	LOS A	5.5	39.4	0.31	0.28	56.8
North: Moorebank Avenue (N)											
8	T1	1513	2.5	0.956	30.4	LOS C	55.5	397.0	0.56	0.73	38.5
9	R2	1	0.0	0.956	43.4	LOS D	55.5	397.0	0.64	0.86	21.7
Approach		1514	2.5	0.956	30.4	LOS C	55.5	397.0	0.56	0.73	38.5
West: Military Access 1 (W)											
10	L2	9	0.0	0.100	49.3	LOS D	0.6	4.1	0.96	0.68	25.2
12	R2	4	0.0	0.100	49.2	LOS D	0.6	4.1	0.96	0.68	22.6
Approach		14	0.0	0.100	49.2	LOS D	0.6	4.1	0.96	0.68	24.4
All Vehicles		1972	2.5	0.956	24.4	LOS B	55.5	397.0	0.51	0.62	41.4

PHASING SUMMARY



Site: I-03 2015 DN BASE PM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2015 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	76
Green Time (sec)	70	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	76	14
Phase Split	84 %	16 %



I-04 Intersection of Moorebank Avenue and DNSDC Access

MOVEMENT SUMMARY



Site: I-04 2015 DN BASE AM

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2015 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo	Demand	Flows	Deg.	Satn	Average	Level of	95% Back of Queue	Prop.	Effective	Average
	v	Total	HV			Delay	Service	Vehicles	Queued	Stop Rate	Speed
		veh/h	%		v/c	sec		veh	m	per veh	km/h
South: Moorebank Avenue (S)											
2	T1	1288	2.6	0.696		4.9	LOS A	19.3	138.4	0.50	55.0
3	R2	22	0.0	0.696		11.1	LOS A	19.3	138.4	0.57	53.5
Approach		1311	2.6	0.696		5.0	LOS A	19.3	138.4	0.50	54.9
East: DNSDC Access (W)											
4	L2	5	20.0	0.043		44.8	LOS D	0.2	1.7	0.95	33.8
6	R2	7	14.3	0.042		42.0	LOS C	0.3	2.1	0.93	33.0
Approach		13	16.7	0.043		43.2	LOS D	0.3	2.1	0.94	33.4
North: Moorebank Avenue (N)											
7	L2	94	6.7	0.062		6.1	LOS A	0.3	2.3	0.17	52.1
8	T1	603	3.5	0.422		3.9	LOS A	8.5	61.3	0.39	56.0
Approach		697	3.9	0.422		4.2	LOS A	8.5	61.3	0.36	55.5
West: Carpark Access (W)											
10	L2	1	0.0	0.006		39.4	LOS C	0.0	0.3	0.92	24.3
12	R2	1	0.0	0.007		41.7	LOS C	0.0	0.3	0.94	26.0
Approach		2	0.0	0.007		40.5	LOS C	0.0	0.3	0.93	25.2
All Vehicles		2022	3.1	0.696		5.0	LOS A	19.3	138.4	0.46	54.8

PHASING SUMMARY



Site: I-04 2015 DN BASE AM


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2015 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	66
Green Time (sec)	60	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	66	14
Phase Split	83 %	18 %



MOVEMENT SUMMARY



Site: I-04 2015 DN BASE PM

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2015 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
2	T1	411	2.1	0.201	2.9	LOS A	4.1	28.9	0.26	0.22	57.0
3	R2	1	0.0	0.201	8.8	LOS A	4.1	28.9	0.28	0.24	55.4
Approach		412	2.0	0.201	2.9	LOS A	4.1	28.9	0.26	0.22	56.9
East: DNSDC Access (W)											
4	L2	4	0.0	0.050	62.6	LOS E	0.2	1.6	0.98	0.64	29.2
6	R2	22	9.5	0.176	59.9	LOS E	1.2	8.9	0.97	0.71	28.1
Approach		26	8.0	0.176	60.3	LOS E	1.2	8.9	0.97	0.70	28.3
North: Moorebank Avenue (N)											
7	L2	6	16.7	0.004	6.1	LOS A	0.0	0.2	0.11	0.59	51.9
8	T1	1484	2.2	0.947	27.6	LOS B	83.4	595.0	0.88	0.95	39.9
Approach		1491	2.3	0.947	27.5	LOS B	83.4	595.0	0.87	0.95	39.9
West: Carpark Access (W)											
10	L2	6	0.0	0.047	56.7	LOS E	0.3	2.3	0.95	0.65	19.4
12	R2	3	0.0	0.036	60.5	LOS E	0.2	1.2	0.98	0.62	21.0
Approach		9	0.0	0.047	57.9	LOS E	0.3	2.3	0.96	0.64	20.0
All Vehicles		1938	2.3	0.947	22.9	LOS B	83.4	595.0	0.74	0.79	42.3

PHASING SUMMARY



Site: I-04 2015 DN BASE PM


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2015 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	96
Green Time (sec)	90	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	96	14
Phase Split	87 %	13 %



I-05 Intersection of Moorebank Avenue and Chatham Avenue

MOVEMENT SUMMARY



Site: I-05 2015 DN BASE AM

Intersection of Moorebank Avenue and Chatham Avenue

2015 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
		Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	43	0.0	0.028	7.1	LOS A	0.4	2.6	0.18	0.61	51.7
2	T1	1295	2.5	0.983	55.1	LOS D	93.9	671.5	0.98	1.19	31.4
Approach		1338	2.4	0.983	53.6	LOS D	93.9	671.5	0.95	1.17	31.8
North: Moorebank Avenue (N)											
8	T1	446	4.7	0.288	2.5	LOS A	5.6	40.5	0.26	0.23	57.6
9	R2	133	0.8	0.725	59.2	LOS E	7.4	52.4	1.00	0.96	28.2
Approach		579	3.8	0.725	15.5	LOS B	7.4	52.4	0.43	0.40	47.2
West: Chatham Avenue (W)											
10	L2	17	6.3	0.170	56.3	LOS D	1.5	11.4	0.95	0.72	29.1
12	R2	12	27.3	0.170	56.5	LOS D	1.5	11.4	0.95	0.72	28.7
Approach		28	14.8	0.170	56.3	LOS D	1.5	11.4	0.95	0.72	29.0
All Vehicles		1945	3.0	0.983	42.3	LOS C	93.9	671.5	0.80	0.93	35.1

PHASING SUMMARY



Site: I-05 2015 DN BASE AM


Intersection of Moorebank Avenue and Chatham Avenue

2015 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	84	96
Green Time (sec)	78	6	8
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	84	12	14
Phase Split	76 %	11 %	13 %



MOVEMENT SUMMARY



Site: I-05 2015 DN BASE PM

Intersection of Moorebank Avenue and Chatham Avenue

2015 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
1	L2	9	0.0	0.006	7.2	LOS A	0.1	0.6	0.19	0.60	51.6
2	T1	367	2.0	0.290	7.1	LOS A	7.2	51.1	0.44	0.38	53.7
Approach		377	2.0	0.290	7.1	LOS A	7.2	51.1	0.43	0.39	53.6
North: Moorebank Avenue (N)											
8	T1	1460	2.2	0.991	54.0	LOS D	101.1	720.6	0.96	1.22	31.7
9	R2	26	0.0	0.037	10.0	LOS A	0.4	2.6	0.36	0.66	48.9
Approach		1486	2.1	0.991	53.3	LOS D	101.1	720.6	0.95	1.21	31.9
West: Chatham Avenue (W)											
10	L2	40	2.6	0.180	45.6	LOS D	2.1	15.2	0.90	0.74	32.2
12	R2	9	0.0	0.180	45.5	LOS D	2.1	15.2	0.90	0.74	32.2
Approach		49	2.1	0.180	45.6	LOS D	2.1	15.2	0.90	0.74	32.2
All Vehicles		1913	2.1	0.991	44.0	LOS D	101.1	720.6	0.84	1.03	34.7

PHASING SUMMARY



Site: I-05 2015 DN BASE PM


Intersection of Moorebank Avenue and Chatham Avenue

2015 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	73	85
Green Time (sec)	67	6	9
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	73	12	15
Phase Split	73 %	12 %	15 %



Appendix E

2016 SIDRA results with and
without Moorebank IMT

1. 2016 Future traffic with Moorebank IMT development (Phase A)

I-01 Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

MOVEMENT SUMMARY

 **Site: I-01 2016 FU MINT AM**

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2016 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	28	0.0	0.607	24.7	LOS B	15.3	117.2	0.66	0.60	38.7
2	T1	1001	12.1	0.607	17.2	LOS B	15.3	117.2	0.65	0.59	38.9
3	R2	349	3.3	0.640	18.5	LOS B	7.6	54.4	0.73	0.81	39.7
Approach		1379	9.6	0.640	17.7	LOS B	15.3	117.2	0.67	0.65	39.1
East: Anzac Road (E)											
4	L2	200	3.7	0.328	33.2	LOS C	7.3	53.0	0.77	0.79	31.4
5	T1	7	0.0	0.328	26.2	LOS B	7.3	53.0	0.77	0.79	31.4
6	R2	191	13.8	0.641	49.9	LOS D	8.9	69.9	0.97	0.83	25.4
Approach		398	8.5	0.641	41.1	LOS C	8.9	69.9	0.87	0.81	28.2
North: Moorebank Avenue (N)											
7	L2	284	10.0	0.164	7.6	LOS A	0.0	0.0	0.00	0.57	48.5
8	T1	658	16.0	0.396	15.0	LOS B	7.9	63.1	0.53	0.46	39.1
9	R2	128	18.0	0.348	18.6	LOS B	2.4	19.6	0.71	0.76	36.4
Approach		1071	14.7	0.396	13.4	LOS A	7.9	63.1	0.41	0.52	40.9
West: Bapaume Road (W)											
10	L2	25	91.7	0.061	11.7	LOS A	0.3	4.1	0.44	0.54	36.8
11	T1	1	0.0	0.008	38.1	LOS C	0.1	0.6	0.86	0.59	20.3
12	R2	1	0.0	0.008	45.2	LOS D	0.1	0.6	0.86	0.59	20.3
Approach		27	84.6	0.061	14.0	LOS A	0.3	4.1	0.47	0.55	34.6
All Vehicles		2875	12.0	0.641	19.3	LOS B	15.3	117.2	0.60	0.62	37.5

PHASING SUMMARY

 **Site: I-01 2016 FU MINT AM**


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2016 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	53	81
Green Time (sec)	47	22	13
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	53	28	19
Phase Split	53 %	28 %	19 %



MOVEMENT SUMMARY

 **Site: I-01 2016 FU MINT PM**

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2016 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles veh	Distance m			
		veh/h	%								
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.214	11.2	LOS A	2.0	16.9	0.19	0.17	53.4
2	T1	469	21.1	0.214	3.7	LOS A	2.0	16.9	0.19	0.17	53.5
3	R2	188	1.1	0.536	37.6	LOS C	8.3	58.9	0.96	0.87	29.4
Approach		659	15.3	0.536	13.4	LOS A	8.3	58.9	0.41	0.37	43.4
East: Anzac Road (E)											
4	L2	424	2.2	0.570	32.6	LOS C	16.0	113.9	0.82	0.84	31.6
5	T1	1	0.0	0.570	25.6	LOS B	16.0	113.9	0.82	0.84	31.6
6	R2	287	5.5	0.909	67.1	LOS E	17.2	126.3	1.00	1.04	21.1
Approach		713	3.5	0.909	46.5	LOS D	17.2	126.3	0.90	0.92	26.3
North: Moorebank Avenue (N)											
7	L2	286	4.0	0.159	7.6	LOS A	0.0	0.0	0.00	0.59	48.5
8	T1	1191	9.7	0.757	18.5	LOS B	20.3	153.6	0.71	0.64	36.0
9	R2	41	59.0	0.145	26.0	LOS B	1.2	13.0	0.63	0.68	31.6
Approach		1518	10.0	0.757	16.7	LOS B	20.3	153.6	0.57	0.63	37.7
West: Bapaume Road (W)											
10	L2	137	18.5	0.199	10.9	LOS A	1.9	15.2	0.37	0.63	37.5
11	T1	9	0.0	0.112	34.4	LOS C	1.2	8.2	0.83	0.70	21.2
12	R2	20	0.0	0.112	41.5	LOS C	1.2	8.2	0.83	0.70	21.2
Approach		166	15.2	0.199	15.9	LOS B	1.9	15.2	0.45	0.64	33.1
All Vehicles		3056	9.9	0.909	22.9	LOS B	20.3	153.6	0.61	0.64	34.8

PHASING SUMMARY

 **Site: I-01 2016 FU MINT PM**


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2016 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	53	70
Green Time (sec)	47	11	24
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	53	17	30
Phase Split	53 %	17 %	30 %



I-02 Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

MOVEMENT SUMMARY



Site: I-02 2016 FU MINT AM

Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2016 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate	Average Speed		
		veh/h	%	v/c	sec	veh	m	per veh	km/h		
South: Moorebank Avenue (S)											
1	L2	6	0.0	0.562	9.6	LOS A	7.9	59.6	0.26	0.24	46.1
2	T1	1361	8.9	0.562	4.0	LOS A	7.9	59.6	0.26	0.24	53.3
3	R2	22	0.0	0.198	56.7	LOS E	1.1	7.6	0.98	0.70	12.3
Approach		1389	8.7	0.562	4.9	LOS A	7.9	59.6	0.27	0.24	51.5
East: DNSDC Access (E)											
4	L2	5	20.0	0.096	52.8	LOS D	0.6	4.8	0.95	0.69	15.7
6	R2	7	14.3	0.096	52.8	LOS D	0.6	4.8	0.95	0.69	18.7
Approach		13	16.7	0.096	52.8	LOS D	0.6	4.8	0.95	0.69	17.5
North: Moorebank Avenue (N)											
7	L2	95	6.7	0.354	13.6	LOS A	8.8	67.9	0.48	0.49	29.6
8	T1	739	13.0	0.354	8.0	LOS A	9.0	69.7	0.48	0.45	47.3
9	R2	26	44.0	0.310	58.9	LOS E	1.3	12.9	0.99	0.72	17.0
Approach		860	13.2	0.354	10.2	LOS A	9.0	69.7	0.49	0.46	43.1
West: Warehouse Access 1 (W)											
10	L2	13	91.7	0.071	44.1	LOS D	0.6	7.0	0.87	0.69	19.6
12	R2	1	0.0	0.071	43.3	LOS D	0.6	7.0	0.87	0.69	18.2
Approach		14	84.6	0.071	44.1	LOS D	0.6	7.0	0.87	0.69	19.5
All Vehicles		2276	10.9	0.562	7.4	LOS A	9.0	69.7	0.36	0.33	47.3

PHASING SUMMARY



Site: I-02 2016 FU MINT AM


Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2016 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



MOVEMENT SUMMARY



Site: I-02 2016 FU MINT PM

Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2016 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.260	8.6	LOS A	2.3	18.1	0.17	0.15	48.0
2	T1	612	14.5	0.260	3.0	LOS A	2.3	18.1	0.17	0.15	54.8
3	R2	1	0.0	0.006	13.9	LOS A	0.0	0.1	0.40	0.62	21.9
Approach		614	14.4	0.260	3.0	LOS A	2.3	18.1	0.17	0.15	54.7
East: DNSDC Access (E)											
4	L2	4	0.0	0.224	55.9	LOS D	1.3	9.7	0.98	0.71	15.6
6	R2	22	9.5	0.224	55.9	LOS D	1.3	9.7	0.98	0.71	18.1
Approach		26	8.0	0.224	55.9	LOS D	1.3	9.7	0.98	0.71	17.7
North: Moorebank Avenue (N)											
7	L2	6	16.7	0.564	10.3	LOS A	15.5	114.8	0.43	0.40	32.4
8	T1	1618	7.0	0.564	4.5	LOS A	15.5	114.8	0.42	0.39	52.5
9	R2	13	91.7	0.187	59.6	LOS E	0.6	8.1	0.98	0.69	16.5
Approach		1637	7.7	0.564	5.0	LOS A	15.5	114.8	0.43	0.39	51.7
West: Warehouse Access 1 (W)											
10	L2	26	44.0	0.167	47.3	LOS D	1.5	13.3	0.92	0.72	19.4
12	R2	6	0.0	0.167	46.9	LOS D	1.5	13.3	0.92	0.72	17.3
Approach		33	35.5	0.167	47.2	LOS D	1.5	13.3	0.92	0.72	19.0
All Vehicles		2309	9.9	0.564	5.6	LOS A	15.5	114.8	0.37	0.34	50.7

PHASING SUMMARY



Site: I-02 2016 FU MINT PM


Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2016 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



I-03 Intersection of Moorebank Avenue and Warehouse Access 2

MOVEMENT SUMMARY



Site: I-03 2016 FU MINT AM

Intersection of Moorebank Avenue and Warehouse Access 2

2016 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay v/c	Level of Service sec	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate per veh	Average Speed km/h		
South: Moorebank Avenue (S)											
1	L2	6	0.0	0.600	18.4	LOS B	18.1	135.6	0.65	0.59	45.0
2	T1	1377	8.0	0.600	10.9	LOS A	18.2	135.7	0.65	0.59	45.0
Approach		1383	7.9	0.600	11.0	LOS A	18.2	135.7	0.65	0.59	45.0
North: Moorebank Avenue (N)											
8	T1	718	11.9	0.262	0.8	LOS A	1.0	8.0	0.07	0.06	56.8
9	R2	26	44.0	0.120	15.6	LOS B	0.4	3.8	0.59	0.67	31.2
Approach		744	13.0	0.262	1.4	LOS A	1.0	8.0	0.09	0.08	55.4
West: Warehouse Access 2 (W)											
10	L2	13	91.7	0.060	39.5	LOS C	0.5	6.0	0.84	0.66	13.8
12	R2	1	0.0	0.060	39.6	LOS C	0.5	6.0	0.84	0.66	13.8
Approach		14	84.6	0.060	39.5	LOS C	0.5	6.0	0.84	0.66	13.8
All Vehicles		2141	10.2	0.600	7.8	LOS A	18.2	135.7	0.46	0.42	46.6

PHASING SUMMARY



Site: I-03 2016 FU MINT AM


Intersection of Moorebank Avenue and Warehouse Access 2

2016 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



MOVEMENT SUMMARY



Site: I-03 2016 FU MINT PM

Intersection of Moorebank Avenue and Warehouse Access 2

2016 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	15.6	LOS B	5.7	44.7	0.48	0.42	48.1
2	T1	585	13.1	8.2	LOS A	5.7	44.7	0.48	0.42	48.1
Approach		586	13.1	8.2	LOS A	5.7	44.7	0.48	0.42	48.1
North: Moorebank Avenue (N)										
8	T1	1616	6.3	1.2	LOS A	3.8	28.2	0.12	0.11	55.5
9	R2	13	91.7	11.7	LOS A	0.2	1.9	0.40	0.55	35.3
Approach		1628	7.0	1.3	LOS A	3.8	28.2	0.12	0.11	55.2
West: Warehouse Access 2 (W)										
10	L2	26	44.0	42.8	LOS D	1.3	11.5	0.89	0.72	13.0
12	R2	6	0.0	42.9	LOS D	1.3	11.5	0.89	0.72	13.0
Approach		33	35.5	42.8	LOS D	1.3	11.5	0.89	0.72	13.0
All Vehicles		2247	9.0	3.7	LOS A	5.7	44.7	0.23	0.20	50.9

PHASING SUMMARY



Site: I-03 2016 FU MINT PM


Intersection of Moorebank Avenue and Warehouse Access 2

2016 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



I-04 Intersection of Moorebank Avenue and Warehouse Access 3

MOVEMENT SUMMARY



Site: I-04 2016 FU MINT AM

Intersection of Moorebank Avenue and Warehouse Access 3

2016 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	v/c	sec	veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	13	0.0	0.590	18.3	LOS B	17.8	131.6	0.64	0.59	44.0
2	T1	1361	6.4	0.590	10.8	LOS A	17.9	131.9	0.64	0.59	44.0
Approach		1374	6.4	0.590	10.9	LOS A	17.9	131.9	0.64	0.59	44.0
North: Moorebank Avenue (N)											
8	T1	667	9.5	0.240	3.5	LOS A	4.3	32.5	0.32	0.28	53.8
9	R2	51	43.8	0.227	15.8	LOS B	0.8	7.8	0.61	0.69	41.9
Approach		718	11.9	0.240	4.3	LOS A	4.3	32.5	0.34	0.31	52.8
West: Warehouse Access 3 (W)											
10	L2	23	95.5	0.104	39.1	LOS C	0.9	11.1	0.84	0.68	13.9
12	R2	1	0.0	0.104	39.2	LOS C	0.9	11.1	0.84	0.68	13.9
Approach		24	91.3	0.104	39.1	LOS C	0.9	11.1	0.84	0.68	13.9
All Vehicles		2116	9.2	0.590	9.0	LOS A	17.9	131.9	0.54	0.49	46.5

PHASING SUMMARY



Site: I-04 2016 FU MINT AM


Intersection of Moorebank Avenue and Warehouse Access 3

2016 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



MOVEMENT SUMMARY



Site: I-04 2016 FU MINT PM

Intersection of Moorebank Avenue and Warehouse Access 3

2016 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.244	16.4	LOS B	5.4	41.4	0.50	0.43	46.3
2	T1	535	10.2	0.244	9.0	LOS A	5.4	41.5	0.50	0.43	46.3
Approach		536	10.2	0.244	9.0	LOS A	5.4	41.5	0.50	0.43	46.3
North: Moorebank Avenue (N)											
8	T1	1600	5.0	0.562	5.0	LOS A	14.7	107.6	0.46	0.42	51.5
9	R2	23	95.5	0.061	11.7	LOS A	0.3	3.5	0.40	0.56	45.3
Approach		1623	6.3	0.562	5.0	LOS A	14.7	107.6	0.46	0.42	51.4
West: Warehouse Access 3 (W)											
10	L2	51	43.8	0.257	42.9	LOS D	2.5	22.6	0.90	0.75	13.0
12	R2	13	0.0	0.257	43.0	LOS D	2.5	22.6	0.90	0.75	13.0
Approach		63	35.0	0.257	42.9	LOS D	2.5	22.6	0.90	0.75	13.0
All Vehicles		2222	8.1	0.562	7.1	LOS A	14.7	107.6	0.48	0.43	48.9

PHASING SUMMARY



Site: I-04 2016 FU MINT PM


Intersection of Moorebank Avenue and Warehouse Access 3

2016 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	60	76
Green Time (sec)	54	10	8
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	60	16	14
Phase Split	67 %	18 %	16 %



I-05 Intersection of Moorebank Avenue and Main Access

MOVEMENT SUMMARY



Site: I-05 2016 FU MINT AM

Intersection of Moorebank Avenue and Main Access

2016 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	24	0.0	0.591	19.4	LOS B	18.3	131.2	0.67	0.62	42.9
2	T1	1329	3.2	0.591	11.9	LOS A	18.3	131.6	0.67	0.61	43.0
Approach		1354	3.2	0.591	12.0	LOS A	18.3	131.6	0.67	0.61	43.0
North: Moorebank Avenue (N)											
8	T1	566	3.3	0.225	4.0	LOS A	4.3	31.2	0.34	0.29	53.1
9	R2	101	43.8	0.472	17.8	LOS B	2.1	19.8	0.74	0.75	40.4
Approach		667	9.5	0.472	6.1	LOS A	4.3	31.2	0.40	0.36	50.8
West: Main Access (W)											
10	L2	45	97.7	0.089	36.6	LOS C	0.8	10.6	0.81	0.67	14.6
12	R2	1	0.0	0.089	37.2	LOS C	0.8	10.1	0.81	0.67	14.4
Approach		46	95.5	0.089	36.6	LOS C	0.8	10.6	0.81	0.67	14.6
All Vehicles		2067	7.3	0.591	10.7	LOS A	18.3	131.6	0.58	0.53	44.7

PHASING SUMMARY



Site: I-05 2016 FU MINT AM


Intersection of Moorebank Avenue and Main Access

2016 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	60	78
Green Time (sec)	54	12	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	60	18	12
Phase Split	67 %	20 %	13 %



MOVEMENT SUMMARY



Site: I-05 2016 FU MINT PM

Intersection of Moorebank Avenue and Main Access

2016 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.232	21.6	LOS B	5.5	38.9	0.61	0.52	41.4
2	T1	434	2.4	0.232	14.1	LOS A	5.5	39.0	0.61	0.52	41.4
Approach		435	2.4	0.232	14.2	LOS A	5.5	39.0	0.61	0.52	41.4
North: Moorebank Avenue (N)											
8	T1	1568	2.3	0.624	5.8	LOS A	18.3	130.5	0.49	0.45	50.4
9	R2	45	97.7	0.100	12.0	LOS A	0.6	7.5	0.43	0.58	45.0
Approach		1614	5.0	0.624	6.0	LOS A	18.3	130.5	0.49	0.46	50.3
West: Main Access (W)											
10	L2	101	43.8	0.176	30.9	LOS C	2.7	26.0	0.75	0.72	16.5
12	R2	24	0.0	0.176	46.1	LOS D	1.5	11.7	0.92	0.73	12.3
Approach		125	35.3	0.176	33.9	LOS C	2.7	26.0	0.78	0.72	15.5
All Vehicles		2174	6.2	0.624	9.2	LOS A	18.3	130.5	0.53	0.48	46.4

PHASING SUMMARY



Site: I-05 2016 FU MINT PM


Intersection of Moorebank Avenue and Main Access

2016 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	50	68
Green Time (sec)	44	12	16
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	50	18	22
Phase Split	56 %	20 %	24 %



2. 2016 Future traffic without Moorebank IMT development (Do-nothing scenario)

I-01 Intersection of Moorebank Avenue and Bapaume Road

MOVEMENT SUMMARY



Site: I-01 2016 DN BASE AM

Intersection of Moorebank Avenue and Bapaume Road
2016 Do-nothing AM PEAK
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	19	0.0	0.010	5.5	LOS A	0.0	0.0	0.00	0.58	45.1
2	T1	1102	5.3	0.584	0.0	LOS A	0.0	0.0	0.00	0.00	59.8
Approach		1121	5.2	0.584	0.1	NA	0.0	0.0	0.00	0.01	59.5
North: Moorebank Avenue (S)											
8	T1	854	5.4	0.355	4.0	LOS A	4.2	30.1	0.22	0.08	51.8
9	R2	82	1.3	0.355	23.8	LOS B	4.2	30.1	1.00	0.35	37.6
Approach		936	5.1	0.355	5.7	NA	4.2	30.1	0.29	0.10	49.7
West: Bapaume Road (W)											
10	L2	3	33.3	0.021	28.4	LOS B	0.1	0.6	0.86	0.94	32.4
12	R2	1	0.0	0.074	229.6	LOS F	0.2	1.3	0.99	0.99	5.1
Approach		4	25.0	0.074	78.7	LOS F	0.2	1.3	0.89	0.95	17.2
All Vehicles		2061	5.2	0.584	2.8	NA	4.2	30.1	0.13	0.05	54.3

MOVEMENT SUMMARY



Site: I-01 2016 DN BASE PM

Intersection of Moorebank Avenue and Bapaume Road
2016 Do-nothing PM PEAK
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.001	5.5	LOS A	0.0	0.0	0.00	0.58	45.1
2	T1	554	4.6	0.292	0.0	LOS A	0.0	0.0	0.00	0.00	59.9
Approach		555	4.6	0.292	0.0	NA	0.0	0.0	0.00	0.00	59.9
North: Moorebank Avenue (S)											
8	T1	1407	2.8	0.381	2.9	LOS A	6.0	43.0	0.36	0.01	54.2
9	R2	19	11.1	0.381	11.6	LOS A	6.0	43.0	0.74	0.02	47.7
Approach		1426	2.9	0.381	3.0	NA	6.0	43.0	0.36	0.01	54.1
West: Bapaume Road (W)											
10	L2	91	3.5	0.145	9.6	LOS A	0.6	4.0	0.55	0.77	45.8
12	R2	13	0.0	0.471	189.1	LOS F	1.4	9.5	0.98	1.03	6.0
Approach		103	3.1	0.471	31.6	LOS C	1.4	9.5	0.60	0.80	30.5
All Vehicles		2084	3.3	0.471	3.6	NA	6.0	43.0	0.28	0.05	52.9

I-02 Intersection of Moorebank Avenue and Anzac Road

MOVEMENT SUMMARY



Site: I-02 2016 DN BASE AM

Intersection of Moorebank Avenue and Anzac Road

2016 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
2	T1	928	3.5	0.697	9.6	LOS A	27.0	194.4	0.64	0.59	47.6
3	R2	349	3.3	0.543	25.5	LOS B	13.4	96.5	0.85	0.83	41.4
Approach		1278	3.5	0.697	14.0	LOS A	27.0	194.4	0.70	0.66	45.0
East: Anzac Road (E)											
4	L2	220	3.3	0.266	24.1	LOS B	6.8	48.8	0.66	0.75	42.1
6	R2	194	13.6	0.736	54.1	LOS D	10.0	77.9	1.00	0.87	21.0
Approach		414	8.1	0.736	38.1	LOS C	10.0	77.9	0.82	0.81	31.1
North: Moorebank Avenue (N)											
7	L2	284	10.0	0.186	6.1	LOS A	1.0	7.5	0.15	0.59	49.8
8	T1	576	3.3	0.532	22.4	LOS B	16.1	115.9	0.76	0.66	37.3
Approach		860	5.5	0.532	17.0	LOS B	16.1	115.9	0.56	0.63	40.7
All Vehicles		2552	4.9	0.736	18.9	LOS B	27.0	194.4	0.67	0.67	40.3

PHASING SUMMARY



Site: I-02 2016 DN BASE AM


Intersection of Moorebank Avenue and Anzac Road

2016 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	50	78
Green Time (sec)	44	22	19
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	50	28	25
Phase Split	49 %	27 %	24 %



MOVEMENT SUMMARY



Site: I-02 2016 DN BASE PM

Intersection of Moorebank Avenue and Anzac Road

2016 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
2	T1	284	3.7	0.238	9.5	LOS A	6.5	47.3	0.47	0.40	47.8
3	R2	172	1.2	0.801	59.8	LOS E	9.8	69.7	1.00	1.01	29.9
Approach		456	2.8	0.801	28.4	LOS B	9.8	69.7	0.67	0.63	36.8
East: Anzac Road (E)											
4	L2	432	2.2	0.633	36.0	LOS C	19.0	135.6	0.88	0.84	37.0
6	R2	287	5.5	0.680	47.6	LOS D	14.3	104.9	0.97	0.84	22.4
Approach		719	3.5	0.680	40.7	LOS C	19.0	135.6	0.91	0.84	31.1
North: Moorebank Avenue (N)											
7	L2	228	5.1	0.143	6.0	LOS A	0.8	5.6	0.13	0.59	50.2
8	T1	1124	2.4	0.852	25.7	LOS B	42.2	301.7	0.85	0.81	35.4
Approach		1353	2.9	0.852	22.4	LOS B	42.2	301.7	0.73	0.77	37.3
All Vehicles		2527	3.0	0.852	28.7	LOS C	42.2	301.7	0.77	0.77	34.8

PHASING SUMMARY



Site: I-02 2016 DN BASE PM


Intersection of Moorebank Avenue and Anzac Road

2016 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	63	75
Green Time (sec)	57	6	29
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	63	12	35
Phase Split	57 %	11 %	32 %



I-03 Intersection of Moorebank Avenue and Defence Support Access

MOVEMENT SUMMARY



Site: I-03 2016 DN BASE AM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2016 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	16	0.0	0.010	6.0	LOS A	0.0	0.3	0.14	0.59	46.8
2	T1	1265	3.1	0.854	9.7	LOS A	39.1	281.1	0.72	0.70	51.0
Approach		1281	3.0	0.854	9.6	LOS A	39.1	281.1	0.71	0.70	50.9
North: Moorebank Avenue (N)											
8	T1	740	3.7	0.498	6.4	LOS A	12.4	89.4	0.46	0.42	53.6
9	R2	16	0.0	0.498	13.0	LOS A	12.4	89.4	0.52	0.48	30.9
Approach		756	3.6	0.498	6.5	LOS A	12.4	89.4	0.46	0.42	53.1
West: Military Access 1 (W)											
10	L2	2	0.0	0.023	48.3	LOS D	0.1	0.9	0.94	0.63	25.5
12	R2	1	0.0	0.023	48.2	LOS D	0.1	0.9	0.94	0.63	22.8
Approach		3	0.0	0.023	48.3	LOS D	0.1	0.9	0.94	0.63	24.6
All Vehicles		2040	3.3	0.854	8.5	LOS A	39.1	281.1	0.62	0.60	51.7

PHASING SUMMARY



Site: I-03 2016 DN BASE AM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2016 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	76
Green Time (sec)	70	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	76	14
Phase Split	84 %	16 %



MOVEMENT SUMMARY



Site: I-03 2016 DN BASE PM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2016 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.001	6.0	LOS A	0.0	0.14	0.58	46.8
2	T1	446	2.4	0.299	3.1	LOS A	5.6	0.31	0.28	56.8
Approach		447	2.4	0.299	3.1	LOS A	5.6	0.31	0.28	56.8
North: Moorebank Avenue (N)										
8	T1	1634	2.3	1.041	75.6	LOS F	111.5	0.85	1.30	25.2
9	R2	1	0.0	1.041	101.2	LOS F	111.5	1.00	1.58	13.8
Approach		1635	2.3	1.041	75.7	LOS F	111.5	0.85	1.30	25.1
West: Military Access 1 (W)										
10	L2	9	0.0	0.100	49.3	LOS D	0.6	0.96	0.68	25.2
12	R2	4	0.0	0.100	49.2	LOS D	0.6	0.96	0.68	22.6
Approach		14	0.0	0.100	49.2	LOS D	0.6	0.96	0.68	24.4
All Vehicles		2096	2.3	1.041	60.0	LOS E	111.5	0.73	1.07	28.5

PHASING SUMMARY



Site: I-03 2016 DN BASE PM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2016 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	76
Green Time (sec)	70	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	76	14
Phase Split	84 %	16 %



I-04 Intersection of Moorebank Avenue and DNSDC Access

MOVEMENT SUMMARY



Site: I-04 2016 DN BASE AM

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2016 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
2	T1	1312	2.6	0.714	5.0	LOS A	19.9	142.6	0.51	0.47	54.9
3	R2	22	0.0	0.714	11.2	LOS A	19.9	142.6	0.58	0.54	53.4
Approach		1334	2.6	0.714	5.1	LOS A	19.9	142.6	0.51	0.47	54.9
East: DNSDC Access (W)											
4	L2	5	20.0	0.043	44.8	LOS D	0.2	1.7	0.95	0.65	33.8
6	R2	7	14.3	0.042	42.0	LOS C	0.3	2.1	0.93	0.66	33.0
Approach		13	16.7	0.043	43.2	LOS D	0.3	2.1	0.94	0.65	33.4
North: Moorebank Avenue (N)											
7	L2	95	6.7	0.063	6.1	LOS A	0.3	2.3	0.17	0.61	52.1
8	T1	607	3.5	0.425	3.9	LOS A	8.6	61.9	0.40	0.36	56.0
Approach		702	3.9	0.425	4.2	LOS A	8.6	61.9	0.36	0.39	55.5
West: Carpark Access (W)											
10	L2	1	0.0	0.006	39.4	LOS C	0.0	0.3	0.92	0.59	24.3
12	R2	1	0.0	0.007	41.7	LOS C	0.0	0.3	0.94	0.59	26.0
Approach		2	0.0	0.007	40.5	LOS C	0.0	0.3	0.93	0.59	25.2
All Vehicles		2051	3.1	0.714	5.1	LOS A	19.9	142.6	0.46	0.45	54.8

PHASING SUMMARY



Site: I-04 2016 DN BASE AM


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2016 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	66
Green Time (sec)	60	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	66	14
Phase Split	83 %	18 %



MOVEMENT SUMMARY



Site: I-04 2016 DN BASE PM

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2016 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
2	T1	414	2.0	0.203	2.9	LOS A	4.1	29.1	0.26	0.22	56.9
3	R2	1	0.0	0.203	8.8	LOS A	4.1	29.1	0.28	0.24	55.4
Approach		415	2.0	0.203	2.9	LOS A	4.1	29.1	0.26	0.22	56.9
East: DNSDC Access (W)											
4	L2	4	0.0	0.050	62.6	LOS E	0.2	1.6	0.98	0.64	29.2
6	R2	22	9.5	0.176	59.9	LOS E	1.2	8.9	0.97	0.71	28.1
Approach		26	8.0	0.176	60.3	LOS E	1.2	8.9	0.97	0.70	28.3
North: Moorebank Avenue (N)											
7	L2	6	16.7	0.004	6.1	LOS A	0.0	0.2	0.11	0.59	51.9
8	T1	1500	2.2	0.957	32.2	LOS C	90.4	644.4	0.91	1.01	37.8
Approach		1506	2.2	0.957	32.1	LOS C	90.4	644.4	0.90	1.01	37.8
West: Carpark Access (W)											
10	L2	6	0.0	0.047	56.7	LOS E	0.3	2.3	0.95	0.65	19.4
12	R2	3	0.0	0.036	60.5	LOS E	0.2	1.2	0.98	0.62	21.0
Approach		9	0.0	0.047	57.9	LOS E	0.3	2.3	0.96	0.64	20.0
All Vehicles		1957	2.3	0.957	26.4	LOS B	90.4	644.4	0.77	0.84	40.4

PHASING SUMMARY



Site: I-04 2016 DN BASE PM


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2016 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	96
Green Time (sec)	90	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	96	14
Phase Split	87 %	13 %



I-05 Intersection of Moorebank Avenue and Chatham Avenue

MOVEMENT SUMMARY

 **Site: I-05 2016 DN BASE AM**

Intersection of Moorebank Avenue and Chatham Avenue

2016 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Prop. Queued	Effective Stop Rate	Average Speed		
		veh/h	%	sec		veh		per veh	km/h		
South: Moorebank Avenue (S)											
1	L2	43	0.0	0.028	7.1	LOS A	0.4	2.6	0.18	0.61	51.7
2	T1	1319	2.6	1.001	68.3	LOS E	109.6	783.7	1.00	1.28	28.2
Approach		1362	2.5	1.001	66.3	LOS E	109.6	783.7	0.97	1.26	28.6
North: Moorebank Avenue (N)											
8	T1	449	4.7	0.290	2.5	LOS A	5.6	40.9	0.26	0.23	57.6
9	R2	134	0.8	0.775	62.8	LOS E	7.4	51.9	1.00	0.96	27.3
Approach		583	3.8	0.775	16.3	LOS B	7.4	51.9	0.43	0.40	46.7
West: Chatham Avenue (W)											
10	L2	17	6.3	0.170	56.3	LOS D	1.5	11.4	0.95	0.72	29.1
12	R2	12	27.3	0.170	56.5	LOS D	1.5	11.4	0.95	0.72	28.7
Approach		28	14.8	0.170	56.3	LOS D	1.5	11.4	0.95	0.72	29.0
All Vehicles		1974	3.0	1.001	51.4	LOS D	109.6	783.7	0.81	1.00	32.2

PHASING SUMMARY

 **Site: I-05 2016 DN BASE AM**


Intersection of Moorebank Avenue and Chatham Avenue

2016 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	84	96
Green Time (sec)	78	6	8
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	84	12	14
Phase Split	76 %	11 %	13 %



MOVEMENT SUMMARY



Site: I-05 2016 DN BASE PM

Intersection of Moorebank Avenue and Chatham Avenue

2016 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	9	0.0	0.006	7.2	LOS A	0.1	0.6	0.19	0.60	51.6
2	T1	369	2.0	0.292	7.1	LOS A	7.2	51.5	0.44	0.38	53.7
Approach		379	1.9	0.292	7.1	LOS A	7.2	51.5	0.43	0.39	53.6
North: Moorebank Avenue (N)											
8	T1	1476	2.1	1.002	62.2	LOS E	115.5	823.3	1.00	1.30	29.6
9	R2	26	0.0	0.037	10.0	LOS A	0.4	2.6	0.36	0.66	48.9
Approach		1502	2.1	1.002	61.3	LOS E	115.5	823.3	0.99	1.29	29.8
West: Chatham Avenue (W)											
10	L2	40	2.6	0.180	45.6	LOS D	2.1	15.2	0.90	0.74	32.2
12	R2	9	0.0	0.180	45.5	LOS D	2.1	15.2	0.90	0.74	32.2
Approach		49	2.1	0.180	45.6	LOS D	2.1	15.2	0.90	0.74	32.2
All Vehicles		1931	2.1	1.002	50.2	LOS D	115.5	823.3	0.88	1.10	32.7

PHASING SUMMARY



Site: I-05 2016 DN BASE PM


Intersection of Moorebank Avenue and Chatham Avenue

2016 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	73	85
Green Time (sec)	67	6	9
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	73	12	15
Phase Split	73 %	12 %	15 %



Appendix F

2023 SIDRA results with and
without Moorebank IMT

1. 2023 Future traffic with Moorebank IMT development (Phase B)

I-01 Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

MOVEMENT SUMMARY



Site: I-01 2023 FU MINT AM

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2023 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV %	Average Delay v/c	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		Vehicles	Distance m		per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	33	0.0	0.758	29.7	LOS C	21.9	172.3	0.81	0.74	35.3
2	T1	1147	15.6	0.758	22.1	LOS B	21.9	172.3	0.80	0.73	35.5
3	R2	427	3.2	0.734	21.2	LOS B	10.1	72.7	0.89	0.87	37.8
Approach		1607	12.0	0.758	22.0	LOS B	21.9	172.6	0.83	0.77	36.1
East: Anzac Road (E)											
4	L2	214	3.4	0.352	33.5	LOS C	8.0	57.5	0.78	0.80	31.3
5	T1	9	0.0	0.352	26.5	LOS B	8.0	57.5	0.78	0.80	31.3
6	R2	200	13.7	0.771	56.2	LOS D	10.2	80.0	1.00	0.90	23.6
Approach		423	8.2	0.771	44.0	LOS D	10.2	80.0	0.88	0.85	27.1
North: Moorebank Avenue (N)											
7	L2	351	9.9	0.202	7.6	LOS A	0.0	0.0	0.00	0.57	48.5
8	T1	763	20.8	0.505	18.4	LOS B	10.9	90.1	0.63	0.55	36.3
9	R2	137	13.1	0.314	20.7	LOS B	3.0	23.2	0.78	0.78	34.9
Approach		1251	16.9	0.505	15.6	LOS B	10.9	90.1	0.47	0.58	38.9
West: Bapaume Road (W)											
10	L2	20	89.5	0.049	14.0	LOS A	0.3	4.2	0.51	0.56	34.8
11	T1	1	0.0	0.011	42.2	LOS C	0.1	0.6	0.90	0.60	19.2
12	R2	1	0.0	0.011	49.3	LOS D	0.1	0.6	0.90	0.60	19.2
Approach		22	81.0	0.049	17.0	LOS B	0.3	4.2	0.54	0.57	32.3
All Vehicles		3303	13.8	0.771	22.4	LOS B	21.9	172.6	0.70	0.71	35.4

PHASING SUMMARY



Site: I-01 2023 FU MINT AM


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2023 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	50	75
Green Time (sec)	44	19	19
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	50	25	25
Phase Split	50 %	25 %	25 %



MOVEMENT SUMMARY



Site: I-01 2023 FU MINT PM

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2023 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 105 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo	Demand	Flows	Deg. Satn	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV	%	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.279	12.6	LOS A	3.3	28.4	0.24	0.21	51.4
2	T1	572	27.1	0.279	5.2	LOS A	3.3	28.4	0.24	0.21	51.4
3	R2	206	1.0	0.879	69.9	LOS E	13.1	92.2	1.00	1.13	20.5
Approach		779	20.1	0.879	22.3	LOS B	13.1	92.2	0.44	0.45	36.8
East: Anzac Road (E)											
4	L2	499	2.3	0.720	38.1	LOS C	21.9	156.2	0.92	0.87	29.3
5	T1	1	0.0	0.720	31.1	LOS C	21.9	156.2	0.92	0.87	29.3
6	R2	343	5.5	0.896	64.6	LOS E	20.8	152.3	1.00	1.01	21.6
Approach		843	3.6	0.896	48.9	LOS D	21.9	156.2	0.95	0.92	25.6
North: Moorebank Avenue (N)											
7	L2	309	4.1	0.171	7.6	LOS A	0.0	0.0	0.00	0.59	48.5
8	T1	1321	13.1	0.819	19.6	LOS B	25.1	195.6	0.69	0.66	35.4
9	R2	37	51.4	0.138	25.2	LOS B	1.1	11.2	0.60	0.68	32.1
Approach		1667	12.2	0.819	17.5	LOS B	25.1	195.6	0.56	0.65	37.2
West: Bapaume Road (W)											
10	L2	145	13.8	0.237	11.8	LOS A	2.2	17.6	0.41	0.66	36.7
11	T1	12	0.0	0.179	42.4	LOS C	1.6	11.5	0.90	0.73	19.0
12	R2	24	0.0	0.179	49.5	LOS D	1.6	11.5	0.90	0.73	19.0
Approach		181	11.0	0.237	18.8	LOS B	2.2	17.6	0.51	0.67	31.0
All Vehicles		3471	11.9	0.896	26.3	LOS B	25.1	195.6	0.63	0.67	32.9

PHASING SUMMARY



Site: I-01 2023 FU MINT PM


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2023 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 105 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	59	71
Green Time (sec)	53	6	28
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	59	12	34
Phase Split	56 %	11 %	32 %



I-02 Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

MOVEMENT SUMMARY



Site: I-02 2023 FU MINT AM

Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2023 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue	Prop. Queued	Effective Stop Rate	Average Speed	
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m	per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	11	0.0	0.664	10.1	LOS A	11.3	86.2	0.32	0.30	45.1
2	T1	1583	11.0	0.664	4.5	LOS A	11.3	86.2	0.32	0.29	52.5
3	R2	24	0.0	0.217	56.9	LOS E	1.2	8.4	0.98	0.71	12.3
Approach		1618	10.8	0.664	5.3	LOS A	11.3	86.2	0.33	0.30	50.9
East: DNSDC Access (E)											
4	L2	5	20.0	0.093	52.7	LOS D	0.6	4.7	0.95	0.69	15.7
6	R2	7	14.3	0.093	52.7	LOS D	0.6	4.7	0.95	0.69	18.7
Approach		13	16.7	0.093	52.7	LOS D	0.6	4.7	0.95	0.69	17.5
North: Moorebank Avenue (N)											
7	L2	111	6.7	0.406	14.0	LOS A	10.4	82.0	0.50	0.52	29.3
8	T1	824	17.2	0.406	8.4	LOS A	10.5	84.4	0.50	0.48	46.8
9	R2	41	41.0	0.476	59.7	LOS E	2.1	20.1	1.00	0.74	16.8
Approach		976	17.0	0.476	11.2	LOS A	10.5	84.4	0.52	0.49	42.0
West: Warehouse Access 1 (W)											
10	L2	18	94.1	0.097	43.5	LOS D	0.8	9.9	0.87	0.70	19.7
12	R2	1	0.0	0.097	42.7	LOS D	0.8	9.9	0.87	0.70	18.4
Approach		19	88.9	0.097	43.5	LOS D	0.8	9.9	0.87	0.70	19.7
All Vehicles		2625	13.7	0.664	8.0	LOS A	11.3	86.2	0.41	0.38	46.5

PHASING SUMMARY



Site: I-02 2023 FU MINT AM


Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2023 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



MOVEMENT SUMMARY



Site: I-02 2023 FU MINT PM

Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2023 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.312	8.7	LOS A	2.9	23.3	0.18	0.16	47.7
2	T1	713	19.4	0.312	3.1	LOS A	2.9	23.3	0.18	0.16	54.6
3	R2	1	0.0	0.008	16.4	LOS B	0.0	0.2	0.45	0.62	21.0
Approach		715	19.3	0.312	3.2	LOS A	2.9	23.3	0.18	0.16	54.5
East: DNSDC Access (E)											
4	L2	4	0.0	0.229	55.9	LOS D	1.3	10.0	0.98	0.72	15.6
6	R2	23	9.1	0.229	55.9	LOS D	1.3	10.0	0.98	0.72	18.1
Approach		27	7.7	0.229	55.9	LOS D	1.3	10.0	0.98	0.72	17.7
North: Moorebank Avenue (N)											
7	L2	6	16.7	0.645	10.9	LOS A	19.7	148.5	0.48	0.45	32.0
8	T1	1821	9.1	0.645	5.1	LOS A	19.7	148.5	0.48	0.44	51.7
9	R2	18	94.1	0.268	60.2	LOS E	0.9	11.7	0.99	0.71	16.3
Approach		1845	10.0	0.645	5.6	LOS A	19.7	148.5	0.48	0.45	50.8
West: Warehouse Access 1 (W)											
10	L2	41	41.0	0.265	48.1	LOS D	2.3	21.0	0.93	0.75	19.2
12	R2	11	0.0	0.265	47.7	LOS D	2.3	21.0	0.93	0.75	17.1
Approach		52	32.7	0.265	48.0	LOS D	2.3	21.0	0.93	0.75	18.8
All Vehicles		2639	12.9	0.645	6.3	LOS A	19.7	148.5	0.41	0.38	49.7

PHASING SUMMARY



Site: I-02 2023 FU MINT PM


Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2023 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



I-03 Intersection of Moorebank Avenue and Warehouse Access 2

MOVEMENT SUMMARY



Site: I-03 2023 FU MINT AM

Intersection of Moorebank Avenue and Warehouse Access 2

2023 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay v/c	Level of Service sec	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate per veh	Average Speed km/h		
South: Moorebank Avenue (S)											
1	L2	14	0.0	0.705	19.7	LOS B	23.6	178.6	0.73	0.67	43.7
2	T1	1596	9.6	0.705	12.2	LOS A	23.6	178.9	0.73	0.67	43.7
Approach		1609	9.5	0.705	12.3	LOS A	23.6	178.9	0.73	0.67	43.7
North: Moorebank Avenue (N)											
8	T1	775	15.6	0.290	0.9	LOS A	1.2	9.2	0.07	0.07	56.8
9	R2	55	40.4	0.278	19.3	LOS B	1.2	11.1	0.72	0.73	28.2
Approach		829	17.3	0.290	2.1	LOS A	1.2	11.1	0.12	0.11	53.5
West: Warehouse Access 2 (W)											
10	L2	23	95.5	0.104	39.1	LOS C	0.9	11.1	0.84	0.68	13.9
12	R2	1	0.0	0.104	39.2	LOS C	0.9	11.1	0.84	0.68	13.9
Approach		24	91.3	0.104	39.1	LOS C	0.9	11.1	0.84	0.68	13.9
All Vehicles		2463	12.9	0.705	9.1	LOS A	23.6	178.9	0.52	0.48	45.0

PHASING SUMMARY



Site: I-03 2023 FU MINT AM


Intersection of Moorebank Avenue and Warehouse Access 2

2023 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



MOVEMENT SUMMARY



Site: I-03 2023 FU MINT PM

Intersection of Moorebank Avenue and Warehouse Access 2

2023 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 85 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.314	LOS B	6.7	53.8	0.53	0.46	47.2
2	T1	658	17.6	0.314	LOS A	6.7	53.8	0.53	0.46	47.2
Approach		659	17.6	0.314	LOS A	6.7	53.8	0.53	0.46	47.2
North: Moorebank Avenue (N)										
8	T1	1814	8.0	0.660	LOS A	5.0	37.3	0.15	0.13	54.9
9	R2	23	95.5	0.076	LOS A	0.3	3.6	0.44	0.57	34.7
Approach		1837	9.1	0.660	LOS A	5.0	37.3	0.15	0.14	54.5
West: Warehouse Access 2 (W)										
10	L2	55	40.4	0.270	LOS C	2.6	22.8	0.90	0.75	13.4
12	R2	14	0.0	0.270	LOS C	2.6	22.8	0.90	0.75	13.4
Approach		68	32.3	0.270	LOS C	2.6	22.8	0.90	0.75	13.4
All Vehicles		2564	11.9	0.660	LOS A	6.7	53.8	0.27	0.24	49.3

PHASING SUMMARY



Site: I-03 2023 FU MINT PM


Intersection of Moorebank Avenue and Warehouse Access 2

2023 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 85 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	57	73
Green Time (sec)	51	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	57	16	12
Phase Split	67 %	19 %	14 %



I-04 Intersection of Moorebank Avenue and Warehouse Access 3

MOVEMENT SUMMARY



Site: I-04 2023 FU MINT AM

Intersection of Moorebank Avenue and Warehouse Access 3

2023 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue	Prop. Queued	Effective Stop Rate	Average Speed	
	v	Total	HV				Vehicles				
		veh/h	%	v/c	sec		veh	m	per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	3	0.0	0.694	19.5	LOS B	23.1	173.7	0.72	0.66	42.8
2	T1	1593	8.5	0.694	12.1	LOS A	23.1	173.8	0.72	0.66	42.8
Approach		1596	8.5	0.694	12.1	LOS A	23.1	173.8	0.72	0.66	42.8
North: Moorebank Avenue (N)											
8	T1	751	13.9	0.278	3.6	LOS A	5.0	39.3	0.33	0.29	53.6
9	R2	24	69.6	0.141	18.0	LOS B	0.5	5.1	0.66	0.67	40.3
Approach		775	15.6	0.278	4.1	LOS A	5.0	39.3	0.34	0.30	53.1
West: Warehouse Access 3 (W)											
10	L2	18	94.1	0.082	38.8	LOS C	0.7	8.5	0.83	0.67	14.0
12	R2	1	0.0	0.082	39.0	LOS C	0.7	8.5	0.83	0.67	14.0
Approach		19	88.9	0.082	38.9	LOS C	0.7	8.5	0.83	0.67	14.0
All Vehicles		2389	11.5	0.694	9.7	LOS A	23.1	173.8	0.60	0.54	45.6

PHASING SUMMARY



Site: I-04 2023 FU MINT AM


Intersection of Moorebank Avenue and Warehouse Access 3

2023 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



MOVEMENT SUMMARY



Site: I-04 2023 FU MINT PM

Intersection of Moorebank Avenue and Warehouse Access 3

2023 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.288	LOS B	6.3	50.3	0.49	0.43	47.0
2	T1	634	15.6	0.288	LOS A	6.3	50.3	0.49	0.43	47.0
Approach		635	15.6	0.288	LOS A	6.3	50.3	0.49	0.43	47.0
North: Moorebank Avenue (N)										
8	T1	1811	7.0	0.649	LOS A	19.0	141.1	0.52	0.48	50.6
9	R2	18	94.1	0.056	LOS A	0.2	2.7	0.41	0.56	45.1
Approach		1828	7.9	0.649	LOS A	19.0	141.1	0.52	0.48	50.6
West: Warehouse Access 3 (W)										
10	L2	24	69.6	0.116	LOS C	1.0	11.0	0.86	0.70	13.5
12	R2	3	0.0	0.116	LOS C	1.0	11.0	0.86	0.70	13.5
Approach		27	61.5	0.116	LOS C	1.0	11.0	0.86	0.70	13.5
All Vehicles		2491	10.4	0.649	LOS A	19.0	141.1	0.51	0.47	49.2

PHASING SUMMARY



Site: I-04 2023 FU MINT PM


Intersection of Moorebank Avenue and Warehouse Access 3

2023 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



I-05 Intersection of Moorebank Avenue and Main Access

MOVEMENT SUMMARY



Site: I-05 2023 FU MINT AM

Intersection of Moorebank Avenue and Main Access

2023 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 85 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	v/c	sec	veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	35	0.0	0.748	23.6	LOS B	24.6	176.5	0.83	0.77	39.1
2	T1	1508	3.2	0.748	16.1	LOS B	24.6	177.3	0.83	0.76	39.3
Approach		1543	3.1	0.748	16.3	LOS B	24.6	177.3	0.83	0.76	39.2
North: Moorebank Avenue (N)											
8	T1	581	2.9	0.235	4.2	LOS A	4.5	32.2	0.36	0.31	52.7
9	R2	169	51.6	0.715	30.8	LOS C	5.5	55.7	1.00	0.93	32.9
Approach		751	13.9	0.715	10.2	LOS A	5.5	55.7	0.50	0.45	46.6
West: Main Access (W)											
10	L2	88	98.8	0.142	31.6	LOS C	1.4	18.5	0.77	0.68	16.2
12	R2	1	0.0	0.142	31.8	LOS C	1.4	17.7	0.77	0.68	16.2
Approach		89	97.6	0.142	31.6	LOS C	1.4	18.5	0.77	0.68	16.2
All Vehicles		2383	10.1	0.748	15.0	LOS B	24.6	177.3	0.73	0.66	40.7

PHASING SUMMARY



Site: I-05 2023 FU MINT AM


Intersection of Moorebank Avenue and Main Access

2023 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 85 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	52	70
Green Time (sec)	46	12	9
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	52	18	15
Phase Split	61 %	21 %	18 %



MOVEMENT SUMMARY



Site: I-05 2023 FU MINT PM

Intersection of Moorebank Avenue and Main Access

2023 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.303	27.2	LOS B	7.0	49.7	0.72	0.61	37.1
2	T1	464	2.5	0.303	19.8	LOS B	7.0	49.8	0.72	0.61	37.1
Approach		465	2.5	0.303	19.8	LOS B	7.0	49.8	0.72	0.61	37.1
North: Moorebank Avenue (N)											
8	T1	1726	2.3	0.708	6.2	LOS A	20.9	149.1	0.53	0.49	49.9
9	R2	88	98.8	0.181	12.6	LOS A	1.2	15.1	0.48	0.61	44.5
Approach		1815	7.0	0.708	6.5	LOS A	20.9	149.1	0.53	0.49	49.6
West: Main Access (W)											
10	L2	169	51.6	0.253	26.4	LOS B	4.2	42.6	0.69	0.71	18.4
12	R2	35	0.0	0.253	46.7	LOS D	2.1	17.0	0.93	0.75	12.1
Approach		204	42.8	0.253	29.8	LOS C	4.2	42.6	0.73	0.72	16.9
All Vehicles		2484	9.1	0.708	10.9	LOS A	20.9	149.1	0.58	0.53	44.5

PHASING SUMMARY



Site: I-05 2023 FU MINT PM


Intersection of Moorebank Avenue and Main Access

2023 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	42	60
Green Time (sec)	36	12	24
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	42	18	30
Phase Split	47 %	20 %	33 %



2. 2023 Future traffic without Moorebank IMT development (Do-nothing scenario)

I-01 Intersection of Moorebank Avenue and Bapaume Road

MOVEMENT SUMMARY



Site: I-01 2023 DN BASE AM

Intersection of Moorebank Avenue and Bapaume Road
2023 Do-nothing AM PEAK
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	20	0.0	0.011	5.5	LOS A	0.0	0.0	0.00	0.58	45.1
2	T1	1191	5.2	0.631	0.0	LOS A	0.0	0.0	0.00	0.00	59.7
Approach		1211	5.1	0.631	0.1	NA	0.0	0.0	0.00	0.01	59.5
North: Moorebank Avenue (S)											
8	T1	949	5.4	0.421	4.1	LOS A	4.1	29.9	0.16	0.07	51.8
9	R2	88	1.2	0.421	30.0	LOS C	4.1	29.9	1.00	0.42	33.9
Approach		1038	5.1	0.421	6.3	NA	4.1	29.9	0.24	0.10	49.0
West: Bapaume Road (W)											
10	L2	3	33.3	0.028	35.7	LOS C	0.1	0.7	0.89	0.95	29.2
12	R2	1	0.0	0.136	416.1	LOS F	0.3	2.3	0.99	1.00	2.9
Approach		4	25.0	0.136	130.8	LOS F	0.3	2.3	0.92	0.96	11.9
All Vehicles		2253	5.1	0.631	3.2	NA	4.1	29.9	0.11	0.05	53.6

MOVEMENT SUMMARY



Site: I-01 2023 DN BASE PM

Intersection of Moorebank Avenue and Bapaume Road
2023 Do-nothing PM PEAK
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.001	5.5	LOS A	0.0	0.0	0.00	0.58	45.1
2	T1	627	4.5	0.331	0.0	LOS A	0.0	0.0	0.00	0.00	59.9
Approach		628	4.5	0.331	0.0	NA	0.0	0.0	0.00	0.00	59.9
North: Moorebank Avenue (S)											
8	T1	1507	2.8	0.409	3.7	LOS A	7.5	53.5	0.42	0.01	52.8
9	R2	20	10.5	0.409	13.3	LOS A	7.5	53.5	0.86	0.03	46.1
Approach		1527	2.9	0.409	3.8	NA	7.5	53.5	0.42	0.01	52.7
West: Bapaume Road (W)											
10	L2	97	3.3	0.173	10.6	LOS A	0.7	4.8	0.59	0.82	44.9
12	R2	14	0.0	0.773	385.4	LOS F	2.3	16.4	1.00	1.07	3.2
Approach		111	2.9	0.773	57.0	LOS E	2.3	16.4	0.64	0.85	22.3
All Vehicles		2266	3.3	0.773	5.4	NA	7.5	53.5	0.31	0.05	50.2

I-02 Intersection of Moorebank Avenue and Anzac Road

MOVEMENT SUMMARY



Site: I-02 2023 DN BASE AM

Intersection of Moorebank Avenue and Anzac Road

2023 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
2	T1	1021	3.5	0.896	22.5	LOS B	42.5	306.1	0.71	0.75	37.3
3	R2	427	3.2	0.685	30.9	LOS C	16.6	119.4	0.92	0.93	39.0
Approach		1448	3.4	0.896	25.0	LOS B	42.5	306.1	0.77	0.80	38.0
East: Anzac Road (E)											
4	L2	231	3.2	0.278	24.2	LOS B	7.2	51.4	0.66	0.76	42.0
6	R2	203	13.5	0.772	55.5	LOS D	10.7	83.3	1.00	0.89	20.7
Approach		434	8.0	0.772	38.8	LOS C	10.7	83.3	0.82	0.82	30.9
North: Moorebank Avenue (N)											
7	L2	351	9.9	0.229	6.1	LOS A	1.3	9.7	0.16	0.59	49.8
8	T1	617	3.2	0.570	22.9	LOS B	17.6	126.8	0.77	0.67	37.1
Approach		967	5.7	0.570	16.8	LOS B	17.6	126.8	0.55	0.64	40.9
All Vehicles		2849	4.9	0.896	24.3	LOS B	42.5	306.1	0.70	0.75	37.3

PHASING SUMMARY



Site: I-02 2023 DN BASE AM


Intersection of Moorebank Avenue and Anzac Road

2023 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	50	78
Green Time (sec)	44	22	19
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	50	28	25
Phase Split	49 %	27 %	24 %



MOVEMENT SUMMARY



Site: I-02 2023 DN BASE PM

Intersection of Moorebank Avenue and Anzac Road

2023 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
		Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
2	T1	303	3.8	0.254	9.6	LOS A	7.1	51.1	0.47	0.41	47.6
3	R2	184	1.1	0.961	89.0	LOS F	12.9	91.2	1.00	1.20	24.1
Approach		487	2.8	0.961	39.6	LOS C	12.9	91.2	0.67	0.71	32.0
East: Anzac Road (E)											
4	L2	507	2.3	0.745	38.2	LOS C	23.8	170.1	0.93	0.87	36.2
6	R2	343	5.5	0.813	53.7	LOS D	19.0	139.2	1.00	0.92	21.1
Approach		851	3.6	0.813	44.4	LOS D	23.8	170.1	0.96	0.89	30.0
North: Moorebank Avenue (N)											
7	L2	315	4.0	0.196	6.0	LOS A	1.1	8.1	0.14	0.59	50.2
8	T1	1204	2.4	0.913	34.2	LOS C	54.1	386.9	0.90	0.92	31.2
Approach		1519	2.8	0.913	28.4	LOS B	54.1	386.9	0.74	0.85	33.8
All Vehicles		2857	3.0	0.961	35.1	LOS C	54.1	386.9	0.79	0.84	32.0

PHASING SUMMARY



Site: I-02 2023 DN BASE PM


Intersection of Moorebank Avenue and Anzac Road

2023 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	63	75
Green Time (sec)	57	6	29
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	63	12	35
Phase Split	57 %	11 %	32 %



I-03 Intersection of Moorebank Avenue and Defence Support Access

MOVEMENT SUMMARY



Site: I-03 2023 DN BASE AM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2023 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	17	0.0	0.010	6.0	LOS A	0.1	0.4	0.14	0.60	46.8
2	T1	1437	3.1	0.973	44.0	LOS D	88.0	632.3	0.98	1.20	33.2
Approach		1454	3.0	0.973	43.5	LOS D	88.0	632.3	0.97	1.19	33.3
North: Moorebank Avenue (N)											
8	T1	791	3.7	0.694	12.1	LOS A	17.6	126.8	0.61	0.54	49.0
9	R2	19	0.0	0.694	21.6	LOS B	17.6	126.8	0.75	0.67	27.6
Approach		809	3.6	0.694	12.3	LOS A	17.6	126.8	0.61	0.55	48.4
West: Military Access 1 (W)											
10	L2	2	0.0	0.023	48.3	LOS D	0.1	0.9	0.94	0.63	25.5
12	R2	1	0.0	0.023	48.2	LOS D	0.1	0.9	0.94	0.63	22.8
Approach		3	0.0	0.023	48.3	LOS D	0.1	0.9	0.94	0.63	24.6
All Vehicles		2266	3.3	0.973	32.4	LOS C	88.0	632.3	0.84	0.96	37.5

PHASING SUMMARY



Site: I-03 2023 DN BASE AM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2023 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	76
Green Time (sec)	70	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	76	14
Phase Split	84 %	16 %



MOVEMENT SUMMARY



Site: I-03 2023 DN BASE PM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2023 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.001	6.0	LOS A	0.0	0.14	0.58	46.8
2	T1	476	2.4	0.319	3.1	LOS A	6.1	0.32	0.28	56.8
Approach		477	2.4	0.319	3.1	LOS A	6.1	0.32	0.28	56.7
North: Moorebank Avenue (N)										
8	T1	1686	2.5	1.076	96.4	LOS F	128.3	0.85	1.45	21.7
9	R2	1	0.0	1.076	127.6	LOS F	128.3	1.00	1.77	11.8
Approach		1687	2.5	1.076	96.4	LOS F	128.3	0.85	1.45	21.7
West: Military Access 1 (W)										
10	L2	11	0.0	0.109	49.3	LOS D	0.6	0.96	0.69	25.2
12	R2	4	0.0	0.109	49.3	LOS D	0.6	0.96	0.69	22.5
Approach		15	0.0	0.109	49.3	LOS D	0.6	0.96	0.69	24.5
All Vehicles		2179	2.5	1.076	75.7	LOS F	128.3	0.73	1.19	25.1

PHASING SUMMARY



Site: I-03 2023 DN BASE PM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2023 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	76
Green Time (sec)	70	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	76	14
Phase Split	84 %	16 %



I-04 Intersection of Moorebank Avenue and DNSDC Access

MOVEMENT SUMMARY



Site: I-04 2023 DN BASE AM

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2023 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate	Average Speed		
		veh/h	%	v/c	sec	veh	m	per veh	km/h		
South: Moorebank Avenue (S)											
2	T1	1488	2.6	0.890	14.2	LOS A	34.9	249.8	0.56	0.61	47.6
3	R2	24	0.0	0.890	24.5	LOS B	34.9	249.8	0.65	0.74	44.7
Approach		1513	2.6	0.890	14.4	LOS A	34.9	249.8	0.56	0.61	47.5
East: DNSDC Access (W)											
4	L2	5	20.0	0.043	44.8	LOS D	0.2	1.7	0.95	0.65	33.8
6	R2	7	14.3	0.042	42.0	LOS C	0.3	2.1	0.93	0.66	33.0
Approach		13	16.7	0.043	43.2	LOS D	0.3	2.1	0.94	0.65	33.4
North: Moorebank Avenue (N)											
7	L2	111	6.7	0.073	6.1	LOS A	0.4	2.7	0.17	0.61	52.1
8	T1	648	3.4	0.453	4.0	LOS A	9.5	68.2	0.41	0.37	55.9
Approach		759	3.9	0.453	4.3	LOS A	9.5	68.2	0.37	0.41	55.3
West: Carpark Access (W)											
10	L2	1	0.0	0.006	39.4	LOS C	0.0	0.3	0.92	0.59	24.3
12	R2	1	0.0	0.007	41.7	LOS C	0.0	0.3	0.94	0.59	26.0
Approach		2	0.0	0.007	40.5	LOS C	0.0	0.3	0.93	0.59	25.2
All Vehicles		2286	3.1	0.890	11.2	LOS A	34.9	249.8	0.50	0.54	49.7

PHASING SUMMARY



Site: I-04 2023 DN BASE AM


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2023 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	66
Green Time (sec)	60	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	66	14
Phase Split	83 %	18 %



MOVEMENT SUMMARY



Site: I-04 2023 DN BASE PM

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2023 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
2	T1	441	2.1	0.219	3.4	LOS A	4.8	33.9	0.28	0.24	56.5
3	R2	1	0.0	0.219	9.4	LOS A	4.8	33.9	0.30	0.27	54.9
Approach		442	2.1	0.219	3.4	LOS A	4.8	33.9	0.28	0.24	56.5
East: DNSDC Access (W)											
4	L2	4	0.0	0.050	62.6	LOS E	0.2	1.6	0.98	0.64	29.2
6	R2	23	9.1	0.185	59.9	LOS E	1.2	9.3	0.97	0.71	28.1
Approach		27	7.7	0.185	60.3	LOS E	1.2	9.3	0.97	0.70	28.3
North: Moorebank Avenue (N)											
7	L2	6	16.7	0.004	6.1	LOS A	0.0	0.2	0.11	0.59	51.9
8	T1	1655	2.2	1.056	98.8	LOS F	162.9	1161.2	1.00	1.51	21.4
Approach		1661	2.2	1.056	98.4	LOS F	162.9	1161.2	1.00	1.50	21.5
West: Carpark Access (W)											
10	L2	6	0.0	0.047	56.7	LOS E	0.3	2.3	0.95	0.65	19.4
12	R2	3	0.0	0.036	60.5	LOS E	0.2	1.2	0.98	0.62	21.0
Approach		9	0.0	0.047	57.9	LOS E	0.3	2.3	0.96	0.64	20.0
All Vehicles		2140	2.3	1.056	78.1	LOS F	162.9	1161.2	0.85	1.23	24.7

PHASING SUMMARY



Site: I-04 2023 DN BASE PM


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2023 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	96
Green Time (sec)	90	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	96	14
Phase Split	87 %	13 %



I-05 Intersection of Moorebank Avenue and Chatham Avenue

MOVEMENT SUMMARY



Site: I-05 2023 DN BASE AM

Intersection of Moorebank Avenue and Chatham Avenue

2023 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles										
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	v/c	sec	veh	m	per veh	km/h	
South: Moorebank Avenue (S)										
1	L2	46	0.0	0.030	7.1	LOS A	0.4	2.8	0.18	51.7
2	T1	1497	2.5	1.134	171.7	LOS F	182.5	1304.9	1.00	1.89
Approach		1543	2.5	1.134	166.8	LOS F	182.5	1304.9	0.98	1.85
North: Moorebank Avenue (N)										
8	T1	479	4.6	0.363	2.6	LOS A	6.1	44.4	0.26	57.6
9	R2	143	0.7	0.829	65.2	LOS E	8.1	56.8	1.00	1.00
Approach		622	3.7	0.829	17.0	LOS B	8.1	56.8	0.43	0.41
West: Chatham Avenue (W)										
10	L2	18	5.9	0.182	56.4	LOS D	1.6	12.2	0.95	0.72
12	R2	13	25.0	0.182	56.6	LOS E	1.6	12.2	0.95	0.72
Approach		31	13.8	0.182	56.4	LOS D	1.6	12.2	0.95	0.72
All Vehicles		2196	3.0	1.134	122.8	LOS F	182.5	1304.9	0.82	1.43

PHASING SUMMARY



Site: I-05 2023 DN BASE AM


Intersection of Moorebank Avenue and Chatham Avenue

2023 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	84	96
Green Time (sec)	78	6	8
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	84	12	14
Phase Split	76 %	11 %	13 %



MOVEMENT SUMMARY



Site: I-05 2023 DN BASE PM

Intersection of Moorebank Avenue and Chatham Avenue

2023 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	11	0.0	0.007	7.2	LOS A	0.1	0.6	0.19	0.60	51.6
2	T1	393	1.9	0.310	7.2	LOS A	7.8	55.5	0.44	0.39	53.6
Approach		403	1.8	0.310	7.2	LOS A	7.8	55.5	0.44	0.40	53.6
North: Moorebank Avenue (N)											
8	T1	1628	2.1	1.105	140.9	LOS F	177.0	1261.9	1.00	1.83	18.0
9	R2	28	0.0	0.041	10.3	LOS A	0.4	2.9	0.38	0.66	48.7
Approach		1657	2.1	1.105	138.7	LOS F	177.0	1261.9	0.99	1.81	18.2
West: Chatham Avenue (W)											
10	L2	43	2.4	0.196	46.6	LOS D	2.3	16.7	0.91	0.74	31.9
12	R2	11	0.0	0.196	46.5	LOS D	2.3	16.7	0.91	0.74	31.8
Approach		54	2.0	0.196	46.6	LOS D	2.3	16.7	0.91	0.74	31.9
All Vehicles		2114	2.0	1.105	111.3	LOS F	177.0	1261.9	0.88	1.51	21.1

PHASING SUMMARY



Site: I-05 2023 DN BASE PM


Intersection of Moorebank Avenue and Chatham Avenue

2023 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	73	85
Green Time (sec)	67	6	9
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	73	12	15
Phase Split	73 %	12 %	15 %



Appendix G

2028 SIDRA results with and
without Moorebank IMT

1. 2028 Future traffic with Moorebank IMT development (Phase C)

I-01 Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

MOVEMENT SUMMARY



Site: I-01 2028 FU MINT AM

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2028 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	37	0.0	0.766	31.1	LOS C	24.7	190.9	0.81	0.74	34.4
2	T1	1188	12.9	0.766	23.5	LOS B	24.7	190.9	0.81	0.73	34.7
3	R2	463	3.2	0.748	20.8	LOS B	11.2	80.2	0.85	0.86	38.1
Approach		1688	10.0	0.766	23.0	LOS B	24.7	191.0	0.82	0.77	35.5
East: Anzac Road (E)											
4	L2	216	3.9	0.350	34.9	LOS C	8.7	62.8	0.77	0.80	30.6
5	T1	9	0.0	0.350	27.9	LOS B	8.7	62.8	0.77	0.80	30.6
6	R2	216	13.7	0.782	60.0	LOS E	12.1	94.4	1.00	0.90	22.7
Approach		441	8.6	0.782	47.0	LOS D	12.1	94.4	0.88	0.85	26.1
North: Moorebank Avenue (N)											
7	L2	375	9.8	0.216	7.6	LOS A	0.0	0.0	0.00	0.57	48.5
8	T1	673	19.6	0.436	18.9	LOS B	9.8	80.4	0.59	0.51	36.0
9	R2	139	7.6	0.312	22.0	LOS B	3.4	25.2	0.79	0.79	34.1
Approach		1186	15.1	0.436	15.7	LOS B	9.8	80.4	0.42	0.56	39.0
West: Bapaume Road (W)											
10	L2	13	83.3	0.032	14.8	LOS B	0.2	2.7	0.51	0.56	34.1
11	T1	1	0.0	0.010	45.4	LOS D	0.1	0.7	0.89	0.60	18.4
12	R2	1	0.0	0.010	52.5	LOS D	0.1	0.7	0.89	0.60	18.4
Approach		15	71.4	0.032	19.7	LOS B	0.2	2.7	0.57	0.57	30.5
All Vehicles		3331	11.9	0.782	23.6	LOS B	24.7	191.0	0.68	0.70	34.8

PHASING SUMMARY



Site: I-01 2028 FU MINT AM


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2028 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	55	83
Green Time (sec)	49	22	21
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	55	28	27
Phase Split	50 %	25 %	25 %



MOVEMENT SUMMARY



Site: I-01 2028 FU MINT PM

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2028 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 105 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.244	13.5	LOS A	3.1	26.3	0.27	0.23	50.3
2	T1	485	26.5	0.244	6.0	LOS A	3.1	26.3	0.27	0.23	50.3
3	R2	212	1.0	0.927	81.6	LOS F	13.9	98.3	1.00	1.19	18.5
Approach		698	18.7	0.927	28.9	LOS C	13.9	98.3	0.49	0.52	33.1
East: Anzac Road (E)											
4	L2	562	2.2	0.754	37.1	LOS C	24.9	177.5	0.92	0.88	29.7
5	T1	1	0.0	0.754	30.1	LOS C	24.9	177.5	0.92	0.88	29.7
6	R2	386	5.4	0.929	71.0	LOS F	25.1	183.7	1.00	1.06	20.4
Approach		949	3.5	0.929	50.9	LOS D	25.1	183.7	0.95	0.95	25.0
North: Moorebank Avenue (N)											
7	L2	343	4.0	0.190	7.6	LOS A	0.0	0.0	0.00	0.59	48.5
8	T1	1364	10.8	0.896	31.1	LOS C	35.3	269.8	0.80	0.84	28.9
9	R2	31	37.9	0.098	25.8	LOS B	0.9	8.5	0.60	0.68	31.7
Approach		1738	9.9	0.896	26.3	LOS B	35.3	269.8	0.64	0.79	31.5
West: Bapaume Road (W)											
10	L2	148	8.5	0.225	12.7	LOS A	2.5	19.1	0.43	0.67	35.9
11	T1	13	0.0	0.210	42.8	LOS D	1.9	13.0	0.90	0.73	18.9
12	R2	27	0.0	0.210	49.9	LOS D	1.9	13.0	0.90	0.73	18.9
Approach		188	6.7	0.225	20.1	LOS B	2.5	19.1	0.53	0.68	30.2
All Vehicles		3574	9.8	0.929	33.0	LOS C	35.3	269.8	0.69	0.77	29.5

PHASING SUMMARY



Site: I-01 2028 FU MINT PM


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2028 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 105 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	56	69
Green Time (sec)	50	7	30
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	56	13	36
Phase Split	53 %	12 %	34 %



I-02 Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

MOVEMENT SUMMARY



Site: I-02 2028 FU MINT AM

Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2028 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Prop. Queued	Effective Stop Rate	Average Speed		
		veh/h	%	v/c	sec	veh	m	per veh	km/h		
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.691	10.1	LOS A	12.4	93.9	0.33	0.31	45.1
2	T1	1674	9.6	0.691	4.6	LOS A	12.4	93.9	0.33	0.31	52.4
3	R2	25	0.0	0.227	56.9	LOS E	1.3	8.8	0.98	0.71	12.3
Approach		1700	9.4	0.691	5.4	LOS A	12.4	93.9	0.34	0.31	50.8
East: DNSDC Access (E)											
4	L2	5	20.0	0.094	52.7	LOS D	0.6	4.7	0.95	0.69	15.7
6	R2	7	14.3	0.094	52.7	LOS D	0.6	4.7	0.95	0.69	18.7
Approach		13	16.7	0.094	52.7	LOS D	0.6	4.7	0.95	0.69	17.5
North: Moorebank Avenue (N)											
7	L2	116	6.4	0.380	13.8	LOS A	9.5	74.6	0.49	0.51	29.3
8	T1	762	16.4	0.380	8.2	LOS A	9.6	77.0	0.49	0.47	46.9
9	R2	11	70.0	0.142	58.6	LOS E	0.5	5.9	0.98	0.68	16.8
Approach		888	15.8	0.380	9.5	LOS A	9.6	77.0	0.49	0.48	43.5
West: Warehouse Access 1 (W)											
10	L2	8	87.5	0.051	43.9	LOS D	0.4	4.7	0.86	0.67	19.7
12	R2	1	0.0	0.051	43.1	LOS D	0.4	4.7	0.86	0.67	18.3
Approach		9	77.8	0.051	43.8	LOS D	0.4	4.7	0.86	0.67	19.6
All Vehicles		2611	11.9	0.691	7.2	LOS A	12.4	93.9	0.40	0.37	47.6

PHASING SUMMARY



Site: I-02 2028 FU MINT AM


Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2028 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



MOVEMENT SUMMARY



Site: I-02 2028 FU MINT PM

Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2028 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.288	8.6	LOS A	2.6	20.9	0.17	0.15	47.8
2	T1	662	18.3	0.288	3.1	LOS A	2.6	20.9	0.17	0.15	54.7
3	R2	1	0.0	0.009	17.5	LOS B	0.0	0.2	0.47	0.63	20.6
Approach		664	18.2	0.288	3.1	LOS A	2.6	20.9	0.17	0.15	54.6
East: DNSDC Access (E)											
4	L2	4	0.0	0.245	56.1	LOS D	1.4	10.4	0.98	0.72	15.5
6	R2	24	8.7	0.245	56.1	LOS D	1.4	10.4	0.98	0.72	18.0
Approach		28	7.4	0.245	56.1	LOS D	1.4	10.4	0.98	0.72	17.7
North: Moorebank Avenue (N)											
7	L2	6	16.7	0.676	11.2	LOS A	21.9	163.4	0.51	0.47	31.8
8	T1	1940	7.8	0.676	5.4	LOS A	21.9	163.4	0.50	0.47	51.3
9	R2	8	87.5	0.123	58.9	LOS E	0.4	5.2	0.97	0.68	16.6
Approach		1955	8.2	0.676	5.6	LOS A	21.9	163.4	0.51	0.47	50.8
West: Warehouse Access 1 (W)											
10	L2	11	70.0	0.056	43.6	LOS D	0.5	5.3	0.87	0.68	20.0
12	R2	1	0.0	0.056	43.0	LOS D	0.5	5.3	0.87	0.68	18.3
Approach		12	63.6	0.056	43.6	LOS D	0.5	5.3	0.87	0.68	19.9
All Vehicles		2659	10.9	0.676	5.7	LOS A	21.9	163.4	0.43	0.40	50.7

PHASING SUMMARY



Site: I-02 2028 FU MINT PM


Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2028 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



I-03 Intersection of Moorebank Avenue and Warehouse Access 2

MOVEMENT SUMMARY



Site: I-03 2028 FU MINT AM

Intersection of Moorebank Avenue and Warehouse Access 2

2028 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue	Prop. Queued	Effective Stop Rate	Average Speed	
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m	per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.738	20.1	LOS B	25.8	194.4	0.76	0.70	43.3
2	T1	1692	9.0	0.738	12.7	LOS A	25.8	194.4	0.76	0.70	43.3
Approach		1693	9.0	0.738	12.7	LOS A	25.8	194.4	0.76	0.70	43.3
North: Moorebank Avenue (N)											
8	T1	756	15.6	0.282	0.9	LOS A	1.1	8.9	0.07	0.06	56.8
9	R2	12	72.7	0.071	18.9	LOS B	0.2	2.6	0.67	0.64	28.5
Approach		767	16.5	0.282	1.1	LOS A	1.1	8.9	0.08	0.07	56.0
West: Warehouse Access 2 (W)											
10	L2	9	88.9	0.047	39.3	LOS C	0.4	4.5	0.83	0.66	13.8
12	R2	1	0.0	0.047	39.5	LOS C	0.4	4.5	0.83	0.66	13.8
Approach		11	80.0	0.047	39.4	LOS C	0.4	4.5	0.83	0.66	13.8
All Vehicles		2471	11.6	0.738	9.2	LOS A	25.8	194.4	0.55	0.50	45.0

PHASING SUMMARY



Site: I-03 2028 FU MINT AM


Intersection of Moorebank Avenue and Warehouse Access 2

2028 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



MOVEMENT SUMMARY



Site: I-03 2028 FU MINT PM

Intersection of Moorebank Avenue and Warehouse Access 2

2028 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.299	LOS B	6.6	52.8	0.50	0.43	47.8
2	T1	651	17.3	0.299	LOS A	6.6	52.8	0.50	0.43	47.8
Approach		652	17.3	0.299	LOS A	6.6	52.8	0.50	0.43	47.8
North: Moorebank Avenue (N)										
8	T1	1937	7.4	0.689	LOS A	6.1	45.2	0.16	0.15	54.5
9	R2	9	88.9	0.030	LOS A	0.1	1.4	0.41	0.55	35.1
Approach		1946	7.8	0.689	LOS A	6.1	45.2	0.16	0.15	54.4
West: Warehouse Access 2 (W)										
10	L2	12	72.7	0.052	LOS C	0.5	5.1	0.84	0.66	13.9
12	R2	1	0.0	0.052	LOS C	0.5	5.1	0.84	0.66	13.9
Approach		13	66.7	0.052	LOS C	0.5	5.1	0.84	0.66	13.9
All Vehicles		2611	10.4	0.689	LOS A	6.6	52.8	0.25	0.22	51.2

PHASING SUMMARY



Site: I-03 2028 FU MINT PM


Intersection of Moorebank Avenue and Warehouse Access 2

2028 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



I-04 Intersection of Moorebank Avenue and Warehouse Access 3

MOVEMENT SUMMARY



Site: I-04 2028 FU MINT AM

Intersection of Moorebank Avenue and Warehouse Access 3

2028 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay v/c	Level of Service sec	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate per veh	Average Speed km/h		
South: Moorebank Avenue (S)											
1	L2	2	0.0	0.729	20.0	LOS B	25.3	189.6	0.75	0.69	42.3
2	T1	1678	8.2	0.729	12.6	LOS A	25.3	189.7	0.75	0.69	42.3
Approach		1680	8.1	0.729	12.6	LOS A	25.3	189.7	0.75	0.69	42.3
North: Moorebank Avenue (N)											
8	T1	735	14.0	0.272	3.6	LOS A	4.9	38.3	0.33	0.29	53.6
9	R2	21	70.0	0.126	19.3	LOS B	0.4	4.8	0.69	0.67	39.4
Approach		756	15.6	0.272	4.0	LOS A	4.9	38.3	0.34	0.30	53.1
West: Warehouse Access 3 (W)											
10	L2	16	93.3	0.073	38.8	LOS C	0.6	7.5	0.83	0.67	14.0
12	R2	1	0.0	0.073	38.9	LOS C	0.6	7.5	0.83	0.67	14.0
Approach		17	87.5	0.073	38.8	LOS C	0.6	7.5	0.83	0.67	14.0
All Vehicles		2453	11.0	0.729	10.1	LOS A	25.3	189.7	0.62	0.57	45.1

PHASING SUMMARY



Site: I-04 2028 FU MINT AM


Intersection of Moorebank Avenue and Warehouse Access 3

2028 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



MOVEMENT SUMMARY



Site: I-04 2028 FU MINT PM

Intersection of Moorebank Avenue and Warehouse Access 3

2028 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.286	LOS B	6.3	49.9	0.49	0.43	47.0
2	T1	629	15.6	0.286	LOS A	6.3	49.9	0.49	0.43	47.0
Approach		631	15.5	0.286	LOS A	6.3	49.9	0.49	0.43	47.0
North: Moorebank Avenue (N)										
8	T1	1923	6.7	0.689	LOS A	21.5	159.0	0.55	0.51	50.2
9	R2	16	93.3	0.049	LOS A	0.2	2.4	0.41	0.56	45.1
Approach		1939	7.4	0.689	LOS A	21.5	159.0	0.55	0.51	50.1
West: Warehouse Access 3 (W)										
10	L2	21	70.0	0.095	LOS C	0.9	9.2	0.85	0.69	13.7
12	R2	2	0.0	0.095	LOS C	0.9	9.2	0.85	0.69	13.7
Approach		23	63.6	0.095	LOS C	0.9	9.2	0.85	0.69	13.7
All Vehicles		2593	9.9	0.689	LOS A	21.5	159.0	0.54	0.49	49.0

PHASING SUMMARY



Site: I-04 2028 FU MINT PM


Intersection of Moorebank Avenue and Warehouse Access 3

2028 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



I-05 Intersection of Moorebank Avenue and Main Access

MOVEMENT SUMMARY



Site: I-05 2028 FU MINT AM

Intersection of Moorebank Avenue and Main Access

2028 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 85 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	19	0.0	0.734	21.6	LOS B	24.5	175.9	0.79	0.73	40.8
2	T1	1596	3.2	0.734	14.2	LOS A	24.5	176.3	0.79	0.73	40.8
Approach		1615	3.2	0.734	14.3	LOS A	24.5	176.3	0.79	0.73	40.8
North: Moorebank Avenue (N)											
8	T1	604	3.0	0.245	4.3	LOS A	4.7	33.7	0.36	0.31	52.7
9	R2	131	65.3	0.736	30.8	LOS C	4.6	50.0	1.00	0.94	32.9
Approach		735	14.0	0.736	9.0	LOS A	4.7	50.0	0.47	0.42	47.8
West: Main Access (W)											
10	L2	86	98.8	0.157	34.3	LOS C	1.5	18.9	0.81	0.69	15.3
12	R2	1	0.0	0.157	34.4	LOS C	1.4	18.3	0.81	0.69	15.3
Approach		87	97.6	0.157	34.3	LOS C	1.5	18.9	0.81	0.69	15.3
All Vehicles		2437	9.8	0.736	13.4	LOS A	24.5	176.3	0.70	0.63	42.0

PHASING SUMMARY



Site: I-05 2028 FU MINT AM


Intersection of Moorebank Avenue and Main Access

2028 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 85 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	55	73
Green Time (sec)	49	12	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	55	18	12
Phase Split	65 %	21 %	14 %



MOVEMENT SUMMARY



Site: I-05 2028 FU MINT PM

Intersection of Moorebank Avenue and Main Access

2028 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.317	LOS B	7.4	53.0	0.72	0.61	37.5
2	T1	499	2.5	0.317	LOS B	7.4	53.0	0.72	0.61	37.5
Approach		500	2.5	0.317	LOS B	7.4	53.0	0.72	0.61	37.5
North: Moorebank Avenue (N)										
8	T1	1841	2.3	0.766	LOS A	23.2	165.5	0.56	0.52	49.4
9	R2	86	98.8	0.183	LOS A	1.1	14.7	0.48	0.61	44.5
Approach		1927	6.7	0.766	LOS A	23.2	165.5	0.56	0.52	49.2
West: Main Access (W)										
10	L2	131	65.3	0.196	LOS B	3.0	32.2	0.70	0.69	17.7
12	R2	19	0.0	0.196	LOS D	1.7	15.2	0.91	0.73	12.6
Approach		149	57.0	0.196	LOS C	3.0	32.2	0.72	0.70	16.9
All Vehicles		2577	8.8	0.766	LOS A	23.2	165.5	0.60	0.55	44.9

PHASING SUMMARY



Site: I-05 2028 FU MINT PM


Intersection of Moorebank Avenue and Main Access

2028 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	43	61
Green Time (sec)	37	12	23
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	43	18	29
Phase Split	48 %	20 %	32 %



2. 2028 Future traffic without Moorebank IMT development (Do-nothing scenario)

I-01 Intersection of Moorebank Avenue and Bapaume Road

MOVEMENT SUMMARY



Site: I-01 2028 DN BASE AM

Intersection of Moorebank Avenue and Bapaume Road
2028 Do-nothing AM PEAK
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	21	0.0	0.011	5.5	LOS A	0.0	0.0	0.00	0.58	45.1
2	T1	1272	5.2	0.674	0.0	LOS A	0.0	0.0	0.00	0.00	59.7
Approach		1293	5.1	0.674	0.1	NA	0.0	0.0	0.00	0.01	59.4
North: Moorebank Avenue (S)											
8	T1	991	5.4	0.478	2.8	LOS A	3.7	26.4	0.09	0.05	54.1
9	R2	93	1.1	0.478	35.5	LOS C	3.7	26.4	1.00	0.59	30.9
Approach		1083	5.1	0.478	5.6	NA	3.7	26.4	0.17	0.10	50.0
West: Bapaume Road (W)											
10	L2	3	33.3	0.037	45.3	LOS D	0.1	0.9	0.92	0.97	26.0
12	R2	1	0.0	0.222	760.5	LOS F	0.5	3.7	1.00	1.00	1.7
Approach		4	25.0	0.222	224.1	LOS F	0.5	3.7	0.94	0.97	7.6
All Vehicles		2380	5.1	0.674	3.0	NA	3.7	26.4	0.08	0.05	53.9

MOVEMENT SUMMARY



Site: I-01 2028 DN BASE PM

Intersection of Moorebank Avenue and Bapaume Road
2028 Do-nothing PM PEAK
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.001	5.5	LOS A	0.0	0.0	0.00	0.58	45.1
2	T1	668	4.6	0.353	0.0	LOS A	0.0	0.0	0.00	0.00	59.9
Approach		669	4.6	0.353	0.0	NA	0.0	0.0	0.00	0.00	59.9
North: Moorebank Avenue (S)											
8	T1	1612	2.8	0.438	4.3	LOS A	9.2	66.2	0.48	0.01	51.8
9	R2	21	10.0	0.438	14.7	LOS B	9.2	66.2	1.00	0.03	44.9
Approach		1633	2.9	0.438	4.5	NA	9.2	66.2	0.49	0.01	51.6
West: Bapaume Road (W)											
10	L2	102	3.1	0.194	11.2	LOS A	0.7	5.3	0.61	0.83	44.4
12	R2	15	0.0	1.000	558.0	LOS F	3.5	24.6	1.00	1.14	2.2
Approach		117	2.7	1.000	80.1	LOS F	3.5	24.6	0.66	0.87	17.9
All Vehicles		2419	3.4	1.000	6.9	NA	9.2	66.2	0.36	0.05	48.0

I-02 Intersection of Moorebank Avenue and Anzac Road

MOVEMENT SUMMARY



Site: I-02 2028 DN BASE AM

Intersection of Moorebank Avenue and Anzac Road

2028 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
2	T1	1091	3.5	1.038	103.0	LOS F	101.5	732.0	1.00	1.51	15.9
3	R2	463	3.2	0.754	35.1	LOS C	18.8	135.1	0.95	0.98	37.3
Approach		1554	3.4	1.038	82.7	LOS F	101.5	732.0	0.99	1.35	20.8
East: Anzac Road (E)											
4	L2	249	3.4	0.301	24.4	LOS B	7.8	56.5	0.67	0.76	41.9
6	R2	219	13.5	0.832	58.8	LOS E	12.0	94.0	1.00	0.94	20.1
Approach		468	8.1	0.832	40.5	LOS C	12.0	94.0	0.82	0.84	30.4
North: Moorebank Avenue (N)											
7	L2	375	9.8	0.244	6.1	LOS A	1.4	10.6	0.16	0.59	49.8
8	T1	638	3.3	0.590	23.1	LOS B	18.4	132.7	0.78	0.68	36.9
Approach		1013	5.7	0.590	16.8	LOS B	18.4	132.7	0.55	0.65	40.9
All Vehicles		3035	4.9	1.038	54.2	LOS D	101.5	732.0	0.82	1.04	26.0

PHASING SUMMARY



Site: I-02 2028 DN BASE AM


Intersection of Moorebank Avenue and Anzac Road

2028 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	50	78
Green Time (sec)	44	22	19
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	50	28	25
Phase Split	49 %	27 %	24 %



MOVEMENT SUMMARY



Site: I-02 2028 DN BASE PM

Intersection of Moorebank Avenue and Anzac Road

2028 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
2	T1	320	3.9	0.268	9.7	LOS A	7.5	54.6	0.48	0.42	47.5
3	R2	203	1.0	1.183	208.2	LOS F	24.8	175.0	1.00	1.34	13.5
Approach		523	2.8	1.183	86.8	LOS F	24.8	175.0	0.68	0.77	20.8
East: Anzac Road (E)											
4	L2	572	2.2	0.839	45.0	LOS D	30.7	218.8	0.98	0.93	33.9
6	R2	386	5.4	0.914	66.8	LOS E	24.9	182.3	1.00	1.01	18.7
Approach		958	3.5	0.914	53.8	LOS D	30.7	218.8	0.99	0.96	27.4
North: Moorebank Avenue (N)											
7	L2	349	3.9	0.217	6.0	LOS A	1.3	9.2	0.14	0.59	50.2
8	T1	1287	2.5	0.976	52.6	LOS D	73.0	521.8	0.91	1.05	24.8
Approach		1637	2.8	0.976	42.7	LOS D	73.0	521.8	0.74	0.95	27.8
All Vehicles		3118	3.0	1.183	53.5	LOS D	73.0	521.8	0.81	0.93	26.1

PHASING SUMMARY



Site: I-02 2028 DN BASE PM


Intersection of Moorebank Avenue and Anzac Road

2028 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	63	75
Green Time (sec)	57	6	29
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	63	12	35
Phase Split	57 %	11 %	32 %



I-03 Intersection of Moorebank Avenue and Defence Support Access

MOVEMENT SUMMARY



Site: I-03 2028 DN BASE AM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2028 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	v/c	sec	veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	18	0.0	0.011	6.0	LOS A	0.1	0.4	0.14	0.60	46.8
2	T1	1536	3.1	1.040	87.9	LOS F	129.6	931.5	1.00	1.55	23.0
Approach		1554	3.0	1.040	87.0	LOS F	129.6	931.5	0.99	1.54	23.1
North: Moorebank Avenue (N)											
8	T1	822	3.7	0.827	18.7	LOS B	22.3	160.6	0.65	0.64	44.6
9	R2	20	0.0	0.827	32.3	LOS C	22.3	160.6	0.84	0.85	24.3
Approach		842	3.6	0.827	19.0	LOS B	22.3	160.6	0.65	0.65	44.0
West: Military Access 1 (W)											
10	L2	2	0.0	0.023	48.3	LOS D	0.1	0.9	0.94	0.63	25.5
12	R2	1	0.0	0.023	48.2	LOS D	0.1	0.9	0.94	0.63	22.8
Approach		3	0.0	0.023	48.3	LOS D	0.1	0.9	0.94	0.63	24.6
All Vehicles		2399	3.2	1.040	63.1	LOS E	129.6	931.5	0.87	1.22	27.7

PHASING SUMMARY



Site: I-03 2028 DN BASE AM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2028 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	76
Green Time (sec)	70	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	76	14
Phase Split	84 %	16 %



MOVEMENT SUMMARY



Site: I-03 2028 DN BASE PM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2028 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.001	6.0	LOS A	0.0	0.14	0.58	46.8
2	T1	501	2.5	0.336	3.2	LOS A	6.5	0.32	0.29	56.7
Approach		502	2.5	0.336	3.2	LOS A	6.5	0.32	0.29	56.7
North: Moorebank Avenue (N)										
8	T1	1822	2.5	1.162	152.7	LOS F	173.0	0.85	1.82	15.8
9	R2	1	0.0	1.162	199.4	LOS F	173.0	1.00	2.25	8.5
Approach		1823	2.5	1.162	152.7	LOS F	173.0	0.85	1.82	15.8
West: Military Access 1 (W)										
10	L2	12	0.0	0.117	49.4	LOS D	0.7	0.96	0.69	25.2
12	R2	4	0.0	0.117	49.4	LOS D	0.7	0.96	0.69	22.5
Approach		16	0.0	0.117	49.4	LOS D	0.7	0.96	0.69	24.5
All Vehicles		2341	2.5	1.162	119.9	LOS F	173.0	0.74	1.49	18.7

PHASING SUMMARY



Site: I-03 2028 DN BASE PM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2028 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	76
Green Time (sec)	70	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	76	14
Phase Split	84 %	16 %



I-04 Intersection of Moorebank Avenue and DNSDC Access

MOVEMENT SUMMARY



Site: I-04 2028 DN BASE AM

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2028 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay v/c	Level of Service sec	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate per veh	Average Speed km/h		
South: Moorebank Avenue (S)											
2	T1	1592	2.6	1.004	50.2	LOS D	80.1	573.1	0.80	1.10	31.3
3	R2	25	0.0	1.004	77.9	LOS F	80.1	573.1	1.00	1.47	27.0
Approach		1617	2.6	1.004	50.7	LOS D	80.1	573.1	0.80	1.10	31.2
East: DNSDC Access (W)											
4	L2	5	20.0	0.043	44.8	LOS D	0.2	1.7	0.95	0.65	33.8
6	R2	7	14.3	0.042	42.0	LOS C	0.3	2.1	0.93	0.66	33.0
Approach		13	16.7	0.043	43.2	LOS D	0.3	2.1	0.94	0.65	33.4
North: Moorebank Avenue (N)											
7	L2	116	6.4	0.077	6.1	LOS A	0.4	2.9	0.17	0.61	52.1
8	T1	675	3.4	0.472	4.1	LOS A	10.1	72.6	0.42	0.38	55.8
Approach		791	3.9	0.472	4.4	LOS A	10.1	72.6	0.38	0.41	55.2
West: Carpark Access (W)											
10	L2	1	0.0	0.006	39.4	LOS C	0.0	0.3	0.92	0.59	24.3
12	R2	1	0.0	0.007	41.7	LOS C	0.0	0.3	0.94	0.59	26.0
Approach		2	0.0	0.007	40.5	LOS C	0.0	0.3	0.93	0.59	25.2
All Vehicles		2422	3.1	1.004	35.5	LOS C	80.1	573.1	0.66	0.88	36.4

PHASING SUMMARY



Site: I-04 2028 DN BASE AM


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2028 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	66
Green Time (sec)	60	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	66	14
Phase Split	83 %	18 %



MOVEMENT SUMMARY



Site: I-04 2028 DN BASE PM

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2028 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
2	T1	464	2.0	0.230	3.4	LOS A	5.1	36.0	0.28	0.24	56.5
3	R2	1	0.0	0.230	9.5	LOS A	5.1	36.0	0.31	0.27	54.9
Approach		465	2.0	0.230	3.4	LOS A	5.1	36.0	0.28	0.24	56.5
East: DNSDC Access (W)											
4	L2	4	0.0	0.050	62.6	LOS E	0.2	1.6	0.98	0.64	29.2
6	R2	24	8.7	0.193	60.0	LOS E	1.3	9.7	0.97	0.71	28.1
Approach		28	7.4	0.193	60.3	LOS E	1.3	9.7	0.97	0.70	28.2
North: Moorebank Avenue (N)											
7	L2	6	16.7	0.004	6.1	LOS A	0.0	0.2	0.11	0.59	51.9
8	T1	1788	2.2	1.141	170.3	LOS F	221.6	1580.2	1.00	1.91	14.6
Approach		1795	2.2	1.141	169.7	LOS F	221.6	1580.2	1.00	1.91	14.6
West: Carpark Access (W)											
10	L2	6	0.0	0.047	56.7	LOS E	0.3	2.3	0.95	0.65	19.4
12	R2	3	0.0	0.036	60.5	LOS E	0.2	1.2	0.98	0.62	21.0
Approach		9	0.0	0.047	57.9	LOS E	0.3	2.3	0.96	0.64	20.0
All Vehicles		2298	2.2	1.141	134.2	LOS F	221.6	1580.2	0.85	1.55	17.4

PHASING SUMMARY



Site: I-04 2028 DN BASE PM


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2028 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	96
Green Time (sec)	90	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	96	14
Phase Split	87 %	13 %



I-05 Intersection of Moorebank Avenue and Chatham Avenue

MOVEMENT SUMMARY



Site: I-05 2028 DN BASE AM

Intersection of Moorebank Avenue and Chatham Avenue

2028 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Prop. Queued	Effective Stop Rate	Average Speed		
		veh/h	%	v/c	sec	veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	48	0.0	0.031	7.1	LOS A	0.4	3.0	0.18	0.61	51.7
2	T1	1599	2.5	1.211	238.4	LOS F	228.1	1630.7	1.00	2.23	12.2
Approach		1647	2.4	1.211	231.6	LOS F	228.1	1630.7	0.98	2.18	12.4
North: Moorebank Avenue (N)											
8	T1	499	4.6	0.386	2.6	LOS A	6.5	47.0	0.27	0.24	57.5
9	R2	151	0.7	0.872	68.1	LOS E	8.7	61.3	1.00	1.05	26.2
Approach		649	3.7	0.872	17.8	LOS B	8.7	61.3	0.44	0.43	45.8
West: Chatham Avenue (W)											
10	L2	19	5.6	0.186	56.3	LOS D	1.6	12.6	0.95	0.72	29.1
12	R2	13	25.0	0.186	56.5	LOS E	1.6	12.6	0.95	0.72	28.7
Approach		32	13.3	0.186	56.4	LOS D	1.6	12.6	0.95	0.72	29.0
All Vehicles		2328	2.9	1.211	169.6	LOS F	228.1	1630.7	0.83	1.67	15.7

PHASING SUMMARY



Site: I-05 2028 DN BASE AM


Intersection of Moorebank Avenue and Chatham Avenue

2028 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	84	96
Green Time (sec)	78	6	8
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	84	12	14
Phase Split	76 %	11 %	13 %



MOVEMENT SUMMARY



Site: I-05 2028 DN BASE PM

Intersection of Moorebank Avenue and Chatham Avenue

2028 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	12	0.0	0.008	7.2	LOS A	0.1	0.7	0.19	0.60	51.6
2	T1	413	1.8	0.326	7.3	LOS A	8.3	59.0	0.45	0.40	53.5
Approach		424	1.7	0.326	7.3	LOS A	8.3	59.0	0.44	0.40	53.5
North: Moorebank Avenue (N)											
8	T1	1760	2.2	1.194	217.8	LOS F	235.1	1675.9	1.00	2.27	13.1
9	R2	29	0.0	0.044	10.3	LOS A	0.4	3.0	0.38	0.66	48.7
Approach		1789	2.1	1.194	214.4	LOS F	235.1	1675.9	0.99	2.24	13.2
West: Chatham Avenue (W)											
10	L2	45	2.3	0.210	46.7	LOS D	2.5	17.7	0.92	0.75	31.9
12	R2	12	0.0	0.210	46.7	LOS D	2.5	17.7	0.92	0.75	31.8
Approach		57	1.9	0.210	46.7	LOS D	2.5	17.7	0.92	0.75	31.8
All Vehicles		2271	2.0	1.194	171.5	LOS F	235.1	1675.9	0.89	1.86	15.6

PHASING SUMMARY



Site: I-05 2028 DN BASE PM


Intersection of Moorebank Avenue and Chatham Avenue

2028 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	73	85
Green Time (sec)	67	6	9
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	73	12	15
Phase Split	73 %	12 %	15 %



Appendix H

2030 SIDRA results with and
without Moorebank IMT

1. Moorebank Avenue – 2030 Future traffic without Moorebank IMT development (Do-nothing scenario)

I-01 Intersection of Moorebank Avenue and Bapaume Road

MOVEMENT SUMMARY



Site: I-01 2030 DN BASE AM

Intersection of Moorebank Avenue and Bapaume Road
2030 Do-nothing AM PEAK
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	21	0.0	0.011	5.5	LOS A	0.0	0.0	0.00	0.58	45.1
2	T1	1283	5.3	0.680	0.0	LOS A	0.0	0.0	0.00	0.00	59.6
Approach		1304	5.2	0.680	0.1	NA	0.0	0.0	0.00	0.01	59.4
North: Moorebank Avenue (S)											
8	T1	1001	5.5	0.491	2.4	LOS A	3.5	25.4	0.08	0.05	54.8
9	R2	95	1.1	0.491	36.1	LOS C	3.5	25.4	1.00	0.65	30.5
Approach		1096	5.1	0.491	5.3	NA	3.5	25.4	0.16	0.10	50.4
West: Bapaume Road (W)											
10	L2	3	33.3	0.038	47.0	LOS D	0.1	1.0	0.92	0.97	25.5
12	R2	1	0.0	0.243	853.7	LOS F	0.6	4.0	1.00	1.00	1.5
Approach		4	25.0	0.243	248.6	LOS F	0.6	4.0	0.94	0.98	7.0
All Vehicles		2404	5.2	0.680	2.9	NA	3.5	25.4	0.07	0.05	54.1

MOVEMENT SUMMARY



Site: I-01 2030 DN BASE PM

Intersection of Moorebank Avenue and Bapaume Road
2030 Do-nothing PM PEAK
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.001	5.5	LOS A	0.0	0.0	0.00	0.58	45.1
2	T1	674	4.5	0.356	0.0	LOS A	0.0	0.0	0.00	0.00	59.9
Approach		675	4.5	0.356	0.0	NA	0.0	0.0	0.00	0.00	59.9
North: Moorebank Avenue (S)											
8	T1	1638	2.8	0.445	4.5	LOS A	9.4	67.7	0.48	0.01	51.6
9	R2	21	10.0	0.445	14.9	LOS B	9.4	67.7	1.00	0.03	44.6
Approach		1659	2.9	0.445	4.6	NA	9.4	67.7	0.49	0.01	51.4
West: Bapaume Road (W)											
10	L2	104	3.0	0.199	11.2	LOS A	0.8	5.5	0.61	0.84	44.3
12	R2	15	0.0	1.000	553.3	LOS F	3.5	24.4	1.00	1.14	2.3
Approach		119	2.7	1.000	78.4	LOS F	3.5	24.4	0.66	0.87	18.2
All Vehicles		2453	3.3	1.000	6.9	NA	9.4	67.7	0.36	0.05	48.0

I-02 Intersection of Moorebank Avenue and Anzac Road

MOVEMENT SUMMARY



Site: I-02 2030 DN BASE AM

Intersection of Moorebank Avenue and Anzac Road

2030 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay v/c	Level of Service sec	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate per veh	Average Speed km/h		
South: Moorebank Avenue (S)											
2	T1	1101	3.4	1.044	107.2	LOS F	104.4	752.0	1.00	1.53	15.4
3	R2	473	3.1	0.773	36.9	LOS C	19.6	140.6	0.96	1.00	36.7
Approach		1574	3.3	1.044	86.1	LOS F	104.4	752.0	0.99	1.37	20.3
East: Anzac Road (E)											
4	L2	258	3.3	0.311	24.5	LOS B	8.1	58.6	0.67	0.76	41.9
6	R2	227	13.4	0.864	61.5	LOS E	12.9	100.8	1.00	0.97	19.6
Approach		485	8.0	0.864	41.9	LOS C	12.9	100.8	0.83	0.86	30.0
North: Moorebank Avenue (N)											
7	L2	383	9.9	0.250	6.1	LOS A	1.4	10.9	0.16	0.59	49.8
8	T1	644	3.3	0.595	23.1	LOS B	18.7	134.4	0.78	0.68	36.9
Approach		1027	5.7	0.595	16.8	LOS B	18.7	134.4	0.55	0.65	40.9
All Vehicles		3086	4.9	1.044	56.1	LOS D	104.4	752.0	0.82	1.05	25.5

PHASING SUMMARY



Site: I-02 2030 DN BASE AM


Intersection of Moorebank Avenue and Anzac Road

2030 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 103 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	50	78
Green Time (sec)	44	22	19
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	50	28	25
Phase Split	49 %	27 %	24 %



MOVEMENT SUMMARY



Site: I-02 2030 DN BASE PM

Intersection of Moorebank Avenue and Anzac Road

2030 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
2	T1	323	3.9	0.271	9.7	LOS A	7.6	55.3	0.48	0.42	47.5
3	R2	208	1.0	1.210	231.3	LOS F	26.9	189.8	1.00	1.38	12.4
Approach		532	2.8	1.210	96.6	LOS F	26.9	189.8	0.68	0.79	19.4
East: Anzac Road (E)											
4	L2	578	2.2	0.848	46.1	LOS D	31.5	224.9	0.99	0.94	33.6
6	R2	391	5.4	0.924	69.1	LOS E	25.7	188.0	1.00	1.02	18.4
Approach		968	3.5	0.924	55.3	LOS D	31.5	224.9	0.99	0.97	27.1
North: Moorebank Avenue (N)											
7	L2	359	3.8	0.223	6.1	LOS A	1.3	9.5	0.15	0.59	50.2
8	T1	1307	2.4	0.997	61.7	LOS E	80.8	577.3	0.91	1.11	22.5
Approach		1666	2.7	0.997	49.8	LOS D	80.8	577.3	0.74	1.00	25.5
All Vehicles		3166	3.0	1.210	59.3	LOS E	80.8	577.3	0.81	0.96	24.6

PHASING SUMMARY



Site: I-02 2030 DN BASE PM


Intersection of Moorebank Avenue and Anzac Road

2030 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	63	75
Green Time (sec)	57	6	29
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	63	12	35
Phase Split	57 %	11 %	32 %



I-03 Intersection of Moorebank Avenue and Defence Support Access

MOVEMENT SUMMARY



Site: I-03 2030 DN BASE AM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2030 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	18	0.0	0.011	6.0	LOS A	0.1	0.4	0.14	0.60	46.8
2	T1	1551	3.1	1.050	95.2	LOS F	135.3	971.6	1.00	1.60	21.9
Approach		1568	3.0	1.050	94.2	LOS F	135.3	971.6	0.99	1.59	21.9
North: Moorebank Avenue (N)											
8	T1	835	3.7	0.837	19.4	LOS B	23.1	166.3	0.65	0.65	44.2
9	R2	20	0.0	0.837	33.3	LOS C	23.1	166.3	0.84	0.86	24.0
Approach		855	3.6	0.837	19.7	LOS B	23.1	166.3	0.66	0.66	43.6
West: Military Access 1 (W)											
10	L2	2	0.0	0.023	48.3	LOS D	0.1	0.9	0.94	0.63	25.5
12	R2	1	0.0	0.023	48.2	LOS D	0.1	0.9	0.94	0.63	22.8
Approach		3	0.0	0.023	48.3	LOS D	0.1	0.9	0.94	0.63	24.6
All Vehicles		2426	3.2	1.050	67.9	LOS E	135.3	971.6	0.87	1.26	26.6

PHASING SUMMARY



Site: I-03 2030 DN BASE AM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2030 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	76
Green Time (sec)	70	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	76	14
Phase Split	84 %	16 %



MOVEMENT SUMMARY



Site: I-03 2030 DN BASE PM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2030 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.001	6.0	LOS A	0.0	0.14	0.58	46.8
2	T1	506	2.5	0.339	3.2	LOS A	6.6	0.33	0.29	56.7
Approach		507	2.5	0.339	3.2	LOS A	6.6	0.32	0.29	56.7
North: Moorebank Avenue (N)										
8	T1	1844	2.5	1.177	162.4	LOS F	180.6	0.85	1.88	15.1
9	R2	1	0.0	1.177	211.7	LOS F	180.6	1.00	2.33	8.1
Approach		1845	2.5	1.177	162.4	LOS F	180.6	0.85	1.88	15.1
West: Military Access 1 (W)										
10	L2	12	0.0	0.117	49.4	LOS D	0.7	0.96	0.69	25.2
12	R2	4	0.0	0.117	49.4	LOS D	0.7	0.96	0.69	22.5
Approach		16	0.0	0.117	49.4	LOS D	0.7	0.96	0.69	24.5
All Vehicles		2368	2.5	1.177	127.5	LOS F	180.6	0.74	1.53	18.0

PHASING SUMMARY



Site: I-03 2030 DN BASE PM

Intersection of Moorebank Avenue and Defence Support Access (Military Access 1)

2030 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	76
Green Time (sec)	70	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	76	14
Phase Split	84 %	16 %



I-04 Intersection of Moorebank Avenue and DNSDC Access

MOVEMENT SUMMARY



Site: I-04 2030 DN BASE AM

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2030 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay v/c	Level of Service sec	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate per veh	Average Speed km/h		
South: Moorebank Avenue (S)											
2	T1	1607	2.6	1.014	54.6	LOS D	83.8	599.8	0.80	1.14	30.0
3	R2	25	0.0	1.014	84.3	LOS F	83.8	599.8	1.00	1.52	25.8
Approach		1633	2.6	1.014	55.0	LOS D	83.8	599.8	0.80	1.14	29.9
East: DNSDC Access (W)											
4	L2	5	20.0	0.043	44.8	LOS D	0.2	1.7	0.95	0.65	33.8
6	R2	7	14.3	0.042	42.0	LOS C	0.3	2.1	0.93	0.66	33.0
Approach		13	16.7	0.043	43.2	LOS D	0.3	2.1	0.94	0.65	33.4
North: Moorebank Avenue (N)											
7	L2	118	6.3	0.078	6.1	LOS A	0.4	2.9	0.17	0.61	52.1
8	T1	685	3.4	0.479	4.2	LOS A	10.3	74.3	0.42	0.38	55.8
Approach		803	3.8	0.479	4.4	LOS A	10.3	74.3	0.38	0.42	55.2
West: Carpark Access (W)											
10	L2	1	0.0	0.006	39.4	LOS C	0.0	0.3	0.92	0.59	24.3
12	R2	1	0.0	0.007	41.7	LOS C	0.0	0.3	0.94	0.59	26.0
Approach		2	0.0	0.007	40.5	LOS C	0.0	0.3	0.93	0.59	25.2
All Vehicles		2451	3.0	1.014	38.4	LOS C	83.8	599.8	0.66	0.90	35.2

PHASING SUMMARY



Site: I-04 2030 DN BASE AM


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2030 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 80 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	66
Green Time (sec)	60	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	66	14
Phase Split	83 %	18 %



MOVEMENT SUMMARY



Site: I-04 2030 DN BASE PM

Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2030 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
2	T1	468	2.0	0.232	3.4	LOS A	5.1	36.4	0.28	0.24	56.5
3	R2	1	0.0	0.232	9.5	LOS A	5.1	36.4	0.31	0.27	54.9
Approach		469	2.0	0.232	3.4	LOS A	5.1	36.4	0.28	0.24	56.5
East: DNSDC Access (W)											
4	L2	4	0.0	0.050	62.6	LOS E	0.2	1.6	0.98	0.64	29.2
6	R2	24	8.7	0.193	60.0	LOS E	1.3	9.7	0.97	0.71	28.1
Approach		28	7.4	0.193	60.3	LOS E	1.3	9.7	0.97	0.70	28.2
North: Moorebank Avenue (N)											
7	L2	6	16.7	0.004	6.1	LOS A	0.0	0.2	0.11	0.59	51.9
8	T1	1809	2.2	1.154	181.8	LOS F	231.0	1647.0	1.00	1.97	13.9
Approach		1816	2.2	1.154	181.2	LOS F	231.0	1647.0	1.00	1.97	13.9
West: Carpark Access (W)											
10	L2	6	0.0	0.047	56.7	LOS E	0.3	2.3	0.95	0.65	19.4
12	R2	3	0.0	0.036	60.5	LOS E	0.2	1.2	0.98	0.62	21.0
Approach		9	0.0	0.047	57.9	LOS E	0.3	2.3	0.96	0.64	20.0
All Vehicles		2323	2.2	1.154	143.3	LOS F	231.0	1647.0	0.85	1.60	16.6

PHASING SUMMARY



Site: I-04 2030 DN BASE PM


Intersection of Moorebank Avenue and DNSDC Access (Military Access 2)

2030 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	96
Green Time (sec)	90	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	96	14
Phase Split	87 %	13 %



I-05 Intersection of Moorebank Avenue and Chatham Avenue

MOVEMENT SUMMARY



Site: I-05 2030 DN BASE AM

Intersection of Moorebank Avenue and Chatham Avenue

2030 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	49	0.0	0.032	7.1	LOS A	0.4	3.0	0.18	0.61	51.7
2	T1	1615	2.5	1.223	249.2	LOS F	235.4	1682.6	1.00	2.28	11.7
Approach		1664	2.4	1.223	242.0	LOS F	235.4	1682.6	0.98	2.23	12.0
North: Moorebank Avenue (N)											
8	T1	506	4.6	0.392	2.6	LOS A	6.6	47.9	0.27	0.24	57.5
9	R2	154	0.7	0.890	69.8	LOS E	9.0	63.5	1.00	1.07	25.8
Approach		660	3.7	0.890	18.3	LOS B	9.0	63.5	0.44	0.43	45.5
West: Chatham Avenue (W)											
10	L2	19	5.6	0.186	56.3	LOS D	1.6	12.6	0.95	0.72	29.1
12	R2	13	25.0	0.186	56.5	LOS E	1.6	12.6	0.95	0.72	28.7
Approach		32	13.3	0.186	56.4	LOS D	1.6	12.6	0.95	0.72	29.0
All Vehicles		2356	2.9	1.223	176.8	LOS F	235.4	1682.6	0.82	1.70	15.2

PHASING SUMMARY



Site: I-05 2030 DN BASE AM


Intersection of Moorebank Avenue and Chatham Avenue

2030 Do-nothing AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	84	96
Green Time (sec)	78	6	8
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	84	12	14
Phase Split	76 %	11 %	13 %



MOVEMENT SUMMARY



Site: I-05 2030 DN BASE PM

Intersection of Moorebank Avenue and Chatham Avenue

2030 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	12	0.0	0.008	7.2	LOS A	0.1	0.7	0.19	51.6
2	T1	417	1.8	0.329	7.3	LOS A	8.4	59.8	0.45	53.5
Approach		428	1.7	0.329	7.3	LOS A	8.4	59.8	0.44	53.5
North: Moorebank Avenue (N)										
8	T1	1781	2.1	1.209	230.6	LOS F	244.7	1744.1	1.00	12.5
9	R2	31	0.0	0.045	10.6	LOS A	0.5	3.2	0.39	48.4
Approach		1812	2.1	1.209	226.9	LOS F	244.7	1744.1	0.99	12.6
West: Chatham Avenue (W)										
10	L2	46	2.3	0.213	46.7	LOS D	2.5	18.1	0.92	31.9
12	R2	12	0.0	0.213	46.7	LOS D	2.5	18.1	0.92	31.8
Approach		58	1.8	0.213	46.7	LOS D	2.5	18.1	0.92	31.8
All Vehicles		2298	2.0	1.209	181.5	LOS F	244.7	1744.1	0.89	15.0

PHASING SUMMARY



Site: I-05 2030 DN BASE PM


Intersection of Moorebank Avenue and Chatham Avenue

2030 Do-nothing PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	73	85
Green Time (sec)	67	6	9
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	73	12	15
Phase Split	73 %	12 %	15 %



2. Moorebank Avenue – 2030 Future traffic with Moorebank IMT development (Full Build)

I-01 Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

MOVEMENT SUMMARY



Site: I-01 2030 FU MINT AM

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	37	0.0	30.0	LOS C	25.1	199.6	0.82	0.78	35.1
2	T1	1255	16.7	22.4	LOS B	25.1	199.6	0.82	0.77	35.3
3	R2	473	3.1	30.0	LOS C	14.2	102.1	0.93	0.94	32.8
Approach		1764	12.7	24.6	LOS B	25.1	199.8	0.85	0.82	34.6
East: Anzac Road (E)										
4	L2	217	3.9	33.6	LOS C	8.2	58.9	0.78	0.80	31.2
5	T1	9	0.0	26.6	LOS B	8.2	58.9	0.78	0.80	31.2
6	R2	224	13.6	58.2	LOS E	11.9	92.9	1.00	0.94	23.1
Approach		451	8.6	45.7	LOS D	11.9	92.9	0.89	0.87	26.6
North: Moorebank Avenue (N)										
7	L2	383	9.9	7.6	LOS A	0.0	0.0	0.00	0.57	48.5
8	T1	691	27.1	16.3	LOS B	9.0	77.7	0.57	0.50	38.0
9	R2	142	5.2	22.7	LOS B	3.4	25.2	0.84	0.79	33.6
Approach		1216	19.1	14.3	LOS A	9.0	77.7	0.42	0.55	40.2
West: Bapaume Road (W)										
10	L2	9	77.8	15.3	LOS B	0.2	2.0	0.55	0.57	33.7
11	T1	1	0.0	41.1	LOS C	0.1	0.6	0.89	0.60	19.5
12	R2	1	0.0	48.3	LOS D	0.1	0.6	0.89	0.60	19.5
Approach		12	63.6	20.7	LOS B	0.2	2.0	0.61	0.57	29.8
All Vehicles		3442	14.6	23.7	LOS B	25.1	199.8	0.70	0.73	34.7

PHASING SUMMARY



Site: I-01 2030 FU MINT AM


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	52	78
Green Time (sec)	46	20	16
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	52	26	22
Phase Split	52 %	26 %	22 %



MOVEMENT SUMMARY



Site: I-01 2030 FU MINT PM

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 120 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.254	LOS A	2.9	26.7	0.21	0.19	51.8
2	T1	506	36.4	5.0	LOS A	2.9	26.7	0.21	0.19	51.8
3	R2	211	1.0	0.956	LOS F	17.1	120.5	1.00	1.25	15.6
Approach		718	26.0	0.956	LOS C	17.1	120.5	0.44	0.50	30.8
East: Anzac Road (E)										
4	L2	568	2.2	0.814	LOS D	31.4	224.0	0.96	0.91	26.1
5	T1	1	0.0	0.814	LOS C	31.4	224.0	0.96	0.91	26.1
6	R2	391	5.4	0.973	LOS F	31.4	230.0	1.00	1.10	16.9
Approach		960	3.5	0.973	LOS E	31.4	230.0	0.98	0.99	21.3
North: Moorebank Avenue (N)										
7	L2	353	3.9	0.195	LOS A	0.0	0.0	0.00	0.59	48.5
8	T1	1436	14.2	0.896	LOS C	39.7	311.9	0.74	0.77	29.7
9	R2	27	30.8	0.084	LOS B	0.9	7.6	0.56	0.68	32.2
Approach		1816	12.5	0.896	LOS B	39.7	311.9	0.59	0.73	32.2
West: Bapaume Road (W)										
10	L2	152	6.3	0.237	LOS A	2.9	21.3	0.41	0.67	35.6
11	T1	13	0.0	0.278	LOS D	2.2	15.7	0.95	0.74	16.4
12	R2	27	0.0	0.278	LOS E	2.2	15.7	0.95	0.74	16.4
Approach		192	4.9	0.278	LOS B	2.9	21.3	0.52	0.68	28.6
All Vehicles		3685	12.4	0.973	LOS C	39.7	311.9	0.66	0.75	27.8

PHASING SUMMARY



Site: I-01 2030 FU MINT PM


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 120 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	68	82
Green Time (sec)	62	8	32
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	68	14	38
Phase Split	57 %	12 %	32 %



I-02 Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

MOVEMENT SUMMARY

 **Site: I-02 2030 FU MINT AM**

Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2030 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.735	10.4	LOS A	14.4	111.5	0.37	0.34	44.7
2	T1	1743	12.0	0.735	4.8	LOS A	14.4	111.5	0.37	0.34	52.1
3	R2	25	0.0	0.227	56.9	LOS E	1.3	8.8	0.98	0.71	12.3
Approach		1769	11.8	0.735	5.6	LOS A	14.4	111.5	0.37	0.34	50.6
East: DNSDC Access (E)											
4	L2	5	20.0	0.092	52.6	LOS D	0.6	4.7	0.95	0.69	15.7
6	R2	7	14.3	0.092	52.6	LOS D	0.6	4.7	0.95	0.69	18.7
Approach		13	16.7	0.092	52.6	LOS D	0.6	4.7	0.95	0.69	17.5
North: Moorebank Avenue (N)											
7	L2	118	6.3	0.398	13.9	LOS A	9.9	80.0	0.50	0.52	29.2
8	T1	774	22.6	0.398	8.3	LOS A	9.9	82.8	0.50	0.47	46.7
9	R2	16	86.7	0.229	59.8	LOS E	0.8	9.9	0.98	0.70	16.5
Approach		907	21.6	0.398	10.0	LOS A	9.9	82.8	0.50	0.48	42.9
West: Warehouse Access 1 (W)											
10	L2	15	92.9	0.082	43.4	LOS D	0.7	8.1	0.86	0.69	19.8
12	R2	1	0.0	0.082	42.5	LOS D	0.7	8.1	0.86	0.69	18.4
Approach		16	86.7	0.082	43.3	LOS D	0.7	8.1	0.86	0.69	19.7
All Vehicles		2705	15.6	0.735	7.5	LOS A	14.4	111.5	0.42	0.39	47.2

PHASING SUMMARY

 **Site: I-02 2030 FU MINT AM**


Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2030 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



MOVEMENT SUMMARY



Site: I-02 2030 FU MINT PM

Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2030 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.306	8.7	LOS A	2.7	23.0	0.18	0.16	47.7
2	T1	677	25.2	0.306	3.1	LOS A	2.7	23.0	0.18	0.16	54.6
3	R2	1	0.0	0.010	19.2	LOS B	0.0	0.2	0.51	0.63	20.0
Approach		679	25.1	0.306	3.2	LOS A	2.7	23.0	0.18	0.16	54.5
East: DNSDC Access (E)											
4	L2	4	0.0	0.232	55.8	LOS D	1.4	10.4	0.98	0.72	15.6
6	R2	24	8.7	0.232	55.8	LOS D	1.4	10.4	0.98	0.72	18.1
Approach		28	7.4	0.232	55.8	LOS D	1.4	10.4	0.98	0.72	17.7
North: Moorebank Avenue (N)											
7	L2	6	16.7	0.714	11.5	LOS A	24.3	184.6	0.54	0.51	31.5
8	T1	2012	10.0	0.714	5.7	LOS A	24.3	184.6	0.53	0.50	50.8
9	R2	15	92.9	0.220	59.9	LOS E	0.8	9.5	0.98	0.70	16.4
Approach		2033	10.7	0.714	6.1	LOS A	24.3	184.6	0.54	0.50	50.2
West: Warehouse Access 1 (W)											
10	L2	16	86.7	0.084	43.3	LOS D	0.7	8.4	0.86	0.70	19.9
12	R2	1	0.0	0.084	42.5	LOS D	0.7	8.4	0.86	0.70	18.4
Approach		17	81.3	0.084	43.2	LOS D	0.7	8.4	0.86	0.70	19.8
All Vehicles		2757	14.6	0.714	6.1	LOS A	24.3	184.6	0.46	0.42	50.1

PHASING SUMMARY



Site: I-02 2030 FU MINT PM


Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2030 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



I-03 Intersection of Moorebank Avenue and Warehouse Access 2

MOVEMENT SUMMARY



Site: I-03 2030 FU MINT AM

Intersection of Moorebank Avenue and Warehouse Access 2

2030 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h	
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.774	20.7	LOS B	27.9	213.7	0.79	0.73	42.8
2	T1	1753	11.0	0.774	13.3	LOS A	27.9	213.7	0.79	0.73	42.8
Approach		1754	11.0	0.774	13.3	LOS A	27.9	213.7	0.79	0.73	42.8
North: Moorebank Avenue (N)											
8	T1	759	20.9	0.293	0.9	LOS A	1.1	9.4	0.07	0.07	56.7
9	R2	20	84.2	0.130	20.9	LOS B	0.4	5.3	0.72	0.67	27.1
Approach		779	22.6	0.293	1.4	LOS A	1.1	9.4	0.09	0.08	55.3
West: Warehouse Access 2 (W)											
10	L2	18	94.1	0.082	38.8	LOS C	0.7	8.5	0.83	0.67	14.0
12	R2	1	0.0	0.082	39.0	LOS C	0.7	8.5	0.83	0.67	14.0
Approach		19	88.9	0.082	38.9	LOS C	0.7	8.5	0.83	0.67	14.0
All Vehicles		2552	15.1	0.774	9.8	LOS A	27.9	213.7	0.58	0.53	44.3

PHASING SUMMARY



Site: I-03 2030 FU MINT AM


Intersection of Moorebank Avenue and Warehouse Access 2

2030 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



MOVEMENT SUMMARY



Site: I-03 2030 FU MINT PM

Intersection of Moorebank Avenue and Warehouse Access 2

2030 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.312	LOS B	6.7	56.4	0.50	0.44	47.7
2	T1	657	23.4	0.312	LOS A	6.7	56.4	0.50	0.44	47.7
Approach		658	23.4	0.312	LOS A	6.7	56.4	0.50	0.44	47.7
North: Moorebank Avenue (N)										
8	T1	2000	9.3	0.720	LOS A	6.9	51.8	0.17	0.16	54.2
9	R2	18	94.1	0.059	LOS A	0.2	2.7	0.43	0.56	34.8
Approach		2018	10.0	0.720	LOS A	6.9	51.8	0.17	0.16	54.0
West: Warehouse Access 2 (W)										
10	L2	20	84.2	0.087	LOS C	0.8	9.0	0.83	0.68	14.0
12	R2	1	0.0	0.087	LOS C	0.8	9.0	0.83	0.68	14.0
Approach		21	80.0	0.087	LOS C	0.8	9.0	0.83	0.68	14.0
All Vehicles		2697	13.8	0.720	LOS A	6.9	56.4	0.26	0.23	50.8

PHASING SUMMARY



Site: I-03 2030 FU MINT PM


Intersection of Moorebank Avenue and Warehouse Access 2

2030 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



I-04 Intersection of Moorebank Avenue and Warehouse Access 3

MOVEMENT SUMMARY



Site: I-04 2030 FU MINT AM

Intersection of Moorebank Avenue and Warehouse Access 3

2030 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Prop. Queued	Effective Stop Rate	Average Speed		
		veh/h	%	sec		veh	Distance m	per veh	km/h		
South: Moorebank Avenue (S)											
1	L2	2	0.0	0.756	20.4	LOS B	26.9	203.7	0.77	0.71	41.9
2	T1	1726	9.5	0.756	13.0	LOS A	26.9	203.7	0.77	0.71	41.9
Approach		1728	9.5	0.756	13.0	LOS A	26.9	203.7	0.77	0.71	41.9
North: Moorebank Avenue (N)											
8	T1	725	18.0	0.275	3.6	LOS A	4.8	39.1	0.33	0.29	53.6
9	R2	34	84.4	0.217	21.1	LOS B	0.8	9.3	0.74	0.70	38.2
Approach		759	20.9	0.275	4.4	LOS A	4.8	39.1	0.35	0.31	52.7
West: Warehouse Access 3 (W)											
10	L2	29	96.4	0.130	38.5	LOS C	1.1	14.0	0.83	0.69	14.1
12	R2	1	0.0	0.130	38.6	LOS C	1.1	14.0	0.83	0.69	14.1
Approach		31	93.1	0.130	38.5	LOS C	1.1	14.0	0.83	0.69	14.1
All Vehicles		2518	14.0	0.756	10.7	LOS A	26.9	203.7	0.65	0.59	44.5

PHASING SUMMARY



Site: I-04 2030 FU MINT AM


Intersection of Moorebank Avenue and Warehouse Access 3

2030 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



MOVEMENT SUMMARY



Site: I-04 2030 FU MINT PM

Intersection of Moorebank Avenue and Warehouse Access 3

2030 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.302	LOS B	6.6	54.4	0.52	0.45	45.8
2	T1	623	20.1	0.302	LOS A	6.6	54.4	0.52	0.45	45.8
Approach		624	20.1	0.302	LOS A	6.6	54.4	0.52	0.45	45.8
North: Moorebank Avenue (N)										
8	T1	1974	7.9	0.721	LOS A	23.5	176.0	0.57	0.53	49.8
9	R2	29	96.4	0.089	LOS A	0.4	4.5	0.42	0.57	45.1
Approach		2003	9.2	0.721	LOS A	23.5	176.0	0.57	0.53	49.8
West: Warehouse Access 3 (W)										
10	L2	34	84.4	0.138	LOS C	1.3	15.3	0.84	0.70	14.1
12	R2	2	0.0	0.138	LOS C	1.3	15.3	0.84	0.70	14.1
Approach		36	79.4	0.138	LOS C	1.3	15.3	0.84	0.70	14.1
All Vehicles		2663	12.7	0.721	LOS A	23.5	176.0	0.56	0.51	48.3

PHASING SUMMARY



Site: I-04 2030 FU MINT PM


Intersection of Moorebank Avenue and Warehouse Access 3

2030 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	60	76
Green Time (sec)	54	10	8
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	60	16	14
Phase Split	67 %	18 %	16 %



I-05 Intersection of Moorebank Avenue and Main Access

MOVEMENT SUMMARY



Site: I-05 2030 FU MINT AM

Intersection of Moorebank Avenue and Main Access

2030 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed
		veh/h	%	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.747	23.1	LOS B	26.5	190.8	0.81	39.7
2	T1	1616	3.2	0.747	15.7	LOS B	26.5	190.8	0.81	39.7
Approach		1617	3.2	0.747	15.7	LOS B	26.5	190.8	0.81	39.7
North: Moorebank Avenue (N)										
8	T1	609	2.9	0.249	4.7	LOS A	5.1	36.9	0.37	52.1
9	R2	116	97.3	0.723	31.9	LOS C	4.3	54.7	1.00	32.4
Approach		725	18.0	0.723	9.1	LOS A	5.1	54.7	0.47	47.7
West: Main Access (W)										
10	L2	114	99.1	0.192	34.7	LOS C	2.0	25.9	0.80	15.2
12	R2	1	0.0	0.192	34.8	LOS C	2.0	25.2	0.80	15.2
Approach		115	98.2	0.192	34.7	LOS C	2.0	25.9	0.80	15.2
All Vehicles		2457	12.0	0.747	14.6	LOS B	26.5	190.8	0.71	40.9

PHASING SUMMARY



Site: I-05 2030 FU MINT AM


Intersection of Moorebank Avenue and Main Access

2030 Future with MINT AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	57	77
Green Time (sec)	51	14	7
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	57	20	13
Phase Split	63 %	22 %	14 %



MOVEMENT SUMMARY



Site: I-05 2030 FU MINT PM

Intersection of Moorebank Avenue and Main Access

2030 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles veh	Distance m			
		veh/h	%								
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.373	30.7	LOS C	8.3	59.4	0.79	0.67	35.0
2	T1	507	2.5	0.373	23.2	LOS B	8.3	59.5	0.79	0.67	35.0
Approach		508	2.5	0.373	23.3	LOS B	8.3	59.5	0.79	0.67	35.0
North: Moorebank Avenue (N)											
8	T1	1863	2.4	0.820	8.9	LOS A	26.6	189.7	0.61	0.58	47.0
9	R2	114	99.1	0.238	13.7	LOS A	1.7	21.6	0.54	0.64	43.6
Approach		1977	7.9	0.820	9.2	LOS A	26.6	189.7	0.61	0.58	46.8
West: Main Access (W)											
10	L2	116	97.3	0.113	21.5	LOS B	1.4	18.5	0.58	0.62	20.9
12	R2	1	0.0	0.113	22.6	LOS B	1.4	18.2	0.60	0.63	20.3
Approach		117	96.4	0.113	21.5	LOS B	1.4	18.5	0.58	0.62	20.9
All Vehicles		2602	10.8	0.820	12.5	LOS A	26.6	189.7	0.64	0.60	43.2

PHASING SUMMARY



Site: I-05 2030 FU MINT PM


Intersection of Moorebank Avenue and Main Access

2030 Future with MINT PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	38	58
Green Time (sec)	32	14	26
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	38	20	32
Phase Split	42 %	22 %	36 %



3. On the wider road network – 2030 Future traffic without Moorebank IMT development (Do-nothing scenario)

I-01 Intersection of the Hume Highway and Orange Grove Road

MOVEMENT SUMMARY



Site: I-01 2030 BASE AM

Hume Highway / Orange Grove Road

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
NorthEast: Hume Highway (NE)											
25	T1	953	11.3	0.683	24.2	LOS B	19.5	150.0	0.84	0.76	35.9
26	R2	389	10.0	0.907	86.6	LOS F	17.0	128.8	1.00	0.94	23.8
Approach		1342	10.9	0.907	42.3	LOS C	19.5	150.0	0.89	0.82	30.0
NorthWest: Orange Grove Road (NW)											
27	L2	603	6.6	0.715	18.9	LOS B	19.6	145.2	0.54	0.81	44.7
29	R2	1312	6.6	0.940	75.3	LOS F	38.2	282.7	1.00	0.94	23.0
Approach		1915	6.6	0.940	57.6	LOS E	38.2	282.7	0.86	0.90	27.7
SouthWest: Hume Highway (SW)											
30	L2	1252	6.5	0.441	11.5	LOS A	13.8	101.7	0.34	0.70	52.2
31	T1	2187	5.0	0.806	22.9	LOS B	39.5	288.4	0.71	0.65	40.1
Approach		3439	5.5	0.806	18.7	LOS B	39.5	288.4	0.57	0.67	44.6
All Vehicles		6696	6.9	0.940	34.6	LOS C	39.5	288.4	0.72	0.76	34.4

PHASING SUMMARY



Site: I-01 2030 BASE AM


Hume Highway / Orange Grove Road

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	84	108
Green Time (sec)	77	17	36
Yellow Time (sec)	5	4	5
All-Red Time (sec)	2	2	2
Phase Time (sec)	84	23	43
Phase Split	56 %	15 %	29 %



MOVEMENT SUMMARY



Site: I-01 2030 BASE PM

Hume Highway / Orange Grove Road

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles veh	Distance m			
		veh/h	%								
NorthEast: Hume Highway (NE)											
25	T1	1762	3.3	0.918	44.0	LOS D	49.8	358.6	0.91	0.97	27.0
26	R2	816	2.8	0.958	68.1	LOS E	24.7	176.9	1.00	1.04	27.6
Approach		2578	3.1	0.958	51.6	LOS D	49.8	358.6	0.94	0.99	27.2
NorthWest: Orange Grove Road (NW)											
27	L2	391	4.3	0.365	12.4	LOS A	6.7	48.6	0.27	0.64	49.3
29	R2	1358	3.1	1.040	119.8	LOS F	51.7	371.7	1.00	1.10	17.0
Approach		1748	3.4	1.040	95.8	LOS F	51.7	371.7	0.84	1.00	20.3
SouthWest: Hume Highway (SW)											
30	L2	1278	3.0	0.745	19.2	LOS B	19.5	139.7	0.77	0.83	46.0
31	T1	1085	5.3	0.975	88.0	LOS F	37.6	275.5	1.00	1.12	18.1
Approach		2363	4.1	0.975	50.8	LOS D	37.6	275.5	0.88	0.97	28.8
All Vehicles		6689	3.5	1.040	62.9	LOS E	51.7	371.7	0.89	0.98	25.2

PHASING SUMMARY



Site: I-01 2030 BASE PM

Hume Highway / Orange Grove Road

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C	D
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	53	80	124
Green Time (sec)	47	20	38	19
Yellow Time (sec)	5	4	5	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	54	26	45	25
Phase Split	36 %	17 %	30 %	17 %



I-02 Intersection of the Hume Highway and Elizabeth Drive

MOVEMENT SUMMARY



Site: I-02 2030 BASE AM

Hume Highway / Elizabeth Drive

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	137	5.4	0.155	22.6	LOS B	3.7	27.3	0.40	0.68	36.5
2	T1	2352	6.3	0.942	57.2	LOS E	64.3	474.4	0.98	1.01	20.6
Approach		2488	6.2	0.962	55.3	LOS D	64.3	474.4	0.95	0.99	21.2
East: Elizabeth Drive (E)											
4	L2	39	5.4	0.427	59.7	LOS E	10.6	77.7	0.92	0.82	18.6
5	T1	503	5.9	0.427	55.9	LOS D	11.9	87.5	0.90	0.83	23.7
6	R2	156	2.7	0.754	78.2	LOS F	11.7	83.5	1.00	0.87	14.8
Approach		698	5.1	0.754	61.1	LOS E	11.9	87.5	0.92	0.84	21.1
North: Hume Highway (N)											
7	L2	82	2.6	0.624	26.2	LOS B	23.1	172.9	0.60	0.57	31.4
8	T1	1715	8.7	0.624	19.6	LOS B	23.1	172.9	0.58	0.53	36.1
9	R2	353	9.6	1.170	248.6	LOS F	25.1	189.8	1.00	1.38	7.6
Approach		2149	8.6	1.170	57.4	LOS E	25.1	189.8	0.65	0.67	20.9
West: Elizabeth Drive (W)											
10	L2	628	5.4	1.014	110.4	LOS F	63.2	462.6	1.00	1.07	14.4
11	T1	1091	3.1	1.052	136.6	LOS F	59.7	429.3	1.00	1.35	11.8
12	R2	512	6.6	1.120	358.8	LOS F	58.3	431.0	1.00	1.57	5.6
Approach		2231	4.5	1.120	180.2	LOS F	63.2	462.6	1.00	1.32	9.7
All Vehicles		7566	6.3	1.170	93.2	LOS F	64.3	474.4	0.88	0.98	15.3

PHASING SUMMARY



Site: I-02 2030 BASE AM


Hume Highway / Elizabeth Drive

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	D	F	A	E
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	66	89	131
Green Time (sec)	60	17	36	13
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	66	23	42	19
Phase Split	44 %	15 %	28 %	13 %



MOVEMENT SUMMARY



Site: I-02 2030 BASE PM

Hume Highway / Elizabeth Drive

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	316	4.3	0.461	39.6	LOS C	14.7	106.7	0.69	0.78	28.5
2	T1	1496	4.9	0.868	56.4	LOS D	36.7	267.7	0.97	0.93	20.8
Approach		1812	4.8	0.868	53.5	LOS D	36.7	267.7	0.92	0.90	22.0
East: Elizabeth Drive (E)											
4	L2	128	0.8	0.985	108.6	LOS F	33.8	240.3	1.00	1.17	12.0
5	T1	1083	2.4	0.985	104.7	LOS F	43.0	307.3	1.00	1.20	15.1
6	R2	172	0.0	1.066	165.1	LOS F	19.6	137.4	1.00	1.29	8.2
Approach		1383	2.0	1.066	112.6	LOS F	43.0	307.3	1.00	1.21	13.7
North: Hume Highway (N)											
7	L2	66	4.8	0.854	22.7	LOS B	39.2	281.8	0.70	0.68	33.9
8	T1	2444	2.9	0.854	16.9	LOS B	39.9	286.3	0.70	0.66	38.3
9	R2	961	3.0	0.917	76.9	LOS F	37.9	271.9	1.00	0.96	19.4
Approach		3472	2.9	0.917	33.6	LOS C	39.9	286.3	0.78	0.75	29.2
West: Elizabeth Drive (W)											
10	L2	327	6.4	0.439	34.2	LOS C	13.8	101.8	0.62	0.76	29.6
11	T1	532	4.8	0.703	61.9	LOS E	17.7	128.9	0.96	0.82	20.9
12	R2	311	2.7	0.983	115.3	LOS F	14.6	104.6	1.00	1.09	14.4
Approach		1169	4.7	0.983	68.3	LOS E	17.7	128.9	0.88	0.87	20.0
All Vehicles		7836	3.5	1.066	57.3	LOS E	43.0	307.3	0.87	0.88	21.6

PHASING SUMMARY



Site: I-02 2030 BASE PM


Hume Highway / Elizabeth Drive

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	D	F	A	E
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	53	72	108
Green Time (sec)	47	13	30	36
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	53	19	36	42
Phase Split	35 %	13 %	24 %	28 %



I-03 Intersection of the Hume Highway and Memorial Avenue

MOVEMENT SUMMARY



Site: I-03 2030 BASE AM

Hume Highway / Memorial Avenue

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	157	1.3	0.955	65.8	LOS E	66.8	491.9	1.00	1.06	27.4
2	T1	2104	7.3	0.955	57.6	LOS E	67.8	504.3	0.93	1.01	25.7
3	R2	267	0.0	1.137	222.0	LOS F	36.2	253.5	1.00	1.30	9.4
Approach		2528	6.1	1.137	75.5	LOS F	67.8	504.3	0.94	1.04	22.0
East: Memorial Avenue (E)											
4	L2	26	20.0	1.170	251.7	LOS F	23.5	175.1	1.00	1.53	8.6
5	T1	160	5.3	1.170	247.0	LOS F	23.5	175.1	1.00	1.53	8.4
6	R2	125	12.6	1.170	251.8	LOS F	21.4	164.2	1.00	1.52	6.0
Approach		312	9.5	1.170	249.3	LOS F	23.5	175.1	1.00	1.52	7.5
North: Hume Highway (N)											
7	L2	121	6.1	0.103	12.4	LOS A	2.6	19.4	0.36	0.64	39.4
8	T1	1715	11.1	0.725	27.9	LOS B	30.5	233.5	0.72	0.65	36.6
9	R2	101	3.1	0.439	72.0	LOS F	7.0	50.1	0.97	0.79	21.4
Approach		1937	10.4	0.725	29.2	LOS C	30.5	233.5	0.71	0.66	35.4
West: Memorial Avenue (W)											
10	L2	128	3.3	1.178	239.1	LOS F	47.3	337.1	1.00	1.56	9.1
11	T1	460	1.6	1.178	242.0	LOS F	58.9	420.6	1.00	1.62	8.5
12	R2	163	3.2	1.178	253.8	LOS F	58.9	420.6	1.00	1.67	10.9
Approach		752	2.2	1.178	244.1	LOS F	58.9	420.6	1.00	1.62	9.2
All Vehicles		5528	7.3	1.178	92.0	LOS F	67.8	504.3	0.87	1.01	19.0

PHASING SUMMARY



Site: I-03 2030 BASE AM


Hume Highway / Memorial Avenue

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	F
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	75	108	125
Green Time (sec)	69	27	11	19
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	75	33	17	25
Phase Split	50 %	22 %	11 %	17 %



MOVEMENT SUMMARY



Site: I-03 2030 BASE PM

Hume Highway / Memorial Avenue

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	119	0.9	0.793	44.9	LOS D	34.3	249.8	0.89	0.83	32.9
2	T1	1604	5.6	0.793	37.1	LOS C	35.2	258.5	0.85	0.77	32.3
3	R2	116	0.0	0.779	84.5	LOS F	8.9	62.5	1.00	0.87	19.4
Approach		1839	5.0	0.793	40.5	LOS C	35.2	258.5	0.86	0.78	31.1
East: Memorial Avenue (E)											
4	L2	55	0.0	1.235	306.0	LOS F	46.8	333.1	1.00	1.84	7.3
5	T1	291	2.5	1.235	301.5	LOS F	46.8	333.1	1.00	1.81	7.1
6	R2	212	6.5	1.235	306.5	LOS F	43.2	316.9	1.00	1.69	5.1
Approach		557	3.8	1.235	303.8	LOS F	46.8	333.1	1.00	1.77	6.4
North: Hume Highway (N)											
7	L2	152	2.8	0.090	8.4	LOS A	2.0	14.7	0.24	0.61	43.5
8	T1	2933	3.0	0.922	17.5	LOS B	58.7	421.7	0.65	0.64	42.8
9	R2	214	2.0	0.729	42.6	LOS D	9.2	65.3	1.00	0.83	28.2
Approach		3298	2.9	0.922	18.7	LOS B	58.7	421.7	0.66	0.65	41.5
West: Memorial Avenue (W)											
10	L2	82	1.3	0.947	94.0	LOS F	17.8	125.8	1.00	1.14	18.3
11	T1	209	1.0	0.947	90.9	LOS F	22.1	155.1	1.00	1.12	17.5
12	R2	171	0.0	0.947	98.0	LOS F	22.1	155.1	1.00	1.09	21.4
Approach		462	0.7	0.947	94.1	LOS F	22.1	155.1	1.00	1.11	19.2
All Vehicles		6156	3.5	1.235	56.7	LOS E	58.7	421.7	0.78	0.83	25.5

PHASING SUMMARY



Site: I-03 2030 BASE PM


Hume Highway / Memorial Avenue

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	D	E	F
Reference Phase	Yes	No	No	No	No
Phase Change Time (sec)	0	67	81	108	132
Green Time (sec)	61	8	21	18	12
Yellow Time (sec)	4	4	4	4	4
All-Red Time (sec)	2	2	2	2	2
Phase Time (sec)	67	14	27	24	18
Phase Split	45 %	9 %	18 %	16 %	12 %



I-04 Intersection of the Hume Highway and Hoxton Park Drive

MOVEMENT SUMMARY



Site: I-04 2030 BASE AM

Hume Highway / Hoxton Park Road / Macquarie Street

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		veh	m		per veh	km/h	
South: Hume Highway (S)											
1	L2	102	7.2	0.085	8.7	LOS A	0.8	6.2	0.12	0.57	50.9
2	T1	2126	5.1	0.822	28.8	LOS C	40.6	296.7	0.80	0.74	39.1
3	R2	1213	1.9	1.079	138.0	LOS F	52.5	373.6	1.00	1.22	13.8
Approach		3441	4.0	1.079	66.7	LOS E	52.5	373.6	0.85	0.90	25.5
East: Macquarie Street (E)											
4	L2	361	5.8	0.230	21.3	LOS B	5.5	40.4	0.66	0.73	39.0
5	T1	545	4.6	1.080	170.2	LOS F	32.6	237.6	1.00	1.38	13.2
Approach		906	5.1	1.080	110.9	LOS F	32.6	237.6	0.86	1.12	17.4
North: Hume Highway (N)											
7	L2	236	15.6	0.965	89.2	LOS F	50.1	384.1	1.00	1.22	20.5
8	T1	1428	8.1	0.965	81.3	LOS F	51.3	384.4	0.98	1.12	23.8
9	R2	247	19.6	1.265	334.8	LOS F	41.9	342.5	1.00	1.61	9.1
Approach		1912	10.5	1.265	115.1	LOS F	51.3	384.4	0.98	1.19	19.0
West: Hoxton Park Road (W)											
10	L2	338	16.2	0.564	46.9	LOS D	19.7	157.1	0.86	0.83	32.6
11	T1	1363	4.2	1.117	216.5	LOS F	66.9	485.3	1.00	1.60	10.9
12	R2	384	3.3	1.096	150.7	LOS F	25.5	183.5	1.00	1.17	16.1
Approach		2085	6.0	1.117	176.9	LOS F	66.9	485.3	0.98	1.40	13.4
All Vehicles		8344	6.1	1.265	110.1	LOS F	66.9	485.3	0.92	1.12	18.8

PHASING SUMMARY



Site: I-04 2030 BASE AM


Hume Highway / Hoxton Park Road / Macquarie Street

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	E	D	F
Reference Phase	Yes	No	No	No	No
Phase Change Time (sec)	0	49	77	100	126
Green Time (sec)	43	22	17	20	18
Yellow Time (sec)	4	4	4	4	4
All-Red Time (sec)	2	2	2	2	2
Phase Time (sec)	49	28	23	26	24
Phase Split	33 %	19 %	15 %	17 %	16 %



MOVEMENT SUMMARY



Site: I-04 2030 BASE PM

Hume Highway / Hoxton Park Road / Macquarie Street

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	196	5.4	0.164	9.5	LOS A	2.0	14.6	0.15	0.59	50.3
2	T1	1549	5.2	0.607	23.6	LOS B	23.3	170.0	0.62	0.55	41.7
3	R2	448	1.2	0.934	95.5	LOS F	19.1	135.2	1.00	1.00	18.1
Approach		2194	4.4	0.934	37.1	LOS C	23.3	170.0	0.65	0.65	34.8
East: Macquarie Street (E)											
4	L2	785	1.5	1.024	163.1	LOS F	39.7	281.3	0.98	1.11	12.1
5	T1	706	3.3	1.087	167.6	LOS F	41.8	300.7	1.00	1.39	13.3
Approach		1492	2.3	1.087	165.2	LOS F	41.8	300.7	0.99	1.24	12.7
North: Hume Highway (N)											
7	L2	101	5.2	0.950	31.1	LOS C	69.1	495.9	0.88	0.92	37.5
8	T1	2813	2.7	0.950	26.1	LOS B	70.9	507.4	0.79	0.82	40.3
9	R2	284	6.7	1.414	467.1	LOS F	57.2	423.6	1.00	1.83	6.8
Approach		3198	3.1	1.414	65.5	LOS E	70.9	507.4	0.81	0.91	27.2
West: Hoxton Park Road (W)											
10	L2	251	3.8	0.392	44.3	LOS D	13.6	98.3	0.80	0.80	33.6
11	T1	714	3.8	0.436	46.6	LOS D	14.1	101.9	0.87	0.73	30.4
12	R2	380	1.7	1.207	217.5	LOS F	31.6	224.2	1.00	1.34	12.2
Approach		1344	3.2	1.207	94.5	LOS F	31.6	224.2	0.89	0.92	21.2
All Vehicles		8227	3.3	1.414	80.7	LOS F	70.9	507.4	0.81	0.90	23.3

PHASING SUMMARY



Site: I-04 2030 BASE PM


Hume Highway / Hoxton Park Road / Macquarie Street

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	E	D	F
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	78	98	127
Green Time (sec)	72	14	23	17
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	78	20	29	23
Phase Split	52 %	13 %	19 %	15 %



I-05 Intersection of the Hume Highway and Reilly Street

MOVEMENT SUMMARY



Site: I-05 2030 BASE AM

Hume Highway / Reilly Street

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %		Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Hume Highway (S)											
1	L2	80	2.6	0.922	27.7	LOS B	64.3	464.0	0.80	0.80	38.2
2	T1	3145	3.6	0.922	21.5	LOS B	64.3	464.0	0.74	0.75	38.5
3	R2	14	7.7	0.099	22.4	LOS B	0.5	3.6	0.48	0.67	37.1
Approach		3239	3.6	0.922	21.6	LOS B	64.3	464.0	0.74	0.75	38.4
East: Congressional Drive (E)											
4	L2	49	2.1	0.263	59.1	LOS E	5.9	42.6	0.89	0.74	24.5
5	T1	46	4.5	0.263	54.5	LOS D	5.9	42.6	0.89	0.74	24.0
6	R2	91	4.7	0.430	67.3	LOS E	6.1	44.6	0.95	0.79	18.7
Approach		186	4.0	0.430	61.9	LOS E	6.1	44.6	0.92	0.76	21.6
North: Hume Highway (N)											
7	L2	32	3.3	0.547	17.8	LOS B	21.3	158.2	0.52	0.56	39.5
8	T1	1809	7.2	0.547	11.0	LOS A	24.5	182.4	0.49	0.48	46.6
9	R2	99	1.1	0.767	58.8	LOS E	6.2	43.8	1.00	0.94	22.9
Approach		1940	6.8	0.767	13.5	LOS A	24.5	182.4	0.52	0.51	44.1
West: Reilly Street (W)											
10	L2	121	4.3	0.277	50.4	LOS D	7.7	56.1	0.83	0.76	24.4
11	T1	14	7.7	0.277	45.8	LOS D	7.7	56.1	0.83	0.76	25.6
12	R2	235	1.8	1.033	151.3	LOS F	26.1	185.6	1.00	1.22	14.4
Approach		369	2.8	1.033	114.3	LOS F	26.1	185.6	0.94	1.05	16.5
All Vehicles		5735	4.7	1.033	26.2	LOS B	64.3	464.0	0.69	0.69	35.5

PHASING SUMMARY



Site: I-05 2030 BASE AM


Hume Highway / Reilly Street

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E2
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	100	138
Green Time (sec)	94	32	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	100	38	12
Phase Split	67 %	25 %	8 %



MOVEMENT SUMMARY



Site: I-05 2030 BASE PM

Hume Highway / Reilly Street

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	223	0.5	0.645	19.5	LOS B	24.9	179.0	0.52	0.56	41.9
2	T1	2007	4.5	0.645	11.4	LOS A	24.9	179.0	0.44	0.43	45.9
3	R2	21	5.0	0.388	28.4	LOS B	1.0	7.2	0.59	0.73	34.2
Approach		2252	4.1	0.645	12.4	LOS A	24.9	179.0	0.45	0.45	45.2
East: Congressional Drive (E)											
4	L2	42	2.5	0.205	61.9	LOS E	4.2	29.6	0.90	0.73	23.8
5	T1	24	0.0	0.205	57.3	LOS E	4.2	29.6	0.90	0.73	23.3
6	R2	52	0.0	0.236	65.6	LOS E	3.4	23.6	0.92	0.75	19.1
Approach		118	0.9	0.236	62.6	LOS E	4.2	29.6	0.91	0.74	21.7
North: Hume Highway (N)											
7	L2	67	0.0	0.961	25.5	LOS B	61.6	439.1	0.52	0.59	34.2
8	T1	3665	2.2	0.961	21.5	LOS B	61.6	439.1	0.40	0.47	38.5
9	R2	178	1.2	0.780	49.7	LOS D	11.2	79.0	1.00	0.99	25.1
Approach		3911	2.2	0.961	22.9	LOS B	61.6	439.1	0.43	0.50	37.5
West: Reilly Street (W)											
10	L2	65	0.0	0.235	56.1	LOS D	5.8	40.6	0.86	0.74	23.5
11	T1	32	0.0	0.235	51.6	LOS D	5.8	40.6	0.86	0.74	24.5
12	R2	262	2.0	1.127	219.6	LOS F	35.6	253.4	1.00	1.39	10.8
Approach		359	1.5	1.127	175.1	LOS F	35.6	253.4	0.96	1.21	12.4
All Vehicles		6639	2.8	1.127	28.2	LOS B	61.6	439.1	0.47	0.52	34.5

PHASING SUMMARY



Site: I-05 2030 BASE PM


Hume Highway / Reilly Street

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E2
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	98	133
Green Time (sec)	92	29	11
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	98	35	17
Phase Split	65 %	23 %	11 %



I-06 Intersection of Newbridge Road and Moorebank Avenue

MOVEMENT SUMMARY



Site: I-06 2030 BASE AM



Network: 2030 BASE AM

Newbridge Road / Moorebank Avenue

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo	Demand Flows		Arrival Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV	Total	HV				Vehicles	Distance			
	veh/h	%	veh/h	%	v/c				sec	veh			
South: Moorebank Avenue (S)													
1	L2	1535	3.2	1279	3.2	0.660	19.5	LOS B	15.0	108.2	0.58	0.83	41.9
3	R2	1365	9.0	1138	9.1	0.669	15.1	LOS B	14.1	106.4	0.42	0.69	52.7
Approach		2900	5.9	2417 ^{N1}	5.9	0.669	17.4	LOS B	15.0	108.2	0.51	0.76	47.7
East: Newbridge Road (E)													
4	L2	687	19.8	687	19.8	0.563	18.5	LOS B	8.3	68.3	0.71	0.80	51.9
5	T1	966	5.2	966	5.2	1.262	313.4	LOS F	77.6	567.9	1.00	1.91	14.6
Approach		1654	11.3	1654	11.3	1.262	190.8	LOS F	77.6	567.9	0.88	1.45	18.8
West: Newbridge Road (W)													
11	T1	1579	6.4	1579	6.4	0.850	12.2	LOS A	30.6	225.7	0.63	0.59	61.0
12	R2	867	7.4	867	7.4	1.577	575.4	LOS F	87.3	650.0	1.00	1.90	3.6
Approach		2446	6.8	2446	6.8	1.577	211.9	LOS F	87.3	650.0	0.76	1.06	16.3
All Vehicles		7000	7.5	6517 ^{N1}	8.0	1.577	134.4	LOS F	87.3	650.0	0.70	1.05	21.1

PHASING SUMMARY



Network: 2030 BASE AM



Site: I-06 2030 BASE AM


Newbridge Road / Moorebank Avenue

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C	D
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	33	55	116
Green Time (sec)	27	16	55	11
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	33	22	61	17
Phase Split	25 %	17 %	46 %	13 %



MOVEMENT SUMMARY

 Site: I-06 2030 BASE PM

 Network: 2030 BASE PM

Newbridge Road / Moorebank Avenue

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 116 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Arrival Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV	Total	HV				Vehicles	Distance			
		veh/h	%	veh/h	%				veh	m			
South: Moorebank Avenue (S)													
1	L2	1001	3.3	887	3.4	0.507	22.5	LOS B	13.1	94.7	0.57	0.75	39.8
3	R2	953	10.7	847	11.1	1.097	148.5	LOS F	17.0	130.6	1.00	1.30	19.0
Approach		1954	6.9	1734 ^{N1}	7.1	1.097	84.0	LOS F	17.0	130.6	0.78	1.02	23.9
East: Newbridge Road (E)													
4	L2	1243	5.1	1243	5.1	1.047	144.1	LOS F	66.2	483.9	1.00	1.19	18.6
5	T1	1371	4.7	1371	4.7	0.921	50.6	LOS D	42.4	308.7	1.00	1.03	43.4
Approach		2614	4.9	2614	4.9	1.047	95.1	LOS F	66.2	483.9	1.00	1.11	29.2
West: Newbridge Road (W)													
11	T1	1127	3.8	1127	3.8	0.441	9.3	LOS A	14.6	105.3	0.50	0.45	62.9
12	R2	1118	2.6	1118	2.6	1.188	222.8	LOS F	72.6	519.7	1.00	1.44	8.5
Approach		2245	3.2	2245	3.2	1.188	115.6	LOS F	72.6	519.7	0.75	0.95	23.1
All Vehicles		6813	4.9	6593 ^{N1}	5.1	1.188	99.2	LOS F	72.6	519.7	0.86	1.03	25.8

PHASING SUMMARY

 Site: I-06 2030 BASE PM

 Network: 2030 BASE PM


Newbridge Road / Moorebank Avenue

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 116 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	44	76
Green Time (sec)	38	26	34
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	44	32	40
Phase Split	38 %	28 %	34 %



I-07 Intersection of Moorebank Avenue and Heathcote Road

MOVEMENT SUMMARY



Site: I-07 2030 BASE AM



Network: 2030 BASE AM

Moorebank Avenue / Heathcote Road

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Arrival Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV	Total	HV				Vehicles	Distance			
		veh/h	%	veh/h	%				veh	m			
South: Moorebank Avenue (S)													
2	T1	1920	5.6	1834	5.7	1.192	219.3	LOS F	60.0	440.6	1.00	1.95	4.4
3	R2	24	21.7	23	21.9	0.213	72.1	LOS F	1.5	12.4	0.98	0.71	30.5
Approach		1944	5.8	1857 ^{N1}	5.9	1.192	217.5	LOS F	60.0	440.6	1.00	1.93	4.6
East: Heathcote Road (E)													
4	L2	29	57.1	29	57.1	1.385	431.6	LOS F	92.8	700.6	1.00	1.86	7.5
6	R2	953	6.0	953	6.0	1.385	430.9	LOS F	95.9	705.9	1.00	1.87	7.5
Approach		982	7.5	982	7.5	1.385	430.9	LOS F	95.9	705.9	1.00	1.87	7.5
North: Moorebank Avenue (N)													
7	L2	794	7.8	632	8.7	0.393	10.7	LOS A	12.7	95.4	0.54	0.71	51.4
8	T1	783	16.9	631	18.6	0.360	21.2	LOS B	12.2	99.1	0.65	0.57	13.2
Approach		1577	12.3	1263 ^{N1}	13.6	0.393	15.9	LOS B	12.7	99.1	0.59	0.64	41.5
All Vehicles		4503	8.5	4102 ^{N1}	9.3	1.385	206.5	LOS F	95.9	705.9	0.88	1.52	8.5

PHASING SUMMARY



Site: I-07 2030 BASE AM



Network: 2030 BASE AM


Moorebank Avenue / Heathcote Road

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Phase Timing Results

Phase	B	A	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	15	88
Green Time (sec)	9	67	39
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	15	73	45
Phase Split	11 %	55 %	34 %



MOVEMENT SUMMARY



Site: I-07 2030 BASE PM



Network: 2030 BASE PM

Moorebank Avenue / Heathcote Road

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 116 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	HV %	Arrival Flows Total veh/h	HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)													
2	T1	1163	8.3	1163	8.3	0.910	45.1	LOS D	42.9	321.6	0.91	1.05	16.7
3	R2	48	8.7	48	8.7	0.401	64.7	LOS E	2.8	20.9	1.00	0.74	32.2
Approach		1212	8.3	1212	8.3	0.910	45.9	LOS D	42.9	321.6	0.92	1.04	18.0
East: Heathcote Road (E)													
4	L2	76	19.4	76	19.4	1.415	430.1	LOS F	92.9	690.4	1.00	1.99	7.5
6	R2	811	5.1	811	5.1	1.415	429.4	LOS F	92.9	690.4	1.00	1.99	7.5
Approach		886	6.3	886	6.3	1.415	429.5	LOS F	92.9	690.4	1.00	1.99	7.5
North: Moorebank Avenue (N)													
7	L2	883	3.6	796	3.6	0.389	7.5	LOS A	5.4	39.0	0.24	0.61	53.8
8	T1	1454	4.1	1310	4.2	0.667	6.3	LOS A	11.9	86.2	0.35	0.32	29.3
Approach		2337	3.9	2106 ^{N1}	4.0	0.667	6.7	LOS A	11.9	86.2	0.31	0.43	48.6
All Vehicles		4435	5.6	4204 ^{N1}	5.9	1.415	107.1	LOS F	92.9	690.4	0.63	0.93	14.2

PHASING SUMMARY



Site: I-07 2030 BASE PM



Network: 2030 BASE PM


Moorebank Avenue / Heathcote Road

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 116 seconds (User-Given Phase Times)

Phase Timing Results

Phase	B	A	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	14	80
Green Time (sec)	8	60	30
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	14	66	36
Phase Split	12 %	57 %	31 %



I-08 Intersection of Moorebank Avenue and Industry Park Access

MOVEMENT SUMMARY



Site: I-08 2030 BASE AM



Network: 2030 BASE AM

Moorebank Avenue / Industry Park Access

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Arrival Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV	Total	HV				Vehicles	Distance			
		veh/h	%	veh/h	%				veh	m			
South: Moorebank Avenue (S)													
1	L2	88	1.2	88	1.2	0.053	6.1	LOS A	0.4	2.8	0.12	0.58	43.1
2	T1	1899	4.9	1899	4.9	1.215	256.5	LOS F	156.8	1144.3	1.00	2.09	6.2
Approach		1987	4.8	1987	4.8	1.215	245.3	LOS F	156.8	1144.3	0.96	2.02	6.6
North: Moorebank Avenue (N)													
8	T1	695	16.2	558	17.6	0.193	2.5	LOS A	3.6	29.1	0.22	0.19	56.9
9	R2	65	38.7	54	41.1	1.017	119.3	LOS F	4.7	44.9	1.00	1.06	11.5
Approach		760	18.1	612 ^{N1}	19.6	1.017	12.7	LOS A	4.7	44.9	0.29	0.27	45.9
West: Industry Park Access (W)													
10	L2	34	62.5	34	62.5	0.415	64.9	LOS E	2.3	24.3	0.95	0.73	9.6
12	R2	56	71.7	56	71.7	0.392	67.8	LOS E	2.6	29.5	0.98	0.73	19.9
Approach		89	68.2	89	68.2	0.415	66.7	LOS E	2.6	29.5	0.97	0.73	16.7
All Vehicles		2837	10.4	2688 ^{N1}	10.9	1.215	186.5	LOS F	156.8	1144.3	0.81	1.58	9.1

PHASING SUMMARY



Site: I-08 2030 BASE AM



Network: 2030 BASE AM


Moorebank Avenue / Industry Park Access

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C
Reference Phase	Yes	No
Phase Change Time (sec)	0	116
Green Time (sec)	110	11
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	116	17
Phase Split	87 %	13 %



MOVEMENT SUMMARY



Site: I-08 2030 BASE PM



Network: 2030 BASE PM

Moorebank Avenue / Industry Park Access

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 65 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	HV %	Arrival Flows Total veh/h	HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)													
1	L2	8	12.5	8	12.5	0.007	6.6	LOS A	0.0	0.3	0.22	0.58	42.7
2	T1	1133	7.6	1133	7.6	0.440	4.8	LOS A	7.9	59.1	0.48	0.42	51.7
Approach		1141	7.7	1141	7.7	0.440	4.8	LOS A	7.9	59.1	0.47	0.43	51.6
North: Moorebank Avenue (N)													
8	T1	1527	3.9	1366	3.8	0.518	5.2	LOS A	10.4	75.0	0.52	0.47	54.0
9	R2	25	62.5	22	62.1	0.124	13.9	LOS A	0.4	3.8	0.48	0.67	33.2
Approach		1553	4.8	1388 ^{N1}	4.7	0.518	5.3	LOS A	10.4	75.0	0.52	0.47	53.6
West: Industry Park Access (W)													
10	L2	34	15.6	34	15.6	0.065	3.6	LOS A	0.3	2.0	0.34	0.42	26.7
12	R2	187	9.0	187	9.0	0.436	32.4	LOS C	2.9	22.2	0.97	0.76	28.2
Approach		221	10.0	221	10.0	0.436	28.0	LOS B	2.9	22.2	0.87	0.71	28.1
All Vehicles		2915	6.3	2750 ^{N1}	6.7	0.518	6.9	LOS A	10.4	75.0	0.53	0.47	49.3

PHASING SUMMARY



Site: I-08 2030 BASE PM



Network: 2030 BASE PM


Moorebank Avenue / Industry Park Access

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 65 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C
Reference Phase	Yes	No
Phase Change Time (sec)	0	51
Green Time (sec)	45	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	51	14
Phase Split	78 %	22 %



I-09 Intersection of Moorebank Avenue and Church Road

MOVEMENT SUMMARY

▽ Site: I-09 2030 BASE AM

Moorebank Avenue / Church Road
2030 BASE AM PEAK 7:45 am - 8:45 am
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h	
South: Moorebank Avenue (S)											
2	T1	2101	6.4	0.737	4.3	LOS A	11.1	82.6	0.18	0.11	55.5
3	R2	282	7.8	0.737	25.5	LOS B	11.1	82.6	1.00	0.60	40.4
Approach		2383	6.6	0.921	6.8	NA	11.1	82.6	0.28	0.17	53.1
East: Church Road (E)											
4	L2	200	14.2	0.243	7.1	LOS A	1.0	7.6	0.48	0.70	47.6
6	R2	7	0.0	0.945	845.2	LOS F	2.5	17.2	1.00	1.07	4.0
Approach		207	13.7	0.945	36.9	LOS C	2.5	17.2	0.50	0.71	34.2
North: Moorebank Avenue (N)											
7	L2	37	0.0	0.219	5.6	LOS A	0.0	0.0	0.00	0.06	57.7
8	T1	717	21.1	0.219	0.0	LOS A	0.0	0.0	0.00	0.03	59.6
Approach		754	20.1	0.219	0.3	NA	0.0	0.0	0.00	0.03	59.5
All Vehicles		3344	10.1	0.945	7.2	NA	11.1	82.6	0.23	0.17	52.5

MOVEMENT SUMMARY

▽ Site: I-09 2030 BASE PM

Moorebank Avenue / Church Road
2030 BASE PM PEAK 4:30 pm - 5:30 pm
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
2	T1	1177	11.9	0.598	3.2	LOS A	5.8	44.3	0.08	0.05	56.7
3	R2	108	11.7	0.598	44.4	LOS D	5.8	44.3	1.00	0.68	33.1
Approach		1285	11.9	0.598	6.7	NA	5.8	44.3	0.16	0.11	53.4
East: Church Road (E)											
4	L2	424	4.5	1.291	324.8	LOS F	78.0	566.9	1.00	4.91	9.2
6	R2	1	0.0	0.124	374.1	LOS F	0.3	2.1	0.99	1.00	8.2
Approach		425	4.5	1.291	324.9	LOS F	78.0	566.9	1.00	4.90	9.2
North: Moorebank Avenue (N)											
7	L2	14	7.7	0.899	6.8	LOS A	0.0	0.0	0.00	0.01	55.6
8	T1	1687	4.6	0.899	1.4	LOS A	0.0	0.0	0.00	0.00	57.2
Approach		1701	4.6	0.899	1.5	NA	0.0	0.0	0.00	0.00	57.2
All Vehicles		3412	7.3	1.291	43.7	NA	78.0	566.9	0.18	0.65	33.7

I-10 Intersection of Heathcote Road and Nuwarra Road

MOVEMENT SUMMARY



Site: I-10 2030 BASE AM

Heathcote Road / Nuwarra Road / Wattle Grove Drive

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 131 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
SouthEast: Heathcote Road (SE)											
4	L2	249	1.3	0.173	8.2	LOS A	3.3	23.3	0.27	0.63	48.3
5	T1	2074	5.3	1.255	285.8	LOS F	161.5	1181.8	1.00	2.14	10.3
6	R2	647	3.3	1.268	267.3	LOS F	42.9	308.4	1.00	1.54	11.2
Approach		2971	4.5	1.268	258.4	LOS F	161.5	1181.8	0.94	1.88	11.1
NorthEast: Nuwarra Road (NE)											
7	L2	416	4.8	0.485	24.6	LOS B	16.5	120.4	0.71	0.78	42.4
8	T1	246	8.5	0.397	53.0	LOS D	7.1	53.4	0.94	0.75	26.2
9	R2	508	5.8	1.436	477.0	LOS F	49.8	365.8	1.00	1.93	6.6
Approach		1171	6.0	1.436	227.1	LOS F	49.8	365.8	0.88	1.27	11.9
NorthWest: Heathcote Road (NW)											
10	L2	255	12.0	0.336	21.5	LOS B	7.9	60.6	0.70	0.76	42.7
11	T1	1047	11.6	0.963	56.6	LOS E	44.0	338.3	0.91	0.98	30.7
12	R2	236	6.7	0.792	75.7	LOS F	8.1	59.7	1.00	0.89	19.9
Approach		1538	10.9	0.963	53.7	LOS D	44.0	338.3	0.89	0.93	30.5
SouthWest: Wattle Grove Drive (SW)											
1	L2	639	2.1	0.849	51.8	LOS D	31.9	227.1	0.99	1.15	24.8
2	T1	543	4.5	0.817	61.8	LOS E	19.6	142.7	1.00	0.94	23.7
3	R2	263	4.0	1.277	332.6	LOS F	42.3	306.5	1.00	1.80	6.6
Approach		1445	3.4	1.277	106.7	LOS F	42.3	306.5	0.99	1.19	16.1
All Vehicles		7124	5.9	1.436	178.3	LOS F	161.5	1181.8	0.93	1.44	13.9

PHASING SUMMARY



Site: I-10 2030 BASE AM

Heathcote Road / Nuwarra Road / Wattle Grove Drive

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 131 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	D	E	G
Reference Phase	Yes	No	No	No	No
Phase Change Time (sec)	0	54	67	86	114
Green Time (sec)	48	7	13	22	11
Yellow Time (sec)	4	4	4	4	4
All-Red Time (sec)	2	2	2	2	2
Phase Time (sec)	54	13	19	28	17
Phase Split	41 %	10 %	15 %	21 %	13 %



MOVEMENT SUMMARY



Site: I-10 2030 BASE PM

Heathcote Road / Nuwarra Road / Wattle Grove Drive

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 139 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
SouthEast: Heathcote Road (SE)											
4	L2	337	2.5	0.282	15.4	LOS B	8.9	63.6	0.45	0.70	42.4
5	T1	1332	5.5	0.993	78.0	LOS F	59.6	436.7	0.93	1.13	26.0
6	R2	469	3.1	1.197	269.1	LOS F	34.2	246.1	1.00	1.49	11.2
Approach		2138	4.5	1.197	110.1	LOS F	59.6	436.7	0.87	1.14	20.4
NorthEast: Nuwarra Road (NE)											
7	L2	644	2.5	0.945	77.5	LOS F	46.1	329.7	1.00	1.21	26.4
8	T1	620	1.2	0.993	95.2	LOS F	29.3	207.2	1.00	1.17	18.1
9	R2	551	6.1	1.103	168.0	LOS F	34.2	251.7	1.00	1.27	15.5
Approach		1815	3.1	1.103	111.0	LOS F	46.1	329.7	1.00	1.21	19.5
NorthWest: Heathcote Road (NW)											
10	L2	258	6.1	0.232	21.3	LOS B	8.5	62.5	0.53	0.73	43.0
11	T1	1701	2.7	1.169	221.8	LOS F	119.2	853.6	1.00	1.79	12.7
12	R2	467	2.0	1.103	167.2	LOS F	28.6	203.5	1.00	1.24	11.1
Approach		2426	3.0	1.169	190.0	LOS F	119.2	853.6	0.95	1.57	13.5
SouthWest: Wattle Grove Drive (SW)											
1	L2	305	1.7	0.387	33.9	LOS C	14.1	100.1	0.76	0.85	30.6
2	T1	325	1.3	0.462	57.5	LOS E	10.0	71.0	0.95	0.78	24.7
3	R2	357	1.2	1.323	381.7	LOS F	63.0	445.2	1.00	1.84	5.8
Approach		987	1.4	1.323	167.4	LOS F	63.0	445.2	0.91	1.18	11.5
All Vehicles		7366	3.2	1.323	144.3	LOS F	119.2	853.6	0.93	1.31	16.2

PHASING SUMMARY



Site: I-10 2030 BASE PM


Heathcote Road / Nuwarra Road / Wattle Grove Drive

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 139 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	G
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	63	89	118
Green Time (sec)	57	20	23	15
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	63	26	29	21
Phase Split	45 %	19 %	21 %	15 %



I-11 Intersection of Newbridge Road and Nuwarra Road

MOVEMENT SUMMARY



Site: I-11 2030 BASE AM

Newbridge Road / Nuwarra Road

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c sec	Level of Service	95% Back of Queue Vehicles veh	Prop. Queued Distance m	Effective Stop Rate per veh	Average Speed km/h		
South: Nuwarra Road (S)											
1	L2	37	8.6	0.900	67.1	LOS E	27.7	197.7	0.92	0.99	32.6
2	T1	353	1.8	0.900	64.1	LOS E	27.7	197.7	0.92	0.99	27.5
3	R2	857	6.8	1.245	312.8	LOS F	74.3	549.9	1.00	1.55	10.8
Approach		1246	5.4	1.245	235.2	LOS F	74.3	549.9	0.97	1.38	13.4
East: Newbridge Road (E)											
4	L2	347	17.9	0.636	27.8	LOS B	21.9	173.4	0.73	0.78	45.0
5	T1	1281	11.3	0.636	23.5	LOS B	22.7	174.2	0.68	0.63	51.1
Approach		1628	12.7	0.636	24.4	LOS B	22.7	174.2	0.69	0.66	49.8
North: Nuwarra Road (N)											
7	L2	8	0.0	0.981	108.4	LOS F	11.3	79.5	1.00	1.23	22.4
8	T1	153	0.7	1.227	149.0	LOS F	26.9	195.3	1.00	1.34	17.8
9	R2	141	5.2	1.227	293.8	LOS F	26.9	195.3	1.00	1.76	12.0
Approach		302	2.8	1.227	215.5	LOS F	26.9	195.3	1.00	1.53	14.4
West: Newbridge Road (W)											
10	L2	306	2.4	1.139	197.1	LOS F	113.0	835.4	1.00	1.57	16.4
11	T1	2284	8.9	1.212	222.8	LOS F	137.7	1037.8	1.00	1.82	15.8
Approach		2591	8.2	1.212	219.7	LOS F	137.7	1037.8	1.00	1.79	15.9
All Vehicles		5767	8.6	1.245	167.7	LOS F	137.7	1037.8	0.91	1.37	18.7

PHASING SUMMARY



Site: I-11 2030 BASE AM


Newbridge Road / Nuwarra Road

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	89
Green Time (sec)	66	11	45
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	17	51
Phase Split	51 %	12 %	36 %



MOVEMENT SUMMARY



Site: I-11 2030 BASE PM

Newbridge Road / Nuwarra Road

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Nuwarra Road (S)											
1	L2	58	7.3	0.771	71.1	LOS F	14.8	105.7	1.00	0.89	31.8
2	T1	156	0.7	0.771	66.7	LOS E	14.8	105.7	1.00	0.89	28.9
3	R2	564	6.2	1.009	122.0	LOS F	27.4	201.9	1.00	1.12	21.8
Approach		778	5.1	1.009	107.2	LOS F	27.4	201.9	1.00	1.06	23.5
East: Newbridge Road (E)											
4	L2	772	4.5	0.784	18.1	LOS B	32.5	236.7	0.58	0.79	50.2
5	T1	2224	5.8	0.784	16.5	LOS B	40.5	297.9	0.66	0.64	55.5
Approach		2996	5.4	0.784	16.9	LOS B	40.5	297.9	0.64	0.68	54.1
North: Nuwarra Road (N)											
7	L2	18	0.0	0.867	75.8	LOS F	17.8	125.6	1.00	1.01	29.1
8	T1	295	0.7	1.084	97.2	LOS F	32.9	231.9	1.00	1.09	24.0
9	R2	212	1.0	1.084	181.8	LOS F	32.9	231.9	1.00	1.37	17.7
Approach		524	0.8	1.084	130.6	LOS F	32.9	231.9	1.00	1.20	20.9
West: Newbridge Road (W)											
10	L2	102	0.0	0.539	21.5	LOS B	17.3	127.8	0.50	0.51	48.5
11	T1	1674	7.8	0.613	14.6	LOS B	20.1	149.8	0.50	0.47	56.9
Approach		1776	7.4	0.613	15.0	LOS B	20.1	149.8	0.50	0.47	56.4
All Vehicles		6074	5.6	1.084	37.7	LOS C	40.5	297.9	0.68	0.71	42.3

PHASING SUMMARY



Site: I-11 2030 BASE PM


Newbridge Road / Nuwarra Road

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	84	112
Green Time (sec)	78	22	22
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	84	28	28
Phase Split	60 %	20 %	20 %



I-12 Intersection of Newbridge Road and Governor Macquarie Drive

MOVEMENT SUMMARY



Site: I-12 2030 BASE AM

Newbridge Road / Governor Macquarie Drive

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Brickmakers Drive (S)											
1	L2	14	0.0	0.909	84.6	LOS F	17.3	122.1	1.00	1.07	24.1
2	T1	207	1.0	0.909	80.3	LOS F	17.3	122.1	1.00	1.07	23.8
3	R2	720	1.2	1.239	301.6	LOS F	55.9	395.6	1.00	1.68	12.6
Approach		941	1.1	1.239	249.7	LOS F	55.9	395.6	1.00	1.53	13.8
East: Newbridge Road (E)											
4	L2	242	3.0	0.178	7.9	LOS A	2.2	15.7	0.19	0.64	58.1
5	T1	1459	11.0	0.425	13.9	LOS A	16.5	126.1	0.55	0.49	59.9
6	R2	686	10.3	1.058	160.0	LOS F	37.1	282.3	1.00	1.17	23.3
Approach		2387	10.0	1.058	55.3	LOS D	37.1	282.3	0.64	0.70	40.9
North: Governor Macquarie Drive (N)											
7	L2	775	9.0	0.740	53.4	LOS D	23.9	180.2	0.96	0.86	40.0
8	T1	136	3.1	0.553	64.3	LOS E	8.9	63.9	0.99	0.80	27.0
9	R2	186	35.0	1.097	187.9	LOS F	22.4	204.1	1.00	1.30	16.5
Approach		1097	12.7	1.097	77.6	LOS F	23.9	204.1	0.97	0.93	32.3
West: Newbridge Road (W)											
10	L2	135	31.3	1.206	252.1	LOS F	154.7	1175.7	1.00	1.85	13.6
11	T1	2987	6.8	1.206	244.6	LOS F	159.4	1180.2	1.00	1.89	17.6
12	R2	5	20.0	0.043	32.9	LOS C	0.2	1.8	0.60	0.67	37.8
Approach		3127	7.8	1.206	244.6	LOS F	159.4	1180.2	1.00	1.89	17.5
All Vehicles		7553	8.4	1.239	161.1	LOS F	159.4	1180.2	0.88	1.33	22.5

PHASING SUMMARY



Site: I-12 2030 BASE AM


Newbridge Road / Governor Macquarie Drive

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	G1
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	66	88	112
Green Time (sec)	60	16	18	22
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	66	22	24	28
Phase Split	47 %	16 %	17 %	20 %



MOVEMENT SUMMARY



Site: I-12 2030 BASE PM

Newbridge Road / Governor Macquarie Drive

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Brickmakers Drive (S)											
1	L2	11	0.0	0.554	70.4	LOS E	7.2	52.4	1.00	0.79	26.8
2	T1	97	5.4	0.554	66.3	LOS E	7.2	52.4	1.00	0.79	26.5
3	R2	271	0.8	0.641	70.4	LOS E	9.1	64.3	1.00	0.81	32.5
Approach		378	1.9	0.641	69.3	LOS E	9.1	64.3	1.00	0.81	31.0
East: Newbridge Road (E)											
4	L2	689	1.5	0.487	9.5	LOS A	8.3	59.1	0.29	0.70	57.0
5	T1	2751	4.4	0.923	30.0	LOS C	52.5	381.4	0.75	0.77	51.3
6	R2	752	11.2	1.142	229.6	LOS F	50.7	389.2	1.00	1.32	18.2
Approach		4192	5.2	1.142	62.4	LOS E	52.5	389.2	0.72	0.86	38.8
North: Governor Macquarie Drive (N)											
7	L2	586	3.6	0.429	46.0	LOS D	15.7	113.2	0.84	0.81	42.3
8	T1	311	0.7	1.031	128.1	LOS F	30.2	212.7	1.00	1.27	17.8
9	R2	242	19.1	1.147	226.2	LOS F	32.2	262.1	1.00	1.37	14.5
Approach		1139	6.1	1.147	106.7	LOS F	32.2	262.1	0.92	1.05	26.0
West: Newbridge Road (W)											
10	L2	177	16.7	0.857	45.7	LOS D	44.9	337.5	0.93	0.88	39.2
11	T1	2064	6.1	0.857	37.7	LOS C	45.6	336.0	0.91	0.86	47.9
12	R2	4	0.0	0.070	54.4	LOS D	0.2	1.7	0.80	0.69	30.3
Approach		2245	6.9	0.857	38.4	LOS C	45.6	337.5	0.91	0.86	47.2
All Vehicles		7954	5.6	1.147	62.3	LOS E	52.5	389.2	0.82	0.88	38.1

PHASING SUMMARY



Site: I-12 2030 BASE PM


Newbridge Road / Governor Macquarie Drive

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	G1
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	64	86	107
Green Time (sec)	58	16	15	27
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	64	22	21	33
Phase Split	46 %	16 %	15 %	24 %



I-13 Intersection of Moorebank Avenue and M5 Motorway

MOVEMENT SUMMARY



Site: I-13 2030 BASE AM

Moorebank Avenue / the M5 Motorway

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 74 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
1	L2	285	11.1	0.247	9.2	LOS A	3.3	25.1	0.42	0.66	50.3
2	T1	669	4.2	0.768	32.3	LOS C	12.4	89.9	0.99	0.92	37.9
3	R2	307	2.7	0.428	33.2	LOS C	5.4	38.8	0.90	0.79	36.8
Approach		1262	5.4	0.768	27.3	LOS B	12.4	89.9	0.84	0.83	39.8
East: M5 Motorway on&off ramp (E)											
4	L2	231	7.3	0.231	8.1	LOS A	1.8	13.1	0.39	0.66	51.5
6	R2	237	6.2	0.246	28.8	LOS C	3.4	25.1	0.82	0.76	40.4
Approach		467	6.8	0.246	18.6	LOS B	3.4	25.1	0.61	0.71	44.9
North: Moorebank Avenue (N)											
7	L2	52	49.0	0.051	7.7	LOS A	0.3	3.3	0.28	0.60	51.2
8	T1	192	12.6	0.231	25.6	LOS B	2.9	22.4	0.85	0.67	41.0
9	R2	458	26.2	0.782	38.1	LOS C	10.2	87.3	0.98	0.88	36.2
Approach		701	24.2	0.782	32.4	LOS C	10.2	87.3	0.89	0.80	38.2
West: M5 Motorway on&off ramp (W)											
10	L2	1736	8.2	0.989	9.4	LOS A	0.0	0.0	0.00	0.48	49.5
12	R2	384	4.1	0.394	29.9	LOS C	5.8	42.0	0.86	0.79	38.6
Approach		2120	7.4	0.989	13.1	LOS A	5.8	42.0	0.16	0.54	47.3
All Vehicles		4551	9.4	0.989	20.6	LOS B	12.4	89.9	0.51	0.68	43.3

PHASING SUMMARY



Site: I-13 2030 BASE AM


Moorebank Avenue / the M5 Motorway

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 74 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	E	F
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	24	51
Green Time (sec)	17	20	16
Yellow Time (sec)	4	4	4
All-Red Time (sec)	3	3	3
Phase Time (sec)	24	27	23
Phase Split	32 %	36 %	31 %



MOVEMENT SUMMARY

 **Site: I-13 2030 BASE PM**

Moorebank Avenue / the M5 Motorway

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 94 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
1	L2	306	3.1	0.396	19.7	LOS B	8.1	58.2	0.71	0.77	43.7
2	T1	180	7.6	0.650	49.6	LOS D	4.4	32.5	1.00	0.82	31.6
3	R2	298	2.1	0.247	28.0	LOS B	5.2	37.4	0.73	0.75	39.1
Approach		784	3.8	0.650	29.7	LOS C	8.1	58.2	0.78	0.77	38.6
East: M5 Motorway on&off ramp (E)											
4	L2	439	2.9	0.466	12.3	LOS A	7.2	51.3	0.55	0.74	48.4
6	R2	97	21.7	0.177	42.7	LOS D	2.0	16.2	0.89	0.73	34.9
Approach		536	6.3	0.466	17.8	LOS B	7.2	51.3	0.62	0.74	45.0
North: Moorebank Avenue (N)											
7	L2	140	6.8	0.111	6.9	LOS A	0.9	7.0	0.24	0.61	53.0
8	T1	726	3.6	0.779	39.2	LOS C	16.7	120.6	0.99	0.92	35.1
9	R2	1495	7.4	0.926	45.0	LOS D	35.4	263.7	1.00	1.07	34.1
Approach		2361	6.2	0.926	40.9	LOS C	35.4	263.7	0.95	1.00	35.2
West: M5 Motorway on&off ramp (W)											
10	L2	631	15.2	0.376	5.8	LOS A	0.0	0.0	0.00	0.52	54.3
12	R2	255	3.7	0.414	44.2	LOS D	5.4	38.8	0.94	0.78	33.1
Approach		885	11.9	0.414	16.9	LOS B	5.4	38.8	0.27	0.60	46.4
All Vehicles		4566	6.9	0.926	31.6	LOS C	35.4	263.7	0.75	0.85	38.5

PHASING SUMMARY

 **Site: I-13 2030 BASE PM**


Moorebank Avenue / the M5 Motorway

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 94 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	E	F
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	14	30	53
Green Time (sec)	7	9	16	34
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	3	3	3	3
Phase Time (sec)	14	16	23	41
Phase Split	15 %	17 %	24 %	44 %



I-14 Intersection of M5 Motorway and Hume Highway

MOVEMENT SUMMARY



Site: I-14 2030 BASE AM

M5 Motorway / Hume Highway

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 159 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Prop. Queued Distance m	Effective Stop Rate per veh	Average Speed km/h		
South: Hume Highway (S)											
2	T1	4252	4.5	1.025	58.2	LOS E	151.4	1100.9	1.00	1.20	33.5
3	R2	640	4.1	0.881	42.9	LOS D	17.4	125.8	1.00	0.90	37.8
Approach		4892	4.5	1.025	56.2	LOS D	151.4	1100.9	1.00	1.16	34.1
East: M5 Motorway on&off-ramp (E)											
4	L2	340	6.5	0.135	30.6	LOS C	4.8	35.8	0.60	0.71	41.9
6	R2	1180	3.9	1.214	292.5	LOS F	64.9	469.4	1.00	1.43	8.6
Approach		1520	4.5	1.214	233.9	LOS F	64.9	469.4	0.91	1.27	11.3
North: Hume Highway (N)											
7	L2	699	5.9	0.530	12.1	LOS A	18.8	138.4	0.45	0.71	47.3
8	T1	1213	7.0	0.492	28.5	LOS C	17.9	132.8	0.62	0.55	43.3
Approach		1912	6.6	0.530	22.5	LOS B	18.8	138.4	0.56	0.61	44.3
All Vehicles		8323	5.0	1.214	80.9	LOS F	151.4	1100.9	0.88	1.06	27.4

PHASING SUMMARY



Site: I-14 2030 BASE AM


M5 Motorway / Hume Highway

2030 BASE AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 159 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C	D
Reference Phase	No	No	No	Yes
Phase Change Time (sec)	20	97	123	0
Green Time (sec)	70	19	29	13
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	3	3	3	3
Phase Time (sec)	77	26	36	20
Phase Split	48 %	16 %	23 %	13 %



MOVEMENT SUMMARY



Site: I-14 2030 BASE PM

M5 Motorway / Hume Highway

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 159 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
2	T1	2552	3.8	0.623	2.2	LOS A	7.0	50.8	0.12	0.11	58.3
3	R2	401	1.8	1.023	122.1	LOS F	20.4	145.1	1.00	1.07	22.6
Approach		2953	3.5	1.023	18.5	LOS B	20.4	145.1	0.24	0.24	48.0
East: M5 Motorway on&off-ramp (E)											
4	L2	1465	3.6	1.104	217.9	LOS F	88.9	641.3	1.00	1.28	15.1
6	R2	1175	3.6	1.152	240.1	LOS F	59.4	428.7	1.00	1.33	10.2
Approach		2640	3.6	1.152	227.8	LOS F	88.9	641.3	1.00	1.30	12.9
North: Hume Highway (N)											
7	L2	852	2.1	0.643	13.1	LOS A	26.5	189.0	0.56	0.78	46.8
8	T1	2844	2.7	0.889	23.0	LOS B	56.7	405.9	0.79	0.75	45.7
Approach		3696	2.6	0.889	20.8	LOS B	56.7	405.9	0.74	0.76	45.9
All Vehicles		9288	3.2	1.152	78.9	LOS F	88.9	641.3	0.65	0.75	27.8

PHASING SUMMARY



Site: I-14 2030 BASE PM


M5 Motorway / Hume Highway

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 159 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	97	121
Green Time (sec)	90	17	31
Yellow Time (sec)	4	4	4
All-Red Time (sec)	3	3	3
Phase Time (sec)	97	24	38
Phase Split	61 %	15 %	24 %



I-15 Intersection of Cambridge Avenue and Canterbury Road

MOVEMENT SUMMARY



Site: I-15 2030 BASE AM

Canterbury Road / Cambridge Avenue / Glenfield Road

2030 BASE AM PEAK 7:45 am - 8:45 am

Roundabout

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows	Deg. Satn	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h	
		Total veh/h	HV %			Vehicles veh	Distance m				
South: Canterbury Road (S)											
1	L2	449	3.5	0.498	6.1	LOS A	3.1	22.6	0.61	0.70	52.9
2	T1	8	0.0	0.827	8.6	LOS A	11.9	84.6	0.86	0.89	50.3
3	R2	999	2.1	0.827	14.0	LOS A	11.9	84.6	0.86	0.89	50.4
Approach		1457	2.5	0.827	11.6	LOS A	11.9	84.6	0.78	0.83	51.0
East: Cambridge Avenue (E)											
4	L2	307	3.1	0.163	3.5	LOS A	0.0	0.0	0.00	0.43	56.5
5	T1	81	7.8	0.088	5.5	LOS A	0.5	3.9	0.56	0.59	53.2
6	R2	54	9.8	0.088	10.7	LOS A	0.5	3.9	0.57	0.61	53.5
Approach		442	4.8	0.163	4.7	LOS A	0.5	3.9	0.17	0.48	55.5
North: Railway Parade (N)											
7	L2	319	3.0	0.747	33.0	LOS C	8.5	60.8	1.00	1.30	38.7
8	T1	4	25.0	0.613	28.7	LOS C	4.7	35.6	0.97	1.16	39.7
9	R2	181	8.7	0.613	34.0	LOS C	4.7	35.6	0.97	1.16	37.9
Approach		504	5.2	0.747	33.3	LOS C	8.5	60.8	0.99	1.25	38.5
West: Glenfield Road (W)											
10	L2	395	5.3	1.135	105.8	LOS F	39.1	287.1	1.00	2.26	20.0
11	T1	200	6.8	1.135	106.6	LOS F	39.1	287.1	1.00	2.21	20.1
12	R2	363	5.8	1.135	113.8	LOS F	32.6	239.6	1.00	2.12	19.9
Approach		958	5.8	1.135	109.0	LOS F	39.1	287.1	1.00	2.20	20.0
All Vehicles		3361	4.2	1.135	41.7	LOS C	39.1	287.1	0.80	1.24	35.2

MOVEMENT SUMMARY



Site: I-15 2030 BASE PM

Canterbury Road / Cambridge Avenue / Glenfield Road

2030 BASE PM PEAK 4:30 pm - 5:30 pm

Roundabout

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows	Deg. Satn	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h	
		Total	HV			Vehicles	Distance				
		veh/h	%			v/c	veh				m
South: Canterbury Road (S)											
1	L2	338	2.2	0.467	8.7	LOS A	3.0	21.3	0.78	0.92	51.1
2	T1	6	0.0	0.399	7.1	LOS A	2.4	17.2	0.75	0.90	51.3
3	R2	334	1.3	0.399	12.5	LOS A	2.4	17.2	0.75	0.90	51.4
Approach		678	1.7	0.467	10.6	LOS A	3.0	21.3	0.77	0.91	51.3
East: Cambridge Avenue (E)											
4	L2	1111	2.3	0.586	3.6	LOS A	0.0	0.0	0.00	0.43	56.3
5	T1	291	8.0	0.444	7.2	LOS A	3.5	24.8	0.75	0.75	52.0
6	R2	323	1.0	0.444	12.3	LOS A	3.5	24.8	0.80	0.78	52.3
Approach		1724	3.0	0.586	5.8	LOS A	3.5	24.8	0.28	0.55	54.8
North: Railway Parade (N)											
7	L2	125	1.7	0.191	7.9	LOS A	1.0	6.8	0.69	0.80	52.8
8	T1	0	0.0	0.000	0.0	NA	0.0	0.0	0.00	0.00	0.0
9	R2	240	8.3	0.294	12.7	LOS A	1.7	12.6	0.72	0.86	50.0
Approach		365	6.1	0.294	11.0	LOS A	1.7	12.6	0.71	0.84	51.0
West: Glenfield Road (W)											
10	L2	271	4.7	0.425	8.4	LOS A	2.8	19.9	0.75	0.84	51.3
11	T1	54	0.0	0.425	8.3	LOS A	2.8	19.9	0.75	0.84	53.2
12	R2	451	3.7	0.495	13.6	LOS A	3.8	27.5	0.78	0.90	49.5
Approach		775	3.8	0.495	11.4	LOS A	3.8	27.5	0.77	0.87	50.3
All Vehicles		3542	3.2	0.586	8.5	LOS A	3.8	27.5	0.52	0.72	52.7

4. On the wider road network – 2030 Future traffic with Moorebank IMT development (Full Build)

I-01 Intersection of the Hume Highway and Orange Grove Road

MOVEMENT SUMMARY



Site: I-01 2030 MIMT AM

Hume Highway / Orange Grove Road

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV %	Average Delay v/c	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	v/c	sec	Vehicles	Distance m		per veh	km/h	
NorthEast: Hume Highway (NE)											
25	T1	956	11.2	0.686	24.2	LOS B	19.7	150.8	0.84	0.77	35.8
26	R2	389	10.0	0.907	86.6	LOS F	17.0	128.8	1.00	0.94	23.8
Approach		1346	10.9	0.907	42.3	LOS C	19.7	150.8	0.89	0.82	30.0
NorthWest: Orange Grove Road (NW)											
27	L2	602	6.5	0.712	18.8	LOS B	19.5	144.4	0.54	0.81	44.8
29	R2	1342	8.5	1.000	116.3	LOS F	46.3	352.8	1.00	1.07	17.3
Approach		1945	7.9	1.052	86.1	LOS F	46.3	352.8	0.86	0.99	21.9
SouthWest: Hume Highway (SW)											
30	L2	1280	8.6	0.461	11.7	LOS A	14.5	110.3	0.34	0.70	50.1
31	T1	2186	4.9	0.805	22.9	LOS B	39.5	287.9	0.71	0.65	40.2
Approach		3466	6.3	0.805	18.7	LOS B	39.5	287.9	0.57	0.67	44.0
All Vehicles		6757	7.6	1.052	42.8	LOS D	46.3	352.8	0.72	0.79	30.8

PHASING SUMMARY



Site: I-01 2030 MIMT AM

Hume Highway / Orange Grove Road

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	84	108
Green Time (sec)	77	17	36
Yellow Time (sec)	5	4	5
All-Red Time (sec)	2	2	2
Phase Time (sec)	84	23	43
Phase Split	56 %	15 %	29 %



MOVEMENT SUMMARY



Site: I-01 2030 MIMT PM

Hume Highway / Orange Grove Road

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
NorthEast: Hume Highway (NE)											
25	T1	1766	3.5	0.922	45.3	LOS D	50.7	365.8	0.91	0.98	26.5
26	R2	816	2.8	0.958	68.1	LOS E	24.7	176.9	1.00	1.04	27.6
Approach		2582	3.3	0.958	52.5	LOS D	50.7	365.8	0.94	1.00	27.0
NorthWest: Orange Grove Road (NW)											
27	L2	391	4.3	0.366	12.4	LOS A	6.7	48.7	0.27	0.64	49.3
29	R2	1387	5.1	1.087	151.4	LOS F	59.4	440.3	1.00	1.18	14.3
Approach		1777	4.9	1.087	120.9	LOS F	59.4	440.3	0.84	1.06	17.3
SouthWest: Hume Highway (SW)											
30	L2	1308	5.0	0.780	19.7	LOS B	20.6	152.9	0.80	0.84	44.7
31	T1	1091	5.5	0.982	90.8	LOS F	38.5	282.8	1.00	1.14	17.7
Approach		2399	5.2	0.982	52.0	LOS D	38.5	282.8	0.89	0.98	28.1
All Vehicles		6758	4.4	1.087	70.3	LOS E	59.4	440.3	0.90	1.01	23.4

PHASING SUMMARY



Site: I-01 2030 MIMT PM


Hume Highway / Orange Grove Road

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C	D
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	53	80	124
Green Time (sec)	47	20	38	19
Yellow Time (sec)	5	4	5	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	54	26	45	25
Phase Split	36 %	17 %	30 %	17 %



I-02 Intersection of the Hume Highway and Elizabeth Drive

MOVEMENT SUMMARY



Site: I-02 2030 MIMT AM

Hume Highway / Elizabeth Drive

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles										
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c sec	Level of Service	95% Back of Queue Vehicles veh	Prop. Queued Distance m	Effective Stop Rate per veh	Average Speed km/h	
South: Hume Highway (S)										
1	L2	137	5.4	0.155	22.6	LOS B	3.7	27.3	0.40	0.68
2	T1	2384	7.6	0.968	67.4	LOS E	71.2	534.9	0.99	1.07
Approach		2521	7.4	0.988	65.0	LOS E	71.2	534.9	0.95	1.05
East: Elizabeth Drive (E)										
4	L2	39	5.4	0.426	59.6	LOS E	10.5	77.4	0.91	0.82
5	T1	502	5.7	0.426	55.8	LOS D	11.9	87.2	0.90	0.82
6	R2	156	2.7	0.754	78.2	LOS F	11.7	83.5	1.00	0.87
Approach		697	5.0	0.754	61.0	LOS E	11.9	87.2	0.92	0.83
North: Hume Highway (N)										
7	L2	82	2.6	0.645	25.8	LOS B	23.8	181.6	0.60	0.58
8	T1	1749	10.1	0.645	19.7	LOS B	24.1	185.8	0.59	0.55
9	R2	353	9.6	1.170	248.6	LOS F	25.1	189.8	1.00	1.38
Approach		2184	9.8	1.170	56.9	LOS E	25.1	189.8	0.66	0.68
West: Elizabeth Drive (W)										
10	L2	627	5.2	1.011	108.6	LOS F	62.6	457.9	1.00	1.06
11	T1	1089	3.0	1.050	135.4	LOS F	59.4	426.7	1.00	1.34
12	R2	515	7.0	1.126	374.7	LOS F	60.4	450.4	1.00	1.59
Approach		2232	4.5	1.126	183.1	LOS F	62.6	457.9	1.00	1.32
All Vehicles		7634	7.0	1.170	96.8	LOS F	71.2	534.9	0.88	1.01

PHASING SUMMARY



Site: I-02 2030 MIMT AM


Hume Highway / Elizabeth Drive

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	D	F	A	E
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	66	89	131
Green Time (sec)	60	17	36	13
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	66	23	42	19
Phase Split	44 %	15 %	28 %	13 %



MOVEMENT SUMMARY



Site: I-02 2030 MIMT PM

Hume Highway / Elizabeth Drive

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Hume Highway (S)											
1	L2	320	5.4	0.473	39.8	LOS C	15.0	110.9	0.69	0.78	28.3
2	T1	1533	6.7	0.924	66.5	LOS E	42.8	321.2	0.98	1.01	18.7
Approach		1853	6.5	0.924	61.9	LOS E	42.8	321.2	0.93	0.97	20.0
East: Elizabeth Drive (E)											
4	L2	128	0.8	0.984	107.9	LOS F	33.6	239.2	1.00	1.16	12.0
5	T1	1082	2.3	0.984	104.0	LOS F	42.8	305.9	1.00	1.19	15.2
6	R2	172	0.0	1.066	165.1	LOS F	19.6	137.4	1.00	1.29	8.2
Approach		1382	1.9	1.066	112.0	LOS F	42.8	305.9	1.00	1.20	13.7
North: Hume Highway (N)											
7	L2	66	4.8	0.876	25.9	LOS B	43.9	321.2	0.74	0.73	31.8
8	T1	2477	4.2	0.876	20.0	LOS B	44.6	326.5	0.74	0.72	35.9
9	R2	961	3.0	0.917	76.9	LOS F	37.9	271.9	1.00	0.96	19.4
Approach		3504	3.8	0.917	35.7	LOS C	44.6	326.5	0.81	0.78	28.3
West: Elizabeth Drive (W)											
10	L2	325	5.8	0.434	34.2	LOS C	13.6	100.2	0.62	0.76	29.6
11	T1	529	4.4	0.698	61.8	LOS E	17.6	127.6	0.96	0.82	20.9
12	R2	309	2.4	0.978	112.9	LOS F	14.4	102.8	1.00	1.08	14.6
Approach		1164	4.2	0.978	67.6	LOS E	17.6	127.6	0.88	0.87	20.2
All Vehicles		7903	4.2	1.066	59.9	LOS E	44.6	326.5	0.88	0.91	21.0

PHASING SUMMARY



Site: I-02 2030 MIMT PM


Hume Highway / Elizabeth Drive

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	D	F	A	E
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	53	72	108
Green Time (sec)	47	13	30	36
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	53	19	36	42
Phase Split	35 %	13 %	24 %	28 %



I-03 Intersection of the Hume Highway and Memorial Avenue

MOVEMENT SUMMARY



Site: I-03 2030 MIMT AM

Hume Highway / Memorial Avenue

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Hume Highway (S)											
1	L2	157	1.3	0.975	75.2	LOS F	72.7	543.0	1.00	1.10	25.5
2	T1	2128	8.3	0.975	67.0	LOS E	73.9	559.0	0.94	1.06	23.6
3	R2	267	0.0	1.137	222.0	LOS F	36.2	253.5	1.00	1.30	9.4
Approach		2553	7.0	1.137	83.7	LOS F	73.9	559.0	0.95	1.09	20.6
East: Memorial Avenue (E)											
4	L2	29	28.6	1.264	333.5	LOS F	29.0	222.7	1.00	1.72	6.7
5	T1	164	7.7	1.264	328.8	LOS F	29.0	222.7	1.00	1.71	6.6
6	R2	134	18.1	1.264	333.8	LOS F	26.0	208.4	1.00	1.69	4.7
Approach		327	13.8	1.264	331.2	LOS F	29.0	222.7	1.00	1.71	5.8
North: Hume Highway (N)											
7	L2	121	6.1	0.103	12.4	LOS A	2.6	19.4	0.36	0.64	39.4
8	T1	1756	12.8	0.756	28.5	LOS B	32.4	254.3	0.74	0.67	36.3
9	R2	101	3.1	0.439	72.0	LOS F	7.0	50.1	0.97	0.79	21.4
Approach		1978	11.9	0.756	29.7	LOS C	32.4	254.3	0.73	0.68	35.1
West: Memorial Avenue (W)											
10	L2	128	3.3	1.179	239.8	LOS F	47.4	337.9	1.00	1.57	9.0
11	T1	460	1.6	1.179	242.8	LOS F	59.1	421.5	1.00	1.62	8.5
12	R2	164	3.2	1.179	254.5	LOS F	59.1	421.5	1.00	1.68	10.9
Approach		752	2.2	1.179	244.8	LOS F	59.1	421.5	1.00	1.62	9.1
All Vehicles		5610	8.5	1.264	100.7	LOS F	73.9	559.0	0.88	1.05	17.8

PHASING SUMMARY



Site: I-03 2030 MIMT AM


Hume Highway / Memorial Avenue

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	F
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	75	108	125
Green Time (sec)	69	27	11	19
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	75	33	17	25
Phase Split	50 %	22 %	11 %	17 %



MOVEMENT SUMMARY



Site: I-03 2030 MIMT PM

Hume Highway / Memorial Avenue

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	119	0.9	0.822	47.2	LOS D	36.9	274.1	0.91	0.86	32.2
2	T1	1639	7.2	0.822	39.2	LOS C	37.6	283.2	0.87	0.81	31.5
3	R2	116	0.0	0.779	84.5	LOS F	8.9	62.5	1.00	0.87	19.4
Approach		1874	6.4	0.822	42.5	LOS D	37.6	283.2	0.88	0.82	30.4
East: Memorial Avenue (E)											
4	L2	55	0.0	1.228	299.2	LOS F	46.0	326.8	1.00	1.82	7.4
5	T1	289	2.2	1.228	294.7	LOS F	46.0	326.8	1.00	1.79	7.2
6	R2	211	6.0	1.228	299.7	LOS F	42.5	310.9	1.00	1.68	5.2
Approach		555	3.4	1.228	297.1	LOS F	46.0	326.8	1.00	1.75	6.5
North: Hume Highway (N)											
7	L2	152	2.8	0.090	8.4	LOS A	2.0	14.7	0.24	0.61	43.5
8	T1	2958	3.8	0.939	20.9	LOS B	65.2	474.9	0.69	0.69	40.6
9	R2	214	2.0	0.729	42.6	LOS D	9.2	65.3	1.00	0.83	28.2
Approach		3323	3.7	0.939	21.7	LOS B	65.2	474.9	0.69	0.70	39.5
West: Memorial Avenue (W)											
10	L2	82	1.3	0.947	94.0	LOS F	17.8	125.8	1.00	1.14	18.3
11	T1	209	1.0	0.947	90.9	LOS F	22.1	155.1	1.00	1.12	17.5
12	R2	171	0.0	0.947	98.0	LOS F	22.1	155.1	1.00	1.09	21.4
Approach		462	0.7	0.947	94.1	LOS F	22.1	155.1	1.00	1.11	19.2
All Vehicles		6214	4.2	1.228	57.9	LOS E	65.2	474.9	0.80	0.86	25.2

PHASING SUMMARY



Site: I-03 2030 MIMT PM


Hume Highway / Memorial Avenue

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	D	E	F
Reference Phase	Yes	No	No	No	No
Phase Change Time (sec)	0	67	81	108	132
Green Time (sec)	61	8	21	18	12
Yellow Time (sec)	4	4	4	4	4
All-Red Time (sec)	2	2	2	2	2
Phase Time (sec)	67	14	27	24	18
Phase Split	45 %	9 %	18 %	16 %	12 %



I-04 Intersection of the Hume Highway and Hoxton Park Drive

MOVEMENT SUMMARY



Site: I-04 2030 MIMT AM

Hume Highway / Hoxton Park Road / Macquarie Street

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c sec	Level of Service	95% Back of Queue Vehicles veh	Prop. Queued Distance m	Effective Stop Rate per veh	Average Speed km/h		
South: Hume Highway (S)											
1	L2	109	12.7	0.096	8.8	LOS A	0.9	7.2	0.13	0.57	50.6
2	T1	2153	6.3	0.847	31.0	LOS C	43.8	326.0	0.83	0.77	38.1
3	R2	1213	1.9	1.079	138.0	LOS F	52.5	373.6	1.00	1.22	13.8
Approach		3474	4.9	1.079	67.7	LOS E	52.5	373.6	0.87	0.92	25.3
East: Macquarie Street (E)											
4	L2	361	5.8	0.230	21.3	LOS B	5.5	40.4	0.66	0.73	39.0
5	T1	545	4.6	1.080	170.2	LOS F	32.6	237.6	1.00	1.38	13.2
Approach		906	5.1	1.080	110.9	LOS F	32.6	237.6	0.86	1.12	17.4
North: Hume Highway (N)											
7	L2	236	15.6	1.004	61.0	LOS E	47.8	373.0	1.00	1.05	25.9
8	T1	1468	10.0	1.004	94.7	LOS F	58.7	452.7	1.00	1.16	21.7
9	R2	246	19.2	1.257	327.7	LOS F	41.2	336.2	1.00	1.59	9.2
Approach		1950	11.9	1.257	120.1	LOS F	58.7	452.7	1.00	1.20	18.5
West: Hoxton Park Road (W)											
10	L2	345	18.0	0.583	47.3	LOS D	20.3	164.2	0.87	0.83	32.5
11	T1	1372	4.8	1.131	228.0	LOS F	69.0	502.7	1.00	1.64	10.4
12	R2	390	4.6	1.138	175.3	LOS F	28.7	209.7	1.00	1.24	14.4
Approach		2107	6.9	1.138	188.6	LOS F	69.0	502.7	0.98	1.44	12.8
All Vehicles		8437	7.1	1.257	114.6	LOS F	69.0	502.7	0.92	1.14	18.3

PHASING SUMMARY



Site: I-04 2030 MIMT AM


Hume Highway / Hoxton Park Road / Macquarie Street

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	E	D	F
Reference Phase	Yes	No	No	No	No
Phase Change Time (sec)	0	49	77	100	126
Green Time (sec)	43	22	17	20	18
Yellow Time (sec)	4	4	4	4	4
All-Red Time (sec)	2	2	2	2	2
Phase Time (sec)	49	28	23	26	24
Phase Split	33 %	19 %	15 %	17 %	16 %



MOVEMENT SUMMARY



Site: I-04 2030 MIMT PM

Hume Highway / Hoxton Park Road / Macquarie Street

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	199	6.7	0.170	9.6	LOS A	2.0	15.3	0.16	0.59	50.2
2	T1	1592	7.2	0.639	24.1	LOS B	24.9	187.5	0.64	0.57	41.5
3	R2	448	1.2	0.934	95.5	LOS F	19.1	135.2	1.00	1.00	18.1
Approach		2240	6.0	0.934	37.1	LOS C	24.9	187.5	0.67	0.66	34.8
East: Macquarie Street (E)											
4	L2	785	1.5	1.024	163.1	LOS F	39.7	281.3	0.98	1.11	12.1
5	T1	706	3.3	1.087	167.6	LOS F	41.8	300.7	1.00	1.39	13.3
Approach		1492	2.3	1.087	165.2	LOS F	41.8	300.7	0.99	1.24	12.7
North: Hume Highway (N)											
7	L2	101	5.2	0.967	36.9	LOS C	77.7	565.2	0.95	1.01	34.8
8	T1	2841	3.6	0.967	32.1	LOS C	78.9	574.2	0.84	0.89	37.6
9	R2	283	6.3	1.406	459.4	LOS F	56.5	417.3	1.00	1.82	6.9
Approach		3225	3.9	1.406	69.7	LOS E	78.9	574.2	0.85	0.98	26.2
West: Hoxton Park Road (W)											
10	L2	252	4.2	0.395	44.4	LOS D	13.7	99.2	0.80	0.80	33.6
11	T1	717	4.3	0.439	46.6	LOS D	14.2	102.8	0.87	0.73	30.4
12	R2	388	3.6	1.262	259.3	LOS F	35.2	256.7	1.00	1.43	10.5
Approach		1356	4.1	1.262	107.0	LOS F	35.2	256.7	0.89	0.94	19.6
All Vehicles		8312	4.2	1.406	84.2	LOS F	78.9	574.2	0.83	0.93	22.7

PHASING SUMMARY



Site: I-04 2030 MIMT PM


Hume Highway / Hoxton Park Road / Macquarie Street

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	E	D	F
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	78	98	127
Green Time (sec)	72	14	23	17
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	78	20	29	23
Phase Split	52 %	13 %	19 %	15 %



I-05 Intersection of the Hume Highway and Reilly Street

MOVEMENT SUMMARY



Site: I-05 2030 MIMT AM

Hume Highway / Reilly Street

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Hume Highway (S)											
1	L2	80	2.6	0.942	33.9	LOS C	73.7	538.9	0.86	0.88	35.3
2	T1	3174	4.5	0.942	27.7	LOS B	73.7	538.9	0.79	0.82	34.9
3	R2	14	7.7	0.108	23.7	LOS B	0.5	3.7	0.50	0.67	36.5
Approach		3267	4.5	0.942	27.8	LOS B	73.7	538.9	0.79	0.82	34.9
East: Congressional Drive (E)											
4	L2	49	2.1	0.263	59.1	LOS E	5.9	42.6	0.89	0.74	24.5
5	T1	46	4.5	0.263	54.5	LOS D	5.9	42.6	0.89	0.74	24.0
6	R2	91	4.7	0.428	67.2	LOS E	6.1	44.6	0.95	0.79	18.7
Approach		186	4.0	0.428	61.9	LOS E	6.1	44.6	0.92	0.76	21.6
North: Hume Highway (N)											
7	L2	32	3.3	0.560	18.0	LOS B	21.9	167.2	0.53	0.57	39.3
8	T1	1856	9.1	0.560	11.1	LOS A	25.1	191.8	0.50	0.49	46.5
9	R2	99	1.1	0.772	60.4	LOS E	6.1	43.2	1.00	0.93	22.5
Approach		1986	8.6	0.772	13.7	LOS A	25.1	191.8	0.53	0.51	44.0
West: Reilly Street (W)											
10	L2	120	3.5	0.274	50.3	LOS D	7.6	55.2	0.83	0.76	24.5
11	T1	14	7.7	0.274	45.7	LOS D	7.6	55.2	0.83	0.76	25.6
12	R2	234	1.3	1.028	147.6	LOS F	25.7	182.2	1.00	1.21	14.7
Approach		368	2.3	1.028	112.1	LOS F	25.7	182.2	0.94	1.04	16.8
All Vehicles		5808	5.7	1.028	29.4	LOS C	73.7	538.9	0.71	0.73	33.9

PHASING SUMMARY



Site: I-05 2030 MIMT AM


Hume Highway / Reilly Street

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E2
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	100	138
Green Time (sec)	94	32	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	100	38	12
Phase Split	67 %	25 %	8 %



MOVEMENT SUMMARY



Site: I-05 2030 MIMT PM

Hume Highway / Reilly Street

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	224	0.5	0.670	19.8	LOS B	26.3	193.0	0.53	0.57	41.8
2	T1	2053	6.2	0.670	11.7	LOS A	26.3	193.0	0.46	0.45	45.6
3	R2	21	5.0	0.392	30.4	LOS C	1.0	7.5	0.62	0.73	33.4
Approach		2298	5.7	0.670	12.7	LOS A	26.3	193.0	0.47	0.46	45.0
East: Congressional Drive (E)											
4	L2	42	2.5	0.205	61.9	LOS E	4.2	29.6	0.90	0.73	23.8
5	T1	24	0.0	0.205	57.3	LOS E	4.2	29.6	0.90	0.73	23.3
6	R2	52	0.0	0.236	65.6	LOS E	3.4	23.6	0.92	0.75	19.1
Approach		118	0.9	0.236	62.6	LOS E	4.2	29.6	0.91	0.74	21.7
North: Hume Highway (N)											
7	L2	67	0.0	0.989	40.8	LOS C	100.8	728.5	0.82	0.94	27.0
8	T1	3699	3.1	0.989	36.9	LOS C	100.8	728.5	0.62	0.76	30.6
9	R2	178	1.2	0.802	57.1	LOS E	11.6	82.2	1.00	1.01	23.3
Approach		3944	3.0	0.989	37.9	LOS C	100.8	728.5	0.64	0.77	30.1
West: Reilly Street (W)											
10	L2	65	0.0	0.235	56.1	LOS D	5.8	40.6	0.86	0.74	23.5
11	T1	32	0.0	0.235	51.6	LOS D	5.8	40.6	0.86	0.74	24.5
12	R2	261	1.6	1.120	214.2	LOS F	35.0	248.2	1.00	1.37	11.0
Approach		358	1.2	1.120	171.0	LOS F	35.0	248.2	0.96	1.20	12.6
All Vehicles		6718	3.8	1.120	36.8	LOS C	100.8	728.5	0.61	0.69	30.7

PHASING SUMMARY



Site: I-05 2030 MIMT PM


Hume Highway / Reilly Street

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E2
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	98	133
Green Time (sec)	92	29	11
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	98	35	17
Phase Split	65 %	23 %	11 %



I-06 Intersection of Newbridge Road and Moorebank Avenue

MOVEMENT SUMMARY



Site: I-06 2030 MIMT AM



Network: 2030 MIMT AM

Newbridge Road / Moorebank Avenue

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo	Demand Flows		Arrival Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV	Total	HV				Vehicles	Distance			
	veh/h	%	veh/h	%	v/c				sec	veh			
South: Moorebank Avenue (S)													
1	L2	1534	3.1	1233	3.2	0.637	19.0	LOS B	13.7	98.5	0.57	0.82	42.2
3	R2	1401	11.3	1129	11.6	0.683	15.2	LOS B	14.4	112.9	0.43	0.69	52.4
Approach		2935	7.0	2362 ^{N1}	7.2	0.683	17.2	LOS B	14.4	112.9	0.50	0.76	47.8
East: Newbridge Road (E)													
4	L2	707	21.6	707	21.6	0.637	19.2	LOS B	9.3	78.2	0.75	0.81	51.4
5	T1	965	5.1	965	5.1	1.260	311.5	LOS F	77.3	564.9	1.00	1.91	14.7
Approach		1673	12.1	1673	12.1	1.260	187.9	LOS F	77.3	564.9	0.90	1.44	19.0
West: Newbridge Road (W)													
11	T1	1581	6.5	1581	6.5	0.852	12.4	LOS A	30.8	227.8	0.63	0.60	60.9
12	R2	874	7.7	874	7.7	1.671	660.9	LOS F	98.1	732.8	1.00	1.98	3.1
Approach		2455	6.9	2455	6.9	1.671	243.2	LOS F	98.1	732.8	0.76	1.09	14.6
All Vehicles		7062	8.2	6489 ^{N1}	8.9	1.671	146.7	LOS F	98.1	732.8	0.70	1.06	19.9

PHASING SUMMARY



Site: I-06 2030 MIMT AM



Network: 2030 MIMT AM


Newbridge Road / Moorebank Avenue

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C	D
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	33	55	116
Green Time (sec)	27	16	55	11
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	33	22	61	17
Phase Split	25 %	17 %	46 %	13 %



MOVEMENT SUMMARY



Site: I-06 2030 MIMT PM



Network: 2030 MIMT PM

Newbridge Road / Moorebank Avenue

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 116 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	HV %	Arrival Flows Total veh/h	HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)													
1	L2	1002	2.9	888	3.1	0.506	22.5	LOS B	13.2	94.5	0.57	0.75	39.9
3	R2	965	11.5	859	12.0	1.130	176.4	LOS F	16.7	130.6	1.00	1.39	16.8
Approach		1966	7.1	1747 ^{N1}	7.4	1.130	98.1	LOS F	16.7	130.6	0.78	1.06	21.6
East: Newbridge Road (E)													
4	L2	1274	7.4	1274	7.4	1.114	196.1	LOS F	80.2	605.8	1.00	1.32	14.7
5	T1	1373	4.8	1373	4.8	0.923	51.1	LOS D	42.7	311.4	1.00	1.04	43.3
Approach		2647	6.1	2647	6.1	1.114	120.9	LOS F	80.2	605.8	1.00	1.17	25.2
West: Newbridge Road (W)													
11	T1	1129	4.0	1129	4.0	0.442	9.3	LOS A	14.6	105.8	0.50	0.45	62.9
12	R2	1120	2.8	1120	2.8	1.201	234.1	LOS F	75.0	537.8	1.00	1.47	8.2
Approach		2249	3.4	2249	3.4	1.201	121.3	LOS F	75.0	537.8	0.75	0.96	22.4
All Vehicles		6862	5.5	6643 ^{N1}	5.7	1.201	115.0	LOS F	80.2	605.8	0.86	1.07	23.4

PHASING SUMMARY



Site: I-06 2030 MIMT PM



Network: 2030 MIMT PM


Newbridge Road / Moorebank Avenue

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 116 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	44	76
Green Time (sec)	38	26	34
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	44	32	40
Phase Split	38 %	28 %	34 %



I-07 Intersection of Moorebank Avenue and Heathcote Road

MOVEMENT SUMMARY



Site: I-07 2030 MIMT AM



Network: 2030 MIMT AM

Moorebank Avenue / Heathcote Road

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Arrival Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV	Total	HV				Vehicles	Distance			
		veh/h	%	veh/h	%				veh	m			
South: Moorebank Avenue (S)													
2	T1	1949	7.0	1768	7.1	1.167	197.8	LOS F	58.4	440.6	1.00	1.86	4.8
3	R2	23	18.2	21	18.4	0.190	71.8	LOS F	1.4	11.0	0.98	0.71	30.6
Approach		1972	7.2	1789 ^{N1}	7.3	1.167	196.3	LOS F	58.4	440.6	1.00	1.85	5.1
East: Heathcote Road (E)													
4	L2	29	57.1	29	57.1	1.441	481.7	LOS F	102.1	768.9	1.00	1.95	6.8
6	R2	952	5.9	952	5.9	1.441	481.5	LOS F	102.1	768.9	1.00	1.95	6.8
Approach		981	7.4	981	7.4	1.441	481.5	LOS F	102.1	768.9	1.00	1.95	6.8
North: Moorebank Avenue (N)													
7	L2	795	7.9	618	8.9	0.383	10.7	LOS A	12.3	92.8	0.54	0.71	51.4
8	T1	813	19.2	643	21.4	0.377	21.4	LOS B	12.6	106.4	0.66	0.57	13.1
Approach		1608	13.6	1261 ^{N1}	15.3	0.383	16.2	LOS B	12.6	106.4	0.60	0.64	41.1
All Vehicles		4561	9.5	4031 ^{N1}	10.7	1.441	209.4	LOS F	102.1	768.9	0.87	1.49	8.4

PHASING SUMMARY



Site: I-07 2030 MIMT AM



Network: 2030 MIMT AM


Moorebank Avenue / Heathcote Road

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Phase Timing Results

Phase	B	A	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	15	88
Green Time (sec)	9	67	39
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	15	73	45
Phase Split	11 %	55 %	34 %



MOVEMENT SUMMARY



Site: I-07 2030 MIMT PM



Network: 2030 MIMT PM

Moorebank Avenue / Heathcote Road

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 116 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	HV %	Arrival Flows Total veh/h	HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)													
2	T1	1184	9.4	1184	9.4	0.938	56.1	LOS D	48.7	372.7	0.95	1.16	14.2
3	R2	48	8.7	48	8.7	0.401	64.7	LOS E	2.8	20.9	1.00	0.74	32.2
Approach		1233	9.3	1233	9.3	0.938	56.5	LOS D	48.7	372.7	0.95	1.14	15.5
East: Heathcote Road (E)													
4	L2	76	19.4	76	19.4	1.415	430.1	LOS F	93.1	692.3	1.00	1.99	7.5
6	R2	812	5.2	812	5.2	1.415	429.4	LOS F	93.1	692.3	1.00	1.99	7.5
Approach		887	6.4	887	6.4	1.415	429.4	LOS F	93.1	692.3	1.00	1.99	7.5
North: Moorebank Avenue (N)													
7	L2	884	3.7	767	3.7	0.362	7.5	LOS A	5.1	36.8	0.24	0.61	53.8
8	T1	1484	6.1	1288	6.2	0.670	6.3	LOS A	11.8	87.9	0.35	0.32	29.3
Approach		2369	5.2	2054 ^{N1}	5.3	0.670	6.7	LOS A	11.8	87.9	0.31	0.43	48.5
All Vehicles		4489	6.6	4174 ^{N1}	7.1	1.415	111.3	LOS F	93.1	692.3	0.65	0.97	13.7

PHASING SUMMARY



Site: I-07 2030 MIMT PM



Network: 2030 MIMT PM


Moorebank Avenue / Heathcote Road

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 116 seconds (User-Given Phase Times)

Phase Timing Results

Phase	B	A	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	14	80
Green Time (sec)	8	60	30
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	14	66	36
Phase Split	12 %	57 %	31 %



I-08 Intersection of Moorebank Avenue and Industry Park Access

MOVEMENT SUMMARY



Site: I-08 2030 MIMT AM



Network: 2030 MIMT AM

Moorebank Avenue / Industry Park Access

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Arrival Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
		Total veh/h	HV %	Total veh/h	HV %	v/c	sec		Vehicles veh	Distance m		per veh	km/h
South: Moorebank Avenue (S)													
1	L2	90	3.1	90	3.1	0.055	6.1	LOS A	0.4	2.6	0.12	0.58	43.1
2	T1	1930	6.5	1930	6.5	1.259	295.3	LOS F	169.8	1273.9	1.00	2.23	5.5
Approach		2020	6.3	2020	6.3	1.259	282.4	LOS F	169.8	1273.9	0.96	2.16	5.8
North: Moorebank Avenue (N)													
8	T1	725	18.8	572	20.7	0.204	2.5	LOS A	3.8	31.6	0.22	0.20	56.9
9	R2	65	38.7	53	41.4	0.998	109.1	LOS F	4.4	42.0	1.00	1.03	12.3
Approach		790	20.4	624 ^{N1}	22.5	0.998	11.5	LOS A	4.4	42.0	0.29	0.27	46.9
West: Industry Park Access (W)													
10	L2	34	62.5	34	62.5	0.415	64.9	LOS E	2.3	24.3	0.95	0.73	9.6
12	R2	58	72.7	58	72.7	0.412	68.0	LOS E	2.7	31.3	0.98	0.73	19.8
Approach		91	68.9	91	68.9	0.415	66.9	LOS E	2.7	31.3	0.97	0.73	16.8
All Vehicles		2902	12.1	2736 ^{N1}	12.9	1.259	213.4	LOS F	169.8	1273.9	0.81	1.68	8.2

PHASING SUMMARY



Site: I-08 2030 MIMT AM



Network: 2030 MIMT AM


Moorebank Avenue / Industry Park Access

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C
Reference Phase	Yes	No
Phase Change Time (sec)	0	116
Green Time (sec)	110	11
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	116	17
Phase Split	87 %	13 %



MOVEMENT SUMMARY



Site: I-08 2030 MIMT PM



Network: 2030 MIMT PM

Moorebank Avenue / Industry Park Access

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 65 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	HV %	Arrival Flows Total veh/h	HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)													
1	L2	10	27.8	10	27.8	0.009	6.8	LOS A	0.0	0.4	0.22	0.57	42.7
2	T1	1154	8.7	1154	8.7	0.473	4.9	LOS A	8.7	66.1	0.49	0.44	51.5
Approach		1164	8.9	1164	8.9	0.473	4.9	LOS A	8.7	66.1	0.49	0.44	51.4
North: Moorebank Avenue (N)													
8	T1	1558	5.8	1344	5.7	0.521	5.2	LOS A	10.2	76.2	0.52	0.47	53.9
9	R2	25	62.5	22	62.3	0.127	14.4	LOS A	0.4	3.9	0.50	0.67	32.8
Approach		1583	6.7	1366 ^{N1}	6.6	0.521	5.3	LOS A	10.2	76.2	0.52	0.47	53.6
West: Industry Park Access (W)													
10	L2	34	15.6	34	15.6	0.073	3.9	LOS A	0.3	2.2	0.36	0.43	26.5
12	R2	189	9.9	189	9.9	0.445	32.4	LOS C	3.0	22.8	0.97	0.76	28.1
Approach		223	10.8	223	10.8	0.445	28.1	LOS B	3.0	22.8	0.88	0.71	28.0
All Vehicles		2970	7.8	2753 ^{N1}	8.5	0.521	7.0	LOS A	10.2	76.2	0.54	0.48	49.2

PHASING SUMMARY



Site: I-08 2030 MIMT PM



Network: 2030 MIMT PM


Moorebank Avenue / Industry Park Access

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 65 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C
Reference Phase	Yes	No
Phase Change Time (sec)	0	51
Green Time (sec)	45	8
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	51	14
Phase Split	78 %	22 %



I-09 Intersection of Moorebank Avenue and Church Road

MOVEMENT SUMMARY

▽ Site: I-09 2030 MIMT AM

Moorebank Avenue / Church Road
2030 MIMT AM PEAK 7:45 am - 8:45 am
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
2	T1	2132	7.8	0.783	6.3	LOS A	12.1	91.8	0.16	0.11	53.8
3	R2	284	8.5	0.783	30.2	LOS C	12.1	91.8	1.00	0.70	38.3
Approach		2416	7.8	0.978	9.1	NA	12.1	91.8	0.25	0.18	51.3
East: Church Road (E)											
4	L2	204	15.8	0.264	7.5	LOS A	1.1	8.5	0.51	0.73	47.2
6	R2	7	0.0	0.945	878.2	LOS F	2.6	17.9	1.00	1.07	3.8
Approach		211	15.2	0.945	37.9	LOS C	2.6	17.9	0.53	0.74	33.8
North: Moorebank Avenue (N)											
7	L2	37	0.0	0.236	5.6	LOS A	0.0	0.0	0.00	0.06	57.7
8	T1	754	24.2	0.236	0.0	LOS A	0.0	0.0	0.00	0.03	59.6
Approach		791	23.0	0.236	0.3	NA	0.0	0.0	0.00	0.03	59.5
All Vehicles		3418	11.8	0.978	8.8	NA	12.1	91.8	0.21	0.18	51.3

MOVEMENT SUMMARY

▽ Site: I-09 2030 MIMT PM

Moorebank Avenue / Church Road
2030 MIMT PM PEAK 4:30 pm - 5:30 pm
Giveway / Yield (Two-Way)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	sec		veh	m		per veh	km/h	
South: Moorebank Avenue (S)											
2	T1	1190	12.3	0.664	0.2	LOS A	0.0	0.0	0.00	0.00	59.7
3	R2	111	13.6	0.667	48.9	LOS D	3.3	26.4	0.98	1.18	31.1
Approach		1301	12.4	0.667	4.3	NA	3.3	26.4	0.08	0.10	55.2
East: Church Road (E)											
4	L2	427	5.1	1.381	400.7	LOS F	89.9	660.8	1.00	5.35	7.7
6	R2	1	0.0	0.173	565.4	LOS F	0.4	2.9	1.00	1.00	5.7
Approach		428	5.1	1.381	401.1	LOS F	89.9	660.8	1.00	5.34	7.7
North: Moorebank Avenue (N)											
7	L2	14	7.7	0.934	7.4	LOS A	0.0	0.0	0.00	0.01	54.4
8	T1	1721	6.4	0.934	2.2	LOS A	0.0	0.0	0.00	0.00	55.8
Approach		1735	6.4	0.934	2.2	NA	0.0	0.0	0.00	0.00	55.8
All Vehicles		3464	8.5	1.381	52.3	NA	89.9	660.8	0.15	0.70	31.1

I-10 Intersection of Heathcote Road and Nuwarra Road

MOVEMENT SUMMARY



Site: I-10 2030 MIMT AM

Heathcote Road / Nuwarra Road / Wattle Grove Drive

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 131 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	v/c	sec	veh	m		per veh	km/h	
SouthEast: Heathcote Road (SE)											
4	L2	253	1.2	0.175	8.2	LOS A	3.4	23.8	0.27	0.63	48.2
5	T1	2073	5.2	1.255	286.2	LOS F	161.7	1183.1	1.00	2.15	10.3
6	R2	647	3.3	1.268	267.3	LOS F	42.9	308.4	1.00	1.54	11.2
Approach		2974	4.5	1.268	258.4	LOS F	161.7	1183.1	0.94	1.88	11.1
NorthEast: Nuwarra Road (NE)											
7	L2	416	4.8	0.484	24.5	LOS B	16.5	120.1	0.71	0.78	42.4
8	T1	252	8.4	0.405	53.1	LOS D	7.3	54.6	0.94	0.76	26.2
9	R2	508	5.8	1.436	477.0	LOS F	49.8	365.8	1.00	1.93	6.6
Approach		1176	6.0	1.436	226.3	LOS F	49.8	365.8	0.88	1.27	11.9
NorthWest: Heathcote Road (NW)											
10	L2	254	11.6	0.334	21.5	LOS B	7.8	60.1	0.70	0.76	42.7
11	T1	1044	11.2	0.957	54.9	LOS D	42.9	329.5	0.90	0.97	31.2
12	R2	235	6.3	0.786	75.4	LOS F	8.0	59.1	1.00	0.89	19.9
Approach		1532	10.5	0.957	52.5	LOS D	42.9	329.5	0.88	0.92	30.8
SouthWest: Wattle Grove Drive (SW)											
1	L2	639	2.1	0.849	51.8	LOS D	31.9	227.1	0.99	1.15	24.8
2	T1	543	4.5	0.817	61.8	LOS E	19.6	142.7	1.00	0.94	23.7
3	R2	263	4.0	1.277	332.6	LOS F	42.3	306.5	1.00	1.80	6.6
Approach		1445	3.4	1.277	106.7	LOS F	42.3	306.5	0.99	1.19	16.1
All Vehicles		7127	5.8	1.436	178.1	LOS F	161.7	1183.1	0.93	1.43	13.9

PHASING SUMMARY



Site: I-10 2030 MIMT AM

Heathcote Road / Nuwarra Road / Wattle Grove Drive

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 131 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	D	E	G
Reference Phase	Yes	No	No	No	No
Phase Change Time (sec)	0	54	67	86	114
Green Time (sec)	48	7	13	22	11
Yellow Time (sec)	4	4	4	4	4
All-Red Time (sec)	2	2	2	2	2
Phase Time (sec)	54	13	19	28	17
Phase Split	41 %	10 %	15 %	21 %	13 %



MOVEMENT SUMMARY



Site: I-10 2030 MIMT PM

Heathcote Road / Nuwarra Road / Wattle Grove Drive

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 139 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
SouthEast: Heathcote Road (SE)											
4	L2	337	2.5	0.282	15.4	LOS B	8.9	63.6	0.45	0.70	42.4
5	T1	1331	5.4	0.992	77.8	LOS F	59.5	435.9	0.93	1.13	26.0
6	R2	469	3.1	1.197	269.1	LOS F	34.2	246.1	1.00	1.49	11.2
Approach		2137	4.5	1.197	110.0	LOS F	59.5	435.9	0.87	1.14	20.5
NorthEast: Nuwarra Road (NE)											
7	L2	646	2.8	0.950	79.5	LOS F	47.1	337.5	1.00	1.22	26.0
8	T1	621	1.4	0.996	96.4	LOS F	29.6	209.3	1.00	1.17	18.0
9	R2	556	7.0	1.120	181.1	LOS F	35.9	266.2	1.00	1.30	14.7
Approach		1823	3.6	1.120	116.3	LOS F	47.1	337.5	1.00	1.23	18.9
NorthWest: Heathcote Road (NW)											
10	L2	258	6.1	0.232	21.3	LOS B	8.5	62.5	0.53	0.73	43.0
11	T1	1701	2.7	1.170	222.2	LOS F	119.3	854.8	1.00	1.79	12.7
12	R2	467	2.0	1.103	167.2	LOS F	28.6	203.5	1.00	1.24	11.1
Approach		2427	3.0	1.170	190.2	LOS F	119.3	854.8	0.95	1.57	13.5
SouthWest: Wattle Grove Drive (SW)											
1	L2	305	1.7	0.387	33.9	LOS C	14.1	100.1	0.76	0.85	30.6
2	T1	331	1.3	0.470	57.6	LOS E	10.2	72.3	0.95	0.78	24.7
3	R2	361	1.2	1.338	395.1	LOS F	64.9	458.6	1.00	1.87	5.6
Approach		997	1.4	1.338	172.5	LOS F	64.9	458.6	0.91	1.20	11.3
All Vehicles		7384	3.3	1.338	146.3	LOS F	119.3	854.8	0.93	1.31	16.0

PHASING SUMMARY



Site: I-10 2030 MIMT PM


Heathcote Road / Nuwarra Road / Wattle Grove Drive

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 139 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	G
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	63	89	118
Green Time (sec)	57	20	23	15
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	63	26	29	21
Phase Split	45 %	19 %	21 %	15 %



I-11 Intersection of Newbridge Road and Nuwarra Road

MOVEMENT SUMMARY



Site: I-11 2030 MIMT AM

Newbridge Road / Nuwarra Road

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand	Flows	Deg. Satn	Average	Level of	95% Back of Queue	Prop.	Effective	Average	
	v	Total	HV		Delay	Service	Vehicles	Queued	Stop Rate	Speed	
		veh/h	%	v/c	sec		veh	m	per veh	km/h	
South: Nuwarra Road (S)											
1	L2	37	8.6	0.884	63.6	LOS E	26.7	190.6	0.91	0.97	33.5
2	T1	352	1.5	0.884	60.6	LOS E	26.7	190.6	0.91	0.97	28.2
3	R2	852	6.2	1.232	301.9	LOS F	72.5	534.1	1.00	1.53	11.1
Approach		1240	4.9	1.232	226.4	LOS F	72.5	534.1	0.97	1.36	13.8
East: Newbridge Road (E)											
4	L2	347	17.0	0.644	28.2	LOS B	22.4	177.8	0.74	0.78	44.9
5	T1	1292	11.9	0.644	23.7	LOS B	23.0	178.7	0.68	0.63	51.0
Approach		1639	13.0	0.644	24.6	LOS B	23.0	178.7	0.69	0.66	49.7
North: Nuwarra Road (N)											
7	L2	8	0.0	0.986	110.2	LOS F	11.4	80.6	1.00	1.23	22.2
8	T1	154	0.7	1.232	151.9	LOS F	27.3	197.8	1.00	1.36	17.6
9	R2	141	5.2	1.232	298.4	LOS F	27.3	197.8	1.00	1.77	11.9
Approach		303	2.8	1.232	218.9	LOS F	27.3	197.8	1.00	1.54	14.3
West: Newbridge Road (W)											
10	L2	305	2.1	1.161	215.6	LOS F	119.4	892.4	1.00	1.63	15.4
11	T1	2307	9.8	1.235	242.4	LOS F	143.9	1105.1	1.00	1.89	14.8
Approach		2612	8.9	1.235	239.3	LOS F	143.9	1105.1	1.00	1.86	14.9
All Vehicles		5794	8.9	1.235	174.8	LOS F	143.9	1105.1	0.91	1.40	18.2

PHASING SUMMARY



Site: I-11 2030 MIMT AM


Newbridge Road / Nuwarra Road

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	89
Green Time (sec)	66	11	45
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	17	51
Phase Split	51 %	12 %	36 %



MOVEMENT SUMMARY



Site: I-11 2030 MIMT PM

Newbridge Road / Nuwarra Road

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Nuwarra Road (S)											
1	L2	58	7.3	0.774	71.3	LOS F	14.9	106.5	1.00	0.90	31.8
2	T1	157	0.7	0.774	66.9	LOS E	14.9	106.5	1.00	0.90	28.9
3	R2	568	6.3	1.017	126.5	LOS F	28.1	207.3	1.00	1.13	21.3
Approach		783	5.2	1.017	110.5	LOS F	28.1	207.3	1.00	1.07	23.1
East: Newbridge Road (E)											
4	L2	766	3.8	0.789	18.3	LOS B	33.3	242.9	0.59	0.79	50.1
5	T1	2233	6.2	0.789	16.6	LOS B	40.9	304.1	0.67	0.65	55.4
Approach		3000	5.6	0.789	17.0	LOS B	40.9	304.1	0.65	0.68	54.1
North: Nuwarra Road (N)											
7	L2	18	0.0	0.876	76.8	LOS F	18.0	127.2	1.00	1.02	28.9
8	T1	296	1.1	1.094	100.2	LOS F	33.9	240.3	1.00	1.11	23.6
9	R2	213	1.5	1.094	190.2	LOS F	33.9	240.3	1.00	1.39	17.1
Approach		526	1.2	1.094	135.8	LOS F	33.9	240.3	1.00	1.22	20.4
West: Newbridge Road (W)											
10	L2	102	0.0	0.547	21.6	LOS B	17.6	131.3	0.51	0.52	48.4
11	T1	1687	8.4	0.622	14.8	LOS B	20.5	154.7	0.50	0.47	56.9
Approach		1789	7.9	0.622	15.1	LOS B	20.5	154.7	0.50	0.47	56.3
All Vehicles		6098	5.8	1.094	38.7	LOS C	40.9	304.1	0.68	0.72	42.0

PHASING SUMMARY



Site: I-11 2030 MIMT PM


Newbridge Road / Nuwarra Road

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	84	112
Green Time (sec)	78	22	22
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	84	28	28
Phase Split	60 %	20 %	20 %



I-12 Intersection of Newbridge Road and Governor Macquarie Drive

MOVEMENT SUMMARY



Site: I-12 2030 MIMT AM

Newbridge Road / Governor Macquarie Drive

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay v/c	Level of Service sec	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate per veh	Average Speed km/h		
South: Brickmakers Drive (S)											
1	L2	14	0.0	0.909	84.6	LOS F	17.3	122.1	1.00	1.07	24.1
2	T1	207	1.0	0.909	80.3	LOS F	17.3	122.1	1.00	1.07	23.8
3	R2	720	1.2	1.239	301.6	LOS F	55.9	395.6	1.00	1.68	12.6
Approach		941	1.1	1.239	249.7	LOS F	55.9	395.6	1.00	1.53	13.8
East: Newbridge Road (E)											
4	L2	242	3.0	0.178	7.9	LOS A	2.2	15.7	0.19	0.64	58.1
5	T1	1472	11.5	0.432	14.0	LOS A	16.7	129.5	0.55	0.49	59.9
6	R2	683	9.9	1.050	154.1	LOS F	36.1	274.4	1.00	1.16	23.9
Approach		2398	10.2	1.050	53.3	LOS D	36.1	274.4	0.64	0.70	41.5
North: Governor Macquarie Drive (N)											
7	L2	765	7.8	0.725	52.8	LOS D	23.4	174.6	0.96	0.86	40.2
8	T1	135	2.3	0.546	64.2	LOS E	8.8	62.9	0.99	0.79	27.0
9	R2	178	31.9	1.030	138.6	LOS F	18.2	162.2	1.00	1.18	20.4
Approach		1078	11.1	1.030	68.4	LOS E	23.4	174.6	0.97	0.90	34.3
West: Newbridge Road (W)											
10	L2	132	29.9	1.224	268.0	LOS F	160.8	1235.1	1.00	1.91	12.9
11	T1	3009	7.4	1.224	260.5	LOS F	165.2	1241.2	1.00	1.95	16.8
12	R2	5	20.0	0.045	33.0	LOS C	0.2	1.8	0.60	0.68	37.8
Approach		3147	8.4	1.224	260.5	LOS F	165.2	1241.2	1.00	1.95	16.7
All Vehicles		7563	8.4	1.239	166.1	LOS F	165.2	1241.2	0.88	1.35	22.1

PHASING SUMMARY



Site: I-12 2030 MIMT AM


Newbridge Road / Governor Macquarie Drive

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	G1
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	66	88	112
Green Time (sec)	60	16	18	22
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	66	22	24	28
Phase Split	47 %	16 %	17 %	20 %



MOVEMENT SUMMARY



Site: I-12 2030 MIMT PM

Newbridge Road / Governor Macquarie Drive

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Brickmakers Drive (S)											
1	L2	11	0.0	0.554	70.4	LOS E	7.2	52.4	1.00	0.79	26.8
2	T1	97	5.4	0.554	66.3	LOS E	7.2	52.4	1.00	0.79	26.5
3	R2	271	0.8	0.641	70.4	LOS E	9.1	64.3	1.00	0.81	32.5
Approach		378	1.9	0.641	69.3	LOS E	9.1	64.3	1.00	0.81	31.0
East: Newbridge Road (E)											
4	L2	688	1.4	0.485	9.5	LOS A	8.3	58.6	0.29	0.70	57.0
5	T1	2766	5.0	0.932	32.3	LOS C	55.3	406.6	0.76	0.79	50.3
6	R2	744	10.3	1.124	214.3	LOS F	48.3	368.3	1.00	1.29	19.1
Approach		4198	5.3	1.124	60.8	LOS E	55.3	406.6	0.73	0.86	39.2
North: Governor Macquarie Drive (N)											
7	L2	614	7.9	0.463	46.7	LOS D	16.6	124.4	0.86	0.81	42.0
8	T1	314	1.7	1.055	145.7	LOS F	32.6	231.3	1.00	1.33	16.2
9	R2	305	35.9	1.604	632.9	LOS F	70.2	645.6	1.00	2.02	6.1
Approach		1233	13.3	1.604	217.1	LOS F	70.2	645.6	0.93	1.24	16.2
West: Newbridge Road (W)											
10	L2	174	15.2	0.856	45.6	LOS D	44.7	336.7	0.93	0.88	39.2
11	T1	2062	5.8	0.856	37.6	LOS C	45.4	335.3	0.91	0.86	47.9
12	R2	4	0.0	0.070	55.3	LOS D	0.2	1.7	0.80	0.69	30.0
Approach		2241	6.5	0.856	38.2	LOS C	45.4	336.7	0.91	0.86	47.3
All Vehicles		8050	6.7	1.604	78.9	LOS F	70.2	645.6	0.82	0.92	34.0

PHASING SUMMARY



Site: I-12 2030 MIMT PM


Newbridge Road / Governor Macquarie Drive

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 140 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	G1
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	64	86	107
Green Time (sec)	58	16	15	27
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	64	22	21	33
Phase Split	46 %	16 %	15 %	24 %



I-13 Intersection of Moorebank Avenue and M5 Motorway

MOVEMENT SUMMARY



Site: I-13 2030 MIMT AM

Moorebank Avenue / the M5 Motorway

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 74 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles	Distance			
		veh/h	%				veh	m			
South: Moorebank Avenue (S)											
1	L2	398	36.2	0.438	10.4	LOS A	5.1	54.2	0.48	0.70	48.6
2	T1	716	10.5	0.878	40.4	LOS C	15.3	122.4	1.00	1.08	34.7
3	R2	319	6.3	0.463	33.5	LOS C	5.7	43.2	0.91	0.79	36.6
Approach		1433	16.7	0.878	30.5	LOS C	15.3	122.4	0.84	0.91	38.2
East: M5 Motorway on&off ramp (E)											
4	L2	273	17.3	0.347	10.4	LOS A	3.3	28.4	0.54	0.71	49.3
6	R2	237	6.2	0.246	28.8	LOS C	3.4	25.1	0.82	0.76	40.4
Approach		509	12.2	0.347	19.0	LOS B	3.4	28.4	0.67	0.73	44.5
North: Moorebank Avenue (N)											
7	L2	51	47.9	0.050	7.9	LOS A	0.4	3.5	0.29	0.60	51.1
8	T1	224	22.4	0.300	26.2	LOS B	3.5	31.0	0.87	0.69	40.7
9	R2	454	25.5	0.772	37.8	LOS C	10.0	85.2	0.97	0.88	36.3
Approach		729	26.1	0.772	32.1	LOS C	10.0	85.2	0.89	0.80	38.3
West: M5 Motorway on&off ramp (W)											
10	L2	1722	7.5	0.977	8.2	LOS A	0.0	0.0	0.00	0.50	51.2
12	R2	536	25.0	0.683	34.0	LOS C	9.3	89.4	0.95	0.86	36.4
Approach		2258	11.6	0.977	14.3	LOS A	9.3	89.4	0.23	0.58	47.0
All Vehicles		4929	15.3	0.977	22.1	LOS B	15.3	122.4	0.55	0.73	42.6

PHASING SUMMARY



Site: I-13 2030 MIMT AM


Moorebank Avenue / the M5 Motorway

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 74 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	E	F
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	24	51
Green Time (sec)	17	20	16
Yellow Time (sec)	4	4	4
All-Red Time (sec)	3	3	3
Phase Time (sec)	24	27	23
Phase Split	32 %	36 %	31 %



MOVEMENT SUMMARY



Site: I-13 2030 MIMT PM

Moorebank Avenue / the M5 Motorway

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 94 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	456	27.4	0.733	24.6	LOS B	15.6	154.7	0.88	0.85	40.4
2	T1	212	18.2	0.852	55.7	LOS D	5.6	48.4	1.00	0.97	29.9
3	R2	348	12.7	0.323	29.0	LOS C	6.3	52.9	0.76	0.77	38.4
Approach		1015	20.4	0.852	32.6	LOS C	15.6	154.7	0.86	0.85	37.0
East: M5 Motorway on&off ramp (E)											
4	L2	462	7.6	0.581	17.2	LOS B	9.5	73.2	0.71	0.82	45.0
6	R2	97	21.7	0.177	42.7	LOS D	2.0	16.2	0.89	0.73	34.9
Approach		558	10.1	0.581	21.6	LOS B	9.5	73.2	0.74	0.80	42.7
North: Moorebank Avenue (N)											
7	L2	139	6.1	0.114	7.3	LOS A	1.1	8.1	0.26	0.62	52.7
8	T1	760	7.8	0.852	44.7	LOS D	19.1	147.3	1.00	1.01	33.1
9	R2	1488	7.0	0.920	43.0	LOS D	34.3	254.6	1.00	1.06	34.8
Approach		2387	7.2	0.920	41.5	LOS C	34.3	254.6	0.96	1.02	35.0
West: M5 Motorway on&off ramp (W)											
10	L2	620	13.8	0.367	5.8	LOS A	0.0	0.0	0.00	0.52	54.4
12	R2	375	34.5	0.825	55.3	LOS D	9.6	103.2	1.00	0.97	29.4
Approach		995	21.6	0.825	24.4	LOS B	9.6	103.2	0.38	0.69	41.9
All Vehicles		4955	13.1	0.920	34.0	LOS C	34.3	254.6	0.80	0.89	37.4

PHASING SUMMARY



Site: I-13 2030 MIMT PM


Moorebank Avenue / the M5 Motorway

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 94 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	E	F
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	14	30	53
Green Time (sec)	7	9	16	34
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	3	3	3	3
Phase Time (sec)	14	16	23	41
Phase Split	15 %	17 %	24 %	44 %



I-14 Intersection of M5 Motorway and Hume Highway

MOVEMENT SUMMARY



Site: I-14 2030 MIMT AM

M5 Motorway / Hume Highway

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 159 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate	Average Speed		
		veh/h	%	v/c	sec	veh	m	per veh	km/h		
South: Hume Highway (S)											
2	T1	4256	4.6	1.027	59.4	LOS E	152.3	1108.5	1.00	1.21	33.2
3	R2	648	4.2	0.894	44.1	LOS D	17.9	129.9	1.00	0.91	37.4
Approach		4904	4.6	1.027	57.4	LOS E	152.3	1108.5	1.00	1.17	33.7
East: M5 Motorway on&off-ramp (E)											
4	L2	338	5.9	0.134	30.5	LOS C	4.8	35.4	0.60	0.71	41.9
6	R2	1211	6.4	1.287	357.1	LOS F	74.1	558.3	1.00	1.54	7.3
Approach		1549	6.3	1.287	285.8	LOS F	74.1	558.3	0.91	1.36	9.6
North: Hume Highway (N)											
7	L2	742	10.1	0.590	13.0	LOS A	22.0	172.6	0.50	0.73	46.5
8	T1	1208	6.7	0.490	28.5	LOS B	17.8	131.7	0.62	0.55	43.3
Approach		1950	8.0	0.590	22.6	LOS B	22.0	172.6	0.57	0.62	44.2
All Vehicles		8403	5.7	1.287	91.4	LOS F	152.3	1108.5	0.89	1.08	25.5

PHASING SUMMARY



Site: I-14 2030 MIMT AM


M5 Motorway / Hume Highway

2030 MIMT AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 159 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C	D
Reference Phase	No	No	No	Yes
Phase Change Time (sec)	20	97	123	0
Green Time (sec)	70	19	29	13
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	3	3	3	3
Phase Time (sec)	77	26	36	20
Phase Split	48 %	16 %	23 %	13 %



MOVEMENT SUMMARY



Site: I-14 2030 MIMT PM

M5 Motorway / Hume Highway

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 159 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
2	T1	2555	3.9	0.624	2.2	LOS A	7.1	51.1	0.12	0.11	58.3
3	R2	401	1.8	1.023	122.1	LOS F	20.4	145.1	1.00	1.07	22.6
Approach		2956	3.6	1.023	18.4	LOS B	20.4	145.1	0.24	0.24	48.0
East: M5 Motorway on&off-ramp (E)											
4	L2	1471	3.4	1.107	220.1	LOS F	89.7	646.4	1.00	1.28	15.0
6	R2	1217	6.2	1.235	312.3	LOS F	71.0	533.8	1.00	1.46	8.1
Approach		2688	4.7	1.235	261.9	LOS F	89.7	646.4	1.00	1.36	11.5
North: Hume Highway (N)											
7	L2	887	6.0	0.702	14.7	LOS B	27.7	210.3	0.61	0.82	45.5
8	T1	2837	2.4	0.870	20.5	LOS B	51.6	368.7	0.78	0.73	47.0
Approach		3724	3.3	0.870	19.1	LOS B	51.6	368.7	0.74	0.75	46.7
All Vehicles		9368	3.8	1.235	88.5	LOS F	89.7	646.4	0.66	0.77	26.0

PHASING SUMMARY



Site: I-14 2030 MIMT PM


M5 Motorway / Hume Highway

2030 MIMT PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 159 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	97	121
Green Time (sec)	90	17	31
Yellow Time (sec)	4	4	4
All-Red Time (sec)	3	3	3
Phase Time (sec)	97	24	38
Phase Split	61 %	15 %	24 %



I-15 Intersection of Cambridge Avenue and Canterbury Road

MOVEMENT SUMMARY



Site: I-15 2030 MIMT AM

Canterbury Road / Cambridge Avenue / Glenfield Road
2030 MIMT AM PEAK 7:45 am - 8:45 am
Roundabout

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Canterbury Road (S)											
1	L2	449	3.5	0.491	5.9	LOS A	3.0	21.7	0.59	0.68	53.0
2	T1	8	0.0	0.828	8.4	LOS A	11.9	84.6	0.85	0.87	50.5
3	R2	1017	2.1	0.828	13.8	LOS A	11.9	84.6	0.85	0.87	50.6
Approach		1475	2.5	0.828	11.4	LOS A	11.9	84.6	0.77	0.81	51.2
East: Cambridge Avenue (E)											
4	L2	307	3.1	0.163	3.5	LOS A	0.0	0.0	0.00	0.43	56.5
5	T1	81	7.8	0.087	5.4	LOS A	0.5	3.8	0.55	0.58	53.2
6	R2	54	9.8	0.087	10.6	LOS A	0.5	3.8	0.55	0.60	53.5
Approach		442	4.8	0.163	4.7	LOS A	0.5	3.8	0.17	0.48	55.5
North: Railway Parade (N)											
7	L2	316	0.7	0.737	32.5	LOS C	8.3	58.6	1.00	1.29	39.0
8	T1	3	0.0	0.548	25.1	LOS B	4.0	28.8	0.97	1.12	41.4
9	R2	168	1.9	0.548	30.5	LOS C	4.0	28.8	0.97	1.12	39.6
Approach		488	1.1	0.737	31.8	LOS C	8.3	58.6	0.99	1.23	39.2
West: Glenfield Road (W)											
10	L2	399	6.3	1.188	126.9	LOS F	45.3	335.6	1.00	2.45	17.6
11	T1	207	8.1	1.188	127.7	LOS F	45.3	335.6	1.00	2.39	17.8
12	R2	367	6.9	1.188	134.9	LOS F	37.5	278.5	1.00	2.27	17.7
Approach		973	6.9	1.188	130.1	LOS F	45.3	335.6	1.00	2.37	17.7
All Vehicles		3378	3.9	1.188	47.6	LOS D	45.3	335.6	0.79	1.28	33.3

MOVEMENT SUMMARY



Site: I-15 2030 MIMT PM

Canterbury Road / Cambridge Avenue / Glenfield Road
2030 MIMT PM PEAK 4:30 pm - 5:30 pm
Roundabout

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Canterbury Road (S)											
1	L2	338	2.2	0.471	8.8	LOS A	3.0	21.5	0.78	0.92	51.0
2	T1	6	0.0	0.402	7.2	LOS A	2.5	17.4	0.76	0.91	51.2
3	R2	334	1.3	0.402	12.6	LOS A	2.5	17.4	0.76	0.91	51.4
Approach		678	1.7	0.471	10.6	LOS A	3.0	21.5	0.77	0.92	51.2
East: Cambridge Avenue (E)											
4	L2	1129	2.2	0.596	3.6	LOS A	0.0	0.0	0.00	0.43	56.3
5	T1	294	7.9	0.450	7.2	LOS A	3.5	25.3	0.76	0.75	52.0
6	R2	328	1.0	0.450	12.3	LOS A	3.5	25.3	0.81	0.78	52.3
Approach		1751	2.9	0.596	5.8	LOS A	3.5	25.3	0.28	0.55	54.8
North: Railway Parade (N)											
7	L2	125	1.7	0.191	7.9	LOS A	1.0	6.8	0.69	0.80	52.8
8	T1	0	0.0	0.000	0.0	NA	0.0	0.0	0.00	0.00	0.0
9	R2	240	8.3	0.294	12.7	LOS A	1.7	12.6	0.72	0.86	50.0
Approach		365	6.1	0.294	11.0	LOS A	1.7	12.6	0.71	0.84	51.0
West: Glenfield Road (W)											
10	L2	271	4.7	0.428	8.5	LOS A	2.8	20.2	0.75	0.84	51.2
11	T1	54	0.0	0.428	8.3	LOS A	2.8	20.2	0.75	0.84	53.1
12	R2	451	3.7	0.498	13.7	LOS A	3.8	27.8	0.79	0.90	49.4
Approach		775	3.8	0.498	11.5	LOS A	3.8	27.8	0.77	0.88	50.2
All Vehicles		3569	3.2	0.596	8.5	LOS A	3.8	27.8	0.52	0.72	52.7

Appendix I

2030 SIDRA results with Moorebank
IMT and SIMTA

1. Moorebank Avenue – 2030 cumulative scenario 1

I-01 Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

MOVEMENT SUMMARY



Site: I-01 Cumulative Scenario 1 AM

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Cumulative Scenario 1 AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	37	0.0	0.843	33.8	LOS C	31.3	253.1	0.87	0.85	31.7
2	T1	1293	19.1	0.843	28.1	LOS B	31.3	253.1	0.87	0.84	36.6
3	R2	473	3.1	0.856	37.1	LOS C	18.4	132.2	1.00	0.99	33.4
Approach		1802	14.5	0.856	30.6	LOS C	31.3	253.6	0.91	0.88	35.5
East: Anzac Road (E)											
4	L2	238	3.5	0.388	33.5	LOS C	9.8	70.8	0.79	0.79	34.9
5	T1	9	0.0	0.388	29.1	LOS C	9.8	70.8	0.79	0.79	34.2
6	R2	224	13.6	0.841	62.4	LOS E	13.2	103.3	1.00	0.95	28.1
Approach		472	8.3	0.841	47.1	LOS D	13.2	103.3	0.89	0.87	31.1
North: Moorebank Avenue (N)											
7	L2	383	9.9	0.221	5.7	LOS A	0.0	0.0	0.00	0.52	54.2
8	T1	848	26.6	0.561	19.6	LOS B	13.5	116.4	0.64	0.57	41.6
9	R2	142	5.2	0.322	22.5	LOS B	3.9	28.5	0.83	0.78	37.3
Approach		1374	19.7	0.561	16.0	LOS B	13.5	116.4	0.48	0.58	44.5
West: Bapaume Road (W)											
10	L2	9	77.8	0.021	15.3	LOS B	0.2	2.3	0.56	0.61	39.4
11	T1	1	0.0	0.012	48.4	LOS D	0.1	0.7	0.91	0.60	28.7
12	R2	1	0.0	0.012	52.1	LOS D	0.1	0.7	0.91	0.60	24.2
Approach		12	63.6	0.021	21.7	LOS B	0.2	2.3	0.63	0.60	36.3
All Vehicles		3659	15.8	0.856	27.2	LOS B	31.3	253.6	0.74	0.77	37.7

PHASING SUMMARY



Site: I-01 Cumulative Scenario 1 AM


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Cumulative Scenario 1 AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	56	83
Green Time (sec)	50	21	21
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	56	27	27
Phase Split	51 %	25 %	25 %



MOVEMENT SUMMARY



Site: I-01 Cumulative Scenario 1 PM

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Cumulative Scenario 1 PM PEAK

Signals - Fixed Time Cycle Time = 120 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
1	L2	1	0.0	0.308	LOS A	2.7	24.0	0.15	0.13	50.0
2	T1	664	33.4	0.308	LOS A	2.7	24.0	0.15	0.13	56.2
3	R2	232	0.9	1.043	LOS F	23.7	167.5	1.00	1.26	17.1
Approach		897	25.0	1.043	LOS C	23.7	167.5	0.37	0.42	34.3
East: Anzac Road (E)										
4	L2	568	2.2	0.914	LOS E	38.8	277.0	1.00	0.99	25.8
5	T1	1	0.0	0.914	LOS E	38.8	277.0	1.00	0.99	25.4
6	R2	391	5.4	1.120	LOS F	45.9	336.1	1.00	1.40	13.6
Approach		960	3.5	1.120	LOS F	45.9	336.1	1.00	1.16	18.5
North: Moorebank Avenue (N)										
7	L2	353	3.9	0.195	LOS A	0.0	0.0	0.00	0.53	54.4
8	T1	1474	16.4	0.903	LOS B	40.8	325.7	0.66	0.71	37.2
9	R2	27	30.8	0.087	LOS B	0.8	7.0	0.51	0.68	38.0
Approach		1854	14.3	0.903	LOS B	40.8	325.7	0.53	0.67	40.2
West: Bapaume Road (W)										
10	L2	152	6.3	0.249	LOS A	2.6	19.1	0.37	0.60	45.1
11	T1	13	0.0	0.452	LOS E	2.4	17.1	1.00	0.74	24.7
12	R2	27	0.0	0.452	LOS E	2.4	17.1	1.00	0.74	20.4
Approach		192	4.9	0.452	LOS B	2.6	19.1	0.50	0.63	37.4
All Vehicles		3902	13.6	1.120	LOS D	45.9	336.1	0.61	0.73	29.6

PHASING SUMMARY



Site: I-01 Cumulative Scenario 1 PM


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Cumulative Scenario 1 PM PEAK

Signals - Fixed Time Cycle Time = 120 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	73	87
Green Time (sec)	67	8	27
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	73	14	33
Phase Split	61 %	12 %	28 %



I-02 Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

MOVEMENT SUMMARY



Site: I-02 Cumulative Scenario 1 AM

Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2030 Cumulative Scenario 1 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue	Prop. Queued	Effective Stop Rate	Average Speed	
	v	Total	HV				Vehicles				
		veh/h	%	v/c	sec		veh	m	per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.762	10.6	LOS A	15.9	123.9	0.40	0.37	44.4
2	T1	1769	13.3	0.762	4.9	LOS A	15.9	123.9	0.38	0.35	51.9
3	R2	56	0.0	0.501	58.3	LOS E	2.8	19.9	1.00	0.75	12.1
Approach		1826	12.9	0.762	6.6	LOS A	15.9	123.9	0.40	0.37	48.8
East: DNSDC Access (E)											
4	L2	5	20.0	0.219	55.2	LOS D	1.2	12.3	0.97	0.72	15.2
6	R2	19	66.7	0.219	55.4	LOS D	1.2	12.3	0.97	0.72	17.5
Approach		24	56.5	0.219	55.3	LOS D	1.2	12.3	0.97	0.72	17.1
North: Moorebank Avenue (N)											
7	L2	207	12.7	0.488	15.2	LOS B	13.3	108.1	0.55	0.60	28.1
8	T1	863	22.4	0.488	9.2	LOS A	13.3	108.1	0.54	0.53	45.6
9	R2	16	86.7	0.229	59.8	LOS E	0.8	9.9	0.98	0.70	16.5
Approach		1086	21.5	0.488	11.1	LOS A	13.3	108.1	0.55	0.54	40.8
West: Warehouse Access 1 (W)											
10	L2	15	92.9	0.082	43.4	LOS D	0.7	8.1	0.86	0.69	19.8
12	R2	1	0.0	0.082	42.5	LOS D	0.7	8.1	0.86	0.69	18.4
Approach		16	86.7	0.082	43.3	LOS D	0.7	8.1	0.86	0.69	19.7
All Vehicles		2953	16.8	0.762	8.8	LOS A	15.9	123.9	0.46	0.44	44.8

PHASING SUMMARY



Site: I-02 Cumulative Scenario 1 AM


Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2030 Cumulative Scenario 1 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



MOVEMENT SUMMARY



Site: I-02 Cumulative Scenario 1 PM

Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2030 Cumulative Scenario 1 PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.386	11.3	LOS A	4.9	41.8	0.31	0.27	43.2
2	T1	774	25.4	0.386	5.8	LOS A	4.9	41.8	0.31	0.27	50.8
3	R2	1	0.0	0.010	25.4	LOS B	0.0	0.2	0.64	0.63	18.1
Approach		776	25.4	0.386	5.8	LOS A	4.9	41.8	0.31	0.27	50.7
East: DNSDC Access (E)											
4	L2	35	0.0	0.825	55.7	LOS D	7.0	52.9	1.00	0.95	15.6
6	R2	106	12.9	0.825	55.7	LOS D	7.0	52.9	1.00	0.95	18.1
Approach		141	9.7	0.825	55.7	LOS D	7.0	52.9	1.00	0.95	17.5
North: Moorebank Avenue (N)											
7	L2	25	79.2	0.782	14.4	LOS A	28.0	217.0	0.68	0.64	28.8
8	T1	2031	10.9	0.782	7.9	LOS A	28.0	217.0	0.67	0.63	48.0
9	R2	15	92.9	0.198	53.9	LOS D	0.7	8.5	0.98	0.70	17.6
Approach		2071	12.3	0.782	8.3	LOS A	28.0	217.0	0.67	0.63	47.3
West: Warehouse Access 1 (W)											
10	L2	16	86.7	0.065	35.0	LOS C	0.6	7.0	0.81	0.69	22.4
12	R2	1	0.0	0.065	34.2	LOS C	0.6	7.0	0.81	0.69	21.1
Approach		17	81.3	0.065	34.9	LOS C	0.6	7.0	0.81	0.69	22.3
All Vehicles		3004	15.9	0.825	10.0	LOS A	28.0	217.0	0.60	0.55	45.1

PHASING SUMMARY



Site: I-02 Cumulative Scenario 1 PM


Intersection of Moorebank Avenue, Warehouse Access 1 and DNSDC Access

2030 Cumulative Scenario 1 PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	60	78
Green Time (sec)	54	12	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	60	18	12
Phase Split	67 %	20 %	13 %



I-03 Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Central Access

MOVEMENT SUMMARY



Site: I-03 Cumulative Scenario 1 AM

Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Central Access

2030 Cumulative Scenario 1 AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay v/c	Level of Service sec	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate per veh	Average Speed km/h		
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.882	32.9	LOS C	42.1	324.0	0.93	0.97	34.8
2	T1	1798	11.5	0.882	27.3	LOS B	42.1	324.0	0.91	0.95	38.1
3	R2	31	0.0	0.064	10.9	LOS A	0.4	2.9	0.45	0.65	36.2
Approach		1829	11.3	0.882	27.0	LOS B	42.1	324.0	0.90	0.95	38.1
East: SIMTA Central Access (E)											
4	L2	1	0.0	0.002	31.1	LOS C	0.0	0.2	0.75	0.60	33.2
6	R2	13	91.7	0.078	44.3	LOS D	0.5	6.4	0.90	0.69	15.7
Approach		14	84.6	0.078	43.3	LOS D	0.5	6.4	0.89	0.68	17.0
North: Moorebank Avenue (N)											
7	L2	89	21.2	0.100	15.8	LOS B	1.8	15.1	0.50	0.69	26.4
8	T1	759	20.9	0.383	6.9	LOS A	5.4	44.5	0.35	0.31	52.4
9	R2	20	84.2	0.133	25.3	LOS B	0.5	6.2	0.84	0.71	23.6
Approach		868	22.4	0.383	8.2	LOS A	5.4	44.5	0.38	0.35	49.5
West: Warehouse Access 2 (W)											
10	L2	18	94.1	0.068	33.3	LOS C	0.6	8.0	0.79	0.69	17.7
12	R2	1	0.0	0.068	32.5	LOS C	0.6	8.0	0.79	0.69	32.0
Approach		19	88.9	0.068	33.3	LOS C	0.6	8.0	0.79	0.69	18.6
All Vehicles		2731	15.8	0.882	21.2	LOS B	42.1	324.0	0.73	0.76	40.7

PHASING SUMMARY



Site: I-03 Cumulative Scenario 1 AM


Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Central Access

2030 Cumulative Scenario 1 AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	58	78
Green Time (sec)	52	14	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	58	20	12
Phase Split	64 %	22 %	13 %



MOVEMENT SUMMARY



Site: I-03 Cumulative Scenario 1 PM

Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Central Access

2030 Cumulative Scenario 1 PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.347	16.3	LOS B	7.7	65.9	0.57	0.49	45.7
2	T1	672	25.1	0.347	10.7	LOS A	7.7	65.9	0.57	0.49	49.0
3	R2	1	0.0	0.008	15.6	LOS B	0.0	0.2	0.46	0.62	33.8
Approach		674	25.0	0.347	10.7	LOS A	7.7	65.9	0.56	0.49	48.9
East: SIMTA Central Access (E)											
4	L2	31	0.0	0.123	43.6	LOS D	1.2	8.5	0.91	0.72	28.3
6	R2	82	14.1	0.388	45.9	LOS D	3.5	27.1	0.96	0.77	17.6
Approach		113	10.3	0.388	45.2	LOS D	3.5	27.1	0.94	0.75	21.0
North: Moorebank Avenue (N)											
7	L2	20	94.7	0.025	10.7	LOS A	0.3	3.2	0.31	0.62	28.5
8	T1	2031	9.1	0.776	1.9	LOS A	8.7	65.5	0.21	0.20	57.8
9	R2	18	94.1	0.064	12.6	LOS A	0.3	3.2	0.48	0.66	31.0
Approach		2068	10.7	0.776	2.0	LOS A	8.7	65.5	0.22	0.21	57.3
West: Warehouse Access 2 (W)											
10	L2	20	84.2	0.072	33.2	LOS C	0.7	8.4	0.79	0.69	18.1
12	R2	1	0.0	0.072	32.5	LOS C	0.7	8.4	0.79	0.69	32.0
Approach		21	80.0	0.072	33.2	LOS C	0.7	8.4	0.79	0.69	18.8
All Vehicles		2876	14.5	0.776	6.0	LOS A	8.7	65.9	0.33	0.30	52.8

PHASING SUMMARY



Site: I-03 Cumulative Scenario 1 PM


Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Central Access

2030 Cumulative Scenario 1 PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	58	78
Green Time (sec)	52	14	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	58	20	12
Phase Split	64 %	22 %	13 %



I-04 Intersection of Moorebank Avenue and Warehouse Access 3

MOVEMENT SUMMARY



Site: I-04 Cumulative Scenario 1 AM

Intersection of Moorebank Avenue and Warehouse Access 3

2030 Cumulative Scenario 1 AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	2	0.0	0.791	19.5	LOS B	29.7	225.4	0.81	0.75	41.8
2	T1	1801	9.9	0.791	14.0	LOS A	29.7	225.5	0.81	0.75	49.3
Approach		1803	9.9	0.791	14.0	LOS A	29.7	225.5	0.81	0.75	49.2
North: Moorebank Avenue (N)											
8	T1	725	18.0	0.275	3.6	LOS A	4.8	39.1	0.33	0.29	56.8
9	R2	34	84.4	0.220	21.1	LOS B	0.8	9.8	0.76	0.73	36.1
Approach		759	20.9	0.275	4.4	LOS A	4.8	39.1	0.35	0.31	55.9
West: Warehouse Access 3 (W)											
10	L2	29	96.4	0.130	36.7	LOS C	1.1	14.0	0.83	0.71	28.7
12	R2	1	0.0	0.130	35.9	LOS C	1.1	14.0	0.83	0.71	29.1
Approach		31	93.1	0.130	36.7	LOS C	1.1	14.0	0.83	0.71	28.7
All Vehicles		2593	14.1	0.791	11.5	LOS A	29.7	225.5	0.67	0.62	50.7

PHASING SUMMARY



Site: I-04 Cumulative Scenario 1 AM


Intersection of Moorebank Avenue and Warehouse Access 3

2030 Cumulative Scenario 1 AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	62	78
Green Time (sec)	56	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	62	16	12
Phase Split	69 %	18 %	13 %



MOVEMENT SUMMARY



Site: I-04 Cumulative Scenario 1 PM

Intersection of Moorebank Avenue and Warehouse Access 3

2030 Cumulative Scenario 1 PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.312	15.0	LOS B	6.8	56.9	0.53	0.46	45.8
2	T1	638	21.9	0.312	9.5	LOS A	6.8	56.9	0.53	0.46	52.3
Approach		639	21.9	0.312	9.5	LOS A	6.8	56.9	0.53	0.46	52.3
North: Moorebank Avenue (N)											
8	T1	2034	7.7	0.757	6.4	LOS A	26.4	196.7	0.59	0.55	54.6
9	R2	29	96.4	0.091	11.2	LOS A	0.4	4.5	0.44	0.66	42.0
Approach		2063	9.0	0.757	6.4	LOS A	26.4	196.7	0.59	0.55	54.4
West: Warehouse Access 3 (W)											
10	L2	34	84.4	0.138	36.5	LOS C	1.3	15.3	0.84	0.72	28.9
12	R2	2	0.0	0.138	35.8	LOS C	1.3	15.3	0.84	0.72	29.1
Approach		36	79.4	0.138	36.5	LOS C	1.3	15.3	0.84	0.72	28.9
All Vehicles		2738	12.9	0.757	7.5	LOS A	26.4	196.7	0.58	0.53	53.5

PHASING SUMMARY



Site: I-04 Cumulative Scenario 1 PM


Intersection of Moorebank Avenue and Warehouse Access 3

2030 Cumulative Scenario 1 PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	60	76
Green Time (sec)	54	10	8
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	60	16	14
Phase Split	67 %	18 %	16 %



I-05 Intersection of Moorebank Avenue, Main Access and SIMTA Southern Access

MOVEMENT SUMMARY



Site: I-05 Cumulative Scenario 1 AM

Intersection of Moorebank Avenue, Main Access and SIMTA Southern Access

2030 Cumulative Scenario 1 AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
		Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.774	21.7	LOS B	28.3	203.2	0.84	0.76	40.3
2	T1	1676	3.1	0.774	16.1	LOS B	28.3	203.2	0.84	0.76	48.0
Approach		1677	3.1	0.774	16.1	LOS B	28.3	203.2	0.84	0.76	48.0
East: SIMTA Southern Access (E)											
4	L2	1	0.0	0.004	41.9	LOS C	0.0	0.3	0.88	0.59	27.5
6	R2	16	93.3	0.115	45.9	LOS D	0.7	8.2	0.92	0.70	26.1
Approach		17	87.5	0.115	45.7	LOS D	0.7	8.2	0.92	0.70	26.2
North: Moorebank Avenue (N)											
8	T1	609	2.9	0.249	4.7	LOS A	5.1	36.9	0.37	0.32	55.9
9	R2	116	97.3	0.730	32.1	LOS C	4.3	55.3	1.00	0.94	31.0
Approach		725	18.0	0.730	9.1	LOS A	5.1	55.3	0.47	0.42	51.5
West: Main Access (W)											
10	L2	114	99.1	0.192	32.9	LOS C	2.0	25.9	0.80	0.73	30.0
12	R2	1	0.0	0.192	32.1	LOS C	2.0	25.2	0.80	0.73	30.6
Approach		115	98.2	0.192	32.9	LOS C	2.0	25.9	0.80	0.73	30.0
All Vehicles		2534	12.2	0.774	15.1	LOS B	28.3	203.2	0.73	0.66	47.9

PHASING SUMMARY



Site: I-05 Cumulative Scenario 1 AM


Intersection of Moorebank Avenue, Main Access and SIMTA Southern Access

2030 Cumulative Scenario 1 AM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	57	77
Green Time (sec)	51	14	7
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	57	20	13
Phase Split	63 %	22 %	14 %



MOVEMENT SUMMARY



Site: I-05 Cumulative Scenario 1 PM

Intersection of Moorebank Avenue, Main Access and SIMTA Southern Access

2030 Cumulative Scenario 1 PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.373	28.8	LOS C	8.3	59.4	0.79	0.67	35.6
2	T1	507	2.5	0.373	23.2	LOS B	8.3	59.5	0.79	0.67	44.1
Approach		508	2.5	0.373	23.3	LOS B	8.3	59.5	0.79	0.67	44.1
East: SIMTA Southern Access (E)											
4	L2	1	0.0	0.004	41.9	LOS C	0.0	0.3	0.88	0.59	27.5
6	R2	15	100.0	0.104	44.7	LOS D	0.6	7.8	0.91	0.70	27.1
Approach		16	93.3	0.104	44.5	LOS D	0.6	7.8	0.91	0.69	27.1
North: Moorebank Avenue (N)											
8	T1	1923	2.3	0.877	13.1	LOS A	32.4	231.4	0.63	0.63	49.9
9	R2	114	99.1	0.238	12.9	LOS A	1.7	21.6	0.54	0.71	41.0
Approach		2037	7.7	0.877	13.1	LOS A	32.4	231.4	0.62	0.64	49.5
West: Main Access (W)											
10	L2	116	97.3	0.113	19.7	LOS B	1.4	18.5	0.58	0.68	35.8
12	R2	1	0.0	0.113	19.8	LOS B	1.4	18.2	0.60	0.68	36.8
Approach		117	96.4	0.113	19.7	LOS B	1.4	18.5	0.58	0.68	35.9
All Vehicles		2678	11.1	0.877	15.5	LOS B	32.4	231.4	0.66	0.64	47.7

PHASING SUMMARY



Site: I-05 Cumulative Scenario 1 PM


Intersection of Moorebank Avenue, Main Access and SIMTA Southern Access

2030 Cumulative Scenario 1 PM PEAK

Signals - Fixed Time Cycle Time = 90 seconds (Optimum Cycle Time - Minimum Delay)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	38	58
Green Time (sec)	32	14	26
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	38	20	32
Phase Split	42 %	22 %	36 %



2. Moorebank Avenue – 2030 cumulative scenario 2

I-01 Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

MOVEMENT SUMMARY



Site: I-01 Cumulative Scenario 2 AM

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Cumulative Scenario 2 AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	19	0.0	0.648	15.2	LOS B	15.0	130.0	0.48	0.44	43.7
2	T1	1258	16.9	0.648	9.6	LOS A	15.0	130.0	0.47	0.43	49.4
3	R2	473	3.1	0.976	86.8	LOS F	31.9	229.2	1.00	1.21	21.7
Approach		1749	13.0	0.976	30.5	LOS C	31.9	229.2	0.62	0.64	36.0
East: Anzac Road (E)											
4	L2	245	3.4	0.371	31.8	LOS C	9.6	68.9	0.77	0.78	35.9
5	T1	3	0.0	0.371	27.5	LOS B	9.6	68.9	0.77	0.78	34.8
6	R2	224	13.6	0.929	75.8	LOS F	14.9	116.4	1.00	1.06	25.3
Approach		473	8.2	0.929	52.7	LOS D	14.9	116.4	0.88	0.91	29.6
North: Moorebank Avenue (N)											
7	L2	383	9.9	0.221	5.7	LOS A	0.0	0.0	0.00	0.52	54.2
8	T1	1058	17.8	0.938	44.7	LOS D	29.9	266.2	0.70	0.87	30.2
9	R2	100	4.2	0.339	15.0	LOS B	1.7	12.4	0.63	0.73	41.7
Approach		1541	15.0	0.938	33.1	LOS C	29.9	266.2	0.52	0.77	35.4
West: Bapaume Road (W)											
10	L2	6	66.7	0.010	10.1	LOS A	0.1	0.8	0.42	0.57	43.0
11	T1	1	0.0	0.014	50.6	LOS D	0.1	0.7	0.93	0.60	28.1
12	R2	1	0.0	0.014	54.4	LOS D	0.1	0.7	0.93	0.60	24.0
Approach		8	50.0	0.014	20.7	LOS B	0.1	0.8	0.55	0.58	37.1
All Vehicles		3772	13.3	0.976	34.3	LOS C	31.9	266.2	0.61	0.73	34.7

PHASING SUMMARY



Site: I-01 Cumulative Scenario 2 AM


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Cumulative Scenario 2 AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	D	E
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	58	83	97
Green Time (sec)	52	19	8	7
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	58	25	14	13
Phase Split	53 %	23 %	13 %	12 %



MOVEMENT SUMMARY



Site: I-01 Cumulative Scenario 2 PM

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Cumulative Scenario 2 PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Prop. Queued Distance m	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)									
1	L2	1	0.0	0.437	LOS A	3.9	35.0	0.16	50.6
2	T1	975	17.8	0.437	LOS A	3.9	35.0	0.16	56.5
3	R2	245	0.9	1.084	LOS F	26.7	188.0	1.00	14.9
Approach		1221	14.4	1.084	LOS C	26.7	188.0	0.33	35.1
East: Anzac Road (E)									
4	L2	568	2.2	0.954	LOS F	40.4	288.5	1.00	24.1
5	T1	1	0.0	0.954	LOS E	40.4	288.5	1.00	23.4
6	R2	391	5.4	1.198	LOS F	51.8	379.2	1.00	10.9
Approach		960	3.5	1.198	LOS F	51.8	379.2	1.00	15.8
North: Moorebank Avenue (N)									
7	L2	353	3.9	0.195	LOS A	0.0	0.0	0.00	54.4
8	T1	1423	13.5	0.891	LOS B	34.2	287.7	0.63	39.3
9	R2	24	21.7	0.107	LOS B	0.7	5.6	0.52	38.3
Approach		1800	11.7	0.891	LOS B	34.2	287.7	0.51	42.1
West: Bapaume Road (W)									
10	L2	109	5.8	0.240	LOS A	1.6	11.7	0.37	45.7
11	T1	6	0.0	0.212	LOS E	0.9	6.2	0.99	25.7
12	R2	9	0.0	0.212	LOS E	0.9	6.2	0.99	21.8
Approach		125	5.0	0.240	LOS B	1.6	11.7	0.45	41.0
All Vehicles		4106	10.4	1.198	LOS D	51.8	379.2	0.57	28.4

PHASING SUMMARY



Site: I-01 Cumulative Scenario 2 PM


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Cumulative Scenario 2 PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	68	81
Green Time (sec)	62	7	23
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	68	13	29
Phase Split	62 %	12 %	26 %



I-02 Intersection of Moorebank Avenue and DNSDC Access

MOVEMENT SUMMARY



Site: I-02 Cumulative Scenario 2 AM

Intersection of Moorebank Avenue and DNSDC Access

2030 Cumulative Scenario 2 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)										
2	T1	1726	12.2	0.635	LOS A	2.2	18.0	0.06	0.05	59.4
3	R2	34	0.0	0.113	LOS A	0.4	3.1	0.50	0.68	46.9
Approach		1760	12.0	0.635	LOS A	2.2	18.0	0.07	0.07	59.1
East: DNSDC Access (E)										
4	L2	5	20.0	0.349	LOS D	1.4	20.9	0.98	0.73	30.3
6	R2	23	72.7	0.349	LOS E	1.4	20.9	0.98	0.73	23.1
Approach		28	63.0	0.349	LOS E	1.4	20.9	0.98	0.73	24.4
North: Moorebank Avenue (N)										
7	L2	304	11.4	0.603	LOS A	13.0	110.8	0.45	0.57	44.5
8	T1	1002	16.4	0.603	LOS A	13.0	110.8	0.34	0.36	54.0
Approach		1306	15.2	0.603	LOS A	13.0	110.8	0.36	0.41	51.6
All Vehicles		3095	13.8	0.635	LOS A	13.0	110.8	0.20	0.22	55.1

PHASING SUMMARY



Site: I-02 Cumulative Scenario 2 AM


Intersection of Moorebank Avenue and DNSDC Access

2030 Cumulative Scenario 2 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



MOVEMENT SUMMARY



Site: I-02 Cumulative Scenario 2 PM

Intersection of Moorebank Avenue and DNSDC Access

2030 Cumulative Scenario 2 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
2	T1	965	16.7	0.434	3.0	LOS A	4.1	35.7	0.19	0.17	56.9
3	R2	1	0.0	0.010	24.7	LOS B	0.0	0.2	0.60	0.63	40.7
Approach		966	16.7	0.434	3.1	LOS A	4.1	35.7	0.19	0.17	56.9
East: DNSDC Access (E)											
4	L2	16	0.0	0.866	57.5	LOS E	14.9	114.5	1.00	0.98	30.3
6	R2	255	5.8	0.866	57.6	LOS E	14.9	114.5	1.00	0.98	25.7
Approach		271	5.4	0.866	57.6	LOS E	14.9	114.5	1.00	0.98	26.0
North: Moorebank Avenue (N)											
7	L2	25	79.2	0.845	14.5	LOS B	23.6	192.2	0.48	0.48	44.5
8	T1	1975	9.3	0.845	7.6	LOS A	23.6	192.2	0.48	0.47	52.8
Approach		2000	10.2	0.845	7.7	LOS A	23.6	192.2	0.48	0.47	52.7
All Vehicles		3237	11.7	0.866	10.5	LOS A	23.6	192.2	0.44	0.43	49.8

PHASING SUMMARY



Site: I-02 Cumulative Scenario 2 PM


Intersection of Moorebank Avenue and DNSDC Access

2030 Cumulative Scenario 2 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	73
Green Time (sec)	67	21
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	73	27
Phase Split	73 %	27 %



I-03 Intersection of Moorebank Avenue, MIMT Main Access and SIMTA Central Access

MOVEMENT SUMMARY

Site: I-03 Cumulative Scenario 2 AM

Intersection of Moorebank Avenue, MIMT Main Access and SIMTA Central Access

2030 Cumulative Scenario 2 AM PEAK

Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue	Prop. Queued	Effective Stop Rate	Average Speed	
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m	per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	4	0.0	0.719	11.4	LOS A	16.4	127.6	0.36	0.34	48.2
2	T1	1704	9.1	0.719	5.8	LOS A	16.4	127.6	0.36	0.34	54.7
3	R2	8	0.0	0.060	62.7	LOS E	0.5	3.3	0.95	0.67	21.6
Approach		1717	9.0	0.719	6.1	LOS A	16.4	127.6	0.36	0.34	54.5
East: SIMTA Central Access (E)											
4	L2	1	0.0	0.003	43.3	LOS D	0.0	0.3	0.80	0.59	26.2
6	R2	16	100.0	0.200	64.8	LOS E	0.9	18.3	0.96	0.71	24.3
Approach		17	93.8	0.200	63.4	LOS E	0.9	18.3	0.95	0.70	24.4
North: Moorebank Avenue (N)											
7	L2	186	14.7	0.429	12.9	LOS A	8.6	72.4	0.35	0.47	47.4
8	T1	773	12.8	0.429	5.3	LOS A	8.6	72.4	0.26	0.29	54.5
9	R2	48	80.4	0.720	74.4	LOS F	3.2	55.6	1.00	0.88	22.9
Approach		1007	16.4	0.720	10.0	LOS A	8.6	72.4	0.31	0.35	50.5
West: Main Access (W)											
10	L2	39	100.0	0.226	48.6	LOS D	2.0	39.3	0.86	0.74	28.0
12	R2	1	0.0	0.007	58.2	LOS E	0.1	0.4	0.93	0.59	22.3
Approach		40	97.4	0.226	48.9	LOS D	2.0	39.3	0.86	0.74	27.8
All Vehicles		2781	13.5	0.720	8.5	LOS A	16.4	127.6	0.36	0.35	52.1

PHASING SUMMARY

Site: I-03 Cumulative Scenario 2 AM


Intersection of Moorebank Avenue, MIMT Main Access and SIMTA Central Access

2030 Cumulative Scenario 2 AM PEAK

Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	85	105
Green Time (sec)	79	14	9
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	85	20	15
Phase Split	71 %	17 %	13 %



MOVEMENT SUMMARY



Site: I-03 Cumulative Scenario 2 PM

Intersection of Moorebank Avenue, MIMT Main Access and SIMTA Central Access

2030 Cumulative Scenario 2 PM PEAK

Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.414	21.7	LOS B	9.4	80.7	0.51	0.44	39.3
2	T1	687	16.1	0.414	16.2	LOS B	9.4	80.7	0.51	0.44	47.4
3	R2	1	0.0	0.013	27.7	LOS B	0.0	0.3	0.59	0.63	32.7
Approach		689	16.0	0.414	16.2	LOS B	9.4	80.7	0.51	0.44	47.4
East: SIMTA Central Access (E)											
4	L2	12	0.0	0.029	44.0	LOS D	0.5	3.7	0.81	0.67	26.0
6	R2	231	5.5	0.806	60.1	LOS E	14.2	109.7	1.00	0.93	25.9
Approach		242	5.2	0.806	59.3	LOS E	14.2	109.7	0.99	0.92	25.9
North: Moorebank Avenue (N)											
7	L2	19	100.0	0.812	13.0	LOS A	24.0	186.9	0.47	0.45	48.5
8	T1	1933	6.5	0.812	6.7	LOS A	24.3	182.8	0.47	0.44	54.0
9	R2	39	100.0	0.419	63.8	LOS E	2.3	46.0	0.97	0.76	25.1
Approach		1991	9.2	0.812	7.9	LOS A	24.3	186.9	0.48	0.45	53.0
West: Main Access (W)											
10	L2	48	80.4	0.141	31.7	LOS C	1.9	32.7	0.68	0.71	32.6
12	R2	4	0.0	0.013	44.0	LOS D	0.2	1.3	0.81	0.64	26.1
Approach		53	74.0	0.141	32.7	LOS C	1.9	32.7	0.69	0.70	32.1
All Vehicles		2975	11.6	0.812	14.4	LOS A	24.3	186.9	0.53	0.49	47.9

PHASING SUMMARY



Site: I-03 Cumulative Scenario 2 PM


Intersection of Moorebank Avenue, MIMT Main Access and SIMTA Central Access

2030 Cumulative Scenario 2 PM PEAK

Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	65	100
Green Time (sec)	59	29	14
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	65	35	20
Phase Split	54 %	29 %	17 %



I-04 Intersection of Moorebank Avenue and Warehouse Access 1

MOVEMENT SUMMARY



Site: I-04 Cumulative Scenario 2 AM

Intersection of Moorebank Avenue and Warehouse Access 1

2030 Cumulative Scenario 2 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	5	0.0	0.713	10.3	LOS A	13.4	103.6	0.35	0.33	47.7
2	T1	1703	8.3	0.713	4.7	LOS A	13.4	103.6	0.35	0.33	54.0
Approach		1708	8.3	0.713	4.8	LOS A	13.4	103.6	0.35	0.33	53.9
North: Moorebank Avenue (N)											
8	T1	746	11.4	0.271	0.3	LOS A	0.5	3.9	0.03	0.03	59.5
9	R2	27	53.8	0.158	12.2	LOS A	0.4	3.8	0.49	0.68	41.5
Approach		774	12.9	0.271	0.8	LOS A	0.5	3.9	0.05	0.05	58.7
West: Warehouse Access 1 (W)											
10	L2	15	100.0	0.083	43.0	LOS D	0.7	8.4	0.86	0.70	25.6
12	R2	1	0.0	0.083	42.6	LOS D	0.7	8.4	0.86	0.70	23.8
Approach		16	93.3	0.083	43.0	LOS D	0.7	8.4	0.86	0.70	25.5
All Vehicles		2498	10.2	0.713	3.8	LOS A	13.4	103.6	0.26	0.24	55.0

PHASING SUMMARY



Site: I-04 Cumulative Scenario 2 AM


Intersection of Moorebank Avenue and Warehouse Access 1

2030 Cumulative Scenario 2 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



MOVEMENT SUMMARY



Site: I-04 Cumulative Scenario 2 PM

Intersection of Moorebank Avenue and Warehouse Access 1

2030 Cumulative Scenario 2 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.294	8.7	LOS A	2.6	22.0	0.17	0.15	49.8
2	T1	660	14.5	0.294	3.1	LOS A	2.6	22.0	0.17	0.15	55.9
Approach		661	14.5	0.294	3.1	LOS A	2.6	22.0	0.17	0.15	55.9
North: Moorebank Avenue (N)											
8	T1	1934	5.7	0.667	0.6	LOS A	2.7	20.1	0.06	0.06	59.2
9	R2	15	100.0	0.047	9.5	LOS A	0.2	2.3	0.33	0.63	43.8
Approach		1948	6.4	0.667	0.6	LOS A	2.7	20.1	0.06	0.06	59.1
West: Warehouse Access 1 (W)											
10	L2	27	53.8	0.163	46.4	LOS D	1.4	14.0	0.91	0.72	24.6
12	R2	5	0.0	0.163	45.9	LOS D	1.4	14.0	0.91	0.72	22.8
Approach		33	45.2	0.163	46.3	LOS D	1.4	14.0	0.91	0.72	24.3
All Vehicles		2642	8.9	0.667	1.8	LOS A	2.7	22.0	0.10	0.09	57.4

PHASING SUMMARY



Site: I-04 Cumulative Scenario 2 PM

Intersection of Moorebank Avenue and Warehouse Access 1

2030 Cumulative Scenario 2 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase times determined by the program

Sequence: NEW TCS I-04 PM


Movement Class: All Movement Classes

Input Sequence: A, B, C

Output Sequence: A, B, C

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



I-05 Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Southern Access

MOVEMENT SUMMARY



Site: I-05 Cumulative Scenario 2 AM

Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Southern Access

2030 Cumulative Scenario 2 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	4	0.0	0.732	13.0	LOS A	17.9	134.7	0.48	0.44	45.0
2	T1	1674	6.4	0.732	7.4	LOS A	17.9	134.7	0.48	0.44	50.1
Approach		1678	6.3	0.732	7.4	LOS A	17.9	134.7	0.48	0.44	50.1
East: SIMTA Southern Access (E)											
4	L2	1	0.0	0.237	52.1	LOS D	1.1	21.4	0.95	0.73	21.8
6	R2	22	100.0	0.237	52.6	LOS D	1.1	21.4	0.95	0.73	19.0
Approach		23	95.5	0.237	52.6	LOS D	1.1	21.4	0.95	0.73	19.1
North: Moorebank Avenue (N)											
8	T1	722	10.1	0.275	0.4	LOS A	0.5	3.8	0.03	0.03	59.4
9	R2	23	54.5	0.135	14.7	LOS B	0.4	3.8	0.58	0.69	37.1
Approach		745	11.4	0.275	0.8	LOS A	0.5	3.8	0.05	0.05	58.5
West: Warehouse Access 2 (W)											
10	L2	13	100.0	0.059	39.0	LOS C	0.5	6.8	0.82	0.68	24.3
12	R2	1	0.0	0.059	38.6	LOS C	0.5	6.8	0.82	0.68	25.6
Approach		14	92.3	0.059	39.0	LOS C	0.5	6.8	0.82	0.68	24.4
All Vehicles		2460	9.2	0.732	6.0	LOS A	17.9	134.7	0.35	0.32	51.5

PHASING SUMMARY



Site: I-05 Cumulative Scenario 2 AM


Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Southern Access

2030 Cumulative Scenario 2 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	68	88
Green Time (sec)	62	14	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	68	20	12
Phase Split	68 %	20 %	12 %



MOVEMENT SUMMARY

Site: I-05 Cumulative Scenario 2 PM

Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Southern Access
2030 Cumulative Scenario 2 PM PEAK
Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Prop. Queued Distance m	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)									
1	L2	1	0.0	0.284	LOS A	3.4	27.4	0.24	47.9
2	T1	619	10.7	4.9	LOS A	3.4	27.4	0.24	53.1
Approach		620	10.7	4.9	LOS A	3.4	27.4	0.24	53.1
East: SIMTA Southern Access (E)									
4	L2	1	0.0	0.179	LOS D	0.9	16.9	0.94	21.9
6	R2	17	100.0	52.1	LOS D	0.9	16.9	0.94	19.1
Approach		18	94.1	52.1	LOS D	0.9	16.9	0.94	19.3
North: Moorebank Avenue (N)									
8	T1	1926	5.1	0.698	LOS A	2.9	21.8	0.07	59.0
9	R2	13	100.0	10.7	LOS A	0.2	2.3	0.38	40.4
Approach		1939	5.7	0.698	LOS A	2.9	21.8	0.07	58.8
West: Warehouse Access 2 (W)									
10	L2	23	54.5	0.108	LOS C	1.1	11.0	0.86	23.3
12	R2	4	0.0	41.5	LOS C	1.1	11.0	0.86	24.6
Approach		27	46.2	41.9	LOS C	1.1	11.0	0.86	23.5
All Vehicles		2604	7.9	0.698	LOS A	3.4	27.4	0.13	56.0


PHASING SUMMARY

Site: I-05 Cumulative Scenario 2 PM

Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Southern Access
2030 Cumulative Scenario 2 PM PEAK
Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	68	88
Green Time (sec)	62	14	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	68	20	12
Phase Split	68 %	20 %	12 %



I-06 Intersection of Moorebank Avenue and Warehouse Access 3

MOVEMENT SUMMARY



Site: I-06 Cumulative Scenario 2 AM

Intersection of Moorebank Avenue and Warehouse Access 3

2030 Cumulative Scenario 2 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	24	0.0	0.676	17.7	LOS B	25.2	181.0	0.69	0.64	44.1
2	T1	1625	3.2	0.676	12.1	LOS A	25.2	181.6	0.69	0.63	48.2
Approach		1649	3.2	0.676	12.2	LOS A	25.2	181.6	0.69	0.63	48.2
North: Moorebank Avenue (N)											
8	T1	611	3.1	0.228	0.3	LOS A	0.4	3.0	0.03	0.02	59.6
9	R2	112	48.1	0.668	31.2	LOS C	4.9	60.3	1.00	0.93	28.6
Approach		722	10.1	0.668	5.1	LOS A	4.9	60.3	0.18	0.16	53.5
West: Warehouse Access 3 (W)											
10	L2	54	100.0	0.182	44.7	LOS D	1.2	22.2	0.88	0.73	21.2
12	R2	1	0.0	0.182	44.2	LOS D	1.2	20.6	0.88	0.73	28.1
Approach		55	98.1	0.182	44.7	LOS D	1.2	22.2	0.88	0.73	21.3
All Vehicles		2426	7.4	0.676	10.8	LOS A	25.2	181.6	0.54	0.50	48.6

PHASING SUMMARY



Site: I-06 Cumulative Scenario 2 AM


Intersection of Moorebank Avenue and Warehouse Access 3

2030 Cumulative Scenario 2 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	70	86
Green Time (sec)	64	10	8
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	70	16	14
Phase Split	70 %	16 %	14 %



MOVEMENT SUMMARY



Site: I-06 Cumulative Scenario 2 PM

Intersection of Moorebank Avenue and Warehouse Access 3

2030 Cumulative Scenario 2 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.270	21.5	LOS B	7.2	51.5	0.63	0.53	41.5
2	T1	507	2.5	0.270	16.0	LOS B	7.2	51.5	0.63	0.53	45.5
Approach		508	2.5	0.270	16.0	LOS B	7.2	51.5	0.63	0.53	45.5
North: Moorebank Avenue (N)											
8	T1	1879	2.4	0.698	0.5	LOS A	3.2	22.7	0.06	0.06	59.4
9	R2	54	100.0	0.157	10.3	LOS A	0.6	11.7	0.41	0.67	41.4
Approach		1933	5.1	0.698	0.8	LOS A	3.2	22.7	0.07	0.07	58.9
West: Warehouse Access 3 (W)											
10	L2	112	48.1	0.266	33.4	LOS C	3.8	47.1	0.79	0.75	24.3
12	R2	24	0.0	0.266	54.3	LOS D	1.5	12.5	0.97	0.73	25.3
Approach		136	39.5	0.266	37.2	LOS C	3.8	47.1	0.82	0.74	24.5
All Vehicles		2577	6.4	0.698	5.7	LOS A	7.2	51.5	0.22	0.20	53.0

PHASING SUMMARY



Site: I-06 Cumulative Scenario 2 PM


Intersection of Moorebank Avenue and Warehouse Access 3

2030 Cumulative Scenario 2 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	55	71
Green Time (sec)	49	10	23
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	55	16	29
Phase Split	55 %	16 %	29 %



3. Moorebank Avenue – 2030 cumulative scenario 3

I-01 Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

MOVEMENT SUMMARY



Site: I-01 Cumulative Scenario 3 AM

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Cumulative Scenario 3 AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles	Distance			
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	20	0.0	0.632	14.9	LOS B	12.1	104.5	0.43	0.49	44.0
2	T1	1264	17.3	0.632	8.7	LOS A	13.2	114.9	0.42	0.43	50.3
3	R2	473	3.1	1.482	475.0	LOS F	81.9	588.3	1.00	1.87	5.7
Approach		1757	13.3	1.482	134.2	LOS F	81.9	588.3	0.58	0.82	15.4
East: Anzac Road (E)											
4	L2	271	3.1	0.472	36.6	LOS C	11.7	83.8	0.84	0.81	34.0
5	T1	4	0.0	0.472	32.3	LOS C	11.7	83.8	0.84	0.81	33.0
6	R2	224	13.6	0.909	71.5	LOS F	14.4	112.2	1.00	1.03	26.1
Approach		499	7.8	0.909	52.3	LOS D	14.4	112.2	0.91	0.91	29.7
North: Moorebank Avenue (N)											
7	L2	383	9.9	0.221	5.7	LOS A	0.0	0.0	0.00	0.52	54.2
8	T1	1452	13.4	1.096	147.4	LOS F	71.2	598.4	0.86	1.58	14.1
9	R2	101	3.1	0.375	14.8	LOS B	1.8	12.7	0.62	0.72	41.8
Approach		1936	12.2	1.096	112.5	LOS F	71.2	598.4	0.68	1.33	17.8
West: Bapaume Road (W)											
10	L2	5	60.0	0.008	9.8	LOS A	0.1	0.6	0.41	0.56	43.4
11	T1	1	0.0	0.017	53.2	LOS D	0.1	0.8	0.95	0.61	27.4
12	R2	1	0.0	0.017	56.9	LOS E	0.1	0.8	0.95	0.61	23.4
Approach		7	42.9	0.017	22.7	LOS B	0.1	0.8	0.56	0.57	36.3
All Vehicles		4199	12.2	1.482	114.3	LOS F	81.9	598.4	0.66	1.06	17.6

PHASING SUMMARY



Site: I-01 Cumulative Scenario 3 AM


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Cumulative Scenario 3 AM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	D	E
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	64	89	101
Green Time (sec)	58	19	6	3
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	64	25	12	9
Phase Split	58 %	23 %	11 %	8 %



MOVEMENT SUMMARY



Site: I-01 Cumulative Scenario 3 PM

Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Cumulative Scenario 3 PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.513	8.5	LOS A	5.4	45.8	0.19	0.17	50.3
2	T1	1186	14.3	0.513	3.0	LOS A	5.4	45.8	0.18	0.17	56.3
3	R2	261	0.8	1.079	143.7	LOS F	27.7	195.0	1.00	1.35	15.4
Approach		1448	11.8	1.079	28.4	LOS B	27.7	195.0	0.33	0.38	37.0
East: Anzac Road (E)											
4	L2	568	2.2	0.929	64.0	LOS E	37.6	268.4	1.00	1.02	26.0
5	T1	1	0.0	0.929	59.6	LOS E	37.6	268.4	1.00	1.02	25.2
6	R2	391	5.4	1.212	264.7	LOS F	53.1	389.1	1.00	1.65	10.5
Approach		960	3.5	1.212	145.6	LOS F	53.1	389.1	1.00	1.28	15.8
North: Moorebank Avenue (N)											
7	L2	353	3.9	0.195	5.7	LOS A	0.0	0.0	0.00	0.53	54.4
8	T1	1419	13.2	0.904	27.1	LOS B	36.1	301.0	0.65	0.72	37.6
9	R2	23	18.2	0.128	22.3	LOS B	0.7	5.6	0.56	0.69	37.3
Approach		1795	11.4	0.904	22.8	LOS B	36.1	301.0	0.52	0.68	40.5
West: Bapaume Road (W)											
10	L2	111	4.8	0.287	9.3	LOS A	1.6	11.7	0.41	0.61	45.5
11	T1	7	0.0	0.204	58.3	LOS E	1.0	6.9	0.99	0.70	26.1
12	R2	11	0.0	0.204	62.0	LOS E	1.0	6.9	0.99	0.70	22.2
Approach		128	4.1	0.287	16.4	LOS B	1.6	11.7	0.49	0.63	40.6
All Vehicles		4332	9.6	1.212	51.7	LOS D	53.1	389.1	0.56	0.71	28.8

PHASING SUMMARY



Site: I-01 Cumulative Scenario 3 PM


Intersection of Moorebank Avenue, Anzac Road and Bapaume Road

2030 Cumulative Scenario 3 PM PEAK

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	67	81
Green Time (sec)	61	8	23
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	67	14	29
Phase Split	61 %	13 %	26 %



I-02 Intersection of Moorebank Avenue and DNSDC Access

MOVEMENT SUMMARY



Site: I-02 Cumulative Scenario 3 AM

Intersection of Moorebank Avenue and DNSDC Access

2030 Cumulative Scenario 3 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay v/c	Level of Service sec	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate per veh	Average Speed km/h		
South: Moorebank Avenue (S)											
2	T1	1718	11.7	0.627	0.5	LOS A	2.1	17.3	0.06	0.05	59.4
3	R2	44	2.4	0.201	17.9	LOS B	1.0	7.3	0.69	0.73	43.7
Approach		1762	11.5	0.627	1.0	LOS A	2.1	17.3	0.07	0.07	58.8
East: DNSDC Access (E)											
4	L2	6	33.3	0.608	59.4	LOS E	2.4	37.7	1.00	0.83	29.5
6	R2	39	83.8	0.608	60.0	LOS E	2.4	37.7	1.00	0.83	22.2
Approach		45	76.7	0.608	59.9	LOS E	2.4	37.7	1.00	0.83	23.2
North: Moorebank Avenue (N)											
7	L2	516	11.4	0.773	16.6	LOS B	24.4	200.7	0.66	0.73	42.0
8	T1	1205	11.9	0.773	6.6	LOS A	24.4	200.7	0.47	0.47	52.9
Approach		1721	11.7	0.773	9.6	LOS A	24.4	200.7	0.53	0.55	49.3
All Vehicles		3528	12.4	0.773	5.9	LOS A	24.4	200.7	0.31	0.31	52.9

PHASING SUMMARY



Site: I-02 Cumulative Scenario 3 AM


Intersection of Moorebank Avenue and DNSDC Access

2030 Cumulative Scenario 3 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



MOVEMENT SUMMARY



Site: I-02 Cumulative Scenario 3 PM

Intersection of Moorebank Avenue and DNSDC Access

2030 Cumulative Scenario 3 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
2	T1	1083	13.4	0.517	6.5	LOS A	8.4	70.7	0.35	0.31	53.7
3	R2	1	100.0	0.017	45.5	LOS D	0.0	0.6	0.84	0.63	33.4
Approach		1084	13.5	0.517	6.6	LOS A	8.4	70.7	0.35	0.31	53.7
East: DNSDC Access (E)											
4	L2	21	0.0	0.935	67.2	LOS E	24.1	188.7	1.00	1.07	28.3
6	R2	363	7.2	0.935	67.3	LOS E	24.1	188.7	1.00	1.07	23.6
Approach		384	6.8	0.935	67.2	LOS E	24.1	188.7	1.00	1.07	23.9
North: Moorebank Avenue (N)											
7	L2	46	88.6	0.926	33.1	LOS C	47.3	390.0	0.83	0.91	34.8
8	T1	1952	8.1	0.926	25.6	LOS B	48.7	377.3	0.83	0.90	41.1
Approach		1998	10.0	0.926	25.7	LOS B	48.7	390.0	0.83	0.90	41.0
All Vehicles		3466	10.8	0.935	24.3	LOS B	48.7	390.0	0.70	0.74	41.1

PHASING SUMMARY



Site: I-02 Cumulative Scenario 3 PM

Intersection of Moorebank Avenue and DNSDC Access

2030 Cumulative Scenario 3 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase times determined by the program

Sequence: NEW TCS I-02 PM 2


Movement Class: All Movement Classes

Input Sequence: A, B

Output Sequence: A, B

Phase Timing Results

Phase	A	B
Reference Phase	Yes	No
Phase Change Time (sec)	0	67
Green Time (sec)	61	27
Yellow Time (sec)	4	4
All-Red Time (sec)	2	2
Phase Time (sec)	67	33
Phase Split	67 %	33 %



I-03 Intersection of Moorebank Avenue, MIMT Main Access and SIMTA Central Access

MOVEMENT SUMMARY



Site: I-03 Cumulative Scenario 3 AM

Intersection of Moorebank Avenue, MIMT Main Access and SIMTA Central Access

2030 Cumulative Scenario 3 AM PEAK

Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand	Flows	Deg. Satn	Average	Level of	95% Back of Queue	Prop.	Effective	Average	
	v	Total	HV		Delay	Service	Vehicles	Queued	Stop Rate	Speed	
		veh/h	%	v/c	sec		veh	m	per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	7	0.0	0.693	9.5	LOS A	12.1	93.4	0.27	0.25	50.2
2	T1	1709	8.7	0.693	3.9	LOS A	12.1	93.4	0.26	0.25	56.3
3	R2	19	5.6	0.212	68.4	LOS E	1.1	8.3	0.99	0.70	20.4
Approach		1736	8.7	0.693	4.7	LOS A	12.1	93.4	0.27	0.25	55.7
East: SIMTA Central Access (E)											
4	L2	1	100.0	0.005	47.2	LOS D	0.0	0.6	0.83	0.60	24.4
6	R2	32	100.0	0.362	64.9	LOS E	1.9	35.2	0.98	0.74	24.3
Approach		33	100.0	0.362	64.3	LOS E	1.9	35.2	0.97	0.74	24.3
North: Moorebank Avenue (N)											
7	L2	398	13.0	0.501	14.5	LOS B	13.3	110.2	0.45	0.64	45.0
8	T1	775	9.4	0.501	4.2	LOS A	13.3	110.2	0.23	0.26	55.4
9	R2	39	54.1	0.701	75.9	LOS F	2.6	34.7	1.00	0.85	22.7
Approach		1212	12.0	0.701	9.9	LOS A	13.3	110.2	0.33	0.40	50.1
West: Main Access (W)											
10	L2	21	100.0	0.133	50.2	LOS D	1.1	20.2	0.86	0.72	27.6
12	R2	1	0.0	0.007	58.2	LOS E	0.1	0.4	0.93	0.59	22.3
Approach		22	95.2	0.133	50.6	LOS D	1.1	20.2	0.87	0.71	27.3
All Vehicles		3002	11.6	0.701	7.8	LOS A	13.3	110.2	0.31	0.32	52.5

PHASING SUMMARY



Site: I-03 Cumulative Scenario 3 AM


Intersection of Moorebank Avenue, MIMT Main Access and SIMTA Central Access

2030 Cumulative Scenario 3 AM PEAK

Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	88	108
Green Time (sec)	82	14	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	88	20	12
Phase Split	73 %	17 %	10 %



MOVEMENT SUMMARY



Site: I-03 Cumulative Scenario 3 PM

Intersection of Moorebank Avenue, MIMT Main Access and SIMTA Central Access

2030 Cumulative Scenario 3 PM PEAK

Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	95% Back of Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.649	42.6	LOS D	16.5	137.9	0.85	0.74	28.7
2	T1	706	14.3	0.649	37.0	LOS C	16.5	137.9	0.85	0.74	37.3
3	R2	1	100.0	0.020	52.3	LOS D	0.1	0.7	0.83	0.64	23.8
Approach		708	14.4	0.649	37.1	LOS C	16.5	137.9	0.85	0.74	37.2
East: SIMTA Central Access (E)											
4	L2	17	0.0	0.032	37.5	LOS C	0.7	4.9	0.75	0.67	28.1
6	R2	339	7.1	0.923	73.6	LOS F	24.7	195.3	1.00	1.06	23.1
Approach		356	6.8	0.923	71.9	LOS F	24.7	195.3	0.99	1.04	23.3
North: Moorebank Avenue (N)											
7	L2	40	100.0	0.902	29.1	LOS C	47.5	374.4	0.80	0.83	38.2
8	T1	1912	5.1	0.902	22.2	LOS B	48.9	360.7	0.80	0.81	43.9
9	R2	21	100.0	0.113	47.3	LOS D	1.0	19.2	0.83	0.72	29.2
Approach		1973	8.1	0.902	22.7	LOS B	48.9	374.4	0.80	0.81	43.6
West: Main Access (W)											
10	L2	39	54.1	0.063	18.1	LOS B	1.0	13.9	0.48	0.65	39.4
12	R2	7	0.0	0.018	37.5	LOS C	0.3	2.1	0.74	0.65	28.2
Approach		46	45.5	0.063	21.1	LOS B	1.0	13.9	0.52	0.65	37.5
All Vehicles		3083	9.9	0.923	31.6	LOS C	48.9	374.4	0.83	0.82	38.8

PHASING SUMMARY



Site: I-03 Cumulative Scenario 3 PM


Intersection of Moorebank Avenue, MIMT Main Access and SIMTA Central Access

2030 Cumulative Scenario 3 PM PEAK

Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	44	87
Green Time (sec)	38	37	27
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	44	43	33
Phase Split	37 %	36 %	28 %



I-04 Intersection of Moorebank Avenue and Warehouse Access 1

MOVEMENT SUMMARY



Site: I-04 Cumulative Scenario 3 AM

Intersection of Moorebank Avenue and Warehouse Access 1

2030 Cumulative Scenario 3 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV				Vehicles				
		veh/h	%	v/c	sec		veh	m		per veh	km/h
South: Moorebank Avenue (S)											
1	L2	11	0.0	0.721	10.4	LOS A	13.9	107.1	0.36	0.34	47.5
2	T1	1724	8.0	0.721	4.8	LOS A	13.9	107.1	0.36	0.33	53.9
Approach		1735	7.9	0.721	4.9	LOS A	13.9	107.1	0.36	0.33	53.8
North: Moorebank Avenue (N)											
8	T1	739	8.3	0.259	0.3	LOS A	0.5	3.6	0.03	0.03	59.5
9	R2	36	32.4	0.182	12.0	LOS A	0.5	4.4	0.50	0.68	41.9
Approach		775	9.4	0.259	0.9	LOS A	0.5	4.4	0.05	0.06	58.5
West: Warehouse Access 1 (W)											
10	L2	12	100.0	0.068	43.8	LOS D	0.5	6.7	0.87	0.69	25.4
12	R2	1	0.0	0.068	43.3	LOS D	0.5	6.7	0.87	0.69	23.5
Approach		13	91.7	0.068	43.8	LOS D	0.5	6.7	0.87	0.69	25.2
All Vehicles		2522	8.8	0.721	3.8	LOS A	13.9	107.1	0.27	0.25	54.9

PHASING SUMMARY



Site: I-04 Cumulative Scenario 3 AM


Intersection of Moorebank Avenue and Warehouse Access 1

2030 Cumulative Scenario 3 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



MOVEMENT SUMMARY



Site: I-04 Cumulative Scenario 3 PM

Intersection of Moorebank Avenue and Warehouse Access 1

2030 Cumulative Scenario 3 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total	HV				Vehicles veh	Distance m			
		veh/h	%								
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.294	8.6	LOS A	2.6	21.8	0.17	0.15	49.8
2	T1	669	13.2	0.294	3.1	LOS A	2.6	21.8	0.17	0.15	55.9
Approach		671	13.2	0.294	3.1	LOS A	2.6	21.8	0.17	0.15	55.9
North: Moorebank Avenue (N)											
8	T1	1925	4.5	0.655	0.5	LOS A	2.6	18.9	0.06	0.06	59.2
9	R2	12	100.0	0.037	9.5	LOS A	0.1	1.8	0.33	0.63	43.8
Approach		1937	5.1	0.655	0.6	LOS A	2.6	18.9	0.06	0.06	59.1
West: Warehouse Access 1 (W)											
10	L2	36	32.4	0.232	48.5	LOS D	2.1	17.9	0.93	0.74	24.3
12	R2	11	0.0	0.232	48.3	LOS D	2.1	17.9	0.93	0.74	22.1
Approach		46	25.0	0.232	48.5	LOS D	2.1	17.9	0.93	0.74	23.8
All Vehicles		2654	7.5	0.655	2.1	LOS A	2.6	21.8	0.11	0.10	57.1

PHASING SUMMARY



Site: I-04 Cumulative Scenario 3 PM


Intersection of Moorebank Avenue and Warehouse Access 1

2030 Cumulative Scenario 3 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



I-05 Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Southern Access

MOVEMENT SUMMARY



Site: I-05 Cumulative Scenario 3 AM

Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Southern Access

2030 Cumulative Scenario 3 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue	Prop. Queued	Effective Stop Rate	Average Speed	
	v	Total	HV								
		veh/h	%	v/c	sec		veh	m	per veh	km/h	
South: Moorebank Avenue (S)											
1	L2	8	0.0	0.728	13.0	LOS A	17.9	131.9	0.47	0.44	45.0
2	T1	1683	5.1	0.728	7.4	LOS A	17.9	131.9	0.47	0.44	50.2
Approach		1692	5.1	0.728	7.4	LOS A	17.9	131.9	0.47	0.44	50.1
East: SIMTA Southern Access (E)											
4	L2	1	100.0	0.429	54.0	LOS D	2.1	40.0	0.97	0.76	19.2
6	R2	42	100.0	0.429	54.0	LOS D	2.1	40.0	0.97	0.76	18.8
Approach		43	100.0	0.429	54.0	LOS D	2.1	40.0	0.97	0.76	18.8
North: Moorebank Avenue (N)											
8	T1	708	7.3	0.261	0.4	LOS A	0.5	3.5	0.03	0.03	59.4
9	R2	29	32.1	0.149	14.1	LOS A	0.4	4.0	0.57	0.69	37.8
Approach		738	8.3	0.261	0.9	LOS A	0.5	4.0	0.05	0.05	58.3
West: Warehouse Access 2 (W)											
10	L2	9	100.0	0.047	39.7	LOS C	0.4	5.2	0.82	0.67	24.0
12	R2	1	0.0	0.047	39.3	LOS C	0.4	5.2	0.82	0.67	25.4
Approach		11	90.0	0.047	39.7	LOS C	0.4	5.2	0.82	0.67	24.2
All Vehicles		2483	8.1	0.728	6.4	LOS A	17.9	131.9	0.36	0.33	50.8

PHASING SUMMARY



Site: I-05 Cumulative Scenario 3 AM


Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Southern Access

2030 Cumulative Scenario 3 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	68	88
Green Time (sec)	62	14	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	68	20	12
Phase Split	68 %	20 %	12 %



MOVEMENT SUMMARY



Site: I-05 Cumulative Scenario 3 PM

Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Southern Access

2030 Cumulative Scenario 3 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.268	10.4	LOS A	3.3	25.0	0.24	0.21	48.0
2	T1	606	7.6	0.268	4.8	LOS A	3.3	25.0	0.24	0.21	53.2
Approach		607	7.6	0.268	4.8	LOS A	3.3	25.0	0.24	0.21	53.2
East: SIMTA Southern Access (E)											
4	L2	1	100.0	0.339	53.4	LOS D	1.7	31.9	0.96	0.75	19.3
6	R2	33	100.0	0.339	53.4	LOS D	1.7	31.9	0.96	0.75	18.9
Approach		34	100.0	0.339	53.4	LOS D	1.7	31.9	0.96	0.75	18.9
North: Moorebank Avenue (N)											
8	T1	1926	4.0	0.689	0.6	LOS A	2.8	20.8	0.07	0.06	59.0
9	R2	9	100.0	0.028	10.6	LOS A	0.1	1.7	0.37	0.63	40.6
Approach		1936	4.5	0.689	0.7	LOS A	2.8	20.8	0.07	0.07	58.9
West: Warehouse Access 2 (W)											
10	L2	29	32.1	0.148	43.8	LOS D	1.6	13.7	0.89	0.72	23.0
12	R2	8	0.0	0.148	43.6	LOS D	1.6	13.7	0.89	0.72	24.0
Approach		38	25.0	0.148	43.8	LOS D	1.6	13.7	0.89	0.72	23.2
All Vehicles		2615	6.8	0.689	3.0	LOS A	3.3	31.9	0.13	0.12	55.2

PHASING SUMMARY



Site: I-05 Cumulative Scenario 3 PM


Intersection of Moorebank Avenue, Warehouse Access 2 and SIMTA Southern Access

2030 Cumulative Scenario 3 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	D
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	68	88
Green Time (sec)	62	14	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	68	20	12
Phase Split	68 %	20 %	12 %



I-06 Intersection of Moorebank Avenue and Warehouse Access 3

MOVEMENT SUMMARY



Site: I-06 Cumulative Scenario 3 AM

Intersection of Moorebank Avenue and Warehouse Access 3

2030 Cumulative Scenario 3 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay v/c	Level of Service sec	95% Back of Queue Vehicles	Prop. Queued Distance	Effective Stop Rate per veh	Average Speed km/h		
South: Moorebank Avenue (S)											
1	L2	28	0.0	0.671	16.6	LOS B	24.8	178.0	0.66	0.62	44.9
2	T1	1660	3.2	0.671	11.0	LOS A	24.8	178.7	0.66	0.61	49.1
Approach		1688	3.2	0.671	11.1	LOS A	24.8	178.7	0.66	0.61	49.0
North: Moorebank Avenue (N)											
8	T1	612	3.3	0.229	0.3	LOS A	0.4	3.0	0.03	0.02	59.6
9	R2	98	33.3	0.595	23.1	LOS B	3.5	36.3	0.90	0.84	32.7
Approach		709	7.4	0.595	3.5	LOS A	3.5	36.3	0.15	0.14	55.4
West: Warehouse Access 3 (W)											
10	L2	33	100.0	0.121	46.0	LOS D	0.8	13.0	0.89	0.71	20.9
12	R2	1	0.0	0.121	45.6	LOS D	0.7	11.7	0.89	0.71	27.7
Approach		34	96.9	0.121	46.0	LOS D	0.8	13.0	0.89	0.71	21.1
All Vehicles		2432	5.7	0.671	9.4	LOS A	24.8	178.7	0.52	0.47	50.0

PHASING SUMMARY



Site: I-06 Cumulative Scenario 3 AM


Intersection of Moorebank Avenue and Warehouse Access 3

2030 Cumulative Scenario 3 AM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	72	88
Green Time (sec)	66	10	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	72	16	12
Phase Split	72 %	16 %	12 %



MOVEMENT SUMMARY



Site: I-06 Cumulative Scenario 3 PM

Intersection of Moorebank Avenue and Warehouse Access 3

2030 Cumulative Scenario 3 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Moorebank Avenue (S)											
1	L2	1	0.0	0.233	16.8	LOS B	6.1	43.4	0.53	0.45	44.9
2	T1	508	2.7	0.233	11.3	LOS A	6.1	43.5	0.53	0.45	48.9
Approach		509	2.7	0.233	11.3	LOS A	6.1	43.5	0.53	0.45	48.9
North: Moorebank Avenue (N)											
8	T1	1903	2.4	0.707	0.5	LOS A	3.3	23.6	0.06	0.06	59.4
9	R2	33	100.0	0.102	10.0	LOS A	0.4	6.5	0.38	0.65	41.7
Approach		1936	4.0	0.707	0.7	LOS A	3.3	23.6	0.07	0.07	59.1
West: Warehouse Access 3 (W)											
10	L2	98	33.3	0.271	38.9	LOS C	3.7	38.4	0.85	0.76	23.5
12	R2	28	0.0	0.271	54.2	LOS D	1.6	12.1	0.97	0.73	25.3
Approach		126	25.8	0.271	42.3	LOS C	3.7	38.4	0.88	0.75	24.0
All Vehicles		2572	4.8	0.707	4.8	LOS A	6.1	43.5	0.20	0.18	54.1

PHASING SUMMARY



Site: I-06 Cumulative Scenario 3 PM


Intersection of Moorebank Avenue and Warehouse Access 3

2030 Cumulative Scenario 3 PM PEAK

Signals - Fixed Time Cycle Time = 100 seconds (User-Given Cycle Time)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	63	79
Green Time (sec)	57	10	15
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	63	16	21
Phase Split	63 %	16 %	21 %



4. On the wider road network – 2030 cumulative scenario 1

I-01 Intersection of the Hume Highway and Orange Grove Road

MOVEMENT SUMMARY



Site: I-01 2030 MIMT & SIMTA AM

Hume Highway / Orange Grove Road

2030 MIMT & SIMTA AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
	v	Total	HV		sec		Vehicles	Distance		per veh	km/h
		veh/h	%	v/c			veh	m			
NorthEast: Hume Highway (NE)											
25	T1	965	11.1	0.691	24.4	LOS B	19.9	152.6	0.85	0.77	35.7
26	R2	389	10.0	0.907	86.6	LOS F	17.0	128.8	1.00	0.94	23.8
Approach		1354	10.8	0.907	42.3	LOS C	19.9	152.6	0.89	0.82	30.0
NorthWest: Orange Grove Road (NW)											
27	L2	602	6.5	0.712	18.8	LOS B	19.5	144.4	0.54	0.81	44.8
29	R2	1355	8.9	1.011	122.9	LOS F	48.1	367.8	1.00	1.09	16.6
Approach		1957	8.1	1.065	90.9	LOS F	48.1	367.8	0.86	1.00	21.1
SouthWest: Hume Highway (SW)											
30	L2	1286	9.0	0.465	11.7	LOS A	14.6	111.6	0.35	0.70	50.0
31	T1	2186	4.9	0.805	22.9	LOS B	39.5	287.9	0.71	0.65	40.2
Approach		3472	6.4	0.805	18.7	LOS B	39.5	287.9	0.57	0.67	43.9
All Vehicles		6784	7.8	1.065	44.2	LOS D	48.1	367.8	0.72	0.79	30.3

PHASING SUMMARY



Site: I-01 2030 MIMT & SIMTA AM

Hume Highway / Orange Grove Road

2030 MIMT & SIMTA AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	84	108
Green Time (sec)	77	17	36
Yellow Time (sec)	5	4	5
All-Red Time (sec)	2	2	2
Phase Time (sec)	84	23	43
Phase Split	56 %	15 %	29 %



MOVEMENT SUMMARY

 **Site: I-01 2030 MIMT & SIMTA PM**

Hume Highway / Orange Grove Road

2030 MIMT & SIMTA PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMov	Demand Flows		Deg. Satn	Average Delay	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate	Average Speed
		Total	HV				Vehicles	Distance			
		veh/h	%				v/c	sec			
NorthEast: Hume Highway (NE)											
25	T1	1766	3.5	0.922	45.5	LOS D	50.8	366.7	0.91	0.98	26.5
26	R2	816	2.8	0.958	68.1	LOS E	24.7	176.9	1.00	1.04	27.6
Approach		2582	3.3	0.958	52.6	LOS D	50.8	366.7	0.94	1.00	26.9
NorthWest: Orange Grove Road (NW)											
27	L2	391	4.3	0.366	12.9	LOS A	7.0	50.8	0.28	0.64	49.0
29	R2	1393	5.5	1.094	156.7	LOS F	60.7	451.1	1.00	1.20	13.9
Approach		1783	5.3	1.094	125.2	LOS F	60.7	451.1	0.84	1.07	16.9
SouthWest: Hume Highway (SW)											
30	L2	1320	5.4	0.789	19.8	LOS B	21.0	156.3	0.80	0.84	44.6
31	T1	1100	5.5	0.990	94.2	LOS F	39.6	291.0	1.00	1.15	17.2
Approach		2420	5.4	0.990	53.6	LOS D	39.6	291.0	0.89	0.98	27.6
All Vehicles		6786	4.6	1.094	72.1	LOS F	60.7	451.1	0.90	1.01	23.1

PHASING SUMMARY

 **Site: I-01 2030 MIMT & SIMTA PM**


Hume Highway / Orange Grove Road

2030 MIMT & SIMTA PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C	D
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	53	80	124
Green Time (sec)	47	20	38	19
Yellow Time (sec)	5	4	5	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	54	26	45	25
Phase Split	36 %	17 %	30 %	17 %



I-02 Intersection of the Hume Highway and Elizabeth Drive

MOVEMENT SUMMARY

 **Site: I-02 2030 MIMT & SIMTA AM**

Hume Highway / Elizabeth Drive

2030 MIMT & SIMTA AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h	
South: Hume Highway (S)											
1	L2	137	5.4	0.155	22.6	LOS B	3.7	27.3	0.40	0.68	36.5
2	T1	2390	7.8	0.972	69.1	LOS E	72.3	544.2	0.99	1.08	18.2
Approach		2527	7.7	0.992	66.6	LOS E	72.3	544.2	0.96	1.06	18.8
East: Elizabeth Drive (E)											
4	L2	39	5.4	0.426	59.6	LOS E	10.5	77.4	0.91	0.82	18.6
5	T1	502	5.7	0.426	55.8	LOS D	11.9	87.2	0.90	0.82	23.7
6	R2	156	2.7	0.754	78.2	LOS F	11.7	83.5	1.00	0.87	14.8
Approach		697	5.0	0.754	61.0	LOS E	11.9	87.2	0.92	0.83	21.1
North: Hume Highway (N)											
7	L2	82	2.6	0.653	25.9	LOS B	24.4	185.9	0.61	0.58	31.5
8	T1	1770	10.4	0.653	19.8	LOS B	24.7	190.2	0.60	0.55	35.9
9	R2	353	9.6	1.170	248.6	LOS F	25.1	189.8	1.00	1.38	7.6
Approach		2205	9.9	1.170	56.6	LOS E	25.1	190.2	0.66	0.69	21.1
West: Elizabeth Drive (W)											
10	L2	627	5.2	1.011	108.6	LOS F	62.6	457.9	1.00	1.06	14.6
11	T1	1089	3.0	1.050	135.4	LOS F	59.4	426.7	1.00	1.34	11.9
12	R2	517	7.1	1.129	381.8	LOS F	61.4	458.6	1.00	1.60	5.3
Approach		2234	4.6	1.129	184.9	LOS F	62.6	458.6	1.00	1.32	9.5
All Vehicles		7663	7.2	1.170	97.7	LOS F	72.3	544.2	0.88	1.01	14.8

PHASING SUMMARY

 **Site: I-02 2030 MIMT & SIMTA AM**


Hume Highway / Elizabeth Drive

2030 MIMT & SIMTA AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	D	F	A	E
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	66	89	131
Green Time (sec)	60	17	36	13
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	66	23	42	19
Phase Split	44 %	15 %	28 %	13 %



MOVEMENT SUMMARY



Site: I-02 2030 MIMT & SIMTA PM

Hume Highway / Elizabeth Drive

2030 MIMT & SIMTA PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	323	5.6	0.477	39.9	LOS C	15.2	112.2	0.70	0.78	28.3
2	T1	1554	7.0	0.941	71.2	LOS F	45.3	340.7	0.98	1.05	17.8
Approach		1876	6.8	0.941	65.8	LOS E	45.3	340.7	0.93	1.00	19.2
East: Elizabeth Drive (E)											
4	L2	128	0.8	0.984	107.9	LOS F	33.6	239.2	1.00	1.16	12.0
5	T1	1082	2.3	0.984	104.0	LOS F	42.8	305.9	1.00	1.19	15.2
6	R2	172	0.0	1.066	165.1	LOS F	19.6	137.4	1.00	1.29	8.2
Approach		1382	1.9	1.066	112.0	LOS F	42.8	305.9	1.00	1.20	13.7
North: Hume Highway (N)											
7	L2	66	4.8	0.880	26.4	LOS B	44.8	328.2	0.75	0.74	31.5
8	T1	2483	4.4	0.880	20.6	LOS B	45.5	333.6	0.75	0.73	35.5
9	R2	961	3.0	0.917	76.9	LOS F	37.9	271.9	1.00	0.96	19.4
Approach		3511	4.0	0.917	36.1	LOS C	45.5	333.6	0.82	0.79	28.1
West: Elizabeth Drive (W)											
10	L2	325	5.8	0.434	34.2	LOS C	13.6	100.2	0.62	0.76	29.6
11	T1	529	4.4	0.698	61.8	LOS E	17.6	127.6	0.96	0.82	20.9
12	R2	309	2.4	0.978	112.9	LOS F	14.4	102.8	1.00	1.08	14.6
Approach		1164	4.2	0.978	67.6	LOS E	17.6	127.6	0.88	0.87	20.2
All Vehicles		7933	4.3	1.066	61.0	LOS E	45.5	340.7	0.88	0.92	20.8

PHASING SUMMARY



Site: I-02 2030 MIMT & SIMTA PM


Hume Highway / Elizabeth Drive

2030 MIMT & SIMTA PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	D	F	A	E
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	53	72	108
Green Time (sec)	47	13	30	36
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	53	19	36	42
Phase Split	35 %	13 %	24 %	28 %



I-03 Intersection of the Hume Highway and Memorial Avenue

MOVEMENT SUMMARY



Site: I-03 2030 MIMT & SIMTA AM

Hume Highway / Memorial Avenue

2030 MIMT & SIMTA AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total veh/h	Deg. Satn HV %	Average Delay v/c sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h	
South: Hume Highway (S)											
1	L2	157	1.3	0.979	77.2	LOS F	73.9	553.0	1.00	1.11	25.1
2	T1	2135	8.6	0.979	69.0	LOS E	75.1	569.7	0.94	1.07	23.2
3	R2	267	0.0	1.137	222.0	LOS F	36.2	253.5	1.00	1.30	9.4
Approach		2559	7.2	1.137	85.4	LOS F	75.1	569.7	0.95	1.10	20.3
East: Memorial Avenue (E)											
4	L2	29	28.6	1.264	333.5	LOS F	29.0	222.7	1.00	1.72	6.7
5	T1	164	7.7	1.264	328.8	LOS F	29.0	222.7	1.00	1.71	6.6
6	R2	134	18.1	1.264	333.8	LOS F	26.0	208.4	1.00	1.69	4.7
Approach		327	13.8	1.264	331.2	LOS F	29.0	222.7	1.00	1.71	5.8
North: Hume Highway (N)											
7	L2	121	6.1	0.103	12.4	LOS A	2.6	19.4	0.36	0.64	39.4
8	T1	1779	13.0	0.767	28.7	LOS C	33.2	261.6	0.75	0.68	36.2
9	R2	101	3.1	0.439	72.0	LOS F	7.0	50.1	0.97	0.79	21.4
Approach		2001	12.1	0.767	29.9	LOS C	33.2	261.6	0.74	0.68	35.1
West: Memorial Avenue (W)											
10	L2	128	3.3	1.181	241.5	LOS F	47.6	339.8	1.00	1.57	9.0
11	T1	460	1.6	1.181	244.4	LOS F	59.4	423.7	1.00	1.63	8.5
12	R2	165	3.2	1.181	256.2	LOS F	59.4	423.7	1.00	1.68	10.8
Approach		753	2.2	1.181	246.5	LOS F	59.4	423.7	1.00	1.63	9.1
All Vehicles		5641	8.7	1.264	101.5	LOS F	75.1	569.7	0.88	1.06	17.7

PHASING SUMMARY



Site: I-03 2030 MIMT & SIMTA AM


Hume Highway / Memorial Avenue

2030 MIMT & SIMTA AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E	F
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	75	108	125
Green Time (sec)	69	27	11	19
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	75	33	17	25
Phase Split	50 %	22 %	11 %	17 %



MOVEMENT SUMMARY



Site: I-03 2030 MIMT & SIMTA PM

Hume Highway / Memorial Avenue

2030 MIMT & SIMTA PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	121	0.9	0.834	48.4	LOS D	38.2	284.9	0.92	0.88	31.8
2	T1	1663	7.5	0.834	40.3	LOS C	39.0	294.5	0.88	0.83	31.0
3	R2	116	0.0	0.779	84.5	LOS F	8.9	62.5	1.00	0.87	19.4
Approach		1899	6.6	0.834	43.5	LOS D	39.0	294.5	0.89	0.83	30.1
East: Memorial Avenue (E)											
4	L2	55	0.0	1.228	299.2	LOS F	46.0	326.8	1.00	1.82	7.4
5	T1	289	2.2	1.228	294.7	LOS F	46.0	326.8	1.00	1.79	7.2
6	R2	211	6.0	1.228	299.7	LOS F	42.5	310.9	1.00	1.68	5.2
Approach		555	3.4	1.228	297.1	LOS F	46.0	326.8	1.00	1.75	6.5
North: Hume Highway (N)											
7	L2	152	2.8	0.090	8.4	LOS A	2.0	14.7	0.24	0.61	43.5
8	T1	2964	4.1	0.942	21.7	LOS B	66.7	486.4	0.70	0.70	40.1
9	R2	214	2.0	0.729	42.6	LOS D	9.2	65.3	1.00	0.83	28.2
Approach		3330	3.9	0.942	22.4	LOS B	66.7	486.4	0.69	0.71	39.1
West: Memorial Avenue (W)											
10	L2	82	1.3	0.947	94.0	LOS F	17.8	125.8	1.00	1.14	18.3
11	T1	209	1.0	0.947	90.9	LOS F	22.1	155.1	1.00	1.12	17.5
12	R2	171	0.0	0.947	98.0	LOS F	22.1	155.1	1.00	1.09	21.4
Approach		462	0.7	0.947	94.1	LOS F	22.1	155.1	1.00	1.11	19.2
All Vehicles		6246	4.4	1.228	58.5	LOS E	66.7	486.4	0.80	0.87	25.1

PHASING SUMMARY



Site: I-03 2030 MIMT & SIMTA PM


Hume Highway / Memorial Avenue

2030 MIMT & SIMTA PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	D	E	F
Reference Phase	Yes	No	No	No	No
Phase Change Time (sec)	0	67	81	108	132
Green Time (sec)	61	8	21	18	12
Yellow Time (sec)	4	4	4	4	4
All-Red Time (sec)	2	2	2	2	2
Phase Time (sec)	67	14	27	24	18
Phase Split	45 %	9 %	18 %	16 %	12 %



I-04 Intersection of the Hume Highway and Hoxton Park Drive

MOVEMENT SUMMARY



Site: I-04 2030 MIMT & SIMTA AM

Hume Highway / Hoxton Park Road / Macquarie Street

2030 MIMT & SIMTA AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo v	Demand Flows Total	Deg. Satn HV	Average Delay	Level of Service	95% Back of Queue Vehicles	Queue Distance	Prop. Queued	Effective Stop Rate	Average Speed	
		veh/h	%	v/c	sec	veh	m		per veh	km/h	
South: Hume Highway (S)											
1	L2	110	13.8	0.098	8.8	LOS A	0.9	7.4	0.13	0.57	50.6
2	T1	2159	6.5	0.852	31.5	LOS C	44.5	331.6	0.83	0.78	37.9
3	R2	1213	1.9	1.079	138.0	LOS F	52.5	373.6	1.00	1.22	13.8
Approach		3481	5.1	1.079	67.9	LOS E	52.5	373.6	0.87	0.93	25.3
East: Macquarie Street (E)											
4	L2	361	5.8	0.230	21.3	LOS B	5.5	40.4	0.66	0.73	39.0
5	T1	545	4.6	1.080	170.2	LOS F	32.6	237.6	1.00	1.38	13.2
Approach		906	5.1	1.080	110.9	LOS F	32.6	237.6	0.86	1.12	17.4
North: Hume Highway (N)											
7	L2	236	15.6	1.020	70.7	LOS F	51.1	399.0	1.00	1.07	23.8
8	T1	1493	10.3	1.020	104.2	LOS F	61.9	478.9	1.00	1.20	20.4
9	R2	246	19.2	1.257	327.7	LOS F	41.2	336.2	1.00	1.59	9.2
Approach		1975	12.1	1.257	128.1	LOS F	61.9	478.9	1.00	1.24	17.7
West: Hoxton Park Road (W)											
10	L2	345	18.0	0.583	47.3	LOS D	20.3	164.2	0.87	0.83	32.5
11	T1	1372	4.8	1.131	228.5	LOS F	69.0	502.9	1.00	1.64	10.4
12	R2	392	4.8	1.148	181.2	LOS F	29.4	215.4	1.00	1.25	14.0
Approach		2109	7.0	1.148	190.0	LOS F	69.0	502.9	0.98	1.44	12.7
All Vehicles		8471	7.2	1.257	116.9	LOS F	69.0	502.9	0.93	1.15	18.1

PHASING SUMMARY



Site: I-04 2030 MIMT & SIMTA AM


Hume Highway / Hoxton Park Road / Macquarie Street

2030 MIMT & SIMTA AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	C	E	D	F
Reference Phase	Yes	No	No	No	No
Phase Change Time (sec)	0	49	77	100	126
Green Time (sec)	43	22	17	20	18
Yellow Time (sec)	4	4	4	4	4
All-Red Time (sec)	2	2	2	2	2
Phase Time (sec)	49	28	23	26	24
Phase Split	33 %	19 %	15 %	17 %	16 %



MOVEMENT SUMMARY



Site: I-04 2030 MIMT & SIMTA PM

Hume Highway / Hoxton Park Road / Macquarie Street

2030 MIMT & SIMTA PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	201	7.0	0.171	9.6	LOS A	2.1	15.4	0.16	0.59	50.2
2	T1	1617	7.5	0.651	24.3	LOS B	25.6	193.6	0.64	0.58	41.4
3	R2	448	1.2	0.934	95.5	LOS F	19.1	135.2	1.00	1.00	18.1
Approach		2266	6.2	0.934	37.1	LOS C	25.6	193.6	0.67	0.66	34.8
East: Macquarie Street (E)											
4	L2	785	1.5	1.024	163.1	LOS F	39.7	281.3	0.98	1.11	12.1
5	T1	706	3.3	1.087	167.6	LOS F	41.8	300.7	1.00	1.39	13.3
Approach		1492	2.3	1.087	165.2	LOS F	41.8	300.7	0.99	1.24	12.7
North: Hume Highway (N)											
7	L2	101	5.2	0.971	38.2	LOS C	79.4	579.2	0.96	1.03	34.2
8	T1	2847	3.8	0.971	33.4	LOS C	80.6	587.5	0.85	0.91	37.0
9	R2	283	6.3	1.406	459.4	LOS F	56.5	417.3	1.00	1.82	6.9
Approach		3232	4.1	1.406	70.8	LOS F	80.6	587.5	0.86	0.99	26.0
West: Hoxton Park Road (W)											
10	L2	252	4.2	0.395	44.4	LOS D	13.7	99.2	0.80	0.80	33.6
11	T1	717	4.3	0.439	46.6	LOS D	14.2	102.8	0.87	0.73	30.4
12	R2	389	3.9	1.270	265.4	LOS F	35.7	261.3	1.00	1.44	10.3
Approach		1357	4.2	1.270	108.9	LOS F	35.7	261.3	0.89	0.95	19.3
All Vehicles		8347	4.4	1.406	84.7	LOS F	80.6	587.5	0.84	0.94	22.6

PHASING SUMMARY



Site: I-04 2030 MIMT & SIMTA PM


Hume Highway / Hoxton Park Road / Macquarie Street

2030 MIMT & SIMTA PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	E	D	F
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	78	98	127
Green Time (sec)	72	14	23	17
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	78	20	29	23
Phase Split	52 %	13 %	19 %	15 %



I-05 Intersection of the Hume Highway and Reilly Street

MOVEMENT SUMMARY



Site: I-05 2030 MIMT & SIMTA AM

Hume Highway / Reilly Street

2030 MIMT & SIMTA AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles											
Mov ID	ODMo	Demand	Flows	Deg. Satn	Average	Level of	95% Back of Queue	Prop.	Effective	Average	
	v	Total	HV		Delay	Service	Vehicles	Queued	Stop Rate	Speed	
		veh/h	%	v/c	sec		veh	m	per veh	km/h	
South: Hume Highway (S)											
1	L2	80	2.6	0.946	35.3	LOS C	75.7	554.5	0.87	0.90	34.8
2	T1	3181	4.7	0.946	29.1	LOS C	75.7	554.5	0.80	0.84	34.2
3	R2	14	7.7	0.112	24.3	LOS B	0.5	3.8	0.51	0.68	36.2
Approach		3275	4.7	0.946	29.2	LOS C	75.7	554.5	0.80	0.84	34.2
East: Congressional Drive (E)											
4	L2	49	2.1	0.263	59.1	LOS E	5.9	42.6	0.89	0.74	24.5
5	T1	46	4.5	0.263	54.5	LOS D	5.9	42.6	0.89	0.74	24.0
6	R2	91	4.7	0.428	67.2	LOS E	6.1	44.6	0.95	0.79	18.7
Approach		186	4.0	0.428	61.9	LOS E	6.1	44.6	0.92	0.76	21.6
North: Hume Highway (N)											
7	L2	32	3.3	0.567	18.1	LOS B	22.4	170.9	0.53	0.57	39.3
8	T1	1883	9.4	0.567	11.2	LOS A	25.5	195.5	0.51	0.49	46.4
9	R2	99	1.1	0.773	60.7	LOS E	6.1	43.1	1.00	0.93	22.5
Approach		2013	8.9	0.773	13.8	LOS A	25.5	195.5	0.53	0.52	43.9
West: Reilly Street (W)											
10	L2	120	3.5	0.274	50.3	LOS D	7.6	55.2	0.83	0.76	24.5
11	T1	14	7.7	0.274	45.7	LOS D	7.6	55.2	0.83	0.76	25.6
12	R2	235	1.3	1.033	150.9	LOS F	26.2	185.2	1.00	1.22	14.4
Approach		369	2.3	1.033	114.3	LOS F	26.2	185.2	0.94	1.05	16.6
All Vehicles		5844	6.0	1.033	30.3	LOS C	75.7	554.5	0.72	0.74	33.4

PHASING SUMMARY



Site: I-05 2030 MIMT & SIMTA AM


Hume Highway / Reilly Street

2030 MIMT & SIMTA AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E2
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	100	138
Green Time (sec)	94	32	6
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	100	38	12
Phase Split	67 %	25 %	8 %



MOVEMENT SUMMARY



Site: I-05 2030 MIMT & SIMTA PM

Hume Highway / Reilly Street

2030 MIMT & SIMTA PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows		Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue		Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
		Total veh/h	HV %				Vehicles veh	Distance m			
South: Hume Highway (S)											
1	L2	225	0.5	0.679	19.9	LOS B	27.0	198.3	0.54	0.58	41.7
2	T1	2080	6.5	0.679	11.8	LOS A	27.0	198.3	0.47	0.45	45.5
3	R2	21	5.0	0.392	31.0	LOS C	1.0	7.6	0.62	0.73	33.1
Approach		2326	5.9	0.679	12.8	LOS A	27.0	198.3	0.48	0.47	44.9
East: Congressional Drive (E)											
4	L2	42	2.5	0.205	61.9	LOS E	4.2	29.6	0.90	0.73	23.8
5	T1	24	0.0	0.205	57.3	LOS E	4.2	29.6	0.90	0.73	23.3
6	R2	52	0.0	0.236	65.6	LOS E	3.4	23.6	0.92	0.75	19.1
Approach		118	0.9	0.236	62.6	LOS E	4.2	29.6	0.91	0.74	21.7
North: Hume Highway (N)											
7	L2	67	0.0	0.993	43.5	LOS D	110.4	799.2	0.91	1.03	26.0
8	T1	3707	3.3	0.993	39.6	LOS C	110.4	799.2	0.69	0.83	29.6
9	R2	178	1.2	0.810	59.8	LOS E	11.8	83.4	1.00	1.02	22.7
Approach		3952	3.2	0.993	40.6	LOS C	110.4	799.2	0.70	0.84	29.1
West: Reilly Street (W)											
10	L2	65	0.0	0.235	56.1	LOS D	5.8	40.6	0.86	0.74	23.5
11	T1	32	0.0	0.235	51.6	LOS D	5.8	40.6	0.86	0.74	24.5
12	R2	261	1.6	1.120	214.2	LOS F	35.0	248.2	1.00	1.37	11.0
Approach		358	1.2	1.120	171.0	LOS F	35.0	248.2	0.96	1.20	12.6
All Vehicles		6754	4.0	1.120	38.3	LOS C	110.4	799.2	0.64	0.73	30.1

PHASING SUMMARY



Site: I-05 2030 MIMT & SIMTA PM


Hume Highway / Reilly Street

2030 MIMT & SIMTA PM PEAK 4:30 pm - 5:30 pm

Signals - Fixed Time Cycle Time = 150 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	D	E2
Reference Phase	Yes	No	No
Phase Change Time (sec)	0	98	133
Green Time (sec)	92	29	11
Yellow Time (sec)	4	4	4
All-Red Time (sec)	2	2	2
Phase Time (sec)	98	35	17
Phase Split	65 %	23 %	11 %



I-06 Intersection of Newbridge Road and Moorebank Avenue

MOVEMENT SUMMARY



Site: I-06 2030 MIMT & SIMTA AM



Network: 2030 MIMT &
SIMTA AM

Newbridge Road / Moorebank Avenue

2030 MIMT & SIMTA AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Movement Performance - Vehicles

Mov ID	ODMo v	Demand Flows Total veh/h	HV %	Arrival Flows Total veh/h	HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Moorebank Avenue (S)													
1	L2	1535	3.1	1224	3.2	0.632	18.9	LOS B	13.4	96.5	0.56	0.82	42.3
3	R2	1410	11.9	1127	12.2	0.684	15.2	LOS B	14.4	113.6	0.43	0.69	52.3
Approach		2944	7.3	2351 ^{N1}	7.5	0.684	17.1	LOS B	14.4	113.6	0.50	0.76	47.8
East: Newbridge Road (E)													
4	L2	719	21.8	719	21.8	0.663	19.5	LOS B	9.7	81.7	0.77	0.82	51.2
5	T1	965	5.1	965	5.1	1.260	311.5	LOS F	77.3	564.9	1.00	1.91	14.7
Approach		1684	12.2	1684	12.2	1.260	186.9	LOS F	77.3	564.9	0.90	1.44	19.0
West: Newbridge Road (W)													
11	T1	1581	6.5	1581	6.5	0.852	12.4	LOS A	30.8	227.8	0.63	0.60	60.9
12	R2	882	7.6	882	7.6	1.711	697.0	LOS F	103.0	769.2	1.00	2.01	3.0
Approach		2463	6.9	2463	6.9	1.711	257.6	LOS F	103.0	769.2	0.76	1.10	14.0
All Vehicles		7092	8.4	6498 ^{N1}	9.1	1.711	152.3	LOS F	103.0	769.2	0.70	1.07	19.4

PHASING SUMMARY



Site: I-06 2030 MIMT & SIMTA AM



Network: 2030 MIMT &
SIMTA AM

Newbridge Road / Moorebank Avenue

2030 MIMT & SIMTA AM PEAK 7:45 am - 8:45 am

Signals - Fixed Time Cycle Time = 133 seconds (User-Given Phase Times)

Phase Timing Results

Phase	A	B	C	D
Reference Phase	Yes	No	No	No
Phase Change Time (sec)	0	33	55	116
Green Time (sec)	27	16	55	11
Yellow Time (sec)	4	4	4	4
All-Red Time (sec)	2	2	2	2
Phase Time (sec)	33	22	61	17
Phase Split	25 %	17 %	46 %	13 %

