

Horsley Drive Business Park Traffic Impact Assessment for a Part 4 Concept Plan Application

Reference: 12.096r01v4 TRAFFIX Report

traffix
traffic & transport planners

po box 1061
potts point nsw 1335
t: +61 2 8324 8700
f: +61 2 9380 4481
w: www.traffix.com.au
abn: 66065132961



Document Verification

| | | | | |
|-------------|--------------------------------|----------|------------|---|
| Job Number: | 12.096 | | | |
| Project: | Horsley Drive Business Park | | | |
| Client: | Western Sydney Parklands Trust | | | |
| Revision | | Initials | Date | Signature |
| Report V01 | Prepared by: | PC | 10/04/2012 |  |
| | Checked by: | AJ | 28/05/2012 |  |
| | Approved by: | GP | 29/05/2012 |  |

traffix
traffic & transport planners

po box 1061
potts point nsw 1335
t: +61 2 8324 8700
f: +61 2 9380 4481
w: www.traffix.com.au
abn: 66065132961



Contents

| | |
|---|-----------|
| 1. Introduction | 3 |
| 1.1 Background | 3 |
| 1.2 Director Generals Requirements | 4 |
| 2. Location and Site | 6 |
| 3. Strategic Context | 11 |
| 3.1 Relevant State and Local Planning Policies | 11 |
| 4. Existing Traffic Conditions | 17 |
| 4.1 Road Hierarchy | 17 |
| 4.2 General Description of Road Environment | 20 |
| 4.3 Existing Intersection Performances | 26 |
| 5. Proposed Concept Plan Application | 29 |
| 5.1 Proposed Development | 29 |
| 6. Parking Requirements | 30 |
| 7. Traffic Modelling | 32 |
| 7.1 Paramics | 32 |
| 7.2 Overview and Input Data for Base Case Models | 33 |
| 7.3 Model Development | 35 |
| 7.4 Calibration and Validation | 36 |
| 8. Traffic Impacts | 42 |
| 8.1 Scenario Testing | 42 |
| 8.2 Traffic Generation and Distribution | 42 |
| 8.3 Scenario 2 – Base Case plus Growth | 43 |
| 8.4 Scenario 3 – Base Case plus Growth plus Development | 46 |
| 8.5 Scenario 4 – Base Case plus Development | 46 |
| 8.6 Modelling Conclusions | 55 |
| 9. Alternative Transport Assessment | 57 |
| 9.2 Workplace Travel Plan | 60 |
| 10. Conclusions | 62 |



Appendices:

| | |
|-------------|--|
| Appendix A: | SIDRA Intersection Results - Existing Intersection Operation |
| Appendix B: | Proposed Subdivision Plan |
| Appendix C: | Balanced AM & PM Count Data |
| Appendix D: | Calibration Report |
| Appendix E: | Adopted Distribution and JTW Data |
| Appendix F: | Future Intersection Analysis |
| Appendix G: | Proposed Intersection Geometry and Cycle times |



1. Introduction

1.1 Background

TRAFFIX has been commissioned by Western Sydney Parklands Trust (WSPT) to undertake a Traffic Impact Assessment for a Concept Plan application relating to the subdivision of land for the purpose of warehousing and industrial uses. The development is known as the Horsley Drive Business Park. This current application relates to the following:

- Subdivision of the approximately 21.4 hectare site,
- Demolition of all existing structures and remediation of the land,
- Bulk and detailed earthworks,
- Construction of estate infrastructure, and
- Estate landscaping.

The site is located immediately adjacent to the Smithfield-Wetherill Park Industrial Area and falls within the WSPT's functions under the *Western Sydney Parklands Act 2006* and the *Western Sydney Parklands Plan of Management 2020*.

The WSPT prepared a report entitled "*Request for DGR's – Supporting Document*" dated February 2012, to assist the Departure of Planning and Infrastructure (DoPI) in its initial consideration of the development as State Significant Development under the Environmental Planning and Assessment Act 1979 (EP&A Act). The Roads and Maritime Services (RMS) also issued a letter to the DoPI dated 5 March 2012, detailing key issues and assessment requirements for inclusion in the DG's Environmental Assessment (EA) requirements.

The DoPI issued the Director General's Environmental Assessment Requirements on the 16th March 2012, which includes the Transport and Accessibility (Construction and Operation) requirements to be included in this Traffic Impact Assessment.



1.2 Director Generals Requirements

The Director General's Environmental Assessment Requirements letter requires the following transport and accessibility issues to be assessed as part of the application:

- A strategic four step model should be undertaken to determine the traffic and transport impacts of the proposal, including consideration of traffic generation, traffic distribution, modal split and traffic assignment. The methodology and assumptions used for the modelling shall be to the satisfaction of the Roads and Maritime Services (RMS) and Transport for NSW (TfNSW).
- Provide a detailed traffic analysis of the proposal which includes a base case model, a separate model with full development, and a 10 year background traffic growth model. The traffic analysis is to be to the satisfaction of the RMS and Transport for NSW.
- Detail access and parking provisions associated with the proposed development including how compliance with the requirements of the relevant Australian Standards will be able to adhered (sic).
- Detail the proposed number of car parking spaces and compliance with appropriate parking codes.
- Demonstrate how future uses of the development will be able to make travel choices that support the achievement of State Plan targets.
- Detail existing pedestrian and cycle movements within the vicinity of the site and determine the adequacy of the proposal to meet the likely future demand for increased public transport and pedestrian and cycle access.
- Describe the measures to be implemented to promote sustainable means of transport including public transport usage and pedestrian and bicycle linkages in addition to addressing the potential for implementing a location specific sustainable travel plan and the provision of facilities to increase the non-car mode share for travel to and from the site.
- Estimate the total daily and peak hour trips anticipated to be generated by the business park, including accurate details of the current and future daily vehicle movements and assess the impacts of the traffic generated on local road networks, including intersection capacity and the potential need/associated funding for upgrading or road works, having regard to the local planning controls. The following key intersections are to be examined / modelled:



- The Horsley Drive / Cowpasture Road
- The Horsley Drive / Ferrers Road
- The Horsley Drive / Westlink M7
- Cowpasture Road / Newton Road
- Cowpasture Road / Victoria Street.

➤ Relevant Policies and Guidelines:

- Guide to Traffic Generating Developments (RTA);
- Planning Guidelines for Walking and Cycling;
- The Metropolitan Transport Plan 2010;
- EIS Guidelines – Road and Related Facilities (DoPI).



2. Location and Site

The Western Sydney Parklands is a 27 kilometre corridor stretching from Quakers Hill to Leppington, located in Western Sydney. A site plan of the Parklands is shown in **Figure 1**. The proposed Horsley Drive Business Park is situated within Precinct 9 of the Parklands, being approximately 2 kilometres south of Prospect Reservoir and approximately 31 kilometres west of Sydney CBD.

The site is irregular in configuration and has a total site area of 21.4 hectares. It is situated on northern-western corner of The Horsley Drive and Cowpasture Road intersection within Horsley Park and is immediately adjacent to the existing Smithfield-Wetherill Park Industrial Area.

The site is wholly within the Fairfield LGA, and comprises 18 separate land parcels, including:

- Lots 23 (part), 24 (part), 25, 28B, 30, 30A, 30B, 32 and 32A in DP13961,
- Lots 1 to 5 in DP 1098128,
- Lot 100 in DP 879680,
- Lot 1 in DP 1036933,
- Lot 10 in DP 879209, and
- Lot C in DP 103755.


The site is currently vacant with land use surrounding the site including:

- North: Parklands, including an electricity transmission line easement immediately to the north of the site.
- East: Cowpasture Road, with the Smithfield-Wetherill Park Industrial Area beyond.
- South: The Horsley Drive, with Parklands beyond, including the Lizard Log Community and Passive Recreation Hub approximately 300 metres to the south.



- ② West: Parklands, with a regional cycleway located immediately west of the site, and Sydney Water's Upper Canal located to the west of the cycleway, approximately 35 metres from the site boundary.

A Location and Site Plan are included respectively in **Figure 2** and **3** below.



Source: Horsley Drive Business Park: Request for DGRs - Supporting Document

Figure 1: Western Sydney Parklands



Figure 2: Location Plan



Figure 3: Site Plan (building layouts are indicative only)



3. Strategic Context

3.1 Relevant State and Local Planning Policies

The strategic context of the study area is governed by State and Regional Planning Policies. The NSW planning policies and strategies applicable to the subject site and those considered as part of the development of the Traffic Impact Assessment include:

- State Environmental Planning Policy (Infrastructure) 2007
- State Environmental Planning Policy (Western Sydney Employment Area)
- State Environmental Planning Policy (Western Sydney Parklands) 2009
- Fairfield Council Development Control Plans
- The Metropolitan Plan (2036)
- SEPP WSEA 2009
- The Metropolitan Transport Plan, and
- Planning Guidelines for Walking and Cycling.

A summary of these policies is provided below, together with an overview of local planning policies.

3.1.1 State Environmental Planning Policy (Infrastructure) 2007

This Policy contains provisions for referral of certain development applications, considered to be traffic generating development, to the RMS. The Horsley Drive Business Park is for an industrial purpose and all significant development within this Business Park will need to be referred to RMS. Notwithstanding this, it is noted that the aims of the SEPP (Infrastructure) 2007 are as follows:

(a) improving regulatory certainty and efficiency through a consistent planning regime for infrastructure and the provision of services,

(b) providing greater flexibility in the location of infrastructure and service facilities,



- (c) allowing for the efficient development, redevelopment or disposal of surplus government owned land,
- (d) identifying the environmental assessment category into which different types of infrastructure and services development fall (including identifying certain development of minimal environmental impact as exempt development),
- (e) identifying matters to be considered in the assessment of development adjacent to particular types of infrastructure development, and
- (f) providing for consultation with relevant public authorities about certain development during the assessment process or prior to development commencing.

3.1.2 State Environmental Planning Policy (Western Sydney Employment Area)

State Environmental Planning Policy (Western Sydney Employment Area) 2009 was gazetted in August 2009. The SEPP seeks to protect and enhance the Western Sydney Employment Area ("WSEA") for future employment purposes. The aims of the SEPP are as follows:

- "(a) to promote economic development and the creation of employment in the Western Sydney Employment Area by providing for development including major warehousing, distribution, freight transport, industrial, high technology and research facilities,
- (b) to provide for the co-ordinated planning and development of land in the Western Sydney Employment Area,
- (c) to rezone land for employment or environmental conservation purposes,
- (d) to improve certainty and regulatory efficiency by providing a consistent planning regime for future development and infrastructure provision in the Western Sydney Employment Area,
- (e) to ensure that development occurs in a logical, environmentally sensitive and cost-effective manner and only after a development control plan (including specific development controls) has been prepared for the land concerned,
- (f) to conserve and rehabilitate areas that have a high biodiversity or heritage or cultural value, in particular areas of remnant vegetation."



The proposed developments within the Horsley Drive Business Park are generally consistent with these aims. The land has been zoned appropriately, will be developed in a staged manner and is on land that is suitable for the intended purpose.

3.1.3 State Environmental Planning Policy (Western Sydney Parklands) 2009

Clause 12 of the Parklands SEPP requires a consent authority to consider a number of matters (insofar as they are relevant) when determining an application for development on land in the Parklands. The matters include:

- (a) the aim of the SEPP,
- (b) the impact on drinking water catchments and associated infrastructure,
- (c) the impact on utility services and easements,
- (d) the impact of carrying out the development on environmental conservation areas and the natural environment, including endangered ecological communities,
- (e) the impact on the continuity of the Parklands as a corridor linking core habitat such as the endangered Cumberland Plain Woodland,
- (f) the impact on the Parkland's linked north-south circulation and access network and whether the development will enable access to all parts of the Parklands that are available for recreational use,
- (g) the impact on the physical and visual continuity of the Parklands as a scenic break in the urban fabric of western Sydney,
- (h) the impact on public access to the Western Parklands,
- (i) consistency with:
 - (i) any plan of management for the Parklands, or
 - (ii) any precinct plan for a precinct of the Parklands,
- (j) the impact on surrounding residential amenity,



(k) the impact on significant views,

(l) the effect on drainage patterns, groundwater, flood patterns and wetland viability,

(m) the impact on heritage items, and

(n) the impact on traffic and parking.

3.1.4 Fairfield City Wide Development Control Plan 2006 – version 17

Fairfield City Wide DCP sets the specific controls for all development within the Fairfield Council LGA. In this regard, it is noted that any further development applications within the Horsley Drive Business Park will provide an additional assessment against the DCP controls within Fairfield City Council for review and response by Council.

3.1.5 Metropolitan Strategy and Transport Plan 2031

In 2005, the Metropolitan Strategy provided a framework for growth within the Sydney Metropolitan Area to 2031. The plan identified housing and employment capacity targets within strategic centres but has been superseded by the Metropolitan Transport Plan (2036) as discussed below.

3.1.6 Metropolitan Plan 2036

The Metropolitan Plan 2036 is to be reviewed every 5 years and forms an integrated plan for Sydney to 2036. It focuses on transforming Sydney from a single-centred city to a more connected, multi centred city where the regional cities of Parramatta, Liverpool and Penrith in particular deliver increased jobs and improved services. The long term vision is to develop Sydney as a “city of cities” and includes the following objectives:

- Radial public transport links feeding into each city.
- Cross regional transport connections linking more subregions to the Global Economic Corridor, and
- A developing network of transport connections serving a range of different trips and strategic centres that support economic activity across more locations.



3.1.7 Metropolitan Transport Plan

This plan produced in 2010 provides a 25 year vision for the connection of Sydney's land use planning with the transport network. The plan incorporates ten year funding for transport infrastructure and includes the following noteworthy services:

- A \$4.5 billion Western Express City Rail Service which is intended to significantly reduce commuting times between Western Sydney and the city.
- Commencement of works on the North West rail connection from Epping to Rouse Hill with an estimated cost of \$6.75 billion.
- Improvement to bus services which includes 100 new buses in strategic bus corridors.
- New trains with an additional 626 rail carriages
- \$158 million for cycleway
- \$400 million for commuter car parks
- \$483 million to deliver important freight works In Sydney
- \$21.9 million of State and Federal Funded road projects.

3.1.8 Planning Guidelines for Walking and Cycling (2004)

The aim of this guideline is to assist land-use planners and other related professionals to improve consideration of walking and cycling in their work. The intention of the guideline is to ultimately create further opportunities for people to live in places with easy walking and cycling access to urban services and public transport and reducing private vehicle usage.

3.1.9 NSW Bike Plan (2010)

The Metropolitan Transport Plan committed \$158 million towards improving urban cycle networks and lead to the development of the NSW Bikeplan which outlined a 10 year bicycle infrastructure plan including:

- \$80 million over ten years to connect Sydney's district centres by building missing links in the Metro Sydney Bike Network.



- \$78 million over ten years to fast-track subregional bike networks for Parramatta, Liverpool and Penrith to grow cycling in these three River Cities.
- At least \$5 million every year for regional cities and local councils across NSW to complete neighbourhood cycleway networks.

3.1.10 Summary

The plans and strategies discussed above are relevant to the Horsley Drive Business Park and are referred to throughout this Traffic Impact Assessment report within the Public Transport and Pedestrian & Cycleway Linkages Sections 4.2 below.



4. Existing Traffic Conditions

4.1 Road Hierarchy

The road hierarchy in the vicinity of the site is shown in **Figure 4** with the following roads of particular interest:

- **M7 Motorway:** a major arterial road that provides Sydney with a key orbital connection between numerous radial arterial roads including the M2, M4 and M5 motorways. It runs in a north-south direction between the M2 in the north and the M5 in the south, carrying approximately 70,000vpd in the vicinity of the study area. It carries two lanes of traffic in either direction within a divided carriageway of width 38.0 metres.
- **The Horsley Drive:** an RMS State Road (MR 609) that runs in an east-west direction between the Hume Highway in the east and Wallgrove Road in the west, carrying approximately 20,000vpd within the study area. It generally carries two lanes of traffic in either direction within a divided carriageway of width 27.0 metres.
- **Wallgrove Road:** a classified road (MR 515) that runs in a north-south direction to the west of the site. It historically carried in the order of 31,500vpd, however this has reduced to approximately 20,000vpd with the completion of the M7 Motorway. The approved Northern Link Road will form a linkage with Wallgrove Road connecting with Lenore Lane / Mamre Road in the west.
- **Cowpasture Road:** forms part of an RMS State Road (MR 648), a Regional Road and a collector road within the study area, carrying approximately 29,000vpd. Cowpasture Road is a State Road south of its roundabout controlled intersection with The Horsley Drive, a Regional Road between its signalised intersection with The Horsley Drive and roundabout controlled intersection with Victoria Street and a collector road north of



its intersection with Victoria Street. . It carries two lanes of traffic in either direction within a divided carriageway of width 19.0 metres.

- ② Newton Road: a local road that runs in an east-west direction which links Victoria Street in the east with Cowpasture Road in the west. It carries a single lane of traffic in either direction within an undivided carriageway of width 8.5 metres.
- ② Ferrers Road: a Regional Road (RR 7153) that runs in a north-south direction between Brabham Drive in the north and The Horsley Drive in the south. It carries a single lane of traffic in either direction within an undivided carriageway of width 8.5 metres.
- ② Victoria Road: a Regional Road that runs in an east-west direction between Cowpasture Road in the east and Warren Road in the west. . It carries two lanes of traffic in either direction within a divided carriageway of width 22.5 metres.
- ② Northern Link Road: a major RTA road currently under construction by the RMS. This road will eventually provide a link between Erskine Park in the west and Wallgrove Road in the east.

It can be seen from **Figure 4** that the site is conveniently located with respect to the arterial and local road systems serving the region including access to the M7 motorway which in turn provides direct access to both the M4 and M5 motorways.




Figure 4: Road Hierarchy



4.2 General Description of Road Environment

The Horsley Drive is a major RMS State Road providing access between the M7 Motorway and the Hume Highway. In the vicinity of the site the Horsley Drive is generally constructed with a 12.8m wide undivided carriageway carrying two lanes of traffic in either direction. Parking is not permitted generally along its entire length and no footpaths or pedestrian infrastructure is provided in the vicinity of the site.

The Horsley Drive forms the major signal controlled T Junction with Cowpasture Road immediately adjacent to the site. The intersection is constructed with two through lanes on both the northbound and eastbound approaches in addition to a dual signalised left turn slip lane of length 300m for southbound vehicles turning east into Cowpasture Road; and a dual signalised right turn bay of length 80m for northbound vehicles turning east into Cowpasture Road.

Approximately 160m south of the above mentioned intersection; The Horsley Drive forms the northern approach to a roundabout controlled junction with Cowpasture Road and the access road to the Lizard Creek Park.

To the immediate east of the site Cowpasture Road forms the major approach to a roundabout controlled intersection with Newton Road with an inscribed radius of 20 metres and with generally two circulating lanes.

The general intersection layout and road geometry at these two intersections is shown in **Figure 5** below.



Figure 5: Intersections of The Horsley Drive & Cowpasture Road

4.2.1 Bus Services

The existing bus services within the vicinity of site are shown in **Figure 6**. It is evident that the site benefits from services which operate along The Horsley Drive and Cowpasture Road, with two bus stops located immediately adjacent to the south-eastern site boundary. The 813 and 814 bus services provide connections to Fairfield Railway Station which is located approximately 8 kilometres to the south-east of the site. It is however noted that these service are relatively infrequent and generally operate only during Peak periods.



4.2.2 Rail Services

The Fairfield Railway Station is located approximately 8 kilometres to the south-east of the site. **Figure 7** illustrates the location of railway station in a regional context. Direct connections between Fairfield Railway Station and the site are available using the 814 Westbus service.

4.2.3 Cycle Network

The existing regional and local cycle networks are shown in **Figure 8** below. The site is well located with respect to the existing cycle network which links the site to the major residential land areas to the east. A major north-south cycle route also exists directly to the west of the site linking it with Eastern Creek and the regional cycle network.




Figure 6: Bus Services




Figure 8: Cycleway Network



4.3 Existing Intersection Performances

To assess the operation of key intersections in the vicinity of the site, turning movements were surveyed at the critical intersections identified by the RMS during both the AM and PM Peak Periods. Signal Diagnostics were obtained from the RMS and these were used for the purpose of assessment. The key intersections analysed include:

- ➡ The Horsley Drive / Cowpasture Road
- ➡ The Horsley Drive / Ferrers Road
- ➡ The Horsley Drive / Westlink M7
- ➡ Cowpasture Road / Newton Road
- ➡ Cowpasture Road / Victoria Street.

The intersections were then analysed using the SIDRA computer program to determine their performance characteristics under existing traffic conditions. The SIDRA model produces a range of outputs, the most useful of which are the Degree of Saturation (DOS) and Average Vehicle Delay per vehicle (AVD). The AVD is in turn related to a level of service (LOS) criteria. These performance measures can be interpreted using the following explanations:

DOS - the DOS is a measure of the operational performance of individual intersections. As both queue length and delay increase rapidly as DOS approaches 1, it is usual to attempt to keep DOS to less than 0.9. When DOS exceeds 0.9 residual queues can be anticipated, as occurs at many major intersections throughout the metropolitan area during peak periods. In this regard, a practical limit of 1.1 can be assumed. For intersections controlled by roundabout or give way/stop control, satisfactory intersection operation is generally indicated by a DOS of 0.8 or less.

AVD - the AVD for individual intersections provides a measure of the operational performance of an intersection. In general, levels of acceptability of AVD for individual intersections depend on the time of day (motorists generally accept higher delays during peak commuter periods) and the road system being modelled (motorists are more likely to accept longer delays on side streets than on the main road system).



LOS - this is a comparative measure which provides an indication of the operating performance of an intersection as shown below:

| Level of Service | Average Delay per Vehicle (sec/veh) | Traffic Signals, Roundabout | Give Way and Stop Signs |
|------------------|-------------------------------------|---|--|
| A | less than 14 | Good operation | Good operation |
| B | 15 to 28 | Good with acceptable delays and spare capacity | Acceptable delays and spare capacity |
| C | 29 to 42 | Satisfactory | Satisfactory but accident study required |
| D | 43 to 56 | Operating near capacity | Near capacity and accident study required |
| E | 57 to 70 | At capacity; at signals incidents will cause excessive delays. Roundabouts require other control mode | At capacity and requires other control mode |
| F | More than 70 | Unsatisfactory and requires additional capacity. | Unsatisfactory and requires other control mode or major treatment. |

A summary of the modelled results are provided in Table 1 below. Reference should also be made to the SIDRA outputs provided in **Appendix A** which provide detailed results for individual lanes and approaches.

It is evident from Table 1 that the network operates at a generally satisfactory level of service (LoS) during the AM and PM peak periods. It is however relevant that the LoS reported above does not accurately reflect the congestion within the network as it is a measurement of average performance across all approaches. In practice, some approaches operate with reduced LoS to that which is reported below.

Notwithstanding this, the most relevant use of the above is the comparison with the future operation of the network taking into account the proposed development yield. This is discussed further below.



Table 1: Existing Intersection Performance: AM and PM Peak Periods

| Intersection Description | Control Type | Period | Degree of Saturation | Intersection Delay | Level of Service |
|-------------------------------------|--------------|--------|----------------------|--------------------|------------------|
| The Horsley Drive / Westlink M7 | Signals | AM | 0.55 | 40.1 | C |
| | | PM | 0.61 | 25.3 | B |
| The Horsley Drive / Ferrers Road | Signal | AM | 1.05 | 28.6 | C |
| | | PM | 0.78 | 14.4 | A |
| The Horsley Drive / Cowpasture Road | Priority | AM | 1.04 | 55.5 | D |
| | | PM | 0.88 | 34.0 | C |
| The Horsley Drive / Cowpasture Road | Roundabout | AM | 0.98 | 23.8 | B |
| | | PM | 0.85 | 31.5 | C |
| Cowpasture Road / Newton Road | Roundabout | AM | 0.46 | 6.5 | A |
| | | PM | 1.08 | 31.5 | C |
| Cowpasture Road / Victoria Street. | Roundabout | AM | 0.78 | 9.4 | A |
| | | PM | 0.53 | 8.7 | A |



5. Proposed Concept Plan Application

5.1 Proposed Development

The WSPT is proposing to develop an industrial business park on the site, in a manner that is consistent with the vision, principles and strategic directions of the Parklands Plan of Management 2020. A detailed description of the Concept Plan Application is provided in the Environmental Impact Statement (EIS) prepared by McKenzie Group Consulting. In summary, the Concept Plan development for which approval is now sought comprises the following components:

- Subdivision of the site into eleven (11) development lots, an estate road and a service lot (stormwater).
- Demolition of all existing structures and remediation of land,
- Bulk and detailed earthworks,
- Construction of estate infrastructure, which will predominantly comprise warehousing distribution with ancillary office uses.
- Estate landscaping, and
- Provision of an internal estate road to serve the Business Park, which accesses the roundabout controlled intersection of Cowpasture Road and Newton Road.

The preliminary Concept Design is shown in **Appendix B** however, it is noted that aspects of the proposed development may be subject to change following detailed development design planning and environmental assessment.



6. Parking Requirements

The Concept Plan Application relates to bulk earthworks, infrastructure and subdivision only, however for the purpose of assessment a nominal gross floor area (GFA) of 95,400m² has been adopted to assess the parking requirements of the future development.

In this regard the Fairfield Council's DCP 12 stipulates a rate of 1 space per 80m² for Warehouse uses. This compares to a rate of 1 space per 300m² suggested for adoption in the RMS Guide to Traffic Generating Developments. Accordingly, having regard for the objectives of state planning policy as well as other precedents, a rate of 1 space per 200m² is proposed. A summary of these requirements is provided in **Table 2** below based on the indicative development yield of 95,400m².

Table 2: Council Parking Rates and Provision

| Type | Number Attending | Council Parking Rates | Spaces Required |
|--------------------|----------------------|----------------------------------|-----------------|
| Fairfield Council | 95,400m ² | 1.0 spaces per 80m ² | 1,193 |
| RMS Guide | 95,400m ² | 1.0 spaces per 300m ² | 318 |
| Proposed Provision | 95,400m ² | 1.0 spaces per 200m ² | 477 |

It is evident from Table 2 that the parking requirements under Council's DCP are excessive and represent a 375% increase over and above the suggested rates of the RMS. Accordingly adoption of the proposed rate of 1 space per 200m² is considered sufficient to accommodate the likely future demands of the precinct whilst achieving the planning objectives of the NSW Government.

The rate of 1 space per 200m² (or less) has also been adopted in other industrial precinct subdivisions within the Western Sydney Employment Area (WSEA) including areas within the Fairfield Council LGA. These include:



- ② Oakdale Central (MP08_0065) – 1 space per 200m²
- ② Greystanes Southern Employment Lands (MP06_0181) - 1 space per 300m²

The proposed parking provision of 1 space per 200m² is therefore consistent with previous approvals granted by the DoPI and adheres to the NSW Governments Strategic objectives.

Conversely, the provision of parking in accordance with Council's DCP would result in a considerable oversupply of parking and would generally encourage the use of private vehicles rather than alternative transport modes. Council's rate also reflects a provision some 375% greater than that which would be required under the RMS Guide to Traffic Generating Developments. Accordingly, the proposed rate is considered supportable having regard for the location and state objectives.



7. Traffic Modelling

7.1 Paramics

The DGR's require the future impacts of the development to be assessed using a four step strategic model. In this regard consultation was undertaken with the RMS regarding the strategic model and methodology to be adopted. Consequently the use of Paramics micro simulation model was considered the most suitable model for adoption.

The methodology and assumptions that were to underpin the analysis were confirmed in the above mentioned meeting. In general the following key aspects were identified:

- The scenarios to be investigated were to be as per the DGR's with the inclusion of an additional scenario being the Base Case + Background Traffic Growth following further consultation with the RMS. Accordingly the three Scenarios investigated include:
 - Existing Base Case
 - Existing Base Case + Growth
 - Existing Base Case + Growth + Development,
- Growth rates to be adopted were to be established through interpolation of RMS EMME2 data provided by the RMS.
- The traffic generation associated with the future development is to be assessed at the rate of 15 trips per hectare which is consistent with similar developments in the locality
- The base case model is to be independently reviewed prior to its use for scenario testing.

The results of the Paramics assessment and the methodology adopted are discussed further below.



7.2 Overview and Input Data for Base Case Models

7.2.1 Paramics Overview

Paramics is a micro simulation application that is used to replicate an areas transportation infrastructure in order to simulate the interactions of various modes of road traffic and other forms of transportation. This includes assessment of the combined effects of private vehicles, pedestrians and public transport modes (buses & rail). The program allows the user to examine a defined road network as a whole and accordingly the dynamic impacts on all intersections and vehicles within the network can be measured both numerically and visually.

Paramics allows the user to simulate the movement of each individual vehicle in a network with its individual characteristics and objectives relative to other vehicles, network constraints and environmental considerations such as acceleration and deceleration of vehicles, gap acceptance data, headways and cost impacts. This allows an analysis of queue build up and dispersion in addition to network congestion and overall levels of service.

7.2.2 Road Geometry

To identify existing road geometry, aerial photography was used and confirmed using signal layout plans and survey plans of the study area. This information was used to code the road network for the 'base' model. This provided relevant information to enable coding including lane widths, lane lengths, number of lanes, direction of travel, road positioning, speed limits, location of bus stops and intersection configurations. In addition to the above numerous site inspections were also undertaken to review parking and clearway restrictions as well as other relevant details such as traffic movement restrictions and signal phasings.

7.2.3 Traffic Signal Data

TCS and IDM data was provided by the RMS and utilised for all phase sequences of the signalised intersections of the M7 with The Horsley Drive, M7 with Wallgrove Road and The Horsley Drive with Cowpasture Road. LX Data was also provided by the RMS and utilised for intersection offsets. It should be noted that the signalised intersections in the network are all SCATS optimised signal timings are varied depending on demand. It is also noted that the maximum cycle time for all intersections was 120 seconds. Signal timings at intersections where IDM data was not available were recorded through on-site investigations.



7.2.4 Traffic Survey Data

Traffic surveys were undertaken at all critical intersections within the study area. The surveys that were undertaken are summarised below;

- Turning movement counts summarised into 15 minute intervals between 6:30am and 9:00am.
- Turning movement counts summarised into 15 minute intervals between 3:30pm and 6:00pm.
- Queue length surveys on all approaches at key intersections; and
- Pedestrian surveys at key intersections.

This data was then input into the model to provide the necessary information to allow the assessment to be undertaken. A copy of the AM and PM balanced count data is provided in **Appendix C**.

7.2.5 RMS Standard Files

The RMS provides a series of standard files for use in Paramics projects. These were used in both the AM and PM models and include the following:

- Categories,
- Configuration,
- Acceleration Profiles,
- Behaviour.

Changes to the vehicle file were undertaken to reflect the higher percentage of heavy vehicles that were observed during the traffic surveys. The vehicle proportions are discussed separately below.



7.3 Model Development

7.3.1 Network Coding

The network is shown in **Figure 9** below and includes all roads within the study area. The model was coded using aerial photographs of the area imported into Paramics and as such the model is at scale.




Figure 9: Extent of Model Network

7.3.2 Vehicle Classifications

The observed traffic counts differentiated between light vehicles and heavy vehicles, for the purpose of determining the percentage of heavy vehicles for adoption in the model. The traffic counts demonstrated a higher heavy vehicle percentage compared to the standard vehicle proportions provided in the RMS Guide to Paramics Microsimulation Modelling. In this regard, the standard vehicle proportions were modified to reflect the increased percentage of heavy vehicles observed through the network. The adopted vehicle proportions are provided in the Calibration Report included



in **Appendix D** below and demonstrate a heavy vehicle percentage of 8% for both the AM and PM models.

7.3.3 Peak Periods and Profiles

The traffic count data demonstrated the following AM and PM peak periods and accordingly, these time periods were adopted for the model:

- AM: 7:30am to 8:30am,
- PM: 3:30pm to 4:30pm.

Sufficient traffic count data was collected to allow traffic profiles to be established at 15 minute intervals over the AM and PM peak periods. These profiles were calculated by summing the approach volumes on all major intersections every 15 minutes and are provided in the calibration report provided in **Appendix D**.

7.4 Calibration and Validation

A summary of the critical inputs and calibration statistics is provided below. Reference should also be made to the detailed calibration report submitted with the base case models which is provided in **Appendix D**.

7.4.1 Estimation Inputs

The demand matrices were developed through the use of the Paramics Estimator tool that develops base case OD matrices by balancing turning counts, link flows and cordon flows. To assist in the process Pattern Matrices were also developed with the use of an R^2 statistical assessment through the utilisation of the observed link flows at the network boundary.

The link flow and turn count data used in the estimation were established by balancing the surveyed data for both the AM and PM peaks so that the flow out of an upstream intersection matched flows arriving at a downstream intersection. Estimator was then able to produce an initial matrix for the AM and PM peaks, these were then further refined during the calibration process.



7.4.2 Estimation Criteria and Validation

The criteria used to calibrate and validate the model have been adopted from the Paramics Microsimulation Modelling – RTA Manual which adopts the criteria outlined in the “UK Design Manual for Roads and Bridges”. This document outlines a number of validation criteria that are to be adopted depending on the type and use of the model. The following criteria are relevant:

📌 Links:

- Percentage within 20% or 200 vehicles per hour (target 95%)
- Percentage within 10% or 100 vehicles per hour (target 90%)
- Percentage within 5% or 50 vehicles per hour (target 85%)

📌 Intersection Counts:

- Greater than 85% of all individual modelled flows to have a GEH of less than 5.
- For observed flows less than 700 vehicles per hour, at least 85% of all individual flows to be within 100 vehicles per hour of observed flows.

The above criteria was achieved for both the AM and PM peak period models with the results summarised in **Table 3 and 4** below.

Table 3: Link Statistics

| Estimation Criteria | AM | PM% |
|---|------|------|
| Links within 200 veh/hr of modelled flows | 100% | 100% |
| Links within 100 veh/hr of modelled flows | 100% | 100% |
| Links within 50 veh/hr of modelled flows | 83% | 89% |
| Number of links with GEH <5.0 | 100% | 100% |



Table 4: Turn Count Statistics

| GEH | AM Period | | PM Period | |
|------|-----------------|------------|-----------------|------------|
| | Number of Cases | Percentage | Number of Cases | Percentage |
| <2 | 40 | 68% | 41 | 71% |
| 2-5 | 17 | 98% | 17 | 100% |
| 5-10 | 1 | 2% | 0 | 0% |

It is evident that both Link and Turn flows for the base case scenarios exceed (are superior to) the minimum requirements as set out by the RTA and the model is therefore considered representative of observed conditions.

7.4.3 Travel Time Assessment

Travel times through the network were undertaken during the survey period and used to calibrate the model. Appropriate travel routes were tested depending on the critical route in each peak. Each travel route was measured between 2 to 3 times between 7:00am-8:00am and 4:00pm-5:00pm with the average of the three runs used for validation purposes. The respective times are provided within the calibration report included in Appendix D. For validation purposes modelled times within 15% of the surveyed times are considered acceptable. This was achieved for both the AM and PM peak periods with the largest variation between observed and modelled times being 10.9% in the AM peak and 8.5% in the PM peak.

7.4.4 Queue Length Assessment

A queue length assessment was undertaken for both the AM and PM models. The observed max queues were then compared to the 95% queues taken from the model. A summary of the critical AM and PM queues is provided in the Calibration Report =.

7.4.5 Model Stability

As required by the RMS an assessment of the model under 5 varying Seeds was undertaken. The AM and PM models were run for the 5 standard seed numbers (28, 2894, 560, 86524 and 7771)



defined in the RMS Paramics Modelling Guide, to ensure that the model is stable and robust. The results of this assessment are provided in the calibration report.

7.4.6 Base Case Network Results

The existing signal operations are discussed in Section 5.3 above and summarised below.

Table 5: Existing Intersection Operation

| Intersection Description | Control Type | Period | Degree of Saturation | Intersection Delay | Level of Service |
|-------------------------------------|--------------|--------|----------------------|--------------------|------------------|
| The Horsley Drive / Westlink M7 | Signals | AM | 0.55 | 40.1 | C |
| | | PM | 0.61 | 25.3 | B |
| The Horsley Drive / Ferrers Road | Signal | AM | 1.05 | 28.6 | C |
| | | PM | 0.78 | 14.4 | A |
| The Horsley Drive / Cowpasture Road | Priority | AM | 1.04 | 55.5 | D |
| | | PM | 0.88 | 34.0 | C |
| The Horsley Drive / Cowpasture Road | Roundabout | AM | 0.94 | 19.4 | B |
| | | PM | 0.85 | 31.5 | C |
| Cowpasture Road / Newton Road | Roundabout | AM | 0.46 | 6.5 | A |
| | | PM | 1.08 | 31.5 | C |
| Cowpasture Road / Victoria Street. | Roundabout | AM | 0.78 | 9.4 | A |
| | | PM | 0.53 | 8.7 | A |

The on-site investigations also identified a number of existing network operational issues relevant to the assessment. These are summarised below, separately for the AM and PM periods:

AM Peak

- Extensive queuing for southbound traffic along The Horsley Drive was observed on approach to the signalised intersection with Cowpasture Road. These queues are a direct result of the operation of the roundabout controlled junction of Cowpasture Road and The Horsley Drive where queues extend north to the signalised junction of Cowpasture Road and The Horsley Drive. The



intermediate road network between these two intersections operates with considerable delays and limits the discharge of southbound vehicles.

- Considerable northbound queues on Cowpasture Road on approach to its roundabout controlled junction with The Horsley Drive were observed. These queues are a result of the high right turn movement from The Horsley Drive which operates with minimal delays.
- Considerable delays were observed for northbound vehicles accessing Ferrers Road. These queues extended south for a considerable distance and impeded northbound movements of vehicles accessing the M7 and Wallgrove Road.

PM Peak

- Southbound queues on Cowpasture Road occurred between The Horsley Drive and Newton Road. These queues limited access to Cowpasture Road from Newton Road and resulted in extensive westbound queues and delays.
- Delays at the roundabout controlled junction of The Horsley Road and Cowpasture Road were observed. In particular southbound Queues on Cowpasture Road and westbound queues on The Horsley Drive.

A summary of the key network statistics for the Existing AM and PM base case model is provided below for comparison purposes:

Table 6: 2012 Key Network Statistics (Base Model Network)

| Statistic | AM Peak | PM Peak |
|----------------------------|---------|---------|
| network traffic demand | 6632 | 6722 |
| average network speed | 36 km/h | 44 km/h |
| Average Network Link Delay | 5.1 sec | 4.7 sec |



7.4.7 Independent Model Audit

As required by the RMS the model was independently audited to ensure the base case model was fit for purpose. As part of the submission a Calibration report was produced and submitted with the model. The independent assessment concluded that “the base models are well calibrated and acceptable for testing future scenarios”.



8. Traffic Impacts

8.1 Scenario Testing

As discussed above the RMS requested the following scenarios to be tested to establish the impacts of the proposed development on the existing road network:

- Scenario 1: Existing Base Case
- Scenario 2: Existing Base Case + Growth
- Scenario 3: Existing Base Case + Growth + Development

In addition to that identified above, an additional scenario being Existing Base Case + Development was also undertaken. The results of which are summarised below.

8.2 Traffic Generation and Distribution

As discussed above, the traffic impacts associated with the application were assessed based on a future traffic generation of 15 trips per hectare. This generation rate was recommended by the RMS and as such adopted. The overall site includes a site area of 21.4Ha and as such results in an overall generation of 321 vehicles per hour. These trips have been proportioned with 70:30 split in the direction of peak flow and results in the following generations:

- AM Peak: 225veh in : 96veh out, and
- PM Peak: 96veh in : 225veh out, and

The distribution of these trips onto the network was undertaken using the 2006 Journey to Work Data (JTWD) for Travel Zone 1042 which represents the significant industrial precinct directly to the east of the site. A summary of the JTWD analysis and future distribution is included in Appendix E and summarised below: It is noted that the direction of travel represents the likely routes to be adopted by vehicles entering/exiting the site.



Table 7: Travel Movements

| Direction of Travel (To/From) | Route | Volume | % |
|----------------------------------|---------------------------------|--------|------|
| North | M7 & Horsley Drive | 3051 | 49% |
| South | Cowpasture Road | 836 | 13% |
| West | N/A | NA | 0% |
| East | The Horsley Drive & Victoria St | 2322 | 37% |
| Total | | 6209 | 100% |

8.3 Scenario 2 – Base Case plus Growth

8.3.1 2022 OD Matrix Development

The growth rates were established through the interpolation of the RMS EMME2 Data for the design years of 2016 and 2026. These growth rates were established for the major road corridors of Wallgrove Road and The Horsley Drive/Cowpasture Road for both the AM and PM Peak Periods. The growth annual growth rates applied were”

➤ Wallgrove Road:

- Northbound: AM: 2.7% PM:2.9%
- Southbound: AM: 1.3% PM:2.6%

➤ The Horsley Drive/Cowpasture Road:

- Northbound: AM: 1.9% PM:1.0%
- Southbound: AM: 1.2% PM:2.0%

These rates were then applied to the relevant existing OD matrices to establish the future year network



8.3.2 2022 Network Results

Once the 2022 OD Matrices were established the model was run using the base case model network with no infrastructure upgrades.

The modelling showed extensive queuing on Ferrers Road, Cowpasture Road and The Horsley Drive with a high number of unrealised vehicles at the end of the simulation period. Signal timings and some minor network upgrades were investigated however this resulted in no considerable change in the overall operation of the network under the future year scenario. The key network statistics are summarised below in Table 8:

Table 8: 2012 key network statistics (base model network)

| Statistic | AM Peak | PM Peak |
|----------------------------|---------|---------|
| network traffic demand | 7448 | 7569 |
| average network speed | 25 km/h | 25 km/h |
| Average Network Link Delay | 8.9sec | 11.7sec |

The considerable increase in congestion is generally contributed to the proximity of the roundabout controlled junction and signal controlled junction of Cowpasture Road and The Horsley Drive, and the inability to coordinate major movements. The model also demonstrated considerable increases in queue lengths in the PM peak period along the northern section of Cowpasture Road adjacent to the site. Screen shots of the AM and PM network are shown in **Figures 10** and **11** below.

Accordingly after consultation with the RMS, it was deemed that the only relevant scenario to be considered in further detail would be that of the existing + development due to the considerable delays and necessary infrastructure upgrades that would be required within the network to accommodate the estimated growth which is would be outside the scope of the applicant. That is, the provision of capacity improvements to accommodate network growth in the region is rightly the responsibility of Council and RMS in undertaking their strategic planning responsibilities.




Figure 10: Scenario 1 Network Queues - AM




Figure 11: Scenario 1 Network Queues - PM



8.3.3 SIDRA Intersection Analysis

Due to the considerable queues, delays and blocking, it was not considered necessary to undertake a SIDRA intersection analysis of this Scenario.

8.4 Scenario 3 – Base Case plus Growth plus Development

8.4.1 Paramics Model

As discussed above, this Scenario was not assessed due to the considerable delays and queues measured in Scenario 2. This approach was confirmed with the RMS.

8.5 Scenario 4 – Base Case plus Development

8.5.1 Paramics Model

The estimated traffic generation and development yield were superimposed onto the existing Base Case network. The proposed access to the development was coded providing direct access from Cowpasture Road via the existing roundabout controlled junction with Newton Road. A new development zone – Zone 15, was also coded.

The model was run and indicated only minor increases in delays during the AM peak period. During the PM peak, increased delays and queues were recorded along the northern section of Cowpasture Road extending from The Horsley Drive to the east of its intersection with Victoria Street. The model also indicated a increases in queues and delays along Newton Street and within the development.

Accordingly, upgrades to the existing network were investigated to maintain the existing LoS and delays through the network. The options tested included:

1. Provision of an additional access from The Horsley Drive to facilitate entry movements by southbound vehicles accessing the site.



2. Extension of the existing left turn auxiliary lanes on the Horsley Drive for vehicles turning east into Cowpasture Road.
3. Limiting exit movements from the proposed development to left out only onto Cowpasture Road.
4. Signalisation of the proposed future site access of Cowpasture Road and Newton Road.

These options were applied to the network to assess the benefits of each. The results of each option are summarised below:

Options 1 and 2

Options 1 and 2 were implemented and resulted in no measureable improvement in the operation of the network during either the AM or PM peak periods. Accordingly, the implementation of these options is not recommended.

Option 3

Option 3 investigated the impacts resulting from limiting all exit movements from the development to left out only onto Cowpasture Road. This requires all vehicles accessing the Horsley Drive undertake a U Turn manoeuvre at the intersection of Cowpasture Road and Victoria Street.

This option had no major impact on the AM peak period which operated generally as per the existing base case scenario however resulted in considerable delays southbound on Victoria Street during the PM peak period. The increased volume of the southbound through movement also resulted in increased delays to westbound vehicles on Newton Road.

It was evident that the majority of the queuing occurred as a result of residual queues from the signal controlled junction of Cowpasture Road and The Horsley Drive. Queues at this intersection currently extend to the intersection with Victoria Street and as such any spare capacity on this link is taken up from the least interrupted movements being the through movements from Cowpasture Road.

This option resulted in no major improvement in the road network to that achieved with full turning movements being permissible from the site access. As such this option has not been adopted.



Option 4

Option 4 involved the signalisation of the existing roundabout controlled intersection of Cowpasture Road with Newton Road. The objective of this was to coordinate the major movements in the AM and PM peaks to reduce queues within Cowpasture Road. The key geometric and operational characterises of this option included:

1. Provision of a 120m right turn bay within Cowpasture Road to facilitate northbound traffic turning east into Newton Road
2. Provision of a 50m long right turn bay within Cowpasture Road to facilitate southbound traffic on Cowpasture Road turning west into the site
3. Signalised pedestrian crossings on the northern, eastern and western approaches.
4. The banning of all right turn and through movements from Newton Road onto Cowpasture Road
5. The banning of all right turn and through movements from the proposed site access
6. Signalisation of the existing left turn slip lane from Cowpasture Road to The Horsley Drive

The signalisation of the existing left turn slip lane referred to above was implemented after initial testing indicated that the left turn queues extended through the proposed intersection in the PM peak period in the Base Case + Development Scenario. The signalisation of this movement resulted in improved operation and reduced queues and was therefore adopted.

The signal phases associated with the proposed intersection were optimised in SIDRA with cycle times designed to match those achieved at the critical intersection of The Horsley Drive and Cowpasture Road. Signal off-sets between the proposed intersection and the existing intersection of Cowpasture Road and The Horsley Drive were manually varied in the model until the optimal arrangement was identified.

The implementation of the above network changes resulted in satisfactory operation of the network compared to Scenario 1 (base case model) during both the AM and PM peak periods. The phasing adopted for the proposed junction gave maximum green time to the northbound movement and right turn movement into Newton Street during the AM peak to ensure that queues did not extend to the intersection of The Horsley Drive. Similarly the phase times adopted in the PM peak gave priority to the southbound movement on Cowpasture Road and Newton Road to minimise queues and delays.



Accordingly the network upgrades identified in Scenario 4 were adopted.

8.5.2 Modelling Results of Adopted Network Upgrades

The geometric design of the proposed upgrades to the existing intersection of Cowpasture Road and Newton Road including the proposed site access is shown in **Figures 12** and **13** below. The design reflects the upgrades noted above, including the signalisation of the left turn slip lane at the critical intersection of The Horsley Drive and Cowpasture Road.




Figure 12: Proposed Network Upgrades




Figure 13: Proposed Intersection of Cowpasture Rd and Newton Rd Upgrades

The application seeks to ban the existing right turn movement from Newton Road onto Cowpasture Road. This is considered acceptable for the following reasons:

- ➊ This movement currently accommodates a low volume of vehicles surveyed as 17veh in the AM peak and 30veh in the PM peak.
- ➋ A number of alternate routes are available and as such coupled with the low volumes will have a negligible impact on the operation of existing intersections
- ➌ The banning of this movement results in a considerable improvement in the operation of the intersection and reduced delays to vehicles currently using Newton Road to that which would occur should the movement be retained.



- The proposed intersection geometry and banning of the right turn movement from Newton Street has been discussed with Council officers and is supported in principle, subject to review of critical data by Council.

Accordingly, the removal of the right turn movement is considered supportable based on the overall network improvements and delivers a significant network improvement with no unacceptable consequences. As such this has been included in all subsequent modelling. A summary of the key network statistics including these upgrades compared to those measured in the base case model are included below for both the AM and PM peak periods

Table 9: 2012 key network statistics (base model network)

| Statistic | AM Peak | | PM Peak | |
|----------------------------|----------|---------|----------|----------|
| | Existing | Future | Existing | Future |
| network traffic demand | 6632 | 6902 | 6722 | 7044 |
| average network speed | 36 km/h | 34 km/h | 44 km/h | 39.7km/h |
| Average Network Link Delay | 5.1 sec | 5.8 sec | 4.7 sec | 4.9 sec |

Table 9 above demonstrates that the proposed variations have a minor impact on the overall delay and travel speeds within the network under both the AM and PM model. This level of delay is however considered supportable having regard for the congested nature of the network in both peaks.

The most relevant statistics are however the variations in travel times and intersection level of service. These are provided in the tables below. It should be noted that the signal timings at the intersections of Cowpasture Road with The Horsley Drive and Ferrers Road with The Horsley Drive were amended from the base case scenario to accommodate the additional traffic demand. These timings were however varied whilst still maintaining the maximum existing cycle times of 120seconds at each intersection. It is also noted that the signal times in the SIDRA analysis were optimised based on the adopted cycle times in the Paramics model. It is evident from Table 10 that the Intersection LoS is generally maintained in all scenarios with the exception of the following:

- The Horsley Drive & Cowpasture Road (signals) – LoS has reduced from “D” under existing conditions to “E” under the future scenario. This is however misleading as the reduced LoS is



associated with only a minor deterioration in delays. In this regard delays during the AM peak period have increased from 55.5sec to 57.7sec which represents an increase of only 2.2sec per vehicle.

- Cowpasture Road & Newton Road – The LoS at the intersection of Cowpasture Road and Newton Road has reduced from “A” in the under the existing scenario to “B” in the future. This is expected due to the signalisation of the intersection under the future scenario.

Table 10: Future Intersection Operation (Option 4)

| Intersection Description | Control Type | Period | Degree of Saturation | Intersection Delay | Level of Service |
|-------------------------------------|--------------|--------|----------------------|--------------------|------------------|
| The Horsley Drive / Westlink M7 | Signals | EX AM | 0.55 | 40.1 | C |
| | | EX PM | 0.61 | 25.3 | B |
| | | FU AM | 0.60 | 39.4 | C |
| | | FU PM | 0.61 | 25.7 | B |
| The Horsley Drive / Ferrers Road | Signals | EX AM | 1.05 | 28.6 | C |
| | | EX PM | 0.78 | 14.4 | A |
| | | FU AM | 1.05 | 31.1 | C |
| | | FU PM | 0.81 | 14.1 | A |
| The Horsley Drive / Cowpasture Road | Signals | EX AM | 1.04 | 55.5 | D |
| | | EX PM | 0.88 | 34.0 | C |
| | | FU AM | 1.05 | 57.7 | E |
| | | FU PM | 0.91 | 40.6 | C |
| The Horsley Drive / Cowpasture Road | Roundabout | EX AM | 0.94 | 19.4 | B |
| | | EX PM | 0.85 | 31.5 | C |
| | | FU AM | 0.96 | 25.2 | B |
| | | FU PM | 0.89 | 39.2 | C |
| Cowpasture Road / Newton Road | Roundabout | EX AM | 0.46 | 6.5 | A |
| | | EX PM | 1.08 | 31.5 | C |
| | Signals | FU AM | 0.79 | 17.0 | B |
| | | FU PM | 0.86 | 37.2 | C |
| Cowpasture Road / Victoria Street. | Roundabout | EX AM | 0.78 | 9.4 | A |
| | | EX PM | 0.53 | 8.7 | A |
| | | FU AM | 0.80 | 9.7 | A |
| | | FU PM | 0.54 | 8.7 | A |



The relevant travel times for the AM peak periods are shown in Tables 11 and 12 respectively.

Table 11: AM Travel Time Statistics (Option 4)

| Origin | Destination | Travel Times | | ABS Difference | Diff (%) |
|--|--|----------------|----------------|----------------|--------------|
| | | Existing | Future | | |
| Horsley Drive – West of Wallgrove Rd | Cowpasture Road – South of The Horsley Drive | 0:07:23 | 0:07:39 | 0:00:16 | 3.61% |
| | Horsley Drive – East of Cowpasture Rd | 0:07:46 | 0:07:08 | 0:00:38 | -8.15% |
| M7 Off Ramp - Southbound | Cowpasture Rd – South of The Horsley Dr | 0:07:33 | 0:07:09 | 0:00:24 | -5.30% |
| | Horsley Drive – East of Cowpasture Rd | 0:07:37 | 0:07:09 | 0:00:28 | -6.13% |
| M7 Off Ramp - Northbound | Cowpasture Road – South of The Horsley Drive | 0:07:01 | 0:06:38 | 0:00:23 | -5.46% |
| | Horsley Drive – East of Cowpasture Rd | 0:07:04 | 0:06:43 | 0:00:21 | -4.95% |
| Cowpasture Road – South of The Horsley Drive | M7 On Ramp - Northbound | 0:05:20 | 0:05:04 | 0:00:16 | -5.00% |
| | M7 On Ramp - Southbound | 0:04:37 | 0:04:45 | 0:00:08 | 2.89% |
| Victoria Road – Southbound | Cowpasture Road – South of The Horsley Drive | 0:02:57 | 0:03:13 | 0:00:16 | 9.04% |
| | M7 On Ramp - Northbound | 0:04:55 | 0:05:56 | 0:01:01 | 20.68% |
| | M7 On Ramp - Southbound | 0:04:54 | 0:04:54 | 0:00:00 | 0.00% |
| Newton Road - Westbound | Cowpasture Road – South of The Horsley Drive | 0:02:19 | 0:02:53 | 0:00:34 | 24.46% |
| | M7 On Ramp - Northbound | 0:04:35 | 0:05:07 | 0:00:32 | 11.64% |
| | M7 On Ramp - Southbound | 0:04:03 | 0:04:36 | 0:00:33 | 13.58% |
| Ferrers Road | Cowpasture Road – South of The Horsley Drive | 0:03:25 | 0:04:24 | 0:00:59 | 28.78% |
| | M7 On Ramp - Northbound | 0:03:25 | 0:04:24 | 0:00:59 | 28.78% |
| Totals | | 1:37:27 | 1:38:54 | 0:08:15 | 1.49% |



Table 12: PM Travel Time Statistics (Option 4)

| Origin | Destination | Travel Times | | ABS Difference | Diff (%) |
|--|--|--------------|---------|----------------|----------|
| | | Existing | Future | | |
| Horsley Drive – West of Wallgrove Rd | Cowpasture Road – South of The Horsley Drive | 0:05:48 | 0:05:46 | 0:00:02 | -0.57% |
| | Horsley Drive – East of Cowpasture Rd | 0:05:41 | 0:05:48 | 0:00:07 | 2.05% |
| M7 Off Ramp - Southbound | Cowpasture Road – South of The Horsley Drive | 0:04:57 | 0:04:59 | 0:00:02 | 0.67% |
| | Horsley Drive – East of Cowpasture Rd | 0:04:53 | 0:05:08 | 0:00:15 | 5.12% |
| M7 Off Ramp - Northbound | Cowpasture Road – South of The Horsley Drive | 0:05:24 | 0:05:24 | 0:00:00 | 0.00% |
| | Horsley Drive – East of Cowpasture Rd | 0:05:06 | 0:05:17 | 0:00:11 | 3.59% |
| Cowpasture Road – South of The Horsley Drive | M7 On Ramp - Northbound | 0:04:06 | 0:04:10 | 0:00:04 | 1.63% |
| | M7 On Ramp - Southbound | 0:03:38 | 0:03:38 | 0:00:00 | 0.00% |
| Victoria Road – Southbound | Cowpasture Road – South of The Horsley Drive | 0:04:13 | 0:04:14 | 0:00:01 | 0.40% |
| | M7 On Ramp - Northbound | 0:05:40 | 0:05:54 | 0:00:14 | 4.12% |
| | M7 On Ramp - Southbound | 0:05:13 | 0:05:23 | 0:00:10 | 3.19% |
| Newton Road - Westbound | Cowpasture Road – South of The Horsley Drive | 0:06:27 | 0:03:31 | 0:02:56 | -45.48% |
| | M7 On Ramp - Northbound | 0:08:10 | 0:05:15 | 0:02:55 | -35.71% |
| | M7 On Ramp - Southbound | 0:08:03 | 0:04:49 | 0:03:14 | -40.17% |
| Ferrers Road | Cowpasture Road – South of The Horsley Drive | 0:03:11 | 0:03:16 | 0:00:05 | 2.62% |
| | M7 On Ramp - Northbound | 0:03:14 | 0:03:12 | 0:00:02 | -1.03% |
| Totals | | 1:39:09 | 1:31:36 | 0:11:01 | -7.61% |

Table 11 above demonstrates that the proposed development and the signalisation of the intersections of Cowpasture Road and Newton Road under Option 4 has only a minor impact on the network during the AM Peak Period. It is reiterated that the signal timings at some intersections were varied to accommodate the additional demand however these variations were generally to the detriment of the minor roads with priority given to the major through movements. In this regard the



major northbound and southbound movements are generally unchanged or improved with a maximum increased delay of 8 seconds for vehicles travelling from Cowpasture Road, south of the Horsley Drive to the M7 Motorway.

Some additional delays to movements from Ferrers Road were recorded however this was to improve the overall operation of The Horsley Drive. Travel times for vehicles traversing Victoria Road and Newton Road also increased, however this is to be expected as priority at the proposed intersection was given to the northbound vehicles to ensure queues did not extend south to The Horsley Drive.

The PM travel times detailed above in Table 12 demonstrate a reduction in the overall times through the network. The major northbound and southbound movements are generally unchanged (within 15 seconds of the base case scenario) however the signalisation has resulted in a considerable reduction in travel times for vehicles using Newton Road. The movements from Newton Road decreased by as much as 45% or 2:56 minutes from those recorded in the base case model. These reductions are a result of the improved ability for vehicles to exit Newton Road which was not previously possible due to the inability to coordinate major movements.

The Sidra intersection analysis results and proposed geometry and phase times are provided in **Appendices F and G** respectively.

8.6 Modelling Conclusions

The modeling was undertaken in accordance with the requirements of the DGR's and RMS. All scenarios required by the RMS for investigation were analysed and demonstrated that:

1. The existing network operates with limited spare capacity due to the interaction of the signalised intersection and roundabout controlled intersection of The Horsley Drive and Cowpasture Road. The inability to coordinate major movements at these intersection results in considerable delays and queues on some approaches.



2. There is insufficient capacity within the existing network to support the estimated growth as provided by the RMS. Accordingly infrastructure upgrades are required along The Horsley Drive and Cowpasture Road in the short to medium term to accommodate this growth.
3. The inability of the network to support the estimated growth resulted in only the Existing and the Existing + Development Traffic scenarios being assessed. The Existing + Growth and the Existing + Growth + Development scenarios provided inconsistent results which were deemed inappropriate for adoption or for reporting purposes.
4. The analysis demonstrated that whilst the network operates at a level approaching capacity, the additional generation of the site can be accommodated subject to the implementation of infrastructure upgrades including:
 - Signalisation of the existing roundabout controlled intersection of Cowpasture Road and Newton Road
 - Provision of a 120m right turn bay within Cowpasture Road to facilitate northbound traffic turning east into Newton Road
 - Provision of a 50m long right turn bay within Cowpasture Road to facilitate southbound traffic on Cowpasture Road turning west into the site
 - Signalised pedestrian crossings on the northern, eastern and western approaches.
 - The banning of all right turn and through movements from Newton Road onto Cowpasture Road
 - The banning of all right turn and through movements from the proposed site access
 - Signalisation of the existing left turn slip lane from Cowpasture Road to The Horsley Drive

Based on these improvements, the application is considered supportable on traffic planning grounds.



9. Alternative Transport Assessment

9.1.1 Achieving Target Mode Splits

The strategy to improve public transport facilities will be facilitated once the WSEA road network is further developed. These improved public transport facilities will assist in achieving a shift from private car usage, although this is not able to be quantified at this time. The following sections provide an overview of the existing public transport facilities and potential improvements that are available.

9.1.2 Bus Opportunities

The development benefits from existing bus services which operate along The Horsley Drive and Cowpasture Road, with two Bus Stops provided immediately adjacent to the south-eastern corner of the site. These services provide connections to such centres as Parramatta, Fairfield and Liverpool, as well as Fairfield Railway Station, which is located approximately 8 kilometres to the south-east of the site.

The Horsley Drive Business Park will itself result in a demand for additional bus services and frequencies. This demand will increase when account is taken of the cumulative effect of the proposed development and development of the WSEA more generally. The provision of these additional bus services and frequencies will therefore improve the accessibility of the site and promote a reduction in car dependency, in accordance with the State Planning Policy. In this regard, service improvements can be expected to respond to a demonstrated increase in demand over time.

9.1.3 Rail Opportunities

The Metropolitan Transport Plan produced in 2010 incorporates a ten year funding program which intends to provide a \$4.5 billion Western Express City Rail Service. This service would significantly reduce commuting times between Western Sydney and the city. The project includes the construction of a new 5 kilometre tunnel linking Central Station with Redfern Station, Town Hall and Wynyard. This will allow express services from Richmond, Penrith, Blacktown and Parramatta to the Sydney CBD.

This will have a considerable impact on the accessibility of the subject site, noting the existing bus connections along Cowpasture Road and The Horsley Drive, with Fairfield Railway Station. It is



envisaged that a consolidated regional assessment would be undertaken as part of this proposal to ensure that improved services are provided to employment areas within Greater Western Sydney.

9.1.4 Cycling

The NSW Government's Metropolitan Plan for Sydney 2036 published in 2010, outlines the following objectives:

- The RMS in cooperation with local government is to continue to upgrade walking and cycling facilities, and
- That future planning of walking and cycling networks should be developed to ensure appropriate linkages with both existing and proposed public transport routes with the aim of improving overall network connectivity.

These objectives have been adopted in the NSW Bike Plan (2010) which outlines a ten-year bicycle infrastructure implementation schedule to improve the existing accessibility to local and regional bike networks. The plan states the RMS will provide on an average \$5 million in 50/50 funding each year for the upgrade of cycleways and shared paths to local Councils. Additionally, the NSW Bike Plan seeks to deliver cycleways as an integrated component of road upgrades.

9.1.5 Cycling Opportunities

Cycleway / shared path upgrades are proposed by the RMS on Lenore Lane and Erskine Park Link Road (Northern Link Road) in Erskine Park and on The Horsley Drive. These will provide links to the Horsley Drive Business Park, existing commercial centres, the M7 motorway and provide a framework for the future cycleway development. It is noted that future cycleway development is dependent on future road construction and progressive development of the region.

In particular the existing M7 shared path which runs parallel to the M7 motorway between Prestons and West Baulkham Hills with an overall length of 40 kilometres provides extensive opportunities to implement future cycle networks in accordance with the objectives of the NSW Bike Plan. There are existing connections in the vicinity of the site at The Horsley Drive, Cowpasture Road, Chandos Road, The Austral Bricks access road, Wallgrove Road and Old Wallgrove Road. These connections provide a basis for potential future cycleway upgrades linking the WSEA.



The development proposes a link to the existing cycleway / shared path which runs along the western side of the site, as shown in Figure 8. This link will further develop the cycleway / shared path network in the locality and promote alternative modes of transport.

The provision of adequate bicycle facilities including bicycle lockers / parking and showers will further encourage the use of the existing networks and will assist in the reduction of trips associated with private vehicles for the journey to work.

9.1.6 Walking

As is the case with cycleways, the NSW Government's Metropolitan Plan for Sydney 2036 seeks to improve local walking networks. Particular emphasis is placed on aligning pedestrian paths with existing public transport routes and providing pedestrian paths as an integrated part of road upgrades. Pedestrian facilities in the locality are comprised of short sections of walkways which are generally only provided adjacent to the signalised and roundabout controlled intersections of The Horsley Drive and Cowpasture Road. In this regard, the existing walkway facilities provide a poor level of amenity for pedestrians.

9.1.7 Walking Opportunities

The development will generate relatively low levels of walking demand within the Horsley Park area both to and from the site. Whilst the intention of this assessment is to encourage alternative modes of transport and specifically reduce dependency of vehicle users, it is evident that pedestrian linkages will not have any significant bearing on this objective, but will largely improve local accessibility. Nevertheless, it is acknowledged that footpaths will be provided throughout the development and along The Horsley Drive and Cowpasture Road. In addition to this, signalised pedestrian crossings will also be provided across the northern, eastern and western approaches to the proposed upgraded intersection of Cowpasture Road and Newton Road.

It is essential that the location of the Horsley Drive Business Park be placed into context with regard to pedestrian connectivity. Although it is unlikely that there will be any significant walking trips in the short to medium term, the construction of the pedestrian paths throughout the site, along The Horsley Drive and Cowpasture Road, will provide a link to the existing paths in the locality and provide a more integrated network. These facilities will also provide a safe path for pedestrians between the Horsley Drive Business Park and Bus Stops on The Horsley Drive.



9.2 Workplace Travel Plan

A Workplace Travel Plan (WTP) is the term used to describe the package of measures required by a development to promote alternative travel choices whilst reducing private vehicle usage. The WTP requires the implementation of initiatives and targets that will enable the Horsley Drive Business Park to reduce the impact of transport on the nearby environment. Such a plan is recommended to achieve the objectives of this assessment progressively over time, given the relative isolation of the subject site with respect to public transport. A suitable condition requiring this plan to be prepared and to be reviewed every 5 years is therefore considered appropriate. The plan will therefore be able to evolve in line with the ongoing development of the WSEA and the progressive implementation of public transport and other infrastructure improvements. The plan should be issued to all staff and provided in common areas and should include a Travel Information Pack as part staff induction procedures. The following initiatives should be considered:

- Local bus network maps and timetables.
- Rail network maps and timetables.
- Cycle route maps.
- Location of critical services within walking distances.
- Taxi contact numbers.

In addition opportunity exists to implement initiatives to further reduce car dependency. Initiatives implemented at similar developments which have resulted in a demonstrated reduction in car trips include:

- Promoting a car-pooling scheme for work related journeys.
- Staff sharing scheme for fleet vehicles.
- Use of taxis for work related journeys.
- Provision of a mini-bus facility and interchange area.
- Possible shuttle bus services from Fairfield Railway Station.
- Providing staff with a discount or subsidy on public transport costs.



- Employee cycling allowance.
- Provision of on-site facilities, which may include change rooms, showers, lockers and storage facilities, to encourage cycling and walking as a mode of transport.

The implementation of a shuttle bus services from Fairfield Railway Station or bus interchanges and the encouragement of car pooling is a realistic method of reducing private vehicle usage given the overall accessibility to public transport. It is therefore recommended that these services be encouraged. It is however acknowledged that the implementation of these services would be the responsibility of tenants. Having regard for the above, it is expected that a Workplace Travel Plan for staff would be prepared for all developments within the precinct, prior to issue of an occupation certificate. The transport options currently available to commuters are inhibited by a lack of development within the area, and the progressive construction of the surrounding infrastructure.



10. Conclusions

In summary:

- ⑦ The application seeks approval for the subdivision and construction of major services including roads. The application does not seek approval for the construction of any built form.
- ⑦ The impacts associated with the future use of the site, has been assessed in accordance with the requirements of the DGR's. A meeting was held with the RMS to confirm these requirements and the proposed methodology adopted in this report.
- ⑦ The proposed parking provision of 1 space per 200m² is consistent with previous approvals granted by the DoPI and adheres to the NSW Governments Strategic objectives. The provision of parking in accordance with Council's DCP would result in a considerable oversupply of parking and would generally encourage the use of private vehicles rather than alternative transport modes. Council's rate also reflects a provision some 375% greater than that which would be required under the RMS Guide to Traffic Generating Developments. Accordingly, the proposed rate is considered supportable having regard for the location and state objectives.
- ⑦ The impacts associated with the proposed development have been assessed using both SIDRA and Paramics. The modelling demonstrated that the proposed development will have only a minor impact on the operation of the network subject to the implementation of infrastructure upgrades identified above. These upgrades include the signalisation of the intersection of Cowpasture Road with Newton Road and the signalisation of the existing left turn slip lane from Cowpasture Road onto The Horsley Drive.
- ⑦ It is recommended that a transport access guide (TAG) be developed and displayed in common areas. The aim of this is to inform residents of the alternative transport options available to them and the location of critical services. This will encourage the use of alternative transport modes and will assist in the reduction of private vehicle trips.

It is therefore concluded that the proposed development concept envisaged under the Subdivision Plan is supportable on traffic planning grounds and the proposed development will operate satisfactorily. Further detailed planning and refinement will continue through the subsequent development application process, within the context of this Concept Plan.



Appendix A

MOVEMENT SUMMARY

Site: M7 On/Off - Ramp / The
Horsley Drive - EX AM

M7 and The Horsley Drive, Horsley Park

Existing - AM

Signals - Fixed Time Cycle Time = 110 seconds (User-Given Cycle Time)

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|--------------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: M7 On / Off-Ramp (South) | | | | | | | | | | | |
| S_L | L | 59 | 8.0 | 0.056 | 11.7 | LOS A | 0.6 | 4.2 | 0.26 | 0.69 | 42.6 |
| S_R | R | 484 | 8.0 | 0.536 | 44.0 | LOS D | 11.3 | 84.8 | 0.92 | 0.81 | 18.1 |
| Approach | | 543 | 8.0 | 0.536 | 40.5 | LOS C | 11.3 | 84.8 | 0.84 | 0.79 | 19.5 |
| East: The Horsley Drive | | | | | | | | | | | |
| E_L | L | 157 | 8.0 | 0.309 | 20.3 | LOS B | 3.7 | 27.7 | 0.48 | 0.73 | 45.0 |
| E_T | T | 483 | 8.0 | 0.473 | 40.0 | LOS C | 10.9 | 81.4 | 0.89 | 0.78 | 29.7 |
| 6 | R | 251 | 8.0 | 0.250 | 41.0 | LOS C | 5.2 | 38.9 | 0.81 | 0.76 | 32.6 |
| Approach | | 891 | 8.0 | 0.473 | 36.8 | LOS C | 10.9 | 81.4 | 0.79 | 0.77 | 32.8 |
| North: M7 On / Off-Ramp (North) | | | | | | | | | | | |
| N_L | L | 537 | 8.0 | 0.547 | 45.9 | LOS D | 12.6 | 94.0 | 0.90 | 0.83 | 19.7 |
| N_R | R | 37 | 8.0 | 0.082 | 38.9 | LOS C | 1.5 | 11.2 | 0.79 | 0.69 | 19.7 |
| Approach | | 574 | 8.0 | 0.547 | 45.5 | LOS D | 12.6 | 94.0 | 0.89 | 0.82 | 19.7 |
| West: The Horsley Drive | | | | | | | | | | | |
| W_L | L | 25 | 8.0 | 0.023 | 10.7 | LOS A | 0.2 | 1.1 | 0.18 | 0.67 | 54.3 |
| W_T | T | 565 | 8.0 | 0.553 | 41.0 | LOS C | 13.1 | 97.9 | 0.91 | 0.80 | 29.3 |
| 12 | R | 34 | 8.0 | 0.090 | 38.6 | LOS C | 0.7 | 5.5 | 0.75 | 0.66 | 33.7 |
| Approach | | 624 | 8.0 | 0.553 | 39.6 | LOS C | 13.1 | 97.9 | 0.87 | 0.79 | 30.2 |
| All Vehicles | | 2632 | 8.0 | 0.553 | 40.1 | LOS C | 13.1 | 97.9 | 0.84 | 0.79 | 27.0 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

SIDRA Standard Delay Model used.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|--------------------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P1 | Across S approach | 11 | 2.2 | LOS A | 0.0 | 0.0 | 0.20 | 0.20 |
| P2 | Across S approach | 11 | 32.1 | LOS D | 0.0 | 0.0 | 0.76 | 0.76 |
| P5 | Across N approach | 11 | 10.0 | LOS B | 0.0 | 0.0 | 0.43 | 0.43 |
| P6 | Across N approach | 11 | 32.1 | LOS D | 0.0 | 0.0 | 0.76 | 0.76 |
| All Pedestrians | | 44 | 19.1 | LOS B | | | 0.54 | 0.54 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)

Pedestrian movement LOS values are based on average delay per pedestrian movement.

Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

Processed: Tuesday, 29 May 2012 3:49:45 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: M7 On/Off - Ramp / The
Horsley Drive - EX PM

M7 and The Horsley Drive, Horsley Park

Existing - AM

Signals - Fixed Time Cycle Time = 95 seconds (Optimum Cycle Time - Minimum Delay)

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|--------------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: M7 On / Off-Ramp (South) | | | | | | | | | | | |
| S_L | L | 49 | 8.0 | 0.057 | 13.8 | LOS A | 0.9 | 6.4 | 0.57 | 0.73 | 39.6 |
| S_R | R | 182 | 8.0 | 0.427 | 48.5 | LOS D | 4.2 | 31.4 | 0.99 | 0.78 | 16.8 |
| Approach | | 232 | 8.0 | 0.427 | 41.1 | LOS C | 4.2 | 31.4 | 0.90 | 0.77 | 19.5 |
| East: The Horsley Drive | | | | | | | | | | | |
| E_L | L | 440 | 8.0 | 0.608 | 15.9 | LOS B | 7.3 | 54.7 | 0.49 | 0.76 | 48.8 |
| E_T | T | 757 | 8.0 | 0.384 | 18.1 | LOS B | 10.3 | 77.2 | 0.64 | 0.68 | 42.9 |
| 6 | R | 477 | 8.0 | 0.473 | 24.8 | LOS B | 5.9 | 43.9 | 0.87 | 0.79 | 41.4 |
| Approach | | 1674 | 8.0 | 0.608 | 19.4 | LOS B | 10.3 | 77.2 | 0.66 | 0.73 | 43.9 |
| North: M7 On / Off-Ramp (North) | | | | | | | | | | | |
| N_L | L | 273 | 8.0 | 0.290 | 26.1 | LOS B | 3.5 | 26.5 | 0.90 | 0.79 | 28.6 |
| N_R | R | 44 | 8.0 | 0.208 | 46.9 | LOS D | 2.0 | 14.8 | 0.97 | 0.74 | 17.2 |
| Approach | | 317 | 8.0 | 0.290 | 29.0 | LOS C | 3.5 | 26.5 | 0.91 | 0.78 | 26.4 |
| West: The Horsley Drive | | | | | | | | | | | |
| W_L | L | 54 | 8.0 | 0.057 | 11.7 | LOS A | 0.5 | 3.4 | 0.27 | 0.68 | 53.1 |
| W_T | T | 569 | 8.0 | 0.516 | 34.1 | LOS C | 11.1 | 82.9 | 0.88 | 0.79 | 32.4 |
| 12 | R | 35 | 8.0 | 0.101 | 48.5 | LOS D | 0.8 | 6.2 | 0.91 | 0.69 | 29.7 |
| Approach | | 658 | 8.0 | 0.516 | 33.0 | LOS C | 11.1 | 82.9 | 0.84 | 0.77 | 33.5 |
| All Vehicles | | 2880 | 8.0 | 0.608 | 25.3 | LOS B | 11.1 | 82.9 | 0.75 | 0.75 | 37.4 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

SIDRA Standard Delay Model used.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|--------------------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P1 | Across S approach | 11 | 2.5 | LOS A | 0.0 | 0.0 | 0.23 | 0.23 |
| P2 | Across S approach | 11 | 26.5 | LOS C | 0.0 | 0.0 | 0.75 | 0.75 |
| P5 | Across N approach | 11 | 18.3 | LOS B | 0.0 | 0.0 | 0.62 | 0.62 |
| P6 | Across N approach | 11 | 26.5 | LOS C | 0.0 | 0.0 | 0.75 | 0.75 |
| All Pedestrians | | 44 | 18.5 | LOS B | | | 0.59 | 0.59 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)

Pedestrian movement LOS values are based on average delay per pedestrian movement.

Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

Processed: Tuesday, 29 May 2012 3:49:46 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Horsley Dr & Cowpasture Rd
- EX AM

Horsley Drive and Cowpasture Rd

Signals - Fixed Time Cycle Time = 115 seconds (Optimum Cycle Time - Minimum Delay)

| Movement Performance - Vehicles | | | | | | | | | | | |
|----------------------------------|------|----------------------|---------|--------------------|----------------------|------------------|--------------------------------------|------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: The Horsley Drive (south) | | | | | | | | | | | |
| 2 | T | 1155 | 8.0 | 0.387 | 3.2 | LOS A | 8.9 | 66.3 | 0.30 | 0.27 | 46.8 |
| 3 | R | 467 | 8.0 | 1.000 ³ | 91.2 | LOS F | 19.6 | 146.9 | 1.00 | 1.05 | 8.8 |
| Approach | | 1622 | 8.0 | 1.000 | 28.6 | LOS C | 19.6 | 146.9 | 0.50 | 0.50 | 20.9 |
| East: Cowpasture Road | | | | | | | | | | | |
| 4 | L | 165 | 8.0 | 0.271 | 35.1 | LOS C | 7.1 | 53.2 | 0.87 | 0.79 | 20.1 |
| 6 | R | 291 | 8.0 | 0.951 | 82.6 | LOS F | 9.9 | 74.3 | 1.00 | 1.09 | 10.8 |
| Approach | | 456 | 8.0 | 0.951 | 65.3 | LOS E | 9.9 | 74.3 | 0.95 | 0.98 | 13.0 |
| North: The Horsley Drive (north) | | | | | | | | | | | |
| 7 | L | 893 | 8.0 | 0.510 | 15.0 | LOS B | 9.7 | 72.8 | 0.43 | 0.72 | 42.9 |
| 8 | T | 1213 | 8.0 | 1.038 | 117.8 | LOS F | 62.9 | 470.6 | 1.00 | 1.54 | 13.8 |
| Approach | | 2105 | 8.0 | 1.038 | 74.2 | LOS F | 62.9 | 470.6 | 0.76 | 1.20 | 19.5 |
| All Vehicles | | 4183 | 8.0 | 1.038 | 55.5 | LOS D | 62.9 | 470.6 | 0.68 | 0.90 | 19.1 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

SIDRA Standard Delay Model used.

3 x = 1.00 due to short lane. Refer to the Lane Summary report for information about excess flow and related conditions.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|------------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P3 | Across E approach | 11 | 16.2 | LOS B | 0.0 | 0.0 | 0.53 | 0.53 |
| All Pedestrians | | 11 | 16.2 | LOS B | | | 0.53 | 0.53 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)

Pedestrian movement LOS values are based on average delay per pedestrian movement.

Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

Processed: Tuesday, 29 May 2012 3:49:33 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip
8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Horsley Dr & Cowpasture Rd
- EX PM

Horsley Drive and Cowpasture Rd

Signals - Fixed Time Cycle Time = 105 seconds (Optimum Cycle Time - Minimum Delay)

| Movement Performance - Vehicles | | | | | | | | | | | |
|----------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|--------------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: The Horsley Drive (south) | | | | | | | | | | | |
| 2 | T | 1040 | 8.0 | 0.463 | 12.9 | LOS A | 14.8 | 110.8 | 0.61 | 0.54 | 30.7 |
| 3 | R | 144 | 8.0 | 0.718 | 66.6 | LOS E | 4.0 | 30.1 | 1.00 | 0.84 | 11.5 |
| Approach | | 1184 | 8.0 | 0.718 | 19.4 | LOS B | 14.8 | 110.8 | 0.65 | 0.58 | 25.5 |
| East: Cowpasture Road | | | | | | | | | | | |
| 4 | L | 609 | 8.0 | 0.748 | 33.4 | LOS C | 23.7 | 177.1 | 0.99 | 0.99 | 21.0 |
| 6 | R | 914 | 8.0 | 0.881 | 56.3 | LOS D | 25.9 | 194.1 | 1.00 | 0.98 | 14.7 |
| Approach | | 1523 | 8.0 | 0.881 | 47.1 | LOS D | 25.9 | 194.1 | 0.99 | 0.98 | 16.7 |
| North: The Horsley Drive (north) | | | | | | | | | | | |
| 7 | L | 300 | 8.0 | 0.131 | 9.6 | LOS A | 1.4 | 10.5 | 0.20 | 0.65 | 47.9 |
| 8 | T | 1306 | 8.0 | 0.875 | 37.4 | LOS C | 35.7 | 266.8 | 0.97 | 1.01 | 33.2 |
| Approach | | 1606 | 8.0 | 0.875 | 32.3 | LOS C | 35.7 | 266.8 | 0.83 | 0.94 | 34.8 |
| All Vehicles | | 4314 | 8.0 | 0.881 | 34.0 | LOS C | 35.7 | 266.8 | 0.84 | 0.85 | 26.6 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

SIDRA Standard Delay Model used.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|--------------------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P3 | Across E approach | 11 | 20.7 | LOS C | 0.0 | 0.0 | 0.63 | 0.63 |
| All Pedestrians | | 11 | 20.7 | LOS C | | | 0.63 | 0.63 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)

Pedestrian movement LOS values are based on average delay per pedestrian movement.

Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

Processed: Tuesday, 29 May 2012 3:49:34 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Cowpasture Rd & Newton Dr
- EX AM

Cowpasture Road & Newton Road
Roundabout

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|---------------------|-------------------------|---------------------|--------------------------------|------------------------|-----------------|-----------------------------------|--------------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Vehicles veh | Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: Cowpasture Road (south) | | | | | | | | | | | |
| 2 | T | 723 | 8.0 | 0.456 | 3.6 | LOS A | 3.8 | 28.1 | 0.15 | 0.34 | 41.4 |
| 3 | R | 757 | 8.0 | 0.456 | 9.1 | LOS A | 3.8 | 28.1 | 0.13 | 0.62 | 41.2 |
| Approach | | 1480 | 8.0 | 0.456 | 6.4 | LOS A | 3.8 | 28.1 | 0.14 | 0.48 | 41.3 |
| East: Newton Road | | | | | | | | | | | |
| 4 | L | 273 | 8.0 | 0.279 | 5.4 | LOS A | 1.5 | 11.1 | 0.40 | 0.53 | 43.3 |
| 6 | R | 18 | 8.0 | 0.279 | 10.0 | LOS A | 1.5 | 11.1 | 0.40 | 0.75 | 41.0 |
| Approach | | 291 | 8.0 | 0.279 | 5.6 | LOS A | 1.5 | 11.1 | 0.40 | 0.54 | 43.1 |
| North: Cowpasture Road (south) | | | | | | | | | | | |
| 7 | L | 75 | 8.0 | 0.163 | 8.7 | LOS A | 0.9 | 6.7 | 0.66 | 0.73 | 41.8 |
| 8 | T | 183 | 8.0 | 0.163 | 7.8 | LOS A | 0.9 | 6.7 | 0.66 | 0.70 | 42.1 |
| Approach | | 258 | 8.0 | 0.163 | 8.1 | LOS A | 0.9 | 6.7 | 0.66 | 0.71 | 42.0 |
| All Vehicles | | 2028 | 8.0 | 0.456 | 6.5 | LOS A | 3.8 | 28.1 | 0.24 | 0.52 | 41.7 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model used.

Processed: Tuesday, 29 May 2012 3:49:38 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12_096ms01v4 TRAFFIX Final.sip
8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Cowpasture Rd & Newton Dr
- EX PM

Cowpasture Road & Newton Road
Roundabout

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|---------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: Cowpasture Road (south) | | | | | | | | | | | |
| 2 | T | 218 | 8.0 | 0.144 | 3.6 | LOS A | 1.0 | 7.2 | 0.16 | 0.34 | 41.3 |
| 3 | R | 226 | 8.0 | 0.144 | 9.1 | LOS A | 1.0 | 7.2 | 0.15 | 0.61 | 41.1 |
| Approach | | 444 | 8.0 | 0.144 | 6.4 | LOS A | 1.0 | 7.2 | 0.16 | 0.48 | 41.2 |
| East: Newton Road | | | | | | | | | | | |
| 4 | L | 534 | 8.0 | 1.079 | 99.9 | LOS F | 37.8 | 282.6 | 1.00 | 3.56 | 14.7 |
| 6 | R | 32 | 8.0 | 1.079 | 104.5 | LOS F | 37.8 | 282.6 | 1.00 | 3.56 | 15.0 |
| Approach | | 565 | 8.0 | 1.079 | 100.1 | LOS F | 37.8 | 282.6 | 1.00 | 3.56 | 14.7 |
| North: Cowpasture Road (north) | | | | | | | | | | | |
| 7 | L | 44 | 8.0 | 0.537 | 5.9 | LOS A | 2.5 | 18.9 | 0.44 | 0.60 | 43.4 |
| 8 | T | 989 | 8.0 | 0.537 | 4.7 | LOS A | 2.5 | 18.9 | 0.44 | 0.49 | 43.7 |
| Approach | | 1034 | 8.0 | 0.537 | 4.8 | LOS A | 2.5 | 18.9 | 0.44 | 0.49 | 43.6 |
| All Vehicles | | 2043 | 8.0 | 1.079 | 31.5 | LOS C | 37.8 | 282.6 | 0.53 | 1.34 | 27.6 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model used.

Processed: Tuesday, 29 May 2012 3:49:38 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip
8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Cowpasture Rd & Horsley Drive - EX AM

Cowpasture Rd & Horsley Drive
Roundabout

| Movement Performance - Vehicles | | | | | | | | | | | |
|----------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|---------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: Cowpasture Road | | | | | | | | | | | |
| 2 | T | 1016 | 8.0 | 0.929 | 18.3 | LOS B | 16.7 | 124.8 | 1.00 | 1.35 | 43.5 |
| 3 | R | 655 | 8.0 | 0.929 | 27.8 | LOS B | 16.0 | 119.6 | 1.00 | 1.37 | 38.5 |
| Approach | | 1671 | 8.0 | 0.929 | 22.0 | LOS B | 16.7 | 124.8 | 1.00 | 1.36 | 41.3 |
| East: The Horsley Drive (east) | | | | | | | | | | | |
| 4 | L | 161 | 8.0 | 0.327 | 7.0 | LOS A | 2.8 | 20.8 | 0.66 | 0.60 | 47.5 |
| 5 | T | 2 | 8.0 | 0.327 | 5.3 | LOS A | 2.8 | 20.8 | 0.66 | 0.53 | 47.5 |
| 6 | R | 604 | 8.0 | 0.327 | 13.6 | LOS A | 2.8 | 20.8 | 0.67 | 0.72 | 44.3 |
| Approach | | 767 | 8.0 | 0.327 | 12.2 | LOS A | 2.8 | 20.8 | 0.67 | 0.69 | 44.9 |
| North: The Horsley Drive (north) | | | | | | | | | | | |
| 7 | L | 980 | 8.0 | 0.941 | 25.1 | LOS B | 24.5 | 183.4 | 0.95 | 1.35 | 23.6 |
| 8 | T | 398 | 8.0 | 0.522 | 8.6 | LOS A | 4.2 | 31.3 | 0.72 | 0.77 | 39.5 |
| 9 | R | 1 | 8.0 | 0.522 | 16.4 | LOS B | 4.2 | 31.3 | 0.72 | 0.99 | 35.1 |
| Approach | | 1379 | 8.0 | 0.941 | 20.3 | LOS B | 24.5 | 183.4 | 0.88 | 1.18 | 26.7 |
| West: Park Access | | | | | | | | | | | |
| 10 | L | 2 | 8.0 | 0.017 | 9.6 | LOS A | 0.1 | 0.7 | 0.89 | 0.77 | 20.2 |
| 11 | T | 1 | 8.0 | 0.017 | 9.4 | LOS A | 0.1 | 0.7 | 0.89 | 0.76 | 20.2 |
| 12 | R | 2 | 8.0 | 0.017 | 14.6 | LOS B | 0.1 | 0.7 | 0.89 | 0.85 | 20.8 |
| Approach | | 5 | 8.0 | 0.017 | 11.6 | LOS A | 0.1 | 0.7 | 0.89 | 0.80 | 20.5 |
| All Vehicles | | 3822 | 8.0 | 0.941 | 19.4 | LOS B | 24.5 | 183.4 | 0.89 | 1.16 | 38.1 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model used.

Processed: Tuesday, 29 May 2012 4:30:41 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Cowpasture Rd & Horsley Drive - EX PM

Cowpasture Rd & Horsley Drive
Roundabout

| Movement Performance - Vehicles | | | | | | | | | | | |
|----------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: Cowpasture Road | | | | | | | | | | | |
| 2 | T | 435 | 8.0 | 0.424 | 7.0 | LOS A | 2.7 | 20.0 | 0.75 | 0.60 | 52.2 |
| 3 | R | 286 | 8.0 | 0.424 | 15.5 | LOS B | 2.5 | 18.7 | 0.75 | 0.92 | 47.1 |
| Approach | | 721 | 8.0 | 0.424 | 10.4 | LOS A | 2.7 | 20.0 | 0.75 | 0.73 | 49.9 |
| East: The Horsley Drive (east) | | | | | | | | | | | |
| 4 | L | 458 | 8.0 | 0.845 | 68.7 | LOS E | 44.9 | 335.6 | 1.00 | 1.29 | 20.8 |
| 5 | T | 4 | 8.0 | 0.845 | 67.1 | LOS E | 44.9 | 335.6 | 1.00 | 1.29 | 20.8 |
| 6 | R | 743 | 8.0 | 0.845 | 91.1 | LOS F | 44.9 | 335.6 | 1.00 | 1.47 | 18.5 |
| Approach | | 1205 | 8.0 | 0.845 | 82.5 | LOS F | 44.9 | 335.6 | 1.00 | 1.40 | 19.3 |
| North: The Horsley Drive (north) | | | | | | | | | | | |
| 7 | L | 816 | 8.0 | 0.727 | 9.0 | LOS A | 8.2 | 61.3 | 0.58 | 0.68 | 38.8 |
| 8 | T | 1100 | 8.0 | 0.777 | 6.6 | LOS A | 10.5 | 78.8 | 0.59 | 0.60 | 41.1 |
| 9 | R | 1 | 8.0 | 0.777 | 14.4 | LOS A | 10.5 | 78.8 | 0.59 | 0.92 | 36.8 |
| Approach | | 1917 | 8.0 | 0.777 | 7.6 | LOS A | 10.5 | 78.8 | 0.59 | 0.63 | 40.1 |
| West: Park Access | | | | | | | | | | | |
| 10 | L | 6 | 8.0 | 0.024 | 4.9 | LOS A | 0.1 | 0.8 | 0.72 | 0.65 | 21.3 |
| 11 | T | 6 | 8.0 | 0.024 | 4.7 | LOS A | 0.1 | 0.8 | 0.72 | 0.64 | 21.2 |
| 12 | R | 1 | 8.0 | 0.024 | 10.0 | LOS A | 0.1 | 0.8 | 0.72 | 0.91 | 21.8 |
| Approach | | 14 | 8.0 | 0.024 | 5.2 | LOS A | 0.1 | 0.8 | 0.72 | 0.67 | 21.3 |
| All Vehicles | | 3857 | 8.0 | 0.845 | 31.5 | LOS C | 44.9 | 335.6 | 0.75 | 0.89 | 28.0 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model used.

Processed: Tuesday, 29 May 2012 3:49:43 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Ferrers Rd & Horsley Dr - EX
AM

Ferrers Rd & Horsley Dr

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|--------------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| East: Horsley Drive (east) | | | | | | | | | | | |
| 5 | T | 866 | 8.0 | 0.344 | 0.6 | LOS A | 1.8 | 13.7 | 0.08 | 0.07 | 67.9 |
| 6 | R | 459 | 8.0 | 1.045 | 120.7 | LOS F | 38.4 | 287.1 | 1.00 | 1.19 | 15.0 |
| Approach | | 1325 | 8.0 | 1.045 | 42.2 | LOS C | 38.4 | 287.1 | 0.40 | 0.45 | 30.7 |
| North: Ferrers Road | | | | | | | | | | | |
| 7 | L | 557 | 8.0 | 0.672 | 18.3 | LOS B | 16.7 | 124.9 | 0.75 | 0.80 | 34.9 |
| 9 | R | 24 | 8.0 | 0.197 | 56.8 | LOS E | 1.2 | 9.0 | 0.99 | 0.71 | 21.1 |
| Approach | | 581 | 8.0 | 0.672 | 19.9 | LOS B | 16.7 | 124.9 | 0.76 | 0.80 | 34.0 |
| West: Horsley Drive (west) | | | | | | | | | | | |
| 10 | L | 38 | 8.0 | 0.793 | 30.1 | LOS C | 31.2 | 233.7 | 0.86 | 0.96 | 39.5 |
| 11 | T | 1548 | 8.0 | 0.793 | 20.2 | LOS B | 31.5 | 235.6 | 0.87 | 0.80 | 40.7 |
| Approach | | 1586 | 8.0 | 0.793 | 20.5 | LOS B | 31.5 | 235.6 | 0.87 | 0.81 | 40.6 |
| All Vehicles | | 3493 | 8.0 | 1.045 | 28.6 | LOS C | 38.4 | 287.1 | 0.67 | 0.67 | 35.2 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

SIDRA Standard Delay Model used.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|--------------------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P5 | Across N approach | 5 | 13.0 | LOS B | 0.0 | 0.0 | 0.51 | 0.51 |
| All Pedestrians | | 5 | 13.0 | LOS B | | | 0.51 | 0.51 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)

Pedestrian movement LOS values are based on average delay per pedestrian movement.

Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

Processed: Tuesday, 29 May 2012 3:50:00 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Ferrers Rd & Horsley Dr - EX
PM

Ferrers Rd & Horsley Dr

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|---------------------|-------------------------|---------------------|--------------------------------|------------------------|-----------------|-----------------------------------|--------------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Vehicles veh | Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| East: Horsley Drive (east) | | | | | | | | | | | |
| 5 | T | 1609 | 8.0 | 0.569 | 1.9 | LOS A | 4.2 | 31.7 | 0.18 | 0.17 | 64.7 |
| 6 | R | 344 | 8.0 | 0.784 | 51.0 | LOS D | 16.2 | 120.9 | 0.96 | 0.88 | 27.5 |
| Approach | | 1954 | 8.0 | 0.784 | 10.6 | LOS A | 16.2 | 120.9 | 0.32 | 0.29 | 52.4 |
| North: Ferrers Road | | | | | | | | | | | |
| 7 | L | 600 | 8.0 | 0.593 | 11.2 | LOS A | 12.3 | 91.7 | 0.55 | 0.73 | 39.5 |
| 9 | R | 64 | 8.0 | 0.411 | 48.2 | LOS D | 3.0 | 22.2 | 0.96 | 0.75 | 23.2 |
| Approach | | 664 | 8.0 | 0.593 | 14.8 | LOS B | 12.3 | 91.7 | 0.59 | 0.73 | 37.0 |
| West: Horsley Drive (west) | | | | | | | | | | | |
| 10 | L | 18 | 8.0 | 0.601 | 31.1 | LOS C | 18.4 | 137.5 | 0.79 | 0.96 | 38.6 |
| 11 | T | 1006 | 8.0 | 0.601 | 21.3 | LOS B | 18.6 | 139.0 | 0.80 | 0.71 | 40.2 |
| Approach | | 1024 | 8.0 | 0.601 | 21.5 | LOS B | 18.6 | 139.0 | 0.80 | 0.71 | 40.1 |
| All Vehicles | | 3642 | 8.0 | 0.784 | 14.4 | LOS A | 18.6 | 139.0 | 0.50 | 0.49 | 45.3 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

SIDRA Standard Delay Model used.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|-------------------------|---------------------|--------------------------------------|------------------------|-----------------|-----------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Pedestrian ped | Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P5 | Across N approach | 5 | 17.4 | LOS B | 0.0 | 0.0 | 0.59 | 0.59 |
| All Pedestrians | | 5 | 17.4 | LOS B | | | 0.59 | 0.59 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)

Pedestrian movement LOS values are based on average delay per pedestrian movement.

Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

Processed: Tuesday, 29 May 2012 3:50:00 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Victoria St & Cowpasture Rd
- EX AM

Victoria Street & Cowpasture Road
Roundabout

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: Cowpasture Road (south) | | | | | | | | | | | |
| 1 | L | 247 | 8.0 | 0.256 | 6.6 | LOS A | 1.6 | 11.6 | 0.31 | 0.52 | 49.8 |
| 2 | T | 494 | 8.0 | 0.256 | 5.4 | LOS A | 1.6 | 11.6 | 0.32 | 0.45 | 50.6 |
| Approach | | 741 | 8.0 | 0.256 | 5.8 | LOS A | 1.6 | 11.6 | 0.32 | 0.47 | 50.4 |
| North: Victoria Street | | | | | | | | | | | |
| 8 | T | 156 | 8.0 | 0.109 | 5.2 | LOS A | 0.6 | 4.1 | 0.25 | 0.43 | 51.2 |
| 9 | R | 127 | 8.0 | 0.109 | 11.8 | LOS A | 0.5 | 4.1 | 0.26 | 0.65 | 45.6 |
| Approach | | 283 | 8.0 | 0.109 | 8.2 | LOS A | 0.6 | 4.1 | 0.26 | 0.53 | 48.4 |
| West: Cowpasture Road (west) | | | | | | | | | | | |
| 10 | L | 585 | 8.0 | 0.781 | 12.8 | LOS A | 8.2 | 61.6 | 0.84 | 1.05 | 44.4 |
| 12 | R | 102 | 8.0 | 0.781 | 18.5 | LOS B | 8.2 | 61.6 | 0.84 | 1.11 | 41.6 |
| Approach | | 687 | 8.0 | 0.781 | 13.7 | LOS A | 8.2 | 61.6 | 0.84 | 1.06 | 44.0 |
| All Vehicles | | 1712 | 8.0 | 0.781 | 9.4 | LOS A | 8.2 | 61.6 | 0.52 | 0.72 | 47.3 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model used.

Processed: Tuesday, 29 May 2012 3:50:02 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip
8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Victoria St & Cowpasture Rd
- EX PM

Victoria Street & Cowpasture Road
Roundabout

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|---------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: Cowpasture Road (south) | | | | | | | | | | | |
| 1 | L | 87 | 8.0 | 0.116 | 7.8 | LOS A | 0.7 | 5.5 | 0.59 | 0.63 | 48.2 |
| 2 | T | 162 | 8.0 | 0.116 | 7.0 | LOS A | 0.7 | 5.5 | 0.60 | 0.60 | 48.6 |
| Approach | | 249 | 8.0 | 0.116 | 7.3 | LOS A | 0.7 | 5.5 | 0.59 | 0.61 | 48.5 |
| North: Victoria Street | | | | | | | | | | | |
| 8 | T | 832 | 8.0 | 0.533 | 6.1 | LOS A | 3.8 | 28.2 | 0.52 | 0.53 | 49.1 |
| 9 | R | 467 | 8.0 | 0.533 | 12.9 | LOS A | 3.7 | 27.6 | 0.53 | 0.74 | 45.0 |
| Approach | | 1299 | 8.0 | 0.533 | 8.6 | LOS A | 3.8 | 28.2 | 0.52 | 0.61 | 47.5 |
| West: Cowpasture Road (west) | | | | | | | | | | | |
| 10 | L | 164 | 8.0 | 0.351 | 6.6 | LOS A | 2.0 | 15.1 | 0.40 | 0.53 | 49.0 |
| 12 | R | 226 | 8.0 | 0.351 | 12.3 | LOS A | 2.0 | 15.1 | 0.40 | 0.71 | 45.4 |
| Approach | | 391 | 8.0 | 0.351 | 9.9 | LOS A | 2.0 | 15.1 | 0.40 | 0.64 | 46.8 |
| All Vehicles | | 1939 | 8.0 | 0.533 | 8.7 | LOS A | 3.8 | 28.2 | 0.51 | 0.61 | 47.5 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model used.

Processed: Tuesday, 29 May 2012 3:50:02 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip
8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION



Appendix B



Western Sydney Parklands



STAGE 1 - PROPOSED DEVELOPMENT SITE AREAS

| LOT No. | SITE AREA |
|-------------|-----------|
| LOT 1-1 | 13 567 m2 |
| LOT 1-2 | 16 417 m2 |
| LOT 1-3 | 19 190 m2 |
| OSD BASIN | 1 780 m2 |
| ACCESS ROAD | 6 994 m2 |
| SUBTOTAL | 57 948 m2 |

STAGE 2 - PROPOSED DEVELOPMENT SITE AREAS

| LOT No. | SITE AREA |
|----------|-----------|
| LOT 2-1 | 19 014 m2 |
| LOT 2-2 | 20 029 m2 |
| LOT 2-3 | 10 297 m2 |
| LOT 2-4 | 25 384 m2 |
| SUBTOTAL | 74 724 m2 |

STAGE 3 - PROPOSED DEVELOPMENT SITE AREAS

| LOT No. | SITE AREA |
|-------------|-----------|
| LOT 3-1 | 15 447 m2 |
| LOT 3-2 | 30 922 m2 |
| LOT 3-3 | 9 894 m2 |
| LOT 3-4 | 9 923 m2 |
| LOT 3-5 | 9 976 m2 |
| ACCESS ROAD | 6 789 m2 |
| SUBTOTAL | 82 951 m2 |

TOTAL 215 623 m2

DEVELOPMENT DATA

| | |
|---|------------|
| TOTAL SITE AREA | 215 623 m2 |
| TOTAL ACCESS ROAD | 13 783 m2 |
| OSD BASIN | 1780 m2 |
| DEVELOPABLE SITE AREA (INCLUDING LANDSCAPE AREA) | 200 060 m2 |

NOTE:
DRAINAGE CHANNEL EXCLUDED FROM TOTAL SITE AREA



Western Sydney
Parklands Trust



project

HORSLEY DRIVE BUSINESS PARK
CNR HORSLEY DRIVE & COWPASTURE ROAD, WETHERILL PARK, NSW



CONCEPTARCHITECTURE P/L
CONCEPTARCHITECTURE Pty Ltd
abr 66 124 369 971
m 0405 522 516
P.O.BOX 3473, RHODES NSW 2138

title

**CONCEPT
LOT PLAN**

date

23.05.2012

drawing no.

HY-HW-MP-004 rev A


scale

1:1500 @ A1




Appendix C

Balanced Counts - AM



Balanced Counts - PM





Appendix D



Ref 12.096I01v1

17 May 2012

Bitzios Consulting
Studio 23, 3 Gladston Street
Newtown, NSW 2042

traffix
traffic & transport planners

suite 3.08
level 3 46a macleay street
potts point nsw 2011
po box 1061
potts point nsw 1335
t: +61 2 8324 8700
f: +61 2 9380 4481
w: www.traffix.com.au
director graham pindar
acn: 065132961
abn: 66065132961

Attention: Stephen Read

Re: Horsley Park Business Park – Paramics Micro Simulation Calibration Report

Dear Stephen,

TRAFFIX has been commissioned by the Western Sydney Parklands Trust to undertake a Paramics Micro Simulation Assessment in response to the Director General's Environmental Assessment Requirements dated 16 March 2012. The application relates to the construction of a industrial park on lands located on the corner of The Horsley Drive and Cowpasture Road, Horsley Park.

The requirements of the modelling were set out in the Roads and Maritime Services (RMS) letter dated 5 March 2012 and confirmed in a meeting held between the RMS and TRAFFIX dated 16 April 2012.

The purpose of this report is to provide the calibration and validation data for the purpose of obtaining approval for the base case models prior to the commencement of the scenario testing.

In this regard the base case model has been assessed taking due account of the RMS Guide to Paramics Microsimulation Modelling and other relevant documentation.

Site and Study Area

Site

The site is located approximately 1.8 kilometres south of Prospect Reservoir and approximately 30 kilometres west of Sydney CBD. More specifically, it is situated on the north western corner of the signalised 'T'-junction of the The Horsley Drive and Cowpasture Road, Horsley Park.

The site is irregular in configuration with a total site area of 213,833m².

Vehicular access is proposed via an internal roadway which is to intersect to the roundabout controlled intersection of Cowpasture Road and Newtown Road. The proposed internal roadway will convert the existing 3-way roundabout into a 4-way roundabout.



Study Area

The study area for the Paramics model will generally be confined within Horsley Park with the following roads / streets to be included the assessment:

- **M7:** an RMS State Road the runs in a north-south direction between the M2 in the north and the M5 in the south, carrying approximately 70,000 vpd in the vicinity of the study area. The M7 forms one of Sydney's major north-south corridors. It carries two lanes of traffic in either direction within a divided carriageway of width 38.0 metres.
- **The Horsley Drive** an RMS State Road (MR 609) that runs in an east-west direction between the Hume Highway in the east and Wallgrove Road in the west, carrying approximately 20,000 vpd within the study area. . It generally carries two lanes of traffic in either direction within a divided carriageway of width 27.0 metres.
- **Wallgrove Road:** an RMS State Road (MR 515) that runs in a north-south direction between the Great Western Highway in the north and Elizabeth Drive in the south, carrying approximately 20,000 vpd within the study area. It carries a single lane of traffic in either direction within an undivided carriageway of width 8.5 metres.
- **Cowpasture Road:** forms part of an RMS State Road, a Regional Road and a collector road within the study area, carrying approximately 29,000 vpd within the study area. Cowpasture Road is a State Road south of its roundabout controlled intersection with The Horsley Drive, a Regional Road between its signalised intersection with The Horsley Drive and roundabout controlled intersection with Victoria Street and a collector road north of its intersection with Victoria Street. . It carries two lanes of traffic in either direction within a divided carriageway of width 19.0 metres.
- **Newton Road:** a local road that runs in an east-west direction which links Victoria Street in the east with Cowpasture Road in the west. . It carries a single lane of traffic in either direction within an undivided carriageway of width 8.5 metres.
- **Ferrers Road:** a Regional Road (RR 7153) that runs in a north-south direction between Brabham Drive in the north and The Horsley Drive in the south. It carries a single lane of traffic in either direction within an undivided carriageway of width 8.5 metres.
- **Victoria Road:** a Regional Road that runs in an east-west direction between Cowpasture Road in the east and Warren Road in the west. . It carries two lanes of traffic in either direction within a divided carriageway of width 22.5 metres.



Input Data

Road Geometry

To identify existing road geometry, aerial photography was used and confirmed using signal layout plans and survey plans of the study area. This information was used to code the road network for the 'base' model. This information provided relevant information to enable coding including lane widths, lane lengths, number of lanes, direction of travel, road positioning, speed limits, location of bus stops and intersection configurations. In addition to the above numerous site inspections were also undertaken to review parking and clearway restrictions as well as other relevant details such as traffic movement restrictions and signal phasings.

Traffic Signal Data

TCS data was provided by the RMS and utilised for all phase sequences of the signalised intersections of the M7 / The Horsley Drive, M7 / Wallgrove Road and The Horsley Drive / Cowpasture Road. LX Data was also provided by the RMS and utilised for intersection offsets. It should be noted that the signalised intersections in the network are all SCATS optimised signal timings are varied depending on demand. It is also noted that the maximum cycle time for all intersections was 120 seconds.

Traffic Survey Data

Traffic surveys were undertaken at all critical intersections within the study area on Thursday the 5th April 2012. The surveys that were undertaken are summarised below;

- Turning movement counts summarised into 15 minute intervals between 6:30am and 9:00am.
- Turning movement counts summarised into 15 minute intervals between 3:30pm and 6:00pm.
- Queue length surveys on all approaches at key intersections only.
- Pedestrian surveys at key intersections only.

RMS Standard Files

The RMS provides a series of standard files for use in Paramics projects. These were used in both the AM and PM models and include the following:

- Categories,
- Configuration,
- Acceleration Profiles,
- Behaviour.

Changes to the vehicle file were undertaken to reflect the higher percentage of heavy vehicles that were observed during the traffic surveys. The vehicle proportions are discussed separately below.



2 Model Development

Network Coding

The network is shown in **Figure 1** below and includes all roads within the study area. The model was coded using aerial photographs of the area imported into Paramics and as such the model is at scale.




Figure 1: Extent of Model Network

Demand Zones

Following coding of the road network, demand zones were added to the model. Demand zones were positioned on the perimeter of the model and provide connections for through traffic on each external link. A total of 14 zones were created and are also shown in **Figure 1**.

Vehicle Classifications

The observed traffic counts differentiated between light vehicles and heavy vehicles, for the purpose of determining the percentage of heavy vehicles. The traffic counts demonstrated a higher heavy vehicle percentage compared to the standard vehicle proportions provided in the RMS Guide to Paramics Microsimulation Modelling. In this regard, the standard vehicle proportions were modified to reflect the increased percentage of heavy vehicles. The assumed vehicle classification proportions are given in Table 1 below.



Table 1: Vehicle Proportions

| Type No. | Vehicle | Proportion |
|----------|-------------------|------------|
| 1 | Small Car | 25.96% |
| 2 | Medium Car | 36.00% |
| 3 | Large Car | 21.25% |
| 4 | Taxi | 1.28% |
| 5 | LGV | 7.01% |
| 6 | STA Mini Bus | 0.00% |
| 7 | Non-STA Mini Bus | 0.00% |
| 8 | STA Bus | 0.00% |
| 9 | Non STA Bus | 0.00% |
| 10 | OD Bus | 0.10% |
| 11 | Rigid (Light) | 1.00% |
| 12 | Rigid (Medium) | 4.72% |
| 13 | Rigid (Heavy) | 1.00% |
| 14 | Semi (Light) | 0.23% |
| 15 | Semi (Medium) | 0.84% |
| 16 | Semi (Heavy) | 0.33% |
| 17 | B-Double (Light) | 0.15% |
| 18 | B-Double (Medium) | 0.12% |
| 19 | B-Double (Heavy) | 0.10% |
| Total | | 100% |

Peak Periods and Profiles

The traffic count data demonstrated the following AM and PM peak periods and accordingly, these time periods were adopted for the model:



- AM: 7:30am to 8:30am,
- PM: 3:30pm to 4:30pm.

Sufficient traffic count data was collected to allow traffic profiles to be established at 15 minute intervals over the AM and PM peak periods. Table 2 provides these profiles, calculated by summing the approach volumes on all major intersections every 15 minutes.

Table 2: Traffic Profiles

| AM Period | % of Peak | PM Period | % of Peak |
|-----------|-----------|-----------|-----------|
| 0730-0745 | 26% | 1530-1545 | 26% |
| 0745-0800 | 25% | 1545-1600 | 25% |
| 0800-0815 | 25% | 1600-1615 | 25% |
| 0815-0830 | 24% | 1615-1630 | 24% |

Model Calibration and Validation

Estimation Inputs

The demand matrices were developed through the use of the Paramics Estimator tool that develops base case OD matrices by balancing turning counts, link flows and cordon flows. To assist in the process Pattern Matrices was also developed with the use of an R^2 assessment and utilisation of the observed link flows at the network boundary.

The link flow and turn count data used in the estimation was established by balancing the surveyed data for both the AM and PM peaks so that the flow out of an upstream intersection matched flows arriving at a downstream intersection. Estimator was then able to produce an initial matrix for the AM and PM peaks, however these were then further refined during the calibration process.

Validation Statistics

The models were validated with the use of GEH statistics, comparisons of link and turn counts and queue lengths and model stability plots. GEH is considered the most effective measure in this case as it places greater relative emphasis on high volume movements compared to low volume movements. For example, volumes along The Horsley Drive were more heavily weighted than those along Ferrers Road.

Estimation Criteria

The criteria used to calibrate and validate the models have been adopted from the Paramics Microsimulation Modelling – RMS Manual which adopts the criteria outlined in the “UK Design



Manual for Roads and Bridges”. This document outlines a number of validation criteria, however these are to be adopted depending on the type and use of the model. In this case the following criteria have been adopted (it should however be noted that non compliance with these criteria does not necessarily indicate an incorrect model and the validation guidelines should be viewed in that context, as a guide in the assessment process):

Links Flows:

- Percentage within 20% or 200 vehicles per hour (target 95%).
- Percentage within 10% or 100 vehicles per hour (target 90%).
- Percentage within 5% or 50 vehicles per hour (target 85%).

Intersection Counts:

- Greater than 85% of all individual modelled flows to have a GEH of less than 5.

Travel Times:

- Average modelled travel time compared with average observed travel time with 95% confidence interval.

Queue Lengths:

- A range of the modelled queue lengths should be compared against the observed queue lengths to ensure they are similar.

Model Stability:

- A graph of the network vehicles over the simulation time period is to demonstrate consistency between model runs.

AM Model Validation

The AM model was calibrated to the balanced turning movements and estimation criteria discussed above. The summary of the key validation statistics for the AM period are as follows:

Link Flows:

Table 3: AM Link Statistics

| AM Period | % of Links |
|--|------------|
| Links within 20% or 200 veh/hr of modelled flows | 100% |
| Links within 10% or 100 veh/hr of modelled flows | 100% |
| Links within 5% or 50 veh/hr of modelled flows | 83% |



| | |
|-------------------------------|------|
| Number of links with GEH <5.0 | 100% |
|-------------------------------|------|

Table 3 demonstrates that 100% of links are within 100 veh/hr of modelled flows and 100% of links have a GEH of less than 5. Accordingly, the link statistic requirements have been satisfied having regard for the abovementioned estimation criteria.

Intersection Counts:

Table 4: AM Turn Count Statistics

| GEH | Number of Cases | Percentage |
|------|-----------------|------------|
| <2 | 40 | 69% |
| 2-5 | 17 | 29% |
| 5-10 | 1 | 2% |

Table 4 demonstrates that 98% of individual modelled counts have a GEH of less than 5. Accordingly, the intersection count link requirements have been satisfied having regard for the aforementioned estimation criteria.

Travel Times:

Travel times were also measured along the main routes on Thursday the 5th April 2012. Each travel route was measured between 2 to 3 times between 7:00am-8:00am and 4:00pm-5:00pm with the average of the three runs used for validation purposes. The routes tested and respective times are provided in **Table 5**. For validation purposes modelled times within 15% of the surveyed times are considered acceptable.

Table 5: AM Travel Time Statistics

| From Zone No. | To Zone No. | Surveyed (sec) | Modelled (sec) | Difference |
|---------------|-------------|----------------|----------------|------------|
| 3 | 12 | 410 | 443 | 8.1% |
| 3 | 11 | 420 | 466 | 10.9% |
| 6 | 9 | 360 | 396 | 10.0% |
| 9 | 3 | 360 | 343 | -4.7% |
| 12 | 7 | 290 | 273 | -5.9% |
| 11 | 3 | 310 | 283 | -8.7% |

Table 5 demonstrates that the modelled travel times are within 11% of the surveyed times and accordingly, the travel times requirements have also been satisfied.



Queue Lengths:

The queue lengths were observed on approach to all key intersections at 15 minute intervals over the AM and PM surveyed periods. **Table 6** provides a comparison between the range of observed queue lengths and the 95th percentile modelled queue lengths for each of the key intersections.

Table 6: AM Comparison of Queue Lengths

| Intersection | Direction | Observed Queue Range | 95% Percentile Modelled Queue |
|--|-----------|----------------------|-------------------------------|
| M7 / The Horsley Drive | SB | 13-27 veh. | 12 veh |
| | NB | 6-14 veh. | 5 veh |
| | WB | 8-18 veh. | 7 veh |
| | EB | 7-9 veh. | 12 veh |
| The Horsley Drive / Ferrers Road | SB | 10-15 veh. | 29 veh |
| | WB | 17-35 veh. | 33 veh |
| | EB | 20-27 veh. | 32 veh |
| The Horsley Drive / Cowpasture Road | SB | 17-75 veh. | 81 veh |
| | NB | 12-23 veh. | 17 veh |
| | WB | 5-10 veh. | 5 veh |
| The Horsley Drive / Cowpasture Road / Horsley Park Access Road | SB | 14-22 veh. | 16 veh |
| | NB | 20-30 veh. | 43 veh |
| | WB | 2-5 veh. | 4 veh |
| | EB | 0 veh. | 2 veh |

It can be seen from Table 6 that the 95% percentile modelled queue lengths are comparable with the observed queue ranges and therefore the modelled queues are considered representative.



Model Stability:

A model is considered 'stable' when it produces similar and comparable results between runs. The AM model has been run 5 times using the 5 standard seed numbers (28, 2894, 560, 86524 and 7771) defined in the RMS Paramics Modelling Guide, to ensure that the model is stable and robust. **Figure 3** shows the number of vehicles in the network over the AM peak period of 7:30-8:30am. It is noted that each run included a 15 minute warm-up period prior to the start of data collection period.




Figure 3: AM Base Stability Graph

Figure 3 demonstrates that the number of vehicles in the network are comparable between the various runs over the period 7:30-8:30am. The AM model is therefore considered stable. It is noted that Seed 86524 has been used for the generation of AM model results.

The above model statistics therefore meet the requirements of the RMS and represent an accurate model for the AM peak period between 7:30am and 8:30am. The 2012 base AM model is therefore considered adequate for future year scenarios testing and assessment and adequately reflects existing conditions.

PM Model Validation

The PM model was also calibrated to the balanced turning movements and estimation criteria discussed previously. The key validation statistics for the PM peak are as follows:



Link Flows:

Table 6: PM Link Statistics

| AM Period | % of Links |
|---|------------|
| Links within 200 veh/hr of modelled flows | 100% |
| Links within 100 veh/hr of modelled flows | 100% |
| Links within 50 veh/hr of modelled flows | 89% |
| Number of links with GEH <5.0 | 100% |

Table 6 demonstrates that 100% of links are within 100 veh/hr of modelled flows and 100% of links have a GEH of less than 5. Accordingly, the link statistic requirements have been satisfied having regard for the RMS estimation criteria.

Intersection Counts:

Table 7: PM Turn Count Statistics

| GEH | Number of Cases | Percentage |
|------|-----------------|------------|
| <2 | 41 | 71% |
| 2-5 | 17 | 29% |
| 5-10 | 58 | 100% |

Table 7 demonstrates that 100% of individual modelled counts have a GEH of less than 5. Accordingly, the intersection count link requirements have been satisfied having regard for the RMS estimation criteria.

Travel Times:

Table 8 provides a comparison between the observed and modelled travel times. For validation purposes modelled times within 15% of the surveyed times are considered acceptable.



Table 8: PM Travel Times

| From Zone No. | To Zone No. | Surveyed (sec) | Modelled (sec) | Difference |
|---------------|-------------|----------------|----------------|------------|
| 3 | 11 | 350 | 341 | -2.6% |
| 6 | 9 | 250 | 266 | 6.4% |
| 11 | 5 | 375 | 345 | -8.0% |
| 4 | 9 | 295 | 282 | -1.0% |
| 9 | 3 | 340 | 348 | 8.5% |

Table 8 demonstrates that the modelled travel times are within 10% of the surveyed times and accordingly, the travel time requirement has been satisfied.

Queue Lengths:

Table 9 provides a comparison between the range of observed queue lengths and the 95th percentile modelled queue lengths for each of the key intersections.

Table 9: PM Comparison of Queue Lengths

| Intersection | Direction | Observed Queue Range | 95% Percentile Modelled Queue |
|-------------------------------------|-----------|----------------------|-------------------------------|
| M7 / The Horsley Drive | SB | 6-10 veh. | 3 veh |
| | NB | 5-8 veh. | 3 veh |
| | WB | 10-14 veh. | 10 veh |
| | EB | 8-10 veh. | 9 veh |
| The Horsley Drive / Ferrers Road | SB | 8-15 veh. | 15 veh |
| | WB | 9-16 veh. | 19 veh |
| | EB | 10-19 veh. | 11 veh |
| The Horsley Drive / Cowpasture Road | SB | 24-46 veh. | 46 veh |
| | NB | 12-20 veh. | 11 veh |
| | WB | 18-25 veh. | 28 veh |



| | | | |
|--|----|------------|--------|
| The Horsley Drive / Cowpasture Road / Horsley Park Access Road | SB | 16-21 veh. | 15 veh |
| | NB | 5-10 veh. | 4 veh |
| | WB | 10-25 veh. | 29 veh |
| | EB | 0 veh. | 0 veh |

It can be seen from Table 9 that the 95% percentile modelled queue lengths are comparable with the observed queue ranges and are therefore considered representative.

Model Stability:

The PM model has also been run 5 times using the 5 standard seed numbers defined in the RMS Paramics Modelling Guide. **Figure 4** shows the number of vehicles in the network over the PM peak period of 3:30-4:30pm.




Figure 4: PM Base Stability Graph

Figure 4 demonstrates that the PM model is also stable and therefore, is an acceptable base model. It is noted that Seed 28 has been used for the generation of PM model results.



The above model statistics therefore meet the requirements of the RMS and represent an accurate model for the PM peak period between 3:30pm and 4:30pm. The 2012 base PM model is therefore considered adequate for future year scenarios testing and assessment and adequately reflects existing conditions.

Summary

The calibration and validation of the AM and PM base models demonstrates that the models are stable and representative of the observed traffic conditions. In this regard, both the AM and PM models are considered adequate for future year scenarios testing and assessment.

If you have any questions or would like to discuss the models further please do not hesitate to contact the undersigned.

Yours faithfully

traffic



Andrew Johnson
Associate Engineer



Appendix E

Site Generation

Generation to be assessed at rate of 15veh/hr/ha based on NMS correspondence dated 8th May 2012

| | |
|------------------|-------|
| Generation Rate | 15 |
| Site area | 21 |
| Site Generation | 321 |
| Generation Split | 70:30 |
| AM Generation | |
| In | 225 |
| Out | 96 |
| PM Generation | |
| In | 96 |
| Out | 225 |

Traffic Distribution Assumptions

1. East vehicles 65% via Horsley Drive, 25% via Victoria Street, 10% via Newton Rd
2. North 70% via M7, 20% via Walgrove Road, 10% via Ferrers Road
3. South 50% via Cowpasture, 50% via M7

Future Distribution

| Direction | AM | | PM | |
|-----------|-----|-----|----|-----|
| | In | Out | In | Out |
| North | 30 | 47 | 47 | 30 |
| South | 110 | 13 | 13 | 110 |
| East | 0 | 36 | 36 | 0 |
| West | 84 | 0 | 0 | 84 |
| Total | 225 | 96 | 96 | 225 |

Traffic TO Input Travel Zone to Nominated 1042

| SSD Description | SSD No. | Direction of Travel To | Direction of Travel From | Car Driver | Train | Bus | Vehicle Passenger | Other | Not Stated | Stayed At Home |
|----------------------------|---------|------------------------|--------------------------|------------|-------|-----|-------------------|-------|------------|----------------|
| Inner Sydney | 505 | south | north | 59 | 0 | 0 | 0 | 0 | 0 | 0 |
| Eastern Suburbs | 510 | south | north | 22 | 0 | 0 | 0 | 0 | 0 | 0 |
| St George-Sutherland | 515 | north | south | 216 | 0 | 0 | 6 | 0 | 27 | 0 |
| Canterbury-Bankstown | 520 | west | east | 252 | 0 | 0 | 20 | 7 | 9 | 1 |
| Fairfield - Liverpool | 525 | west | east | 2070 | 12 | 66 | 280 | 34 | 103 | 63 |
| Outer South Western Sydney | 530 | north | south | 620 | 0 | 0 | 45 | 11 | 39 | 9 |
| Inner Western Sydney | 535 | south | north | 100 | 33 | 0 | 0 | 5 | 3 | 3 |
| Central Western Sydney | 540 | south | north | 585 | 9 | 23 | 35 | 18 | 30 | 4 |
| Outer Western Sydney | 545 | south | north | 930 | 10 | 0 | 53 | 9 | 60 | 5 |
| Blacktown | 553 | south | north | 826 | 10 | 0 | 94 | 14 | 56 | 22 |
| Lower Northern Sydney | 555 | south | north | 97 | 0 | 0 | 3 | 0 | 9 | 0 |
| Central Northern Sydney | 560 | south | north | 392 | 0 | 0 | 16 | 9 | 25 | 0 |
| Northern Beaches | 565 | south | north | 40 | 0 | 0 | 0 | 0 | 0 | 0 |
| Total Trips | | | | 6209 | 79 | 89 | 552 | 107 | 361 | 107 |

| Direction of Travel Summary To SSD | | Volume | % |
|------------------------------------|--|--------|------|
| Northbound | | 836 | 13% |
| Southbound | | 3051 | 49% |
| Eastbound | | 0 | 0% |
| Westbound | | 2322 | 37% |
| Total | | 6209 | 100% |

| Direction of Travel Summary From SSD | | Volume | % |
|--------------------------------------|--|--------|------|
| Northbound | | 3051 | 49% |
| Southbound | | 836 | 13% |
| Eastbound | | 2322 | 37% |
| Westbound | | 0 | 0% |
| Total | | 6209 | 100% |



Appendix F

MOVEMENT SUMMARY

Site: M7 On/Off - Ramp / The
Horsley Drive - FU AM

M7 and The Horsley Drive, Horsley Park

Existing - AM

Signals - Fixed Time Cycle Time = 105 seconds (User-Given Cycle Time)

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|--------------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: M7 On / Off-Ramp (South) | | | | | | | | | | | |
| S_L | L | 59 | 8.0 | 0.056 | 11.8 | LOS A | 0.6 | 4.2 | 0.27 | 0.69 | 42.4 |
| S_R | R | 502 | 8.0 | 0.594 | 44.3 | LOS D | 11.6 | 86.8 | 0.94 | 0.82 | 18.0 |
| Approach | | 561 | 8.0 | 0.594 | 40.9 | LOS C | 11.6 | 86.8 | 0.87 | 0.80 | 19.3 |
| East: The Horsley Drive | | | | | | | | | | | |
| E_L | L | 163 | 8.0 | 0.322 | 20.9 | LOS B | 3.9 | 29.0 | 0.50 | 0.74 | 44.5 |
| E_T | T | 496 | 8.0 | 0.496 | 39.2 | LOS C | 10.8 | 81.0 | 0.90 | 0.79 | 30.1 |
| 6 | R | 282 | 8.0 | 0.269 | 38.7 | LOS C | 5.5 | 41.5 | 0.81 | 0.76 | 33.7 |
| Approach | | 941 | 8.0 | 0.496 | 35.9 | LOS C | 10.8 | 81.0 | 0.80 | 0.77 | 33.3 |
| North: M7 On / Off-Ramp (North) | | | | | | | | | | | |
| N_L | L | 618 | 8.0 | 0.601 | 44.0 | LOS D | 13.9 | 104.3 | 0.91 | 0.84 | 20.3 |
| N_R | R | 37 | 8.0 | 0.087 | 39.0 | LOS C | 1.5 | 11.0 | 0.81 | 0.69 | 19.7 |
| Approach | | 655 | 8.0 | 0.601 | 43.7 | LOS D | 13.9 | 104.3 | 0.90 | 0.83 | 20.3 |
| West: The Horsley Drive | | | | | | | | | | | |
| W_L | L | 25 | 8.0 | 0.023 | 10.8 | LOS A | 0.2 | 1.2 | 0.20 | 0.67 | 54.0 |
| W_T | T | 588 | 8.0 | 0.589 | 40.2 | LOS C | 13.2 | 99.1 | 0.92 | 0.81 | 29.6 |
| 12 | R | 34 | 8.0 | 0.085 | 36.1 | LOS C | 0.7 | 5.2 | 0.74 | 0.66 | 34.9 |
| Approach | | 647 | 8.0 | 0.589 | 38.9 | LOS C | 13.2 | 99.1 | 0.89 | 0.80 | 30.5 |
| All Vehicles | | 2804 | 8.0 | 0.601 | 39.4 | LOS C | 13.9 | 104.3 | 0.86 | 0.80 | 27.3 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

SIDRA Standard Delay Model used.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|--------------------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P1 | Across S approach | 11 | 2.3 | LOS A | 0.0 | 0.0 | 0.21 | 0.21 |
| P2 | Across S approach | 11 | 31.2 | LOS D | 0.0 | 0.0 | 0.77 | 0.77 |
| P5 | Across N approach | 11 | 10.5 | LOS B | 0.0 | 0.0 | 0.45 | 0.45 |
| P6 | Across N approach | 11 | 31.2 | LOS D | 0.0 | 0.0 | 0.77 | 0.77 |
| All Pedestrians | | 44 | 18.8 | LOS B | | | 0.55 | 0.55 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)

Pedestrian movement LOS values are based on average delay per pedestrian movement.

Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

Processed: Tuesday, 29 May 2012 3:49:47 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: M7 On/Off - Ramp / The
Horsley Drive - FU PM

M7 and The Horsley Drive, Horsley Park

Existing - AM

Signals - Fixed Time Cycle Time = 98 seconds (User-Given Cycle Time)

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|--------------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: M7 On / Off-Ramp (South) | | | | | | | | | | | |
| S_L | L | 49 | 8.0 | 0.058 | 13.7 | LOS A | 0.9 | 6.5 | 0.56 | 0.73 | 39.7 |
| S_R | R | 182 | 8.0 | 0.441 | 50.2 | LOS D | 4.3 | 32.5 | 1.00 | 0.78 | 16.4 |
| Approach | | 232 | 8.0 | 0.441 | 42.4 | LOS C | 4.3 | 32.5 | 0.90 | 0.77 | 19.0 |
| East: The Horsley Drive | | | | | | | | | | | |
| E_L | L | 440 | 8.0 | 0.607 | 15.9 | LOS B | 7.3 | 54.6 | 0.49 | 0.76 | 48.8 |
| E_T | T | 780 | 8.0 | 0.385 | 17.7 | LOS B | 10.7 | 80.1 | 0.62 | 0.67 | 43.2 |
| 6 | R | 558 | 8.0 | 0.513 | 24.6 | LOS B | 7.0 | 52.4 | 0.87 | 0.80 | 41.5 |
| Approach | | 1778 | 8.0 | 0.607 | 19.4 | LOS B | 10.7 | 80.1 | 0.67 | 0.73 | 44.0 |
| North: M7 On / Off-Ramp (North) | | | | | | | | | | | |
| N_L | L | 304 | 8.0 | 0.300 | 25.8 | LOS B | 4.0 | 29.9 | 0.89 | 0.79 | 28.8 |
| N_R | R | 44 | 8.0 | 0.214 | 48.6 | LOS D | 2.1 | 15.3 | 0.97 | 0.74 | 16.8 |
| Approach | | 348 | 8.0 | 0.300 | 28.7 | LOS C | 4.0 | 29.9 | 0.90 | 0.79 | 26.6 |
| West: The Horsley Drive | | | | | | | | | | | |
| W_L | L | 54 | 8.0 | 0.060 | 11.8 | LOS A | 0.5 | 3.6 | 0.28 | 0.69 | 52.9 |
| W_T | T | 582 | 8.0 | 0.544 | 36.0 | LOS C | 11.9 | 88.9 | 0.90 | 0.80 | 31.5 |
| 12 | R | 35 | 8.0 | 0.104 | 50.2 | LOS D | 0.9 | 6.4 | 0.92 | 0.69 | 29.2 |
| Approach | | 671 | 8.0 | 0.544 | 34.8 | LOS C | 11.9 | 88.9 | 0.85 | 0.78 | 32.6 |
| All Vehicles | | 3028 | 8.0 | 0.607 | 25.7 | LOS B | 11.9 | 88.9 | 0.75 | 0.75 | 37.2 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

SIDRA Standard Delay Model used.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|--------------------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P1 | Across S approach | 11 | 2.5 | LOS A | 0.0 | 0.0 | 0.22 | 0.22 |
| P2 | Across S approach | 11 | 27.9 | LOS C | 0.0 | 0.0 | 0.76 | 0.76 |
| P5 | Across N approach | 11 | 19.6 | LOS B | 0.0 | 0.0 | 0.63 | 0.63 |
| P6 | Across N approach | 11 | 27.9 | LOS C | 0.0 | 0.0 | 0.76 | 0.76 |
| All Pedestrians | | 44 | 19.5 | LOS B | | | 0.59 | 0.59 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)

Pedestrian movement LOS values are based on average delay per pedestrian movement.

Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

Processed: Tuesday, 29 May 2012 3:49:48 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Horsley Dr & Cowpasture Rd
- FU AM

Horsley Drive and Cowpasture Rd
Signals - Fixed Time Cycle Time = 111 seconds (User-Given Cycle Time)

| Movement Performance - Vehicles | | | | | | | | | | | |
|----------------------------------|------|----------------------|---------|--------------------|----------------------|------------------|--------------------------------------|------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: The Horsley Drive (south) | | | | | | | | | | | |
| 2 | T | 1255 | 8.0 | 0.431 | 3.8 | LOS A | 10.6 | 79.1 | 0.34 | 0.31 | 44.9 |
| 3 | R | 440 | 8.0 | 1.000 ³ | 102.7 | LOS F | 19.6 | 146.9 | 1.00 | 1.15 | 8.0 |
| Approach | | 1695 | 8.0 | 1.000 | 29.5 | LOS C | 19.6 | 146.9 | 0.51 | 0.53 | 20.4 |
| East: Cowpasture Road | | | | | | | | | | | |
| 4 | L | 198 | 8.0 | 0.338 | 39.1 | LOS C | 9.0 | 67.4 | 0.89 | 0.81 | 18.8 |
| 6 | R | 346 | 8.0 | 0.995 | 95.6 | LOS F | 12.8 | 95.5 | 1.00 | 1.19 | 9.6 |
| Approach | | 544 | 8.0 | 0.995 | 75.1 | LOS F | 12.8 | 95.5 | 0.96 | 1.05 | 11.7 |
| North: The Horsley Drive (north) | | | | | | | | | | | |
| 7 | L | 1026 | 8.0 | 0.472 | 14.8 | LOS B | 11.1 | 83.1 | 0.44 | 0.73 | 43.1 |
| 8 | T | 1213 | 8.0 | 1.050 | 125.5 | LOS F | 63.5 | 475.2 | 1.00 | 1.61 | 13.2 |
| Approach | | 2239 | 8.0 | 1.050 | 74.7 | LOS F | 63.5 | 475.2 | 0.74 | 1.21 | 19.4 |
| All Vehicles | | 4478 | 8.0 | 1.050 | 57.7 | LOS E | 63.5 | 475.2 | 0.68 | 0.93 | 18.6 |

Level of Service (LOS) Method: Delay (RTA NSW).
Vehicle movement LOS values are based on average delay per movement
Intersection and Approach LOS values are based on average delay for all vehicle movements.
SIDRA Standard Delay Model used.

3 x = 1.00 due to short lane. Refer to the Lane Summary report for information about excess flow and related conditions.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|------------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P3 | Across E approach | 11 | 16.2 | LOS B | 0.0 | 0.0 | 0.54 | 0.54 |
| All Pedestrians | | 11 | 16.2 | LOS B | | | 0.54 | 0.54 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)
Pedestrian movement LOS values are based on average delay per pedestrian movement.
Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

MOVEMENT SUMMARY

Site: Horsley Dr & Cowpasture Rd
- FU PM

Horsley Drive and Cowpasture Rd
Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time)

| Movement Performance - Vehicles | | | | | | | | | | | |
|----------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|--------------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: The Horsley Drive (south) | | | | | | | | | | | |
| 2 | T | 1040 | 8.0 | 0.483 | 16.4 | LOS B | 17.9 | 133.6 | 0.64 | 0.57 | 27.4 |
| 3 | R | 177 | 8.0 | 0.863 | 79.3 | LOS F | 5.9 | 43.9 | 1.00 | 0.95 | 10.0 |
| Approach | | 1217 | 8.0 | 0.863 | 25.6 | LOS B | 17.9 | 133.6 | 0.69 | 0.63 | 21.8 |
| East: Cowpasture Road | | | | | | | | | | | |
| 4 | L | 682 | 8.0 | 0.879 | 41.9 | LOS C | 38.0 | 284.2 | 0.92 | 0.94 | 18.2 |
| 6 | R | 1047 | 8.0 | 0.894 | 56.6 | LOS E | 32.4 | 242.4 | 0.99 | 0.97 | 14.6 |
| Approach | | 1729 | 8.0 | 0.894 | 50.8 | LOS D | 38.0 | 284.2 | 0.96 | 0.96 | 15.9 |
| North: The Horsley Drive (north) | | | | | | | | | | | |
| 7 | L | 356 | 8.0 | 0.158 | 9.6 | LOS A | 1.8 | 13.3 | 0.19 | 0.65 | 47.9 |
| 8 | T | 1306 | 8.0 | 0.909 | 49.7 | LOS D | 43.8 | 327.6 | 1.00 | 1.07 | 29.3 |
| Approach | | 1662 | 8.0 | 0.909 | 41.1 | LOS C | 43.8 | 327.6 | 0.83 | 0.98 | 31.3 |
| All Vehicles | | 4608 | 8.0 | 0.909 | 40.6 | LOS C | 43.8 | 327.6 | 0.84 | 0.88 | 23.9 |

Level of Service (LOS) Method: Delay (RTA NSW).
Vehicle movement LOS values are based on average delay per movement
Intersection and Approach LOS values are based on average delay for all vehicle movements.
SIDRA Standard Delay Model used.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|--------------------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P3 | Across E approach | 11 | 24.1 | LOS C | 0.0 | 0.0 | 0.63 | 0.63 |
| All Pedestrians | | 11 | 24.1 | LOS C | | | 0.63 | 0.63 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)
Pedestrian movement LOS values are based on average delay per pedestrian movement.
Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

MOVEMENT SUMMARY

Site: Cowpasture Rd & Horsley Drive - FU AM

Cowpasture Rd & Horsley Drive
Roundabout

| Movement Performance - Vehicles | | | | | | | | | | | |
|----------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|---------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: Cowpasture Road | | | | | | | | | | | |
| 2 | T | 1032 | 8.0 | 0.975 | 27.9 | LOS B | 23.8 | 177.7 | 1.00 | 1.63 | 36.6 |
| 3 | R | 655 | 8.0 | 0.975 | 38.1 | LOS C | 22.3 | 167.1 | 1.00 | 1.63 | 33.1 |
| Approach | | 1686 | 8.0 | 0.975 | 31.8 | LOS C | 23.8 | 177.7 | 1.00 | 1.63 | 35.1 |
| East: The Horsley Drive (east) | | | | | | | | | | | |
| 4 | L | 161 | 8.0 | 0.353 | 7.1 | LOS A | 3.1 | 23.0 | 0.68 | 0.61 | 47.3 |
| 5 | T | 2 | 8.0 | 0.353 | 5.4 | LOS A | 3.1 | 23.0 | 0.68 | 0.54 | 47.3 |
| 6 | R | 661 | 8.0 | 0.353 | 13.7 | LOS A | 3.1 | 23.0 | 0.69 | 0.72 | 44.2 |
| Approach | | 824 | 8.0 | 0.353 | 12.4 | LOS A | 3.1 | 23.0 | 0.69 | 0.70 | 44.8 |
| North: The Horsley Drive (north) | | | | | | | | | | | |
| 7 | L | 1005 | 8.0 | 0.966 | 30.7 | LOS C | 29.6 | 221.4 | 0.97 | 1.51 | 20.8 |
| 8 | T | 405 | 8.0 | 0.531 | 8.7 | LOS A | 4.3 | 32.3 | 0.72 | 0.78 | 39.3 |
| 9 | R | 1 | 8.0 | 0.531 | 16.5 | LOS B | 4.3 | 32.3 | 0.72 | 1.00 | 35.0 |
| Approach | | 1412 | 8.0 | 0.966 | 24.3 | LOS B | 29.6 | 221.4 | 0.90 | 1.30 | 24.0 |
| West: Park Access | | | | | | | | | | | |
| 10 | L | 2 | 8.0 | 0.018 | 10.5 | LOS A | 0.1 | 0.7 | 0.89 | 0.78 | 20.1 |
| 11 | T | 1 | 8.0 | 0.018 | 10.3 | LOS A | 0.1 | 0.7 | 0.89 | 0.77 | 20.0 |
| 12 | R | 2 | 8.0 | 0.018 | 15.5 | LOS B | 0.1 | 0.7 | 0.89 | 0.85 | 20.7 |
| Approach | | 5 | 8.0 | 0.018 | 12.5 | LOS A | 0.1 | 0.7 | 0.89 | 0.81 | 20.3 |
| All Vehicles | | 3927 | 8.0 | 0.975 | 25.0 | LOS B | 29.6 | 221.4 | 0.90 | 1.32 | 34.1 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model used.

Processed: Tuesday, 29 May 2012 4:30:58 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Cowpasture Rd & Horsley Drive - FU PM

Cowpasture Rd & Horsley Drive
Roundabout

| Movement Performance - Vehicles | | | | | | | | | | | |
|----------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|---------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: Cowpasture Road | | | | | | | | | | | |
| 2 | T | 442 | 8.0 | 0.436 | 7.2 | LOS A | 2.8 | 20.8 | 0.76 | 0.62 | 52.1 |
| 3 | R | 286 | 8.0 | 0.436 | 15.7 | LOS B | 2.6 | 19.4 | 0.76 | 0.94 | 47.1 |
| Approach | | 728 | 8.0 | 0.436 | 10.5 | LOS A | 2.8 | 20.8 | 0.76 | 0.74 | 49.9 |
| East: The Horsley Drive (east) | | | | | | | | | | | |
| 4 | L | 458 | 8.0 | 0.890 | 95.2 | LOS F | 58.9 | 440.4 | 1.00 | 1.65 | 16.6 |
| 5 | T | 4 | 8.0 | 0.890 | 93.5 | LOS F | 58.9 | 440.4 | 1.00 | 1.65 | 16.6 |
| 6 | R | 768 | 8.0 | 0.890 | 114.0 | LOS F | 58.9 | 440.4 | 1.00 | 1.74 | 15.8 |
| Approach | | 1231 | 8.0 | 0.890 | 106.9 | LOS F | 58.9 | 440.4 | 1.00 | 1.71 | 16.1 |
| North: The Horsley Drive (north) | | | | | | | | | | | |
| 7 | L | 873 | 8.0 | 0.776 | 9.7 | LOS A | 10.0 | 74.7 | 0.63 | 0.72 | 37.7 |
| 8 | T | 1116 | 8.0 | 0.788 | 6.7 | LOS A | 11.1 | 82.8 | 0.61 | 0.61 | 40.9 |
| 9 | R | 1 | 8.0 | 0.788 | 14.6 | LOS B | 11.1 | 82.8 | 0.61 | 0.92 | 36.7 |
| Approach | | 1989 | 8.0 | 0.788 | 8.0 | LOS A | 11.1 | 82.8 | 0.62 | 0.66 | 39.5 |
| West: Park Access | | | | | | | | | | | |
| 10 | L | 6 | 8.0 | 0.024 | 5.0 | LOS A | 0.1 | 0.8 | 0.73 | 0.66 | 21.2 |
| 11 | T | 6 | 8.0 | 0.024 | 4.8 | LOS A | 0.1 | 0.8 | 0.73 | 0.65 | 21.2 |
| 12 | R | 1 | 8.0 | 0.024 | 10.1 | LOS A | 0.1 | 0.8 | 0.73 | 0.91 | 21.8 |
| Approach | | 14 | 8.0 | 0.024 | 5.3 | LOS A | 0.1 | 0.8 | 0.73 | 0.67 | 21.3 |
| All Vehicles | | 3962 | 8.0 | 0.890 | 39.2 | LOS C | 58.9 | 440.4 | 0.76 | 1.00 | 24.8 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model used.

Processed: Tuesday, 29 May 2012 3:49:44 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Ferrers Rd & Horsley Dr - FU
AM

Ferrers Rd & Horsley Dr

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|--------------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| East: Horsley Drive (east) | | | | | | | | | | | |
| 5 | T | 917 | 8.0 | 0.362 | 0.6 | LOS A | 2.0 | 14.9 | 0.08 | 0.07 | 67.9 |
| 6 | R | 464 | 8.0 | 1.057 | 129.4 | LOS F | 40.3 | 301.8 | 1.00 | 1.21 | 14.2 |
| Approach | | 1381 | 8.0 | 1.057 | 43.9 | LOS D | 40.3 | 301.8 | 0.39 | 0.45 | 30.0 |
| North: Ferrers Road | | | | | | | | | | | |
| 7 | L | 568 | 8.0 | 0.714 | 20.9 | LOS B | 18.7 | 139.6 | 0.81 | 0.83 | 33.4 |
| 9 | R | 24 | 8.0 | 0.230 | 58.3 | LOS E | 1.2 | 9.2 | 1.00 | 0.71 | 20.8 |
| Approach | | 593 | 8.0 | 0.714 | 22.4 | LOS B | 18.7 | 139.6 | 0.82 | 0.82 | 32.6 |
| West: Horsley Drive (west) | | | | | | | | | | | |
| 10 | L | 38 | 8.0 | 0.838 | 33.6 | LOS C | 37.3 | 278.6 | 0.90 | 0.99 | 37.4 |
| 11 | T | 1671 | 8.0 | 0.838 | 23.7 | LOS B | 37.5 | 280.2 | 0.90 | 0.87 | 38.3 |
| Approach | | 1708 | 8.0 | 0.838 | 23.9 | LOS B | 37.5 | 280.2 | 0.90 | 0.88 | 38.3 |
| All Vehicles | | 3682 | 8.0 | 1.057 | 31.1 | LOS C | 40.3 | 301.8 | 0.70 | 0.71 | 33.9 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

SIDRA Standard Delay Model used.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|--------------------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P5 | Across N approach | 5 | 12.5 | LOS B | 0.0 | 0.0 | 0.50 | 0.50 |
| All Pedestrians | | 5 | 12.5 | LOS B | | | 0.50 | 0.50 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)

Pedestrian movement LOS values are based on average delay per pedestrian movement.

Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

Processed: Tuesday, 29 May 2012 3:50:01 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Ferrers Rd & Horsley Dr - FU
PM

Ferrers Rd & Horsley Dr

Signals - Fixed Time Cycle Time = 100 seconds (Optimum Cycle Time - Minimum Delay)

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|--------------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| East: Horsley Drive (east) | | | | | | | | | | | |
| 5 | T | 1714 | 8.0 | 0.597 | 1.9 | LOS A | 4.8 | 36.2 | 0.20 | 0.18 | 64.7 |
| 6 | R | 356 | 8.0 | 0.810 | 52.3 | LOS D | 17.2 | 128.4 | 0.97 | 0.90 | 27.1 |
| Approach | | 2069 | 8.0 | 0.810 | 10.6 | LOS A | 17.2 | 128.4 | 0.33 | 0.30 | 52.3 |
| North: Ferrers Road | | | | | | | | | | | |
| 7 | L | 605 | 8.0 | 0.612 | 11.8 | LOS A | 13.0 | 97.5 | 0.57 | 0.74 | 39.1 |
| 9 | R | 64 | 8.0 | 0.420 | 50.5 | LOS D | 3.0 | 22.7 | 0.98 | 0.76 | 22.6 |
| Approach | | 669 | 8.0 | 0.612 | 15.5 | LOS B | 13.0 | 97.5 | 0.61 | 0.74 | 36.6 |
| West: Horsley Drive (west) | | | | | | | | | | | |
| 10 | L | 18 | 8.0 | 0.601 | 29.9 | LOS C | 18.7 | 140.2 | 0.78 | 0.97 | 39.4 |
| 11 | T | 1051 | 8.0 | 0.601 | 20.0 | LOS B | 19.0 | 141.8 | 0.78 | 0.70 | 41.1 |
| Approach | | 1068 | 8.0 | 0.601 | 20.2 | LOS B | 19.0 | 141.8 | 0.78 | 0.70 | 41.1 |
| All Vehicles | | 3807 | 8.0 | 0.810 | 14.1 | LOS A | 19.0 | 141.8 | 0.51 | 0.49 | 45.6 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

SIDRA Standard Delay Model used.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|--------------------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Back of Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P5 | Across N approach | 5 | 16.2 | LOS B | 0.0 | 0.0 | 0.57 | 0.57 |
| All Pedestrians | | 5 | 16.2 | LOS B | | | 0.57 | 0.57 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)

Pedestrian movement LOS values are based on average delay per pedestrian movement.

Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

Processed: Tuesday, 29 May 2012 3:50:01 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip

8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Victoria St & Cowpasture Rd
- FU AM

Victoria Street & Cowpasture Road
Roundabout

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|---------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: Cowpasture Road (south) | | | | | | | | | | | |
| 1 | L | 251 | 8.0 | 0.259 | 6.6 | LOS A | 1.6 | 11.9 | 0.31 | 0.52 | 49.8 |
| 2 | T | 500 | 8.0 | 0.259 | 5.5 | LOS A | 1.6 | 11.9 | 0.33 | 0.45 | 50.6 |
| Approach | | 751 | 8.0 | 0.259 | 5.8 | LOS A | 1.6 | 11.9 | 0.32 | 0.47 | 50.3 |
| North: Victoria Street | | | | | | | | | | | |
| 8 | T | 162 | 8.0 | 0.114 | 5.2 | LOS A | 0.6 | 4.3 | 0.28 | 0.43 | 51.0 |
| 9 | R | 127 | 8.0 | 0.114 | 11.9 | LOS A | 0.6 | 4.3 | 0.28 | 0.66 | 45.6 |
| Approach | | 289 | 8.0 | 0.114 | 8.1 | LOS A | 0.6 | 4.3 | 0.28 | 0.53 | 48.4 |
| West: Cowpasture Road (west) | | | | | | | | | | | |
| 10 | L | 585 | 8.0 | 0.802 | 13.5 | LOS A | 8.9 | 66.8 | 0.86 | 1.09 | 43.8 |
| 12 | R | 118 | 8.0 | 0.802 | 19.1 | LOS B | 8.9 | 66.8 | 0.86 | 1.14 | 41.2 |
| Approach | | 703 | 8.0 | 0.802 | 14.4 | LOS A | 8.9 | 66.8 | 0.86 | 1.10 | 43.3 |
| All Vehicles | | 1743 | 8.0 | 0.802 | 9.7 | LOS A | 8.9 | 66.8 | 0.53 | 0.73 | 47.0 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model used.

Processed: Tuesday, 29 May 2012 3:50:03 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip
8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Victoria St & Cowpasture Rd
- FU PM

Victoria Street & Cowpasture Road
Roundabout

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|---------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: Cowpasture Road (south) | | | | | | | | | | | |
| 1 | L | 95 | 8.0 | 0.127 | 7.9 | LOS A | 0.8 | 6.0 | 0.59 | 0.63 | 48.2 |
| 2 | T | 177 | 8.0 | 0.127 | 7.0 | LOS A | 0.8 | 6.0 | 0.60 | 0.60 | 48.5 |
| Approach | | 272 | 8.0 | 0.127 | 7.3 | LOS A | 0.8 | 6.0 | 0.60 | 0.61 | 48.4 |
| North: Victoria Street | | | | | | | | | | | |
| 8 | T | 838 | 8.0 | 0.537 | 6.2 | LOS A | 3.8 | 28.7 | 0.52 | 0.54 | 49.0 |
| 9 | R | 467 | 8.0 | 0.537 | 12.9 | LOS A | 3.8 | 28.1 | 0.54 | 0.74 | 45.0 |
| Approach | | 1305 | 8.0 | 0.537 | 8.6 | LOS A | 3.8 | 28.7 | 0.53 | 0.61 | 47.5 |
| West: Cowpasture Road (west) | | | | | | | | | | | |
| 10 | L | 164 | 8.0 | 0.360 | 6.7 | LOS A | 2.1 | 15.5 | 0.42 | 0.54 | 48.9 |
| 12 | R | 229 | 8.0 | 0.360 | 12.3 | LOS A | 2.1 | 15.5 | 0.42 | 0.72 | 45.4 |
| Approach | | 394 | 8.0 | 0.360 | 10.0 | LOS A | 2.1 | 15.5 | 0.42 | 0.65 | 46.7 |
| All Vehicles | | 1971 | 8.0 | 0.537 | 8.7 | LOS A | 3.8 | 28.7 | 0.52 | 0.62 | 47.4 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: SIDRA Standard.

SIDRA Standard Delay Model used.

Processed: Tuesday, 29 May 2012 3:50:03 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip
8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd

www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Cowpasture Rd & Newton Dr
- FU PM

Cowpasture Road & Newton Road
Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time)

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|---------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: Cowpasture Road (south) | | | | | | | | | | | |
| 1 | L | 88 | 8.0 | 0.131 | 13.9 | LOS A | 1.7 | 12.9 | 0.21 | 0.77 | 43.9 |
| 2 | T | 218 | 8.0 | 0.131 | 5.4 | LOS A | 1.8 | 13.3 | 0.21 | 0.18 | 38.4 |
| 3 | R | 226 | 8.0 | 0.352 | 27.5 | LOS B | 6.8 | 50.9 | 0.55 | 0.74 | 30.2 |
| Approach | | 533 | 8.0 | 0.352 | 16.2 | LOS B | 6.8 | 50.9 | 0.36 | 0.51 | 34.3 |
| East: Newton Road | | | | | | | | | | | |
| 4 | L | 534 | 8.0 | 0.862 | 50.3 | LOS D | 32.6 | 244.2 | 0.98 | 0.96 | 22.7 |
| Approach | | 534 | 8.0 | 0.862 | 50.3 | LOS D | 32.6 | 244.2 | 0.98 | 0.96 | 22.7 |
| North: Cowpasture Road (north) | | | | | | | | | | | |
| 7 | L | 53 | 8.0 | 0.857 | 44.6 | LOS D | 36.3 | 271.9 | 0.96 | 0.99 | 25.0 |
| 8 | T | 1196 | 8.0 | 0.857 | 37.9 | LOS C | 36.5 | 272.9 | 0.96 | 0.95 | 25.1 |
| 9 | R | 9 | 8.0 | 0.130 | 71.4 | LOS F | 0.6 | 4.3 | 0.98 | 0.68 | 20.3 |
| Approach | | 1258 | 8.0 | 0.857 | 38.5 | LOS C | 36.5 | 272.9 | 0.96 | 0.95 | 25.1 |
| West: Site Access | | | | | | | | | | | |
| 10 | L | 237 | 8.0 | 0.574 | 48.6 | LOS D | 12.0 | 89.9 | 0.91 | 0.83 | 25.7 |
| Approach | | 237 | 8.0 | 0.574 | 48.6 | LOS D | 12.0 | 89.9 | 0.91 | 0.83 | 25.7 |
| All Vehicles | | 2561 | 8.0 | 0.862 | 37.2 | LOS C | 36.5 | 272.9 | 0.83 | 0.85 | 25.7 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

SIDRA Standard Delay Model used.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|---------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P3 | Across E approach | 11 | 19.8 | LOS B | 0.0 | 0.0 | 0.58 | 0.58 |
| P5 | Across N approach | 11 | 54.2 | LOS E | 0.0 | 0.0 | 0.95 | 0.95 |
| P7 | Across W approach | 11 | 19.8 | LOS B | 0.0 | 0.0 | 0.58 | 0.58 |
| All Pedestrians | | 33 | 31.3 | LOS D | | | 0.70 | 0.70 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)

Pedestrian movement LOS values are based on average delay per pedestrian movement.

Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

Processed: Tuesday, 29 May 2012 3:49:42 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip
8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd
www.sidrasolutions.com

SIDRA
INTERSECTION

MOVEMENT SUMMARY

Site: Cowpasture Rd & Newton Dr
- FU AM

Cowpasture Road & Newton Road
Signals - Fixed Time Cycle Time = 111 seconds (User-Given Cycle Time)

| Movement Performance - Vehicles | | | | | | | | | | | |
|---------------------------------|------|----------------------|---------|------------------|----------------------|------------------|--------------------------------------|------------------------|--------------|--------------------------------|-----------------------|
| Mov ID | Turn | Demand Flow veh/h | HV % | Deg. Satn v/c | Average Delay sec | Level of Service | 95% Back of Queue Vehicles veh | Queue Distance m | Prop. Queued | Effective Stop Rate per veh | Average Speed km/h |
| South: Cowpasture Road (south) | | | | | | | | | | | |
| 1 | L | 206 | 0.0 | 0.413 | 16.3 | LOS B | 8.0 | 58.3 | 0.35 | 0.82 | 41.8 |
| 2 | T | 723 | 8.0 | 0.413 | 8.1 | LOS A | 8.0 | 59.9 | 0.35 | 0.31 | 34.2 |
| 3 | R | 757 | 15.0 | 0.555 | 8.8 | LOS A | 4.3 | 33.7 | 0.18 | 0.66 | 41.6 |
| Approach | | 1686 | 10.2 | 0.555 | 9.4 | LOS A | 8.0 | 59.9 | 0.27 | 0.53 | 39.4 |
| East: Newton Road | | | | | | | | | | | |
| 4 | L | 273 | 8.0 | 0.239 | 10.0 | LOS A | 3.9 | 28.9 | 0.29 | 0.69 | 40.5 |
| Approach | | 273 | 8.0 | 0.239 | 10.0 | LOS A | 3.9 | 28.9 | 0.29 | 0.69 | 40.5 |
| North: Cowpasture Road (north) | | | | | | | | | | | |
| 7 | L | 75 | 8.0 | 0.789 | 65.5 | LOS E | 7.5 | 55.8 | 1.00 | 0.93 | 19.7 |
| 8 | T | 183 | 8.0 | 0.789 | 58.7 | LOS E | 7.7 | 57.4 | 1.00 | 0.93 | 19.9 |
| 9 | R | 22 | 0.0 | 0.266 | 66.8 | LOS E | 1.2 | 8.7 | 0.99 | 0.71 | 21.1 |
| Approach | | 280 | 7.4 | 0.789 | 61.2 | LOS E | 7.7 | 57.4 | 1.00 | 0.92 | 20.0 |
| West: Site Access | | | | | | | | | | | |
| 10 | L | 102 | 8.0 | 0.229 | 39.6 | LOS C | 4.1 | 31.0 | 0.79 | 0.78 | 28.8 |
| Approach | | 102 | 8.0 | 0.229 | 39.6 | LOS C | 4.1 | 31.0 | 0.79 | 0.78 | 28.8 |
| All Vehicles | | 2341 | 9.5 | 0.789 | 17.0 | LOS B | 8.0 | 59.9 | 0.38 | 0.61 | 34.1 |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Intersection and Approach LOS values are based on average delay for all vehicle movements.

SIDRA Standard Delay Model used.

| Movement Performance - Pedestrians | | | | | | | | |
|------------------------------------|-------------------|----------------------|----------------------|------------------|--|------------------------|--------------|--------------------------------|
| Mov ID | Description | Demand Flow ped/h | Average Delay sec | Level of Service | Average Back of Queue Pedestrian ped | Queue Distance m | Prop. Queued | Effective Stop Rate per ped |
| P3 | Across E approach | 11 | 49.7 | LOS E | 0.0 | 0.0 | 0.95 | 0.95 |
| P5 | Across N approach | 11 | 49.7 | LOS E | 0.0 | 0.0 | 0.95 | 0.95 |
| P7 | Across W approach | 11 | 49.7 | LOS E | 0.0 | 0.0 | 0.95 | 0.95 |
| All Pedestrians | | 33 | 49.7 | LOS E | | | 0.95 | 0.95 |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)

Pedestrian movement LOS values are based on average delay per pedestrian movement.

Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

Processed: Tuesday, 29 May 2012 3:49:41 PM

SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip
8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd
www.sidrasolutions.com

SIDRA
INTERSECTION




Appendix G



Cowpasture Road (north)

50



Site Access

Newton Road

120



Cowpasture Road (south)

PHASING SUMMARY


Site: Cowpasture Rd & Newton Dr
- FU AM

Cowpasture Road & Newton Road
Signals - Fixed Time Cycle Time = 111 seconds (User-Given Cycle Time)

Phase times determined by the program
Green Split Priority for Coordinated Movements applies
Sequence: Opposed Turns
Input Sequence: B1, B, A, A1
Output Sequence: B1, B, A, A1

Phase Timing Results

| Phase | B1 | B | A | A1 |
|--------------------|------|------|------|------|
| Green Time (sec) | 22 | 6 | 12 | 47 |
| Yellow Time (sec) | 3 | 3 | 3 | 3 |
| All-Red Time (sec) | 3 | 3 | 3 | 3 |
| Phase Time (sec) | 28 | 12 | 18 | 53 |
| Phase Split | 25 % | 11 % | 16 % | 48 % |



| | |
|---|---|
| █ Normal Movement | █ Permitted/Opposed |
| █ Slip-Lane Movement | █ Opposed Slip-Lane |
| █ Stopped Movement | █ Continuous Movement |
| █ Turn On Red | █ Undetected Movement |
| | ● Phase Transition Applied |

Processed: Tuesday, 29 May 2012 3:49:41 PM
SIDRA INTERSECTION 5.1.11.2079

Project: T:\Synergy\Projects\12\12.096\Modelling\Sidra\12 096ms01v4 TRAFFIX Final.sip
8000844, TRAFFIX, SINGLE

Copyright © 2000-2011 Akcelik and Associates Pty Ltd
www.sidrasolutions.com

SIDRA
INTERSECTION

PHASING SUMMARY


Site: Cowpasture Rd & Newton Dr
- FU PM

Cowpasture Road & Newton Road
Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time)

Phase times determined by the program
Green Split Priority for Coordinated Movements applies
Sequence: Opposed Turns
Input Sequence: B1, B, A, A1
Output Sequence: B1, B, A, A1

Phase Timing Results

| Phase | B1 | B | A | A1 |
|--------------------|------|------|------|------|
| Green Time (sec) | 22 | 6 | 57 | 11 |
| Yellow Time (sec) | 3 | 4 | 3 | 3 |
| All-Red Time (sec) | 3 | 2 | 3 | 3 |
| Phase Time (sec) | 28 | 12 | 63 | 17 |
| Phase Split | 23 % | 10 % | 53 % | 14 % |



| | |
|---|---|
| █ Normal Movement | █ Permitted/Opposed |
| █ Slip-Lane Movement | █ Opposed Slip-Lane |
| █ Stopped Movement | █ Continuous Movement |
| █ Turn On Red | █ Undetected Movement |
| | ● Phase Transition Applied |