



**GENERAL NOTES** ALL DIMENSIONS AND EXISITING CONDITIONS SHALL BE
CHECKED AND VERIFIED BY THE CONTRACTOR BEFORE PROCEEDING WITH THE WORK

 $\circ~$  DO NOT SCALE DRAWINGS. USE FIGURED DIMENSIONS ONLY

o all levels relative to 'Australian Height Datum'

LEGEND						
S	STUDIO					
1B	1 BED					
1BM	1 BED + MEDIA NOOK					
1BS	1 BED + STUDY					
2B	2 BED					
2BM	2 BED + MEDIA NOOK					
2BS	2 BED + STUDY					
2BK	2 BED DUAL KEY					
2BT	2 BED 2 STOREY TERRACE					
3B	3 BED					
3ВМ	3 BED + MEDIA NOOK					
3BS	3 BED + STUDY					
3ВК	3 BED DUAL KEY					
	RETAIL + NON-RESIDENTIAL					

### EXTERNAL AREA COURTYARD/BALCONY/WINTER-GARDEN

2 HOURS OF SUNLIGHT ACCESS NATURAL VENTILATION (NV)

CHILDCARE

WIDE FRONTAGE NATURALLY VENTILLATED ASSISTED VENTILATION

SOUTH FACING APARTMENT

# ADAPTABLE APARTMENT

## TURAL VENTILATION

Anodised aluminium Curtain Wall System with integrated operable windows (allow for euro style multifunction hardware) clip-on custom profiled extrusions

Anodised aluminium Window Wall System with integrated operable windows (allow for euro style multifunction hardware) and door systems (allow for 50/50 split between sliding and bi-fold functionality). Fenestration to facade system being anodised aluminium operable bifold perforated sunshade screens (allow for floor to floor coverage) Anodised aluminium Window Wall System with integrated operable window (allow for euro style multifunction hardware) and door systems (allow for 50/50 split between sliding and bi-fold functionality).

Terracotta cladding (allow for minimum 1200 wide module) Anodised aluminium sliding sunshade screen batten panels with battens at typically 100mm CC, 50mm SHS profile to framing and

Anodised aluminium Window Wall System with integrated operable windows (allow for euro style multifunction hardware) and door systems (allow for 50/50 split between sliding and bi-fold functionality). Profiled timber battens using "clip-on" fixing as noted in elevation.

Anodised aluminium Window Wall System with integrated operable windows (allow for panel lift type e.g. "Renlita") and door systems (allow for full height pivot functionality). Fenestration to facade system being profiled timber battens using "clip-on" fixing as noted in elevation. Full height timber batten screens

Brick Type 1 colour (earthy rust). Bowral pressed or similar. Final selection as per materials board.

Rendered Masonry with integrated anodised aluminium window systems

Balustrade, Frameless glazing with powder coated 8mm plate aluminium portal framing. Glazing is not captured all round Profiled anodised aluminium vertical batten using "clip-on" fixing as

Stainless steel Bollard

Stainless steel Bicycle Rail

DG1 Decomposed Granite Gravel

DG2 Decorative Gravel

HR2 LP1 P1 Lighting strip

P3

Paving Type 4 Exposed Aggregate Concrete path

Paving Type 5
Precast paving to traffic areas
Paving Type 6
Brick Paving

Brick base with a Timber capping Retaining wall

Brick base with a Precast concrete capping Retaining wall

Corten Steel Edging

Timber Bench Seats

Timber Composite vertical batten screen TD3

01 24/10/2014 ISSUED FOR SSDA APPROVAL FJMT BY REV. DATE DESCRIPTION Frasers Broadway



ARCHITECT

SYDNEY
Level 5, 70 King Street
Sydney NSW 2000 Australia
T +61 2 9251 7077
F +61 2 9251 7072 E fjmt@fjmt.com.au W www.fjmt.com.au NOMINATED ARCHITECT: RICHARD FRANCIS-JONES (REG NO 5301)

francis-jones morehen thorp PROJECT

Central Park Block 11 O'Connor Street, Chippendale Sydney Frasers Broadway

TITLE **PLANS Key Plans** 

SSD	<b>11-20</b> 0	01			
SHEET NO	O.	REVISION			
DATE	17/10/14	APPROVED	SB <sub>.</sub>	FB11	
SCALE	1:500 @ A1	DRAWN	FJMT	PROJECT CODE	

WHEN PRINTED AT 50% ON A3 THE SCALE IS 1:1000 **Issued for Approval**