

Check all dimensions and site conditions prior to commencement of any work, the purchase or ordering of any materials, fittings, plant, services or equipment and the preparation of shop drawings and/or the fabrication of any components.

All drawings to be read in conjunction with all architectural documents and all other consultants documents.

Do not scale drawings - refer to figured dimensions only. Any discrepancies shall immediately be referred to the architect for clarification.

All drawings may not be reproduced or distributed without prior permission from the architect.

Electrical & Communications
Riser Cupboard - all
residential levels.



Revision Summary:

NOT FOR CONSTRUCTION

01	29.08.14	For Information	JC	MLS
Revision	Date	Description	Initial	Checked

Site 68
Sydney Olympic Park

General Arrangement Plan
Level 17-24

Scale	1:100 @ A1, 1:200 @ A3
Drawn	Checked
Project No.	S11611
Status	DA
Plot Date	29/8/2014 6:23 PM
Plot File	S:\11600-11699\11611_escove_sopiste6800_main\cad\plots\DA... ... \DA02.17[01]x.dwg
Drawing No.	[Revision]

DA02.17[01]X

Melbourne 1 Nicholson Street
Melbourne VIC 3000 Australia
T 03 8664 6200 F 03 8664 6300
email melb@batessmart.com.au
http://www.batessmart.com.au

Sydney 43 Brisbane Street
Surry Hills NSW 2010 Australia
T 02 8354 5100 F 02 8354 5199
email syd@batessmart.com.au
http://www.batessmart.com.au


Bates Smart Architects Pty Ltd ABN 68 094 740 986

HARON ROBSON
lightmatters wattmatters avmatters

17 September 2014

BATESSMART

Electrical & Communications
Riser Cupboard - all
residential levels.



Check all dimensions and site conditions prior to commencement of any work, the purchase or ordering of any materials, fittings, plant, services or equipment and the preparation of shop drawings and/or the fabrication of any components.

All drawings to be read in conjunction with all architectural documents and all other consultants documents.

Do not scale drawings - refer to figured dimensions only. Any discrepancies shall immediately be referred to the architect for clarification.

All drawings may not be reproduced or distributed without prior permission from the architect.

Revision Summary:

NOT FOR CONSTRUCTION

04	29.08.14	For Coordination	ML	ML
03	12.08.14	For Coordination	ML	ML
02	29.07.14	For Coordination / Review	ML	ML
01	02.07.14	For Information	JC	MLS
Revision	Date	Description	Initial	Checked

Site 68
Sydney Olympic Park

General Arrangement Plan
Levels 25-26

Scale	1:100 @ A1, 1:200 @ A3
Drawn	Checked
Project No.	S11611
Status	DA
Plot Date	29/8/2014 6:16 PM
Plot File	\\lv-rp-01\shared\da\projects\11600-11699\11611_ecove_s... ...spsite68\00_main\cad\plots\DA\DA02.25[01]x.dwg
Drawing No.	[Revision]

DA02.25[01]X

Melbourne 1 Nicholson Street
Melbourne VIC 3000 Australia
T 03 8664 6200 F 03 8664 6300
email melb@batessmart.com.au
http://www.batessmart.com.au

Sydney 43 Brisbane Street
Surry Hills NSW 2010 Australia
T 02 8354 5100 F 02 8354 5199
email syd@batessmart.com.au
http://www.batessmart.com.au

Bates Smart Architects Pty Ltd ABN 68 094 740 986

HARON ROBSON
lightmatters wattmatters avmatters

17 September 2014

BATESSMART

Electrical & Communications
Riser Cupboard - all
residential levels.



Check all dimensions and site conditions prior to commencement of any work, the purchase or ordering of any materials, fittings, plant, services or equipment and the preparation of shop drawings and/or the fabrication of any components.

All drawings to be read in conjunction with all architectural documents and all other consultants documents.

Do not scale drawings - refer to figured dimensions only. Any discrepancies shall immediately be referred to the architect for clarification.

All drawings may not be reproduced or distributed without prior permission from the architect.

Revision Summary:

NOT FOR CONSTRUCTION

02	29.08.14	For Coordination	MLS	MLS
01	26.08.14	For Coordination	MLS	MLS
Revision	Date	Description	Initial	Checked

Site 68
Sydney Olympic Park

General Arrangement Plan
Levels 27-33

Scale	1:100 @ A1, 1:200 @ A3
Drawn	Checked
Project No.	S11611
Status	DA
Plot Date	29/8/2014 6:23 PM
Plot File	S:\11600-11699\s11611_escove_sopiste6800_main\cad\plots\DA... ... \DA02.27[X].dwg
Drawing No.	[Revision]

DA02.27[X]X

Melbourne 1 Nicholson Street
Melbourne VIC 3000 Australia
T 03 8664 6200 F 03 8664 6300
email melb@batessmart.com.au
http://www.batessmart.com.au

Sydney 43 Brisbane Street
Surry Hills NSW 2010 Australia
T 02 8354 5100 F 02 8354 5199
email syd@batessmart.com.au
http://www.batessmart.com.au


Bates Smart Architects Pty Ltd ABN 68 094 740 986

HARON ROBSON
lightmatters wattmatters avmatters

17 September 2014

BATESSMART

Electrical & Communications
Riser Cupboard - all
residential levels.



Check all dimensions and site conditions prior to commencement of any work, the purchase or ordering of any materials, fittings, plant, services or equipment and the preparation of shop drawings and/or the fabrication of any components.

All drawings to be read in conjunction with all architectural documents and all other consultants documents.

Do not scale drawings - refer to figured dimensions only. Any discrepancies shall immediately be referred to the architect for clarification.

All drawings may not be reproduced or distributed without prior permission from the architect.


Revision Summary:

NOT FOR CONSTRUCTION

01	xx.07.14	For Information	JC	MLS
Revision	Date	Description	Initial	Checked

Site 68
Sydney Olympic Park

General Arrangement Plan
Level 34



Scale	1:100 @ A1, 1:200 @ A3
Drawn	Checked
Project No.	S11611
Status	DA
Plot Date	29/8/2014 6:16 PM
Plot File	S:\11600-11699\s11611_escove_sopste6800_main\cad\plots\DA... ... \DA02.34[01]x.dwg
Drawing No.	[Revision]

DA02.34[01]X

Melbourne 1 Nicholson Street Melbourne VIC 3000 Australia T 03 8664 6200 F 03 8664 6300 email melb@batessmart.com.au http://www.batessmart.com.au	Sydney 43 Brisbane Street Surry Hills NSW 2010 Australia T 02 8354 5100 F 02 8354 5199 email syd@batessmart.com.au http://www.batessmart.com.au
--	--


Bates Smart Architects Pty Ltd ABN 68 094 740 986

HARON ROBSON
lightmatters wattmatters avmatters

17 September 2014

BATESSMART

REFERENCE DOCUMENT REGISTER		
DISCIPLINE	DRAWING No.	REVISION OR DATE
ARCH	DA92.2/101X	05.28.08.14
HYDRAULIC		
MECH		
INTERIOR DESIGN		
OTHER		



Typical Riser Detail 1:50

- NOTES :
1. Haron Robson is the owner of the copyright subsisting in these drawings and specifications which must not be reproduced or copied without prior written consent.
 2. Do not scale drawing. Verify all dimensions on site.

A	DA ISSUE	12-09-14
Amendments:		
Project:		
SOPA Site 68		

Architect:	BATES SMART
------------	-------------

Client:	Australia Avenue Developments
---------	-------------------------------

Consultants: Lighting, Electrical and Audio Visual
--



HARON ROBSON
light matters watt matters av matters

181 First Avenue Five Dock NSW 2048
PO Box 963 Five Dock NSW 2048
T +61 2 9712 5544
F +61 2 9712 5598

WE UNDERSTAND AUDIO VISUAL, LIGHTING, ENERGY AND ELECTRICAL SYSTEMS AND ADVISE ON THESE ISSUES WORLDWIDE.

Drawing Title:
ELECTRICAL SERVICES
Typical Electrcial Riser Detail

Date Printed: 12:28 12-09-14	Scale: 1:50	Sht Size: A3	Drawn: GR	Chkd:	Date:
Project No.: 14074	No. in Set/Drawing No.: SKE01		Issue: A		

2 GENERAL ARRANGEMENTS

2.1 Kiosk Types

This Network Standard refers to kiosk types J, L and K. These kiosks are for installation throughout Ausgrid's area, subject to the limitations indicated in Clause 2.2.

Refer to Network Standard NS117, for details of the equipment installed in these kiosks, including transformers, high voltage switchgear, distributors and electrical protection equipment.

These kiosks are completely assembled and delivered by the manufacturer to a previously prepared site. The manufacturer's representative will contact the Service Provider regarding access to the site and provision of a crane, if required.

2.2 Limitations on Usage, Siting and Installation of Kiosk Types

The following kiosk usage, siting and installation limitations apply:

- (a) J type kiosks must be installed as specified in Drawing 151573.
- (b) L type kiosks must be installed as specified in Drawing 151572.
- (c) K type kiosks must be installed as specified in Drawing 151190.
- (d) K type kiosks are not permitted on footpath sites.
- (e) Various other usage and siting limitations apply, as specified in Sections 3, 4, 5, 6 and Appendix A.

In addition, Network Standard NS109 *Design Standards for Overhead Developments* includes electrical supply limitations and limitations on usage of the various kiosk types.

2.3 Multiple Kiosks

In some cases, Ausgrid may approve installation of more than one kiosk at a premises. Where approval is given, each installation must comply with the requirements of this Network Standard. Each individual kiosk site must also comply with the site dimensions required in Appendix A and each kiosk must be positioned within its individual site so as to achieve the specified minimum clearances to its site boundary. Unless agreed otherwise by Ausgrid, the HV ends shall be located facing each other (where kiosks are positioned end-to-end), or at the same end (where kiosks are positioned side-by-side).

Where blast resisting barriers are necessary in accordance with the requirements of Section 6, or where the customer requires blast resisting barriers between or beside kiosks, the blast resisting barriers must be constructed in accordance with Section 6 of this Network Standard and must not encroach into the clearance space required around each kiosk.

AS/NZS 2229.2 – Fuel Dispensing Equipment for Explosive Atmospheres.

AS/NZS 2430 – Classification of Hazardous Areas.

Refer to Section 6 regarding fire segregation requirements including requirements relating to locations near gas meters/regulators.

It should be noted that in accordance with AS 2419.1:2005 – Fire Hydrant Installations – Part 1 System Design, Installation and Commissioning – external fire hydrants are required to be located in a position not less than 10m from any high voltage electrical distribution equipment such as transformers (kiosks) and distribution boards to avoid potential electrical hazards."

Kiosk substations must not be sited under overhead high voltage power lines of nominal voltage 22 kV or above. Kiosk substations should not be sited under overhead 11 kV power lines, unless there is no reasonable alternative. Kiosk substations must not be sited closer than 20 metres to a structure carrying 132 kV overhead power lines and where 132 kV overhead power lines are constructed along a public roadway, kiosk substations should not be located on the footpath on the same side.

Kiosk substations must not be sited on land owned or controlled by a rail authority, excepting where the kiosk site is approved by the rail authority and is required to provide supply for that authority or for installations approved by that authority. A kiosk substation sited on land owned or controlled by a rail authority must not be used for supply to an installation external to that land without Ausgrid's special approval and conditions, including special earthing arrangements.

For URD areas in particular, during the initial selection of kiosk sites at the subdivision stage, the likely future locations for swimming pools should be considered. For off-footpath sites, locations adjoining residential backyards or at corner allotments should be avoided.

All kiosk substation sites must comply with relevant Australian Standards and Standards Australia Handbooks including:

- SAA HB 100 – 2000 (CJC 4) Co-ordination of Power and Telecommunications: Manual for the establishment of safe work practices and the minimisation of operational interference between power systems and paired cable telecommunications systems.

Refer also to Network Standard NS116 *Design Standards for Distribution Earthing* for further information on clearance requirements from telecommunications pits and pillars.

3.2 Site Selection

Kiosk substation sites must also comply with the relevant requirements in the following sub-sections for off-street locations or footpath sites.

3.2.1 Off-Street Locations

The minimum site dimension requirements for the types of kiosk substations covered by this Network Standard are as indicated in Appendix A. (Attention is drawn to the Notes in Appendix A, which indicate restrictions on some of the siting options.)

The overall area of land required for the substation site includes sufficient area around the actual kiosk for personnel access, for cable routes, for installation of earthing electrodes and for hinged or removable doors to be opened or removed. The required substation site is therefore much larger than the actual kiosk enclosure footprint.

Refer to Clause 3.8 for details of site tenure requirements.

3.3 Site Plans and Site Preparation

3.3.1 General

In addition to the requirements of this Network Standard, kiosk substations must be installed in accordance with the relevant drawing:

- for J kiosk – drawing 151573
- for L kiosk – drawing 151572
- for K kiosk – drawing 151190.

For contestable work, the developer/customer is responsible for all substation site preparation to the satisfaction of Ausgrid and for all associated costs, including piers, retaining walls and excavation of rock for the kiosk base and cable entries.

Site plans or sketches of each individual substation site must be submitted for approval by Ausgrid, as part of the Design Certification process and before construction proceeds.

Site plans must show existing or proposed structures for a radius of 10 m from the kiosk, the street location name and the name of nearest cross street, the north point and the scale of the plan.

For J and L type kiosks, site contours must be such that the top of the kiosk base is not lower than 120 mm and not more than 240 mm above finished ground level. Refer to the relevant drawings indicated above for details and requirements for K type kiosks.

The kiosk site should not retain surface water and should not be in a location where sub-surface drainage will collect. If this is likely, it will be necessary for a sub-surface drainage system to be installed to the satisfaction of Ausgrid.

Unless specified otherwise by Ausgrid, kiosks installed on footpath sites should be oriented with the high voltage end facing the oncoming traffic i.e. such that the side door (HV connection / tap changer access) is on the property side of the kiosk - not on the road side.

3.3.2 Retaining Walls and Batter

Sites where retaining walls and/or batter would be required should be avoided unless there are no reasonable alternatives.

Where retaining walls and/or batter are necessary, they must comply with the following requirements:

- Retaining walls, including foundations and batter must be external to the minimum overall dimensions of the substation site.
- They must be constructed to the engineering requirements of the local council and the relevant Australian Standards (including AS 3798 and AS 4678). An Engineer's Certificate is to be supplied by the Service Provider on request.
- They must be suitably drained away from the site.
- They must be constructed of non-perishable material such as concrete or brick.
- Backfill must be compacted and be of suitable clean material free from large solid material over 50 mm in diameter.
- If a retaining wall is used, a handrail may also be required.
- In ground other than rock, the level at the top of the foundations for retaining walls must be at or below the level at the bottom of excavations for the installation of cables and / or conduits.

- for K kiosk – drawing 151190

The minimum depth for kiosk piers is the greater of:

- 1000 mm below the underside of the kiosk base level,
- 500 mm below the level of the ground that will be disturbed during excavation for installation of the cables,
- 500 mm below the bottom of any other service line (eg water, sewer, gas, telecommunications, stormwater) within 2000 mm of any one of the piers.

The maximum *length for kiosk piers complying with the design specifications in the above drawings shall not exceed 1500 mm. If it is necessary for piers to exceed 1500 mm in length to satisfy particular site conditions, as indicated below, a site specific design by a qualified structural engineer will be required.

(*length = depth of pier from underside of kiosk base)

Some kiosk site conditions may require pier design to exceed the minimum specifications indicated in the drawings and pier length to exceed 1500 mm. Examples include terraced sites or sites cut into sloping ground, or sites near other large services, such as large water, stormwater or sewer mains. The Service Provider is responsible for ensuring that pier foundations are stable and adequate and for engaging a qualified structural engineer to design pier foundations where necessary. A structural engineer's report may be required in such cases.

Where pier foundations are installed for J, L and K type kiosks, the area around the piers must be backfilled after installation of the piers with sand and compacted to remove voids under the area where the kiosk base will be installed. Excavations under and around the kiosk base for cable installations must also be backfilled with sand and compacted to remove voids.

The kiosk piers must be allowed at least seven days for the concrete to cure before the kiosk base is installed on the piers and before cables are installed in the kiosk base footprint area.

After completion of the installation, the area around the kiosk must be backfilled, compacted and restored to the finished surrounding site level.

3.5 Avoiding Services and Encroachments

For off-street locations, services such as drains, sewers, pipes and wiring, must not pass through or under the kiosk substation overall site area. For exact dimensions, refer to minimum site requirements in Appendix A and the drawings indicated in Clause 3.3.1. Refer also to the above drawings for the range of acceptable entry angles for consumers' mains at the kiosk.

For footpath sites it is generally not possible to have a site, the size of a standard kiosk easement, which is clear of other services. Therefore, instead of the arrangements discussed above, the following requirements shall apply which are in addition to the requirements outlined in Clause 3.2.2:

- there should be no other services directly beneath the footprint of the kiosk,
- there should be sufficient space around the kiosk to allow cables to be connected to the kiosk without encroaching on minimum separations to other services. Minimum separations are generally as follows, however in each case these should be confirmed with the other Utility/Service Providers in accordance with the NSW Streets Opening Conference Guide to Codes and Practices for Streets Opening:
 - Gas pipes \leq 75mm: 150mm minimum to LV cables, 300mm minimum to HV cables