

Check all dimensions and site conditions prior to commencement of any work, the purchase or ordering of any materials, fittings, plant, services or equipment and the preparation of shop drawings and/or the fabrication of any components.

All drawings to be read in conjunction with all architectural documents and all other consultants documents.

Do not scale drawings - refer to figured dimensions only. Any discrepancies shall immediately be referred to the architect for clarification.

All drawings may not be reproduced or distributed without prior permission from the architect.

Construction general

Glazing	Doors / windows: Aluminium framed single clear glazing to internal windows that open to balconies U-Value: 6.57 (equal to or lower than) SHGC: 0.74 (+ or - 10%)
	Aluminium framed double clear glazing to curtain walls & glazing to balcony edge. U-Value: 4.11 (equal to or lower than) SHGC: 0.58 (+ or - 10%)
	Given values are NFRC, total window values
Roof / ceiling Insulation	Roof: Concrete roof - No insulation No colour nominated
	Ceiling: Plasterboard ceiling - R2.0 bulk insulation to all units to top floor, balconies above & slot areas above
	Note: It has been assumed at DA stage that the area of all ceiling penetrations is less than 0.5% of the total ceiling area. If down lights are proposed at a later stage, BCA loss of insulation calculations will be required.
Wall / floor insulation	External Wall: Lightweight cladding to all external walls with R1.5 bulk insulation No colour nominated
	Internal walls within units: Plasterboard on studs - no insulation
	Inter-tenancy walls / corridor: 75mm hebel power panel plasterboard lined with R1.5 acoustic insulation
	Floors: Concrete - R2.0 Insulation to areas of open floor
	Floor coverings: Tiles to wets areas, carpet to bedrooms and living areas as per plans
Central hot water system	Central gas-fired boiler with R0.6 (~25mm) insulation to ringmain and supply risers.
Reticulated alternative water	Alternative water supply available from Sydney Olympic Park Authority to be used for the irrigation of all landscaping & all toilets within the building (No rainwater tank required for BASIX compliance)

Revision Summary:

NOT FOR CONSTRUCTION

Revision	Date	Description	Initial	Checked
01	02.07.14	For Information	JC	MLS
02	29.07.14	For Coordination / Review	ML	ML
03	12.08.14	For Coordination	ML	ML
04	29.08.14	For Coordination	ML	ML
05	19.09.14	Development Application	KM	MLS

Site 68 Sydney Olympic Park

General Arrangement Plan Levels 25-26



Scale	1:100 @ A1, 1:200 @A3	
Drawn	Checked	
Project No.	S11611	
Status	DA	
Plot Date	19/9/2014 11:08 AM	
Plot File	\\liv-vfp-01\sitedata\$\LIV\projects\11600-11699\s11611_ecove_s opsite68\00 main\cad\plots\DA\DA02.25[05].dwg	
Drawing No.	[Revision]	

DA02.25[05]

Melbourne 1 Nicholson Street
Melbourne VIC 3000 Australia
T 03 8664 6200 F 03 8664 6300
email melb@batessmart.com.au
http://www.batessmart.com.auSydney 43 Brisbane Street
Surry Hills NSW 2010 Australia
T 02 8354 5100 F 02 8354 5199
email syd@batessmart.com.au
http://www.batessmart.com.au

Bates Smart Architects Pty Ltd ABN 68 094 740 986

