

Check all dimensions and site conditions prior to commencement of any work, the purchase or ordering of any materials, fittings, plant, services or equipment and the preparation of shop drawings and or the fabrication of any components.

Do not scale drawings - refer to figured dimensions only. Any discrepancies shall immediately be referred to the architect for clarification.

All drawings may not be reproduced or distributed without prior permission from the architect.

Notes - Construction General (BASIX)

Glazing

Doors / windows:

- Aluminium framed **single clear** glazing to internal windows that open to wintergardens
U-Value: 6.6 (equal to or lower than)
SHGC: 0.69 (+ or - 10%)

- Aluminium framed **double clear** glazing to curtain walls & glazing to balcony edge.
U-Value: 4.4 (equal to or lower than)
SHGC: 0.5 (+ or - 10%)

Given values are NFRC, total window values

Roof / ceiling insulation

Roof:
Concrete roof - No insulation

Default Colour modelled

Ceiling:

Plasterboard ceiling - R3.0 bulk insulation to selected units (34.01 and 34.07) with balconies above.

Plasterboard ceiling - R2.0 bulk insulation to all units to top floor, balconies above & slot areas above to all other units.

Note: It has been assumed at DA stage that the area of all ceiling penetrations is less than 0.5% of the total ceiling area. If down lights are proposed at a later stage, BCA loss of insulation calculations will be required.

Wall / floor insulation

External Wall:

Lightweight cladding to all external walls with R1.5 bulk insulation
No colour nominated

Internal walls within units:

Plasterboard on studs - no insulation

Inter-tenancy walls / corridor:

75mm hebel power panel plasterboard lined with R2.0 acoustic insulation to **selected units only (7.01 and 8.01)**

75mm hebel power panel plasterboard lined with R1.5 acoustic insulation to all other units.

Floors:

Concrete - R2.1 insulation to all units in level 7 with car park below
Concrete - no insulation required between units

Floor coverings:

1 & 2 bed apartments - tiles to wet areas, carpet to bedrooms and living areas as per plans
All 3 & 4 bed apartments tiled throughout

Central hot water system

Central gas-fired boiler with R1.0 (~38mm) insulation to ringmain and supply risers.

Reticulated alternative water

Alternative water supply available from Sydney Olympic Park Authority to be used for the irrigation of all landscaping & all toilets within the building
(No rainwater tank required for BASIX compliance)

Alternative energy

Not required by BASIX

B	20.07.16	Amended DA Issue	JS	CP
A	01.03.16	Development Application	JS	CP
Revision	Date	Description	Initial	Checked

Client: Ecove



ecove

Site 9, Sydney Olympic Park 3 Olympic Boulevard

General Arrangement Plan Level 10, 12, 14



Status	Development Application		
Scale	1 : 100	@	A1
Drawn	Author	Checked	Checker
Project No.	S11890		
Plot Date	20/07/2016 2:59:51 PM		
Plot File			

Drawing no.	Revision
DA02.010	B

Melbourne 1 Nicholson Street
Melbourne VIC 3000 Australia
T 03 8664 6200 F 03 8664 6300
email: mel@batesmart.com.au
http://www.batesmart.com.au

Sydney 43 Brisbane Street
Surry Hills NSW 2010 Australia
T 02 8354 5100 F 02 8354 5199
email: syd@batesmart.com.au
http://www.batesmart.com.au

Bates Smart Pty Ltd ABN 70 004 999 400

BATESSMART



Check all dimensions and site conditions prior to commencement of any work, the purchase or ordering of any materials, fittings, plant, services or equipment and the preparation of shop drawings and or the fabrication of any components.

Do not scale drawings - refer to figured dimensions only. Any discrepancies shall immediately be referred to the architect for clarification.

All drawings may not be reproduced or distributed without prior permission from the architect.

Notes - Construction General (BASIX)

Glazing

Doors / windows:

- Aluminium framed **single clear** glazing to internal windows that open to wintergardens
U-Value: 6.6 (equal to or lower than)
SHGC: 0.69 (+ or - 10%)

- Aluminium framed **double clear** glazing to curtain walls & glazing to balcony edge.
U-Value: 4.4 (equal to or lower than)
SHGC: 0.5 (+ or - 10%)

Given values are NFRC, total window values

Roof / ceiling insulation

Roof:
Concrete roof - No insulation

Default Colour modelled

Ceiling:

Plasterboard ceiling - R3.0 bulk insulation to selected units (34.01 and 34.07) with balconies above.

Plasterboard ceiling - R2.0 bulk insulation to all units to top floor, balconies above & slot areas above to all other units.

Note: It has been assumed at DA stage that the area of all ceiling penetrations is less than 0.5% of the total ceiling area. If down lights are proposed at a later stage, BCA loss of insulation calculations will be required.

Wall / floor insulation

External Wall:

Lightweight cladding to all external walls with R1.5 bulk insulation
No colour nominated

Internal walls within units:

Plasterboard on studs - no insulation

Inter-tenancy walls / corridor:

75mm hebel power panel plasterboard lined with R2.0 acoustic insulation to **selected units only (7.01 and 8.01)**

75mm hebel power panel plasterboard lined with R1.5 acoustic insulation to all other units.

Floors:

Concrete - R2.1 insulation to all units in level 7 with car park below

Concrete - no insulation required between units

Floor coverings:

1 & 2 bed apartments - tiles to wet areas, carpet to bedrooms and living areas as per plans

All 3 & 4 bed apartments tiled throughout

Central hot water system

Central gas-fired boiler with R1.0 (~38mm) insulation to ringmain and supply risers.

Reticulated alternative water

Alternative water supply available from Sydney Olympic Park Authority to be used for the irrigation of all landscaping & all toilets within the building
(No rainwater tank required for BASIX compliance)

Alternative energy

Not required by BASIX

B	20.07.16	Amended DA Issue	JS	CP
A	01.03.16	Development Application	JS	CP
Revision	Date	Description	Initial	Checked

Client: Ecove



ecove

Site 9, Sydney Olympic Park 3 Olympic Boulevard

General Arrangement Plan Level 11, 13



Status	Development Application		
Scale	1 : 100	@ A1	
Drawn	Author	Checked	Checker
Project No.	S11890		
Plot Date	20/07/2016 3:00:12 PM		
Plot File			

Drawing no.	Revision
DA02.011	B

Melbourne 1 Nicholson Street
Melbourne VIC 3000 Australia
T 03 8664 6200 F 03 8664 6300
email: mel@batesmart.com.au
http://www.batesmart.com.au

Sydney 43 Brisbane Street
Surry Hills NSW 2010 Australia
T 02 8354 5100 F 02 8354 5199
email: syd@batesmart.com.au
http://www.batesmart.com.au

Bates Smart Pty Ltd ABN 70 004 999 400

BATESSMART



Check all dimensions and site conditions prior to commencement of any work, the purchase or ordering of any materials, fittings, plant, services or equipment and the preparation of shop drawings and or the fabrication of any components.

Do not scale drawings - refer to figured dimensions only. Any discrepancies shall immediately be referred to the architect for clarification.

All drawings may not be reproduced or distributed without prior permission from the architect.

Notes - Construction General (BASIX)

Glazing

Doors / windows:

- Aluminium framed **single clear** glazing to internal windows that open to wintergardens
U-Value: 6.6 (equal to or lower than)
SHGC: 0.69 (+ or - 10%)

- Aluminium framed **double clear** glazing to curtain walls & glazing to balcony edge.
U-Value: 4.4 (equal to or lower than)
SHGC: 0.5 (+ or - 10%)

Given values are NFRC, total window values

Roof / ceiling insulation

Roof:
Concrete roof - No insulation

Default Colour modelled

Ceiling:

Plasterboard ceiling - R3.0 bulk insulation to selected units (34.01 and 34.07) with balconies above.

Plasterboard ceiling - R2.0 bulk insulation to all units to top floor, balconies above & slot areas above to all other units.

Note: It has been assumed at DA stage that the area of all ceiling penetrations is less than 0.5% of the total ceiling area. If down lights are proposed at a later stage, BCA loss of insulation calculations will be required.

Wall / floor insulation

External Wall:

Lightweight cladding to all external walls with R1.5 bulk insulation
No colour nominated

Internal walls within units:

Plasterboard on studs - no insulation

Inter-tenancy walls / corridor:

75mm hebel power panel plasterboard lined with R2.0 acoustic insulation to **selected units only (7.01 and 8.01)**

75mm hebel power panel plasterboard lined with R1.5 acoustic insulation to all other units.

Floors:

Concrete - R2.1 insulation to all units in level 7 with car park below

Concrete - no insulation required between units

Floor coverings:

1 & 2 bed apartments - tiles to wet areas, carpet to bedrooms and living areas as per plans

All 3 & 4 bed apartments tiled throughout

Central hot water system

Central gas-fired boiler with R1.0 (~38mm) insulation to ringmain and supply risers.

Reticulated alternative water

Alternative water supply available from Sydney Olympic Park Authority to be used for the irrigation of all landscaping & all toilets within the building
(No rainwater tank required for BASIX compliance)

Alternative energy

Not required by BASIX


B	20.07.16	Amended DA Issue	JS	CP
A	01.03.16	Development Application	JS	CP
Revision	Date	Description	Initial	Checked

Client: Ecove



Site 9, Sydney Olympic Park 3 Olympic Boulevard

General Arrangement Plan Level 15, 17, 19



Status	Development Application		
Scale	1 : 100	@ A1	
Drawn	Author	Checked	Checker
Project No.	S11890		
Plot Date	20/07/2016 3:00:33 PM		
Plot File			


Drawing no.	Revision
DA02.015	B

Melbourne 1 Nicholson Street
Melbourne VIC 3000 Australia
T 03 8664 6200 F 03 8664 6300
email: mel@batesmart.com.au
http://www.batesmart.com.au

Sydney 43 Brisbane Street
Surry Hills NSW 2010 Australia
T 02 8354 5100 F 02 8354 5199
email: syd@batesmart.com.au
http://www.batesmart.com.au

Bates Smart Pty Ltd ABN 70 004 999 400

BATESSMART™



All drawings may not be reproduced or distributed without prior permission from the architect.

Alternative energy
Not required by BASIX

100



All drawings may not be reproduced or distributed without prior permission from the architect.

Alternative energy
Not required by BASIX



Bates Smart Pty Ltd ABN 70 004 999 400

Check all dimensions and site conditions prior to commencement of any work, the purchase or ordering of any materials, fittings, plant, services or equipment and the preparation of shop drawings and or the fabrication of any components.

Do not scale drawings - refer to figured dimensions only. Any discrepancies shall immediately be referred to the architect for clarification.

All drawings may not be reproduced or distributed without prior permission from the architect.

Notes - Construction General (BASIX)

Glazing

Doors / windows:

- Aluminium framed **single clear** glazing to internal windows that open to wintergardens
U-Value: 6.6 (equal to or lower than)
SHGC: 0.69 (+ or - 10%)

- Aluminium framed **double clear** glazing to curtain walls & glazing to balcony edge.
U-Value: 4.4 (equal to or lower than)
SHGC: 0.5 (+ or - 10%)

Given values are NFRC, total window values

Roof / ceiling insulation

Roof:
Concrete roof - No insulation

Default Colour modelled

Ceiling:

Plasterboard ceiling - R3.0 bulk insulation to selected units (34.01 and 34.07) with balconies above.

Plasterboard ceiling - R2.0 bulk insulation to all units to top floor, balconies above & slot areas above to all other units.

Note: It has been assumed at DA stage that the area of all ceiling penetrations is less than 0.5% of the total ceiling area. If down lights are proposed at a later stage, BCA loss of insulation calculations will be required.

Wall / floor insulation

External Wall:

Lightweight cladding to all external walls with R1.5 bulk insulation
No colour nominated

Internal walls within units:

Plasterboard on studs - no insulation

Inter-tenancy walls / corridor:

75mm hebel power panel plasterboard lined with R2.0 acoustic insulation to **selected units only (7.01 and 8.01)**

75mm hebel power panel plasterboard lined with R1.5 acoustic insulation to all other units.

Floors:

Concrete - R2.1 insulation to all units in level 7 with car park below

Concrete - no insulation required between units

Floor coverings:

1 & 2 bed apartments - tiles to wet areas, carpet to bedrooms and living areas as per plans

All 3 & 4 bed apartments tiled throughout

Central hot water system

Central gas-fired boiler with R1.0 (~38mm) insulation to ringmain and supply risers.

Reticulated alternative water

Alternative water supply available from Sydney Olympic Park Authority to be used for the irrigation of all landscaping & all toilets within the building

(No rainwater tank required for BASIX compliance)

Alternative energy

Not required by BASIX


B	20.07.16	Amended DA Issue	JS	CP
A	01.03.16	Development Application	JS	CP
Revision	Date	Description	Initial	Checked

Client: Ecove



Site 9, Sydney Olympic Park 3 Olympic Boulevard

General Arrangement Plan Level 21, 23, 25



Status	Development Application		
Scale	1 : 100	@ A1	
Drawn	Author	Checked	Checker
Project No.	S11890		
Plot Date	20/07/2016 3:01:39 PM		
Plot File			

Drawing no.	Revision
DA02.021	B

Melbourne 1 Nicholson Street
Melbourne VIC 3000 Australia
T 03 8664 6200 F 03 8664 6300
email: mel@batesmart.com.au
http://www.batesmart.com.au

Sydney 43 Brisbane Street
Surry Hills NSW 2010 Australia
T 02 8354 5100 F 02 8354 5199
email: syd@batesmart.com.au
http://www.batesmart.com.au

Bates Smart Pty Ltd ABN 70 004 999 400

BATESSMART



All drawings may not be reproduced or distributed without prior permission from the architect.

Alternative energy
Not required by BASIX

Client: Ecove



All drawings may not be reproduced or distributed without prior permission from the architect.

Alternative energy
Not required by BASIX




General Arrangement Plan
Level 28, 30, 32, 34

Drawing no.	Revision
DA02.028	B

Bates Smart Pty Ltd ABN 70 004 999 400

BATESSMART™



Check all dimensions and site conditions prior to commencement of any work, the purchase or ordering of any materials, fittings, plant, services or equipment and the preparation of shop drawings and or the fabrication of any components.

Do not scale drawings - refer to figured dimensions only. Any discrepancies shall immediately be referred to the architect for clarification.

All drawings may not be reproduced or distributed without prior permission from the architect.

Notes - Construction General (BASIX)

Glazing

Doors / windows:

- Aluminium framed **single clear** glazing to internal windows that open to wintergardens
U-Value: 6.6 (equal to or lower than)
SHGC: 0.69 (+ or - 10%)

- Aluminium framed **double clear** glazing to curtain walls & glazing to balcony edge.
U-Value: 4.4 (equal to or lower than)
SHGC: 0.5 (+ or - 10%)

Given values are NFRC, total window values

Roof / ceiling insulation

Roof:
Concrete roof - No insulation

Default Colour modelled

Ceiling:

Plasterboard ceiling - R3.0 bulk insulation to selected units (34.01 and 34.07) with balconies above.

Plasterboard ceiling - R2.0 bulk insulation to all units to top floor, balconies above & slot areas above to all other units.

Note: It has been assumed at DA stage that the area of all ceiling penetrations is less than 0.5% of the total ceiling area. If down lights are proposed at a later stage, BCA loss of insulation calculations will be required.

Wall / floor insulation

External Wall:

Lightweight cladding to all external walls with R1.5 bulk insulation
No colour nominated

Internal walls within units:

Plasterboard on studs - no insulation

Inter-tenancy walls / corridor:

75mm hebel power panel plasterboard lined with R2.0 acoustic insulation to **selected units only (7.01 and 8.01)**

75mm hebel power panel plasterboard lined with R1.5 acoustic insulation to all other units.

Floors:

Concrete - R2.1 insulation to all units in level 7 with car park below

Concrete - no insulation required between units

Floor coverings:

1 & 2 bed apartments - tiles to wet areas, carpet to bedrooms and living areas as per plans

All 3 & 4 bed apartments tiled throughout

Central hot water system

Central gas-fired boiler with R1.0 (~38mm) insulation to ringmain and supply risers.

Reticulated alternative water

Alternative water supply available from Sydney Olympic Park Authority to be used for the irrigation of all landscaping & all toilets within the building

(No rainwater tank required for BASIX compliance)

Alternative energy

Not required by BASIX


B	20.07.16	Amended DA Issue	JS	CP
A	01.03.16	Development Application	JS	CP
Revision	Date	Description	Initial	Checked

Client: Ecove



Site 9, Sydney Olympic Park
3 Olympic Boulevard

General Arrangement Plan
Level 36-37



Status	Development Application		
Scale	1 : 100	@ A1	
Drawn	Author	Checked	Checker
Project No.	S11890		
Plot Date	20/07/2016 3:02:40 PM		
Plot File			


Drawing no.	Revision
DA02.036	B

Melbourne 1 Nicholson Street
Melbourne VIC 3000 Australia
T 03 8664 6200 F 03 8664 6300
email: mel@batesmart.com.au
http://www.batesmart.com.au

Sydney 43 Brisbane Street
Surry Hills NSW 2010 Australia
T 02 8354 5100 F 02 8354 5199
email: syd@batesmart.com.au
http://www.batesmart.com.au

Bates Smart Pty Ltd ABN 70 004 999 400

BATESSMART





Check all dimensions and site conditions prior to commencement of any work, the purchase or ordering of any materials, fittings, plant, services or equipment and the preparation of shop drawings and or the fabrication of any components.

Do not scale drawings - refer to figured dimensions only. Any discrepancies shall immediately be referred to the architect for clarification.

All drawings may not be reproduced or distributed without prior permission from the architect.

Notes - Construction General (BASIX)

Glazing

Doors / windows:

- Aluminium framed **single clear** glazing to internal windows that open to wintergardens
U-Value: 6.6 (equal to or lower than)
SHGC: 0.69 (+ or - 10%)

- Aluminium framed **double clear** glazing to curtain walls & glazing to balcony edge.
U-Value: 4.4 (equal to or lower than)
SHGC: 0.5 (+ or - 10%)

Given values are NFRC, total window values

Roof / ceiling insulation

Roof:
Concrete roof - No insulation

Default Colour modelled

Ceiling:

Plasterboard ceiling - R3.0 bulk insulation to selected units (34.01 and 34.07) with balconies above.

Plasterboard ceiling - R2.0 bulk insulation to all units to top floor, balconies above & slot areas above to all other units.

Note: It has been assumed at DA stage that the area of all ceiling penetrations is less than 0.5% of the total ceiling area. If down lights are proposed at a later stage, BCA loss of insulation calculations will be required.

Wall / floor insulation

External Wall:

Lightweight cladding to all external walls with R1.5 bulk insulation
No colour nominated

Internal walls within units:

Plasterboard on studs - no insulation

Inter-tenancy walls / corridor:

75mm hebel power panel plasterboard lined with R2.0 acoustic insulation to **selected units only (7.01 and 8.01)**

75mm hebel power panel plasterboard lined with R1.5 acoustic insulation to all other units.

Floors:

Concrete - R2.1 insulation to all units in level 7 with car park below
Concrete - no insulation required between units

Floor coverings:

1 & 2 bed apartments - tiles to wets areas, carpet to bedrooms and living areas as per plans
All 3 & 4 bed apartments tiled throughout

Central hot water system

Central gas-fired boiler with R1.0 (~38mm) insulation to ringmain and supply risers.

Reticulated alternative water

Alternative water supply available from Sydney Olympic Park Authority to be used for the irrigation of all landscaping & all toilets within the building
(No rainwater tank required for BASIX compliance)

Alternative energy

Not required by BASIX


B	20.07.16	Amended DA Issue	JS	CP
A	01.03.16	Development Application	JS	CP
Revision	Date	Description	Initial	Checked

Client: Ecove



Site 9, Sydney Olympic Park
3 Olympic Boulevard

General Arrangement Plan
Level 38



Status	Development Application		
Scale	1 : 100	@	A1
Drawn	Author	Checked	Checker
Project No.	S11890		
Plot Date	20/07/2016 4:17:59 PM		
Plot File			

Drawing no.	Revision
DA02.038	B

Melbourne 1 Nicholson Street
Melbourne VIC 3000 Australia
T 03 8664 6200 F 03 8664 6300
email: mel@batesmart.com.au
http://www.batesmart.com.au

Sydney 43 Brisbane Street
Surry Hills NSW 2010 Australia
T 02 8354 5100 F 02 8354 5199
email: syd@batesmart.com.au
http://www.batesmart.com.au

Bates Smart Pty Ltd ABN 70 004 999 400

BATESSMART