



SUITE 17, 808 FOREST ROAD, PEAKHURST 2210 ABN 73 107 291 494  
P 02 9046 3800 ACOUSTICS@DAYDESIGN.COM.AU WWW.DAYDESIGN.COM.AU

# Environmental Noise Assessment

Redevelopment of Wentworthville Public School  
70 – 100 Fullagar Road, Wentworthville, NSW

REPORT NUMBER  
**6396-1.1R Rev A**

DATE ISSUED  
**13 November 2018**

**Prepared For:**  
Fulton Trotter Architects  
PO Box 1669  
Bondi Junction NSW 1355

Attention: Mr John Kennedy



## Revision History

Status	Date	Prepared	Checked	Comment
Draft	24/01/2018	Adam Shearer	Stephen Gauld	By email, for client review
Draft 2	03/09/2018	Adam Shearer	Stephen Gauld	SEARS
Final	09/10/2018	Adam Shearer	Stephen Gauld	
Rev A	13/11/2018	Adam Shearer	Stephen Gauld	

Document 6396-1.1R Rev A, 24 pages plus attachments

## Disclaimer

The work presented in this document was carried out in accordance with the Day Design Pty Ltd Quality Management System. Day Design is certified to ISO9001.

Day Design Pty Ltd reserves all copyright of intellectual property in any or all of Day Design's documents. No permission, license or authority is granted by Day Design to any person or organisation to use any of Day Design's documents for any purpose without written consent of Day Design.

This report has been prepared for the client identified in Section 1.0 only and cannot be relied or used by any third party. Any representation, statement, opinion or advice, expressed or implied in this report is made in good faith but on the basis that Day Design is not liable (whether by reason of negligence, lack of care or otherwise) to any person for any damage or loss whatsoever which has occurred or may occur in relation to that person taking or not taking (as the case may be) action in any respect of any representation, statement, or advice referred to above.

Recommendations made in this report are intended to resolve acoustical problems only. No claims of expertise in other areas are made and no liability is accepted in respect of design or construction for issues falling outside the specialist field of acoustical engineering including but not limited to structural, fire, thermal, architectural buildability, fit for purpose, waterproofing or other aspects of building construction. Supplementary professional advice should be sought in respect of these issues.

The information in this document should not be reproduced, presented or reviewed except in full. Prior to passing onto a third party, the Client is to fully inform the third party of the specific brief and limitations associated with the commission. The only exception to this is for the Regulatory Authority in its use of this report to make a Determination.



## TABLE OF CONTENTS

1.0	CONSULTING BRIEF .....	5
2.0	PROJECT DESCRIPTION & SUMMARY OF FINDINGS.....	6
3.0	ACOUSTIC CRITERIA .....	9
3.1	Measured Ambient Noise Levels.....	9
3.2	NSW Department of Planning and Environment .....	10
3.2.1	SEPP (Educational Establishments and Child Care Facilities) 2017 .....	10
3.2.2	SEPP (Infrastructure) 2007 .....	10
3.2.2.1	SEPP Clause 87 (Rail) .....	10
3.2.2.2	SEPP Clause 102 (Road) .....	11
3.3	NSW Environment Protection Authority – Noise Policy for Industry .....	11
3.3.1	Intrusiveness Criteria.....	11
3.3.2	Amenity Criteria.....	12
3.4	AAAC Noise Criteria for Outdoor Play Areas.....	14
3.5	Project Specific Noise Criteria.....	14
4.0	SCHOOL NOISE EMISSION.....	15
4.1	Outdoor Play Areas .....	15
4.2	General Learning Areas.....	16
4.3	Public Address System & School Bell .....	16
4.4	Mechanical Plant.....	17
4.5	Hall Usage .....	17
4.6	Predicted Noise Level at Receptor Locations .....	19
4.6.1	Outdoor Play Areas .....	19
4.6.2	Cumulative Noise Level – Home Bases & Mechanical Plant.....	20
4.6.3	School Hall .....	21
5.0	NOISE CONTROL RECOMMENDATIONS .....	22
5.1	Construction Certificate / Detailed Design .....	22
5.1.1	Mechanical Plant .....	22
5.1.2	Use of School Hall.....	22
5.2	Air Conditioning Condenser Unit Plant Areas – Ground Floor .....	23
6.0	NOISE IMPACT STATEMENT .....	24



## TABLES

Table 1	Noise Sensitive Receptors.....	6
Table 2	Ambient Noise Levels.....	9
Table 3	Amenity Criteria.....	12
Table 4	$L_{eq, 15 \text{ minute}}$ Sound Power Levels - Children Playing in Outdoor Play Areas.....	15
Table 5	$L_{eq, 15 \text{ minute}}$ Sound Power Levels – Teacher & Students – GLAs.....	16
Table 6	$L_{eq, 15 \text{ minute}}$ Sound Power Levels - Mechanical Plant.....	17
Table 7	$L_{eq, 15 \text{ minute}}$ Sound Power Levels - Proposed Hall.....	18
Table 8	Predicted $L_{eq, 15 \text{ minute}}$ Noise Levels – Outdoor Play.....	19
Table 9	Predicted Cumulative $L_{eq, 15 \text{ minute}}$ Noise Levels – Home Bases & Mechanical Plant.....	20
Table 10	Predicted $L_{eq, 15 \text{ minute}}$ Noise Levels – Hall.....	21



## 1.0 CONSULTING BRIEF

Day Design Pty Ltd was engaged by Fulton Trotter Architects to carry out an acoustic assessment of the proposed redevelopment of the Wentworthville Public School at 70-100 Fullagar Road, Wentworthville, NSW. This commission involves the following:

### Scope of Work:

- Inspect the site and environs
- Measure the background noise levels at critical locations and times
- Establish acceptable noise level criteria
- Quantify noise emissions from the School taking into consideration the proposed redevelopment
- Calculate the level of noise emission, taking into account building envelope transmission, screen walls and distance attenuation
- Prepare a site plan identifying the development and nearby noise sensitive locations
- Provide recommendations for acoustical treatment (if necessary)
- Prepare an Environmental Noise Assessment Report.



## 2.0 PROJECT DESCRIPTION & SUMMARY OF FINDINGS

The Department of Education propose to redevelop the existing Wentworthville Public School at 70-100 Fullagar Road, Wentworthville, NSW.

The existing site is situated on land zoned R2 – Low Density Residential under Holroyd Local Environmental Plan (LEP) 2013.

The existing School comprises of an administration building, library, hall and permanent and demountable learning spaces.

The proposal seeks approval for the removal of the existing structures on the site to accommodate the redevelopment of the School's existing buildings and also the construction of 31 new permanent teaching spaces (home bases). The site plan is shown in the attached Appendix C. The proposal will allow for an additional enrolment of approximately 396 students, taking the total number of students enrolled at the School to  $(604 + 396 = )$  1000 students.

Mechanical plant, including but not limited to air conditioning condenser units and exhaust fans, will be required to serve the proposed home bases, administration building, library and hall.

Wentworthville Public School is bounded by Fullagar Road to the north, Station Street to the east, Monash Street to the south and Garfield Street to the west. Residential dwellings are located in all direction on the opposite sides of the roads and streets bounding the School, as shown on Figure 1.

The nearest noise sensitive receptors to the School, in various directions, are shown on Figure 1 and as follows in Table 1.

**Table 1 Noise Sensitive Receptors**

Receptor and Type	Address	Direction from site
R1 – Residential	109 Fullagar Road	North
R2 – Residential	176-178 Station Street	East
R3 – Residential	10 Monash Street	South
R4 – Residential	77 Garfield Street	West

Each receptor location has been selected to represent the adjacent residential premises, eg R1 is representative of all residential receptors to the north of the School.

The existing and ongoing operating hours for the School are:

*Standard Hours:*

- Monday – Friday: 8.00 am – 4.00 pm.



Outside of standard school hours (community use), the existing and ongoing operating hours for the refurbished Hall are:

*Outside of Standard Hours:*

- Monday: 7.00 pm – 9.00 pm;
- Wednesday: 8.00 am – 10.00 am;
- Saturday: 2.00 pm – 6.00 pm; and
- Sunday: 2.30 pm – 4.30 pm.

The proposal is a State Significant Development (SSD) and has been issued by the NSW Department of Planning and Environment with the Secretary's Environmental Assessment Requirements (SEARs). The SEARs require an assessment against the NSW Environment Protection Authority's (EPA) *Noise Policy for Industry 2017* and the NSW Department of Planning's (DoP) *Development Near Rail Corridors and Busy Roads – Interim Guideline*.


An acoustic assessment of the noise from the outdoor play areas, home bases, public address system and school bell, mechanical plant and the use of the hall both during and outside of standard school hours has been carried out to ensure the noise impact of the School, subsequent to the proposed redevelopment, will not adversely affect the acoustic amenity of the nearby residences or schools.

Calculations show that, provided the recommendations in Section 5 of this report are implemented and adhered to, the level of noise emission, subsequent to the proposed redevelopment, from the School will meet the acoustic requirements in the NSW Department of Planning and Environment's *SEPP (Educational Establishments and Child Care Facilities) 2017*, NSW Environment Protection Authority's (EPA) *Noise Policy for Industry* and the Association of Australasian Acoustical Consultants (AAAC) *Technical Guideline for Child Care Centre Noise Assessment*.

Also, although not applicable to this site, the proposal will also comply with the requirements of the State Environment Planning Policy (SEPP) (Infrastructure) 2007 and the Department of Planning and Environment's (DoPE) *Development Near Rail Corridors and Busy Roads – Interim Guideline*.







**Figure 1. Site Plan - 70 - 100 Fullagar Road, Wentworthville, NSW**





### 3.0 ACOUSTIC CRITERIA

#### 3.1 Measured Ambient Noise Levels

In order to assess the severity of a possible environmental noise problem in a residential area it is necessary to measure the ambient background noise level at the times and locations of worst possible annoyance. The lower the background noise level, the more perceptible the intrusive noise becomes and the more potentially annoying.

The ambient  $L_{90}$  background noise level is a statistical measure of the sound pressure level that is exceeded for 90% of the measuring period (typically 15 minutes).

The Rating Background Level (RBL) is defined by the Environment Protection Authority (NSW) as the median value of the (lower) tenth percentile of  $L_{90}$  ambient background noise levels for day, evening or night periods, measured over a number of days during the proposed days and times of operation.

The places of worst possible annoyance are the nearby residential dwellings. These locations are shown in the Site Plan on Figure 1 as 'R1' to 'R4'. The times of worst possible annoyance will be during the day when the School is operating.

Ambient noise levels were measured in two locations - the front yards of 14 Monash Street and 107 Fullagar Road - shown as Logger Locations 'A' and 'B' on Figure 1, from Wednesday 13 December to Wednesday 20 December, 2017.

The day time ambient noise levels are presented in the attached Appendix B1 and B2 and also below in Table 2.

**Table 2 Ambient Noise Levels**

Noise Measurement Location	Time Period	$L_{90}$ Rating Background Level	Existing $L_{eq}$ Noise Level
Logger Location 'A' - Front yard - 14 Monash Street	Day (7 am to 6 pm)	43 dBA	53 dBA
		45 dBA	58 dBA
Logger Location 'B' - Front yard - 107 Fullagar Road	Day (7 am to 6 pm)	43 dBA	55 dBA
		44 dBA	58 dBA

Meteorological conditions during the testing typically consisted of clear skies and temperatures of 16 to 42°C. Atmospheric conditions were ideal for noise monitoring. Noise measurements were therefore considered reliable and typical for the receptor areas.



## 3.2 NSW Department of Planning and Environment

### 3.2.1 SEPP (Educational Establishments and Child Care Facilities) 2017

The NSW Department of Planning and Environment (DoPE) published the State Environmental Planning Policy (SEPP) (Educational Establishments and Child Care Facilities) 2017 on 1 September 2017. 'Schedule 4 Schools – design quality principles' of the SEPP requires the following:

#### ***'Principle 5. Amenity***

*Schools should provide pleasant and engaging spaces that are accessible for a wide range of educational, informal and community activities, while also considering the amenity of adjacent development and the local neighbourhood.'*

### 3.2.2 SEPP (Infrastructure) 2007

The NSW Department of Planning and Environment (DoPE) published the "Development Near Rail Corridors and Busy Roads – Interim Guidelines" in 2008. The Guidelines refer to Clauses 87 (Rail) and Clause 102 (Road) of the State Environment Planning Policy (Infrastructure) 2007 for the noise criteria for developments affected by railway or road traffic noise.

#### 3.2.2.1 SEPP Clause 87 (Rail)

Clause 87 of the State Environmental Planning Policy (SEPP) (Infrastructure) 2007 details the following in with regards to rail noise and vibration:

- (1) *This clause applies to development for any of the following purposes that is on land in or adjacent to a rail corridor and that the consent authority considers is likely to be adversely affected by rail noise or vibration:*
  - (a) *a building for residential use,*
  - (b) *a place of public worship,*
  - (c) *a hospital,*
  - (d) *an educational establishment or child care centre.*
- (2) *Before determining a development application for development to which this clause applies, the consent authority must take into consideration any guidelines that are issued by the Director-General for the purposes of this clause and published in the Gazette.*

The rail corridor (T1 – North Shore, Northern & Western Line and T5 Cumberland Line) is approximately 750 metres to the north of the development. Therefore, the development will not be 'adversely affected by rail noise or vibration' as per the above, therefore the SEPP is not applicable.



### 3.2.2.2 SEPP Clause 102 (Road)

Clause 102 of the State Environmental Planning Policy (SEPP) (Infrastructure) 2007 details the following in with regards to road noise and vibration:

*This clause applies to development for any of the following purposes that is on land in or adjacent to the road corridor for a freeway, a tollway or a transitway or any other road with an annual average daily traffic volume of more than 40,000 vehicles (based on the traffic volume data published on the website of the RTA) and that the consent authority considers is likely to be adversely affected by road noise or vibration:*

- (a) a building for residential use,*
- (b) a place of public worship,*
- (c) a hospital,*
- (d) an educational establishment or child care centre.*

It is unlikely that the AADT will reach 40,000 on roads surrounding the development site, therefore the SEPP is not applicable.

### 3.3 NSW Environment Protection Authority – Noise Policy for Industry

The NSW Environment Protection Authority (EPA) published the *Noise Policy for Industry* (NPfI) in October 2017. The NPfI is specifically aimed at assessing noise from industrial noise sources listed in Schedule 1 of the Protection of the Environment Operations Act 1997 (POEO, 1997).

While the NPfI is not strictly applicable to this site, as the site is not scheduled, as the standards are consistent with the SEPP, the limits set out in the NPfI will be used as a guide in determining whether the level of noise is considered intrusive or not.

#### 3.3.1 Intrusiveness Criteria

The EPA states in Section 2.3 of its NSW NPfI (October 2017) that the intrusiveness of an industrial noise source may generally be considered acceptable if the level of noise from the source (represented by the  $L_{Aeq}$  descriptor), measured over a 15-minute period, does not exceed the rating background noise level by more than 5 dB when beyond a minimum threshold (EPA NPfI, 2017, Section 2.3).

The NSW EPA in their *Noise Policy for Industry* (2017), Section 2.3, state the following:

*“The objective of carrying out long-term background noise monitoring at a location is to determine existing background noise levels that are indicative of levels during the entire year. However, the RBL for evening or night periods calculated from long-term unattended background noise monitoring can sometimes be higher than the RBL for the daytime period. This situation can arise due to increased noise from, for example, insects or frogs during the evening and night in the warmer months, or due to temperature inversion conditions during winter.*



*In determining project noise trigger levels from RBLs, the community's expectations also need to be considered. The community generally expects greater control of noise during the more sensitive evening and night-time periods than during the less sensitive daytime period. Therefore, in determining project noise trigger levels for a particular development, it is generally recommended that the project intrusiveness noise level for evening be set at no greater than the project intrusiveness noise level for daytime. The project intrusiveness noise level for night-time should be no greater than the project intrusiveness noise level for day or evening. Alternative approaches to these recommendations may be adopted if appropriately justified."*

The Rating Background Level at Logger Location 'A', 14 Monash Street, Wentworthville was 43 dBA during the day and 45 dBA in the evening (see Table 2).

Therefore, the acceptable  $L_{eq, 15 \text{ minute}}$  noise intrusiveness criteria in this area is:

- $(43 + 5 =) 48 \text{ dBA } L_{eq, 15 \text{ minute}}$  during the day and in the evening.

The Rating Background Level at Logger Location 'B', 107 Fullagar Road, Wentworthville was also 43 dBA during the day and 44 dBA in the evening (see Table 2).

Therefore, the acceptable  $L_{eq, 15 \text{ minute}}$  noise intrusiveness criteria in this area is also:

- $(43 + 5 =) 48 \text{ dBA } L_{eq, 15 \text{ minute}}$  during the day and in the evening.

### 3.3.2 Amenity Criteria

Depending on the type of area in which the noise is being made, there is a certain reasonable expectancy for noise amenity. The NSW NPfI provides a schedule of recommended  $L_{eq}$  industrial noise levels that under normal circumstances should not be exceeded. If successive developments occur near a residential area, each one allowing a criterion of background noise level plus 5 dB, the ambient noise level will gradually creep higher.

The recommended  $L_{eq}$  noise levels below in Table 5 are taken from Section 2.4, Table 2.2 of the NPfI.

**Table 3      Amenity Criteria**

Receiver	Noise Amenity Area	Time of Day	$L_{eq}$ , dBA, Recommended Amenity Noise Level
Residential	Suburban	Day	55
		Evening	45
		Night	40



The  $L_{Aeq}$  is determined over a 15-minute period for the project intrusiveness noise level and over an assessment period (day, evening and night) for the project amenity noise level. This leads to the situation where, because of the different averaging periods, the same numerical value does not necessarily represent the same amount of noise heard by a person for different time periods. To standardise the time periods for the intrusiveness and amenity noise levels, the *NPfI* assumes that the  $L_{Aeq,15min}$  will be taken to be equal to the  $L_{Aeq, period} + 3 \text{ decibels (dB)}$  (Section 2.2, *NPfI*).

Compliance with the amenity criteria will limit ambient noise creep. Wherever the existing  $L_{eq}$  noise level from industrial noise sources approaches or exceeds the amenity criteria at a critical receptor location, the intrusive  $L_{eq}$  noise from the noise source in question must be reduced to a level that may be as much as 10 dB below the existing  $L_{eq}$  industrial noise level. **Section 2.4** of the *NPfI* states that where the project amenity noise level is 10 dB or more lower than the existing industrial noise level, the project amenity noise levels can be set at 10 dB below the existing industrial noise levels, provided the existing industrial noise levels are unlikely to reduce over time.

The existing  $L_{eq}$  noise level at Logger Location 'A', 14 Monash Street, Wentworthville was 53 dBA during the day and 58 dBA in the evening (see Table 2). Therefore, the acceptable amenity criteria for the residential receptors in this area are:

- $(55 - 5 + 3 =) 53 \text{ dBA } L_{eq, 15 \text{ minute}}$  during the day; and
- $(58 - 10 + 3 =) 51 \text{ dBA } L_{eq, 15 \text{ minute}}$  in the evening.

The existing  $L_{eq}$  noise level at Logger Location 'B', 107 Fullagar Road, Wentworthville was 55 dBA during the day and 58 dBA in the evening. Therefore, the acceptable amenity criteria for the residential receptors in this area are:

- $(55 - 5 + 3 =) 53 \text{ dBA } L_{eq, 15 \text{ minute}}$  during the day; and
- $(58 - 10 + 3 =) 51 \text{ dBA } L_{eq, 15 \text{ minute}}$  in the evening.



### 3.4 AAAC Noise Criteria for Outdoor Play Areas

In May 2008, the Association of Australasian Acoustical Consultants (AAAC) first published the *Technical Guideline for Child Care Centre Noise Assessment*. The guideline was updated in 2010 to assist both AAAC members and local councils to assess the noise impact from proposed child care centres both accurately and fairly, (see [www.aaac.org.au](http://www.aaac.org.au)).

Although the proposed development comprises alterations and additions to an existing school, and therefore may produce different levels of noise than a childcare centre, there are similarities in noise emission from uses of outdoor play areas for schools and childcare centres. As students do not play outdoors continuously for long periods of time, and as the duration of time for students playing outside is reduced, the overall noise annoyance reduces. Therefore, it is reasonable to allow a higher level of noise impact for a shorter duration.

The AAAC document states that a total time limit of 2 hours of outdoor play per day (e.g. 1 hour in the morning and 1 hour in the afternoon) should allow an additional 5 dB noise impact.

We recommend that the noise criteria detailed in *Technical Guideline for Child Care Centre Noise Assessment* be applied to outdoor areas of the School.

The relevant criteria is  $L_{eq, 15min}$  noise level emitted from the outdoor play area shall not exceed the background noise level by more than 10 dB at the residential assessment location.

**Up to 2 hours (total) per day** – The  $L_{eq, 15minute}$  noise level emitted from the outdoor areas shall not exceed the background noise level by more than 10 dB at the assessment location.

**More than 2 hours per day** – The  $L_{eq, 15minute}$  noise level emitted from the outdoor areas shall not exceed the background noise level by more than 5 dB at the assessment location.

### 3.5 Project Specific Noise Criteria

When all the above factors are considered, we find that the most stringent noise criteria are:

*Residential Receivers – 'R1' to 'R4' – based on Logger Locations 'A' and 'B'*

- **53 dBA**  $L_{eq, 15 minute}$  during the day **for outdoor activities** for up to 2 hours (total) per day;
- **48 dBA**  $L_{eq, 15 minute}$  during the day and evening for all other noise.

These criteria apply at the most-affected point on or within the residential property boundary. For upper floors, the noise is assessed outside the nearest window.



#### 4.0 SCHOOL NOISE EMISSION

The main sources of noise from the School, will be as follows:

- Students playing in the outdoor play area;
- Students inside the home bases;
- Public address system and school bell;
- Mechanical plant; and
- Use of the Hall.

The noise assessment was based on the drawings by Fulton Trotter Architects for Project No. 7068WV01, attached as Appendix C.

#### 4.1 Outdoor Play Areas

Children will be outside for a range of times, including before school, recess, lunch, PE classes and after school, however the outdoor areas are only likely to be at capacity during recess and lunch.

In order to model the worst case scenario of noise emission from students outdoors at play, we have assumed that 2/3 of the 1000 students (666) will engage in active play at the one time, with half (333) of those students making noise at any given time.

Sound power levels of children at play were previously measured for other similar projects and are presented below in Table 4. We believe these levels represent the typical  $L_{eq, 15 \text{ minute}}$  maximum noise levels of children at play and will be used in this noise assessment.

**Table 4**  $L_{eq, 15 \text{ minute}}$  Sound Power Levels - Children Playing in Outdoor Play Areas

Description	Sound Power Levels (dB) at Octave Band Centre Frequencies (Hz)								
	dBA	63	125	250	500	1k	2k	4k	8k
1 Child at play – Primary School	<b>79</b>	50	54	58	71	77	72	66	64
666 Children at play (333 children making noise)	<b>104</b>	75	79	83	96	102	97	91	89





## 4.2 General Learning Areas

We have assumed that the maximum home base class size within the proposed new rooms will be  $(1000 / 45 = )$  23 students.

During normal classroom activities, the main source of noise will be from the teachers and students talking. We have assumed that there may be a maximum of 1/3 (8) of the students talking normally. We have also assumed that the teacher in each classroom may be talking loudly.

Calculations assume students are distributed evenly throughout the inside of the home bases and windows and doors are partially open (10 % of floor area).

Day Design Pty Ltd has previously measured and quantified the Octave Band Centre Frequency sound power level of teachers and students talking at different noise levels. The  $L_{eq, 15 \text{ minute}}$  sound power levels of teachers and students are shown below in Table 5.

**Table 5**  $L_{eq, 15 \text{ minute}}$  Sound Power Levels – Teacher & Students – GLAs

Description	Sound Power Levels (dB) at Octave Band Centre Frequencies (Hz)								
	dBA	63	125	250	500	1k	2k	4k	8k
Teacher talking loudly	<b>79</b>	60	70	75	80	73	70	62	55
School student talking normally	<b>63</b>	53	53	60	63	58	53	52	47
1 teacher and 23 students	<b>80</b>	64	71	76	81	74	71	65	59

## 4.3 Public Address System & School Bell

The School will be provided with a public address system and a bell to signal the start and end of classes. The location of the speakers has not yet been determined however assuming up to 6 speaker locations are provided, the maximum sound pressure level should be no greater than **70 dBA** at 3 metres from each speaker in order to meet the residential noise criteria.



#### 4.4 Mechanical Plant

We have assumed that the air conditioning condenser units will be located in ground floor plant areas on the outer façades of the new buildings or in rooftop plant areas on the new buildings, throughout the development site.

The type of mechanical plant have not yet been selected. The proposed mechanical plant will typically only operate during day time hours, Monday to Friday.

The  $L_{eq, 15 \text{ minute}}$  sound power levels for typical equipment used at school sites are presented below in Table 6.

**Table 6**  $L_{eq, 15 \text{ minute}}$  Sound Power Levels - Mechanical Plant

Description	Sound Power Levels (dB) at Octave Band Centre Frequencies (Hz)								
	dBA	63	125	250	500	1k	2k	4k	8k
Toilet Exhaust Fan	<b>59</b>	48	48	56	57	54	53	45	38
Split system Air Conditioner (Classrooms)	<b>72</b>	76	73	72	69	68	63	55	52
VRF Air Conditioner (Large Spaces)	<b>89</b>	82	82	85	74	87	80	77	69

Once mechanical plant selection has been finalised, a final assessment should be made, prior to the issue of a Construction Certificate.

#### 4.5 Hall Usage

We have assumed the proposed Hall will have capacity for up to 200 people. From our observations of other sites, we have modelled the noise emission from the Hall as follows:

- People talking loudly (10%), guests talking with a raised voice (20 %), guests talking normally (20 %) and the rest are not talking or listening (50 %)
- Amplified music will be played during performances and will consist predominantly of either pre-recorded amplified music or live performances.
- We have assumed as a worst case scenario the Hall may operate at full capacity during a performance.
- We have assumed that the doors will be closed during performances.
- We have assumed any windows will be open (10 % of the floor area) during performances.



Based on information in Harris<sup>1</sup> and in our noise level database gathered over many years, we calculate the sound power levels shown below in Tables 7.

**Table 7**      **Leq, 15 minute Sound Power Levels - Proposed Hall**

<b>Description</b>	<b>Leq Sound Power Level dBA</b>
One Man Talking Loudly	<b>80</b>
One Man Talking with Raised Voice	<b>69</b>
One Man Talking Normally	<b>63</b>
Amplified Live Band	<b>102</b>
200 People	<b>94</b>
200 People with Amplified Live Band	<b>103</b>

<sup>1</sup> *Handbook of Acoustical Measurements and Noise Control, Third Edition, Cyril M. Harris, McGraw-Hill Inc, New York, (Page 16.2)*



#### 4.6 Predicted Noise Level at Receptor Locations

Knowing the sound power level of a noise source (See Tables 4 - 7), the sound pressure level (as measured with a sound level meter) can be calculated at a remote location using suitable formulae to account for distance losses, sound barriers, building envelope transmission, etc. The predicted noise level at the residential and educational receptors from the various noise producing facets of the development are shown below.

Where applicable, calculations include acoustic shielding provided by the proposed School buildings to the residential receptors.

##### 4.6.1 Outdoor Play Areas

Based on a maximum of 530 children playing in the outdoor play areas at any one time, the predicted  $L_{eq\ 15\ minute}$  noise level is calculated to be as shown below in Table 8. The noise prediction was determined by placing all 530 children into four equal groups of 133 children throughout the outdoor play areas.

**Table 8 Predicted  $L_{eq\ 15\ minute}$  Noise Levels – Outdoor Play**

Receptor Location	Predicted Noise Level (dBA)	Noise Criterion (dBA)	Compliance (Yes/No)
R1 – 109 Fullagar Road	47	53	Yes
R2 – 176-178 Station Street	45	53	Yes
R3 – 10 Monash Street	55	53	Yes*
R4 – 77 Garfield Street	45	53	Yes

*\*An exceedance of up to 2 dB is not considered significant and is generally not audible to the human ear.*

The predicted level of noise from the children playing outdoors at the receptor locations 'R1', 'R2', 'R3' and 'R4' complies with the criteria in Section 3.5 of this report, and is therefore acceptable.



#### 4.6.2 Cumulative Noise Level – Home Bases & Mechanical Plant

The cumulative noise impact from the home bases and mechanical plant within the School are summarized and shown in Table 9.

**Table 9 Predicted Cumulative  $L_{eq}$ , 15 minute Noise Levels – Home Bases & Mechanical Plant**

Receptor Location	Predicted $L_{eq}$ Noise Level (dBA)	Acceptable $L_{eq}$ Noise Level (dBA)	Compliance
<b>R1 – 109 Fullagar Road</b>			
- Home Bases	42		
- Mechanical Plant	51		
Cumulative Noise Level	51	48	<b>No ( + 3 dB)</b>
<b>R2 – 176-178 Station Street</b>			
- Home Bases	47		
- Mechanical Plant	41		
Cumulative Noise Level	48	48	Yes
<b>R3 – 10 Monash Street</b>			
- Home Bases	43		
- Mechanical Plant	36		
Cumulative Noise Level	44	48	Yes
<b>R4 – 77 Garfield Street</b>			
- Home Bases	37		
- Mechanical Plant	49		
Cumulative Noise Level	49	48	Yes*

*\*An exceedance of up to 2 dB is not considered significant and is generally not audible to the human ear.*

The predicted cumulative level of noise from the Home Bases and mechanical plant at the receptor locations 'R2', 'R3' and 'R4', complies with the criteria in Section 3.5 of this report, and is therefore acceptable.

However, the predicted cumulative level of noise from the Home Bases and mechanical plant at the receptor location 'R1', exceeds the criteria in Section 3.5 of this report, therefore noise controls as outlined in Section 5 are necessary.



#### 4.6.3 School Hall

The noise impact from the Hall are summarised and shown in Table 10.

**Table 10 Predicted  $L_{eq}$ , 15 minute Noise Levels – Hall**

Receptor Location	Predicted $L_{eq}$ Noise Level (dBA)	Acceptable $L_{eq}$ Noise Level (dBA)	Compliance
<b>Day &amp; Evening – 7.00 am to 10.00 pm</b>			
<b>R1 – 109 Fullagar Road</b>			
- Live Performance	51	48	<b>No (+ 3 dB)</b>
<b>R2 – 176-178 Station Street</b>			
- Live Performance	44	48	Yes
<b>R3 – 10 Monash Street</b>			
- Live Performance	53	48	<b>No (+ 5 dB)</b>
<b>R4 – 77 Garfield Street</b>			
- Live Performance	56	48	<b>No (+ 8 dB)</b>

The predicted level of noise from the Hall at the receptor location 'R2', complies with the criteria in Section 3.5 of this report, and is therefore acceptable.

However, the predicted cumulative level of noise from the Hall at the receptor location 'R1', 'R3' and 'R4' exceeds the criteria in Section 3.5 of this report, therefore noise controls as outlined in Section 5 are necessary.



## **5.0 NOISE CONTROL RECOMMENDATIONS**

### **5.1 Construction Certificate / Detailed Design**

#### **5.1.1 Mechanical Plant**

The levels of noise emission from the mechanical plant associated with the primary school has potential to be in excess of the acceptable noise criteria in Section 3.5 of this report. Therefore, noise controls may be required.

The specifications for the mechanical plant have not yet been finalised for this development. For typical mechanical plant equipment with sound power levels not exceeding those listed in Table 6, it is reasonable and feasible to locate the plant area or equipment itself so that noise will not impact the neighbouring properties.

Once mechanical plant has been finalised, a detailed acoustic assessment should be made, prior to the issue of a Construction Certificate / during the detailed design stage. We recommend that the mechanical services engineers select mechanical plant equipment with the lowest sound power levels to reduce the amount of acoustic treatment necessary to achieve the noise criteria at nearby residential receivers.

We offer to provide detailed noise controls when specifications of the mechanical plant equipment have been finalised.

#### **5.1.2 Use of School Hall**

There is the potential for noise emissions to exceed the noise criteria at several nearby residential receivers during the proposed use of the Hall.

Noise controls including, but not limited to, the following may be required:

- Closing external windows during noisy events;
- Limiting the noise level of any amplification system inside the Hall; and
- Limiting the noise level of any live instruments to be used in the Hall.





## 5.2 Air Conditioning Condenser Unit Plant Areas – Ground Floor

We recommend 1.8 metre high sound barrier walls be constructed on the three open sides around ground floor air conditioning unit plant areas, as shown in the attached Appendix D. The barriers may have a maximum gap of 200 mm between the ground and the bottom of the barrier provided the condenser units are installed on a plinth equal to or above this height (200 mm), to allow for the required airflow to condenser units.

The barrier walls around the eastern plant area may be constructed from 6 mm fibre cement, 19 mm marine plywood, Colorbond steel or masonry. Gaps should be fully sealed to create a solid barrier.

The sides of the barrier facing the air conditioning units and the façade of the building should be lined with 75 mm thick glasswool insulation (density 32 kg/m<sup>3</sup>) with water resistant woven fibreglass facing, such as CSR Bradford Supertel faced with Ultraphon as shown on attached Appendix E.



## 6.0 NOISE IMPACT STATEMENT

Day Design Pty Ltd was engaged by Fulton Trotter Architects to carry out an acoustic assessment of the proposed redevelopment of the Wentworthville Public School at 70-100 Fullagar Road, Wentworthville, NSW.

Calculations show that provided the recommendation in Section 5 of this report are implemented and adhered to, the level of noise emitted from the Wentworthville Public School at 70-100 Fullagar Road, Wentworthville, NSW, will meet the noise level requirements of the NSW Department of Planning and Environment's *SEPP (Educational Establishments and Child Care Facilities) 2017*, NSW Environment Protection Authority's *Noise Policy for Industry* and the Association of Australasian Acoustical Consultants *Technical Guideline for Child Care Centre Noise Assessment* as detailed in Section 3 of this report, and be considered acceptable.

In addition, the amenity of adjacent development and the local neighbourhood will be respected and upheld.

Also, although not applicable to this site, the proposal will also comply with the requirements of the State Environment Planning Policy (SEPP) (Infrastructure) 2007 and the Department of Planning's (DoP) *Development Near Rail Corridors and Busy Roads – Interim Guideline*.



**Adam Shearer**, BCT (Audio), MDesSc (Audio and Acoustics), MAAS  
Senior Acoustical Consultant  
for and on behalf of Day Design Pty Ltd

## AAAC MEMBERSHIP

Day Design Pty Ltd is a member company of the Association of Australasian Acoustical Consultants, and the work herein reported has been performed in accordance with the terms of membership.

## APPENDICES

- Appendix A – Noise Survey Instrumentation
- Appendix B1 & B2 – Ambient Noise Surveys
- Appendix C – Proposed Site Layout
- Appendix D – Air Conditioning Plant Sound Barrier
- Appendix E – Cross Section of Air Conditioning Plant Sound Barrier



**APPENDIX A – NOISE SURVEY INSTRUMENTATION**

Noise level measurements and analysis were made with instrumentation as follows in Table A:

**Table A Noise Instrumentation**

Description	Model No.	Serial No.
Infobyte Noise Logger	iM4	105
Condenser Microphone 0.5" diameter	MK 250	7112
Infobyte Noise Logger	iM4	116
Condenser Microphone 0.5" diameter	MK 250	116


An environmental noise logger is used to continuously monitor ambient noise levels and provide information on the statistical distribution of noise during an extended period of time. The Infobyte Noise Monitor iM4s #105 and #116 are Type 1 (105) and Type 2 (116) precision environmental noise monitor meeting all the applicable requirements of AS1259 for an integrating-averaging sound level meter.

All instrument systems had been laboratory calibrated using instrumentation traceable to Australian National Standards and certified within the last two years thus conforming to Australian Standards. The measurement system was also field calibrated prior to and after noise surveys. Calibration drift was found to be within 1 dB for long-term measurements. No adjustments for instrument drift during the measurement period were warranted.




AMBIENT NOISE SURVEY

Located at 107 Fullagar Road, Wentworthville, NSW



AMBIENT NOISE SURVEY

Located at 14 Monash Road, Wentworthville, NSW







**Safe Roof Access System**  
A safe roof access system shall be provided that complies with the following Australian Standards:


- Industrial fall-arrest systems and devices - Selection, use and maintenance: To AS/NZS 1891.4
- Industrial fall-arrest systems and devices - Safety belts and harnesses: to AS/NZS 1891.1
- Industrial fall-arrest systems and devices - Horizontal lifeline and rail systems: to AS/NZS 1891.2
- Industrial fall-arrest systems and devices - Fall-arrest devices: to AS/NZS 1891.3
- Industrial safety belts and harnesses - Selection, use and maintenance: to AS 2626 (for anchorages only)

The system shall provide a complete fall-arrest roof safety system that:

- Includes a fixed access ladder in a lockable location to provide access to the roofs of multi-storey buildings
- Has minimal visual impact on the completed roof, and is compatible with the roofing materials, construction, loading constraints and colours;

- is structurally sufficient in respect of all loads reasonably expected to be imposed on it, and has no adverse structural or other effect on the completed roof
- may include a number of fully-compatible subsystems, all from one manufacturer/supplier, that allow users to work safely at any point on the roof at all times without the need to disconnect harnesses or restraint lines and lanyards completely, or to carry components of other systems with them;
- prevents free falls wherever possible, and limits possible free falls to the absolute minimum consistent with the user's anticipated work tasks (600mm or less wherever possible, but in no case exceeding 2000 mm);
- allows restrained falls on non-fragile roofed areas only, and includes additional diversionary anchorages near roof edges to prevent a pendulum effect in the event of a fall;
- includes removable means of protecting sharp edges that any line or lanyard may come in contact with, in the event of a free fall;
- exerts a force not exceeding 6kN on any user who is secured to it, and falls;
- distributes fall-arrest forces over the body so that injury is minimised after a fall, and that holds a user in a suitable attitude for rescue after a fall;

- includes anchorages complying with AS 2626;
- has all anchorages positioned so that line and lanyard attachment hardware is kept clear of sharp edges;
- does not include the use of slings, or backhooking of lanyards, as part of an anchorage;
- may include single point, one-person anchorages that have a minimum ultimate strength in the direction of loading of not less than 15kN;
- includes heavy duty, easily operated attachment hardware, other than snaphooks, that is appropriately sized for all lines and lanyards provided as part of the systems;
- includes carrying bags for each complete set of personal fall-arrest equipment
- includes all necessary labels and signs with an expected life equal to the item referred to;
- remains intact, usable and water-resistant under the local and regional ambient climatic conditions with a minimum amount of maintenance;
- includes at least four ladder securing access points to the roof edge or gutter, including a level concrete slab at ground level, unless specified elsewhere in the documents;
- includes at least one removable Type 3 fall-arrest device, that may be attached anywhere a free fall is possible, to assist in the immediate recovery of a user who has fallen;
- includes at least two fully adjustable harnesses, each with an attachment point to front and back. Restraint belts will not be allowed;
- includes the appropriate number (but not less than two) of lanyards, restraint lines, and pole lines as appropriate: each with energy-absorbing fall-arrest characteristics or devices fitted; and
- is certified by a Registered Professional Engineer specialising in structural design and certification.



Copyright  
This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied, directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.

P1	Draft Schematic Design Issue	04/09/2018	JFK
P2	Issued For TSG Review	20/09/2018	JFK
P3	SSDA Consultant Report Issue	05/10/18	WJS
P4	SD / SSDA Client Review Issue	11/10/18	JFK
P5	SSDA Draft Issue	01/11/18	JFK
P6	SSDA Final Coordination Issue	01/11/18	JFK
REV.	DESCRIPTION	DATE	INT.

**fulton trotter**  
ARCHITECTS  
SYDNEY  
Level 3, 35 Spring Street 1, (02) 9369 9941  
PO Box 1860 Bond Junction, NSW 2022  
BRISBANE  
SYDNEY  
sydney@fultontrotter.com.au

DIRECTORS	NEW 6855	OLD 2520
Chris Lewis	NEW 8371	OLD 3113
John Ward	NEW 8371	OLD 3847
James Elbery	NEW 17691	OLD 4109
Mark Trotter	NEW 4421	OLD 1975
Nathan Haskin	NEW 7185	OLD 4121
Paul Skene	NEW 7185	OLD 3169
Phil Trotter	NEW 7177	OLD 3046
Ryan Lovelady	NEW 5802	OLD 4503
Robert Weather	NEW 5802	OLD 3633

www.fultontrotter.com.au

PHASE  
**SCHEMATIC DESIGN**  
CLIENT  
NSW Department of Education

PROJECT  
Wentworthville Public School

ADDRESS  
70-100 Fullagar Road  
WENTWORTHVILLE, NSW

DRAWING  
**BLOCK A - ROOF PLAN**

Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.

PROJECT NUMBER	DIRECTOR	CHECKED
7068WV01	JW	
DRAWING NUMBER	REVISION	
SD-A-2101	P6	

**1 PLAN**  
**ROOF PLAN - BUILDING A**  
SCALE: 1:100



Copyright

This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.



P9	Draft Schematic Design Issue	04/09/2018	JFK
P10	Issued For TSD Review	20/09/2018	JFK
P11	SSDA Consultant Report Issue	05/10/18	WGS
P12	SD SSDA Client Report Issue	11/10/18	JFK
P13	SSDA Draft Issue	01/11/18	JFK
P14	SSDA Final Coordination Issue	01/11/18	JFK
REV.	DESCRIPTION	DATE	INT.

## fulton trotter ARCHITECTS

SYDNEY  
Level 3, 35 Spring Street 1, (D2) 0369 9841  
PO Box 1880 Bond Junction, NSW 2022  
BRISBANE  
SYDNEY

<b>DIRECTORS</b>	NSW 6885	QLD 2920
Chris Isaac	NSW 8371	QLD 3113
Justin Elbery	NSW 8371	QLD 3847
John Ward	NSW 8371	QLD 4509
Kathleen Chingapanta	NSW 17691	NSW 4421
Mark Trotter	NSW 4421	QLD 1975
Matthew Haskin	NSW 5026	QLD 4175
Paul Sakuma	NSW 7180	QLD 3159
Paul Trotter	NSW 7177	QLD 3046
Ryan Lovelady	NSW 5802	QLD 4500
Robert Weather		QLD 3833

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

### PHASE SCHEMATIC DESIGN

CLIENT NSW Department of Education

PROJECT Wentworthville Public School

ADDRESS 70-100 Fullagar Road WENTWORTHVILLE, NSW

DRAWING BLOCK E - GROUND FLOOR PLAN


Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.

PROJECT NUMBER 7068WV01 DIRECTOR JW CHECKED

DRAWING NUMBER SD-E-2001 REVISION P14


1 PLAN  
LEVEL 3 - BUILDING E PROPOSED  
SCALE: 1:100

Copyright  
This drawing shows design features and elements of a design prepared by  
Fulton Trotter Architects and is to be used only for work authorised in  
writing by the designers. It cannot be copied directly or indirectly, in whole  
or in part, nor shall it be used for any other building purposes. Unauthorised  
use will be considered an infringement of these rights.




Copyright


This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied, directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.




**1 ELEVATION**  
**BUILDING E - NORTHERN ELEVATION**  
SCALE: 1:100



**2 ELEVATION**  
**BUILDING E - SOUTHERN ELEVATION**  
SCALE: 1:100



**3 ELEVATION**  
**BUILDING E - WESTERN ELEVATION**  
SCALE: 1:100



**3 ELEVATION**  
**BUILDING E - EASTERN ELEVATION**  
SCALE: 1:100

P3	Schematic Design	24/07/18	LW
P4	Draft Schematic Design Issue	04/09/2018	JFK
P5	Issued For TSO Review	20/09/2018	JFK
P6	SSDA Consultant Report Issue	05/10/18	WS
P7	SD / SSDA Client Review Issue	11/10/18	JFK
P8	SSDA Draft Issue	01/11/18	JFK
P9	SSDA Final Coordination Issue	01/11/18	JFK
REV	DESCRIPTION	DATE	INT.

**fulton trotter**  
ARCHITECTS

SYDNEY  
Level 3, 35 Spring Street 1, (02) 9369 9941  
PO Box 1860  
Bondi Junction, NSW 2022  
BRISBANE  
SYDNEY

<b>DIRECTORS</b>			
Chris Isaac	NSW 6885	QLD 2920	
Justine Elbery	NSW 8371	QLD 3113	
John Ward	NSW 8371	QLD 3847	
Kathleen Thompson	NSW 17691	QLD 1975	
Mark Trotter	NSW 4421	QLD 4121	
Nathan Haskin	NSW 7180	QLD 3158	
Paul Sakera	NSW 7177	QLD 3046	
Ryan Lovelady	NSW 5802	QLD 4502	
Robert Weather			

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

**SCHEMATIC DESIGN**

NSW Department of Education

Wentworthville Public School

70-100 Fullagar Road  
WENTWORTHVILLE, NSW


**BLOCK E - ELEVATIONS**

Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.

PROJECT NUMBER	DIRECTOR	CHECKED
7068WV01	JW	
DRAWING NUMBER	REVISION	
SD-E-3001	P9	

Copyright

This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.



P9	Draft Schematic Design Issue	04/09/2018	JFK
P10	Issued For TSO Review	20/09/2018	JFK
P11	SSDA Consultant Report Issue	05/10/18	WS
P12	SD / SSDA Client Review Issue	11/10/18	JFK
P13	SSDA Draft Issue	01/11/18	JFK
P14	SSDA Final Coordination Issue	01/11/18	JFK
REV.	DESCRIPTION	DATE	INT.

**fulton trotter**  
ARCHITECTS

**SYDNEY**  
Level 3, 35 Spring Street 1, (02) 9369 9841  
PO Box 1888  
Bondi Junction, NSW 2022  
sydney@fultontrotter.com.au

**BRISBANE**  
SYDNEY  
DIRECTORS  
Craig Isaac, NSW  
Joanne Elbery, NSW  
John Ward, NSW  
Kathleen Thompson, NSW  
Mark Trotter, NSW  
Nathan Haskin, NSW  
Paul Siskens, NSW  
Paul Trotter, NSW  
Ryan Lovelady, NSW  
Robert Wastell, NSW  
NSW 6885 QLD 2920  
QLD 3113 QLD 3847  
VIC 18804 NSW 8371  
VIC 17691 NSW 4421 QLD 1975  
NSW 50206 QLD 4121  
NSW 7180 QLD 3159  
NSW 7177 QLD 3046  
QLD 4501  
NSW 5902 QLD 3633

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

**PHASE**  
**SCHEMATIC DESIGN**  
**CLIENT**  
NSW Department of Education

**PROJECT**  
Wentworthville Public School

**ADDRESS**  
70-100 Fullagar Road  
WENTWORTHVILLE, NSW

**DRAWING**  
**BLOCK F - GROUND FLOOR**  
**PLAN**

Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.

**PROJECT NUMBER**  
7068WV01  
**DIRECTOR**  
JW

**DRAWING NUMBER**  
SD-F-2001  
**CHECKED**  
P14  
**REVISION**

Safe Roof Access System

A safe roof access system shall be provided that complies with the following Australian Standards -

- Industrial fall-arrest systems and devices - Selection, use and maintenance: To AS/NZS 1891.4
- Industrial fall-arrest systems and devices - Safety belts and harnesses: to AS/NZS 1891.1
- Industrial fall-arrest systems and devices - Horizontal lifeline and rail systems: to AS/NZS 1891.2
- Industrial fall-arrest systems and devices - Fall-arrest devices: to AS/NZS 1891.3
- Industrial safety belts and harnesses - Selection, use and maintenance: to AS 2626 (for anchorages only)

The system shall provide a complete fall-arrest roof safety system that:

- Includes a fixed access ladder in a lockable location to provide access to the roofs of multi-storey buildings


- has minimal visual impact on the completed roof, and is compatible with the roofing materials, construction, loading constraints and colours;
- is structurally sufficient in respect of all loads
- is reasonably expected to be imposed on it, and has no adverse structural or other effect on the completed roof;
- may include a number of fully-compatible subsystems, all from one manufacturer/supplier, that allow users to work safely at any point on the roof at all times without the need to disconnect harnesses or restraint lines and lanyards completely, or to carry components of other systems with them;
- prevents free falls wherever possible, and limits possible free falls to the absolute minimum consistent with the user's anticipated work tasks (600mm or less wherever possible, but in no case exceeding 2000 mm);
- allows restrained falls on non-fragile roofed areas only, and includes additional diversionary anchorages near roof edges to prevent a pendulum effect in the event of a fall;

- includes removable means of protecting sharp edges that any line or lanyard may come in contact with, in the event of a free fall;
- exerts a force not exceeding 6kN on any user who is secured to it, and falls;
- distributes fall-arrest forces over the body so that injury is minimised after a fall, and that holds a user in a suitable attitude for rescue after a fall;
- includes anchorages complying with AS 2626;
- has all anchorages positioned so that line and lanyard attachment hardware is kept clear of sharp edges;
- does not include the use of slings, or backhooking of lanyards, as part of an anchorage;
- may include single point, one-person anchorages that have a minimum ultimate strength in the direction of loading of not less than 15kN;
- includes heavy duty, easily operated attachment hardware, other than snaphooks, that is appropriately sized for all lines and lanyards provided as part of the systems;
- includes carrying bags for each complete set of personal fall-arrest equipment;

- includes all necessary labels and signs with an expected life equal to the item referred to;
- remains intact, usable and water-resistant under the local and regional ambient climatic conditions with a minimum amount of maintenance;
- includes at least four ladder securing access points to the roof edge or gutter, including a level concrete slab at ground level, unless specified elsewhere in the documents;
- includes at least one removable Type 3 fall-arrest device, that may be attached anywhere a free fall is possible, to assist in the immediate recovery of a user who has fallen;
- includes at least two fully adjustable harnesses, each with an attachment point to front and back. Restraint belts will not be allowed;
- includes the appropriate number (but not less than two) of lanyards, restraint lines, and pole lines as appropriate: each with energy-absorbing fall-arrest characteristics or devices fitted; and
- is certified by a Registered Professional Engineer specialising in structural design and certification.

Copyright

This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied, directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.



P2	PSE-DA	18/07/18	IP
P3	Draft Schematic Design Issue	04/09/2018	JFK
P4	Issued For TSG Review	20/09/2018	JFK
P5	SSDA Consultant Report Issue	05/10/18	WJS
P6	SD / SSDA Client Review Issue	11/10/18	JFK
P7	SSDA Draft Issue	01/11/18	JFK
P8	SSDA Final Coordination Issue	01/11/18	JFK
REV	DESCRIPTION	DATE	INT.

**fulton trotter**  
ARCHITECTS

**SYDNEY**  
Level 3, 35 Spring Street 1, (D2) 0369 9941  
PO Box 1860  
Bond Junction, NSW 2022  
sydney@fultontrotter.com.au

**BRISBANE**  
SYDNEY

<b>DIRECTORS</b>			
Chris Lewis	NSW 6885	QLD 2920	
Justin Eddy	NSW 8371	QLD 3113	
John Ward	NSW 8371	QLD 3847	
Kathleen Thompson	VIC 18804	QLD 4508	
Mark Trotter	VIC 17691	NSW 4421	QLD 1975
Nathan Haskeworth	NSW 50206	QLD 4173	
Paul Sakuma	NSW 7180	QLD 3158	
Paul Trotter	NSW 7177	QLD 3044	
Ryan Lovelady	NSW 5802	QLD 4501	
Robert Weather	NSW 5802	QLD 3833	

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

**PHASE**  
**SCHEMATIC DESIGN**

**CLIENT**  
NSW Department of Education





**PROJECT**  
Wentworthville Public School

**ADDRESS**  
70-100 Fullagar Road  
WENTWORTHVILLE, NSW

**DRAWING**  
**BLOCK F - ROOF PLAN**

Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.

<b>PROJECT NUMBER</b> 7068WV01	<b>DIRECTOR</b> JW	<b>CHECKED</b>
<b>DRAWING NUMBER</b> SD-F-2101	<b>REVISION</b> P8	



P2	Consultant Issue	22/06/18	W
P2	PRE-DA	18/07/18	IF
P3	Schematic Design	24/07/18	LV
P4	Issued For TSG Review	20/09/2018	JF
P5	SSDA Consultant Report Issue	05/10/18	WH
P6	SD / SSDA Client Review Issue	11/10/18	JF
P7	SSDA Draft Issue	6/11/18	JF
P8	SSDA Final Coordination Issue	9/11/18	JF
REV.	DESCRIPTION	DATE	INITIALS

**SYDNEY**  
Level 3, 35 Spring Street t. (02) 9369 5941  
PO Box 1669 e. [sydney@fullcontrollar.com.au](mailto:sydney@fullcontrollar.com.au)  
Rand. Junction NSW 2022

DIRECTORS			
Greg Innes raia		NSW 8855	QLD 292
Justine Elzouy raia			QLD 337
John Ward raia	VIC 18804	NSW 8371	QLD 384
Katerina Dracopoulos raia			QLD 452
Mark Trotter raia	VIC 17691	NSW 4421	QLD 187
Nathan Hildebrandt raia		NSW 10258	QLD 415
Paul Sakriva raia		NSW 7180	QLD 318
Paul Trotter raia		NSW 7177	QLD 266
Ryan Loveday raia			QLD 450
Robert Wessner raia		NSW 5802	QLD 283

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

## PHASE SCHEMATIC DESIGN

NSW Department of Education

CLIENTE \_\_\_\_\_

Wentworthville Public School

\_\_\_\_\_

70-100 Fullagar Road

AD WENTWORTHVILLE, NSW

## CONCLUSIONS

**BLOCK F - ELEVATIONS 1**

■ 0.0001 0.001 0.01 0.1 1 10 100 1000

Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing

PROJECT NUMBER	DIRECTOR	CHECKED
----------------	----------	---------


PROJECT NUMBER	DIRECTOR	CHECKED
7068WV01	JW	

DRAWING NUMBER \_\_\_\_\_ REVISION \_\_\_\_\_

SD-F-3001 P8

Copyright

This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.



P8	Draft Schematic Design Issue	04/09/2018	JFK
P9	Issued For TSG Review	20/09/2018	JFK
P10	SSDA Consultant Report Issue	05/10/18	WJS
P11	SD / SSDA Client Review Issue	11/10/18	JFK
P12	SSDA Draft Issue	01/11/18	JFK
P13	SSDA Final Coordination Issue	01/11/18	JFK
REV.	DESCRIPTION	DATE	INT.

## fulton trotter ARCHITECTS

SYDNEY  
Level 3, 35 Spring Street 1, (02) 9369 9841  
PO Box 1888  
Bond Junction, NSW 2022  
BRISBANE  
SYDNEY

<b>DIRECTORS</b>	NEW 6885	OLD 2920
Chris Davis	NEW 8371	OLD 3847
Justin Elbery	NEW 8371	OLD 4058
John Ward	NEW 8371	OLD 4058
Kathleen Thompson	NEW 8371	OLD 4058
Mark Trotter	NEW 4421	OLD 1975
Nathan Haskin	NEW 5026	OLD 4125
Paul Skene	NEW 7180	OLD 3168
Paul Trotter	NEW 7177	OLD 3044
Ryan Lovelady	NEW 5802	OLD 4502
Robert Wainwright	NEW 5802	OLD 4502

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

### PHASE SCHEMATIC DESIGN

CLIENT NSW Department of Education

PROJECT Wentworthville Public School

ADDRESS 70-100 Fullagar Road  
WENTWORTHVILLE, NSW

### DRAWING BLOCK G - LEVEL 1 - KEY PLAN

Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.

PROJECT NUMBER	DIRECTOR	CHECKED
7068WV01	JW	

DRAWING NUMBER	REVISION
SD-G-2001	P13

### 1 PLAN LEVEL 1 - KEY PLAN SCALE: 1:200



Copyright

This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied, directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.



P7	Draft Schematic Design Issue	04/09/2018	JFK
P8	Issued For TSO Review	20/09/2018	JFK
P9	SSDA Consultant Report Issue	05/10/18	WS
P10	SD / SSDA Client Review Issue	11/10/18	JFK
P11	SSDA Draft Issue	01/11/18	JFK
P12	SSDA Final Coordination Issue	01/11/18	JFK
REV.	DESCRIPTION	DATE	INT.

## fulton trotter ARCHITECTS

SYDNEY  
Level 2, 355 Spring Street, (1) (2) 9369 9841  
PO Box 1888  
Bond Junction, NSW 2022  
BRISBANE  
SYDNEY

<b>DIRECTORS</b>	NSW 6885	OLD 2920
Chris Davis	NSW 8371	OLD 3513
Justin Elbery	NSW 8371	OLD 3847
John Ward	VIC 18804	OLD 4058
Kathleen Thompson	VIC 17691	OLD 1975
Mark Trotter	NSW 4421	OLD 4175
Nathan Thompson	NSW 5026	OLD 4175
Paul Skene	NSW 7185	OLD 3158
Paul Trotter	NSW 7177	OLD 3044
Ryan Lowndes	NSW 5802	OLD 4503
Robert Woodhouse	NSW 5802	OLD 3053

[www.fultontroutter.com.au](http://www.fultontroutter.com.au)

PHASE  
**SCHEMATIC DESIGN**  
CLIENT  
NSW Department of Education

PROJECT  
Wentworthville Public School

ADDRESS  
70-100 Fullagar Road  
WENTWORTHVILLE, NSW

DRAWING  
**BLOCK G - LEVEL 2 - KEY PLAN**

Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.

PROJECT NUMBER  
**7068WV01**  
DIRECTOR  
**JW**  
CHECKED


DRAWING NUMBER  
**SD-G-2002**  
REVISION  
**P12**

**P1** PLAN  
LEVEL 2 - KEY PLAN  
SCALE: 1:200



Copyright

This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.



P7	Draft Schematic Design Issue	04/09/2018	JFK
P8	Issued For TSD Review	20/09/2018	JFK
P9	SSDA Consultant Report Issue	05/10/18	WS
P10	SD / SSDA Client Review Issue	11/10/18	JFK
P11	SSDA Draft Issue	01/11/18	JFK
P12	SSDA Final Coordination Issue	01/11/18	JFK
REV.	DESCRIPTION	DATE	INT.

## fulton trotter

ARCHITECTS

SYDNEY  
Level 3, 355 Spring Street, 1 (D2) 0369 9841  
PO Box 1888  
Bond Junction, NSW 2022  
BRISBANE  
SYDNEY

<b>DIRECTORS</b>	
Chris Isaac	NSW 6885 QLD 2920
Justin Elbery	NSW 8371 QLD 3113
John Ward	NSW 8371 QLD 3847
Kathleen Thompson	NSW 8371 QLD 4028
Mark Trotter	NSW 4421 QLD 1875
Nathan Haskin	NSW 5026 QLD 4121
Paul Siskens	NSW 7185 QLD 3168
Paul Trotter	NSW 7177 QLD 3046
Ryan Lovelady	NSW 5802 QLD 4501
Robert Wetherill	NSW 5802 QLD 3533

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

**SCHEMATIC DESIGN**  
NSW Department of Education

Wentworthville Public School

70-100 Fullagar Road  
WENTWORTHVILLE, NSW

DRAWING

**BLOCK G - LEVEL 3 - KEY PLAN**

Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.


PROJECT NUMBER	DIRECTOR	CHECKED
7068WV01	JW	
DRAWING NUMBER	REVISION	
SD-G-2003	P12	

1 PLAN  
LEVEL 3 - KEY PLAN  
SCALE: 1:200


plot date: Friday, 9 November 2018 File location: BIM Server: sydbmtyd 21 - BIM Server 21\7068 WVPS 1150mm @ A1

Copyright


This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied, directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.



**1 ELEVATION**  
BUILDING G - NORTHERN ELEVATION  
SCALE: 1:100



**2 ELEVATION**  
BUILDING G - SOUTHERN SECTIONAL ELEVATION  
SCALE: 1:100



**3 ELEVATION**  
BUILDING G - WESTERN ELEVATION  
SCALE: 1:100

plot date: Friday, 9 November 2018 110 location: BIM Server: sydneydms21 - BIM Server 21/17088 WVPB 115mm @ A1

P1	PSE-0A	18/07/18	JP
P2	Draft Schematic Design Issue	04/09/2018	JFK
P3	Issued For TSO Review	20/09/2018	JFK
P4	SSDA Consultant Report Issue	05/10/18	WS
P5	SD / SSDA Client Review Issue	11/10/18	JFK
P6	SSDA Draft Issue	01/11/18	JFK
P7	SSDA Final Coordination Issue	01/11/18	JFK
REV.	DESCRIPTION	DATE	INT.

**fulton trotter**  
ARCHITECTS

SYDNEY  
Level 3, 35 Spring Street 1 (02) 9369 9941  
PO Box 1860  
Bond Junction, NSW 2022  
BRISBANE  
SYDNEY

<b>DIRECTORS</b>	NSW 6885	CLD 2920
Chris Trotter	NSW 4113	CLD 3113
John Ward	NSW 4371	CLD 3847
James Edwards	NSW 4529	CLD 4029
Mark Trotter	NSW 4421	CLD 1875
Mark Hadden	NSW 5026	CLD 4175
Paul Siskens	NSW 7188	CLD 3158
Paul Trotter	NSW 7177	CLD 3048
Ryan Lovelady	NSW 5802	CLD 4501
Robert Woodhouse	NSW 5802	CLD 3831

[www.fultontrtrotter.com.au](http://www.fultontrtrotter.com.au)

**SCHEMATIC DESIGN**  
NSW Department of Education


Wentworthville Public School  
70-100 Fullagar Road  
WENTWORTHVILLE, NSW

**BLOCK G - ELEVATIONS 1**


Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.

PROJECT NUMBER	DIRECTOR	CHECKED
7068WV01	JW	
DRAWING NUMBER	REVISION	
SD-G-3001	P7	

Copyright  
This drawing shows design features and elements of a design prepared by  
Fulton Trotter Architects and is to be used only for work authorised in  
writing by the designers. It cannot be copied, directly or indirectly, in whole  
or in part, nor shall it be used for any other building purposes. Unauthorised  
use will be considered an infringement of these rights.



1 ELEVATION  
BUILDING G - NORTHERN ELEVATION  
SCALE: 1:100



2 ELEVATION  
BUILDING G - EASTERN ELEVATION  
SCALE: 1:100

P1	PSE-0A	18/07/18	JP
P2	Draft Schematic Design Issue	04/09/2018	JFK
P3	Issued For TSO Review	20/09/2018	JFK
P4	SSDA Consultant Report Issue	05/10/18	WS
P5	SD / SSDA Client Review Issue	11/10/18	JFK
P6	SSDA Draft Issue	01/11/18	JFK
P7	SSDA Final Coordination Issue	01/11/18	JFK
REV.	DESCRIPTION	DATE	INT.

**fulton trotter**  
ARCHITECTS

**SYDNEY**  
Level 3, 35 Spring Street 1 (02) 9369 9941  
PO Box 1860  
Bondi Junction, NSW 2022  
sydney@fultontrotter.com.au

**BRISBANE**  
SYDNEY

**DIRECTORS**  
Craig Isaac, NSW  
James Elworthy, NSW  
John Ward, NSW  
Kathleen Thompson, NSW  
Mark Trotter, NSW  
Nathan Hadden, NSW  
Paul Sakuma, NSW  
Paul Trotter, NSW  
Ryan Lovelady, NSW  
Robert Woodhouse, NSW

**NEW 6885** OLD 2920  
**NSW 8371** OLD 3113  
**NSW 8347** OLD 4528  
**VIC 18804** NSW 8371  
**NSW 4421** OLD 1875  
**NSW 5028** OLD 4125  
**NSW 7185** OLD 3158  
**NSW 7177** OLD 3048  
**NSW 5802** OLD 4501  
**NSW 5802** OLD 3033

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

PHASE  
CLIENT  
**SCHEMATIC DESIGN**  
NSW Department of Education

PROJECT  
CLIENT  
Wentworthville Public School

ADDRESS  
PROJECT  
70-100 Fullagar Road  
WENTWORTHVILLE, NSW

DRAWING  
BLOCK G - ELEVATIONS 2


Figured dimensions take precedence over  
scale dimensions. Contractors must verify  
all dimensions on site before commencing  
any work or making shop drawings.

PROJECT NUMBER	DIRECTOR	CHECKED
7068WV01	JW	
DRAWING NUMBER	REVISION	
SD-G-3002	P7	




Copyright


This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied, directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.



**1 ELEVATION**  
BUILDING G - WESTERN SECTIONAL ELEVATION  
SCALE: 1:100



**2 ELEVATION**  
BUILDING G - WESTERN SECTIONAL ELEVATION  
SCALE: 1:100



**3 ELEVATION**  
BUILDING G - EASTERN ELEVATION  
SCALE: 1:100

plot date: Friday, 9 November 2018 110 location: BIM Server: syd00001 21 - BIM Server 21/17068 WVPs 1150mm @ A1

REV.	DESCRIPTION	DATE	INT.
P1	PSE-0A	18/07/18	JP
P2	Draft Schematic Design Issue	04/09/2018	JK
P3	Issued For TSO Review	20/09/2018	JK
P4	SSDA Consultant Report Issue	05/10/18	WS
P5	SD / SSDA Client Review Issue	11/10/18	JK
P6	SSDA Draft Issue	01/11/18	JK
P7	SSDA Final Coordination Issue	01/11/18	JK

**fulton trotter**  
ARCHITECTS

**SYDNEY**  
Level 3, 35 Spring Street 1 (02) 9369 9941  
PO Box 1860 Bond Junction, NSW 2022 & sydney@fultontrotter.com.au

**BRISBANE**  
SYDNEY  
DIRECTORS  
Craig Isaac, NSW C.D. 2920  
James Elbery, NSW C.D. 3113  
John Ward, NSW C.D. 3847  
Kathleen Thompson, NSW C.D. 4028  
Mark Trotter, NSW C.D. 4421  
Nathan Marshall, NSW C.D. 4171  
Paul Sakuma, NSW C.D. 3158  
Phil Trotter, NSW C.D. 3177  
Ryan Lovelady, NSW C.D. 4501  
Robert Wetherill, NSW C.D. 3033

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

**PHASE**  
**SCHEMATIC DESIGN**  
**CLIENT**  
NSW Department of Education

**PROJECT**  
Wentworthville Public School

**ADDRESS**  
70-100 Fullagar Road  
WENTWORTHVILLE, NSW

**DRAWING**  
**BLOCK G - ELEVATIONS 3**

Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.

**PROJECT NUMBER**  
7068WV01


**DIRECTOR**  
JW

**DRAWING NUMBER**  
SD-G-3003


**REVISION**  
P7

Copyright

This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied, directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.



**1 ELEVATION**  
**BUILDING G - SOUTERN ELEVATION**  
SCALE: 1:100



**2 ELEVATION**  
**BUILDING G - SOUTHERN SECTIONAL ELEVATION**  
SCALE: 1:100

P1	PSE-DA	18/07/18	JP
P2	Draft Schematic Design Issue	04/09/2018	JFK
P3	Issued For TSO Review	20/09/2018	JFK
P4	SSDA Consultant Report Issue	05/10/18	WS
P5	SD / SSDA Client Review Issue	11/10/18	JFK
P6	SSDA Draft Issue	01/11/18	JFK
P7	SSDA Final Coordination Issue	01/11/18	JFK
REV.	DESCRIPTION	DATE	INT.

**fulton trotter**  
ARCHITECTS

SYDNEY  
Level 3, 35 Spring Street 1 (02) 9369 9941  
PO Box 1860  
Bondi Junction, NSW 2022  
sydney@fultontrotter.com.au

BRISBANE  
SYDNEY

**DIRECTORS**

Chris Burt	NSW 6885	QLD 2920
Justin Elbery	QLD 3113	QLD 3113
John Ward	NSW 8371	QLD 3847
Kathleen Thompson	VIC 18004	QLD 4509
Mark Trotter	NSW 17691	QLD 1973
Nathan Haskin	NSW 4421	QLD 4121
Paul Siskens	NSW 7180	QLD 3169
Paul Trotter	NSW 7177	QLD 3046
Ryan Lovelady	NSW 9802	QLD 4503
Robert Wender	NSW 9802	QLD 3633

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

**PHASE**  
**SCHEMATIC DESIGN**

**CLIENT**  
NSW Department of Education

**PROJECT**  
Wentworthville Public School

**ADDRESS**  
70-100 Fullagar Road  
WENTWORTHVILLE, NSW

**DRAWING**  
**BLOCK G - ELEVATIONS 4**

Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.

**PROJECT NUMBER**  
**7068WV01**

**DIRECTOR**  
**JW**

**DRAWING NUMBER**  
**SD-G-3004**

**REVISION**  
**P7**


150mm @ A1

150

150

Copyright

This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied, directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.



P10	Issued For TSG Review	20/09/2018	JFK
P11	Consultant Issue	27/09/2018	JFK
P12	SSDA Consultant Report Issue	05/10/18	WS
P13	SD / SSDA Client Review Issue	11/10/18	JFK
P14	SSDA Draft Issue	01/11/18	JFK
P15	SSDA Final Coordination Issue	01/11/18	JFK
REV.	DESCRIPTION	DATE	INT.

## fulton trotter

ARCHITECTS

**SYDNEY**  
Level 3, 35 Spring Street, 1 (D2) 0369 9841  
PO Box 1860 Bondi Junction, NSW 2022  
sydney@fultontrotter.com.au

**BRISBANE**  
SYDNEY  
DIRECTORS  
Craig Isaac, NSW  
James Elbery, VIC  
John Ward, VIC  
Matthew Ching, VIC  
Mark Trotter, VIC  
Nathan Hetherington, VIC  
Paul Skene, VIC  
Paul Trotter, VIC  
Ryan Lovelady, VIC  
Robert Wheeler, VIC  
NSW 6885 QLD 2920  
QLD 3113 QLD 3847  
VIC 4505  
VIC 17691 NSW 4421  
NSW 5026 QLD 4131  
NSW 7180 QLD 3169  
NSW 7177 QLD 3046  
NSW 4502 QLD 3633

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

**SCHEMATIC DESIGN**  
NSW Department of Education

**PROJECT** Wentworthville Public School  
**ADDRESS** 70-100 Fullagar Road  
WENTWORTHVILLE, NSW

**DRAWING** BLOCK H - GROUND FLOOR  
**PLAN**

Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.

**PROJECT NUMBER** 7068WV01  
**DIRECTOR** JW  
**DRAWING NUMBER** SD-H-2001  
**REVISION** P15

**Safe Roof Access System**

A safe roof access system shall be provided that complies with the following Australian Standards -

- Industrial fall-arrest systems and devices - Selection, use and maintenance: To AS/NZS 1891.4
- Industrial fall-arrest systems and devices - Safety belts and harnesses: to AS/NZS 1891.1
- Industrial fall-arrest systems and devices - Horizontal lifeline and rail systems: to AS/NZS 1891.2
- Industrial fall-arrest systems and devices - Fall-arrest devices: to AS/NZS 1891.3
- Industrial safety belts and harnesses - Selection, use and maintenance: to AS 2626 (for anchorages only)

The system shall provide a complete fall-arrest roof safety system that:

- Includes a fixed access ladder in a lockable location to provide access to the roofs of multi-storey buildings

- has minimal visual impact on the completed roof, and is compatible with the roofing materials, construction, loading constraints and colours;
- is structurally sufficient in respect of all loads reasonably expected to be imposed on it, and has no adverse structural or other effect on the completed roof;
- may include a number of fully-compatible subsystems, all from one manufacturer/supplier, that allow users to work safely at any point on the roof at all times without the need to disconnect harnesses or restraint lines and lanyards completely, or to carry components of other systems with them;
- prevents free falls whenever possible, and limits possible free falls to the absolute minimum consistent with the user's anticipated work tasks (600mm or less wherever possible, but in no case exceeding 2000 mm);
- allows restrained falls on non-fragile roofed areas only, and includes additional diversionary anchorages near roof edges to prevent a pendulum effect in the event of a fall;

- includes removable means of protecting sharp edges that any line or lanyard may come in contact with, in the event of a free fall;
- exerts a force not exceeding 8kN on any user who is secured to it, and falls;
- distributes fall-arrest forces over the body so that injury is minimised after a fall, and that holds a user in a suitable attitude for rescue after a fall;
- includes anchorages complying with AS 2626;
- has all anchorages positioned so that line and lanyard attachment hardware is kept clear of sharp edges;
- does not include the use of slings, or backhooking of lanyards, as part of an anchorage;
- may include single point, one-person anchorages that have a minimum ultimate strength in the direction of loading of not less than 15kN;
- includes heavy duty, easily operated attachment hardware, other than snaphooks, that is appropriately sized for all lines and lanyards provided as part of the systems;
- includes carrying bags for each complete set of personal fall-arrest equipment;

- includes all necessary labels and signs with an expected life equal to the item referred to;
- remains intact, usable and water-resistant under the local and regional ambient climatic conditions with a minimum amount of maintenance;
- includes at least four ladder securing access points to the roof edge or gutter, including a level concrete slab at ground level, unless specified elsewhere in the documents;
- includes at least one removable Type 3 fall-arrest device, that may be attached anywhere a free fall is possible, to assist in the immediate recovery of a user who has fallen;
- includes at least two fully adjustable harnesses, each with an attachment point to front and back. Restraint belts will not be allowed;
- includes the appropriate number (but not less than two) of lanyards, restraint lines, and pole lines as appropriate: each with energy-absorbing fall-arrest characteristics or devices fitted; and
- is certified by a Registered Professional Engineer specialising in structural design and certification.

Copyright

This drawing shows design features and elements of a design prepared by Fulton Trotter Architects and is to be used only for work authorised in writing by the designers. It cannot be copied, directly or indirectly, in whole or in part, nor shall it be used for any other building purposes. Unauthorised use will be considered an infringement of these rights.

1150mm @ A1

1150

1150



plot date: Friday, 9 November 2018

file location: BIM Server: sydbmsy02 21 - BIM Server 21\7068 WVPS

100

1150mm @ A1

**1 PLAN**  
**ROOF PLAN - BUILDING H**  
SCALE: 1:100



P2	PRE-DA	18/07/18	JP
P3	Draft Schematic Design Issue	04/09/2018	JFK
P4	Issued For TSG Review	20/09/2018	JFK
P5	SSDA Consultant Report Issue	05/10/18	WS
P6	SD / SSDA Client Review Issue	11/10/18	JFK
P7	SSDA Draft Issue	01/11/18	JFK
P8	SSDA Final Coordination Issue	01/11/18	JFK
REV	DESCRIPTION	DATE	INT.

**fulton trotter**  
ARCHITECTS

**SYDNEY**  
Level 3, 35 Spring Street 1, (02) 9369 9841  
PO Box 1860 Bondi Junction, NSW 2022  
sydney@fultontrotter.com.au

**BRISBANE**  
SYDNEY  
Level 3, 35 Spring Street 1, (02) 9369 9841  
PO Box 1860 Bondi Junction, NSW 2022  
brisbane@fultontrotter.com.au

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

**PHASE**  
**SCHEMATIC DESIGN**  
**CLIENT**  
NSW Department of Education

**PROJECT**  
Wentworthville Public School

**ADDRESS**  
70-100 Fullagar Road  
WENTWORTHVILLE, NSW

**DRAWING**  
**BLOCK H - ROOF PLAN**

Figured dimensions take precedence over scale dimensions. Contractors must verify all dimensions on site before commencing any work or making shop drawings.

**PROJECT NUMBER**  
**7068WV01**


**DIRECTOR**  
**JW**

**DRAWING NUMBER**  
**SD-H-2101**


**REVISION**  
**P8**




Copyright  
This drawing shows design features and elements of a design prepared by  
Fulton Trotter Architects and is to be used only for work authorised in  
writing by the designers. It cannot be copied, directly or indirectly, in whole  
or in part, nor shall it be used for any other building purposes. Unauthorised  
use will be considered an infringement of these rights.




1 ELEVATION  
BUILDING H - NORTHERN ELEVATION  
SCALE: 1:100



2 ELEVATION  
BUILDING H - EASTERN ELEVATION  
SCALE: 1:100



3 ELEVATION  
BUILDING H - SOUTHERN ELEVATION  
SCALE: 1:100



4 ELEVATION  
BUILDING H - WESTERN ELEVATION  
SCALE: 1:100

P3	Schematic Design	24/07/18	LW
P4	Draft Schematic Design Issue	04/09/2018	JFK
P5	Issued For TSO Review	20/09/2018	JFK
P6	SSDA Consultant Report Issue	05/10/18	WGS
P7	SD / SSDA Client Review Issue	11/10/18	JFK
P8	SSDA Draft Issue	01/11/18	JFK
P9	SSDA Final Coordination Issue	01/11/18	JFK
REV.	DESCRIPTION	DATE	INT.

**fulton trotter**  
ARCHITECTS  
SYDNEY  
Level 3, 35 Spring Street 1 (02) 9369 9841  
PO Box 1880  
Bondi Junction, NSW 2022  
BRISBANE  
SYDNEY  
sydney@fultontrotter.com.au

DIRECTORS	NEW 6885	C.D 2590
Chris Lewis	NEW 3113	C.D 3113
John Ward	NEW 8371	C.D 3847
James Chapman	NEW 4509	C.D 4509
Mark Trotter	NEW 4421	C.D 1975
Paul Skene	NEW 7185	C.D 3159
Paul Trotter	NEW 7177	C.D 3146
Ryan Lovelady	NEW 5902	C.D 4500
Robert Wainwright	NEW 5902	C.D 3833

[www.fultontrotter.com.au](http://www.fultontrotter.com.au)

PHASE  
**SCHEMATIC DESIGN**  
CLIENT  
NSW Department of Education

PROJECT  
Wentworthville Public School


ADDRESS  
70-100 Fullagar Road  
WENTWORTHVILLE, NSW

DRAWING  
**BLOCK H - ELEVATIONS**


Figured dimensions take precedence over  
scale dimensions. Contractors must verify  
all dimensions on site before commencing  
any work or making shop drawings.

PROJECT NUMBER	DIRECTOR	CHECKED
7068WV01	JW	
DRAWING NUMBER	REVISION	
SD-H-3001	P9	

Front View



Plan View




Note: Not to Scale

Date: 24.10.2017 Drawn By: AS



6396-1  
Appendix E



**DAY DESIGN PTY LTD**

