Risk Con Engineering

State Environmental Planning Policy No. 33 228-230 Blands Land, Wyalong



State Environmental Planning Policy No. 33

228-230 Blands Land, Wyalong

Lightsource Development Services Australia

Prepared by

RiskCon Engineering Pty Ltd Unit 19/5 Pyrmont Bridge Road Camperdown, NSW 2050 www.riskcon-eng.com ABN 74 626 753 820

© RiskCon Engineering Pty Ltd. All rights reserved.

This report has been prepared in accordance with the scope of services described in the contract or agreement between RiskCon Engineering Pty Ltd and the Client. The report relies upon data, surveys, measurements and results taken at or under the particular times and conditions specified herein. Changes to circumstances or facts after certain information or material has been submitted may impact on the accuracy, completeness or currency of the information or material. This report has been prepared solely for use by the Client. RiskCon Engineering Pty Ltd accepts no responsibility for its use by other parties without the specific authorization of RiskCon Engineering Pty Ltd. RiskCon Engineering Pty Ltd reserves the right to alter, amend, discontinue, vary or otherwise change any information, material or service at any time without subsequent notification. All access to, or use of, the information or material is at the user's risk and RiskCon Engineering Pty Ltd accepts no responsibility for the results of any actions taken on the basis of information or material provided, nor for its accuracy, completeness or currency.



Quality Management

Rev	Date	Remarks	Prepared By	Reviewed By	
Α	23 October 2018	Issued draft for comment	Renton Parker	Steve Sylvester	
0	21 January 2019	Issued Final (revised dates)	Nemon Faiker	Sieve Sylvesiei	



Executive Summary

Introduction

Lightsource Development Services Australia (Lightsource) has proposed to develop a solar farm to be located at 228-230 Blands Land, Wyalong, NSW. As the development is classified as a State Significant Development (SSD) the Department of Planning and Environment (DPE) has provided Secretary's Environmental Assessment Requirements (SEARs) which requires a preliminary risk screening of the site and operations in accordance with State Environmental Planning Policy No. 33 (SEPP 33, Ref. [1]).

Urbis on behalf of Lightsource has engaged RiskCon Engineering (RiskCon) to prepare the SEPP 33 assessment for the solar farm to be located at Wyalong.

Conclusions

A review of the quantities of DGs stored at the proposed solar farm and the associated vehicle movements was conducted and compared to the threshold quantities outlined in Applying SEPP 33. The results of this analysis indicates the threshold quantities for the DGs to be stored and transported are not exceeded; hence, SEPP 33 does not apply to the project.

As the facility is not classified as potentially hazardous, it is not necessary to prepare a Preliminary Hazard Analysis for the facility as SEPP 33 does not apply.

Recommendations

No recommendations have been made for the site



	IE OF CONTENTS utive Summary	i
1.0	Introduction	1
1.1 1.2	Background Scope of Work	1 1
2.0	Methodology	2
2.1 2.2	General Methodology Data taken from "Applying SEPP 33"	2
3.0	SEPP 33 Review	5
3.1 3.1.1 3.2 3.2.1 3.2.2	Proposed Storage Details Classification of Stored Products Application of State Environmental Planning Policy No.33 – Hazardous and Offensive Developments Storage Transport	5 5 5 6
4.0	Conclusion and Recommendations	7
4.1 4.2	Conclusions Recommendations	7 7
5.0	References	8
List	of Figures	
Figure	e 2-1: Screening Method to be Used	2
Figure	e 2-2: General Screening Threshold Quantities	3
Figure	e 2-3: Transportation Screening Thresholds	4
List	of Tables	
Table	3-1: DG Classes or Materials Stored and Maximum Quantities	5
Table	3-2: Quantities Stored and SEPP 33 Threshold	5



1.0 Introduction

1.1 Background

Lightsource Development Services Australia (Lightsource) has proposed to develop a solar farm to be located at 228-230 Blands Land, Wyalong, NSW. As the development is classified as a State Significant Development (SSD) the Department of Planning and Environment (DPE) has provided Secretary's Environmental Assessment Requirements (SEARs) which requires a preliminary risk screening of the site and operations in accordance with State Environmental Planning Policy No. 33 (SEPP 33, Ref. [1]).

Urbis on behalf of Lightsource has engaged RiskCon Engineering (RiskCon) to prepare the SEPP 33 assessment for the solar farm to be located at Wyalong.

1.2 Scope of Work

The scope of work is to prepare the SEPP 33 assessment for the Lightsource solar farm located at 228-230 Blands Land, Wyalong. Should any additional studies be required (i.e. PHA) these are not included within the scope of works. No other sites are included within the scope of works.



2.0 Methodology

2.1 General Methodology

The methodology used in this assessment is as follows:

- Review the types and proposed quantities of DGs to be stored at the site.
- Compare the quantities of DGs the threshold quantities listed in "Applying SEPP 33 Hazardous and Offensive Development" (Ref. [1]) to identify whether the storage location or quantity triggers SEPP 33.
- Review the likely vehicular movements involving DGs and compare against the applicable thresholds detailed in Applying SEPP 33 (Ref. [1]).
- Report on the findings of the SEPP 33 assessment.

2.2 Data taken from "Applying SEPP 33"

Figure 2-1, extracted from "Applying SEPP 33" provides details on the application of Figures or Tables from the same document to determine the applied screening Threshold.

Class	Method to Use/Minimum Quantity		
1.1	Use graph at Figure 5 if greater than 100 kg		
1.2-1.3	Table 3		
2.1 — pressurised (excluding LPG)	Figure 6 graph if greater than 100 kg		
2.1 — liquefied (pressure) (excluding LPG)	Figure 7 graph if greater than 500 kg		
LPG (above ground)	table 3		
LPG (underground)	table 3		
2.3	table 3		
3PGI	Figure 8 graph if greater than 2 tonne		
3PGII	Figure 9 graph if greater than 5 tonne		
3PGIII	Figure 9 graph if greater than 5 tonne		
4	table 3		
5	table 3		
6	table 3		
7	table 3		
8	table 3		

Figure 2-1: Screening Method to be Used

Table 3 from "Applying SEPP 33" has been extracted and is shown in Figure 2-2.



Class	Screening Threshold	Description
1.2	5 tonne	or are located within 100 m of a residential area
1.3	10 tonne	or are located within 100 m of a residential area
2.1	(LPG only - not in	ncluding automotive retail outlets')
	10 tonne or16 m ³	if stored above ground
	40 tonne or 64 m ³	if stored underground or mounded
2.3	5 tonne	anhydrous ammonia, kept in the same manner as for liquefied flammable gases and not kept for sale
	1 tonne	chlorine and sulfur dioxide stored as liquefied gas in containers <100 kg
	2.5 tonne	chlorine and sulphur dioxide stored as liquefied gas in containers >100 kg
	100 kg	liquefied gas kept in or on premises
	100 kg	other poisonous gases
4.1	5 tonne	
4.2	1 tonne	
4.3	1 tonne	
5.1	25 tonne	ammonium nitrate — high density fertiliser grade, kept on land zoned rural where rural industry is carried out, if the depot is at least 50 metres from the site boundary
	5 tonne	ammonium nitrate — elsewhere
	2.5 tonne	dry pool chlorine if at a dedicated
		pool supply shop, in containers <30 kg
	1 tonne	dry pool chlorine — if at a dedicated pool supply shop, in containers >30 kg $$
	5 tonne	any other class 5.1
5.2	10 tonne	
6.1	0.5 tonne	packing group I
	2.5 tonne	packing groups II and III
6.2	0.5 tonne	includes clinical waste
7	all	should demonstrate compliance with Australian codes
8	5 tonne	packing group I
	25 tonne	packing group II
	50 tonne	packing group III

Figure 2-2: General Screening Threshold Quantities

Transportation screen thresholds have been provided in Figure 2-3.



	Vehicle Mo	vements	Minimum	Minimum quantity*		
	Cumulative	Peak	per load	d (tonne)		
Class	Annual or	Weekly	Bulk	Packages		
1	see note	see note	see note			
2.1	>500	>30	2	5		
2.3	>100	>6	1	2		
3PGI	>500	>30	1	1		
3PGII	>750	>45	3	10		
3PGIII	>1000	>60	10	no limit		
4.1	>200	>12	1	2		
4.2	>100	>3	2	5		
4.3	>200	>12	5	10		
5	>500	>30	2	5		
6.1	all	all	1	3		
6.2	see note	see note	see note			
7	see note	see note	see note			
8	>500	>30	2	5		
9	>1000	>60	no limit			

Figure 2-3: Transportation Screening Thresholds



3.0 SEPP 33 Review

3.1 Proposed Storage Details

Provided in **Table 3-1** is a summary of the DGs and materials proposed to be stored at the facility as part of the site operations.

Table 3-1: DG Classes or Materials Stored and Maximum Quantities

Class	Description	PG	Quantity (kg)
2.2	Sulphur Hexafluoride (SF6)	n/a	8 kgs/switch gear = <100 kg
9	Lithium Batteries (lithium equivalent)	III	10,602*
C1	Transformer oils	n/a	1,500 L/transformer = <10,000 L

^{*1} cell: 18.56g lithium equivalent content

3.1.1 Classification of Stored Products

The Australian Dangerous Goods Code (ADG, Ref. [2]) provides a list of materials which are classified as DGs under the requirements of the code. The goods to be stored are classified as DGs by the ADG. Therefore, the materials classified as DGs are subject to the assessment requirements of SEPP 33. Combustible liquids not subject to SEPP 33; hence, the C1 and C2 products have been eliminated from further assessment.

3.2 Application of State Environmental Planning Policy No.33 – Hazardous and Offensive Developments

State Environmental Planning Policy No. 33 – Hazadous and Offensive Developments (SEPP 33) has been developed under the Planning and Assesment Act 1979 to control potentially hazardous and offensive developments and to ensure appropriate safety features are installed at a facility to ensure the risks to surrounding land uses is minimised.

The policy includes a guideline that assists government and industry alike in determining whether SEPP 33 applies to a specific development. The guideline, "Applying SEPP 33 - Hazardous and Offensive Developments" (Ref. [1]) provides a list of threshold levels, for the storage of DGs, above which the regulator considers the DG storage to be potentially hazardous. In the event the threshold levels are exceeded, SEPP 33 applies and a Preliminary Hazard Analysis (PHA) is required, followed by a series of hazard analysis studies stipulated by the Department of Planning and Environment in the conditions of consent.

3.2.1 Storage

Threshold limits for the application of SEPP 33 are presented in **Table 3-2** along with maximum DG quantities that will be stored. The results summarised in the table indicates the SEPP 33 criteria is not exceeded; hence, no further assessment would be required.

¹ module = 28 cells

¹ rack = 17 modules

¹ MWh = 24 racks

X 50 MW = 10,602 kg lithium equivalent content



Table 3-2: Quantities Stored and SEPP 33 Threshold

Class	Description	PG	Quantity (kg)	SEPP 33 Threshold (kg)	Does SEPP 33 Apply?
2.2	SF6	n/a	100	n/a*	No
9	Lithium Batteries	III	10,60	n/a*	No
C1	Transformer Oil	n/a	10,000	n/a*	No

^{*}Note: Class 2.2, 9 & C1 materials are not subject to SEPP 33; hence, do not have a threshold.

3.2.2 Transport

The products stored at the site are not subject to SEPP 33; hence, not further assessment has been prepared for transport.



4.0 Conclusion and Recommendations

4.1 Conclusions

A review of the quantities of DGs stored at the proposed solar farm and the associated vehicle movements was conducted and compared to the threshold quantities outlined in Applying SEPP 33. The results of this analysis indicates the threshold quantities for the DGs to be stored and transported are not exceeded; hence, SEPP 33 does not apply to the project.

As the facility is not classified as potentially hazardous, it is not necessary to prepare a Preliminary Hazard Analysis for the facility as SEPP 33 does not apply.

4.2 Recommendations

No recommendations have been made for the site



5.0 References

- [1] Department of Planning, "Applying SEPP 33," Department of Planning, Sydney, 2011.
- [2] National Transport Commission (NTC), "Australian Code for the Transport of Dangerous Goods by Road & Rail, 7th Edition," 2011.